




Centring Pin **Code: G65**

Reference: VW/ AUDI 39V 1205
Reference: BMW B2 4068 2



d	L1	L2	L3	d1	M	r
22	45	16	35	21.95	M8	15
22	55	16	45	21.95	M8	15
32	50	20	35	31.95	M10	20
40	55	20	35	39.95	M10	25
40	65	20	45	39.95	M10	25
50	55	20	35	49.95	M10	25



Order: **G65. d x L1**




Material: 1.7131 (16MnCr5)
Hardness: 58 - 62 HRC



Centring Pin **Code: G66**

Reference: FCA STQ 40015



d	L	L1	d1	t	M	r
22	45	37.5	14	25	M10	20
32	50	40	18	35	M12	20
40	55	40	18	35	M12	20
50	55	40	18	35	M12	20



Order: **G66. d**




Material: 1.7131 (16MnCr5)
Hardness: 58 - 62 HRC



Centring Pin **Code: G62**

Reference: Mercedes-Benz Standard
B8 0602 321 008 801



d	d1	d2	d3	M	t	t1
22	16	11	9	M8	13	16
25	18	11	9	M8	13	16
32	25	11	9	M8	13	16
40	32	15	11	M10	16	20
50	42	15	11	M10	16	20



Order: **G62. d**



Material: 1.7131 (16MnCr5)
Hardness: 58 - 62 HRC

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

Centring Pins: It is used for centring of perforated parts. Using centring pin provides centring repeatedly with high sensitivity at dies and fixtures. Mounted parts are centered with high sensitivity and quickly. Screws used for mounting of products should be provided by user. All dimensions without tolerance are in EN 22768 - 1 (m) standards.

