



Partner WEB PAGE API Documentation

Integration guide for partner websites that query public travel data and redirect users into the Travelo booking flow.

Base URL	https://your-backend-domain.com
Authentication	Header x-api-key: YOUR_PARTNER_API_KEY

Supported endpoints

Method	Endpoint	Purpose	Auth
GET	/web_sale/web_page_harbors	Returns the list of harbors available in the system.	Required
POST	/web_sale/web_page_search_trips	Returns trip data for the provided origin, destination and date.	Required
POST	/web_sale/web_page_redirect	Returns a Travelo redirect URL with prefilled search parameters.	Required
GET	/web_sale/web_page_info	Returns information exposed from the system.	Required
GET	/web_sale/web_page_documentations	Returns this documentation resource.	Required

1. Authentication

Every request to the Travelo partner API must include the partner key in the request header.

```
x-api-key: YOUR_PARTNER_API_KEY
```

Important: the same partner key must be sent on all endpoints listed in this document, including GET requests.

2. Common request rules

- Content-Type must be application/json for POST requests.
- travel_date format must be YYYY-MM-DD.
- Only partner domains configured on the Travelo side are allowed by CORS.
- Rate limiting is applied per IP address.

3. Endpoint details

3.1 GET /web_sale/web_page_harbors

Returns the list of available harbors that can be used as departure and arrival points.

Required headers:

```
GET /web_sale/web_page_harbors
x-api-key: YOUR_PARTNER_API_KEY
```

Example response:

```
{
  "status": 200,
  "harbors": [
    {
      "uuid": "921d1bbb-7f1c-42b5-a43c-acd91b8b5ac1",
      "name": "Split",
      "code": "HR458",
      "longitude": "23.45868",
      "latitude": "45.45856",
      "city": "Split",
      "region": "dsfas",
      "region_uuid": null,
      "country": null
    }
  ]
}
```

3.2 POST /web_sale/web_page_search_trips

Searches available trips for the provided origin, destination and travel date.

Required headers:

```
POST /web_sale/web_page_search_trips
Content-Type: application/json
x-api-key: YOUR_PARTNER_API_KEY
```

Request body:

```
{
  "travel_from_code": "HR458",
  "travel_to_code": "HR555",
  "travel_date": "2026-03-19"
}
```

Field	Type	Required	Description
travel_from_code	string	Yes	Departure harbor code.
travel_to_code	string	Yes	Arrival harbor code.
travel_date	string	Yes	Travel date in YYYY-MM-DD format.

Example response:

```
{
  "status": 200,
  "trips": [
    {
      "id": 891,
      "departure": "19.03.2026. 08:30",
      "actual_departure": "19.03.2026. 08:30",
      "arrival": "19.03.2026. 09:25",
      "actual_arrival": "19.03.2026. 09:25",
      "departure_harbor_order": "10",
      "departure_harbor_id": "HR458",
      "departure_harbor_name": "Split",
      "arrival_harbor_id": "HR555",
      "arrival_harbor_name": "Bol",
      "line_code": "643",
      "line_name": "Split - Bol",
      "prices": [
        {
          "id": 202,
          "ticket_type_name": "Putnik",
          "price": "20"
        }
      ]
    }
  ]
}
```

3.3 POST /web_sale/web_page_redirect

Returns a Travelo URL that can be opened in the browser in order to redirect the user into Travelo with prefilled search parameters.

Required headers:

```
POST /web_sale/web_page_redirect
Content-Type: application/json
x-api-key: YOUR_PARTNER_API_KEY
```

Request body:

```
{
  "travel_from_id": "HR458",
  "travel_to_id": "HR555",
  "travel_date": "2026-03-19"
}
```

Example response:

```
{
  "redirectUrl": "https://your-travelo-domain.com/search?from=HR458&to=HR555&date=2026-03-19&partner=partner1"
}
```

3.4 GET /web_sale/web_page_info

Returns system information exposed for partner integrations.

```
GET /web_sale/web_page_info
x-api-key: YOUR_PARTNER_API_KEY
```

3.5 GET /web_sale/web_page_documentations

Returns the Travelo partner documentation resource.

```
GET /web_sale/web_page_documentations
x-api-key: YOUR_PARTNER_API_KEY
```

4. Error handling

Status	Meaning
400	Invalid payload or invalid travel_date format.
401	Missing x-api-key header.
403	Unauthorized partner or origin not allowed.
429	Too many requests. Try again in a minute.

Example error responses:

```
{ "error": "Missing x-api-key header" }
{ "error": "Unauthorized partner" }
{ "error": "travel_date must be in YYYY-MM-DD format" }
{ "error": "Too many requests. Try again in a minute." }
```

5. Integration notes

- For browser integrations, all requests must be sent from an allowed partner domain.
- The partner key should be stored securely and never committed to source control.
- The redirect endpoint uses the same request body as the search_trips endpoint.