

Algorithm 1 TD3

Initialize critic networks $Q_{\theta_1}, Q_{\theta_2}$, and actor network π_ϕ with random parameters θ_1, θ_2, ϕ

Initialize target networks $\theta'_1 \leftarrow \theta_1, \theta'_2 \leftarrow \theta_2, \phi' \leftarrow \phi$

Initialize replay buffer \mathcal{B}

for $t = 1$ **to** T **do**

 Select action with exploration noise $a \sim \pi_\phi(s) + \epsilon$,
 $\epsilon \sim \mathcal{N}(0, \sigma)$ and observe reward r and new state s'

 Store transition tuple (s, a, r, s') in \mathcal{B}

 Sample mini-batch of N transitions (s, a, r, s') from \mathcal{B}

$\tilde{a} \leftarrow \pi_{\phi'}(s') + \epsilon, \quad \epsilon \sim \text{clip}(\mathcal{N}(0, \tilde{\sigma}), -c, c)$

$y \leftarrow r + \gamma \min_{i=1,2} Q_{\theta'_i}(s', \tilde{a})$

 Update critics $\theta_i \leftarrow \text{argmin}_{\theta_i} N^{-1} \sum (y - Q_{\theta_i}(s, a))^2$

if $t \bmod d$ **then**

 Update ϕ by the deterministic policy gradient:

$\nabla_\phi J(\phi) = N^{-1} \sum \nabla_a Q_{\theta_1}(s, a)|_{a=\pi_\phi(s)} \nabla_\phi \pi_\phi(s)$

 Update target networks:

$\theta'_i \leftarrow \tau \theta_i + (1 - \tau) \theta'_i$

$\phi' \leftarrow \tau \phi + (1 - \tau) \phi'$

end if

end for