post_incompact3d

post_incompact3d is an unofficial post-processing program firstly developed by R. Corsini (University of Modena and Reggio Emilia, UNIMORE) based on Incompact3d version 2.0. This new version is based on Incompact3d v4.0, and it is able to perform calculations of flow statistics with 2 homogeneous directions (\boldsymbol{x} and \boldsymbol{z}), with different flow realizations and (if requested) with averages in time.

Compiling options

The compilation is made with <code>cmake</code>, that needs to be run in a build directory. The default compilation is performed with the option <code>TTBL_MODE=ON</code>, that ensures statistics with averages along homogeneous directions x and z and with different flow realizations. Statistics are printed for each time-unit of snapshots' saving (this is used for temporal cases, e.g. Temporal Turbulent Boundary Layers (TTBLs) and more in general for temporal simulations, e.g. temporal jets). With the default compilation, the program is in $TTBL\ Mode$.

Default compilation (TTBL Mode)

Optionally, it is possible to compile the program with the option TTBL_MODE=0FF. This option allows to average the snapshots also in time (this is used for statistically steady cases, e.g. channel flows). With this option disabled, the program is in *Channel mode*.

Optional compilation (Channel Mode)

```
cmake -DTTBL_MODE=0FF ../
```

The specific compiling option can be also modified by changing the value TTBL_MODE:BOOL inside the CMakeCache.txt file that is present inside the build directory if cmake has been run.

Finally, it is also possible to impose a specific compiler (e.g. gfortran, in Channel Mode):

```
cmake -DTTBL_MODE=OFF -DCMAKE_Fortran_COMPILER=gfortran ../
```

and equivalently for TTBL Mode:

```
cmake -DTTBL_MODE=ON -DCMAKE_Fortran_COMPILER=gfortran ../
```

Usage

post_incompact3d must be run inside the folder of a specific flow case. If different flow realizations are present, the different realizations must be stored in different *data* folders, that must be named <code>data_rn</code> where <code>n</code> is the number of the specific flow realization. If only one realization is present, no modifications are required to the standard folder name <code>data</code>.

post_incompact3d requires the file post.prm as input file. In this file, the following parameters must be specified:

- flowcasename: flow case name added to the images' filename generated with plot_statistics.py
- file1: first snapshot index (index of the snapshot's name)
- filen: final snapshot index (index of the snapshot's name)
- icrfile: file increment (index increment)
- nr: number of flow realizations

- post_mean: compute mean statistics (0: no, 1: yes)
- post_vort : compute mean vorticity and mean gradients (0: no, 1: yes)
- post_diss: compute mean total dissipation rate (0: no, 1: yes)
- post_corz : compute correlation functions along z (0: no, 1: yes) (for *Channel Mode*, mean statistics must be already calculated).

Statistics

As following, we collect the flow statistics calculated.

- Velocity field (O(6))
 - Averages

$$\langle u \rangle, \langle v \rangle, \langle w \rangle$$

Variances

$$\langle u'^2
angle, \langle v'^2
angle, \langle w'^2
angle$$

Skewnesses

$$\mathsf{skew}[u], \mathsf{skew}[v], \mathsf{skew}[w]$$

Kurtoses

$$\mathsf{kurt}[u], \mathsf{kurt}[v], \mathsf{kurt}[w]$$

• Reynolds stresses (O(6))

$$\langle u'v' \rangle, \langle u'w' \rangle, \langle v'w' \rangle$$

- Pressure field (O(6))
 - Average and variance

$$\langle p
angle, \langle p'^2
angle$$

- Scalar field (O(6))
 - Average and variance

$$\langle \varphi \rangle, \langle \varphi'^2 \rangle$$

• Mixed fluctuations

$$\langle u'\varphi'\rangle, \langle v'\varphi'\rangle, \langle w'\varphi'\rangle$$

- Vorticity field (O(6))
 - Averages

$$\langle \omega_x \rangle, \langle \omega_y \rangle, \langle \omega_z \rangle$$

- Mean gradients (O(6))
 - Mean total parallel gradient (to the wall)

$$\langle \sqrt{\left(rac{\partial u}{\partial y}
ight)^2 + \left(rac{\partial w}{\partial y}
ight)^2}
angle = rac{\partial U_\parallel}{\partial y}$$

• Mean streamwise gradient

$$\langle \frac{\partial u}{\partial y} \rangle = \frac{\partial U}{\partial y}$$

• Mean spanwise gradient

$$\langle rac{\partial w}{\partial y}
angle = rac{\partial W}{\partial y}$$

- Mean scalar gradient
 - Mean scalar gradient

$$\langle rac{\partial arphi}{\partial y}
angle = rac{\partial \Phi}{\partial y}$$

- Total dissipation rate (O(6))
 - Average

$$\langle arepsilon
angle = 2
u \langle S_{ij} S_{ij}
angle$$

where double contraction on the indexes i and j is performed.

• Correlation functions

In $Channel\ Mode$, a previous run must be performed in order to calculate the averages, while in $TTBL\ Mode$, correlations must be calculated with the same post-processing run of mean statistics.

Auto-correlation functions for fluctuations of velocity components in spanwise direction (z):

$$R_{ii}(r_z) = \langle u_i'(x,y,z+r_z,t)u_i'(x,y,z,t)
angle$$

where index i stands for the three directions x, y and z.

• Correlation function in spanwise direction (z) for mixed fluctuations u' and v':

$$R_{uv}(r_z) = \langle u'(x,y,z+r_z,t)v'(x,y,z,t)
angle$$

Statistics involving calculations of integrals

For integral quantities of TTBL simulations (e.g displacement thickness, momentum thickness, etc.), the user can employ the python function high_order_integrals.py that can be found in the same parent directory. This function employs the post-processing data generated with post_incompact3d.