

Supplementary Materials

Matteo Manente¹, Livio Finos², Gianmarco Altoè¹, and Filippo Gambarota¹

¹Department of Developmental Psychology and Socialization, University of Padova

²Department of Statistical Sciences, University of Padova

Author Note

Correspondence concerning this article should be addressed to Filippo Gambarota,
Department of Developmental Psychology and Socialization, University of Padova, Via Venezia 8,
Padova, Italy 35131, Email: filippo.gambarota@unipd.it

Supplementary Materials**Table of contents**

Introduction	3
S1. Reproducibility and software	3
S2. Computational comparison with permutation testing	3
S3. Additional simulation results	4
S3.1 Type I error	4
S3.2 Statistical power	4

Supplementary Materials

S1. Reproducibility and software

All analyses were conducted in R. Meta-analytic models were fitted using `metafor`, and score-based sign-flipping inference was performed using `flipmeta`. Random-number seeds were fixed for all simulation and resampling procedures.

The source code used to generate the simulations, empirical application, figures, and tables is available in the accompanying repository. The manuscript and supplementary materials were generated directly from Quarto source files.

Table 1

Main software versions used to reproduce the analyses.

Software	Version
R	4.5.2
Quarto	1.8.26
metafor	5.0.1
flipmeta	0.0.1
flipscores	1.3.2
dplyr	1.2.1
tidyr	1.3.2
ggplot2	4.0.3

The supplementary materials were rendered on Darwin 25.2.0 arm64 from Git commit 25f8ea12c8ca027874cf9494396e63d9bbc72803.

S2. Computational comparison with permutation testing

The main manuscript notes that score sign flipping avoids repeated refitting of the complete meta-regression model. We illustrate the practical computational difference using a mixed-effects meta-regression with 100 independent studies and three predictors.

Both procedures used 1,000 resampling transformations. The benchmark is intended only as an illustration; computation times depend on the model, hardware, software versions, and number of resampling transformations.

In this example, `metafor::permutest()` required approximately 3.2 seconds, compared

Table 2*Illustrative computation times for 1,000 resampling transformations.*

Procedure	Time (seconds)
metafor::permutest()	3.16
flipmeta	0.04

with 0.04 seconds for `flipmeta`.

S3. Additional simulation results

The main manuscript reports simulation results averaged over study sample size and moderator correlation. Here we show the corresponding results separately across these conditions.

S3.1 Type I error

The disaggregated results show the conditions underlying the averages reported in the main manuscript and allow calibration to be inspected across study sample size and moderator correlation.

S3.2 Statistical power

As in the main manuscript, power is shown only for method-condition combinations that adequately controlled Type I error under the corresponding null condition.

These results complement the aggregated power results reported in the main manuscript.

Figure 1

Empirical Type I error rates across study sample sizes and moderator correlations. The horizontal dotted line indicates the nominal significance level of .05. Wald is omitted for readability because it showed substantial Type I error inflation in several conditions.




Figure 2

Empirical power across study sample sizes and moderator correlations. Results are shown only for method-condition combinations that adequately controlled Type I error under the corresponding null condition.

