

# New L<sup>A</sup>T<sub>E</sub>X Style for FAO Yearbook \*

Boris Veytsman<sup>†</sup>

2013/08/18, v0.1

## Abstract

This package provides class for typesetting FAO Yearbook. This is a refactoring of the `faoyeabook` package

## 1 Introduction

The package `faoyearbook` [1] was written in 2011 for FAO Statistical Yearbook.

The package `faosyb` is a refactoring of this package. We use the lessons learned and incorporate new design requirements. We use some (actually plenty) code from the previous version, but since we do not have to be compatibility, we can correct some unfortunate decisions.

## 2 User Guide

The installation of the class follows the usual practice [2] for L<sup>A</sup>T<sub>E</sub>X packages:

1. Run `latex` on `faosyb.ins`. This will produce the L<sup>A</sup>T<sub>E</sub>X class `faosyb.cls`.
2. Put the file `faosyb.cls` to the place where L<sup>A</sup>T<sub>E</sub>X can find it (see [2] or the documentation for your T<sub>E</sub>X system).
3. Update the database of file names. Again, see [2] or the documentation for your T<sub>E</sub>X system for the system-specific details.
4. The file `faosyb.pdf` provides the documentation for the package (this is the file you are probably reading now).

As an alternative to items 2 and 3 you can just put the file `faosyb.cls` in the working directory where your `.tex` file is.

---

\*©2013, Food and Agriculture Organization of the United Nations

<sup>†</sup>[borisv@lk.net](mailto:borisv@lk.net), [boris@varphi.com](mailto:boris@varphi.com)

## 2.1 Invocation

To use the class, put in the preamble of your document

```
\documentclass[\options]{faosyb}
```

If the option **web** (default) is chosen, the pages of the book have the dimensions corresponding to A4 paper. However, if the option **print** is chosen, then the pages are printed on a wider area, and crop marks are added for the trimming.

If the option **issuu** is chosen, the internal links are transformed to external in the form suitable for <http://www.issuu.com>. Note that this option probably does not make much sense unless **web** option is also chosen. However, it is still possible to select both **print** and **issuu** option if someone needs it for an obscure purpose.

The option **Draft** (note the capitalization!) leads to the the large word ‘DRAFT’ printed across the pages. The standard L<sup>A</sup>T<sub>E</sub>X option **draft** leads to the same result, but it also makes other changes, most notably, in the behavior of the `\includegraphics` command and warnings.

`\ifprint` It is possible to query the current mode using the macro `\ifprint`, for example

```
\ifprint
  Stuff for print version
\else
  Stuff for web version
\fi
```

Any branch of this conditional may be empty, so web-only stuff can be coded as

```
\ifprint\else Web-only stuff\fi
```

`\includegraphics` There is a special facility for `\includegraphics` command to choose a file depending on the current mode of the package. Namely, if there is a file `image_print.pdf` visible by L<sup>A</sup>T<sub>E</sub>X, then the commands `\includegraphics{image}` or `\includegraphics{image.pdf}` selects the file `image_print.pdf`. In the case this file is not found, the file `image.pdf` is selected instead. Similarly in the web mode the file `image_web.pdf` will be selected first, and only if it does not exist, `image.pdf` is selected. This rule works also for commands `\includeLargeGraphics` and `\includeExtraLargeGraphics` described below.

Note that at this time there is no similar facility for the `\input` command.

## 2.2 Setting Parameters

`\faoset` Some parameters in the class can be set with the command `\faoset{<key=value>}`, for example

```
\faoset{bgcolor=blue}
```

Most of the parameters are explained below.

## 2.3 Fonts

`\narrowfamily`    The class uses PT Sans fonts [3] for body text and Arev fonts [4] for math. It  
`\textnarrow`    defines two additional families: Narrow and Caption, corresponding to the PT  
`\captionfamily`    Sans Narrow and PT Sans Caption font. They can be selected by the declarations  
`\textcaption`    `\narrowfamily` and `\captionfamily` or by the commands `\textnarrow{<text>}`  
and `\textcaption{<text>}` following the usual L<sup>A</sup>T<sub>E</sub>X conventions. Note that since  
PT Sans does not provide math alphabet, this choice does not change the mathe-  
matical text.

PT Sans Narrow may be useful for typesetting tables, for example,

```
{\scriptsize\narrowfamily
\rowcolors{4}{@bgcolor!30}{@bgcolor!20}
\input{./Tables/P1.DEM_1.tex}}
```

## 2.4 Colors and Icons for Parts

A Yearbook is separated into parts (more on this below). Each part has its own color and icon. They are set by the keys `bgcolor` and `icon` of the `\faoset` command, for example,

```
\faoset{icon=./Icons/agriculture.png}
\faoset{icon=./Icons/population}
\faoset{bgcolor=blue}
\faoset{bgcolor=green!25!yellow}
```

The parameter for the `icon` key can be any file name (with or without extension), suitable for the `\includegraphics` command. The parameter for the `bgcolor` key can be specified in any form acceptable by `xcolor` package [5].

The key `tableheadcolor` sets the color for the headers of tables defined by H or P key (see Section 2.6). Normally it is 30% of the current `@bgcolor` color, but it can be set to any required value.

`\selecticon`    Note that `\faoset` command does not change the icon or background color  
`\selectcolor`    immediately. When issued *before* `\part` command, it sets up icon and color for  
the next part. If needed, you can manually change this using `\selecticon` and  
`\selectcolor` commands. In most cases you should *not* use these commands.

`@bgcolor`    After a `\part` command (or explicit `\selecticon` and `\selectcolor` com-  
`@tableheadcolor`    mand we can access the current values of the color in `@bgcolor`, `@tablecolor`  
`\currenticon`    colors and `\currenticon` macro.

## 2.5 Sectioning

`\part`    The main division of the text are `\parts`. The command `\part{<title>}` is used for  
`\section`    numbered parts, while the command `\part*{<title>}` is used for unnumbered parts.  
`\subsection`    The next division are `\sections` and `\subsections`. They are never numbered.  
The style does not use `\chapters`.

`\EndPartIntro` The sections immediately following new parts are special: they are typeset in one column and cannot have floats. The command `\EndPartIntro` switches to the “normal” sections.

## 2.6 Floats

One of the most important changes from the previous version of the class [1] is the treatment of floats.

In standard L<sup>A</sup>T<sub>E</sub>X floats “float”: they can be placed by the algorithm anywhere. The previous version made them “sticky”: the author explicitly tells T<sub>E</sub>X where floats should be placed. However, to do so the class required the author to make explicit page breaks, which was not very convenient.

This version has a completely rewritten interface and algorithm for placing floats:

1. Like in standard L<sup>A</sup>T<sub>E</sub>X, authors do not normally provide page breaks—T<sub>E</sub>X tries to make this decision for them.
2. Like in the previous version, floats are put exactly where the authors want them—no default placing and second-guessing.

Here is how it is done.

The main unit of the book is *spread*: a verso page and the corresponding recto page. Each page is divided into four quarters, upper left, upper right, lower left and lower right. We will denote them `ul`, `ur`, `ll`, `lr` for the verso page and `UL`, `UR`, `LL`, `LR` for the recto page (Figure 1). We allow four kinds of floats:

**Single floats** occupy exactly one quarter. They are denoted as `S`.

**Tall floats** occupy two quarters stacked vertically (for example, `ul` and `ll`). They are denoted as `T`.

**Wide floats** occupy two quarters adjacent horizontally (for example, `LL` and `LR`). They are denoted as `W`.

**Big floats** occupy all four quarters on a page. They are denoted as `B`.

The parameters  $\{\langle type \rangle\}$  and  $\{\langle location \rangle\}$  are mandatory for floats, for example

```
\begin{map}{T}{ur}
...
\end{map}
\begin{chart}{S}{UL}
...
\end{chart}
```

For multiquarter floats the location is the location of the upper left corner, so Big float can use only `ul` or `UL` location.



Figure 1: A Spread

Of course, not all combinations are valid: you cannot specify float as `{T}{ll}` or `{W}{UR}`, for example. If you use such combinations, the results may be unpredictable. Also it is not predictable what happens if you try to put overlapping floats (e.g. `{S}{UR}` and `{W}{UL}`).

There are two additional rules:

1. A verso page may have text and floats (still it is recommended that if it has text, then it should not have floats occupying the upper left corner).
2. A recto page may have *either* text *or* floats: if there are floats for this page, all text is moved to the following verso page.

`chart` There are three types of floats defined by the class:  
`map`  
`table` **chart** plots and other charts,  
**map** mapped data.  
**table** mini tables.

`caption` Each of these kinds of material is typeset using the corresponding environment: **chart**, **table** or **map**. Note that the caption for each of these environments *must* precede the graphical material, for example:

```

\begin{chart}{B}{UL}
  \caption{Hunger Data}
  \label{chart:hunger}
  \includegraphics{hunger.pdf}
\end{chart}

```

Note that our class redefines `table` environemnt!. For tables on separate pages use `longtable`.

`\chartwidth`      Inside a `chart`, `map` or `table` it is useful to know the size allocated for the  
`\charheight`      graphics or table, for example, to be able to scale the graphics. Two lengths,  
`\chartwidth` and `\charheight` provide this information, so the user can say, for  
example,

```
\includegraphics[width=\chartwidth, height=\charheight]{theChart}
```

`\Source`      Inside a `chart`, `map` or `table` the macro `\Source{<source>}` gives the source  
of the information, for example,

```
\Source{FA0, Statistical Division [FA0STAT]}
```

`\listoftables`      The standard L<sup>A</sup>T<sub>E</sub>X has the command `\listoftables` to produce the list of  
`\listofcharts`      tables in the document. Our class retains this command and produces two addi-  
`\listofmaps`      tional commands `\listofcharts` and `\listofmaps` with the obvious meaning.

## 2.7 Page Breaks

`\clearpage`      Standard L<sup>A</sup>T<sub>E</sub>X has commands for immediate page break (e.g. `\clearpage`)  
`\cleardoublepage`      and for switching to the next recto page, possibly ejecting the next verso page  
`\clearspread`      (`\cleardoublepage`). The class provides another command `\clearspread`. It  
switches to the next *verso* page, possibly ejecting the next recto page (and putting  
there floats intended for this page, if any).

## 2.8 Tables

To typeset numericall items one should use `d` column identifier with the format `d{<a.b>}`, where *a* is the number of decimal in the integer part of the number, and *b* is the number of decimal digitst in the fractional part. For example, a number 12.345 corresponds to `d{2.3}`. The column headers are usually *not* numerical, so one need to use `\multicolumn` entries to typeset them. The class defines several such entries:

**H** produces a centered entry.

**P** produces an entry of a given length, for example, `P{1.5cm}`

**C** produces an entry of the length corresponding to the given number of numerical columns. For example, `C{2}` corresponds to a header of two numerical columns. Each column is assumed to be of the size enough to store  $-99.999$ .

`\hhline` For the rules that do not span the table width `\hhline{<specification>}` command from the `hhline` package should be used. The `{<specification>}` argument of this command has many variants, but for our purposes we need only one variant: the command `-` produces a horizontal line spanning one column. The color of this line is determined by the command `\arrayrulecolor{<color>}`, issued in the last `>{<argument>}` command before the `-` specification. Therefore the command `>{\arrayrulecolor{@tableheadcolor}}-` produces a line of the color `@tableheadcolor`, which is seen as the absence of line. The command `>{\arrayrulecolor{black}}---` produces a black line spanning three columns. Thus if we have a four-column table and want a rule spanning columns 2-3, the following command should be issued:

```
\hhline{>{\arrayrulecolor{@tableheadcolor}}-% Column 1, no rule
>{\arrayrulecolor{black}}--% Columns 2 and 3, black rule
>{\arrayrulecolor{@tableheadcolor}}-% Column 4, no rule
```

The usual `*` specification may be used for repeating patterns, for example, `*{5}{-}` is equivalent to `-----`.

The vertical bar `|` specification in the `\hhline` argument means an interruption of the line. The interruption is by default a black interval, to make it the same color as the header background, use `>{\arrayrulecolor{@tableheadcolor}}|`.

## 2.9 Publication Descriptions

`publication` FAO yearbook describes some FAO publications. These publications should be put inside the environment `publication`. The environment has one mandatory argument, which is the title of the publication, and one optional argument, which sets the file name of the publication cover. Note that the option argument, if present, must precede the mandatory one. If this argument is absent, no cover is included. Inside the environment the macros `\pDescription{<description>}`, `\pEdition{<year>}{<edition>}`, `\pWeb{<URL>}` and `\pCycle{<date>}` are used to typeset the corresponding items related to the publication. For example,

```
\pDescription
\pEdition
\pCycle
pWeb
\begin{publication}[./Plots/StateOfFoodAndAgriculture.png]{The State
of Food and Agriculture}
\pDescription{The State of Food and Agriculture, FAO's major
annual flagship publication, aims at bringing to a wider
audience balanced science-based assessments of important issues
in the field of food and agriculture. Each edition of the
report contains a comprehensive, yet easily accessible, overview
of a selected topic of major relevance for rural and
agricultural development and for global food security. This is
supplemented by a synthetic overview of the current global
agricultural situation.}
\pEdition{2010}{Livestock in the balance}
\pEdition{2011}{Women in Agriculture Closing the gender gap for
development}
\pCycle{May each year}
```

```
\pWeb{http://www.fao.org/docrep/013/i2050e/i2050e00.htm}
\end{publication}
```

Note that, as in the example, some fields may be repeated.

Two spacing parameters can be used for typesetting of publications: `publicationskip` is the amount of additional space between the publications, while `publicationparskip` is the space between the paragraphs inside the publication environment. The default values correspond to the command

```
\faoset{publicationskip=6pt plus 2pt minus 2pt,
        publicationparskip=6pt plus 6pt minus 4pt}
```

## 2.10 Metadata

**MetadataCollection** Each chart, map or table in the book has a *source*. Sources are collected in the environment `MetadataCollection`, which consists of separate `metadata` environments. Each `metadata` environment has two obligatory arguments—the name of the source and the key. The key is used to identify the metadata in the charts, maps, tables and other objects. The environment may include other commands.

**\source** `\source{<source>}` sets the source of the data.

**\owner** `\owner{<owner>}` sets the owner of the data.

Note that there is no “description” command because any text which is not an argument of the commands above is considered to belong to the description of the data.

Example of the usage of these commands:

```
\begin{MetadataCollection}
\begin{metadata}{Agricultural population}{P1.DEM.FAO.POP.AGR}

    Agricultural population is defined as all persons depending for
    their livelihood on agriculture, hunting, fishing and forestry.
    It comprises all persons economically active in agriculture as
    well as their non-working dependents. It is not necessary that
    this referred population exclusively come from rural population.

    \source{FILL ME}
    \owner{FILL ME}
\end{metadata}
\end{MetadataCollection}
```

**\refMetadata** The metadata is referenced by the command `\refMetadata{<key>}`, for example

```
\refMetadata{P1.DEM.FAO.POP.AGR}
```



This command will be typset as

Source: Agricultural population, page NNNN.

This command must *not* occur in the caption of the chart, map or table.

Note that the package automatically provides backreferencing: all charts, maps and tables where the metadata is referenced, are mentioned in the corresponding metadata section.

The sources of each chart, map or table can be shown in the lists of charts, tables, maps or not. The key `metadataInLists` (by default `false`) determines whether they are shown there. To make them visible, put before the lists

```
\faosetup{metadataInLists=true}
```

## 2.11 Concepts and Methods

`ConceptsAndMethods` The environment `ConceptsAndMethods` starts a new section “Concepts and Methods”. Concepts and methods are collected in the series of `concept` environments. Each environment has one obligatory field: the name of the concept, for example:

```
\begin{ConceptsAndMethods}
  \begin{concept}{Gross domestic product}
    Gross domestic product (GDP) is the market value of all officially
    recognized final goods and services produced within a country in a
    given period of time.
  \end{concept}
  \begin{concept}{Gross state product}
    Gross state product (GSP), or gross regional product (GRP), is a
    measurement of the economic output of a state or province (i.e.,
    of a subnational entity). It is the sum of all value added by
    industries within the state and serves as a counterpart to the
    gross domestic product (GDP).
  \end{concept}
\end{ConceptsAndMethods}
```

## 2.12 Further Reading

`freading` The special environment `freading` is used for the “further reading” sections of the book. It starts the text from the new page and changes some defaults.

## 2.13 Subscripts in Text

`\textsubscript` The standard L<sup>A</sup>T<sub>E</sub>X defines `\textsuperscript`. The class adds a similar `\textsubscript` command.

## 2.14 Options

`\faoyearbook@size@warning` The font-changing options are not used in our setup, so we just produce a warning:

```
1 \long\def\faoyearbook@size@warning#1{%
2   \ClassWarning{faoyearbook}{Size-changing option #1 will not be
3     honored}}%
4 \DeclareOption{8pt}{\faoyearbook@size@warning{\CurrentOption}}%
5 \DeclareOption{9pt}{\faoyearbook@size@warning{\CurrentOption}}%
6 \DeclareOption{10pt}{\faoyearbook@size@warning{\CurrentOption}}%
7 \DeclareOption{11pt}{\faoyearbook@size@warning{\CurrentOption}}%
8 \DeclareOption{12pt}{\faoyearbook@size@warning{\CurrentOption}}%
```

`\ifprint` We have a flag which shows whether we are in Web or print mode

```
9 \newif\ifprint
10 \printfalse
11 \DeclareOption{web}{\printfalse}
12 \DeclareOption{print}{\printtrue}
13 \PassOptionsToPackage{papersize={230mm,317mm},layout=a4paper,
14   layoutoffset=1cm,layoutvoffset=1cm,twoside}{geometry}}
```

`\ifDraft` If we are in ‘Draft’ or ‘draft mode’, we print a word ‘draft’ across the page:

```
15 \newif\ifDraft
16 \Draftfalse
17 \DeclareOption{Draft}{\Drafttrue}
18 \DeclareOption{draft}{\Drafttrue}
```

`\if@issuemode` Whether we need issuu-style links

```
19 \newif\if@issuemode
20 \@issuemodefalse
21 \DeclareOption{issuu}{\@issuodemtrue}
```

All other options are just sent to the main class:

```
22 \DeclareOption*{\PassOptionsToClass{\CurrentOption}{report}}
23 \ProcessOptions\relax
```

## 2.15 Loading Class and Packages

We start with the base class and some packages

```
24 \LoadClass[10pt,twoside,twocolumn]{report}
25 \RequirePackage{graphicx,xkeyval}
26 \RequirePackage[table,cmyk]{xcolor}
27 \RequirePackage{tikz,geometry,dcolumn}
28 \RequirePackage{fancyhdr}
29 \RequirePackage[lscape,longtable,siunitx,booktabs}
30 \RequirePackage[multicol,atbegshi,picture,hhline,afterpage}
31 \RequirePackage[T1]{fontenc}
32 \RequirePackage[utf8x]{inputenc}
33 \RequirePackage{pdfpages}
34 \RequirePackage[authoryear]{natbib}
```

```

35 \RequirePackage[breaklinks]{hyperref}
36 \RequirePackage{bookmark}
37 \if@issuemode
38 \RequirePackage{issuulinks}
39 \fi

```

Options for the hyperref package are set as follows:

```

40 \ifprint
41 \hypersetup{breaklinks,colorlinks=false,pdfborder=0 0 0,
42   pdfauthor={FAO},
43   pdfsubject={Statistical Yearbook of the Food And Agricultural Organization for the United Na
44   pdftitle={Statistical Yearbook of the Food And Agricultural Organization for the United Nati
45   pdfkeywords={FAO, Food Security, Undernourishment, Sustainable agriculture},
46   pdfpagelayout=TwoColumnLeft,
47   pdfnewwindow=true
48 }
49 \else
50 \hypersetup{breaklinks,colorlinks=false,pdfborder=0 0 0,
51   pdfauthor={FAO},
52   pdfsubject={Statistical Yearbook of the Food And Agricultural Organization for the United Na
53   pdftitle={Statistical Yearbook of the Food And Agricultural Organization for the United Nati
54   pdfkeywords={FAO, Food Security, Undernourishment, Sustainable agriculture},
55   pdfpagelayout=TwoColumnRight,
56   pdfnewwindow=true
57 }
58 \fi

```

## 2.16 Color

We need to tell the printer that we are using CMYK color model. The following is taken from the pdfx package (the package itself is not too easy to make work).

```

59 \def\@pctchar{\expandafter\@gobble\string\%}
60 \def\@bchar{\expandafter\@gobble\string\}
61 \immediate\pdfobj stream attr{/N 4} file{FOGRA39L.icc}
62 \edef\OBJ@CVR{\the\pdfastobj}
63 \pdfcatalog{/OutputIntents [ <<
64   /Type/OutputIntent
65   /S/GTS_PDFX
66   /OutputCondition (FOGRA39)
67   /OutputConditionIdentifier (FOGRA39 \@bchar(ISO Coated v2
68   300\@pctchar\space \@bchar(ECI\@bchar)\@bchar))
69   /DestOutputProfile \OBJ@CVR\space 0 R
70   /RegistryName(http://www.color.org)
71 >> ]}

```

## 2.17 Key-Value Interface

\faoset We define the family fao for our keys:

```

72 \def\faoset#1{\setkeys{fao}{#1}}

```

## 2.18 Fonts

We use arev for mathematics:

```
73 \RequirePackage{arevmath}
```

For body text we use PT Sans:

```
74 \def\PTSans@scale{0.95}
75 \def\PTSansNarrow@scale{0.95}
76 \def\PTSansCaption@scale{0.95}
77 \renewcommand{\sfdefault}{PTSans-TLF}
78 \renewcommand{\familydefault}{\sfdefault}
79 \renewcommand{\bfdefault}{b}
```

`\narrowfamily` We declare a new family, `\narrowfamily`:

```
80 \DeclareRobustCommand\narrowfamily{\fontfamily{PTSansNarrow-TLF}\selectfont}
```

`\textnarrow` And the matching `\textnarrow` command:

```
81 \DeclareTextFontCommand{\textnarrow}{\narrowfamily}
```

`\captionfamily` Same with `\captionfamily`:

```
82 \DeclareRobustCommand\captionfamily{\fontfamily{PTSansCaption-TLF}\selectfont}
```

`\textcaption` And the matching `\textcaption` command:

```
83 \DeclareTextFontCommand{\textcaption}{\captionfamily}
```

`\normalsize` The basic size is 9.6pt:

```
84 \renewcommand\normalsize{%
85   \@setfontsize\normalsize{9.6pt}{\@xipt}%
86   \abovedisplayskip 10\p@ \@plus2\p@ \@minus5\p@
87   \abovedisplayshortskip \z@ \@plus3\p@
88   \belowdisplayshortskip 6\p@ \@plus3\p@ \@minus3\p@
89   \belowdisplayskip \abovedisplayskip
90   \let\@listi\@listI}
91 \normalsize
```

`\small` This is the small size:

```
92 \renewcommand\small{%
93   \@setfontsize\small{\ixpt{10}}%
94   \abovedisplayskip 8.5\p@ \@plus3\p@ \@minus4\p@
95   \abovedisplayshortskip \z@ \@plus2\p@
96   \belowdisplayshortskip 4\p@ \@plus2\p@ \@minus2\p@
97   \def\@listi{\leftmargin\leftmarginI
98             \topsep 4\p@ \@plus2\p@ \@minus2\p@
99             \parsep 2\p@ \@plus\p@ \@minus\p@
100             \itemsep \parsep}%
101   \belowdisplayskip \abovedisplayskip}
```

We use `rm` style of URL:

```
102 \urlstyle{sf}
```

## 2.19 Margins and Paragraphing

We use a4paper.

```
103 \geometry{layout=a4paper,  
104   left=2cm,right=2cm,bottom=2cm,top=2cm,twoside,  
105   columnsep=30pt, twoside}%  
106 \savegeometry{standard}
```

`\parindent` We use not indented paragraphs with paragraph borders given by skips

```
\parskip 107 \setlength\parindent\z@  
108 \setlength\parskip{6\p@ plus 6\p@ minus 4\p@}
```

## 2.20 Cropmarks

There are several packages that provide crop marks. Unfortunately they do not work for us because they put crop marks at the background. Since we have colored pages, we want crop marks to be on the foreground.

In this section we re-implement cropmarks of the `geometry` package, putting the marks on the foreground.

We postpone the code to the beginning of the document to get the proper value of the switch

```
109 \AtBeginDocument{\ifprint  
110   \AtBeginShipout{%  
111     \AtBeginShipoutUpperLeftForeground{%  
112       \color{black}%  
113       \@tempdima=\Gm@layouthoffset  
114       \@tempdimb=\Gm@layoutvoffset  
115       \put(\@tempdima,-\@tempdimb+6\p@){\line(0,1){50}}%  
116       \put(\@tempdima-6\p@,-\@tempdimb){\line(-1,0){50}}%  
117       \advance\@tempdima by \Gm@layoutwidth  
118       \put(\@tempdima,-\@tempdimb+6\p@){\line(0,1){50}}%  
119       \put(\@tempdima+6\p@,-\@tempdimb){\line(1,0){50}}%  
120       \advance\@tempdimb by \Gm@layoutheight  
121       \put(\@tempdima,-\@tempdimb-6\p@){\line(0,-1){50}}%  
122       \put(\@tempdima+6\p@,-\@tempdimb){\line(1,0){50}}%  
123       \advance\@tempdima by -\Gm@layoutwidth  
124       \put(\@tempdima-6\p@,-\@tempdimb){\line(-1,0){50}}%  
125       \put(\@tempdima,-\@tempdimb-6\p@){\line(0,-1){50}}%  
126     }}\fi}
```

In draft mode we put the word ‘DRAFT’ across the page:

```
127 \AtBeginDocument{\ifDraft  
128   \AtBeginShipout{%  
129     \AtBeginShipoutUpperLeft{%  
130       \color{black!25}%  
131       \@tempdima=\Gm@layouthoffset  
132       \@tempdimb=\Gm@layoutvoffset  
133       \advance\@tempdima by 0.2\Gm@layoutwidth  
134       \advance\@tempdimb by 0.7\Gm@layoutheight
```

```

135     \put(\@tempdima,-\@tempdimb){%
136         \rotatebox{45}{%
137             \fontsize{6cm}{6cm}\selectfont
138             DRAFT}}}\fi}

```

## 2.21 Nonfloats

In Faoyearbook we used float package. Since we changed too much in the internals, here we just rewrite the code from scratch.

<code>\nf@vert@sep</code>	Vertical separation between the floats
	<pre> 139 \newlength\nf@vert@sep 140 \setlength\nf@vert@sep{60pt} </pre>
<code>\nf@width</code>	The width of the nonfloat
	<pre> 141 \newlength\nf@width </pre>
<code>\nf@height</code>	The height of the nonfloat
	<pre> 142 \newlength\nf@height </pre>
<code>\nf@captionheight</code>	The height reserved for the caption
	<pre> 143 \newlength\nf@captionheight 144 \setlength\nf@captionheight{32\p@} </pre>
<code>\nf@sourceheight</code>	The height reserved for the source lines
	<pre> 145 \newlength\nf@sourceheight 146 \setlength\nf@sourceheight{48\p@} </pre>
<code>\nf@margin</code>	Margin for floats
	<pre> 147 \newlength\nf@margin 148 \setlength\nf@margin{12\p@} </pre>
<code>\nf@trianglebase</code>	The design requires a triangle under the caption. Here it is
	<pre> 149 \newlength\nf@trianglebase 150 \setlength\nf@trianglebase{12\p@} </pre>
<code>\chartwidth</code>	The resulting width of a chart
	<pre> 151 \newlength\chartwidth </pre>
<code>\chartheight</code>	The resulting width of a chart
	<pre> 152 \newlength\chartheight </pre>
<code>\nonfloat@type</code>	The counter to keep the next type to assign
	<pre> 153 \newcount\nonfloat@type 154 \nonfloat@type=4\relax </pre>
<code>\nf@contentsbox</code>	The box to keep the contents of the float
	<pre> 155 \newbox\nf@contentsbox </pre>

`\nf@mainbox` The box for the float  
156 `\newbox\nf@mainbox`

`\newnon@float` The macro `\newnon@float` has the following arguments: TYPE, EXT, NAME, LISTNAME, for example  
`\newnon@float{map}{lom}{Map}{List of Maps}`

It defines a nonfloat with these parameters.

157 `\def\newnon@float#1#2#3#4{%`

First, we need to define `\ftype@TYPE`: the type of the float. Note that tables are taken, so we need to make a special care of nonfloats that correspond to floats.

158 `\expandafter\ifx\csname ftype@#1\endcsname\relax`  
159 `\expandafter\edef\csname ftype@#1\endcsname{\the\nonfloat@type}%`  
160 `\multiply\nonfloat@type by 2\relax`  
161 `\fi`

Now we define the extension for the floats

162 `\expandafter\def\csname ext@#1\endcsname{#2}%`

The macro `\fnum@TYPE` formats the line like “Figure 1”. We need to check whether the counter is defined

163 `\expandafter\ifx\csname the#1\endcsname\relax`  
164 `\newcounter{#1}\fi`  
165 `\expandafter\def\csname fnum@#1\endcsname{#3~\csname`  
166 `the#1\endcsname}%`

Now we want to define the environment TYPE. Since it might be already defined, we first delete this definition, otherwise `\newenvironment` might throw an error

167 `\expandafter\let\csname #1\endcsname\relax`  
168 `\expandafter\let\csname end#1\endcsname\relax`

And the actual definition

169 `\newenvironment{#1}{\non@float{#1}}{\endnon@float}}`

`\non@float` Now we are ready to define the `\non@float` macro. It has three parameters: TYPE, SIZE and PLACEMENT. `\nf@source` is the source of the float.

170 `\def\non@float#1#2#3{`  
171 `\def\@capttype{#1}%`  
172 `\def\nf@size{#2}%`  
173 `\def\nf@placement{#3}%`  
174 `\let\nf@source\@empty`

Define the caption producing command:

175 `\long\def\@makecaption##1##2{\long\gdef\nf@caption{%`  
176 `{\bfseries\large\color{white}`  
177 `\MakeUppercase{##1}: ##2}}%`  
178 `\gdef\nf@caption{}}%`

We calculate the size of the float

```

179 \nf@width=\columnwidth
180 \nf@height=\dimexpr(\textheight/2-\nf@vert@sep/2)%
181 \def\tempW{W}%
182 \def\tempT{T}%
183 \def\tempB{B}%
184 \ifx\nf@size\tempW
185   \nf@width=\textwidth
186 \fi
187 \ifx\nf@size\tempT
188   \nf@height=\textheight
189 \fi
190 \ifx\nf@size\tempB
191   \nf@width=\textwidth
192   \nf@height=\textheight
193 \fi
194 \charheight=
195   \dimexpr(\nf@height-\nf@captionheight-\nf@sourceheight
196     -2\nf@margin-\nf@trianglebase)%
197 \chartwidth=\dimexpr(\nf@width-2\nf@margin)%

```

Now we construct the main box.

```

198 \global\setbox\nf@contentsbox
199   \color@vbox
200   \normalcolor
201   \vbox to \charheight
202   \bgroup
203   \hsize\chartwidth
204   \@parboxrestore
205   \@floatboxreset
206 }

```

\endnon@float The actual typesetting

```

207 \def\endnon@float{\@endfloatbox\par
208   \hsize=\nf@width
209   \setbox\nf@mainbox=\vbox to \nf@height\bgroup
210     \hsize=\chartwidth
211     \noindent
212     \begin{picture}(0,0)
213       \put(0,0){\color{\bgcolor}%
214         \begin{tikzpicture}[baseline=(current bounding box.north)]
215           \fill (0,0) -- (\nf@trianglebase,0) -- (0.5\nf@trianglebase,-\nf@trianglebase) -- cy
216         \end{tikzpicture}}
217     \end{picture}%
218     \color{\bgcolor}\color@block{\nf@width}{\nf@captionheight}{\z@}%
219     \hskip\nf@margin\vbox to \nf@captionheight\bgroup
220     \nf@caption\vfill
221     \egroup\par\nointerlineskip\vskip\nf@trianglebase
222     \noindent\hskip\nf@margin\box\nf@contentsbox\vfill\egroup
223   \box\nf@mainbox}

```



`\map` A standard nonfloat:  
224 `\newnon@float{map}{lom}{Map}{List of Maps}`

`\table` Another one  
225 `\newnon@float{table}{lot}{Table}{List of Tables}`

`\chart` And another one  
226 `\newnon@float{chart}{loc}{Chart}{List of Charts}`

## References

- [1] Boris Veytsman. *L<sup>A</sup>T<sub>E</sub>X Style for FAO Yearbook*. FAO UN, 2011.
- [2] UK T<sub>E</sub>X Users Group. UK list of T<sub>E</sub>X frequently asked questions. <http://www.tex.ac.uk/cgi-bin/texfaq2html>, 2008.
- [3] Pavel Farář. *Support Package for Free Fonts by ParaType*, May 2011. <http://mirrors.ctan.org/fonts/paratype>.
- [4] Stephen G. Hartke. *Arev Sans for T<sub>E</sub>X and L<sup>A</sup>T<sub>E</sub>X*, May 2006. <http://mirrors.ctan.org/fonts/arev>.
- [5] Uwe Kern. *Extending L<sup>A</sup>T<sub>E</sub>X's Color Facilities: the xcolor Package*, January 2007. <http://mirrors.ctan.org/macros/latex/contrib/xcolor>.

# Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols		D
\%	59	\DeclareOption . . .
\@bchar	60, 67, 68	4, 5, 6, 7, 8, 11,
\@bgcolor	3	12, 17, 18, 21, 22
\@capttype	171	\DeclareRobustCommand
\@empty	174	\AtBeginShipoutUpperLeftForeground . . . . . 80, 82
\@endfloatbox	207	\DeclareTextFontCommand
\@floatboxreset	205	. . . . . 81, 83
\@gobble	59, 60	\def . . . . . 1, 59,
\@issuumodefalse	20	60, 72, 74, 75,
\@issuumodetrue	21	76, 97, 157, 162,
\@ixpt	93	165, 170, 171,
\@listI	90	172, 173, 175,
\@listi	90, 97	181, 182, 183, 207
\@makecaption	175	\dimexpr . . 180, 195, 197
\@minus	86,	\Draftfalse . . . . . 16
	88, 94, 96, 98, 99	\Drafttrue . . . . . 17, 18
\@parboxrestore	204	
\@pctchar	59, 68	
\@plus	86, 87, 88,	
	94, 95, 96, 98, 99	
\@setfontsize	85, 93	
\@tableheadcolor	3	
\@tempdima	113,	
	115, 116, 117,	
	118, 119, 121,	
	122, 123, 124,	
	125, 131, 133, 135	
\@tempdimb	. . . . .	
	114, 115, 116,	
	118, 119, 120,	
	121, 122, 124,	
	125, 132, 134, 135	
\@xiipt	85	
\\	60	
A		E
\abovedisplayshortskip	. . . . . 87, 95	\edef . . . . . 62, 159
\abovedisplayskip	. . . . . 86, 89, 94, 101	\egroup . . . . . 221, 222
\advance	117,	\else . . . . . 49
	120, 123, 133, 134	\end . . . . . 216, 217
		\endcsname . . . 158,
		159, 162, 163,
		165, 166, 167, 168
		\endnonfloat . 169, 207
		\EndPartIntro . . . . . 4
		environments:
		chart . . . . . 5
		ConceptsAndMethods
		. . . . . 9
		freeding . . . . . 9
		map . . . . . 5
		metadata . . . . . 8
		MetadataCollection
		. . . . . 8
		publication . . . . . 7
		table . . . . . 5
		\expandafter . 59, 60,
		158, 159, 162,
		163, 165, 167, 168
B		
\begin	212, 214	
\belowdisplayshortskip	. . . . . 88, 96	
\belowdisplayskip	. . . . . 89, 101	
\bfdefault	79	
\bfseries	176	
\bgroup	202, 209, 219	
\box	222, 223	
C		
\caption	5	
\captionfamily	3, 82, 83	
\chart	226	
chart (environment)	5	
\charheight	. . . . . 6, 152, 194, 201	
\chartwidth	6,	
	151, 197, 203, 210	
\ClassWarning	2	
\cleardoublepage	6	
\clearpage	6	
\clearspread	6	
\color	112,	
	130, 176, 213, 218	
\color@block	218	
\color@vbox	199	
\columnwidth	179	
ConceptsAndMethods	(environment) . . 9	
\csname	158, 159, 162,	
	163, 165, 167, 168	
\currenticon	3	
\CurrentOption	. . . . . 4, 5, 6, 7, 8, 22	

<b>F</b>		
\familydefault	....	78
\faoset	.....	2, 72
\faoyearbook@size@warning	.....	1
\fi	.....	39, 58, 126, 138, 161, 164, 186, 189, 193
\fill	.....	215
\fontfamily	.....	80, 82
\fontsize	.....	137
\freeding (environ- ment)	.....	9
<b>G</b>		
\gdef	.....	175, 178
\geometry	.....	103
\global	.....	198
\Gm@layoutheight	..	120, 134
\Gm@layouthoffset	..	113, 131
\Gm@layoutvoffset	..	114, 132
\Gm@layoutwidth	...	117, 123, 133
<b>H</b>		
\hhline	.....	7
\hsize	....	203, 208, 210
\hskip	.....	219, 222
\hypersetup	.....	41, 50
<b>I</b>		
\if@issuemode	...	19, 37
\ifDraft	.....	15, 127
\ifprint	..	2, 9, 40, 109
\ifx	.....	158, 163, 184, 187, 190
\immediate	.....	61
\includegraphics	...	2
\itemsep	.....	100
<b>L</b>		
\large	.....	176
\leftmargin	.....	97
\leftmargini	.....	97
\let	...	90, 167, 168, 174
\line	.....	115, 116, 118, 119, 121, 122, 124, 125
\listofcharts	.....	6
\listofmaps	.....	6
\listoftables	.....	6
\LoadClass	.....	24
\long	.....	1, 175
<b>M</b>		
\MakeUppercase	....	177
\map	.....	224
map (environment)	....	5
metadata (environ- ment)	.....	8
MetadataCollection (environment)	..	8
\multiply	.....	160
<b>N</b>		
\narrowfamily	..	3, 80, 81
\newbox	.....	155, 156
\newcount	.....	153
\newcounter	.....	164
\newenvironment	...	169
\newif	.....	9, 15, 19
\newlength	...	139, 141, 142, 143, 145, 147, 149, 151, 152
\newnon@float	.....	157, 224, 225, 226
\nf@caption	175, 178, 220	
\nf@captionheight	..	143, 195, 218, 219
\nf@contentsbox	...	155, 198, 222
\nf@height	142, 180,	188, 192, 195, 209
\nf@mainbox	156, 209, 223	
\nf@margin	...	147, 196, 197, 219, 222
\nf@placement	.....	173
\nf@size	.....	172, 184, 187, 190
\nf@source	.....	174
\nf@sourceheight	..	145, 195
\nf@trianglebase	..	149, 196, 215, 221
\nf@vert@sep	..	139, 180
\nf@width	.....	141, 179, 185, 191, 197, 208, 218
\noindent	....	211, 222
\nointerlineskip	..	221
\non@float	...	169, 170
\nonfloat@type	....	153, 159, 160
\normalcolor	.....	200
\normalsize	.....	84
<b>O</b>		
\OBJ@CVR	.....	62, 69
\owner	.....	8
<b>P</b>		
\p@	..	86, 87, 88, 94, 95, 96, 98, 99, 108, 115, 116, 118, 119, 121, 122, 124, 125, 144, 146, 148, 150
\par	.....	207, 221
\parindent	.....	107
\parsep	.....	99, 100
\parskip	.....	107
\part	.....	3
\PassOptionsToClass	22	
\PassOptionsToPackage	.....	13
\pCycle	.....	7
\pDescription	.....	7
\pdfcatalog	.....	63
\pdfastobj	.....	62
\pdfobj	.....	61
\pEdition	.....	7
\printfalse	.....	10, 11
\printtrue	.....	12
\ProcessOptions	...	23
\PSSans@scale	.....	74
\PSSansCaption@scale	76	
\PSSansNarrow@scale	75	
publication (environ- ment)	.....	7
\put	..	115, 116, 118, 119, 121, 122, 124, 125, 135, 213
\pWeb	.....	7
<b>R</b>		
\refMetadata	.....	8
\relax	..	23, 154, 158, 160, 163, 167, 168

<code>\renewcommand</code> . . . . .	. 107, 108, 140,	<code>\textheight</code> 180, 188, 192
. 77, 78, 79, 84, 92	144, 146, 148, 150	<code>\textnarrow</code> . . . . . 3, <u>81</u>
<code>\RequirePackage</code> 25,	<code>\sfdefault</code> . . . . . 77, 78	<code>\textsubscript</code> . . . . . 9
26, 27, 28, 29,	<code>\small</code> . . . . . <u>92</u>	<code>\textwidth</code> . . . 185, 191
30, 31, 32, 33,	<code>\Source</code> . . . . . 6	<code>\the</code> . . . . . 62, 159
34, 35, 36, 38, 73	<code>\source</code> . . . . . 8	<code>\topsep</code> . . . . . 98
<code>\rotatebox</code> . . . . . 136	<code>\space</code> . . . . . 68, 69	
	<code>\string</code> . . . . . 59, 60	<b>U</b>
<b>S</b>	<code>\subsection</code> . . . . . 3	<code>\urlstyle</code> . . . . . 102
<code>\savegeometry</code> . . . . . 106		
<code>\section</code> . . . . . 3	<b>T</b>	<b>V</b>
<code>\selectcolor</code> . . . . . 3	<code>\table</code> . . . . . <u>225</u>	<code>\vbox</code> . . . . . 201, 209, 219
<code>\selectfont</code> . 80, 82, 137	<code>table (environment)</code> . . 5	<code>\vfill</code> . . . . . 220, 222
<code>\selecticon</code> . . . . . 3	<code>\tempB</code> . . . . . 183, 190	<code>\vskip</code> . . . . . 221
<code>\setbox</code> . . . . . 198, 209	<code>\tempT</code> . . . . . 182, 187	
<code>\setkeys</code> . . . . . 72	<code>\tempW</code> . . . . . 181, 184	<b>Z</b>
<code>\setlength</code> . . . . .	<code>\textcaption</code> . . . . . 3, <u>83</u>	<code>\z@</code> . . . . . 87, 95, 107, 218