

New L^AT_EX Style for FAO Yearbook *

Boris Veytsman[†]

2013/08/18, v0.1

Abstract

This package provides class for typesetting FAO Yearbook. This is a refactoring of the `faoyeabook` package

1 Introduction

The package `faoyearbook` [1] was written in 2011 for FAO Statistical Yearbook.

The package `faosyb` is a refactoring of this package. We use the lessons learned and incorporate new design requirements. We use some (actually plenty) code from the previous version, but since we do not have to be compatibility, we can correct some unfortunate decisions.

2 User Guide

The installation of the class follows the usual practice [2] for L^AT_EX packages:

1. Run `latex` on `faosyb.ins`. This will produce the L^AT_EX class `faosyb.cls`.
2. Put the file `faosyb.cls` to the place where L^AT_EX can find it (see [2] or the documentation for your T_EX system).
3. Update the database of file names. Again, see [2] or the documentation for your T_EX system for the system-specific details.
4. The file `faosyb.pdf` provides the documentation for the package (this is the file you are probably reading now).

As an alternative to items 2 and 3 you can just put the file `faosyb.cls` in the working directory where your `.tex` file is.

*©2013, Food and Agriculture Organization of the United Nations

[†]borisv@lk.net, boris@varphi.com

2.1 Invocation

To use the class, put in the preamble of your document

```
\documentclass[\langle options \rangle]{faosyb}
```

If the option **web** (default) is chosen, the pages of the book have the dimensions corresponding to A4 paper. However, if the option **print** is chosen, then the pages are printed on a wider area, and crop marks are added for the trimming.

If the option **issuu** is chosen, the internal links are transformed to external in the form suitable for <http://www.issuu.com>. Note that this option probably does not make much sense unless **web** option is also chosen. However, it is still possible to select both **print** and **issuu** option if someone needs it for an obscure purpose.

The option **Draft** (note the capitalization!) leads to the the large word ‘DRAFT’ printed across the pages. The standard L^AT_EX option **draft** leads to the same result, but it also makes other changes, most notably, in the behavior of the `\includegraphics` command and warnings.

`\ifprint` It is possible to query the current mode using the macro `\ifprint`, for example

```
\ifprint
  Stuff for print version
\else
  Stuff for web version
\fi
```

Any branch of this conditional may be empty, so web-only stuff can be coded as

```
\ifprint\else Web-only stuff\fi
```

`\includegraphics` There is a special facility for `\includegraphics` command to choose a file depending on the current mode of the package. Namely, if there is a file `image_print.pdf` visible by L^AT_EX, then the commands `\includegraphics{image}` or `\includegraphics{image.pdf}` selects the file `image_print.pdf`. In the case this file is not found, the file `image.pdf` is selected instead. Similarly in the web mode the file `image_web.pdf` will be selected first, and only if it does not exist, `image.pdf` is selected. This rule works also for commands `\includeLargeGraphics` and `\includeExtraLargeGraphics` described below.

Note that at this time there is no similar facility for the `\input` command.

2.2 Setting Parameters

`\faoset` Some parameters in the class can be set with the command `\faoset{\langle key=value \rangle}`, for example

```
\faoset{bgcolor=blue}
```

Most of the parameters are explained below.

2.3 Fonts

`\narrowfamily` The class uses PT Sans fonts [3] for body text and Arev fonts [4] for math. It
`\textnarrow` defines two additional families: Narrow and Caption, corresponding to the PT
`\captionfamily` Sans Narrow and PT Sans Caption font. They can be selected by the declarations
`\textcaption` `\narrowfamily` and `\captionfamily` or by the commands `\textnarrow{<text>}`
and `\textcaption{<text>}` following the usual L^AT_EX conventions. Note that since
PT Sans does not provide math alphabet, this choice does not change the mathe-
matical text.

PT Sans Narrow may be useful for typesetting tables, for example,

```
{\scriptsize\narrowfamily
\rowcolors{4}{@bgcolor!30}{@bgcolor!20}
\input{./Tables/P1.DEM_1.tex}}
```

2.4 Colors and Icons for Parts

A Yearbook is separated into parts (more on this below). Each part has its own color and icon. They are set by the keys `bgcolor` and `icon` of the `\faoset` command, for example,

```
\faoset{icon=./Icons/agriculture.png}
\faoset{icon=./Icons/population}
\faoset{bgcolor=blue}
\faoset{bgcolor=green!25!yellow}
```

The parameter for the `icon` key can be any file name (with or without extension), suitable for the `\includegraphics` command. The parameter for the `bgcolor` key can be specified in any form acceptable by `xcolor` package [5].

The key `tableheadcolor` sets the color for the headers of tables defined by H or P key (see Section 2.6). Normally it is 30% of the current `@bgcolor` color, but it can be set to any required value.

`\selecticon` Note that `\faoset` command does not change the icon or background color
`\selectcolor` immediately. When issued *before* `\part` command, it sets up icon and color for
the next part. If needed, you can manually change this using `\selecticon` and
`\selectcolor` commands. In most cases you should *not* use these commands.

`@bgcolor` After a `\part` command (or explicit `\selecticon` and `\selectcolor` com-
`@tableheadcolor` mand we can access the current values of the color in `@bgcolor`, `@tablecolor`
`\currenticon` colors and `\currenticon` macro.

2.5 Sectioning

`\part` The main division of the text are `\parts`. The command `\part{<title>}` is used for
`\section` numbered parts, while the command `\part*{<title>}` is used for unnumbered parts.
`\subsection` The next division are `\sections` and `\subsections`. They are never numbered.
The style does not use `\chapters`.

`\EndPartIntro` The sections immediately following new parts are special: they are typeset in one column and cannot have floats. The command `\EndPartIntro` switches to the “normal” sections.

2.6 Floats

One of the most important changes from the previous version of the class [1] is the treatment of floats.

In standard L^AT_EX floats “float”: they can be placed by the algorithm anywhere. The previous version made them “sticky”: the author explicitly tells T_EX where floats should be placed. However, to do so the class required the author to make explicit page breaks, which was not very convenient.

This version has a completely rewritten interface and algorithm for placing floats:

1. Like in standard L^AT_EX, authors do not normally provide page breaks—T_EX tries to make this decision for them.
2. Like in the previous version, floats are put exactly where the authors want them—no default placing and second-guessing.

Here is how it is done.

The main unit of the book is *spread*: a verso page and the corresponding recto page. Each page is divided into four quarters, upper left, upper right, lower left and lower right. We will denote them `ul`, `ur`, `ll`, `lr` for the verso page and `UL`, `UR`, `LL`, `LR` for the recto page (Figure 1). We allow four kinds of floats:

Single floats occupy exactly one quarter. They are denoted as `S`.

Tall floats occupy two quarters stacked vertically (for example, `ul` and `ll`). They are denoted as `T`.

Wide floats occupy two quarters adjacent horizontally (for example, `LL` and `LR`). They are denoted as `W`.

Big floats occupy all four quarters on a page. They are denoted as `B`.

The parameters $\{\langle type \rangle\}$ and $\{\langle location \rangle\}$ are mandatory for floats, for example

```
\begin{map}{T}{ur}
...
\end{map}
\begin{chart}{S}{UL}
...
\end{chart}
```

For multiquarter floats the location is the location of the upper left corner, so Big float can use only `ul` or `UL` location.



Figure 1: A Spread

Of course, not all combinations are valid: you cannot specify float as `{T}{ll}` or `{W}{UR}`, for example. If you use such combinations, the results may be unpredictable. Also it is not predictable what happens if you try to put overlapping floats (e.g. `{S}{UR}` and `{W}{UL}`).

There are two additional rules:

1. A verso page may have text and floats (still it is recommended that if it has text, then it should not have floats occupying the upper left corner).
2. A recto page may have *either* text or floats: if there are floats for this page, all text is moved to the following verso page.

chart There are three types of floats defined by the class:

map **chart** plots and other charts,

table **map** mapped data.

table mini tables.

caption Each of these kinds of material is typeset using the corresponding environment: **chart**, **table** or **map**. Note that the caption for each of these environments *must* precede the graphical material, for example:

```

\begin{chart}{B}{UL}
  \caption{Hunger Data}
  \label{chart:hunger}
  \includegraphics{hunger.pdf}
\end{chart}

```

Note that our class redefines `table` environemnt!. For tables on separate pages use `longtable`.

`\chartwidth` Inside a `chart`, `map` or `table` it is useful to know the size allocated for the
`\chartheight` graphics or table, for example, to be able to scale the graphics. Two lengths, `\chartwidth` and `\chartheight` provide this information, so the user can say, for example,

```
\includegraphics[width=\chartwidth, height=\chartheight]{theChart}
```

`\source` Inside a `chart`, `map` or `table` the macro `\source{<source>}` gives the source of the information, for example,

```
\Source{FA0, Statistical Division [FA0STAT]}
```

`\listoftables` The standard L^AT_EX has the command `\listoftables` to produce the list of
`\listofcharts` tables in the document. Our class retains this command and produces two additional commands `\listofcharts` and `\listofmaps` with the obvious meaning.
`\listofmaps`

2.7 Page Breaks

`\clearpage` Standard L^AT_EX has commands for immediate page break (e.g. `\clearpage`)
`\cleardoublepage` and for switching to the next recto page, possibly ejecting the next verso page
`\clearspread` (`\cleardoublepage`). The class provides another command `\clearspread`. It switches to the next *verso* page, possibly ejecting the next recto page (and putting there floats intended for this page, if any).

2.8 Tables

To typeset numericall items one should use `d` column identifier with the format `d{<a.b>}`, where *a* is the number of decimal in the integer part of the number, and *b* is the number of decimal digitst in the fractional part. For example, a number 12.345 corresponds to `d{2.3}`. The column headers are usually *not* numerical, so one need to use `\multicolumn` entries to typeset them. The class defines several such entries:

H produces a centered entry.

P produces an entry of a given length, for example, `P{1.5cm}`

C produces an entry of the length corresponding to the given number of numerical columns. For example, `C{2}` corresponds to a header of two numerical columns. Each column is assumed to be of the size enough to store -99.999 .

`\hhline` For the rules that do not span the table width `\hhline{<specification>}` command from the `hhline` package should be used. The `{<specification>}` argument of this command has many variants, but for our purposes we need only one variant: the command `-` produces a horizontal line spanning one column. The color of this line is determined by the command `\arrayrulecolor{<color>}`, issued in the last `>{<argument>}` command before the `-` specification. Therefore the command `>{\arrayrulecolor{@tableheadcolor}}-` produces a line of the color `@tableheadcolor`, which is seen as the absence of line. The command `>{\arrayrulecolor{black}}---` produces a black line spanning three columns. Thus if we have a four-column table and want a rule spanning columns 2-3, the following command should be issued:

```
\hhline{>{\arrayrulecolor{@tableheadcolor}}-% Column 1, no rule
>{\arrayrulecolor{black}}--% Columns 2 and 3, black rule
>{\arrayrulecolor{@tableheadcolor}}-% Column 4, no rule
```

The usual `*` specification may be used for repeating patterns, for example, `*{5}{-}` is equivalent to `-----`.

The vertical bar `|` specification in the `\hhline` argument means an interruption of the line. The interruption is by default a black interval, to make it the same color as the header background, use `>{\arrayrulecolor{@tableheadcolor}}|`.

2.9 Publication Descriptions

`publication` FAO yearbook describes some FAO publications. These publications should be put inside the environment `publication`. The environment has one mandatory argument, which is the title of the publication, and one optional argument, which sets the file name of the publication cover. Note that the option argument, if present, must precede the mandatory one. If this argument is absent, no cover is included. Inside the environment the macros `\pDescription{<description>}`, `\pEdition{<year>}{<edition>}`, `\pWeb{<URL>}` and `\pCycle{<date>}` are used to typeset the corresponding items related to the publication. For example,

```
\pDescription
\pEdition
\pCycle
pWeb
\begin{publication}[./Plots/StateOfFoodAndAgriculture.png]{The State
of Food and Agriculture}
\pDescription{The State of Food and Agriculture, FAO's major
annual flagship publication, aims at bringing to a wider
audience balanced science-based assessments of important issues
in the field of food and agriculture. Each edition of the
report contains a comprehensive, yet easily accessible, overview
of a selected topic of major relevance for rural and
agricultural development and for global food security. This is
supplemented by a synthetic overview of the current global
agricultural situation.}
\pEdition{2010}{Livestock in the balance}
\pEdition{2011}{Women in Agriculture Closing the gender gap for
development}
\pCycle{May each year}
```

```
\pWeb{http://www.fao.org/docrep/013/i2050e/i2050e00.htm}
\end{publication}
```

Note that, as in the example, some fields may be repeated.

Two spacing parameters can be used for typesetting of publications: `publicationskip` is the amount of additional space between the publications, while `publicationparskip` is the space between the paragraphs inside the publication environment. The default values correspond to the command

```
\faoset{publicationskip=6pt plus 2pt minus 2pt,
        publicationparskip=6pt plus 6pt minus 4pt}
```

2.10 Metadata

MetadataCollection Each chart, map or table in the book has a *source*. Sources are collected in the environment `MetadataCollection`, which consists of separate `metadata` environments. Each `metadata` environment has two obligatory arguments—the name of the source and the key. The key is used to identify the metadata in the charts, maps, tables and other objects. The environment may include other commands.

\source `\source{<source>}` sets the source of the data.

\owner `\owner{<owner>}` sets the owner of the data.

Note that there is no “description” command because any text which is not an argument of the commands above is considered to belong to the description of the data.

Example of the usage of these commands:

```
\begin{MetadataCollection}
\begin{metadata}{Agricultural population}{P1.DEM.FAO.POP.AGR}

    Agricultural population is defined as all persons depending for
    their livelihood on agriculture, hunting, fishing and forestry.
    It comprises all persons economically active in agriculture as
    well as their non-working dependents. It is not necessary that
    this referred population exclusively come from rural population.

    \source{FILL ME}
    \owner{FILL ME}
\end{metadata}
\end{MetadataCollection}
```

\refMetadata The metadata is referenced by the command `\refMetadata{<key>}`, for example

```
\refMetadata{P1.DEM.FAO.POP.AGR}
```


This command will be typset as

Source: Agricultural population, page NNNN.

This command must *not* occur in the caption of the chart, map or table.

Note that the package automatically provides backreferencing: all charts, maps and tables where the metadata is referenced, are mentioned in the corresponding metadata section.

The sources of each chart, map or table can be shown in the lists of charts, tables, maps or not. The key `metadataInLists` (by default `false`) determines whether they are shown there. To make them visible, put before the lists

```
\faosetup{metadataInLists=true}
```

2.11 Concepts and Methods

`ConceptsAndMethods` The environment `ConceptsAndMethods` starts a new section “Concepts and Methods”. Concepts and methods are collected in the series of `concept` environments. Each environment has one obligatory field: the name of the concept, for example:

```
\begin{ConceptsAndMethods}
  \begin{concept}{Gross domestic product}
    Gross domestic product (GDP) is the market value of all officially
    recognized final goods and services produced within a country in a
    given period of time.
  \end{concept}
  \begin{concept}{Gross state product}
    Gross state product (GSP), or gross regional product (GRP), is a
    measurement of the economic output of a state or province (i.e.,
    of a subnational entity). It is the sum of all value added by
    industries within the state and serves as a counterpart to the
    gross domestic product (GDP).
  \end{concept}
\end{ConceptsAndMethods}
```

2.12 Further Reading

`freading` The special environment `freading` is used for the “further reading” sections of the book. It starts the text from the new page and changes some defaults.

2.13 Subscripts in Text

`\textsubscript` The standard L^AT_EX defines `\textsuperscript`. The class adds a similar `\textsubscript` command.

3 Implementation

3.1 Options

`\faoyearbook@size@warning` The font-changing options are not used in our setup, so we just produce a warning:

```
1 \long\def\faoyearbook@size@warning#1{%
2   \ClassWarning{faoyearbook}{Size-changing option #1 will not be
3     honored}}%
4 \DeclareOption{8pt}{\faoyearbook@size@warning{\CurrentOption}}%
5 \DeclareOption{9pt}{\faoyearbook@size@warning{\CurrentOption}}%
6 \DeclareOption{10pt}{\faoyearbook@size@warning{\CurrentOption}}%
7 \DeclareOption{11pt}{\faoyearbook@size@warning{\CurrentOption}}%
8 \DeclareOption{12pt}{\faoyearbook@size@warning{\CurrentOption}}%
```

`\ifprint` We have a flag which shows whether we are in Web or print mode

```
9 \newif\ifprint
10 \printfalse
11 \DeclareOption{web}{\printfalse}
12 \DeclareOption{print}{\printtrue}
13 \PassOptionsToPackage{papersize={230mm,317mm},layout=a4paper,
14   layoutoffset=1cm,layoutvoffset=1cm,twoside}{geometry}}
```

`\ifDraft` If we are in ‘Draft’ or ‘draft mode’, we print a word ‘draft’ across the page:

```
15 \newif\ifDraft
16 \Draftfalse
17 \DeclareOption{Draft}{\Drafttrue}
18 \DeclareOption{draft}{\Drafttrue}
```

`\if@issuemode` Whether we need issue-style links

```
19 \newif\if@issuemode
20 \@issuemodefalse
21 \DeclareOption{issuu}{\@issuodemtrue}
```

All other options are just sent to the main class:

```
22 \DeclareOption*{\PassOptionsToClass{\CurrentOption}{report}}
23 \ProcessOptions\relax
```

3.2 Loading Class and Packages

We start with the base class and some packages

```
24 \LoadClass[10pt,twoside,twocolumn]{report}
25 \RequirePackage{graphicx,xkeyval}
26 \RequirePackage[table,cm]{xcolor}
27 \RequirePackage{tikz,geometry,dcolumn}
28 \usetikzlibrary{calc}
29 \RequirePackage{fancyhdr}
30 \RequirePackage{lscape,longtable,siunitx,booktabs}
31 \RequirePackage{multicol,atbegshi,picture,hhline,afterpage}
32 \RequirePackage[T1]{fontenc}
```

```

33 \RequirePackage[utf8x]{inputenc}
34 \RequirePackage{pdfpages}
35 \RequirePackage[authoryear]{natbib}
36 \RequirePackage[breaklinks]{hyperref}
37 \RequirePackage{bookmark}
38 \if@issuemode
39 \RequirePackage{issuulinks}
40 \fi

```

Options for the hyperref package are set as follows:

```

41 \ifprint
42 \hypersetup{breaklinks,colorlinks=false,pdfborder=0 0 0,
43   pdfauthor={FAO},
44   pdfsubject={Statistical Yearbook of the Food And Agricultural Organization for the United Na
45   pdftitle={Statistical Yearbook of the Food And Agricultural Organization for the United Nati
46   pdfkeywords={FAO, Food Security, Undernourishment, Sustainable agriculture},
47   pdfpagelayout=TwoColumnLeft,
48   pdfnewwindow=true
49 }
50 \else
51 \hypersetup{breaklinks,colorlinks=false,pdfborder=0 0 0,
52   pdfauthor={FAO},
53   pdfsubject={Statistical Yearbook of the Food And Agricultural Organization for the United Na
54   pdftitle={Statistical Yearbook of the Food And Agricultural Organization for the United Nati
55   pdfkeywords={FAO, Food Security, Undernourishment, Sustainable agriculture},
56   pdfpagelayout=TwoColumnRight,
57   pdfnewwindow=true
58 }
59 \fi

```

3.3 Color

We need to tell the printer that we are using CMYK color model. The following is taken from the pdfx package (the package itself is not too easy to make work).

```

60 \def\@pctchar{\expandafter\@gobble\string\%}
61 \def\@bchar{\expandafter\@gobble\string\}
62 \immediate\pdfobj stream attr{/N 4} file{FOGRA39L.icc}
63 \edef\OBJ@CVR{\the\pdfastobj}
64 \pdfcatalog{/OutputIntents [ <<
65   /Type/OutputIntent
66   /S/GTS_PDFX
67   /OutputCondition (FOGRA39)
68   /OutputConditionIdentifier (FOGRA39 \@bchar(ISO Coated v2
69   300\@pctchar\space \@bchar(ECI\@bchar)\@bchar))
70   /DestOutputProfile \OBJ@CVR\space 0 R
71   /RegistryName(http://www.color.org)
72   >> ]}

```

3.4 Key-Value Interface

`\faoset` We define the family `fao` for our keys:

```
73 \def\faoset#1{\setkeys{fao}{#1}}
```

3.5 Fonts

We use `arev` for mathematics:

```
74 \RequirePackage{arevmath}
```

For body text we use PT Sans:

```
75 \def\PTSans@scale{0.95}
76 \def\PTSansNarrow@scale{0.95}
77 \def\PTSansCaption@scale{0.95}
78 \renewcommand{\sfdefault}{PTSans-TLF}
79 \renewcommand{\familydefault}{\sfdefault}
80 \renewcommand{\bfdefault}{b}
```

`\narrowfamily` We declare a new family, `\narrowfamily`:

```
81 \DeclareRobustCommand\narrowfamily{\fontfamily{PTSansNarrow-TLF}\selectfont}
```

`\textnarrow` And the matching `\textnarrow` command:

```
82 \DeclareTextFontCommand{\textnarrow}{\narrowfamily}
```

`\captionfamily` Same with `\captionfamily`:

```
83 \DeclareRobustCommand\captionfamily{\fontfamily{PTSansCaption-TLF}\selectfont}
```

`\textcaption` And the matching `\textcaption` command:

```
84 \DeclareTextFontCommand{\textcaption}{\captionfamily}
```

`\normalsize` The basic size is 9.6pt:

```
85 \renewcommand\normalsize{%
86   \@setfontsize\normalsize{9.6pt}{\@xipt}%
87   \abovedisplayskip 10\p@ \@plus2\p@ \@minus5\p@
88   \abovedisplayshortskip \z@ \@plus3\p@
89   \belowdisplayshortskip 6\p@ \@plus3\p@ \@minus3\p@
90   \belowdisplayskip \abovedisplayskip
91   \let\@listi\@listI}
92 \normalsize
```

`\small` This is the small size:

```
93 \renewcommand\small{%
94   \@setfontsize\small{\ixpt{10}}%
95   \abovedisplayskip 8.5\p@ \@plus3\p@ \@minus4\p@
96   \abovedisplayshortskip \z@ \@plus2\p@
97   \belowdisplayshortskip 4\p@ \@plus2\p@ \@minus2\p@
98   \def\@listi{\leftmargin\leftmarginI
99     \topsep 4\p@ \@plus2\p@ \@minus2\p@
100     \parsep 2\p@ \@plus\p@ \@minus\p@
101     \itemsep \parsep}%
102   \belowdisplayskip \abovedisplayskip}
```

We use `rm` style of URL:

```
103 \urlstyle{sf}
```

3.6 Margins and Paragraphing

We use `a4paper`.

```
104 \geometry{layout=a4paper,
105   left=2cm,right=2cm,bottom=2cm,top=2cm,twoside,
106   columnsep=30pt, twoside}%
107 \savegeometry{standard}
```

`\parindent` We use not indented paragraphs with paragraph borders given by skips

```
\parskip 108 \setlength\parindent\z@
109 \setlength\parskip{6\p@ plus 6\p@ minus 4\p@}
```

3.7 Cropmarks

There are several packages that provide crop marks. Unfortunately they do not work for us because they put crop marks at the background. Since we have colored pages, we want crop marks to be on the foreground.

In this section we re-implement cropmarks of the `geometry` package, putting the marks on the foreground.

We postpone the code to the beginning of the document to get the proper value of the switch

```
110 \AtBeginDocument{\ifprint
111   \AtBeginShipout{%
112     \AtBeginShipoutUpperLeftForeground{%
113       \color{black}%
114       \@tempdima=\Gm@layouthoffset
115       \@tempdimb=\Gm@layoutvoffset
116       \put(\@tempdima,-\@tempdimb+6\p@){\line(0,1){50}}%
117       \put(\@tempdima-6\p@,-\@tempdimb){\line(-1,0){50}}%
118       \advance\@tempdima by \Gm@layoutwidth
119       \put(\@tempdima,-\@tempdimb+6\p@){\line(0,1){50}}%
120       \put(\@tempdima+6\p@,-\@tempdimb){\line(1,0){50}}%
121       \advance\@tempdimb by \Gm@layoutheight
122       \put(\@tempdima,-\@tempdimb-6\p@){\line(0,-1){50}}%
123       \put(\@tempdima+6\p@,-\@tempdimb){\line(1,0){50}}%
124       \advance\@tempdima by -\Gm@layoutwidth
125       \put(\@tempdima-6\p@,-\@tempdimb){\line(-1,0){50}}%
126       \put(\@tempdima,-\@tempdimb-6\p@){\line(0,-1){50}}%
127     }}\fi}
```

In draft mode we put the word ‘DRAFT’ across the page:

```
128 \AtBeginDocument{\ifDraft
129   \AtBeginShipout{%
130     \AtBeginShipoutUpperLeft{%
131       \color{black!25}%
```

```

132 \@tempdima=\Gm@layouthoffset
133 \@tempdimb=\Gm@layoutvoffset
134 \advance\@tempdima by 0.2\Gm@layoutwidth
135 \advance\@tempdimb by 0.7\Gm@layoutheight
136 \put(\@tempdima,-\@tempdimb){%
137 \rotatebox{45}{%
138 \fontsize{6cm}{6cm}\selectfont
139 DRAFT}}}\fi}

```

3.8 Setting Colors and Icons

`\fao@color@string` This is the command that remembers the present color for TOC

```

140 \def\fao@color@string{0,0,0}

```

`@bgcolor@next` We store the next background color in `@bgcolor@next`. We store the next heading background in `@tableheadcolor@next`.

`\setbgcolor` The command `\setbgcolor` selects the next background color:

```

141 \def\setbgcolor#1{\colorlet{@bgcolor@next}[cmyk]{#1}%
142 \addtocontents{toc}{\string\colorlet{@bgcolor}[cmyk]{#1}}%
143 \gdef\fao@color@string{#1}}
144 \setbgcolor{white}

```

The key-value interface for the same command:

```

145 \define@key{fao}{bgcolor}{\setbgcolor{#1}}

```

And for separate setting of `@tableheadcolor`

```

146 \define@key{fao}{tableheadcolor}{\colorlet{@tableheadcolor}[cmyk]{#1}}

```

`@bgcolor` The current color is in the macro `@bgcolor`.

`@tableheadcolor` This command makes the actual color change:

```

\selectcolor 147 \def\selectcolor{\colorlet{@bgcolor}{@bgcolor@next}%
148 \colorlet{@tableheadcolor}{@bgcolor!30}}
149 \selectcolor

```

`@tablebg` The color for table pages

```

150 \define@key{fao}{tablebg}{\colorlet{@tablebg}[cmyk]{#1}}

```

`\seticon` Setting the next icon for the part

```

151 \def\seticon#1{\gdef\next@icon{#1}}
152 \seticon{}
153 \define@key{fao}{icon}{\seticon{#1}}

```

`\selecticon` The actual icon change

`\currenticon`

```

154 \def\selecticon{\gdef\currenticon{\next@icon}}
155 \selecticon

```

3.9 Page Styles

standardpagestyle This is our main page style

```

156 \fancypagestyle{standardpagestyle}{%
157   \fancyhf{}%
158   \fancyhfoffset[LR]{1cm}%
159   \renewcommand\headrulewidth{\z@}%
160   \fancyhead[LE]{\color{bgcolor}\captionfamily
161     \Huge\ifnum\thepart>0\relax
162     \thepart\fi\normalsize\dotfill}%
163   \fancyhead[LO]{\color{bgcolor}\normalsize\dotfill\captionfamily
164     \Huge\leftmark
165     \ifx\currenticon\empty\else\space
166     \raisebox{-0.25\totalheight}{\includegraphics[width=1.1cm]{\currenticon}}\fi}%
167 }
168 \pagestyle{standardpagestyle}

```

3.10 Nonfloats

In Faoyearbook we used float package. Since we changed too much in the internals, here we just rewrite the code from scratch.

\nf@vert@sep Vertical separation between the floats

```

169 \newlength\nf@vert@sep
170 \setlength\nf@vert@sep{30pt}

```

\nf@width The width of the nonfloat

```

171 \newlength\nf@width

```

\nf@height The height of the nonfloat

```

172 \newlength\nf@height

```

\nf@captionheight The height reserved for the caption

```

173 \newlength\nf@captionheight
174 \setlength\nf@captionheight{32\p@}

```

\nf@sourceheight The height reserved for the source lines

```

175 \newlength\nf@sourceheight
176 \setlength\nf@sourceheight{48\p@}

```

\nf@margin Margin for floats

```

177 \newlength\nf@margin
178 \setlength\nf@margin{12\p@}

```

\nf@trianglebase The design requires a triangle under the caption. Here it is

```

179 \newlength\nf@trianglebase
180 \setlength\nf@trianglebase{12\p@}

```

`\chartwidth` The resulting width of a chart
181 `\newlength\chartwidth`

`\chartheight` The resulting width of a chart
182 `\newlength\chartheight`

`\nf@topskip` Top separation for a nonfloat @topskip

`\nf@bottomskip` Bottom separation for a nonfloat @bottomskip

`\nonfloat@type` The counter to keep the next type to assign
183 `\newcount\nonfloat@type`
184 `\nonfloat@type=4\relax`

`\nf@contentsbox` The box to keep the contents of the float
185 `\newbox\nf@contentsbox`

`\nf@mainbox` The box for the float
186 `\newbox\nf@mainbox`

`\newnon@float` The macro `\newnon@float` has the following arguments: TYPE, EXT, NAME, LISTNAME, for example
`\newnon@float{map}{lom}{Map}{List of Maps}`

It defines a nonfloat with these parameters.

187 `\def\newnon@float#1#2#3#4{%`

First, we need to define `\ftype@TYPE`: the type of the float. Note that tables are taken, so we need to make a special care of nonfloats that correspond to floats.

188 `\expandafter\ifx\csname ftype@#1\endcsname\relax`
189 `\expandafter\edef\csname ftype@#1\endcsname{\the\nonfloat@type}%`
190 `\multiply\nonfloat@type by 2\relax`
191 `\fi`

Now we define the extension for the floats

192 `\expandafter\def\csname ext@#1\endcsname{#2}%`

The macro `\fnum@TYPE` formats the line like “Figure 1”. We need to check whether the counter is defined

193 `\expandafter\ifx\csname the#1\endcsname\relax`
194 `\newcounter{#1}\fi`
195 `\expandafter\def\csname fnum@#1\endcsname{#3~\csname`
196 `the#1\endcsname}%`

Now we want to define the environment TYPE. Since it might be already defined, we first delete this definition, otherwise `\newenvironment` might throw an error

197 `\expandafter\let\csname #1\endcsname\relax`
198 `\expandafter\let\csname end#1\endcsname\relax`

And the actual definition

```
199 \newenvironment{#1}{\non@float{#1}}{\endnon@float}}
```

`\@getfirstletter` An aux macro to get a first letter of a word. Used in constructs

```
\edef\U{\@getfirstletter{AAAAA\@endword}}
```

```
200 \def\@getfirstletter#1{\@getfirstletter#1}
```

```
201 \def\@getfirstletter#1{#1\@gobbleword}
```

```
202 \def\@gobbleword#1\@endword{}
```

`\non@float` Now we are ready to define the `\non@float` macro. It has three parameters: TYPE, SIZE and PLACEMENT. `\nf@source` is the source of the float.

```
203 \def\non@float#1#2#3{
```

```
204   \def\@capttype{#1}%
```

```
205   \def\nf@size{#2}%
```

```
206   \def\nf@placement{#3}%
```

The macro `\nf@vert@pos` is either u or l

```
207   \lowercase{\xdef\nf@vert@pos{\@getfirstletter#3\@endword}}
```

```
208   \global\let\nf@source\@empty
```

Define the source command inside float

```
209   \def\source##1{\gdef\nf@source{##1}}
```

Define the caption producing command:

```
210 \long\def\@makecaption##1##2{\long\gdef\nf@caption{%
```

```
211   {\bfseries\large\color{white}
```

```
212   \MakeUppercase{##1}: ##2}}}%
```

```
213 \gdef\nf@caption{}}%
```

We calculate the size of the float and skips

```
214   \nf@width=\columnwidth
```

```
215   \nf@height=\dimexpr\textheight/2-\nf@vert@sep)%
```

```
216   \if\nf@vert@pos u\relax
```

```
217     \nf@topskip=\z@
```

```
218     \nf@bottomskip=\nf@vert@sep
```

```
219   \else
```

```
220     \nf@topskip=\nf@vert@sep%
```

```
221     \nf@bottomskip=\z@
```

```
222   \fi
```

```
223   \def\tempW{W}%
```

```
224   \def\tempT{T}%
```

```
225   \def\tempB{B}%
```

```
226   \ifx\nf@size\tempW
```

```
227     \nf@width=\textwidth
```

```
228   \fi
```

```
229   \ifx\nf@size\tempT
```

```
230     \nf@height=\textheight
```

```
231     \nf@topskip=\z@
```

```
232     \nf@bottomskip=\z@
```

```

233 \fi
234 \ifx\nf@size\tempB
235   \nf@width=\textwidth
236   \nf@height=\textheight
237   \nf@topskip=\z@
238   \nf@bottomskip=\z@
239 \fi
240 \charheight=
241   \dimexpr(\nf@height-\nf@captionheight-\nf@sourceheight
242     -2\nf@margin-\nf@trianglebase)%
243 \chartwidth=\dimexpr(\nf@width-2\nf@margin-0.5\nf@trianglebase)%
244 \nf@height=\dimexpr(\nf@height+\nf@topskip+\nf@bottomskip)%

```

Now we construct the main box.

```

245 \global\setbox\nf@contentsbox
246   \color@vbox
247   \normalcolor
248   \vbox to \charheight
249   \bgroup
250   \hsize\chartwidth
251   \@parboxrestore
252   \@floatboxreset
253 }

```

\endnon@float The actual typesetting

```

254 \def\endnon@float{\@endfloatbox\par
255   \hsize=\nf@width
256   \setbox\nf@mainbox=\vbox to \nf@height\bgroup
257   \hsize=\chartwidth
258   \vskip\nf@topskip
259   \noindent
260   \begin{picture}(0,0)%
261     \put(0,0){\color{@bgcolor}%
262       \begin{tikzpicture}[baseline=(current bounding box.north)]
263         \fill (0,0) -- (\nf@trianglebase,0) --
264           (0.5\nf@trianglebase,-\nf@trianglebase) -- cycle;
265       \end{tikzpicture}}
266   \end{picture}%
267   \def\@tempa{chart}%
268   \ifx\@tempa\@capttype
269   \begin{picture}(0,0)%
270     \put(0,0){\color{@bgcolor}%
271       \begin{tikzpicture}[baseline=(current bounding box.north)]
272         \draw(0,0) -- (\nf@width,0);
273         \draw (0.5\nf@trianglebase,-2\nf@trianglebase) --
274           (0.5\nf@trianglebase,-\charheight-2\nf@trianglebase
275             -\nf@margin) --
276           (\nf@width-\pgflinewidth,-\charheight-2\nf@trianglebase
277             -\nf@margin) -- (\nf@width-\pgflinewidth, 0);
278       \end{tikzpicture}}

```

```

279 \end{picture}%
280 \fi
281 {\color{@bgcolor}\color@block{\nf@width}{\nf@captionheight}{.1\p@}}%
282 \hskip\dimexpr(\nf@margin+0.5\nf@trianglebase)%
283 \vbox to \nf@captionheight\bgroup
284 \nf@caption\vfill
285 \egroup\par\nointerlineskip\vskip\nf@trianglebase
286 \vskip\nf@margin
287 \noindent\hskip\dimexpr(\nf@margin+0.5\nf@trianglebase)%
288 \box\nf@contentsbox\par\nointerlineskip
289 \vskip\nf@margin
290 \hskip\dimexpr(\nf@margin+0.5\nf@trianglebase)%
291 \vbox to \nf@sourceheight\bgroup
292 \ifx\nf@source@empty\else
293 \noindent{\color{@bgcolor}%
294 \rule{.2em}{.2em}~\rule{.2em}{.2em}~%
295 \rule{.2em}{.2em}~\rule{.2em}{.2em}~%
296 \rule{.2em}{.2em}\par}
297 \noindent Source: \nf@source\par\vfill\fi\egroup
298 \vfill\egroup
299 \edef\nf@currbox{\expandafter\csname nfbox@\nf@size
300 @\nf@placement\endcsname}%
301 \global\setbox\nf@currbox=
302 \vbox{\box\nf@currbox\nointerlineskip\penalty0\box\nf@mainbox}}

```

```

\map A standard nonfloat:
303 \newnon@float{map}{lom}{Map}{List of Maps}

\table Another one
304 \newnon@float{table}{lot}{Table}{List of Tables}

\chart And another one
305 \newnon@float{chart}{loc}{Chart}{List of Charts}

```

3.11 Output Routine

This is hairy because output routines are hairy...

We need several insert boxes. Naming convention: the letter for the box size and two letter code for the location. We use `\newbox` instead of `\newinsert` since we do not use associated `\count`, `\dimen` and `\skip` registers.

```

306 \newbox\nfbox@S@ul
307 \newbox\nfbox@S@ur
308 \newbox\nfbox@S@ll
309 \newbox\nfbox@S@lr
310 \newbox\nfbox@S@UL
311 \newbox\nfbox@S@UR
312 \newbox\nfbox@S@LL
313 \newbox\nfbox@S@LR
314 \newbox\nfbox@T@ul

```

```

315 \newbox\nfbox@T@ur
316 \newbox\nfbox@T@UL
317 \newbox\nfbox@T@UR
318 \newbox\nfbox@W@ul
319 \newbox\nfbox@W@ll
320 \newbox\nfbox@W@UL
321 \newbox\nfbox@W@LL
322 \newbox\nfbox@B@ul
323 \newbox\nfbox@B@UL

\@tempboxb Standard LATEX has \@tempboxa. We need more...
324 \ifx\@tempboxb\@undefined
325   \newbox\@tempboxb
326 \fi

\standard@output The standard LATEX output routine is saved as \standard@output. We use it for
one column pages—maybe one even wants a standard float here?
327 \edef\standard@output{\the\output}

\output Right now we use standard output on one column pages and the new one with
two columns
328 \output{\if@twocolumn\the\nf@output\else\standard@output\fi}

\nf@output Here we define our own output routine.
329 \newtoks\nf@output
330 \nf@output {%
    We define the current boxes \curr@nfbox.... Also, uc or lc mean Upper or
    Lower Current column
331   \ifodd\c@page
332     \global\let\curr@nfbox@S@ul\nfbox@S@UL
333     \global\let\curr@nfbox@S@ur\nfbox@S@UR
334     \global\let\curr@nfbox@S@ll\nfbox@S@LL
335     \global\let\curr@nfbox@S@lr\nfbox@S@LR
336     \global\let\curr@nfbox@T@ul\nfbox@T@UL
337     \global\let\curr@nfbox@T@ur\nfbox@T@UR
338     \global\let\curr@nfbox@W@ul\nfbox@W@UL
339     \global\let\curr@nfbox@W@ll\nfbox@W@LL
340     \global\let\curr@nfbox@B@ul\nfbox@B@UL
341   \else
342     \global\let\curr@nfbox@S@ul\nfbox@S@ul
343     \global\let\curr@nfbox@S@ur\nfbox@S@ur
344     \global\let\curr@nfbox@S@ll\nfbox@S@ll
345     \global\let\curr@nfbox@S@lr\nfbox@S@lr
346     \global\let\curr@nfbox@T@ul\nfbox@T@ul
347     \global\let\curr@nfbox@T@ur\nfbox@T@ur
348     \global\let\curr@nfbox@W@ul\nfbox@W@ul
349     \global\let\curr@nfbox@W@ll\nfbox@W@ll
350     \global\let\curr@nfbox@B@ul\nfbox@B@ul

```

```

351 \fi
352 \if@firstcolumn
353   \global\let\curr@nfbox@S@uc\curr@nfbox@S@ul
354   \global\let\curr@nfbox@S@lc\curr@nfbox@S@ll
355   \global\let\curr@nfbox@T@uc\curr@nfbox@T@ul
356 \else
357   \global\let\curr@nfbox@S@uc\curr@nfbox@S@ur
358   \global\let\curr@nfbox@S@lc\curr@nfbox@S@lr
359   \global\let\curr@nfbox@T@uc\curr@nfbox@T@ur
360 \fi
361 \let \par \@@par
362 %
363 % There are several possibilities when we start the output routine for
364 % a single column in a two-column layout.
365 % \begin{enumerate}
366 % \item Wide or big non-floats completely cover the page. In this
367 % case we do not need to create columns, and directly go to the
368 % output.
369 % \item The columnnd is occupied by tall or single nonfloats. We make
370 % a column of nonfloats and send it further.
371 % \item There is room for text on the page, but its height
372 % (\cs{colroom}) is different from the one known to the page builder
373 % (\cs{vsize}). In this case we change \cs{vsize} and return.
374 % \item The room for text is exactly \cs{vsize}. In this case we form
375 % a column and return.
376 % \end{enumerate}
377 % \begin{macrocode}
378 \global\@colht=\textheight
379 \ifdim\ht\curr@nfbox@B@ul>0.5\baselineskip
380   \global\advance\@colht by -\textheight
381 \fi
382 \ifdim\ht\curr@nfbox@W@ul>0.5\baselineskip
383   \global\advance\@colht by -0.5\textheight
384 \fi
385 \ifdim\ht\curr@nfbox@W@ll>0.5\baselineskip
386   \global\advance\@colht by -0.5\textheight
387 \fi
388 \ifdim\@colht < \baselineskip
389   \nf@output@widepage
390 \else
391   \nf@makecol
392 \fi
393 }

```

\nf@output@widepage The macro \nf@output@widepage outputs a page completely filled by wide pictures.

```

394 \def\nf@output@widepage{%
395   \if@firstcolumn\else
396     \ClassError{faosyb}{Wide or big nonfloats defined too late. Move

```

```

397     them up}{I encountered Big or Wide floats when I already made the
398     first column. Please move them up}
399   \fi
400   \ifdim\ht\curr@nfbox@B@ul>0.5\baselineskip
401     \global\setbox\@outputbox\vsplit\curr@nfbox@B@ul to \textheight
402   \else
403     \setbox\@tempboxa\vsplit\curr@nfbox@W@ul to 0.5\textheight
404     \setbox\@tempboxb\vsplit\curr@nfbox@W@ll to 0.5\textheight
405     \setbox\@outputbox\vbox\bgroup
406       \box\@tempboxa
407       \nointerlineskip
408       \box\@tempboxb
409     \egroup
410   \fi
411   \global\size\textheight
412   \global\@colht\textheight
413   \@outputpage
414 }

```

`\nf@makecol` This macro tries to make one column of text. If successful, it puts first column into temporary storage, and outputs the page when or if the second column is ready.

When we start `\nf@makecol`, `\@colht` already reflects possible wide nonfloats. This to get `\@colroom`, we need to take into account only the narrow ones

```

415 \def\nf@makecol{%
416   \global\@colroom\@colht
417   \ifdim\ht\curr@nfbox@T@uc>0.5\baselineskip
418     \global\@colroom=0pt
419   \fi
420   \ifdim\ht\curr@nfbox@S@uc>0.5\baselineskip
421     \global\advance\@colroom by -0.5\textheight
422   \fi
423   \ifdim\ht\curr@nfbox@S@lc>0.5\baselineskip
424     \global\advance\@colroom by -0.5\textheight
425   \fi

```

Now there could be two cases. If `\@colroom` is small, we fill the column with the non-floats only. Otherwise we have a “mixed” column with both text and nonfloats.

```

426   \ifdim\@colroom<0.5\baselineskip
427     \nf@makenfcol
428     \unvbox\@cclv
429   \else
430     \nf@makemixedcol
431   \fi}

```

`\nf@makenfcol` This macro outputs a column with only non-floats. If it is called, we already know that the narrow non-floats would fill the column, so we do not do any additional checks.

```

432 \def\nf@makenfcol{%
433   \ifdim\@colht>0.9\textheight % one tall or two squares
434     \ifdim\ht\curr@nfbox@T@uc>0.5\baselineskip
435       \setbox\@outputbox\vbox\bgroup
436       \boxmaxdepth \@maxdepth
437       \vsplit \@curr@nfbox@T@uc to \textheight
438       \egroup
439     \else
440       \setbox\@tempboxa\vbox\bgroup
441       \boxmaxdepth \@maxdepth
442       \vsplit\curr@nfbox@S@uc to 0.5\textheight
443       \egroup
444       \setbox\@tempboxb\vbox\bgroup
445       \boxmaxdepth \@maxdepth
446       \vsplit\curr@nfbox@S@lc to 0.5\textheight
447       \egroup
448       \setbox\@outputbox\vbox\bgroup
449       \boxmaxdepth \@maxdepth
450       \unvbox\@tempboxa
451       \nointerlineskip
452       \unvbox\@tempboxb
453     \egroup
454   \fi
455 \else % one square
456   \ifdim\ht\curr@nfbox@S@uc>0.49\textheight
457     \setbox\@outputbox\vsplit \curr@nfbox@S@uc to 0.5\textheight
458   \else
459     \setbox\@outputbox\vsplit \curr@nfbox@S@lc to 0.5\textheight
460   \fi
461 \fi
462 \nf@opcol}

```

`\nf@makemixedcol` This macro is used when we have a mix of text with nonfloats (or possibly just text).

We check whether the page builder has the right idea about the text size; if not, we return from the output routine

```

463 \def\nf@makemixedcol{%
464   \ifdim\@colroom=\vsize
465     \nf@makemixedcol@
466   \else
467     \global\vsize=\@colroom
468     \unvbox\@cclv
469   \fi}

```

`\nf@makmixedcol@` And now the real work of `\nf@makemixedcol@`

```

470 \def\nf@makemixedcol@{%
471   \ifvoid\footins
472     \setbox\@outputbox \box\@cclv
473   \else

```

```

474 \setbox\@outputbox \vbox {%
475 \boxmaxdepth \@maxdepth
476 \box \@cclv
477 \vskip \skip\footins
478 \color@begingroup
479 \normalcolor
480 \footnoterule
481 \unvbox \footins
482 \color@endgroup
483 }%
484 \fi
485 \ifdim\ht\curr@nfbox@S@uc>0.49\textheight
486 \setbox\@tempboxa\vsplit\curr@nfbox@S@uc to 0.5\textheight
487 \setbox\@outputbox \vbox
488 \bgroup
489 \box\@tempboxa
490 \nointerlineskip
491 \box\@outputbox
492 \egroup
493 \fi
494 \ifdim\ht\curr@nfbox@S@lc>0.49\textheight
495 \setbox\@tempboxa\vsplit\curr@nfbox@S@lc to 0.5\textheight
496 \setbox\@outputbox \vbox
497 \bgroup
498 \box\@outputbox
499 \nointerlineskip
500 \box\@tempboxa
501 \egroup
502 \fi
503 \nf@opcol}

```

\nf@opcol This is like the standard L^AT_EX \@outputdblcol, but with the treatment of wide nonfloats.

```

504 \def\nf@opcol{%
505 \if@firstcolumn
506 \global\@firstcolumnfalse
507 \global\setbox\@leftcolumn\box\@outputbox
508 \else
509 \global\@firstcolumntrue
510 \ifdim\ht\curr@nfbox@W@ul>0.5\baselineskip
511 \setbox\@tempboxa\vsplit \curr@nfbox@W@ul to 0.5\textheight
512 \else
513 \setbox\@tempboxb\box\@tempboxa
514 \fi
515 \setbox\@outputbox \vbox\bgroup
516 \box\@tempboxa
517 \nointerlineskip
518 \hb@xt@\textwidth {%
519 \hb@xt@\columnwidth {%
520 \box\@leftcolumn \hss}%

```



```

521      \hfil
522      {\normalcolor\vrule \@width\columnseprule}%
523      \hfil
524      \hb@xt@\columnwidth {%
525        \box\@outputbox \hss}%
526    }%
527  \egroup
528  \ifdim\ht\curr@nfbox@W@ll>0.5\baselineskip
529    \setbox\@tempboxa\vsplit \curr@nfbox@W@ll to 0.5\textheight
530    \setbox\@ouputbox\ vbox\bgroup
531      \box\@outputpage
532      \nointerlineskip
533      \box\@tempboxa
534    \egroup
535  \fi
536  \@outputpage
537  \global\vsizel\textheight
538  \global\@colht\textheight
539  \global\@colroom\textheight
540  \fi}

```

`\standard@clearpage` The usual `\clearpage` flushes the floats. We keep it in `\standard@clearpage`

```

541 \let\standard@clearpage\clearpage

```

`\clearpage` Now we can define `\clearpage` to take care of the mode:

```

542 \def\clearpage{%
543   \if@twocolumn
544     \nf@clearpage
545   \else
546     \standard@clearpage
547 \fi}

```

`\nf@totalheight` The total height of all non-floats

```

548 \def\nf@totalheight{\dimexpr(
549   \ht\nfbox@S@UL+
550   \ht\nfbox@S@UR+
551   \ht\nfbox@S@LL+
552   \ht\nfbox@S@LR+
553   \ht\nfbox@T@UL+
554   \ht\nfbox@T@UR+
555   \ht\nfbox@W@UL+
556   \ht\nfbox@W@LL+
557   \ht\nfbox@B@UL+
558   \ht\nfbox@S@ul+
559   \ht\nfbox@S@ur+
560   \ht\nfbox@S@ll+
561   \ht\nfbox@S@lr+
562   \ht\nfbox@T@ul+
563   \ht\nfbox@T@ur+

```

```

564 \ht\nfbox@W@ul+
565 \ht\nfbox@W@ll+
566 \ht\nfbox@B@ul)}

```

`\nf@clearpage` We keep ejecting pages until get rid of nf stuff

```

567 \def\nf@clearpage{%
568   \ifvmode
569     \ifnum \@dbltopnum =\m@ne
570       \ifdim \pagetotal <\topskip
571         \hbox{}%
572       \fi
573     \fi
574   \fi
575   \newpage
576   \write\m@ne{}%
577   \vbox{}%
578   \penalty -\@Mi
579   \if@firstcolumn\else
580     \null\vfill\newpage\fi
581   \ifdim\nf@totalheight>\baselineskip
582     \null\vfill\clearpage\fi
583 }

```

`\clearspread` This is like `\cleardoublepage`, but with the logic inverted:

```

584 \def\clearspread{\clearpage\if@twoside \ifodd\c@page
585   \hbox{}\newpage\if@twocolumn\hbox{}\newpage\fi\fi\fi}

```

We need to clear everything at the end

```

586 \AtEndDocument{\if@twocolumn
587   \ifdim\nf@totalheight>\baselineskip
588     \null\vfill\clearpage\fi
589 \fi}

```

3.12 Headers and Footers

`standardspagestyle` This is the page style for all pages.

```

590 \fancypagestyle{standardpagestyle}{%
591   fancyhf}%
592 }

```

3.13 Sectioning

`\if@mainmatter` This is used to check whether we are at main matter

```

593 \newif\if@mainmatter

```

`\frontmatter` We want Roman numbers for front matter:

```

594 \def\frontmatter{\cleardoublepage
595   \pagenumbering{roman}\onecolumn\@mainmatterfalse}

```

`\mainmatter` We want Arabic numbers for main matter:

```

596 \def\mainmatter{\cleardoublepage\pagenumbering{arabic}\onecolumn
597   \pagestyle{standardpagestyle}%
598   \@mainmattertrue}

```

`\tocdepth` Only sections and up are allowed in TOC:

```

599 \setcounter{tocdepth}{1}

```

`\secnumdepth` Only the parts are numbered in out setup:

```

600 \setcounter{secnumdepth}{-1}

```

`\thepart` And the parts are numbered using Arabic numbers:

```

601 \renewcommand \thepart {\@arabic\c@part}

```

References

- [1] Boris Veytsman. *L^AT_EX Style for FAO Yearbook*. FAO UN, 2011.
- [2] UK T_EX Users Group. UK list of T_EX frequently asked questions. <http://www.tex.ac.uk/cgi-bin/texfaq2html>, 2008.
- [3] Pavel Farář. *Support Package for Free Fonts by ParaType*, May 2011. <http://mirrors.ctan.org/fonts/paratype>.
- [4] Stephen G. Hartke. *Arev Sans for T_EX and L^AT_EX*, May 2006. <http://mirrors.ctan.org/fonts/arev>.
- [5] Uwe Kern. *Extending L^AT_EX's Color Facilities: the xcolor Package*, January 2007. <http://mirrors.ctan.org/macros/latex/contrib/xcolor>.

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in *roman* refer to the code lines where the entry is used.

Symbols	<code>\@ouputbox</code> 530	<code>\addtocontents</code> 142
<code>\%</code> 60	<code>\@outputbox</code> 401, 405,	<code>\advance</code> 118, 121, 124,
<code>\@getfirstletter</code> .	435, 448, 457,	134, 135, 380,
. 200, 201	459, 472, 474,	383, 386, 421, 424
<code>\@par</code> 361	487, 491, 496,	<code>\AtBeginDocument</code> ..
<code>\@Mi</code> 578	498, 507, 515, 525 110, 128
<code>\@arabic</code> 601	<code>\@outputpage</code>	<code>\AtBeginShipout</code> 111, 129
<code>\@bchar</code> 61, 68, 69 413, 531, 536	<code>\AtBeginShipoutUpperLeft</code>
<code>\@bgcolor</code> 3, 147	<code>\@parboxrestore</code> . . . 251 130
<code>\@bgcolor@next</code> 141	<code>\@pctchar</code> 60, 69	<code>\AtBeginShipoutUpperLeftForeground</code>
<code>\@capttype</code> 204, 268	<code>\@plus</code> . . . 87, 88, 89, 112
<code>\@cclv</code> 428, 468, 472, 476	95, 96, 97, 99, 100	<code>\AtEndDocument</code> 586
<code>\@colht</code> . . . 378, 380,	<code>\@setfontsize</code> . . . 86, 94	
383, 386, 388,	<code>\@tablebg</code> 150	B
412, 416, 433, 538	<code>\@tableheadcolor</code> 3, 147	<code>\baselineskip</code> . 379,
<code>\@colroom</code> 416,	<code>\@tempa</code> 267, 268	382, 385, 388,
418, 421, 424,	<code>\@tempboxa</code>	400, 417, 420,
426, 464, 467, 539	. 403, 406, 440,	423, 426, 434,
<code>\@curr@nfbbox@T@uc</code> . 437	450, 486, 489,	510, 528, 581, 587
<code>\@dbltopnum</code> 569	495, 500, 511,	<code>\begin</code> 260, 262,
<code>\@empty</code> . . . 165, 208, 292	513, 516, 529, 533	269, 271, 365, 377
<code>\@endfloatbox</code> 254	<code>\@tempboxb</code> 324, 404,	<code>\belowdisplayshortskip</code>
<code>\@endword</code> 202, 207	408, 444, 452, 513 89, 97
<code>\@firstcolumnfalse</code> . 506	<code>\@tempdima</code> . . . 114,	<code>\belowdisplayskip</code> .
<code>\@firstcolumntrue</code> . 509	116, 117, 118, 90, 102
<code>\@floatboxreset</code> . . . 252	119, 120, 122,	<code>\bfdefault</code> 80
<code>\@getfirstletter</code> ..	123, 124, 125,	<code>\bfseries</code> 211
. 200, 207	126, 132, 134, 136	<code>\bgroup</code> 249, 256, 283,
<code>\@gobble</code> 60, 61	<code>\@tempdimb</code>	291, 405, 435,
<code>\@gobbleword</code> .. 201, 202	. 115, 116, 117,	440, 444, 448,
<code>\@issuumodefalse</code> . . 20	119, 120, 121,	488, 497, 515, 530
<code>\@issuumodetrue</code> . . . 21	122, 123, 125,	<code>\box</code> 288, 302, 406, 408,
<code>\@ixpt</code> 94	126, 133, 135, 136	472, 476, 489,
<code>\@leftcolumn</code> .. 507, 520	<code>\@undefined</code> 324	491, 498, 500,
<code>\@listI</code> 91	<code>\@width</code> 522	507, 513, 516,
<code>\@listi</code> 91, 98	<code>\@xiipt</code> 86	520, 525, 531, 533
<code>\@mainmatterfalse</code> . 595	<code>\@</code> 61	<code>\boxmaxdepth</code> .. 436,
<code>\@mainmattertrue</code> .. 598	A	441, 445, 449, 475
<code>\@makecaption</code> 210	<code>\abovedisplayshortskip</code>	C
<code>\@maxdepth</code> . . . 436, 88, 96	<code>\c@page</code> 331, 584
441, 445, 449, 475	<code>\abovedisplayskip</code> .	<code>\c@part</code> 601
<code>\@minus</code> 87,	. . . 87, 90, 95, 102	<code>\caption</code> 5
89, 95, 97, 99, 100		

\captionfamily	285, 297,
3, 83, 84, 160, 163	298, 409, 438,
\chart	443, 447, 453,
chart (environment)	492, 501, 527, 534
\charheight	\else 50, 165, 219, 292,
240, 248, 274, 276	328, 341, 356,
\chartwidth	390, 395, 402,
181, 243, 250, 257	429, 439, 455,
\ClassError	458, 466, 473,
\ClassWarning	508, 512, 545, 579
\cleardoublepage	\end
6, 594, 596	265,
\clearpage	266, 278, 279, 376
542, 582, 584, 588	\endcsname 188, 189,
\clearspread	192, 193, 195,
6, 584	196, 197, 198, 300
\color	\endnonfloat
113, 131,	199, 254
160, 163, 211,	\EndPartIntro
261, 270, 281, 293	4
\color@begingroup	environments:
478	chart
\color@block	ConceptsAndMethods
281	9
\color@endgroup	9
482	freading
\color@vbox	9
246	map
\colorlet	5
141, 142,	metadata
146, 147, 148, 150	8
\columnseprule	MetadataCollection
522	8
\columnwidth	publication
214, 519, 524	7
ConceptsAndMethods	table
(environment)	5
9	\expandafter
\cs	60, 61, 188,
372, 373, 374	189, 192, 193,
\csname	195, 197, 198, 299
188,	
189, 192, 193,	
195, 197, 198, 299	
\curr@nfbbox@B@ul	
340,	
350, 379, 400, 401	
\curr@nfbbox@S@lc	
354, 358, 423,	
446, 459, 494, 495	
\curr@nfbbox@S@ll	
334, 344, 354	
\curr@nfbbox@S@lr	
335, 345, 358	
\curr@nfbbox@S@uc	
353,	
357, 420, 442,	
456, 457, 485, 486	
\curr@nfbbox@S@ul	
332, 342, 353	
\curr@nfbbox@S@ur	
333, 343, 357	
\curr@nfbbox@T@euc	
355, 359, 417, 434	
\curr@nfbbox@T@eul	
336, 346, 355	
\curr@nfbbox@T@eur	
337, 347, 359	
\curr@nfbbox@W@ell	
339, 349,	
385, 404, 528, 529	
\curr@nfbbox@W@eul	
338, 348,	
382, 403, 510, 511	
\currenticon	
3, 154, 165, 166	
\CurrentOption	
4, 5, 6, 7, 8, 22	
D	
\DeclareOption	
4, 5, 6, 7, 8, 11,	
12, 17, 18, 21, 22	
\DeclareRobustCommand	
81, 83	
\DeclareTextFontCommand	
82, 84	
\def	
1, 60, 61, 73,	
75, 76, 77, 98,	
140, 141, 147,	
151, 154, 187,	
192, 195, 200,	
201, 202, 203,	
204, 205, 206,	
209, 210, 223,	
224, 225, 254,	
267, 394, 415,	
432, 463, 470,	
504, 542, 548,	
567, 584, 594, 596	
\define@key	
145, 146, 150, 153	
\dimexpr	
215,	
241, 243, 244,	
282, 287, 290, 548	
\dotfill	
162, 163	
\Draftfalse	
16	
\Drafttrue	
17, 18	
\draw	
272, 273	
E	
\edef	
63, 189, 299, 327	
\egroup	
285, 297,	
298, 409, 438,	
443, 447, 453,	
492, 501, 527, 534	
\else	
50, 165, 219, 292,	
328, 341, 356,	
390, 395, 402,	
429, 439, 455,	
458, 466, 473,	
508, 512, 545, 579	
\end	
265,	
266, 278, 279, 376	
\endcsname	
188, 189,	
192, 193, 195,	
196, 197, 198, 300	
\endnonfloat	
199, 254	
\EndPartIntro	
4	
environments:	
chart	
ConceptsAndMethods	
9	
freading	
9	
map	
5	
metadata	
8	
MetadataCollection	
8	
publication	
7	
table	
5	
\expandafter	
60, 61, 188,	
189, 192, 193,	
195, 197, 198, 299	
F	
\familydefault	
79	

384, 387, 392, 399, 410, 419, 422, 425, 431, 454, 460, 461, 469, 484, 493, 502, 514, 535, 540, 547, 572, 573, 574, 580, 582, 585, 588, 589	\fill 263 \fontfamily 81, 83 \fontsize 138 \footins .. 471, 477, 481 \footnoterule 480 freading (environ- ment) 9 \frontmatter 594	\hfil 521, 523 \hhline 7 \hspace 250, 255, 257 \hskip 282, 287, 290 \hss 520, 525 \ht .. 379, 382, 385, 400, 417, 420, 423, 434, 456, 485, 494, 510, 528, 549, 550, 551, 552, 553, 554, 555, 556, 557, 558, 559, 560, 561, 562, 563, 564, 565, 566 \Huge 161, 164 \hypersetup 42, 51	\leftmargin 98 \leftmargini 98 \leftmark 164 \let 91, 197, 198, 208, 332, 333, 334, 335, 336, 337, 338, 339, 340, 342, 343, 344, 345, 346, 347, 348, 349, 350, 353, 354, 355, 357, 358, 359, 361, 541 \line 116, 117, 119, 120, 122, 123, 125, 126 \listofcharts 6 \listofmaps 6 \listoftables 6 \LoadClass 24 \long 1, 210 \lowercase 207
G	I	M	
\gdef 143, 151, 154, 209, 210, 213 \geometry 104 \global ... 208, 245, 301, 332, 333, 334, 335, 336, 337, 338, 339, 340, 342, 343, 344, 345, 346, 347, 348, 349, 350, 353, 354, 355, 357, 358, 359, 378, 380, 383, 386, 401, 411, 412, 416, 418, 421, 424, 467, 506, 507, 509, 537, 538, 539 \Gm@layoutheight 121, 135 \Gm@layouthoffset 114, 132 \Gm@layoutvoffset 115, 133 \Gm@layoutwidth 118, 124, 134	\if 216 \if@firstcolumn 352, 395, 505, 579 \if@issuemode ... 19, 38 \if@mainmatter 593 \if@twocolumn 328, 543, 585, 586 \if@twoside 584 \ifdim 379, 382, 385, 388, 400, 417, 420, 423, 426, 433, 434, 456, 464, 485, 494, 510, 528, 570, 581, 587 \ifDraft 15, 128 \ifnum 161, 569 \ifodd 331, 584 \ifprint .. 2, 9, 41, 110 \ifvmode 568 \ifvoid 471 \ifx 165, 188, 193, 226, 229, 234, 268, 292, 324 \immediate 62 \includegraphics 2, 166 \item . 366, 369, 371, 374 \itemsep 101	\m@ne 569, 576 \mainmatter 596 \MakeUppercase 212 \map 303 map (environment) 5 metadata (environ- ment) 8 MetadataCollection (environment) .. 8 \multiply 190	N \narrowfamily . 3, 81, 82 \newbox ... 185, 186, 306, 307, 308, 309, 310, 311, 312, 313, 314, 315, 316, 317, 318, 319, 320, 321, 322, 323, 325 \newcount 183 \newcounter 194 \newenvironment ... 199 \newif ... 9, 15, 19, 593
H	L		
\hb@xt@ ... 518, 519, 524 \hbox 571, 585 \headrulewidth 159	\large 211		

<code>\newlength</code> 169, 171, 172, 173, 175, 177, 179, 181, 182	<code>\nf@trianglebase</code> 179, 242, 243, 263, 264, 273, 274, 276, 282, 285, 287, 290	P <code>\p@</code> 87, 88, 89, 95, 96, 97, 99, 100, 109, 116, 117, 119, 120, 122, 123, 125, 126, 174, 176, 178, 180, 281
<code>\newnon@float</code> 187, 303, 304, 305	<code>\nf@vert@pos</code> .. 207, 216	<code>\pagenumbering</code> 595, 596
<code>\newpage</code> .. 575, 580, 585	<code>\nf@vert@sep</code> 169, 215, 218, 220	<code>\pagestyle</code> ... 168, 597
<code>\newtoks</code> 329	<code>\nf@width</code> 171, 214, 227, 235, 243, 255, 272, 276, 277, 281	<code>\pagetotal</code> 570
<code>\next@icon</code> ... 151, 154	<code>\nfbox@B@UL</code> 323, 340, 557	<code>\par</code> 254, 285, 288, 296, 297, 361
<code>\nf@bottomskip</code> 183, 218, 221, 232, 238, 244	<code>\nfbox@B@ul</code> 322, 350, 566	<code>\parindent</code> 108
<code>\nf@caption</code> 210, 213, 284	<code>\nfbox@S@LL</code> 312, 334, 551	<code>\parsep</code> 100, 101
<code>\nf@captionheight</code> . . 173, 241, 281, 283	<code>\nfbox@S@ll</code> 308, 344, 560	<code>\parskip</code> 108
<code>\nf@clearpage</code> . 544, 567	<code>\nfbox@S@LR</code> 313, 335, 552	<code>\part</code> 3
<code>\nf@contentsbox</code> 185, 245, 288	<code>\nfbox@S@lR</code> 309, 345, 561	<code>\PassOptionsToClass</code> 22
<code>\nf@currbox</code> 299, 301, 302	<code>\nfbox@S@UL</code> 310, 332, 549	<code>\PassOptionsToPackage</code> 13
<code>\nf@height</code> 172, 215, 230, 236, 241, 244, 256	<code>\nfbox@S@ul</code> 306, 342, 558	<code>\pCycle</code> 7
<code>\nf@mainbox</code> 186, 256, 302	<code>\nfbox@S@UR</code> 311, 333, 550	<code>\pDescription</code> 7
<code>\nf@makecol</code> ... 391, 415	<code>\nfbox@S@ur</code> 307, 343, 559	<code>\pdfcatalog</code> 64
<code>\nf@makemixedcol</code> 430, 463	<code>\nfbox@T@UL</code> 316, 336, 553	<code>\pdfastobj</code> 63
<code>\nf@makemixedcol@</code> 465, 470	<code>\nfbox@T@ul</code> 314, 346, 562	<code>\pdfobj</code> 62
<code>\nf@makenfcol</code> . 427, 432	<code>\nfbox@T@UR</code> 317, 337, 554	<code>\pEdition</code> 7
<code>\nf@makmixedcol@</code> .. 470	<code>\nfbox@T@ur</code> 315, 347, 563	<code>\penalty</code> 302, 578
<code>\nf@margin</code> 177, 242, 243, 275, 277, 282, 286, 287, 289, 290	<code>\nfbox@W@LL</code> 321, 339, 556	<code>\pgflinewidth</code> . 276, 277
<code>\nf@opcol</code> . 462, 503, 504	<code>\nfbox@W@ll</code> 319, 349, 565	<code>\printfalse</code> 10, 11
<code>\nf@output</code> ... 328, 329	<code>\nfbox@W@UL</code> 320, 338, 555	<code>\printtrue</code> 12
<code>\nf@output@widepage</code> 389, 394	<code>\nfbox@W@ul</code> 318, 348, 564	<code>\ProcessOptions</code> ... 23
<code>\nf@placement</code> . 206, 300	<code>\noindent</code> 259, 287, 293, 297	<code>\PTSans@scale</code> 75
<code>\nf@size</code> 205, 226, 229, 234, 299	<code>\nointerlineskip</code> 285, 288, 302, 407, 451, 490, 499, 517, 532	<code>\PTSansCaption@scale</code> 77
<code>\nf@source</code> 208, 209, 292, 297	<code>\non@float</code> ... 199, 203	<code>\PTSansNarrow@scale</code> 76
<code>\nf@sourceheight</code> 175, 241, 291	<code>\nonfloat@type</code> 183, 189, 190	<code>publication</code> (environ- ment) 7
<code>\nf@topskip</code> 183, 217, 220, 231, 237, 244, 258	<code>\normalcolor</code> 247, 479, 522	<code>\put</code> 116, 117, 119, 120, 122, 123, 125, 126, 136, 261, 270
<code>\nf@totalheight</code> 548, 581, 587	<code>\normalsize</code> 85, 162, 163	<code>\pWeb</code> 7
	<code>\null</code> 580, 582, 588	R
	O	<code>\raisebox</code> 166
	<code>\OBJ@CVR</code> 63, 70	<code>\refMetadata</code> 8
	<code>\onecolumn</code> ... 595, 596	<code>\relax</code> 23, 161, 184, 188, 190, 193, 197, 198, 216
	<code>\output</code> 327, 328	<code>\renewcommand</code> 78, 79, 80, 85, 93, 159, 601
	<code>\owner</code> 8	<code>\RequirePackage</code> 25, 26, 27, 29, 30,

31, 32, 33, 34, 35, 36, 37, 39, 74	\standard@output	U
\rotatebox 137 327, 328	\unvbox 428,
\rule 294, 295, 296	\standardpagestyle . 156	450, 452, 468, 481
	\standardspagestyle 590	\urlstyle 103
	\string 60, 61, 142	\usetikzlibrary . . . 28
	\subsection 3	
S		V
\savegeometry 107		\vbox . . . 248, 256, 283,
\secnumdepth 600	T	291, 302, 405,
\section 3	\table 304	435, 440, 444,
\selectcolor 3, 147	table (environment) . . 5	448, 474, 487,
\selectfont . . . 81, 83, 138	\tempB 225, 234	496, 515, 530, 577
\selecticon 3, 154	\tempT 224, 229	\vfill 284, 297,
\setbgcolor . . . 141, 145	\tempW 223, 226	298, 580, 582, 588
\setbox 245, 256, 301,	\textcaption 3, 84	\vrule 522
401, 403, 404,	\textheight 215, 230,	\vsize 411, 464, 467, 537
405, 435, 440,	236, 378, 380,	\vskip 258,
444, 448, 457,	383, 386, 401,	285, 286, 289, 477
459, 472, 474,	403, 404, 411,	\vsplit . . . 401, 403,
486, 487, 495,	412, 421, 424,	404, 437, 442,
496, 507, 511,	433, 437, 442,	446, 457, 459,
513, 515, 529, 530	446, 456, 457,	486, 495, 511, 529
\setcounter . . . 599, 600	459, 485, 486,	
\seticon 151	494, 495, 511,	
\setkeys 73	529, 537, 538, 539	W
\setlength	\textnarrow 3, 82	\write 576
. 108, 109, 170,	\textsubscript 9	
174, 176, 178, 180	\textwidth 227, 235, 518	X
\sfdefault 78, 79	\the . . . 63, 189, 327, 328	\xdef 207
\skip 477	\thepart . . 161, 162, 601	
\small 93	\tocdepth 599	Z
\source 6, 8, 209	\topsep 99	\z@ 88, 96, 108,
\space 69, 70, 165	\topskip 570	159, 217, 221,
\standard@clearpage	\totalheight 166	231, 232, 237, 238
. 541, 546		