

New L^AT_EX Style for FAO Yearbook *

Boris Veytsman[†]

2013/12/10, v0.2

Abstract

This package provides class for typesetting FAO Yearbook. This is a refactoring of the `faoyeabook` package

1 Introduction

The package `faoyearbook` [1] was written in 2011 for FAO Statistical Yearbook.

The package `faosyb` is a refactoring of this package. We use the lessons learned and incorporate new design requirements. We use some (actually plenty) code from the previous version, but since we do not have to be compatibility, we can correct some unfortunate decisions.

2 User Guide

The installation of the class follows the usual practice [2] for L^AT_EX packages:

1. Run `latex` on `faosyb.ins`. This will produce the L^AT_EX class `faosyb.cls`.
2. Put the file `faosyb.cls` to the place where L^AT_EX can find it (see [2] or the documentation for your T_EX system).
3. Update the database of file names. Again, see [2] or the documentation for your T_EX system for the system-specific details.
4. The file `faosyb.pdf` provides the documentation for the package (this is the file you are probably reading now).

As an alternative to items 2 and 3 you can just put the file `faosyb.cls` in the working directory where your `.tex` file is.

*©2013, Food and Agriculture Organization of the United Nations

[†]borisv@lk.net, boris@varphi.com

2.1 Invocation

To use the class, put in the preamble of your document

```
\documentclass[<options>]{faosyb}
```

If the option `web` (default) is chosen, the pages of the book have the dimensions corresponding to A4 paper. However, if the option `print` is chosen, then the pages are printed on a wider area, and crop marks are added for the trimming.

If the option `issuu` is chosen, the internal links are transformed to external in the form suitable for <http://www.issuu.com>. Note that this option probably does not make much sense unless `web` option is also chosen. However, it is still possible to select both `print` and `issuu` option if someone needs it for an obscure purpose.

The option `Draft` (note the capitalization!) leads to the the large word ‘DRAFT’ printed across the pages. The standard L^AT_EX option `draft` leads to the same result, but it also makes other changes, most notably, in the behavior of the `\includegraphics` command and warnings.

`\ifprint` It is possible to query the current mode using the macro `\ifprint`, for example

```
\ifprint
  Stuff for print version
\else
  Stuff for web version
\fi
```

Any branch of this conditional may be empty, so web-only stuff can be coded as

```
\ifprint\else Web-only stuff\fi
```

`\includegraphics` There is a special facility for `\includegraphics` command to choose a file depending on the current mode of the package. Namely, if there is a file `image_print.pdf` visible by L^AT_EX, then the commands `\includegraphics{image}` or `\includegraphics{image.pdf}` selects the file `image_print.pdf`. In the case this file is not found, the file `image.pdf` is selected instead. Similarly in the web mode the file `image_web.pdf` will be selected first, and only if it does not exist, `image.pdf` is selected. This rule works also for commands `\includeLargeGraphics` and `\includeExtraLargeGraphics` described below.

Note that at this time there is no similar facility for the `\input` command.

2.2 Setting Parameters

`\faoset` Some parameters in the class can be set with the command `\faoset{<key=value>}`, for example

```
\faoset{bgcolor=blue}
```

Most of the parameters are explained below.

One of the important parameters is **year**. While the package at this time does not provide facilities for the title pages, it needs to know the year for the proper typesetting of footers. The command

```
\faoset{year=2013}
```

is used to provide this information.

2.3 Fonts

<pre>\narrowfamily \textnarrow \captionfamily \textcaption</pre>	<p>The class uses PT Sans fonts [3] for body text and Arev fonts [4] for math. It defines two additional families: Narrow and Caption, corresponding to the PT Sans Narrow and PT Sans Caption font. They can be selected by the declarations <code>\narrowfamily</code> and <code>\captionfamily</code> or by the commands <code>\textnarrow{<text>}</code> and <code>\textcaption{<text>}</code> following the usual L^AT_EX conventions. Note that since PT Sans does not provide math alphabet, this choice does not change the mathematical text.</p>
--	--

PT Sans Narrow may be useful for typesetting tables, for example,

```
{\scriptsize\narrowfamily
\rowcolors{4}{@bgcolor!30}{@bgcolor!20}
\input{./Tables/P1.DEM_1.tex}}
```

The choice of `\narrowfamily` is automatically done by the `tablepages` environment.

2.4 Colors and Icons for Parts

A Yearbook is separated into parts (more on this below). Each part has its own color and icon. They are set by the keys `bgcolor` and `icon` of the `\faoset` command, for example,

```
\faoset{icon=./Icons/agriculture.png}
\faoset{icon=./Icons/population}
\faoset{bgcolor=blue}
\faoset{bgcolor=green!25!yellow}
```

The parameter for the `icon` key can be any file name (with or without extension), suitable for the `\includegraphics` command. The parameter for the `bgcolor` key can be specified in any form acceptable by `xcolor` package [5].

The key `tableheadcolor` sets the color for the headers of tables defined by `H` or `P` key (see Section 2.6). Normally it is the current `@bgcolor` color, but it can be set to any required value.

<pre>\selecticon \selectcolor</pre>	<p>Note that <code>\faoset</code> command does not change the icon or background color immediately. When issued <i>before</i> <code>\part</code> command, it sets up icon and color for</p>
-------------------------------------	---

	the next part. If needed, you can manually change this using <code>\selecticon</code> and <code>\selectcolor</code> commands. In most cases you should <i>not</i> use these commands.
<code>@bgcolor</code>	After a <code>\part</code> command (or explicit <code>\selecticon</code> and <code>\selectcolor</code> command we can access the current values of the color in <code>@bgcolor</code> , <code>@tablecolor</code>
<code>@tableheadcolor</code>	colors and <code>\currenticon</code> macro.
<code>\currenticon</code>	

2.5 Sectioning

<code>\part</code>	The main division of the text are <code>\parts</code> . The command <code>\part{<title>}</code> is used for
<code>\section</code>	numbered parts, while the command <code>\part*{<title>}</code> is used for unnumbered parts.
<code>\subsection</code>	The next division are <code>\sections</code> and <code>\subsections</code> . They are never numbered.
	The style does not use <code>\chapters</code> .
<code>\EndPartIntro</code>	The sections immediately following new parts are special: they are typeset in one column and cannot have floats. The command <code>\EndPartIntro</code> switches to the “normal” sections.

2.6 Floats

One of the most important changes from the previous version of the class [1] is the treatment of floats.

In standard L^AT_EX floats “float”: they can be placed by the algorithm anywhere. The previous version made them “sticky”: the author explicitly tells T_EX where floats should be placed. However, to do so the class required the author to make explicit page breaks, which was not very convenient.

This version has a completely rewritten interface and algorithm for placing floats:

1. Like in standard L^AT_EX, authors do not normally provide page breaks—T_EX tries to make this decision for them.
2. Like in the previous version, floats are put exactly where the authors want them—no default placing and second-guessing.

Here is how it is done.

The main unit of the book is *spread*: a verso page and the corresponding recto page. Each page is divided into four quarters, upper left, upper right, lower left and lower right. We will denote them `ul`, `ur`, `ll`, `lr` for the verso page and `UL`, `UR`, `LL`, `LR` for the recto page (Figure 1). We allow four kinds of floats:

Single floats occupy exactly one quarter. They are denoted as `S`.

Tall floats occupy two quarters stacked vertically (for example, `ul` and `ll`). They are denoted as `T`.

Wide floats occupy two quarters adjacent horizontally (for example, `LL` and `LR`). They are denoted as `W`.

Big floats occupy all four quarters on a page. They are denoted as `B`.



Figure 1: A Spread

The parameters $\{\langle type \rangle\}$ and $\{\langle location \rangle\}$ are mandatory for floats, for example

```
\begin{map}{T}{ur}
...
\end{map}
\begin{chart}{S}{UL}
...
\end{chart}
```

For multiquarter floats the location is the location of the upper left corner, so Big float can use only `ul` or `UL` location.

Of course, not all combinations are valid: you cannot specify float as `{T}{ll}` or `{W}{UR}`, for example. If you use such combinations, the results may be unpredictable. Also it is not predictable what happens if you try to put overlapping floats (e.g. `{S}{UR}` and `{W}{UL}`).

There are two additional rules:

1. A verso page may have text and floats (still it is recommended that if it has text, then it should not have floats occupying the upper left corner).
2. A recto page may have *either* text **or** floats: if there are floats for this page, all text is moved to the following verso page.

`chart` There are three types of floats defined by the class:
`map`
`table` **chart** plots and other charts,
 map mapped data.
 table mini tables.

`caption` Each of these kinds of material is typeset using the corresponding environment: **chart**, **table** or **map**. Note that the caption for each of these environments *must* precede the graphical material, for example:

```

\begin{chart}{B}{UL}
  \caption{Hunger Data}
  \label{chart:hunger}
  \includegraphics{hunger.pdf}
\end{chart}

```

Note that our class redefines `table` environment!. For tables on separate pages use `longtable`.

`\chartwidth` Inside a **chart**, **map** or **table** it is useful to know the size allocated for the
`\charheight` graphics or table, for example, to be able to scale the graphics. Two lengths, `\chartwidth` and `\charheight` provide this information, so the user can say, for example,

```

\includegraphics[width=\chartwidth, height=\charheight]{theChart}

```

`\source` Inside a **chart**, **map** or **table** the macro `\source{<source>}` gives the source of the information, for example,

```

\Source{FA0, Statistical Division [FAO STAT]}

```

`\listoftables` The standard L^AT_EX has the command `\listoftables` to produce the list of
`\listofcharts` tables in the document. Our class retains this command and produces two additional commands `\listofcharts` and `\listofmaps` with the obvious meaning.
`\listofmaps`

2.7 Page Breaks

`\clearpage` Standard L^AT_EX has commands for immediate page break (e.g. `\clearpage`)
`\cleardoublepage` and for switching to the next recto page, possibly ejecting the next verso page
`\clearspread` (`\cleardoublepage`). The class provides another command `\clearspread`. It switches to the next *verso* page, possibly ejecting the next recto page (and putting there floats intended for this page, if any).

2.8 Tables

tablepages The tables at the end of a part should be typeset inside **tablepages** environment. The environment switches to the one column setup, decreases the margins and changes the font to `\narrowfamily`.

To typeset numerical items one should use `d` column identifier with the format `d{<a.b>}`, where *a* is the number of decimal in the integer part of the number, and *b* is the number of decimal digitst in the fractional part. For example, a number 12.345 corresponds to `d{2.3}`. The column headers are usually *not* numerical, so one need to use `\multicolumn` entries to typeset them. The class defines several such entries:

H produces a centered entry.

P produces an entry of a given length, for example, `P{1.5cm}`

C produces an entry of the length corresponding to the given number of numerical columns. For example, `C{2}` corresponds to a header of two numerical columns. Each column is assumed to be of the size enough to store -99.999 .

\hhline For the rules that do not span the table width `\hhline{<specification>}` command from the `hhline` package should be used. The `{<specification>}` argument of this command has many variants, but for our purposes we need only one variant: the command `-` produces a horizontal line spanning one column. The color of this line is determined by the command `\arrayrulecolor{<color>}`, issued in the last `>{<argument>}` command before the `-` specification. Therefore the command `>{\arrayrulecolor{@tableheadcolor}}-` produces a line of the color `@tableheadcolor`, which is seen as the absence of line. The command `>{\arrayrulecolor{black}}---` produces a black line spanning three columns. Thus if we have a four-column table and want a rule spanning columns 2–3, the following command should be issued:

```
\hhline{>{\arrayrulecolor{@tableheadcolor}}-% Column 1, no rule
>{\arrayrulecolor{black}}--% Columns 2 and 3, black rule
>{\arrayrulecolor{@tableheadcolor}}-% Column 4, no rule
```

The usual `*` specification may be used for repeating patterns, for example, `*{5}{-}` is equivalent to `-----`.

The vertical bar `|` specification in the `\hhline` argument means an interruption of the line. The interruption is by default a black interval, to make it the same color as the header background, use `>{\arrayrulecolor{@tableheadcolor}}|`.

The design of the tables in the current edition requires several important changes to the usual tables:

1. There should be no `\toprule` at the beginning of a table.
2. The first row header of a table must be empty and white; this is done by the command `\cellcolor{white}` in this cell.

3. `\hhline` separating rows in the header must not go through this first white cell; this is done by the `~` specification.

2.9 Publication Descriptions

`publication` FAO yearbook describes some FAO publications. These publications should be put inside the environment `publication`. The environment has one mandatory argument, which is the title of the publication, and one optional argument, which sets the file name of the publication cover. Note that the option argument, if present, must precede the mandatory one. If this argument is absent, no cover is included. Inside the environment the macros `\pDescription{<description>}`, `\pEdition{<year>}{<edition>}`, `\pWeb{<URL>}` and `\pCycle{<date>}` are used to typeset the corresponding items related to the publication. For example,

```

\pDescription
\pEdition
\pCycle
pWeb
\begin{publication}[./Plots/StateOfFoodAndAgriculture.png]{The State
of Food and Agriculture}
\pDescription{The State of Food and Agriculture, FAO's major
annual flagship publication, aims at bringing to a wider
audience balanced science-based assessments of important issues
in the field of food and agriculture. Each edition of the
report contains a comprehensive, yet easily accessible, overview
of a selected topic of major relevance for rural and
agricultural development and for global food security. This is
supplemented by a synthetic overview of the current global
agricultural situation.}
\pEdition{2010}{Livestock in the balance}
\pEdition{2011}{Women in Agriculture Closing the gender gap for
development}
\pCycle{May each year}
\pWeb{http://www.fao.org/docrep/013/i2050e/i2050e00.htm}
\end{publication}

```

Note that, as in the example, some fields may be repeated.

Two spacing parameters can be used for typesetting of publications: `publicationskip` is the amount of additional space between the publications, while `publicationparskip` is the space between the paragraphs inside the publication environment. The default values correspond to the command

```

\faoset{publicationskip=6pt plus 2pt minus 2pt,
publicationparskip=6pt plus 6pt minus 4pt}

```

2.10 Metadata

`MetadataCollection` Each chart, map or table in the book has a *source*. Sources are collected in the environment `MetadataCollection`, which consists of separate `metadata` environments. Each `metadata` environment has two obligatory arguments—the name of

the source and the key. The key is used to identify the metadata in the charts, maps, tables and other objects. The environment may include other commands.

`\source` `\source{source}` sets the source of the data.

`\owner` `\owner{owner}` sets the owner of the data.

Note that there is no “description” command because any text which is not an argument of the commands above is considered to belong to the description of the data.

Example of the usage of these commands:

```
\begin{MetadataCollection}
\begin{metadata}{Agricultural population}{P1.DEM.FAO.POP.AGR}

Agricultural population is defined as all persons depending for
their livelihood on agriculture, hunting, fishing and forestry.
It comprises all persons economically active in agriculture as
well as their non-working dependents. It is not necessary that
this referred population exclusively come from rural population.

\source{FILL ME}
\owner{FILL ME}
\end{metadata}
\end{MetadataCollection}
```

`\refMetadata` The metadata is referenced by the command `\refMetadata{key}`, for example

```
\refMetadata{P1.DEM.FAO.POP.AGR}
```

This command will be typeset as

Source: Agricultural population, page NNNN.

This command must *not* occur in the caption of the chart, map or table.

Note that the package automatically provides backreferencing: all charts, maps and tables where the metadata is referenced, are mentioned in the corresponding metadata section.

The sources of each chart, map or table can be shown in the lists of charts, tables, maps or not. The key `metadataInLists` (by default `false`) determines whether they are shown there. To make them visible, put before the lists

```
\faosetup{metadataInLists=true}
```

2.11 Concepts and Methods

`ConceptsAndMethods` The environment `ConceptsAndMethods` starts a new section “Concepts and Meth-

ods”. Concepts and methods are collected in the series of `concept` environments. Each environment has one obligatory field: the name of the concept, for example:

```
\begin{ConceptsAndMethods}
  \begin{concept}{Gross domestic product}
    Gross domestic product (GDP) is the market value of all officially
    recognized final goods and services produced within a country in a
    given period of time.
  \end{concept}
  \begin{concept}{Gross state product}
    Gross state product (GSP), or gross regional product (GRP), is a
    measurement of the economic output of a state or province (i.e.,
    of a subnational entity). It is the sum of all value added by
    industries within the state and serves as a counterpart to the
    gross domestic product (GDP).
  \end{concept}
\end{ConceptsAndMethods}
```

2.12 Further Reading

`freading` The special environment `freading` is used for the “further reading” sections of the book. It starts the text from the new page and changes some defaults.

2.13 Subscripts in Text

`\textsubscript` The standard \LaTeX defines `\textsuperscript`. The class adds a similar `\textsubscript` command.

3 Implementation

3.1 Options

`\faoyearbook@size@warning` The font-changing options are not used in our setup, so we just produce a warning:

```
1 \long\def\faoyearbook@size@warning#1{%
2   \ClassWarning{faoyearbook}{Size-changing option #1 will not be
3     honored}}%
4 \DeclareOption{8pt}{\faoyearbook@size@warning{\CurrentOption}}%
5 \DeclareOption{9pt}{\faoyearbook@size@warning{\CurrentOption}}%
6 \DeclareOption{10pt}{\faoyearbook@size@warning{\CurrentOption}}%
7 \DeclareOption{11pt}{\faoyearbook@size@warning{\CurrentOption}}%
8 \DeclareOption{12pt}{\faoyearbook@size@warning{\CurrentOption}}%
```

`\ifprint` We have a flag which shows whether we are in Web or print mode

```
9 \newif\ifprint
10 \printfalse
11 \DeclareOption{web}{\printfalse}
12 \DeclareOption{print}{\printtrue}
13 \PassOptionsToPackage{papersize={230mm,317mm},layout=a4paper,
14   layoutoffset=1cm,layoutvoffset=1cm,twoside}{geometry}}
```

`\ifDraft` If we are in ‘Draft’ or ‘draft mode’, we print a word ‘draft’ across the page:

```
15 \newif\ifDraft
16 \Draftfalse
17 \DeclareOption{Draft}{\Drafttrue}
18 \DeclareOption{draft}{\Drafttrue}
```

`\if@issuemode` Whether we need issue-style links

```
19 \newif\if@issuemode
20 \@issuemodefalse
21 \DeclareOption{issuu}{\@issuodemtrue}
```

All other options are just sent to the main class:

```
22 \DeclareOption*{\PassOptionsToClass{\CurrentOption}{report}}
23 \ProcessOptions\relax
```

3.2 Loading Class and Packages

We start with the base class and some packages

```
24 \LoadClass[10pt,twoside,twocolumn]{report}
25 \RequirePackage{graphicx,xkeyval}
26 \RequirePackage[table,cm]{xcolor}
27 \RequirePackage{tikz,geometry,dcolumn}
28 \usetikzlibrary{calc}
29 \RequirePackage{fancyhdr}
30 \RequirePackage{lscape,longtable,siunitx,booktabs}
31 \RequirePackage{multicol,atbegshi,picture,hhline,afterpage}
32 \RequirePackage[T1]{fontenc}
```

```

33 \RequirePackage[utf8x]{inputenc}
34 \RequirePackage{pdfpages}
35 \RequirePackage[authoryear]{natbib}
36 \RequirePackage[breaklinks]{hyperref}
37 \RequirePackage{bookmark}
38 \RequirePackage{adjmulticol}
39 \if@issuemode
40 \RequirePackage{issuulinks}
41 \fi

```

Options for the hyperref package are set as follows:

```

42 \ifprint
43 \hypersetup{breaklinks,colorlinks=false,pdfborder=0 0 0,
44   pdfauthor={FAO},
45   pdfsubject={Statistical Yearbook of the Food And Agricultural Organization for the United Na
46   pdftitle={Statistical Yearbook of the Food And Agricultural Organization for the United Nati
47   pdfkeywords={FAO, Food Security, Undernourishment, Sustainable agriculture},
48   pdfpagelayout=TwoColumnLeft,
49   pdfnewwindow=true
50 }
51 \else
52 \hypersetup{breaklinks,colorlinks=false,pdfborder=0 0 0,
53   pdfauthor={FAO},
54   pdfsubject={Statistical Yearbook of the Food And Agricultural Organization for the United Na
55   pdftitle={Statistical Yearbook of the Food And Agricultural Organization for the United Nati
56   pdfkeywords={FAO, Food Security, Undernourishment, Sustainable agriculture},
57   pdfpagelayout=TwoColumnRight,
58   pdfnewwindow=true
59 }
60 \fi

```

3.3 Color

We need to tell the printer that we are using CMYK color model. The following is taken from the pdfx package (the package itself is not too easy to make work).

```

61 \def\@pctchar{\expandafter\@gobble\string\%}
62 \def\@bchar{\expandafter\@gobble\string\}
63 \immediate\pdfobj stream attr{/N 4} file{FOGRA39L.icc}
64 \edef\OBJ@CVR{\the\pdfobj}
65 \pdfcatalog{/OutputIntents [ <<
66   /Type/OutputIntent
67   /S/GTS_PDFX
68   /OutputCondition (FOGRA39)
69   /OutputConditionIdentifier (FOGRA39 \@bchar(ISO Coated v2
70     300\@pctchar\space \@bchar(ECI\@bchar)\@bchar))
71   /DestOutputProfile \OBJ@CVR\space 0 R
72   /RegistryName(http://www.color.org)
73 >> ]}

```

3.4 Key-Value Interface

`\faoset` We define the family `fao` for our keys:

```
74 \def\faoset#1{\setkeys{fao}{#1}}
```

One of the important keys is `year`

```
75 \define@key{fao}{year}{\gdef\fao@year{#1}}
```

```
76 \faoset{year=20XX}
```

3.5 Fonts

We use `arev` for mathematics:

```
77 \RequirePackage{arevmath}
```

For body text we use PT Sans:

```
78 \def\PTSans@scale{0.95}
```

```
79 \def\PTSansNarrow@scale{0.95}
```

```
80 \def\PTSansCaption@scale{0.95}
```

```
81 \renewcommand{\sfdefault}{PTSans-TLF}
```

```
82 \renewcommand{\familydefault}{\sfdefault}
```

```
83 \renewcommand{\bfdefault}{b}
```

`\narrowfamily` We declare a new family, `\narrowfamily`:

```
84 \DeclareRobustCommand\narrowfamily{\fontfamily{PTSansNarrow-TLF}\selectfont}
```

`\textnarrow` And the matching `\textnarrow` command:

```
85 \DeclareTextFontCommand{\textnarrow}{\narrowfamily}
```

`\captionfamily` Same with `\captionfamily`:

```
86 \DeclareRobustCommand\captionfamily{\fontfamily{PTSansCaption-TLF}\selectfont}
```

`\textcaption` And the matching `\textcaption` command:

```
87 \DeclareTextFontCommand{\textcaption}{\captionfamily}
```

`\normalsize` The basic size is 9.6pt:

```
88 \renewcommand\normalsize{%
```

```
89   \@setfontsize\normalsize{9.6pt}{\@xiipt}%
```

```
90   \abovedisplayskip 10\p@ \@plus2\p@ \@minus5\p@
```

```
91   \abovedisplayshortskip \z@ \@plus3\p@
```

```
92   \belowdisplayshortskip 6\p@ \@plus3\p@ \@minus3\p@
```

```
93   \belowdisplayskip \abovedisplayskip
```

```
94   \let\@listi\@listI}
```

```
95 \normalsize
```

`\small` This is the small size:

```
96 \renewcommand\small{%
```

```
97   \@setfontsize\small{\@ixpt{10}}%
```

```
98   \abovedisplayskip 8.5\p@ \@plus3\p@ \@minus4\p@
```

```
99   \abovedisplayshortskip \z@ \@plus2\p@
```

```

100 \belowdisplayskip 4\p@ \@plus2\p@ \@minus2\p@
101 \def\@listi{\leftmargin\leftmargini
102         \topsep 4\p@ \@plus2\p@ \@minus2\p@
103         \parsep 2\p@ \@plus\p@ \@minus\p@
104         \itemsep \parsep}%
105 \belowdisplayskip \abovedisplayskip}

```

We use `rm` style of URL:

```

106 \urlstyle{sf}

```

3.6 Margins and Paragraphing

We use `a4paper`.

```

107 \geometry{layout=a4paper,
108   left=2cm,right=2cm,bottom=2.8cm,top=1.5cm,
109   columnsep=30pt, twoside}%
110 \savegeometry{standard}

```

```

\parindent We use not indented paragraphs with paragraph borders given by skips
\parskip 111 \setlength\parindent\z@
112 \setlength\parskip{6\p@ plus 6\p@ minus 4\p@}

```

```

\footskip We need generous foot
113 \setlength\footskip{18\p@}

```

```

\headheight We need generous headers
114 \setlength\headheight{35\p@}

```

3.7 Cropmarks

There are several packages that provide crop marks. Unfortunately they do not work for us because they put crop marks at the background. Since we have colored pages, we want crop marks to be on the foreground.

In this section we re-implement cropmarks of the `geometry` package, putting the marks on the foreground.

We postpone the code to the beginning of the document to get the proper value of the switch

```

115 \AtBeginDocument{\ifprint
116   \AtBeginShipout{%
117     \AtBeginShipoutUpperLeftForeground{%
118       \color{black}%
119       \@tempdima=\Gm@layouthoffset
120       \@tempdimb=\Gm@layoutvoffset
121       \put(\@tempdima,-\@tempdimb+6\p@){\line(0,1){50}}%
122       \put(\@tempdima-6\p@,-\@tempdimb){\line(-1,0){50}}%
123       \advance\@tempdima by \Gm@layoutwidth
124       \put(\@tempdima,-\@tempdimb+6\p@){\line(0,1){50}}%
125       \put(\@tempdima+6\p@,-\@tempdimb){\line(1,0){50}}%

```

```

126     \advance\@tempdimb by \Gm@layoutheight
127     \put(\@tempdima,-\@tempdimb-6\p@){\line(0,-1){50}}%
128     \put(\@tempdima+6\p@,-\@tempdimb){\line(1,0){50}}%
129     \advance\@tempdima by -\Gm@layoutwidth
130     \put(\@tempdima-6\p@,-\@tempdimb){\line(-1,0){50}}%
131     \put(\@tempdima,-\@tempdimb-6\p@){\line(0,-1){50}}%
132   }}\fi}

```

In draft mode we put the word ‘DRAFT’ across the page:

```

133 \AtBeginDocument{\ifDraft
134   \AtBeginShipout{%
135     \AtBeginShipoutUpperLeft{%
136       \color{black!25}%
137       \@tempdima=\Gm@layouthoffset
138       \@tempdimb=\Gm@layoutvoffset
139       \advance\@tempdima by 0.2\Gm@layoutwidth
140       \advance\@tempdimb by 0.7\Gm@layoutheight
141       \put(\@tempdima,-\@tempdimb){%
142         \rotatebox{45}{%
143           \fontsize{6cm}{6cm}\selectfont
144           DRAFT}}}}\fi}

```

3.8 Setting Colors and Icons

`\fao@color@string` This is the command that remembers the present color for TOC

```

145 \def\fao@color@string{0,0,0}

```

`@bgcolor@next` We store the next background color in `@bgcolor@next`. We store the next heading background in `@tableheadcolor@next`.

`\setbgcolor` The command `\setbgcolor` selects the next background color:

```

146 \def\setbgcolor#1{\colorlet{@bgcolor@next}[cmyk]{#1}%
147   \addtocontents{toc}{\string\colorlet{@bgcolor}[cmyk]{#1}}%
148   \gdef\fao@color@string{#1}}
149 \setbgcolor{white}

```

The key-value interface for the same command:

```

150 \define@key{fao}{bgcolor}{\setbgcolor{#1}}

```

And for separate setting of `@tableheadcolor`

```

151 \define@key{fao}{tableheadcolor}{\colorlet{@tableheadcolor}[cmyk]{#1}}

```

`@bgcolor` The current color is in the macro `@bgcolor`.

`@tableheadcolor` This command makes the actual color change:

```

\selectcolor
152 \def\selectcolor{\colorlet{@bgcolor}{@bgcolor@next}%
153   \colorlet{@tableheadcolor}{@bgcolor}}
154 \selectcolor

```

`@tablebg` The color for table pages

```

155 \define@key{fao}{tablebg}{\colorlet{@tablebg}[cmyk]{#1}}

```

`\seticon` Setting the next icon for the part
156 `\def\seticon#1{\gdef\next@icon{#1}}`
157 `\define@key{fao}{icon}{\seticon{#1}}`

`\selecticon` The actual icon change

`\currenticon` 158 `\def\selecticon{\gdef\currenticon{\next@icon}}`

3.9 Page Styles

`standardpagestyle` This is our main page style

```

159 \fancypagestyle{standardpagestyle}{%
160   \fancyhf{}%
161   \fancyhfoffset[LR]{1.8cm}%
162   \renewcommand\headrulewidth{\z@}%
163   \fancyhead[LE]{\color{@bgcolor}\captionfamily
164     \Huge\ifnum\thepart>0\relax
165     \thepart\fi\normalsize\dotfill}%
166   \fancyhead[LO]{\color{@bgcolor}\normalsize\dotfill\captionfamily
167     \Huge\leftmark
168     \ifx\currenticon\undefined\else\space
169     \raisebox{-0.25\totalheight}{%
170       \includegraphics[width=1.1cm]{\currenticon}}\fi}%
171   \fancyfoot[LE]{
172     \bgroup
173     \setlength\fbboxsep{10\p@}%
174     \color{@bgcolor}%
175     \raisebox{-\height}{\fcolorbox{@bgcolor}{@bgcolor}{\color{white}\thepage}}%
176     \normalsize\dotfill
177     \raisebox{-\height}{\textbf{FAO} Statistical Yearbook \textbf{\fao@year}}%
178     \egroup}%
179   \fancyfoot[LO]{
180     \bgroup
181     \setlength\fbboxsep{10\p@}%
182     \color{@bgcolor}%
183     \raisebox{-\height}{\rightmark}%
184     \normalsize\dotfill
185     \raisebox{-\height}{\fcolorbox{@bgcolor}{@bgcolor}{\color{white}\thepage}}%
186     \egroup}%
187 }
188 \pagestyle{standardpagestyle}

```

`partpagestyle` The page style for the parts introduction

```

189 \fancypagestyle{partpagestyle}{%
190   \fancyhf{}%
191   \fancyhead[L]{%
192     \begin{picture}(0,0)
193       \put(-14,45){\color{@bgcolor!10}%
194         \raisebox{-\height}{%
195           \rule{\dimexpr(\textwidth+4.5cm)}{\dimexpr(\textheight+4.8cm)}}}

```



```

196 \end{picture}}
197 \fancyhfoffset[LR]{1.8cm}%
198 \renewcommand\headrulewidth{\z@}%
199 \fancyfoot[LE]{
200 \bgroup
201 \setlength\fbboxsep{10\p@}%
202 \color{@bgcolor}%
203 \raisebox{-\height}{\fcolorbox{@bgcolor}{@bgcolor}{\color{white}\thepage}}%
204 \normalsize\dotfill
205 \raisebox{-\height}{\textbf{FAO} Statistical Yearbook \textbf{\fao@year}}%
206 \egroup}%
207 \fancyfoot[LO]{
208 \bgroup
209 \setlength\fbboxsep{10\p@}%
210 \color{@bgcolor}%
211 \raisebox{-\height}{\rightmark}%
212 \normalsize\dotfill
213 \raisebox{-\height}{\fcolorbox{@bgcolor}{@bgcolor}{\color{white}\thepage}}%
214 \egroup}%
215 }

```

3.10 Nonfloats

In Faoyearbook we used float package. Since we changed too much in the internals, here we just rewrite the code from scratch.

<code>\nf@vert@sep</code>	Vertical separation between the floats
	<pre> 216 \newlength\nf@vert@sep 217 \setlength\nf@vert@sep{30pt} </pre>
<code>\nf@width</code>	The width of the nonfloat
	<pre> 218 \newlength\nf@width </pre>
<code>\nf@height</code>	The height of the nonfloat
	<pre> 219 \newlength\nf@height </pre>
<code>\nf@captionheight</code>	The height reserved for the caption
	<pre> 220 \newlength\nf@captionheight 221 \setlength\nf@captionheight{32\p@} </pre>
<code>\nf@sourceheight</code>	The height reserved for the source lines
	<pre> 222 \newlength\nf@sourceheight 223 \setlength\nf@sourceheight{48\p@} </pre>
<code>\nf@margin</code>	Margin for floats
	<pre> 224 \newlength\nf@margin 225 \setlength\nf@margin{12\p@} </pre>

`\nf@trianglebase` The design requires a triangle under the caption. Here it is

```

226 \newlength\nf@trianglebase
227 \setlength\nf@trianglebase{12\p@}

```

`\chartwidth` The resulting width of a chart

```

228 \newlength\chartwidth

```

`\chartheight` The resulting width of a chart

```

229 \newlength\chartheight

```

`\nf@topskip` Top separation for a nonfloat @topskip

`\nf@bottomskip` Bottom separation for a nonfloat @bottomskip

`\nonfloat@type` The counter to keep the next type to assign

```

230 \newcount\nonfloat@type
231 \nonfloat@type=4\relax

```

`\nf@contentsbox` The box to keep the contents of the float

```

232 \newbox\nf@contentsbox

```

`\nf@mainbox` The box for the float

```

233 \newbox\nf@mainbox

```

`\newnon@float` The macro `\newnon@float` has the following arguments: TYPE, EXT, NAME, LISTNAME, for example

```

\newnon@float{map}{lom}{Map}{List of Maps}

```

It defines a nonfloat with these parameters.

```

234 \def\newnon@float#1#2#3#4{%

```

First, we need to define `\ftype@TYPE`: the type of the float. Note that tables are taken, so we need to make a special care of nonfloats that correspond to floats.

```

235 \expandafter\ifx\csname ftype@#1\endcsname\relax
236 \expandafter\edef\csname ftype@#1\endcsname{\the\nonfloat@type}%
237 \multiply\nonfloat@type by 2\relax
238 \fi

```

Now we define the extension for the floats

```

239 \expandafter\def\csname ext@#1\endcsname{#2}%

```

The macro `\fnum@TYPE` formats the line like “Figure 1”. We need to check whether the counter is defined

```

240 \expandafter\ifx\csname the#1\endcsname\relax
241 \newcounter{#1}\fi
242 \expandafter\def\csname fnum@#1\endcsname{#3~\csname
243 the#1\endcsname}%

```

Now we want to define the environment TYPE. Since it might be already defined, we first delete this definition, otherwise `\newenvironment` might throw an error

```
244 \expandafter\let\csname #1\endcsname\relax
245 \expandafter\let\csname end#1\endcsname\relax
```

And the actual definition

```
246 \newenvironment{#1}{\non@float{#1}}{\endnon@float}}
```

`\@getfirstletter` An aux macro to get a first letter of a word. Used in constructs

```
\edef\U{\@getfirstletter{AAAAA\@endword}}
```

```
247 \def\@getfirstletter#1{\@getfirstletter#1}
248 \def\@getfirstletter#1{#1\@gobbleword}
249 \def\@gobbleword#1\@endword{}
```

`\non@float` Now we are ready to define the `\non@float` macro. It has three parameters: TYPE, SIZE and PLACEMENT. `\nf@source` is the source of the float.

```
250 \def\non@float#1#2#3{
251   \def\@capttype{#1}%
252   \def\nf@size{#2}%
253   \def\nf@placement{#3}%
```

The macro `\nf@vert@pos` is either u or l

```
254 \lowercase{\xdef\nf@vert@pos{\@getfirstletter#3\@endword}}
255 \global\let\nf@source\@empty
```

Define the source command inside float

```
256 \def\source##1{\gdef\nf@source{##1}}
```

Define the caption producing command:

```
257 \long\def\@makecaption##1##2{\long\gdef\nf@caption{%
258   {\bfseries\large\color{white}
259   \MakeUppercase{##1}: ##2}}}%
260 \gdef\nf@caption{}
```

We calculate the size of the float and skips

```
261 \nf@width=\columnwidth
262 \nf@height=\dimexpr\textheight/2-\nf@vert@sep%
263 \if\nf@vert@pos u\relax
264   \nf@topskip=\z@
265   \nf@bottomskip=\nf@vert@sep
266 \else
267   \nf@topskip=\nf@vert@sep%
268   \nf@bottomskip=\z@
269 \fi
270 \def\tempW{W}%
271 \def\tempT{T}%
272 \def\tempB{B}%
273 \ifx\nf@size\tempW
274   \nf@width=\textwidth
```

```

275 \fi
276 \ifx\nf@size\tempT
277   \nf@height=\textheight
278   \nf@topskip=\z@
279   \nf@bottomskip=\z@
280 \fi
281 \ifx\nf@size\tempB
282   \nf@width=\textwidth
283   \nf@height=\textheight
284   \nf@topskip=\z@
285   \nf@bottomskip=\z@
286 \fi
287 \chartheight=
288   \dimexpr(\nf@height-\nf@captionheight-\nf@sourceheight
289     -2\nf@margin-\nf@trianglebase)%
290 \chartwidth=\dimexpr(\nf@width-2\nf@margin-0.5\nf@trianglebase)%
291 \nf@height=\dimexpr(\nf@height+\nf@topskip+\nf@bottomskip)%

```

Now we construct the main box.

```

292 \global\setbox\nf@contentsbox
293   \color@vbox
294   \normalcolor
295   \vbox to \chartheight
296   \bgroup
297   \hsize\chartwidth
298   \@parboxrestore
299   \@floatboxreset
300 }

```

\endnon@float The actual typesetting

```

301 \def\endnon@float{\@endfloatbox\par
302   \hsize=\nf@width
303   \setbox\nf@mainbox=\vbox to \nf@height\bgroup
304     \hsize=\chartwidth
305     \vskip\nf@topskip
306     \noindent
307     \begin{picture}(0,0)%
308       \put(0,0){\color{\bgcolor}%
309         \begin{tikzpicture}[baseline=(current bounding box.north)]
310           \fill (0,0) -- (\nf@trianglebase,0) --
311             (0.5\nf@trianglebase,-\nf@trianglebase) -- cycle;
312         \end{tikzpicture}}
313     \end{picture}%
314   \def\@tempa{chart}%
315   \ifx\@tempa\@capttype
316     \begin{picture}(0,0)%
317       \put(0,0){\color{\bgcolor}%
318         \begin{tikzpicture}[baseline=(current bounding box.north)]
319           \draw(0,0) -- (\nf@width,0);
320           \draw (0.5\nf@trianglebase,-2\nf@trianglebase) --

```

```

321         (0.5\nf@trianglebase,-\charheight-2\nf@trianglebase
322         -\nf@margin) --
323         (\nf@width-\pgflinewidth, -\charheight-2\nf@trianglebase
324         -\nf@margin) -- (\nf@width-\pgflinewidth, 0);
325     \end{tikzpicture}}
326 \end{picture}%
327 \fi
328 {\color{@bgcolor}\color@block{\nf@width}{\nf@captionheight}{.1\p@}}%
329 \hskip\dimexpr(\nf@margin+0.5\nf@trianglebase)%
330 \vbox to \nf@captionheight\bgroup
331 \nf@caption\vfill
332 \egroup\par\nointerlineskip\vskip\nf@trianglebase
333 \vskip\nf@margin
334 \noindent\hskip\dimexpr(\nf@margin+0.5\nf@trianglebase)%
335 \box\nf@contentsbox\par\nointerlineskip
336 \vskip\nf@margin
337 \hskip\dimexpr(\nf@margin+0.5\nf@trianglebase)%
338 \vbox to \nf@sourceheight\bgroup
339 \ifx\nf@source\@empty\else
340 \noindent{\color{@bgcolor}%
341     \rule{.2em}{.2em}~\rule{.2em}{.2em}~%
342     \rule{.2em}{.2em}~\rule{.2em}{.2em}~%
343     \rule{.2em}{.2em}\par}
344 \noindent Source: \nf@source\par\vfill\fi\egroup
345 \vfill\egroup
346 \edef\nf@currbox{\expandafter\csname nfbox@\nf@size
347     @\nf@placement\endcsname}%
348 \global\setbox\nf@currbox=
349 \vbox{\box\nf@currbox\nointerlineskip\penalty0\box\nf@mainbox}}

```

```

\map A standard nonfloat:
350 \newnon@float{map}{lom}{Map}{List of Maps}

\table Another one
351 \newnon@float{table}{lot}{Table}{List of Tables}

\chart And another one
352 \newnon@float{chart}{loc}{Chart}{List of Charts}

```

3.11 Output Routine

This is hairy because output routines are hairy...

We need several insert boxes. Naming convention: the letter for the box size and two letter code for the location. We use `\newbox` instead of `\newinsert` since we do not use associated `\count`, `\dimen` and `\skip` registers.

```

353 \newbox\nfbox@S@ul
354 \newbox\nfbox@S@ur
355 \newbox\nfbox@S@ll
356 \newbox\nfbox@S@lr

```

```

357 \newbox\nfbox@S@UL
358 \newbox\nfbox@S@UR
359 \newbox\nfbox@S@LL
360 \newbox\nfbox@S@LR
361 \newbox\nfbox@T@ul
362 \newbox\nfbox@T@ur
363 \newbox\nfbox@T@UL
364 \newbox\nfbox@T@UR
365 \newbox\nfbox@W@ul
366 \newbox\nfbox@W@ll
367 \newbox\nfbox@W@UL
368 \newbox\nfbox@W@LL
369 \newbox\nfbox@B@ul
370 \newbox\nfbox@B@UL

\@tempboxb Standard LATEX has \@tempboxa. We need more...
371 \ifx\@tempboxb\@undefined
372   \newbox\@tempboxb
373 \fi

\standard@output The standard LATEX output routine is saved as \standard@output. We use it for
one column pages—maybe one even wants a standard float here?
374 \edef\standard@output{\the\output}

\output Right now we use standard output on one column pages and the new one with
two columns
375 \output{\if@twocolumn\the\nf@output\else\standard@output\fi}

\nf@output Here we define our own output routine.
376 \newtoks\nf@output
377 \nf@output {%
    We define the current boxes \curr@nfbox.... Also, uc or lc mean Upper or
    Lower Current column
378   \ifodd\c@page
379     \global\let\curr@nfbox@S@ul\nfbox@S@UL
380     \global\let\curr@nfbox@S@ur\nfbox@S@UR
381     \global\let\curr@nfbox@S@ll\nfbox@S@LL
382     \global\let\curr@nfbox@S@lr\nfbox@S@LR
383     \global\let\curr@nfbox@T@ul\nfbox@T@UL
384     \global\let\curr@nfbox@T@ur\nfbox@T@UR
385     \global\let\curr@nfbox@W@ul\nfbox@W@UL
386     \global\let\curr@nfbox@W@ll\nfbox@W@LL
387     \global\let\curr@nfbox@B@ul\nfbox@B@UL
388   \else
389     \global\let\curr@nfbox@S@ul\nfbox@S@ul
390     \global\let\curr@nfbox@S@ur\nfbox@S@ur
391     \global\let\curr@nfbox@S@ll\nfbox@S@ll
392     \global\let\curr@nfbox@S@lr\nfbox@S@lr

```

```

393 \global\let\curr@nfbox@T@ul\nfbox@T@ul
394 \global\let\curr@nfbox@T@ur\nfbox@T@ur
395 \global\let\curr@nfbox@W@ul\nfbox@W@ul
396 \global\let\curr@nfbox@W@ll\nfbox@W@ll
397 \global\let\curr@nfbox@B@ul\nfbox@B@ul
398 \fi
399 \if@firstcolumn
400 \global\let\curr@nfbox@S@uc\curr@nfbox@S@ul
401 \global\let\curr@nfbox@S@lc\curr@nfbox@S@ll
402 \global\let\curr@nfbox@T@uc\curr@nfbox@T@ul
403 \else
404 \global\let\curr@nfbox@S@uc\curr@nfbox@S@ur
405 \global\let\curr@nfbox@S@lc\curr@nfbox@S@lr
406 \global\let\curr@nfbox@T@uc\curr@nfbox@T@ur
407 \fi
408 \let \par \@@par
409 %
410 % There are several possibilities when we start the output routine for
411 % a single column in a two-column layout.
412 % \begin{enumerate}
413 % \item Wide or big non-floats completely cover the page. In this
414 % case we do not need to create columns, and directly go to the
415 % output.
416 % \item The columnnd is occupied by tall or single nonfloats. We make
417 % a column of nonfloats and send it further.
418 % \item There is room for text on the page, but its height
419 % (\cs{@colroom}) is different from the one known to the page builder
420 % (\cs{vsize}). In this case we change \cs{vsize} and return.
421 % \item The room for text is exactly \cs{vsize}. In this case we form
422 % a column and return.
423 % \end{enumerate}
424 % \begin{macrocode}
425 \global\@colht=\textheight
426 \ifdim\ht\curr@nfbox@B@ul>0.5\baselineskip
427 \global\advance\@colht by -\textheight
428 \fi
429 \ifdim\ht\curr@nfbox@W@ul>0.5\baselineskip
430 \global\advance\@colht by -0.5\textheight
431 \fi
432 \ifdim\ht\curr@nfbox@W@ll>0.5\baselineskip
433 \global\advance\@colht by -0.5\textheight
434 \fi
435 \ifdim\@colht < \baselineskip
436 \nf@output@widepage
437 \else
438 \nf@makecol
439 \fi
440 }

```

`\nf@output@widepage` The macro `\nf@output@widepage` outputs a page completely filled by wide pic-

tures.

```

441 \def\nf@output@widepage{%
442   \if@firstcolumn\else
443   \ClassError{faosyb}{Wide or big nonfloats defined too late. Move
444     them up}{I encountered Big or Wide floats when I already made the
445     first column. Please move them up}
446   \fi
447   \ifdim\ht\curr@nfbox@B@ul>0.5\baselineskip
448     \global\setbox\@outputbox\vsplit\curr@nfbox@B@ul to \textheight
449   \else
450     \setbox\@tempboxa\vsplit\curr@nfbox@W@ul to 0.5\textheight
451     \setbox\@tempboxb\vsplit\curr@nfbox@W@ll to 0.5\textheight
452     \setbox\@outputbox\vbox\bgroup
453       \box\@tempboxa
454       \nointerlineskip
455       \box\@tempboxb
456     \egroup
457   \fi
458   \global\size\textheight
459   \global\@colht\textheight
460   \@outputpage
461 }
```

`\nf@makecol` This macro tries to make one column of text. If successful, it puts first column into temporary storage, and outputs the page when or if the second column is ready.

When we start `\nf@makecol`, `\@colht` already reflects possible wide nonfloats. This to get `\@colroom`, we need to take into account only the narrow ones

```

462 \def\nf@makecol{%
463   \global\@colroom\@colht
464   \ifdim\ht\curr@nfbox@T@uc>0.5\baselineskip
465     \global\@colroom=0pt
466   \fi
467   \ifdim\ht\curr@nfbox@S@uc>0.5\baselineskip
468     \global\advance\@colroom by -0.5\textheight
469   \fi
470   \ifdim\ht\curr@nfbox@S@lc>0.5\baselineskip
471     \global\advance\@colroom by -0.5\textheight
472   \fi
```

Now there could be two cases. If `\@colroom` is small, we fill the column with the non-floats only. Otherwise we have a “mixed” column with both text and nonfloats.

```

473   \ifdim\@colroom<0.5\baselineskip
474     \nf@makenfcol
475     \unvbox\@cclv
476   \else
477     \nf@makemixedcol
478   \fi}
```


`\nf@makenfcol` This macro outputs a column with only non-floats. If it is called, we already know that the narrow non-floats would fill the column, so we do not do any additional checks.

```

479 \def\nf@makenfcol{%
480   \ifdim\@colht>0.9\textheight % one tall or two squares
481     \ifdim\ht\curr@nfbox@T@uc>0.5\baselineskip
482       \setbox\@outputbox\vbox\bgroup
483       \boxmaxdepth \@maxdepth
484       \vsplit \curr@nfbox@T@uc to \textheight
485       \egroup
486     \else
487       \setbox\@outputbox\vbox\bgroup
488       \boxmaxdepth \@maxdepth
489       \vsplit\curr@nfbox@S@uc to 0.5\textheight
490       \nointerlineskip
491       \vsplit\curr@nfbox@S@lc to 0.5\textheight
492       \egroup
493     \fi
494   \else % one square
495     \ifdim\ht\curr@nfbox@S@uc>0.49\textheight
496       \setbox\@outputbox\vsplit \curr@nfbox@S@uc to 0.5\textheight
497     \else
498       \setbox\@outputbox\vsplit \curr@nfbox@S@lc to 0.5\textheight
499     \fi
500   \fi
501   \nf@opcol}

```

`\nf@makemixedcol` This macro is used when we have a mix of text with nonfloats (or possibly just text).

We check whether the page builder has the right idea about the text size; if not, we return from the output routine

```

502 \def\nf@makemixedcol{%
503   \ifdim\@colroom=\vsize
504     \nf@makemixedcol@
505   \else
506     \global\vsize=\@colroom
507     \unvbox\@cclv
508   \fi}

```

`\nf@makmixedcol@` And now the real work of `\nf@makemixedcol@`

```

509 \def\nf@makemixedcol@{%
510   \ifvoid\footins
511     \setbox\@outputbox \box\@cclv
512   \else
513     \setbox\@outputbox \vbox {%
514       \boxmaxdepth \@maxdepth
515       \unvbox \@cclv
516       \vskip \skip\footins
517       \color@begingroup

```

```

518         \normalcolor
519         \footnoterule
520         \unvbox \footins
521     \color@endgroup
522 }%
523 \fi
524 \ifdim\ht\curr@nfbox@S@uc>0.49\textheight
525     \setbox\@tempboxa\vsplit\curr@nfbox@S@uc to 0.5\textheight
526     \setbox\@outputbox \vbox
527         \bgroup
528         \box\@tempboxa
529         \nointerlineskip
530         \box\@outputbox
531     \egroup
532 \fi
533 \ifdim\ht\curr@nfbox@S@lc>0.49\textheight
534     \setbox\@tempboxa\vsplit\curr@nfbox@S@lc to 0.5\textheight
535     \setbox\@outputbox \vbox
536         \bgroup
537         \box\@outputbox
538         \nointerlineskip
539         \box\@tempboxa
540     \egroup
541 \fi
542 \nf@opcol}

```

\nf@opcol This is like the standard L^AT_EX \@outputdblcol, but with the treatment of wide nonfloats.

```

543 \def\nf@opcol{%
544     \if@firstcolumn
545         \global\@firstcolumnfalse
546         \global\setbox\@leftcolumn\box\@outputbox
547     \else
548         \global\@firstcolumntrue
549         \ifdim\ht\curr@nfbox@W@ul>0.5\baselineskip
550             \setbox\@tempboxa\vsplit \curr@nfbox@W@ul to 0.5\textheight
551         \else
552             \setbox\@tempboxb\box\@tempboxa
553         \fi
554         \setbox\@outputbox \vbox\bgroup
555             \box\@tempboxa
556             \nointerlineskip
557             \hb@xt@\textwidth {%
558                 \hb@xt@\columnwidth {%
559                     \box\@leftcolumn \hss}%
560             \hfil
561             {\normalcolor\vrule \@width\columnseprule}%
562             \hfil
563             \hb@xt@\columnwidth {%
564                 \box\@outputbox \hss}%

```

```

565     }%
566   \egroup
567   \ifdim\ht\curr@nfbox@W@ll>0.5\baselineskip
568     \setbox\@tempboxa\vsplit \curr@nfbox@W@ll to 0.5\textheight
569     \setbox\@outputbox\vbox\bgroup
570       \box\@outputpage
571       \nointerlineskip
572       \box\@tempboxa
573     \egroup
574   \fi
575   \@outputpage
576   \global\vsizel\textheight
577   \global\@colht\textheight
578   \global\@colroom\textheight
579 \fi}

```

`\standard@clearpage` The usual `\clearpage` flushes the floats. We keep it in `\standard@clearpage`

```

580 \let\standard@clearpage\clearpage

```

`\clearpage` Now we can define `\clearpage` to take care of the mode:

```

581 \def\clearpage{%
582   \if@twocolumn
583     \nf@clearpage
584   \else
585     \standard@clearpage
586 \fi}

```

`\nf@totalheight` The total height of all non-floats

```

587 \def\nf@totalheight{\dimexpr(
588   \ht\nfbox@S@UL+
589   \ht\nfbox@S@UR+
590   \ht\nfbox@S@LL+
591   \ht\nfbox@S@LR+
592   \ht\nfbox@T@UL+
593   \ht\nfbox@T@UR+
594   \ht\nfbox@W@UL+
595   \ht\nfbox@W@LL+
596   \ht\nfbox@B@UL+
597   \ht\nfbox@S@ul+
598   \ht\nfbox@S@ur+
599   \ht\nfbox@S@ll+
600   \ht\nfbox@S@lr+
601   \ht\nfbox@T@ul+
602   \ht\nfbox@T@ur+
603   \ht\nfbox@W@ul+
604   \ht\nfbox@W@ll+
605   \ht\nfbox@B@ul)}

```

`\nf@clearpage` We keep ejecting pages until get rid of nf stuff

```

606 \def\nf@clearpage{%
607   \ifvmode
608     \ifnum \@dbltopnum =\m@ne
609       \ifdim \pagetotal <\topskip
610         \hbox{}}%
611     \fi
612   \fi
613 \fi
614 \newpage
615 \write\m@ne{}}%
616 \vbox{}}%
617 \penalty -\@Mi
618 \if@firstcolumn\else
619 \null\vfill\newpage\fi
620 \ifdim\nf@totalheight>\baselineskip
621 \null\vfill\clearpage\fi
622 }

```

`\clearspread` This is like `\cleardoublepage`, but with the logic inverted:

```

623 \def\clearspread{\clearpage\if@twoside \ifodd\c@page
624   \hbox{}}\newpage\if@twocolumn\hbox{}}\newpage\fi\fi\fi}

```

We need to clear everything at the end

```

625 \AtEndDocument{\if@twocolumn
626   \ifdim\nf@totalheight>\baselineskip
627   \null\vfill\clearpage\fi
628 \fi}

```

3.12 Sectioning

`\if@mainmatter` This is used to check whether we are at main matter

```

629 \newif\if@mainmatter

```

`\frontmatter` We want Roman numbers for front matter:

```

630 \def\frontmatter{\cleardoublepage
631   \pagenumbering{roman}\onecolumn\@mainmatterfalse}

```

`\mainmatter` We want Arabic numbers for main matter:

```

632 \def\mainmatter{\cleardoublepage\pagenumbering{arabic}\onecolumn
633   \pagestyle{standardpagestyle}%
634   \@mainmattertrue}

```

`\tocdepth` Only sections and up are allowed in TOC:

```

635 \setcounter{tocdepth}{1}

```

`\secnumdepth` Only the parts are numbered in our setup:

```

636 \setcounter{secnumdepth}{-1}

```

`\thepart` And the parts are numbered using Arabic numbers:

```
637 \renewcommand \thepart {\@arabic\c@part}
```

`\c@fao@partnum` To draw the blobs in part color in the proper position, we need to associate them with parts. However, some parts are numbered, some are not. The macro `\fao@partnum` keeps the current part number counted continuously from the beginning to end.

```
638 \newcounter{fao@partnum}
639 \setcounter{fao@partnum}{0}
```

`\fao@currentpartnum` The current value of `\fao@partnum` used in TOC:

```
640 \def\fao@currentpartnum{0}
```

`\part` The largest partition in the book

```
641 \renewcommand\part{%
642   \clearspread
643   \selectcolor
644   \selecticon
645   \addtocontents{toc}{\string\colorlet{@bgcolor}[cmyk]{\fao@color@string}}%
646   \stepcounter{fao@partnum}%
647   \addtocontents{toc}{%
648     \string\gdef\string\fao@currentpartnum{\thefao@partnum}}%
649   \rowcolors{2}{@bgcolor!10}{}%
650   \pagestyle{partpagestyle}%
651   \if@twocolumn
652     \onecolumn
653   \fi
654   \cleardoublepage\bgroup\color{@bgcolor}%
655   \secdef\@part\@spart}
```

`\EndPartIntro` This command switches off the special formatting of part pages:

```
656 \def\EndPartIntro{\egroup
657   \twocolumn
658   \pagestyle{standardpagestyle}}
```

`iconfill` Fill a line with the current icon of increasing size. The parameters are the initial size and number of repetitions

```
659 \def\iconfill#1#2{%
660   \@tempdima=#1
661   \@tempcnta=#2
662   \hfill
663   \loop
664     \includegraphics[width=\@tempdima]{\currenticon}%
665     \@tempdima=1.44\@tempdima
666     \advance\@tempcnta by -1
667     \ifnum\@tempcnta>0\repeat\hfill}
```

`\@part` This is the actual part making macro.

```
668 \def\@part[#1]#2{%
669     \refstepcounter{part}%
670     \addcontentsline{toc}{part}{\thepart\hspace{1em}#1}%
671     \markboth{#1}{#1}%
672     {\interlinepenalty \@M
673     \iconfill{.7cm}{7}\par
674     \captionfamily
675     \fontsize{240\p@}{240\p@}\selectfont\raggedright\thepart~%
676     \parbox[b]{0.8\textwidth}{\fontsize{64\p@}{72\p@}\selectfont
677     \raggedright\null#2\par}\par\vskip120\p@
678 } \par}
```

`\sectionmark` We do not want to have uppercase sections in the footers

```
679 \def\sectionmark#1{\markright{#1}}
```

`\section` New sections start on a recto page in one column mode and on a verso page in two column mode

```
680 \renewcommand\section{\if@twocolumn\clearspread\else\cleardoublepage\fi
681   \@startsection {section}{1}{\z@}%
682                       {-3.5ex \@plus -1ex \@minus -.2ex}%
683                       {2.3ex \@plus .2ex}%
684                       {\normalfont\Large\bfseries}}
```

3.13 Tables

`\tablepages` Long tables at the end of a part

```
685 \newenvironment{tablepages}{\clearspread\if@twocolumn\onecolumn
686   \bgroup\narrowfamily
687   \def\emph{\textsl}%
688   \begin{adjmulticols}{1}{-1.3cm}{-1.3cm}\centering}%
689   {\end{adjmulticols}\egroup}
```

`\tablemph` Some styles define `\tablemph` commands. Here we supply a stub

```
690 \AtBeginDocument{\providecommand{\tablemph}[1]{\emph{#1}}}
```

We define new column types for table headers:

```
691 \newcolumnntype{d}[1]{D{.}.}{#1}}
692 \newcolumnntype{H}{>{\columncolor{@tableheadcolor}[1.01\tabcolsep][1.01\tabcolsep]}c}
```

P columnntype is much more complex. Basically we want a centered entry with a parbox of the given width inside.:

```
693 \newcolumnntype{P}[1]{>{\columncolor{@tableheadcolor}[1.01\tabcolsep][1.01\tabcolsep]}%
694   \@fao@Pentry{#1}}c<{\end@fao@Pentry}}
```

`\@fao@Pentry` Since `\parbox` needs “real” braces to delimit the argument, we use this trick. Note `\hspace{0pt}` to allow T_EX to hyphenate the first word.

```
695 \def\@fao@Pentry#1#2\end@fao@Pentry{%
696   \parbox[t]{#1}{\centering\strut\hspace{\z@}#2\strut}}
```

Same with C entry:

```
697 \newcolumnntype{C}[1]{>{\columncolor{@tableheadcolor}}[1.01\tabcolsep][1.01\tabcolsep]%
698   \@fao@Centry{#1}}c<{\end@fao@Centry}}
```

`\@fao@Centry` This macro is similar to `\@fao@Pentry`, but with different way to set the width of the `\parbox`:

```
699 \def\@fao@Centry#1#2\end@fao@Centry{%
700   \settowidth{\@tempdima}{${-99.999$}}%
701   \@tempdima=#1\@tempdima\relax
702   \parbox[t]{\@tempdima}{\centering\strut\hspace{\z@}#2\strut}}
```

`\LT@makecaption` This macro produces the caption for the long tables. We redefine it to get the tables in the way specified by the designer

```
703 \def\LT@makecaption#1#2#3{%
704   \LT@mcol\LT@cols {#{1}}{\cellcolor{white}}%
705   \rlap{\fcolorbox{white}{@tableheadcolor}{\normalsize
706     \captionfamily\large\strut
707     \textcolor{white}{#1{\MakeUppercase{#2}: }#3}}}%
708   \begin{picture}(0,0)%
709     \put(.5,-7){\color{@bgcolor}}%
710     \begin{tikzpicture}[baseline=(current bounding box.north)]
711       \fill (0,0) -- (\nf@trianglebase,0) --
712         (.5\nf@trianglebase,-\nf@trianglebase) -- cycle;
713     \end{tikzpicture}}
714   \end{picture}%
715   \raisebox{-17pt}{\strut}}}
```

3.14 The final word

```
716 \normalsize\normalfont
717 </class>
```

References

- [1] Boris Veytsman. *L^AT_EX Style for FAO Yearbook*. FAO UN, 2011.
- [2] UK T_EX Users Group. UK list of T_EX frequently asked questions. <http://www.tex.ac.uk/cgi-bin/texfaq2html>, 2008.
- [3] Pavel Farář. *Support Package for Free Fonts by ParaType*, May 2011. <http://mirrors.ctan.org/fonts/paratype>.
- [4] Stephen G. Hartke. *Arev Sans for T_EX and L^AT_EX*, May 2006. <http://mirrors.ctan.org/fonts/arev>.
- [5] Uwe Kern. *Extending L^AT_EX's Color Facilities: the xcolor Package*, January 2007. <http://mirrors.ctan.org/macros/latex/contrib/xcolor>.

Change History

v0.2	29
\@part: Changed formatting . . .		30
\EndPartIntro: Deleted \clearspread	\section: Redefined	30

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in *roman* refer to the code lines where the entry is used.

Symbols		
\% 61	\@minus .. 90, 92, 98, 100, 102, 103, 682
\@getfirstletter 247, 248	\@ouputbox 569
\@par 408	\@outputbox 448, 452, 482, 487, 496, 498, 511, 513, 526, 530, 535, 537, 546, 554, 564
\@M 672	\@outputpage 460, 570, 575
\@Mi 617	\@parboxrestore ... 298
\@arabic 637	\@part 655, <u>668</u>
\@bchar 62, 69, 70	\@pctchar 61, 70
\@bgcolor 4, <u>152</u>	\@plus 90, 91, 92, 98, 99, 100, 102, 103, 682, 683
\@bgcolor@next <u>146</u>	\@setfontsize ... 89, 97
\@cctype 251, 315	\@spart 655
\@cclv	475, 507, 511, 515	\@startsection 681
\@colht	... 425, 427, 430, 433, 435, 459, 463, 480, 577	\@tablebg <u>155</u>
\@colroom 463, 465, 468, 471, 473, 503, 506, 578	\@tableheadcolor 4, <u>152</u>
\@dbltopnum 608	\@tempa 314, 315
\@empty 255, 339	\@tempboxa ... 450, 453, 525, 528, 534, 539, 550, 552, 555, 568, 572
\@endfloatbox 301	\@tempboxb 371, 451, 455, 552
\@endword 249, 254	\@tempcnta 661, 666, 667
\@fao@Centry	.. 698, <u>699</u>	\@tempdima ... 119, 121, 122, 123, 124, 125, 127, 128, 129, 130, 131, 137, 139, 141, 660, 664, 665, 700, 701, 702
\@fao@Pentry	.. 694, <u>695</u>	\@tempdimb 120, 121, 122, 124, 125, 126, 127, 128, 130, 131, 138, 140, 141
\@firstcolumnfalse	. 545	\@undefined ... 168, 371
\@firstcolumntrue	. 548	\@width 561
\@floatboxreset	... 299	
\@getfirstletter	.. 247, 254	
\@gobble 61, 62	
\@gobbleword	.. 248, 249	
\@issuumodetfalse	.. 20	
\@issuumodetrue	... 21	
\@ixpt 97	
\@leftcolumn	.. 546, 559	
\@listI 94	
\@listi 94, 101	
\@mainmatterfalse	. 631	
\@mainmattertrue	.. 634	
\@makecaption 257	
\@maxdepth	483, 488, 514	
		\@xiipt 89
		\@ .. 62
		A
		\abovedisplayshortskip 91, 99
		\abovedisplayskip 90, 93, 98, 105
		\addcontentsline .. 670
		\addtocontents 147, 645, 647
		\advance 123, 126, 129, 139, 140, 427, 430, 433, 468, 471, 666
		\AtBeginDocument .. 115, 133, 690
		\AtBeginShipout 116, 134
		\AtBeginShipoutUpperLeft 135
		\AtBeginShipoutUpperLeftForeground 117
		\AtEndDocument 625
		B
		\baselineskip . 426, 429, 432, 435, 447, 464, 467, 470, 473, 481, 549, 567, 620, 626
		\begin 192, 307, 309, 316, 318, 412, 424, 688, 708, 710
		\belowdisplayshortskip 92, 100
		\belowdisplayskip 93, 105
		\bfdefault 83
		\bfseries 258, 684
		\bgroup 172, 180, 200, 208, 296, 303, 330, 338, 452, 482,

487, 527, 536,	\columnseprule 561	\def . . . 1, 61, 62, 74,
554, 569, 654, 686	\columnwidth	78, 79, 80, 101,
\box . . 335, 349, 453, 261, 558, 563	145, 146, 152,
455, 511, 528,	ConceptsAndMethods	156, 158, 234,
530, 537, 539,	(environment) . . 9	239, 242, 247,
546, 552, 555,	\cs 419, 420, 421	248, 249, 250,
559, 564, 570, 572	\csname 235,	251, 252, 253,
\boxmaxdepth	236, 239, 240,	256, 257, 270,
. . . . 483, 488, 514	242, 244, 245, 346	271, 272, 301,
	\curr@nfbox@B@ul 387,	314, 441, 462,
	397, 426, 447, 448	479, 502, 509,
C	\curr@nfbox@S@lc . .	543, 581, 587,
\c@fao@partnum 638	. 401, 405, 470,	606, 623, 630,
\c@page 378, 623	491, 498, 533, 534	632, 640, 656,
\c@part 637	\curr@nfbox@S@ll . .	659, 668, 679,
\caption 6 381, 391, 401	687, 695, 699, 703
\captionfamily	\curr@nfbox@S@lr . .	\define@key 75,
. . . . 3, 86, 87, 382, 392, 405	150, 151, 155, 157
163, 166, 674, 706	\curr@nfbox@S@uc 400,	\dimexpr . . 195, 262,
\cellcolor 704	404, 467, 489,	288, 290, 291,
\centering 688, 696, 702	495, 496, 524, 525	329, 334, 337, 587
\chart 352	\curr@nfbox@S@ul . .	\dotfill . . 165, 166,
chart (environment) . . 6 379, 389, 400	176, 184, 204, 212
\charheight . 6, 229,	\curr@nfbox@S@ur . .	\Draftfalse 16
287, 295, 321, 323 380, 390, 404	\Drafttrue 17, 18
\chartwidth 6,	\curr@nfbox@T@uc 402,	\draw 319, 320
228, 290, 297, 304	406, 464, 481, 484	
\ClassError 443	\curr@nfbox@T@ul . .	E
\ClassWarning 2 383, 393, 402	\edef . . 64, 236, 346, 374
\cleardoublepage 6,	\curr@nfbox@T@ur . .	\egroup 178, 186, 206,
630, 632, 654, 680 384, 394, 406	214, 332, 344,
\clearpage . . 6, 580,	\curr@nfbox@W@ll . .	345, 456, 485,
581, 621, 623, 627 386, 396,	492, 531, 540,
\clearspread 6,	432, 451, 567, 568	566, 573, 656, 689
623, 642, 680, 685	\curr@nfbox@W@ul . .	\else 51, 168,
\color 118, 385, 395,	266, 339, 375,
136, 163, 166,	429, 450, 549, 550	388, 403, 437,
174, 175, 182,	\currenticon 4,	442, 449, 476,
185, 193, 202,	158, 168, 170, 664	486, 494, 497,
203, 210, 213,	\CurrentOption	505, 512, 547,
258, 308, 317,	. . . 4, 5, 6, 7, 8, 22	551, 584, 618, 680
328, 340, 654, 709		\emph 687, 690
\color@begingroup . 517	D	\end 196, 312,
\color@block 328	\DeclareOption	313, 325, 326,
\color@endgroup . . 521	4, 5, 6, 7, 8, 11,	423, 689, 713, 714
\color@vbox 293	12, 17, 18, 21, 22	\end@fao@Centry 698, 699
\colorlet	\DeclareRobustCommand	\end@fao@Pentry 694, 695
. 146, 147, 151, 84, 86	\endcsname 235, 236,
152, 153, 155, 645	\DeclareTextFontCommand	239, 240, 242,
\columncolor 85, 87	243, 244, 245, 347
. . . . 692, 693, 697		

<code>\endnon@float</code> . 246, 301	532, 541, 553,	<code>\height</code> ... 175, 177,
<code>\EndPartIntro</code> ... 4, 656	574, 579, 586,	183, 185, 194,
environments:	611, 612, 613,	203, 205, 211, 213
<code>chart</code> 6	619, 621, 624,	<code>\hfil</code> 560, 562
<code>ConceptsAndMethods</code>	627, 628, 653, 680	<code>\hfill</code> 662, 667
..... 9	<code>\fill</code> 310, 711	<code>\hhline</code> 7
<code>freading</code> 10	<code>\fontfamily</code> 84, 86	<code>\hsize</code> 297, 302, 304
<code>map</code> 6	<code>\fontsize</code> . 143, 675, 676	<code>\hskip</code> 329, 334, 337
<code>metadata</code> 8	<code>\footins</code> .. 510, 516, 520	<code>\hspace</code> ... 670, 696, 702
<code>MetadataCollection</code>	<code>\footnoterule</code> 519	<code>\hss</code> 559, 564
..... 8	<code>\footskip</code> 113	<code>\ht</code> .. 426, 429, 432,
<code>publication</code> 8	<code>freading</code> (environ-	447, 464, 467,
<code>table</code> 6	ment) 10	470, 481, 495,
<code>tablepages</code> 7	<code>\frontmatter</code> 630	524, 533, 549,
<code>\expandafter</code>		567, 588, 589,
... 61, 62, 235,		590, 591, 592,
236, 239, 240,		593, 594, 595,
242, 244, 245, 346		596, 597, 598,
		599, 600, 601,
		602, 603, 604, 605
	G	<code>\Huge</code> 164, 167
	<code>\gdef</code> 75, 148, 156, 158,	<code>\hypersetup</code> 43, 52
	256, 257, 260, 648	
	<code>\geometry</code> 107	
	<code>\global</code> ... 255, 292,	
	348, 379, 380,	
	381, 382, 383,	
	384, 385, 386,	
	387, 389, 390,	
	391, 392, 393,	
	394, 395, 396,	
	397, 400, 401,	
	402, 404, 405,	
	406, 425, 427,	
	430, 433, 448,	
	458, 459, 463,	
	465, 468, 471,	
	506, 545, 546,	
	548, 576, 577, 578	
	<code>\Gm@layoutheight</code> ..	
 126, 140	
	<code>\Gm@layouthoffset</code> .	
 119, 137	
	<code>\Gm@layoutvoffset</code> .	
 120, 138	
	<code>\Gm@layoutwidth</code> ...	
 123, 129, 139	
	H	
	<code>\hb@xt@</code> ... 557, 558, 563	
	<code>\hbox</code> 610, 624	
	<code>\headheight</code> 114	
	<code>\headrulewidth</code> 162, 198	
		<code>\iconfill</code> . 659 , 659, 673
		<code>\if</code> 263
		<code>\if@firstcolumn</code> ...
		... 399, 442, 544, 618
		<code>\if@issuemode</code> ... 19 , 39
		<code>\if@mainmatter</code> 629
		<code>\if@twocolumn</code>
		... 375, 582, 624,
		625, 651, 680, 685
		<code>\if@twoside</code> 623
		<code>\ifdim</code> 426,
		429, 432, 435,
		447, 464, 467,
		470, 473, 480,
		481, 495, 503,
		524, 533, 549,
		567, 609, 620, 626
		<code>\ifDraft</code> 15 , 133
		<code>\ifnum</code> 164, 608, 667
		<code>\ifodd</code> 378, 623
		<code>\ifprint</code> .. 2, 9 , 42, 115
		<code>\ifvmode</code> 607
		<code>\ifvoid</code> 510
		<code>\ifx</code> 168, 235,
		240, 273, 276,
		281, 315, 339, 371

\immediate	63	N	\nf@output ...	375, <u>376</u>	
\includegraphics ..		\narrowfamily	\nf@output@widepage	436, <u>441</u>	
.....	2, 170, 664	3, <u>84</u> , 85, 686		
\interlinepenalty ..	672	\newbox ...	232, 233,	\nf@placement ..	253, 347
\item ..	413, 416, 418, 421	353, 354, 355,		\nf@size	252,
\itemsep	104	356, 357, 358,		273, 276, 281, 346	
		359, 360, 361,		\nf@source	
L		362, 363, 364,		. 255, 256, 339, 344	
\Large	684	365, 366, 367,		\nf@sourceheight ..	
\large	258, 706	368, 369, 370, 372		222, 288, 338
\leftmargin	101	\newcolumntype		\nf@topskip	
\leftmargini	101	. 691, 692, 693, 697		. <u>230</u> , 264, 267,	
\leftmark	167	\newcount	230	278, 284, 291, 305	
\let	94, 244,	\newcounter ...	241, 638	\nf@totalheight ...	
245, 255, 379,		\newenvironment	246, 685	587, 620, 626
380, 381, 382,		\newif	9, 15, 19, 629	\nf@trianglebase	226,
383, 384, 385,		\newlength	216, 218,	289, 290, 310,	
386, 387, 389,		219, 220, 222,		311, 320, 321,	
390, 391, 392,		224, 226, 228, 229		323, 329, 332,	
393, 394, 395,		\newnon@float		334, 337, 711, 712	
396, 397, 400,		. <u>234</u> , 350, 351, 352		\nf@vert@pos ..	254, 263
401, 402, 404,		\newpage ..	614, 619, 624	\nf@vert@sep	
405, 406, 408, 580		\newtoks	376	. <u>216</u> , 262, 265, 267	
\line	121,	\next@icon ...	156, 158	\nf@width	
122, 124, 125,		\nf@bottomskip <u>218</u> , 261, 274,	
127, 128, 130, 131		230, 265,	282, 290, 302,	
\listofcharts	6	268, 279, 285, 291		319, 323, 324, 328	
\listofmaps	6	\nf@caption	257, 260, 331	\nfbox@B@UL	370, 387, 596
\listoftables	6	\nf@captionheight		\nfbox@B@ul	369, 397, 605
\LoadClass	24	. <u>220</u> , 288, 328, 330		\nfbox@S@LL	359, 381, 590
\long	1, 257	\nf@clearpage ..	583, <u>606</u>	\nfbox@S@ll	355, 391, 599
\loop	663	\nf@contentsbox ...		\nfbox@S@lR	360, 382, 591
\lowercase	254	232, 292, 335	\nfbox@S@lR	356, 392, 600
\LT@cols	704	\nf@currbox	346, 348, 349	\nfbox@S@UL	357, 379, 588
\LT@makecaption ...	<u>703</u>	\nf@height		\nfbox@S@ul	353, 389, 597
\LT@mcol	704	. <u>219</u> , 262, 277,		\nfbox@S@UR	358, 380, 589
		283, 288, 291, 303		\nfbox@S@ur	354, 390, 598
M		\nf@mainbox	<u>233</u> , 303, 349	\nfbox@T@UL	363, 383, 592
\m@ne	608, 615	\nf@makecol ...	438, <u>462</u>	\nfbox@T@ul	361, 393, 601
\mainmatter	<u>632</u>	\nf@makemixedcol ..		\nfbox@T@UR	364, 384, 593
\MakeUppercase	259, 707	477, <u>502</u>	\nfbox@T@ur	362, 394, 602
\map	<u>350</u>	\nf@makemixedcol@		\nfbox@W@LL	368, 386, 595
map (environment)	6	504, 509	\nfbox@W@ll	366, 396, 604
\markboth	671	\nf@makenfcol ..	474, <u>479</u>	\nfbox@W@UL	367, 385, 594
\markright	679	\nf@makmixedcol@ ..	<u>509</u>	\nfbox@W@ul	365, 395, 603
metadata (environ-		\nf@margin		\noindent	
ment)	8	. <u>224</u> , 289, 290,		. 306, 334, 340, 344	
MetadataCollection		322, 324, 329,		\nointerlineskip ..	
(environment) ..	8	333, 334, 336, 337		332, 335,
\multiply	237	\nf@opcol ..	501, 542, 543		

349, 454, 490, 529, 538, 556, 571	\pdflastobj 64	\section 4, 680
\non@float 246, 250	\pdfobj 63	\sectionmark 679
\nonfloat@type 230, 236, 237	\pEdition 8	\selectcolor 3, 152, 643
\normalcolor 294, 518, 561	\penalty 349, 617	\selectfont 84, 86, 143, 675, 676
\normalfont 684, 716	\pgflinewidth 323, 324	\selecticon 3, 158, 644
\normalsize 88, 165, 166, 176, 184, 204, 212, 705, 716	\printfalse 10, 11	\setbgcolor 146, 150
\null 619, 621, 627, 677	\printtrue 12	\setbox 292, 303, 348, 448, 450, 451, 452, 482, 487, 496, 498, 511, 513, 525, 526, 534, 535, 546, 550, 552, 554, 568, 569
O	\ProcessOptions 23	\setcounter 635, 636, 639
\OBJ@CVR 64, 71	\providecommand 690	\seticon 156
\onecolumn 631, 632, 652, 685	\PTSans@scale 78	\setkeys 74
\output 374, 375	\PTSansCaption@scale 80	\setlength 111, 112, 113, 114, 173, 181, 201, 209, 217, 221, 223, 225, 227
\owner 9	\PTSansNarrow@scale 79	\settowidth 700
	publication (environ- ment) 8	\sfdefault 81, 82
P	\put 121, 122, 124, 125, 127, 128, 130, 131, 141, 193, 308, 317, 709	\skip 516
\p@ 90, 91, 92, 98, 99, 100, 102, 103, 112, 113, 114, 121, 122, 124, 125, 127, 128, 130, 131, 173, 181, 201, 209, 221, 223, 225, 227, 328, 675, 676, 677	\pWeb 8	\small 96
\pagenumbering 631, 632		\source 6, 9, 256
\pagestyle 188, 633, 650, 658		\space 70, 71, 168
\pagetotal 609		\standard@clearpage 580, 585
\par 301, 332, 335, 343, 344, 408, 673, 677, 678		\standard@output 374, 375
\parbox 676, 696, 702		\standardpagestyle . . 159
\parindent 111		\stepcounter 646
\parsep 103, 104		\string 61, 62, 147, 645, 648
\parskip 111		\strut 696, 702, 706, 715
\part 4, 641		\subsection 4
\partpagestyle 189		T
\PassOptionsToClass 22		\tabcolsep 692, 693, 697
\PassOptionsToPackage 13		\table 351
\pCycle 8		table (environment) . . 6
\pDescription 8		\tablemph 690
\pdfcatalog 65		\tablepages 685
	S	tablepages (environ- ment) 7
	\savegeometry 110	\tempB 272, 281
	\secdef 655	\tempT 271, 276
	\secnumdepth 636	

<code>\tempW</code>	270, 273	<code>\thefao@partnum</code> . . .	648	<code>\vfill</code>	331, 344,
<code>\textbf</code>	177, 205	<code>\thepage</code>			345, 619, 621, 627
<code>\textcaption</code>	3, 87		175, 185, 203, 213	<code>\vrule</code>	561
<code>\textcolor</code>	707	<code>\thepart</code>	164,	<code>\vsize</code>	458, 503, 506, 576
<code>\textheight</code>			165, 637, 670, 675	<code>\vskip</code>	305, 332,
	195, 262, 277,	<code>\tocdepth</code>	635		333, 336, 516, 677
	283, 425, 427,	<code>\topsep</code>	102	<code>\vsplit</code>	448, 450,
	430, 433, 448,	<code>\topskip</code>	609		451, 484, 489,
	450, 451, 458,	<code>\totalheight</code>	169		491, 496, 498,
	459, 468, 471,	<code>\twocolumn</code>	657		525, 534, 550, 568
	480, 484, 489,				
	491, 495, 496,				
	498, 524, 525,				
	533, 534, 550,				
	568, 576, 577, 578				
<code>\textnarrow</code>	3, 85				
<code>\textsl</code>	687				
<code>\textsubscript</code>	10				
<code>\textwidth</code>	195,				
	274, 282, 557, 676				
<code>\the</code>	64, 236, 374, 375				

U		W	
<code>\unvbox</code>	475, 507, 515, 520	<code>\write</code>	615
<code>\urlstyle</code>	106		
<code>\usetikzlibrary</code>	28		

V		X	
<code>\vbox</code>	295,	<code>\xdef</code>	254
	303, 330, 338,		
	349, 452, 482,		
	487, 513, 526,		
	535, 554, 569, 616		

Z	
<code>\z@</code>	91, 99, 111, 162,
	198, 264, 268,
	278, 279, 284,
	285, 681, 696, 702