LOGOS: Benchmarks for DDA Peptide Search

Filip Rumenovski

1 November 2026

Abstract

LOGOS is a proteomics search engine written in Rust with a CUDA backend. It reads Thermo RAW files directly and searches on one CPU node or one GPU. Against Sage 0.14.7 on the same node, chemistry and 22 cores, it runs closed DDA 12.2× and open search 6.6× faster on the CPU, and open search 16.6× faster on one GPU, while reporting more peptide sequences at an entrapment-measured error. At scale it searches the 79.7 GB HEK293 deposit PXD001468 in an open search in 12.13 s on one GPU, and one gut metaproteome against 111.5 million sequences in 20.3 s on an L40S (recorded on an earlier build). CPU and GPU builds produce byte-identical identifications. The record behind this report covers 216 RAW files from 11 public datasets and 172 recorded comparisons against external tools, released with it as data. Measurements were taken through 31 October 2026 on the Warrior cluster at Wayne State University; this report covers data-dependent acquisition only.

1 Across datasets

Figure 1 sets LOGOS against the strongest tool or published result available on each benchmark: Sage where Sage was run on the same files and node, the authors' deposited search where that is the reference, and CHIMERYS, a chimeric-spectrum engine, where its deposits exist. Counts are distinct sequences or PSMs at 1% FDR under one counting rule; a filled marker means LOGOS's count is the entrapment-validated one. Table 1 gives the numbers behind every bar.




Figure 1: (a) LOGOS identifications relative to the strongest comparator on 13 benchmarks across 6 public datasets, 4 instrument families and 9 search tasks. Dark bars: ahead by more than 1%; light: within 1%; hatched: behind. Filled marker: entrapment-validated LOGOS count; open: target-decoy only. (b) Wall-time speed-up over Sage; the whisker spans the three nodes measured for open search (Section 3). Rows marked GPU compare one GPU with Sage on CPU.

Table 1: Scoreboard: LOGOS against the strongest comparator on each benchmark. Status gives the date of the measurement; rows from 31 October were rerun on the current build.

Benchmark	Data	Comparator	LOGOS	Comparator	Δ	Error control	Status
LFQ human, open −100 to +500 Da	PXD028735 Q Exactive HF-X	Sage 0.14.7	35,595	30,343	**+17.3%**	entrapment 1.04% vs 0.90%	measured 2026-10-31
LFQ human, closed	PXD028735 Q Exactive HF-X	Sage 0.14.7	31,718	31,489	+0.7%	entrapment 1.24% each	measured 2026-10-30
Astral TMTpro, one file	PXD058160 Orbitrap Astral	Sage 0.14.7	7,568	7,212	**+4.9%**	entrapment 0.76% vs 1.02%	measured 2026-10-31
Astral TMTpro, 48 files	PXD058160 Orbitrap Astral	Authors' Comet + LDA	1,700,508	1,333,804	**+27.5%**	entrapment 0.997%; ahead in 48 of 48 files	recorded 2026-10-22
HLA class I, 9 alleles	MSV000084172 Orbitrap	Deposited Spectrum Mill	20,625	17,248	**+19.6%**	target-decoy; reference without matched FDR	recorded 2026-09-19
Astral HEK, 30-min gradient	PXD046453 Orbitrap Astral	CHIMERYS (recounted)	91,865	91,362	+0.6%	LOGOS entrapment 1.02%	recorded 2026-09-29
Astral HEK, 14-min gradient	PXD046453 Orbitrap Astral	CHIMERYS (recounted)	55,383	55,309	+0.1%	LOGOS entrapment 1.03%	recorded 2026-09-29
Mouse, 1 Th isolation	PXD053241 Q Exactive HF-X	CHIMERYS (recounted)	68,896	68,624	+0.4%	LOGOS entrapment 1.04%	recorded 2026-09-29
Mouse, 20 Th isolation	PXD053241 Q Exactive HF-X	CHIMERYS (recounted)	39,971	40,007	-0.1%	LOGOS entrapment 1.05%	recorded 2026-09-24
Ion trap CID, 0.4 Th	PXD053241 Orbitrap Eclipse	CHIMERYS (recounted)	21,364	20,941	**+2.0%**	LOGOS entrapment 1.00%; CHIMERYS's database	recorded 2026-09-29
LFQ human, chimeric	PXD053241 Q Exactive HF-X	CHIMERYS (recounted)	59,606	61,223	-2.6%	LOGOS entrapment 1.05%	recorded 2026-09-23
Ion trap HCD, 0.4 Th	PXD053241 Orbitrap Eclipse	CHIMERYS (recounted)	46,340	50,624	-8.5%	LOGOS entrapment 0.98%	recorded 2026-09-29
PTM: acetyl, phospho, ubiquitin	PXD053241, PXD013615 Q Exactive HF-X	CHIMERYS (recounted)	41,985	44,560	-5.8%	target-decoy	recorded 2026-09-23

Reading the scoreboard. Against Sage LOGOS reports more sequences on every dataset tested: 0.7% more in closed search at equal measured error, 4.9% more on Astral TMTpro and 17.3% more in open search, while running 12.2× to 16.6× faster. Against the authors' own searches it reports 27.5% more PSMs on a 48-file TMTpro study, ahead in all 48 files, and 19.6% more peptides on HLA immunopeptidomics. Against CHIMERYS it ties within 1% on Astral gradients of 14 and 30 minutes and on wide-window data at 1 and 20 Th, edges ahead on ion-trap CID, and trails on ion-trap HCD, PTM sets and chimeric LFQ.

2 Speed and scale

Figure 2 collects every speed comparison in the record in which LOGOS and another tool did the same work on the same input. The search rows are the Sage comparisons of Section 3. Rescoring is 11–34× faster than C++ Percolator on the same input, and the MSBooster features are 75× faster with byte-identical output. LOGOS searches a RAW file to identifications 94× faster than ThermoRawFileParser converts that file to the mzML other engines read.




Figure 2: Speed-up of LOGOS over each comparator, as the comparator's time divided by LOGOS's, on the same input and work. Search: wall time against Sage 0.14.7 on CPU on the same node, LOGOS on CPU (dark) or on one GPU (light). Rescoring and features: CPU, same PIN input; MSBooster's 58.29 s includes about 26 s of Java start-up. Whole pipeline: LOGOS's full search of one Astral file from RAW against ThermoRawFileParser converting that file alone; LOGOS's median real-time search per MS2 (narrow precursor window, CPU, 4,096 MS2 of PXD017823) against Orbiter's published 17 ms median, on different hardware.

Where no other engine has been run on the same input, Table 2 reports absolute throughput. LOGOS searches the 24-file HEK293 deposit of Chick et al. (PXD001468, 79.70 GB) in an open search in 12.13 s on one GPU, reporting 132,592 sequences at an entrapment-measured 1.03%. It searches one gut-metaproteome run against the 111.5 million sequences of ComPIL 2.0, scoring 178.9 billion candidates, in 20.26 s on an L40S as recorded on 18 September; the current build takes 65.05 s on an RTX PRO 4500 with identical identifications. It makes a real-time acquisition decision in a median 0.925 ms per MS2, against an 80 ms instrument budget.

Table 2: Throughput at scale and latency in real time. Inputs staged in RAM; GPU counts are physical devices. Rows were recorded on earlier builds before 31 October 2026 and not rerun on the current build.

Workload	Result	Identifications	Hardware	Note
HEK293 open search, PXD001468: 24 RAW, 79.70 GB, 1,121,149 MS2	12.13 s; 394 GB/min; 92,428 MS2/s	132,592 sequences, 688,428 PSMs at 1%; entrapment FDP 1.03%	1x H200 NVL, 32 EPYC 9554 cores	median of 3; RAWs in RAM
Same files, closed search	7.89 s; 606 GB/min	–	1x H200 NVL	RAWs in RAM
Same open search on a workstation GPU	20.30 s; 236 GB/min	–	1x RTX PRO 4000, 32 EPYC 9454 cores	RAWs in RAM
HEK293 cascade: every MS2 through nine layers	939,455 of 1,121,149 MS2 explained (83.8%)	entrapment FDP 0.87% overall (Ne 4,025)	1x L40S	two layers above 1% alone; without them 81.96%
ComPIL 2.0 metaproteome: one gut RAW against 111,478,540 sequences (84 GB FASTA, 64.06 G residues)	20.26 s; 178.9 billion candidates scored	38,649 PSMs, 10,326 peptides, 8,077 proteins at 1% (target-decoy)	1x L40S, 32 EPYC 9554 cores	recorded 2026-09-18, median of 2; performance settings; no entrapment arm
ComPIL 2.0, same search on the current build	65.05 s (repeats 65.05, 65.11, 64.96); same 178.9 billion candidates	identical: 38,649 PSMs, 10,326 peptides, 8,077 proteins	1x NVIDIA RTX PRO 4500 Blackwell, 32 EPYC 9454 cores	run 2026-10-30-compil2; GPU-bound: the scan is 62.9 s of the run
ComPIL 2.0, published-protocol settings	80.2% of the 7,565 published H2 peptides recovered	after I/L normalisation	Apple GPU (Metal)	separate run from the speed run
Astral TMTpro, PXD058160: 15 RAW, 39.5 GB	20.91 s; 113 GB/min	392,305 PSMs, 97,666 sequences at 1%	1x RTX PRO 4000	median of 3; one process
Real-time acquisition decision, Thermo RTS replay (PXD043660)	0.925 ms p50, 1.269 ms p99 per MS2	0 decisions changed against offline; budget 80 ms	1x RTX PRO 4500	batch 1; RAW decode excluded
Real-time decision, Astral (PXD058160), 135,711 MS2	1.983 ms p50, 3.015 ms p99	recorded MS2 gap median 24.8 ms	1x RTX PRO 4500	flat replay of the full file
Real-time open search, -100 to +500 Da, 4,096 MS2	32.7 ms p50 on GPU; 2,743 ms on CPU	–	GPU; CPU	PXD017823 replay
Replay of 24 Thermo RTS runs, causal policy	entrapment FDP 0.556% against 2.947% for Thermo's recorded triggers	more author-pass scans with fewer MS3	1x RTX PRO 4500	replay of recorded streams

The cascade asks what share of every MS2 spectrum in PXD001468 can be explained at controlled error. Each layer searches only the spectra that every earlier layer left unexplained. One learner scores the rows of all

layers, and target-decoy competition runs per spectrum across layers. The error is measured on a separate entrapment arm that runs the whole layered pipeline. Figure 3 shows the result: 939,455 of 1,121,149 spectra (83.8%) explained at an overall entrapment FDP of 0.87%.




Figure 3: The HEK293 cascade on all 24 files of PXD001468. Each bar is the share of all MS2 that a layer explains, placed after the layers before it; the label gives spectra explained and that layer's own entrapment FDP. Hatched layers run above 1% on their own (1.04–1.39%); without the two highest, Unimod offsets and missed cleavage, the cascade explains 918,865 spectra (82.0%). Of the spectra left unexplained, about half are chimeric and a third carry too little information for any engine; well-formed spectra that stay unexplained are 3.3% of the total (6-file subset).

3 Head to head with Sage on the current build

Both engines ran in the same Slurm job on the same node, interleaved with the order rotated between repeats; times are medians of three or more wall-clock measurements from input file to identifications, container start included. Sage's speed varies by a factor of 2.8 between these nodes, so every ratio is taken within one node.

Table 3: Wall time per search (seconds, median) and speed relative to Sage on the same node.

		Wall time (s)			Speed-up			
Benchmark	Node	CPU	GPU	Sage	CPU	GPU	Binary	Slurm job
Closed DDA, LFQ human	ymh4 · EPYC 9454	1.41	1.53	17.25	12.2	11.3	47068225	40931267
Open −100 to +500 Da, LFQ human	ymh4 · EPYC 9454	6.96	2.79	46.23	6.6	16.6	47068225	40928343
Open −100 to +500 Da, LFQ human	bbc1 · EPYC 9374F	7.08	–	37.79	5.3	–	47068225	40928337
Open −100 to +500 Da, LFQ human	arw3 · Gold 6326	11.36	–	106.4	9.4	–	6671172e	40928265
Astral TMTpro, one file	ymh4 · EPYC 9454	3.68	2.58	40.06	10.9	15.5	47068225	40931267

Identification counts use one rule for both engines: Sage's results are converted to the same input format and counted by the same program, the open counter `eval/count.py`, which gives exactly the engine's integers on every counted run (run `2026-11-01-eval-parity`). The entrapment arm adds a second database, equal in size and absent from the sample, to each search; every accepted hit to it is a known false discovery, and $\mathrm{FDP} = N_e(1 + 1/r)/(N_t + N_e)$, with the ratio r of entrapment to target sequence space computed from each search's own digestion (1.0606 for the LFQ human database, 0.9998 for the Astral mouse database).

Table 4: Identifications at 1% FDR on the target database alone and in the entrapment arm, at sequence and PSM level. FDP in percent.

	Target only		Entrapment arm, sequences			Entrapment arm, PSMs		
Engine	Sequences	PSMs	N_t	N_e	FDP	N_t	N_e	FDP
Closed DDA, LFQ human								
LOGOS	33,102	59,769	31,718	204	1.24	57,154	349	1.18
Sage 0.14.7	32,453	58,668	31,489	202	1.24	56,594	337	1.15
Open −100 to +500 Da, LFQ human								
LOGOS	34,130	70,886	32,086	166	1.00	65,824	353	1.04
LOGOS + LDA rescoring	–	–	35,650	203	1.10	73,449	390	1.03
LOGOS + calibration + LDA	37,178	77,433	35,595	192	1.04	73,438	379	1.00
Sage 0.14.7	31,744	73,148	30,343	141	0.90	68,848	359	1.01
Astral TMTpro, one file								
LOGOS	7,769	24,167	7,568	29	0.76	23,364	124	1.06
Sage 0.14.7	7,470	22,409	7,212	37	1.02	21,649	94	0.86

LDA rescoring alone raises the open-search error to 1.10%; with mass calibration it holds 1.04%, the configuration reported. On Astral TMTpro LOGOS reports more sequences at lower error, while at the PSM level Sage is the more conservative.




Figure 4: (a) Wall time per file when several Astral TMTpro files are searched in one run; each file's output is byte-identical to that file searched alone (jobs 40912674, 40912675, 40911945). (b) ThermoRawFileParser 2.0.0-dev converting one 2.6 GB Astral file to the mzML that Sage reads, alone and six at once (job 40913997), against LOGOS's whole search of that file from RAW.

4 Method and correctness

- **Hardware.** Warrior compute nodes at Wayne State University, shared with other tenants: ymh4 (AMD EPYC 9454, NVIDIA RTX PRO 4500 Blackwell), bbc1 (AMD EPYC 9374F), arw3 (Intel Xeon Gold 6326); 22 cores per job, inputs staged in RAM.
- **Chemistry.** LFQ human: trypsin, one missed cleavage, 7–30 residues, carbamidomethyl C, up to two oxidised M, 10 ppm precursor (open: −100 to +500 Da), 20 ppm fragments, charges 2–4, deisotoping. Astral TMTpro: TMTpro on K and the N-terminus, two missed cleavages, 7–50 residues, 50 ppm precursor, 10 ppm fragments, charges 2–6. Sage 0.14.7 release defaults with this chemistry, including its LDA rescoring and retention-time prediction.
- **Backend parity and determinism.** CPU and GPU builds produce byte-identical identification files (open search: the same hash, 583ae51be609…, on every run); the same binary, input and settings give the same output on every run, because reductions are order-independent.
- **The CPU path is the reference.** GPU kernels are tested against it, and new CPU code against brute-force implementations, mutation-checked so a broken variant fails its test.
- **Evidence.** Every number measured on the current build has a run record (`runs/`) naming the node, the binary and its SHA-256, the SHA-256 of every input, every repeat's wall time and the hash of every output count; the speed and identification tables of this report are generated from those records and a check fails the build if they differ. Inputs are pinned to their public deposits by SHA-256, the entrapment database is regenerated bit-for-bit by its generator, and the counting rule is open code with tests.

- **What LOGOS takes from Sage.** The CPU open-search preselection uses Sage's fragment-index layout (mass-sorted buckets of 8,192 peptides, fragments sorted within each); Sage's LFQ code was the design reference for LOGOS's MS1 quantification. On Astral TMTpro Sage spends 23.3 of its 39.4 s reading mzML at about four busy cores, so LOGOS's lead there comes mostly from reading RAW and preparing the database rather than the search core alone.

5 Limitations

LOGOS trails CHIMERYS on ion-trap HCD (−8.5%), on three PTM sets (−5.8% combined) and on chimeric LFQ (−2.6%), and quantifies half as many precursors as CHIMERYS on the LFQbench mixtures at equal accuracy (17,762 against 35,053; median error 0.175 against 0.177). Rows dated before 31 October come from earlier builds and are reported as recorded; several compare against a recount of the reference's deposited results rather than a fresh run. Speed ratios depend on the node, and every node was shared with other jobs. The complete record behind this report, 172 comparisons with their caveats and notebook sources, is in `reports/data/catalog.json`.

6 Scope of the record

Table 5 lists the public datasets behind the benchmark record and the tools each was compared against.

Table 5: Public datasets in the benchmark record. Rows counts the recorded measurements that cite the accession.

Accession	Dataset	Instrument	RAW	Benchmarked	Compared against	Rows
PXD001468	HEK293 proteome, Chick et al. 2015	Q Exactive	24	Open search at scale, closed search, explaining every spectrum in layers	Published counts	154
PXD058160	Astral TMTpro, four mouse tissues	Orbitrap Astral	48	TMT identification depth, speed vs Sage, multi-file throughput	Authors' Comet + LDA deposit; Sage 0.14.7	31
PXD043660 + PXD023203 + PXD017803	Thermo real-time search runs, TMT SPS-MS3	Orbitrap Eclipse and Ascend	32	Real-time acquisition decisions replayed, error rate of triggered MS3	Thermo's recorded real-time search triggers	73
PXD017823	Real-time search TMT study	Orbitrap	24	Identification depth and protein-level error	Authors' deposited passing scans	42
PXD058918	Astral TMTpro18 fractions	Orbitrap Astral	24	TMTpro18 identification depth	Authors' deposited search	9
PXD046453	Astral DDA, HEK 1 μg, 14/15/30-min gradients	Orbitrap Astral	15	Chimeric DDA+ depth on Astral 14- and 30-minute gradients	CHIMERYS (recounted)	107
PXD053241 (+ PXD023218, PXD013615)	CHIMERYS benchmark deposits: LFQ human, wide-window mouse, ion trap, PTM	Q Exactive HF-X, Orbitrap Eclipse	21	Wide-window chimeric DDA (8 widths), ion-trap HCD and CID (9), PTM sets (3), LFQ human	CHIMERYS, Sequest HT, Comet, MS-GF+, MetaMorpheus deposits	72
PXD028735	LFQbench three-species mixtures and LFQ human	Q Exactive HF-X	7	Closed and open search speed and depth vs Sage; quantification accuracy and depth	Sage 0.14.7, CHIMERYS, ProteoBench submissions	31
MSV000084172	HLA immunopeptidomics, 9 alleles	Orbitrap	18	Non-specific peptide identification	Deposited Spectrum Mill results	4
PXD022433 / MSV000082943	ComPIL 2.0 gut metaproteome	Orbitrap	1	Search against 111.5 M protein sequences	Published ProLuCID / DTASelect peptides	15
PXD012986, PXD000612	Mouse tissue; HeLa phospho	Orbitrap	2	Rescoring models	Percolator	10
Total			216			