

Website Vulnerability Scanner Report (Light)



Unlock the full capabilities of this scanner



See what the DEEP scanner can do

Perform in-depth website scanning and discover high risk vulnerabilities.

Testing areas	Light scan	Deep scan
Website fingerprinting	✓	✓
Version-based vulnerability detection	✓	✓
Common configuration issues	✓	✓
SQL injection	—	✓
Cross-Site Scripting	—	✓
Local/Remote File Inclusion	—	✓
Remote command execution	—	✓
Discovery of sensitive files	—	✓

✓ <https://scstadmin.fillipsoftware.com/>



The Light Website Scanner didn't check for critical issues like SQLi, XSS, Command Injection, XXE, etc.
[Upgrade to run Deep scans with 40+ tests](#) and detect more vulnerabilities.

Summary

Overall risk level:

Low

Risk ratings:

Critical:	0
High:	0
Medium:	0
Low:	6
Info:	3

Scan information:

Start time:	Apr 21, 2026 / 09:43:01 UTC+03
Finish time:	Apr 21, 2026 / 09:43:24 UTC+03
Scan duration:	23 sec
Tests performed:	38
Scan status:	Finished

Findings



Missing security header: X-Content-Type-Options

port 443/tcp

CONFIRMED

URL	Evidence
https://scstadmin.fillipsoftware.com/	Response headers do not include the X-Content-Type-Options HTTP security header Request / Response

▼ Details

Risk description:

The risk is that lack of this header could make possible attacks such as Cross-Site Scripting or phishing in Internet Explorer browsers.

Recommendation:

We recommend setting the X-Content-Type-Options header such as `X-Content-Type-Options: nosniff`.

References:

<https://developer.mozilla.org/en-US/docs/Web/HTTP/Headers/X-Content-Type-Options>

Classification:

CWE : [CWE-693](#)

OWASP Top 10 - 2017 : [A6 - Security Misconfiguration](#)

OWASP Top 10 - 2021 : [A5 - Security Misconfiguration](#)

OWASP Top 10 - 2025 : [A02 - Security Misconfiguration](#)

🚩 Unsafe security header: Content-Security-Policy

port 443/tcp

CONFIRMED

URL	Evidence
https://scstadmin.fillipsoftware.com/	Response headers include the HTTP Content-Security-Policy security header with the following security issues: <pre>object-src: Missing object-src allows the injection of plugins which can execute JavaScript. We recommend setting it to 'none'. script-src: script-src directive is missing. base-uri: Missing base-uri allows the injection of base tags. They can be used to set the base URL for all relative (script) URLs to an attacker controlled domain. We recommend setting it to 'none' or 'self'. default-src: The default-src directive should be set as a fall-back when other restrictions have not been specified.</pre> Request / Response

▼ Details

Risk description:

For example, if the unsafe-inline directive is present in the CSP header, the execution of inline scripts and event handlers is allowed. This can be exploited by an attacker to execute arbitrary JavaScript code in the context of the vulnerable application.

Recommendation:

Remove the unsafe values from the directives, adopt nonces or hashes for safer inclusion of inline scripts if they are needed, and explicitly define the sources from which scripts, styles, images or other resources can be loaded.

References:

https://cheatsheetseries.owasp.org/cheatsheets/Content_Security_Policy_Cheat_Sheet.html

<https://developer.mozilla.org/en-US/docs/Web/HTTP/Headers/Content-Security-Policy>

Classification:

CWE : [CWE-1021](#)

OWASP Top 10 - 2017 : [A6 - Security Misconfiguration](#)

OWASP Top 10 - 2021 : [A5 - Security Misconfiguration](#)

OWASP Top 10 - 2025 : [A02 - Security Misconfiguration](#)

🚩 Missing security header: Strict-Transport-Security

port 443/tcp

CONFIRMED

URL	Evidence
https://scstadmin.fillipsoftware.com/	Response headers do not include the HTTP Strict-Transport-Security header Request / Response

▼ Details

Risk description:

The risk is that lack of this header permits an attacker to force a victim user to initiate a clear-text HTTP connection to the server, thus opening the possibility to eavesdrop on the network traffic and extract sensitive information (e.g. session cookies).

Recommendation:

The Strict-Transport-Security HTTP header should be sent with each HTTPS response. The syntax is as follows:

```
Strict-Transport-Security: max-age=<seconds>[; includeSubDomains]
```

The parameter `max-age` gives the time frame for requirement of HTTPS in seconds and should be chosen quite high, e.g. several months. A value below 7776000 is considered as too low by this scanner check.
The flag `includeSubDomains` defines that the policy applies also for sub domains of the sender of the response.

Classification:

CWE : [CWE-693](#)

OWASP Top 10 - 2017 : [A6 - Security Misconfiguration](#)

OWASP Top 10 - 2021 : [A5 - Security Misconfiguration](#)

OWASP Top 10 - 2025 : [A02 - Security Misconfiguration](#)

Missing security header: Referrer-Policy

CONFIRMED

port 443/tcp

URL	Evidence
https://scstadmin.fillipsoftware.com/	Response headers do not include the Referrer-Policy HTTP security header as well as the <meta> tag with name 'referrer' is not present in the response. Request / Response

Details

Risk description:

The risk is that if a user visits a web page (e.g. "http://example.com/pricing/") and clicks on a link from that page going to e.g. "https://www.google.com", the browser will send to Google the full originating URL in the `Referer` header, assuming the Referrer-Policy header is not set. The originating URL could be considered sensitive information and it could be used for user tracking.

Recommendation:

The Referrer-Policy header should be configured on the server side to avoid user tracking and inadvertent information leakage. The value `no-referrer` of this header instructs the browser to omit the Referer header entirely.

References:

https://developer.mozilla.org/en-US/docs/Web/Security/Referer_header:_privacy_and_security_concerns

Classification:

CWE : [CWE-693](#)

OWASP Top 10 - 2017 : [A6 - Security Misconfiguration](#)

OWASP Top 10 - 2021 : [A5 - Security Misconfiguration](#)

OWASP Top 10 - 2025 : [A02 - Security Misconfiguration](#)

Robots.txt file found

CONFIRMED

port 443/tcp

URL
https://scstadmin.fillipsoftware.com/robots.txt

Details

Risk description:

There is no particular security risk in having a robots.txt file. However, it's important to note that adding endpoints in it should not be considered a security measure, as this file can be directly accessed and read by anyone.

Recommendation:

We recommend you to manually review the entries from robots.txt and remove the ones which lead to sensitive locations in the website (ex. administration panels, configuration files, etc).

References:

<https://www.theregister.co.uk/2015/05/19/robotstxt/>

Classification:

OWASP Top 10 - 2017 : [A6 - Security Misconfiguration](#)

OWASP Top 10 - 2021 : [A5 - Security Misconfiguration](#)

OWASP Top 10 - 2025 : [A06 - Insecure Design](#)

Server software and technology found

UNCONFIRMED ⓘ

port 443/tcp

Software / Version	Category
--------------------	----------

 HTTP/3	Miscellaneous
 LiteSpeed	Web servers
 PHP 8.2.30	Programming languages
 SweetAlert	JavaScript libraries
SweetAlert2	JavaScript libraries
 Hostinger	Hosting

Details

Risk description:

The risk is that an attacker could use this information to mount specific attacks against the identified software type and version.

Recommendation:

We recommend you to eliminate the information which permits the identification of software platform, technology, server and operating system: HTTP server headers, HTML meta information, etc.

References:

https://owasp.org/www-project-web-security-testing-guide/stable/4-Web_Application_Security_Testing/01-Information_Gathering/02-Fingerprint_Web_Server.html

Classification:

CWE : [CWE-200](#)

OWASP Top 10 - 2017 : [A6 - Security Misconfiguration](#)

OWASP Top 10 - 2021 : [A5 - Security Misconfiguration](#)

OWASP Top 10 - 2025 : [A02 - Security Misconfiguration](#)

Login Interface Found

port 443/tcp

CONFIRMED

URL	Evidence
https://scstadmin.fillipsoftware.com/	<pre><input type="text" name="username" placeholder="Username" class="w-full border rounded-xl px-4 py-2 focus:ring-2 focus:ring-primary-700"> <input id="password" type="password" name="password" placeholder="Password" class="w-full border rounded-xl px-4 py-2 pr-10 focus:ring-2 focus:ring-primary-700"> <button type="submit" class="w-full bg-primary-700 hover:bg-primary-800 text-white py-2 rounded-xl"> Access Dashboard → </button></pre> Request / Response

Details

Risk description:

The risk is that an attacker could use this interface to mount brute force attacks against known passwords and usernames combinations leaked throughout the web.

Recommendation:

Ensure each interface is not bypassable using common knowledge of the application or leaked credentials using occasional password audits.

References:

<https://pentest-tools.com/network-vulnerability-scanning/password-auditor>

<http://capec.mitre.org/data/definitions/16.html>

Classification:

CWE : [CWE-287](#)

OWASP Top 10 - 2025 : [A06 - Insecure Design](#)

Security.txt file is missing

port 443/tcp

CONFIRMED

URL

Missing: <https://scstadmin.fillipsoftware.com/.well-known/security.txt>

Details

Risk description:

There is no particular risk in not having a security.txt file for your server. However, this file is important because it offers a designated channel for reporting vulnerabilities and security issues.

Recommendation:

We recommend you to implement the security.txt file according to the standard, in order to allow researchers or users report any security issues they find, improving the defensive mechanisms of your server.

References:

<https://securitytxt.org/>

Classification:

CWE : [CWE-1188](#)

OWASP Top 10 - 2017 : [A6 - Security Misconfiguration](#)

OWASP Top 10 - 2021 : [A5 - Security Misconfiguration](#)

OWASP Top 10 - 2025 : [A02 - Security Misconfiguration](#)

HTTP OPTIONS enabled

CONFIRMED

port 443/tcp

URL	Method	Summary
https://scstadmin.fillipsoftware.com/	OPTIONS	We did a HTTP OPTIONS request. The server responded with a 200 status code and the header: <code>Allow: GET,HEAD</code> Request / Response

Details

Risk description:

The only risk this might present nowadays is revealing debug HTTP methods that can be used on the server. This can present a danger if any of those methods can lead to sensitive information, like authentication information, secret keys.

Recommendation:

We recommend that you check for unused HTTP methods or even better, disable the OPTIONS method. This can be done using your webserver configuration.

References:

<https://techcommunity.microsoft.com/t5/iis-support-blog/http-options-and-default-page-vulnerabilities/ba-p/1504845>

<https://docs.nginx.com/nginx-management-suite/acm/how-to/policies/allowed-http-methods/>

Classification:

CWE : [CWE-16](#)

OWASP Top 10 - 2017 : [A6 - Security Misconfiguration](#)

OWASP Top 10 - 2021 : [A5 - Security Misconfiguration](#)

OWASP Top 10 - 2025 : [A02 - Security Misconfiguration](#)

Scan coverage information

List of tests performed (38)

Port 443

- ✓ Scanned for missing HTTP header - Referrer
- ✓ Scanned for missing HTTP header - Strict-Transport-Security
- ✓ Scanned for missing HTTP header - X-Content-Type-Options
- ✓ Scanned for robots.txt file
- ✓ Scanned for website technologies
- ✓ Scanned for unsafe HTTP header Content Security Policy
- ✓ Scanned for enabled HTTP OPTIONS method
- ✓ Scanned for login interfaces

- ✓ Scanned for absence of the security.txt file
- ✓ Scanned for version-based vulnerabilities of server-side software
- ✓ Scanned for client access policies
- ✓ Scanned for use of untrusted certificates
- ✓ Scanned for enabled HTTP debug methods
- ✓ Scanned for secure communication
- ✓ Scanned for directory listing
- ✓ Scanned for passwords submitted unencrypted
- ✓ Scanned for error messages
- ✓ Scanned for debug messages
- ✓ Scanned for code comments
- ✓ Scanned for missing HTTP header - Content Security Policy
- ✓ Scanned for passwords submitted in URLs
- ✓ Scanned for domain too loose set for cookies
- ✓ Scanned for mixed content between HTTP and HTTPS
- ✓ Scanned for cross domain file inclusion
- ✓ Scanned for internal error code
- ✓ Scanned for HttpOnly flag of cookie
- ✓ Scanned for Secure flag of cookie
- ✓ Scanned for secure password submission
- ✓ Scanned for sensitive data
- ✓ Scanned for OpenAPI files
- ✓ Scanned for file upload
- ✓ Scanned for SQL statement in request parameter
- ✓ Scanned for password returned in later response
- ✓ Scanned for Path Disclosure
- ✓ Scanned for Session Token in URL
- ✓ Scanned for API endpoints
- ✓ Scanned for emails
- ✓ Scanned for missing HTTP header - Rate Limit

Scan parameters

target:	https://scstadmin.fillipsoftware.com/
scan_type:	Light
authentication:	False

Scan stats

Unique Injection Points Detected:	9
URLs spidered:	21
Total number of HTTP requests:	33
Average time until a response was received:	189ms