U.S. District Court Database Extension

Data Codebook | Federal Supplement opinions, 2013–2019

Eric McKee, Anne Macy, and Wei Zhang. Edition 0.3.1. Prepared 2026-10-31. Prompt instrument v1; deterministic direction rule 2026-10-12.

This codebook describes the existing machine-coded extension of Carp-Manning. The data preserve every source opinion cluster, including opinions outside the substantive coding scheme.

Dataset	Records	Unit
Full extension	44,275	CourtListener opinion cluster
Paper district analysis	43,090	Included court classifications
Codable district opinions	23,027	Model gate passed
District opinions with direction	18,691	Mechanical direction determined

Start here. cluster_id is the unique observation key. in_district_analysis selects the supplied district scope; codable indicates eligibility for substantive coding. Section 5 defines every variable, Section 6 lists codes and meanings, and Section 7 gives examples in Stata, Python, and R.

Contents

1 Coverage, unit, and intended use **3**

2 Construction, versions, and missing data **4**

3 Substantive coding rules **6**

4 Judge and geographic identifiers **9**

5 Variable dictionary **10**

6 Numeric value labels and compatibility lookups **20**

7 Working with the data **33**

1 Coverage, unit, and intended use

The extension contains 44,275 unique CourtListener opinion clusters selected from the Federal Supplement family with decision dates in 2013-2019 inclusive.

Observed dates range from 2013-01-02 to 2019-09-09.

Each observation is an opinion cluster. A docket may have several clusters and a cluster may contain several opinion documents. Coding uses a selected combined/lead opinion, preferring combined then lead/majority text and longer text within equal ranks. The full opinion text is not included in this package. Cite and join by cluster_id; reporter page and cm_casnum are not guaranteed unique. Cluster id does uniquely identify each observation.

Some Observations Are Not District Court records

The full file retains 763 Court of International Trade records, 381 JPML records, and 41 other nondistrict records that were published in the Federal Supplement. The paper's district analysis excludes these 1,185 rows, leaving 43,090.

2 Construction, versions, and missing data

The database includes both a csv source and a Stata edition.

The two-pass coding pipeline first extracts parties, procedural outcome, codability, and case type. A fresh second pass receives the text, first-pass facts, and the case type's focal role; it identifies the focal party and relief. Direction is then computed deterministically rather than requested from the model. The prompts contain no later-published case information.

Production used gpt-5.6-luna with locked v1 prompts. Original run tags and UTC timestamps are preserved. Of the 44,275 records, 99 used shortened text; the coder retained the beginning and end and removed the middle.

Version	Meaning
prompt_version = v1	Measurement instrument
direction_rule_version = 2026-10-12	Expanded criminal any-victory rule
Package 0.3.1	CSV/Stata and codebook edition

Storage and missingness across formats

In the CSV missing values are empty fields. The Stata edition keeps the same 66 variable names and row order. Boolean flags use byte 0=False and 1=True; blank flags become numeric missing (.). focal_prevailed is byte 0=False, 1=True, 2=mixed. Existing Carp-Manning numeric codes and labels are preserved.

cluster_id, cl_person_id, fjc_jid, fjc_nid, volume, page, and cm_casnum contain canonical digit-only values from other databases. Categorical strings, including court IDs, reporter, party, and run/version fields, are labeled integers in the Stata edition. Labels preserve the exact CSV token; the dictionary supplies every code's original CSV value. Empty source categories become numeric missing, never a substantive zero or an extra category.

date_decided is a date variable in Stata with the %td format. coded_at_utc is a double number of milliseconds since 1960-01-01 with %tc display. Interpret coded_at_utc as UTC; Stata stores no timezone attribute. Blank text fields remain empty strings.

A missing value can mean exclusion by the gate, an unidentified focal party, a mixed outcome outside the criminal exception, or unavailable metadata. Consult each variable's missingness definition. Literal none, neither, other, False, and zero are potentially meaningful values; never convert them wholesale to missing. The Stata file uses Unicode format 118 (Stata 14+) with strL storage for free-text fields and the raw docket_id field to avoid fixed-width padding. Because Stata does not allow strL merge keys, validate and copy digit-only docket_id values into a fixed-width string before a docket merge.

Raw outputs are preserved even when inconsistent with the requested schema: 24 codable=False records retain casetype and derived category even though they have no mechanical direction. There are no FJC IDB accepted_nos or disposition crosswalk fields in this package: nature_of_suit is from CourtListener.

Stable encoding conventions

appointing_president uses the president ordinal, consistent with cm_appres: Kennedy=35 through Trump=45. The CSV names George H. W. Bush and George W. Bush separately, and Stata uses the same

names for codes 41 and 43. Edition 0.3.1 corrects these names using existing cm_appres codes and, for one record without that code, the linked CourtListener appointment. Other data values are unchanged.

appointing_party follows Carp-Manning's 1=Democrat, 2=Republican numbering. Reporter codes are the Carp-Manning citation series digits 1/2/3. Recognized court IDs use Carp-Manning district numbering; local codes 10000+ retain other distinct source strings, including appellate courts and aliases. Court codes identify the original token and do not replace court_type or in_district_analysis. CourtListener nature_of_suit codes use the original string's numeric prefix, not an inferred FJC classification.

3 Substantive coding rules

Codability and case-type assignment

Pass 1 excludes opinions with no clear primary winner, no recognized liberal-conservative dimension, categorically excluded subjects, or no outcome. Named exclusions include FOIA, inter-union representation disputes, employer-versus-employer disputes, and many private commercial/intellectual-property disputes. Types 4 and 12 are discontinued and are not active coding options.

Case-type and category assignment

Case type follows the substantive claimant and issue rather than the statutory hook alone. The prompt prefers a specific type over a residual one: voting over generic racial discrimination for voting claims, named discrimination categories over type 11, and disability/race/sex/age categories over residual employment disputes when applicable. Type 3 concerns criminal motions; type 5 concerns conviction or forfeiture itself. casetype_alternate is diagnostic only.

Categories are 1 criminal justice, 2 civil liberties/rights, and 3 economic regulation/labor, derived directly from the primary case type.

Focal interests

The focal interest is a category of litigant (e.g. criminal defendant, union, or federal regulator). It is mechanically determined by case type relying on the identified focal interest in Carp–Manning.

#	Cat.	Case type	Focal interest
1	1	habeas corpus-US	Federal-custody petitioner; includes military/extradition matters.
2	1	habeas corpus-state	State prisoner or state-proceedings petitioner.
3	1	criminal court motions	Criminal defendant bringing a motion within the criminal proceeding.
4	1	contempt of court	Discontinued; no active focal rule.
5	1	(non)conv-criminal case	Criminal defendant or property owner in conviction/forfeiture matters.
6	2	alien petitions	Noncitizen seeking citizenship, relief from removal, or related redress.
7	2	Native American rights	Native American individual or recognized tribe asserting rights.
8	2	voting rights	Person asserting voting, candidacy, or representation rights.
9	3	Social Security case	Social Security disability-benefits claimant.
10	2	racial discrimination	Racial-minority claimant alleging discrimination.
11	2	14th amendment	Individual alleging civil-rights injury, or agency acting for the victim.
12	2	military exclusion	Discontinued; no active focal rule.
13	2	free of expression	Person asserting speech or press protection.
14	2	free of religion	Party asserting free-exercise or establishment-clause protection.

#	Cat.	Case type	Focal interest
15	3	union v. company	Labor union in a union-company dispute.
16	3	member v union	Union member or employee asserting a claim against the union.
17	3	employee v. employer	Employee or worker-side claimant in residual employment matters.
18	3	commercial regulation	Federal regulator asserting commercial regulatory authority.
19	3	environmental protection	Environmental, food/drug, or consumer-protection interest; substantive protection prevails.
20	3	local/state economic	State/local government defending economic regulation.
21	3	labor dispute-govt v union/employer	Secretary of Labor/NLRB; also the worker in the historical FLSA category.
22	3	rent control, excess profits	Government defending rent, price, or excess-profit controls.
23	2	womens rights	Woman asserting rights, or an agency acting on women's behalf.
24	3	NLRB v employer	Secretary of Labor/NLRB in locked v1. The type includes FLSA suits, but the role omits the worker; see Section 3 of accompanying paper.
25	3	NLRB v union	Secretary of Labor/NLRB asserting a claim against a union or employees.
26	2	handicapped rights	Person asserting disability rights.
27	2	reverse discrim-race	Affirmative-action program: upholding the program is liberal.
28	2	reverse discrim-sex	Program giving women preference: upholding the program is liberal.
29	2	right to privacy	Person asserting privacy or personal autonomy; FOIA excluded.
30	2	age discrimination	Older employee asserting age-discrimination protection.
31	1	Sentencing guidelines deviation	Convicted person seeking a lower sentence or resisting an increase.

Mechanical direction: primary analysis measure

libcon_mechanical is 1 for a liberal outcome and 0 for a conservative outcome. With a usable primary case type, focal_prevailed=1 (True) gives liberal and focal_prevailed=0 (False) gives conservative. focal_prevailed=2 (mixed) gives liberal for criminal-justice types 1, 2, 3, 5, and 31, and missing for other types. If no focal party was identified focal_prevailed gives missing. For ideological direction analysis, require codable=1 and a nonmissing direction. In CSV, the corresponding focal-relief values are True, False, and mixed.

Super-mechanical direction: alternative construction

Super-mechanical direction is an alternative construction of the ideological direction that relies less on the LLM coder's judgement. Instead, the determination of which party won is decided by focal_is_movant and disposition. motion_granted_in_part is liberal in the five criminal types once focal_is_movant is known, regardless of its True/False value. Missing focal_is_movant gives missing. The two direction variables do not always agree because they use different inputs.

Disposition	Movant outcome used
motion_granted; judgment_for_moving; agency_reversed_or_remanded	Movant wins
motion_denied; judgment_for_opposing; agency_affirmed; dismissed	Movant loses
motion_granted_in_part	1 for types 1/2/3/5/31; missing otherwise
other; none; blank/unmapped	Missing

Limits affecting inclusion and missing direction

The codability gate can exclude partial criminal victories before direction is calculated. The Carp-Manning exception for modest victories in prisoner civil-rights suits is not separately implemented or flagged in this edition.

Type 24 includes FLSA suits, but the Carp–Manning coded focal role names only the Secretary of Labor or NLRB rather than a worker bringing a suit. Worker suits can therefore lack a focal party and have missing values for variables that require a focal party.

4 Judge and geographic identifiers

Selecting judge records

Author identity from CourtListener was not perfectly matched to FJC biographical information.

judge_match_status describes the level of accuracy of the match. The accepted identity statuses are exact, first_name, concat, national, and fuzzy. A review record retains a candidate cl_person_id and judge_name. A nonmissing name or person ID does not by itself identify an accepted match. judge_match_score is a name-similarity score.

ambiguous_same_party assigns an appointing party when there are multiple possible judge matches that all agree on party. It leaves the person ID and judge name blank. Use these records for an appointer-party grouping only when that inference suits the analysis as they do not identify a particular judge. Other unresolved statuses are defined in Section 6.

Identifier namespaces

cl_person_id identifies a CourtListener person. fjc_jid and fjc_nid are different judge identifiers from the FJC directory. cm_judge is the linked Carp-Manning judge code. These identifiers are not interchangeable.

Geography and appointment variables

cm_circuit, cm_state, and cm_statdist first use the matched judge's district at the decision date, then fall back to the docket court. They can describe a judge's home district when sitting by designation. court_id retains the source docket court, while court_type and in_district_analysis give the supplied analysis classification.

cm_apyear is the earliest Article III confirmation year. cm_appres and appointing_party describe the appointing president. cm_gender and cm_race retain the documented source-recorded Carp-Manning classifications. The FJC directory includes much more extensive biographical information about each judge.

5 Variable dictionary

Variables appear in file order. Each entry gives its meaning, source, missing-value rule, actual Stata storage/display format, and number of empty fields across all 44,275 observations. CSV missing values are empty fields; numeric missing values in Stata are shown as a dot. Section 6 lists the numeric codes and their meanings; due to length the full cm_judge name lookup is in the Stata file and dictionary JSON.

`cluster_id` – CourtListener opinion cluster ID

Logical type: identifier. Stata: long, %12.0g. Empty fields: 0 / 44,275.

Unique CourtListener cluster identifier and primary key. Identifies an opinion cluster, not an entire lawsuit. Join other CourtListener records by this key; never substitute the reporter citation as a unique key. Source: CourtListener; coding input. Missingness: Required.

`case_name` – Case caption

Logical type: text. Stata: strL, %9s. Empty fields: 0 / 44,275.

Case caption returned by pass 1, with the CourtListener input caption used as fallback if the response omits the field. It is not necessarily byte-identical to the source caption. Source: CourtListener input; LLM pass 1. Missingness: Blank if unavailable.

`court_sent_to_coder` – Court supplied in coding prompt

Logical type: text. Stata: int, %8.0g. Empty fields: 5,054 / 44,275.

Court string actually supplied to the model. May be blank when the original metadata could not safely supply a district court; this is distinct from the subsequently attached court_id. Source: Pinned coding input. Missingness: Blank means no court string was supplied.

`date_decided` – Opinion decision date

Logical type: date. Stata: int, %td. Empty fields: 0 / 44,275.

Opinion decision date carried from the coding input, based on CourtListener cluster date_filed. ISO YYYY-MM-DD in CSV; native daily date in Stata. Not the lawsuit filing date and not independently hand-verified. Source: CourtListener cluster metadata. Missingness: Required. CSV representation: ISO YYYY-MM-DD text.

`codable` – Meets model codability gate

Logical type: boolean. Stata: byte, %8.0g. Empty fields: 0 / 44,275.

Pass-1 determination that the opinion fits the coding scheme, has a usable outcome, and satisfies the winner and substantive-dimension rules. Source: LLM pass 1. Missingness: Required; False means the LLM deemed it not codable. CSV: False/True; Stata: 0=False, 1=True.

`codable_reason` – Reason for codability decision

Logical type: text. Stata: strL, %9s. Empty fields: 0 / 44,275.

Model's short explanation of inclusion or exclusion. Free text, not a standardized exclusion classification or independently verified finding. Source: LLM pass 1. Missingness: Blank if not supplied.

`casetype` – Raw primary case type

Logical type: integer. Stata: byte, %8.0g. Empty fields: 20,667 / 44,275.

Primary substantive case type selected in pass 1. Codes 1-31, excluding discontinued 4 and 12. A nonmissing code does not establish codability. Source: LLM pass 1. Missingness: Usually blank when codable=False.

`casetype_alternate` – Raw alternate case type

Logical type: integer. Stata: byte, %8.0g. Empty fields: 37,882 / 44,275.

Optional second-best case type for a potentially ambiguous case. This does not create a second observation and is not used to derive category or direction. Source: LLM pass 1. Missingness: Blank means no alternate was reported.

`disposition` – Disposition of matter before court

Logical type: enum. Stata: byte, %8.0g. Empty fields: 0 / 44,275.

Procedural outcome of the motion, petition, trial, or agency review before the court. A granted motion is not necessarily the end of the lawsuit; additionally the moving party is not always the plaintiff. Source: LLM pass 1. Missingness: Required. Literal none means no outcome; other is a substantive residual code.

`prevailing_party` – Prevailing side in matter

Logical type: enum. Stata: byte, %8.0g. Empty fields: 0 / 44,275.

Side described as prevailing: moving, opposing, mixed, or neither. Side names refer to the matter before the court, not fixed plaintiff/defendant roles. Source: LLM pass 1. Missingness: Required; neither and mixed are meaningful values.

`moving_party_name` – Moving party name

Logical type: text. Stata: strL, %9s. Empty fields: 2 / 44,275.

Name of the party bringing the motion, petition, or matter being decided. Source: LLM pass 1. Missingness: Blank if not identified.

`moving_party_description` – Moving party role description

Logical type: text. Stata: strL, %9s. Empty fields: 1 / 44,275.

Short description of the moving party's role or interest, such as prisoner, employer, or regulator. Source: LLM pass 1. Missingness: Blank if not identified.

`opposing_party_name` – Opposing party name

Logical type: text. Stata: strL, %9s. Empty fields: 2 / 44,275.

Name of the side opposing the matter being decided. Source: LLM pass 1. Missingness: Blank if not identified.

`opposing_party_description` – Opposing party role description

Logical type: text. Stata: strL, %9s. Empty fields: 1 / 44,275.

Short description of the opposing party's role or interest, such as prisoner, employer, or regulator. Source: LLM pass 1. Missingness: Blank if not identified.

`focal_role` – Codebook focal-interest role

Logical type: text. Stata: strL, %9s. Empty fields: 20,691 / 44,275.

Pass-2 restatement of the focal interest specified for the primary case type. Identifies the interest whose success is coded liberal under the scheme; not necessarily the movant or plaintiff. Source: LLM pass 2. Missingness: Blank when pass 2 was skipped or no response supplied.

`focal_party` – Side occupying focal role

Logical type: enum. Stata: byte, %8.0g. Empty fields: 20,691 / 44,275.

moving or opposing identifies the side occupying the focal role; neither means no focal party was found. Neither is a real coding result. Source: LLM pass 2. Missingness: Blank generally means pass 2 was not run; neither is distinct from blank.

`focal_party_name` – Focal party name

Logical type: text. Stata: strL, %9s. Empty fields: 22,250 / 44,275.

Name of the party occupying the focal role, when identified. Source: LLM pass 2. Missingness: Blank when the focal party is unidentified or pass 2 was skipped.

`focal_is_movant` – Focal party brought the matter

Logical type: boolean. Stata: byte, %8.0g. Empty fields: 22,895 / 44,275.

True when the focal party brought the motion or matter; False when it opposed it. Used by super-mechanical direction. Source: LLM pass 2. Missingness: Blank when no focal side was identified or pass 2 was skipped. CSV: False/True; Stata: 0=False, 1=True.

`focal_prevailed` – Focal interest obtained relief

Logical type: enum. Stata: byte, %8.0g. Empty fields: 22,895 / 44,275.

True means the focal party obtained relief; False means it did not; mixed means it won some issues and lost others. CSV tokens map to Stata 1=True, 0=False, 2=mixed; blank maps to missing. This is a three-state result, not a boolean. Source: LLM pass 2. Missingness: Blank when no focal party was identified or pass 2 was skipped.

`focal_reasoning` – Reason for focal-party result

Logical type: text. Stata: strL, %9s. Empty fields: 20,691 / 44,275.

Model's short explanation linking the focal role, party, and relief. Source: LLM pass 2. Missingness: Blank when unavailable or pass 2 was skipped.

`text_chars_original` – Original opinion text characters

Logical type: integer. Stata: long, %12.0g. Empty fields: 0 / 44,275.

Character count before the coder's context-budget shortening. Source: Coding pipeline. Missingness: Blank if absent from the run record.

`text_chars_sent` – Opinion text characters sent

Logical type: integer. Stata: long, %12.0g. Empty fields: 0 / 44,275.

Character count after context-budget shortening, excluding surrounding prompt instructions. Source: Coding pipeline. Missingness: Blank if absent from the run record.

`text_excerpted` – Opinion text was shortened

Logical type: boolean. Stata: byte, %8.0g. Empty fields: 0 / 44,275.

True if the opinion was shortened by retaining its beginning and end and eliding its middle. Enables sensitivity checks for shortened inputs. Source: Coding pipeline. Missingness: Required. CSV: False/True; Stata: 0=False, 1=True.

`model` – Recorded model identifier

Logical type: text. Stata: byte, %8.0g. Empty fields: 0 / 44,275.

Recorded model ID, gpt-5.6-luna in this snapshot. Source: Coding pipeline. Missingness: Required.

`run_tag` – Original production run tag

Logical type: text. Stata: byte, %8.0g. Empty fields: 0 / 44,275.

Original run and shard tag. The run coded cases in nine shards (batches). Source: Coding pipeline. Missingness: Required.

`prompt_version` – Prompt instrument version

Logical type: text. Stata: byte, %8.0g. Empty fields: 0 / 44,275.

Always prompt version v1. What prompt version was used to code this case. Source: Coding pipeline. Missingness: Required.

`coded_at_utc` – Coding timestamp (UTC)

Logical type: timestamp. Stata: double, %tc. Empty fields: 0 / 44,275.

UTC timestamp recorded for the coded result. ISO text in CSV; native Stata clock milliseconds UTC timezone. Source: Coding pipeline. Missingness: Blank if absent from the run record. CSV representation: ISO UTC timestamp text with +00:00 offset.

`ai_casetype` – Numeric primary case type

Logical type: integer. Stata: byte, %8.0g. Empty fields: 20,667 / 44,275.

Numeric parsing of raw casetype. Retains raw codes on the 24 uncodable exceptions. Source: Coding pipeline. Missingness: Blank when casetype is blank or unparsable.

`ai_category` – Broad issue category from case type

Logical type: integer. Stata: byte, %8.0g. Empty fields: 20,667 / 44,275.

Calculated from ai_casetype: 1 criminal justice, 2 civil liberties/rights, 3 economic regulation/labor. Not a separate model judgment. Source: Coding pipeline. Missingness: Blank without a usable primary case type; raw uncodable exceptions can retain this code.

`ai_casetype_era` – Case type with 1972 labor adjustment

Logical type: integer. Stata: byte, %8.0g. Empty fields: 20,667 / 44,275.

ai_casetype with types 21/24/25 mapped to 21 for decisions through 1972. Identical to ai_casetype throughout this 2013-2019 extension; retained for compatibility with validation outputs. Source: Coding pipeline. Missingness: Blank without a primary case type.

`reporter` – Original Federal Supplement reporter

Logical type: text. Stata: byte, %8.0g. Empty fields: 0 / 44,275.

Original citation reporter from the universe manifest. Preserves upstream errors alongside reporter_corrected. Source: CourtListener citation export. Missingness: Blank if unavailable.

`volume` – Reporter volume

Logical type: identifier. Stata: int, %8.0g. Empty fields: 0 / 44,275.

Citation volume: text in CSV and exact integer in Stata. Combine with reporter and page to identify a citation; not a unique identifier. Source: CourtListener citation export. Missingness: Blank if unavailable.

`page` – Reporter first page

Logical type: identifier. Stata: int, %8.0g. Empty fields: 0 / 44,275.

First page of the reporter citation: text in CSV and exact integer in Stata. Distinct decisions may share a starting page so not a unique identifier. Source: CourtListener citation export. Missingness: Blank if unavailable.

`docket_id` – CourtListener docket ID (raw text)

Logical type: identifier. Stata: strL, %9s. Empty fields: 267 / 44,275.

Raw CourtListener docket identifier; may repeat across opinion clusters. Some values are malformed metadata fragments rather than numeric IDs. Validate a nonblank digit-only value before joining to a docket table. Not the court's docket-number string or an FJC IDB row key. Source: CourtListener cluster metadata. Missingness: Blank if missing upstream; malformed nonblank values are preserved, not recoded as missing.

`court_id` – Original CourtListener docket court ID

Logical type: text. Stata: int, %8.0g. Empty fields: 992 / 44,275.

CourtListener court identifier attached through the docket. Original IDs are retained, including cadc on district opinions placed on appellate dockets. Use court_type and in_district_analysis for the existing analysis classification. Source: CourtListener docket metadata. Missingness: Blank when unresolved.

`nature_of_suit` – CourtListener nature of suit

Logical type: text. Stata: int, %8.0g. Empty fields: 44,272 / 44,275.

CourtListener docket nature-of-suit field. Source: CourtListener docket metadata. Missingness: Blank if not recorded.

`author_source` – Source of judge author string

Logical type: enum. Stata: byte, %8.0g. Empty fields: 1,256 / 44,275.

author_str uses the selected opinion's author string; judges uses cluster-level judges as a fallback. Does not itself establish a successful identity match. Source: Coding pipeline. Missingness: Blank when no author string was available.

`judge_author_string` – Author string used for judge matching

Logical type: text. Stata: strL, %9s. Empty fields: 1,256 / 44,275.

Source author string passed to the judge matcher. May be a last name or concatenated names; not a cleaned person identifier. Source: CourtListener; author_source. Missingness: Blank when no usable author text was found.

`judge_match_status` – Judge linkage result

Logical type: enum. Stata: byte, %8.0g. Empty fields: 0 / 44,275.

Status of last name, first name, concatenated name, national, or fuzzy matching against serving judges. Ambiguous_same_party assigns party only when local candidates agree; review remains unresolved for identity and party. Source: Coding pipeline. Missingness: Required; no_author/no_candidate are explicit unresolved statuses.

`judge_match_score` – Judge name-match score (not probability)

Logical type: number. Stata: byte, %8.0g. Empty fields: 4,712 / 44,275.

Name-match score on a 0-100 scale. Exact accepted matches are recorded as 100; fuzzy/review scores use token_sort_ratio. Not a calibrated confidence probability. Source: Coding pipeline. Missingness: Blank where the matching path produces no score.

`cl_person_id` – CourtListener judge person ID or review candidate

Logical type: identifier. Stata: int, %8.0g. Empty fields: 4,712 / 44,275.

CourtListener person identifier for a linked judge or an unaccepted review candidate. Review rows retain candidate IDs and names even though appointment/FJC metadata are cleared. Check judge_match_status before treating this as an accepted identity. Text in CSV, exact integer in Stata; distinct from the FJC and Carp-Manning IDs. Source: Judge crosswalk. Missingness: Blank when no candidate is retained, including party-only matches.

`fjc_jid` – FJC legacy judge ID (jid)

Logical type: identifier. Stata: long, %12.0g. Empty fields: 6,884 / 44,275.

FJC legacy jid from CourtListener people-db fjc_id; joined to the FJC directory export to obtain nid. Not an IDB case identifier. Source: CourtListener people-db; FJC directory. Missingness: Blank without an accepted linked judge or available FJC ID.

`judge_name` – Judge full name or review candidate name

Logical type: text. Stata: strL, %9s. Empty fields: 4,712 / 44,275.

Full name associated with the linked person or a retained review candidate. A nonblank name on a review row is not an accepted identity. Source: CourtListener people-db. Missingness: Blank when no named candidate is retained.

`judge_type` – Matched judge appointment type

Logical type: enum. Stata: byte, %8.0g. Empty fields: 4,589 / 44,275.

article_iii denotes an Article III judge; magistrate denotes a magistrate judge. Party-only ambiguous_same_party matches are also marked article_iii. Type describes appointment class, not the court's jurisdiction. Source: CourtListener positions; judge crosswalk. Missingness: Blank without a usable type, including review rows.

`appointing_president` – Appointing president name

Logical type: text. Stata: byte, %8.0g. Empty fields: 6,969 / 44,275.

President associated with the matched judgeship through CourtListener position records. George H. W. Bush and George W. Bush are distinguished in both formats. Magistrate appointments do not carry an Article III presidential appointer. Source: CourtListener positions; judge crosswalk. Missingness: Blank when appointment or identity is unavailable.

`appointing_party` – Appointing president party

Logical type: enum. Stata: byte, %8.0g. Empty fields: 6,454 / 44,275.

Democrat or Republican denotes the appointing president's party, not the judge's own party. Can be filled without a person ID for ambiguous_same_party local matches. Source: CourtListener presidential positions/affiliations; documented fallback. Missingness: Blank when no party can be assigned, including magistrates.

`court_type` – Court classification for analysis

Logical type: enum. Stata: byte, %8.0g. Empty fields: 0 / 44,275.

district: jurisdiction FD; district_on_appellate_docket: cadc alias treated as D.D.C.; unresolved: blank court ID; cit: Court of International Trade; jpml: Judicial Panel on Multidistrict Litigation; other_nondistrict: remaining non-FD courts. Source: Coding pipeline; CourtListener jurisdiction. Missingness: Required.

`in_district_analysis` – Included in paper district analysis

Logical type: boolean. Stata: byte, %8.0g. Empty fields: 0 / 44,275.

Marks the 43,090 opinions in the paper's district analysis. True for district court opinions, including District of Columbia opinions filed on D.C. Circuit dockets (district_on_appellate_docket) and opinions whose court could not be resolved (unresolved); False for the Court of International Trade, the JPML, and other courts that were clearly not district courts. Reproduces the paper's analysis scope rather than asserting all included opinions were from district courts. Source: Coding pipeline. Missingness: Required. CSV: False/True; Stata: 0=False, 1=True.

`court_sent_blank` – No court string supplied to model

Logical type: boolean. Stata: byte, %8.0g. Empty fields: 0 / 44,275.

True when court_sent_to_coder is empty after trimming. Historical prompt metadata may differ from later court classification; no recoding occurred during packaging. Source: Coding pipeline. Missingness: Required. CSV: False/True; Stata: 0=False, 1=True.

`year` – Opinion decision year

Logical type: integer. Stata: int, %8.0g. Empty fields: 0 / 44,275.

First four digits of date_decided. Opinion year, not case filing or termination year. Source: Coding pipeline. Missingness: Required.

`year_incomplete` – Known incomplete coverage year

Logical type: boolean. Stata: byte, %8.0g. Empty fields: 0 / 44,275.

True for 2019. Indicates known reporter-citation coverage loss; False for other years does not certify universe completeness. Source: Coding pipeline. Missingness: Required. CSV: False/True; Stata: 0=False, 1=True.

`reporter_corrected` – Reporter with known source correction

Logical type: text. Stata: byte, %8.0g. Empty fields: 0 / 44,275.

reporter except that ten records labeled F. Supp. volume 999 are corrected to F. Supp. 2d. Used to build cm_casnum; original reporter is preserved. Source: Coding pipeline. Missingness: Blank if reporter is unavailable.

`libcon_mechanical` – Direction from focal relief (current rule)

Logical type: integer. Stata: byte, %8.0g. Empty fields: 25,099 / 44,275.

Primary direction: 1 liberal, 0 conservative, derived from ai_casetype and focal_prevailed under direction_rule_version. Mixed relief is liberal for types 1/2/3/5/31 and missing otherwise. Filter codable=True as well as nonmissing direction. Source: Coding pipeline. Missingness: Blank for unidentified focal relief, noncriminal mixed relief, or missing/invalid primary type.

`libcon_super_mechanical` – Direction from disposition (current rule)

Logical type: integer. Stata: byte, %8.0g. Empty fields: 26,960 / 44,275.

Alternative direction derived from ai_casetype, disposition, and focal_is_movant. Uses the disposition lookup and criminal partial-relief exception described in Section 3. Source: Coding pipeline. Missingness: Blank without a focal-side indicator, usable type, or mapped outcome; noncriminal partial outcomes are blank.

`direction_rule_version` – Deterministic direction-rule version

Logical type: date. Stata: byte, %8.0g. Empty fields: 0 / 44,275.

2026-10-12 denotes the expanded any-victory rule for all five criminal-justice types. This is a processing-rule date, not an opinion date or prompt version. Source: Coding pipeline. Missingness: Required.

`fjc_nid` – FJC directory node ID (nid)

Logical type: identifier. Stata: long, %12.0g. Empty fields: 6,884 / 44,275.

FJC directory nid attached by matching fjc_jid to the October 7 directory export. Used by the Carp-Manning judge crosswalk; not interchangeable with jid. Source: FJC Biographical Directory export, 2026-10-07. Missingness: Blank without a linked jid/nid.

`cm_judge` – Carp-Manning-compatible judge code

Logical type: integer. Stata: long, %12.0g. Empty fields: 14,249 / 44,275.

Carp-Manning judge code obtained through the FJC nid to Senate Judges Paper crosswalk. When one nid maps to multiple codes, the code used most recently in Carp-Manning is retained. Value labels contain the original judge names. Source: FJC directory; Senate Judges Paper crosswalk; Carp-Manning. Missingness: Blank when no crosswalk code is available; not a newly assigned judge ID.

`cm_casnum` – Carp-Manning-style reporter citation

Logical type: identifier. Stata: long, %12.0g. Empty fields: 0 / 44,275.

Citation encoding: series digit (1 F. Supp., 2 F. Supp. 2d, 3 F. Supp. 3d), three-digit volume, four-digit first page. Uses reporter_corrected. Text in CSV, exact integer in Stata; not unique and not a CourtListener cluster ID. Source: Coding pipeline. Missingness: Blank if the citation cannot be encoded.

`cm_month` – Carp-Manning-compatible opinion month

Logical type: integer. Stata: byte, %8.0g. Empty fields: 0 / 44,275.

Month of date_decided, coded 1-12. Source: Coding pipeline. Missingness: Blank if the decision month is unavailable.

`cm_circuit` – Carp-Manning-compatible circuit

Logical type: integer. Stata: byte, %8.0g. Empty fields: 2,021 / 44,275.

Carp-Manning circuit code from the matched judge's district held on the decision date, falling back to the docket court. The court-code map uses modal linked Carp-Manning codes, preferring 2005-2012 when at least 20 records exist. Source: CourtListener positions; empirical Carp-Manning court-code map. Missingness: Blank for excluded nondistrict courts or an unavailable court map.

`cm_state` – Carp-Manning-compatible state

Logical type: integer. Stata: byte, %8.0g. Empty fields: 2,021 / 44,275.

Carp-Manning state/territory code, using the same judge-district then docket-court preference as cm_circuit. May describe the judge's home district when sitting by designation. Source: CourtListener positions; empirical Carp-Manning court-code map. Missingness: Blank for excluded nondistrict courts or an unavailable court map.

`cm_statdist` – Carp-Manning-compatible district

Logical type: integer. Stata: int, %8.0g. Empty fields: 2,021 / 44,275.

Carp-Manning state/district code, using the same geography rule as cm_circuit. Do not interpret as an independently verified location of the decision. Source: CourtListener positions; empirical Carp-Manning court-code map. Missingness: Blank for excluded nondistrict courts or an unavailable court map.

`cm_appres` – Carp-Manning-compatible appointer code

Logical type: integer. Stata: byte, %8.0g. Empty fields: 7,129 / 44,275.

Carp-Manning appointing-president code. Trump=45 is an extension to the original code vocabulary. President identity is translated from the linked appointment. Source: CourtListener crosswalk; Carp-Manning value labels. Missingness: Blank without a usable appointing-president identity.

`cm_apyear` – First Article III confirmation year

Logical type: integer. Stata: int, %8.0g. Empty fields: 6,509 / 44,275.

Earliest Article III confirmation year in CourtListener for the matched person. Confirmation date was selected by agreement against Carp-Manning, rather than assuming start or nomination year. May precede appointment to the district in which this opinion was decided. Source: CourtListener positions; date_confirmation chosen by validation. Missingness: Blank without a matched person and usable Article III confirmation date.

`cm_gender` – Carp-Manning-compatible recorded gender

Logical type: integer. Stata: byte, %8.0g. Empty fields: 4,911 / 44,275.

CourtListener recorded gender mapped to Carp-Manning: 0 female, 1 male. Source: CourtListener people-db; Carp-Manning mapping. Missingness: Blank without a matched person or mapped source value.

`cm_race` – Carp-Manning-compatible recorded race

Logical type: integer. Stata: byte, %8.0g. Empty fields: 6,453 / 44,275.

CourtListener race values mapped to Carp-Manning's six codes. Multiple entries collapse by priority Black, Hispanic, Asian, American Indian, Pacific Islander, MENA, other, White; Pacific Islander/MENA/other map to code 6. Source: CourtListener people-db race lookup; deterministic compatibility mapping. Missingness: Blank without a matched person or mapped source value.

6 Numeric value labels and compatibility lookups

Case-type and category labels are supplied in Section 3. Numeric booleans use 0=False and 1=True. Both direction variables use 0=Conservative and 1=Liberal. Original Carp-Manning labels are copied from its .dta metadata. cm_judge's 2,318 original name labels plus the crosswalk additions are embedded in Stata and the dictionary JSON rather than printed here; records without a known legacy code remain missing. These historical label vocabularies may include values absent from the extension.

Encoded string categories

The following tables give Stata codes, value labels, and the meaning of categorical results. Labels equal the CSV tokens, including George H. W. Bush (41) and George W. Bush (43). Court lookups include a readable court name in the Meaning column; the Label column retains the original token. The dictionary JSON supplies all mappings and original tokens. Categories have no ordering interpretation unless a stated convention gives them one.

`court_sent_to_coder`

Carp-Manning statdist numbering for recognized districts; local codes 10000+ preserve remaining distinct source strings. These IDs do not redefine the court_type analysis classification.

Code	Label	Meaning
11	Alabama - Northern	Alabama - Northern
12	Alabama - Middle	Alabama - Middle
13	Alabama - Southern	Alabama - Southern
21	Alaska	Alaska
31	Arizona	Arizona
41	Arkansas - Eastern	Arkansas - Eastern
42	Arkansas - Western	Arkansas - Western
43	ard	United States District Court for the District of Arkansas
61	Colorado	Colorado
71	Connecticut	Connecticut
81	Delaware	Delaware
91	Florida - Northern	Florida - Northern
92	Florida - Middle	Florida - Middle
93	Florida - Southern	Florida - Southern
101	Georgia - Northern	Georgia - Northern
102	Georgia - Middle	Georgia - Middle
103	Georgia - Southern	Georgia - Southern
104	gad	District Court, District of Georgia
111	Hawaii	Hawaii
121	Idaho	Idaho
131	Illinois - Northern	Illinois - Northern
132	Illinois - Southern	Illinois - Southern
133	Illinois - Central	Illinois - Central
134	illinoisd	District Court, District of Illinois
141	Indiana - Northern	Indiana - Northern

Code	Label	Meaning
142	Indiana - Southern	Indiana - Southern
151	Iowa - Northern	Iowa - Northern
152	Iowa - Southern	Iowa - Southern
161	Kansas	Kansas
171	Kentucky - Eastern	Kentucky - Eastern
172	Kentucky - Western	Kentucky - Western
181	Louisiana - Eastern	Louisiana - Eastern
182	Louisiana - Middle	Louisiana - Middle
183	Louisiana - Western	Louisiana - Western
191	Maine	Maine
201	Maryland	Maryland
211	Massachusetts	Massachusetts
221	Michigan - Eastern	Michigan - Eastern
222	Michigan - Western	Michigan - Western
231	Minnesota	Minnesota
241	Mississippi - Northern	Mississippi - Northern
242	Mississippi - Southern	Mississippi - Southern
251	Missouri - Eastern	Missouri - Eastern
252	Missouri - Western	Missouri - Western
253	mod	District Court, District of Missouri
261	Montana	Montana
271	Nebraska	Nebraska
281	Nevada	Nevada
291	New Hampshire	New Hampshire
301	New Jersey	New Jersey
311	New Mexico	New Mexico
321	New York - Northern	New York - Northern
322	New York - Southern	New York - Southern
323	New York - Eastern	New York - Eastern
324	New York - Western	New York - Western
331	North Carolina - Eastern	North Carolina - Eastern
332	North Carolina - Middle	North Carolina - Middle
333	North Carolina - Western	North Carolina - Western
341	North Dakota	North Dakota
351	Ohio - Northern	Ohio - Northern
352	Ohio - Southern	Ohio - Southern
361	Oklahoma - Northern	Oklahoma - Northern
363	Oklahoma - Eastern	Oklahoma - Eastern
364	Oklahoma - Western	Oklahoma - Western
371	Oregon	Oregon
381	Pennsylvania - Eastern	Pennsylvania - Eastern
382	Pennsylvania - Middle	Pennsylvania - Middle
383	Pennsylvania - Western	Pennsylvania - Western
391	Rhode Island	Rhode Island
403	South Carolina	South Carolina
411	South Dakota	South Dakota
421	Tennessee - Eastern	Tennessee - Eastern

Code	Label	Meaning
422	Tennessee - Middle	Tennessee - Middle
423	Tennessee - Western	Tennessee - Western
431	Texas - Northern	Texas - Northern
432	Texas - Southern	Texas - Southern
433	Texas - Eastern	Texas - Eastern
434	Texas - Western	Texas - Western
441	Utah	Utah
451	Vermont	Vermont
461	Virginia - Eastern	Virginia - Eastern
462	Virginia - Western	Virginia - Western
471	Washington - Eastern	Washington - Eastern
472	Washington - Western	Washington - Western
473	washd	District Court, District of Washington
481	West Virginia - Northern	West Virginia - Northern
482	West Virginia - Southern	West Virginia - Southern
491	Wisconsin - Eastern	Wisconsin - Eastern
492	Wisconsin - Western	Wisconsin - Western
501	Wyoming	Wyoming
511	Puerto Rico	Puerto Rico
521	vid	District Court, Virgin Islands
551	District of Columbia	District of Columbia
561	nmid	District Court, Northern Mariana Islands
10000	arb	United States Bankruptcy Court, District of Arizona
10001	cit	United States Court of International Trade
10002	dc	District of Columbia Court of Appeals
10003	illinoised	District Court, Eastern District of Illinois
10004	jpml	United States Judicial Panel on Multidistrict Litigation
10005	mc	United States Court of Military Commission Review
10006	mont	Montana Supreme Court
10007	nc	Supreme Court of North Carolina
10008	ohioctapp	Ohio Court of Appeals
10009	orctapp	Court of Appeals of Oregon
10010	reglrailreorgct	Special Court under the Regional Rail Reorganization Act
10011	uscirct	United States Circuit Court
10012	usdistct	United States District Court
10013	wvad	District Court, District of West Virginia

`disposition`

Local categorical codes.

Code	Label	Meaning
1	agency_affirmed	Agency determination upheld
2	agency_reversed_or_remanded	Agency determination set aside or remanded
3	dismissed	Case or claim dismissed
4	judgment_for_moving	Judgment for moving party
5	judgment_for_opposing	Judgment for opposing party
6	motion_denied	Denied in full
7	motion_granted	Granted in full
8	motion_granted_in_part	Granted in part and denied in part
9	none	No outcome
10	other	Other merits outcome

`prevailing_party`

Local categorical codes.

Code	Label	Meaning
1	mixed	Both sides obtained relief
2	moving	Moving side
3	neither	No prevailing side
4	opposing	Opposing side

`focal_party`

Local categorical codes.

Code	Label	Meaning
1	moving	Moving side fills focal role
2	neither	No side fills focal role
3	opposing	Opposing side fills focal role

`focal_prevailed`

0=False, 1=True, 2=mixed; missing is separate.

Code	Label	Meaning
0	False	Did not obtain relief
1	True	Obtained relief
2	mixed	Some relief and some loss

`model`

Local categorical codes.

Code	Label
1	gpt-5.6-luna

`run_tag`

Local categorical codes.

Code	Label
1	fsupp_2013_2019_v1_luna56_shard_0001
2	fsupp_2013_2019_v1_luna56_shard_0002
3	fsupp_2013_2019_v1_luna56_shard_0003
4	fsupp_2013_2019_v1_luna56_shard_0004
5	fsupp_2013_2019_v1_luna56_shard_0005
6	fsupp_2013_2019_v1_luna56_shard_0006
7	fsupp_2013_2019_v1_luna56_shard_0007
8	fsupp_2013_2019_v1_luna56_shard_0008
9	fsupp_2013_2019_v1_luna56_shard_0009
10	fsupp_v1_luna56_shard_0001

`prompt_version`

Local categorical codes.

Code	Label
1	v1

`reporter`

Carp-Manning CASNUM reporter-series digit.

Code	Label
1	F. Supp.
2	F. Supp. 2d
3	F. Supp. 3d

`court_id`

Carp-Manning statdist numbering for recognized districts; local codes 10000+ preserve remaining distinct source strings. These IDs do not redefine the court_type analysis classification.

Code	Label	Meaning
11	alnd	District Court, Northern District of Alabama
12	almd	District Court, Middle District of Alabama
13	alsd	District Court, Southern District of Alabama
21	akd	District Court, District of Alaska
31	azd	District Court, District of Arizona
41	ared	District Court, Eastern District of Arkansas
42	arwd	District Court, Western District of Arkansas
43	ard	United States District Court for the District of Arkansas
51	cand	District Court, Northern District of California
52	casd	District Court, Southern District of California
53	caed	District Court, Eastern District of California

Code	Label	Meaning
54	cacd	District Court, Central District of California
55	californiad	District Court, District of California
61	cod	District Court, District of Colorado
71	ctd	District Court, District of Connecticut
81	ded	District Court, District of Delaware
91	flnd	District Court, Northern District of Florida
92	flmd	District Court, Middle District of Florida
93	flsd	District Court, Southern District of Florida
101	gand	District Court, Northern District of Georgia
102	gamd	District Court, Middle District of Georgia
103	gasd	District Court, Southern District of Georgia
104	gad	District Court, District of Georgia
111	hid	District Court, District of Hawaii
121	idd	District Court, District of Idaho
131	ilnd	District Court, Northern District of Illinois
132	ilsd	District Court, Southern District of Illinois
133	ilcd	District Court, Central District of Illinois
134	illinoisd	District Court, District of Illinois
141	innd	District Court, Northern District of Indiana
142	insd	District Court, Southern District of Indiana
151	iand	District Court, Northern District of Iowa
152	iasd	District Court, Southern District of Iowa
161	ksd	District Court, District of Kansas
171	kyed	District Court, Eastern District of Kentucky
172	kywd	District Court, Western District of Kentucky
181	laed	District Court, Eastern District of Louisiana
182	lamd	District Court, Middle District of Louisiana
183	lawd	District Court, Western District of Louisiana
191	med	District Court, District of Maine
201	mdd	District Court, District of Maryland
211	mad	District Court, District of Massachusetts
221	mied	District Court, Eastern District of Michigan
222	miwd	District Court, Western District of Michigan
231	mnd	District Court, District of Minnesota
241	msnd	District Court, Northern District of Mississippi
242	mssd	District Court, Southern District of Mississippi
251	moed	District Court, Eastern District of Missouri
252	mowd	District Court, Western District of Missouri
253	mod	District Court, District of Missouri
261	mtd	District Court, District of Montana
271	ned	District Court, District of Nebraska
281	nvd	District Court, District of Nevada
291	nhd	District Court, District of New Hampshire
301	njd	District Court, District of New Jersey
311	nmd	District Court, District of New Mexico
321	nynd	District Court, Northern District of New York
322	nysd	District Court, Southern District of New York

Code	Label	Meaning
323	nyed	District Court, Eastern District of New York
324	nywd	District Court, Western District of New York
331	nced	District Court, Eastern District of North Carolina
332	ncmd	District Court, Middle District of North Carolina
333	ncwd	District Court, Western District of North Carolina
341	ndd	District Court, District of North Dakota
351	ohnd	District Court, Northern District of Ohio
352	ohsd	District Court, Southern District of Ohio
361	oknd	District Court, Northern District of Oklahoma
363	oked	District Court, Eastern District of Oklahoma
364	okwd	District Court, Western District of Oklahoma
371	ord	District Court, District of Oregon
381	paed	District Court, Eastern District of Pennsylvania
382	pamd	District Court, Middle District of Pennsylvania
383	pawd	District Court, Western District of Pennsylvania
391	rid	District Court, District of Rhode Island
403	scd	District Court, District of South Carolina
411	sdd	District Court, District of South Dakota
421	tned	District Court, Eastern District of Tennessee
422	tnmd	District Court, Middle District of Tennessee
423	tnwd	District Court, Western District of Tennessee
431	txnd	District Court, Northern District of Texas
432	txsd	District Court, Southern District of Texas
433	txed	District Court, Eastern District of Texas
434	txwd	District Court, Western District of Texas
441	utd	District Court, District of Utah
451	vtd	District Court, District of Vermont
461	vaed	District Court, Eastern District of Virginia
462	vawd	District Court, Western District of Virginia
471	waed	District Court, Eastern District of Washington
472	wawd	District Court, Western District of Washington
473	washd	District Court, District of Washington
481	wvnd	District Court, Northern District of West Virginia
482	wvsd	District Court, Southern District of West Virginia
491	wied	District Court, Eastern District of Wisconsin
492	wiwd	District Court, Western District of Wisconsin
501	wyd	District Court, District of Wyoming
511	prd	District Court, District of Puerto Rico
521	vid	District Court, Virgin Islands
551	dcd	District Court, District of Columbia
561	nmid	District Court, Northern Mariana Islands
10000	arb	United States Bankruptcy Court, District of Arizona
10001	ca1	Court of Appeals for the First Circuit
10002	ca10	Court of Appeals for the Tenth Circuit
10003	ca4	Court of Appeals for the Fourth Circuit
10004	ca9	Court of Appeals for the Ninth Circuit
10005	cadc	Court of Appeals for the D.C. Circuit

Code	Label	Meaning
10006	cit	United States Court of International Trade
10007	dc	District of Columbia Court of Appeals
10008	illinoised	District Court, Eastern District of Illinois
10009	jpml	United States Judicial Panel on Multidistrict Litigation
10010	mc	United States Court of Military Commission Review
10011	mont	Montana Supreme Court
10012	nc	Supreme Court of North Carolina
10013	orctapp	Court of Appeals of Oregon
10014	reglrailreorgct	Special Court under the Regional Rail Reorganization Act
10015	uscirct	United States Circuit Court
10016	usdistct	United States District Court
10017	wvad	District Court, District of West Virginia

`nature_of_suit`

Exact numeric prefix of the original CourtListener string; not an accepted FJC NOS linkage.

Code	Label
3440	3440 Other Civil Rights
3820	3820 Copyright
4190	4190 Other Contract Actions

`author_source`

Local categorical codes.

Code	Label	Meaning
1	author_str	Selected opinion author string
2	judges	Cluster judges fallback

`judge_match_status`

Local categorical codes.

Code	Label	Meaning
1	ambiguous	Multiple candidates remain
2	ambiguous_same_party	Local identities ambiguous but appointer party agrees
3	concat	Unique last name in concatenated author text
4	exact	Unique last name on local serving bench
5	first_name	First name resolves last name ambiguity
6	fuzzy	Unique local fuzzy score at least 90
7	national	Unique last name nationally among serving judges
8	no_author	No usable author text
9	no_candidate	No accepted candidate
10	review	Unaccepted local fuzzy candidate, score at least 70

judge_type

Local categorical codes.

Code	Label	Meaning
1	article_iii	Article III judge
2	magistrate	Magistrate judge

appointing_president

President ordinal, matching Carp-Manning appres. Blank source names remain missing even when cm_appres exists.

Code	Label
35	John Kennedy
36	Lyndon Johnson
37	Richard Nixon
38	Gerald Ford
39	Jimmy Carter
40	Ronald Reagan
41	George H. W. Bush
42	William Clinton
43	George W. Bush
44	Barack Obama
45	Donald Trump

appointing_party

Carp-Manning party numbering (1 Democrat, 2 Republican); this field describes the appointer, not the judge.

Code	Label	Meaning
1	Democrat	Democratic appointer
2	Republican	Republican appointer

court_type

Local categorical codes.

Code	Label	Meaning
1	cit	Court of International Trade
2	district	Resolved FD jurisdiction
3	district_on_appellate_docket	cadc alias treated as D.D.C.
4	jpml	Judicial Panel on Multidistrict Litigation
5	other_nondistrict	Other non-FD court
6	unresolved	Court unresolved; retained

reporter_corrected

Carp-Manning CASNUM reporter-series digit.

Code	Label
1	F. Supp.
2	F. Supp. 2d
3	F. Supp. 3d

direction_rule_version

Local categorical codes.

Code	Label
1	2026-10-12

cm_month

Code	Label	Code	Label
1	January	7	July
2	February	8	August
3	March	9	September
4	April	10	October
5	May	11	November
6	June	12	December

cm_circuit

Code	Label	Code	Label
1	1ST CIRCUIT	7	7TH CIRCUIT
2	2ND CIRCUIT	8	8TH CIRCUIT
3	3RD CIRCUIT	9	9TH CIRCUIT
4	4TH CIRCUIT	10	10TH CIRCUIT
5	5TH CIRCUIT	11	11TH CIRCUIT
6	6TH CIRCUIT	88	WASHINGTON D.C.

cm_state

Code	Label	Code	Label
1	ALABAMA	29	NEW HAMPSHIRE
2	ALASKA	30	NEW JERSEY
3	ARIZONA	31	NEW MEXICO
4	ARKANSAS	32	NEW YORK
5	CALIFORNIA	33	NORTH CAROLINA
6	COLORADO	34	NORTH DAKOTA
7	CONNECTICUT	35	OHIO
8	DELAWARE	36	OKLAHOMA
9	FLORIDA	37	OREGON
10	GEORGIA	38	PENNSYLVANIA
11	HAWAII	39	RHODE ISLAND
12	IDAHO	40	SOUTH CAROLINA
13	ILLINOIS	41	SOUTH DAKOTA
14	INDIANA	42	TENNESSEE
15	IOWA	43	TEXAS
16	KANSAS	44	UTAH
17	KENTUCKY	45	VERMONT
18	LOUISIANA	46	VIRGINIA
19	MAINE	47	WASHINGTON
20	MARYLAND	48	WEST VIRGINIA
21	MASSACHUSETTS	49	WISCONSIN
22	MICHIGAN	50	WYOMING
23	MINNESOTA	51	PUERTO RICO
24	MISSISSIPPI	52	VIRGIN ISLANDS
25	MISSOURI	53	CANAL ZONE
26	MONTANA	54	GUAM
27	NEBRASKA	55	WASHINGTON D.C.
28	NEVADA	56	N. MARIANA ISLANDS

cm_statdist

Code	Label	Code	Label
11	Alabama Northern Dist	291	New Hampshire Dist of NH
12	Alabama Middle Dist	301	New Jersey Dist of NJ
13	Alabama Southern Dist	311	New Mexico Dist of NM
14	Alabama Dist of AL	321	New York Northern Dist
16	Kansas Dist of KS	322	New York Southern Dist
21	Alaska Dist of AK	323	New York Eastern Dist
31	Arizona Dist of AZ	324	New York Western Dist
41	Arkansas Eastern Dist	325	New York Dist of NY
42	Arkansas Western Dist	331	North Carolina Eastern Dist
43	Arkansas Dist of AR	332	North Carolina Middle Dist
51	California Northern Dist	333	North Carolina Western Dist

Code	Label	Code	Label
52	California Southern Dist	334	North Carolina Dist of NC
53	California Eastern Dist	341	North Dakota Dist of ND
54	California Central Dist	351	Ohio Northern Dist
55	California Dist of CA	352	Ohio Southern Dist
61	California Dist of CA	353	Ohio Dist of OH
71	Connecticut Dist of CT	361	Oklahoma Northern Dist
81	Delaware Dist of DE	362	Oklahoma Southern Dist
91	Florida Northern Dist	363	Oklahoma Eastern Dist
92	Florida Middle Dist	364	Oklahoma Western Dist
93	Florida Southern Dist	365	Oklahoma Dist of OK
94	Florida Dist of FL	371	Oregon Dist of OR
101	Georgia Northern Dist	381	Pennsylvania Eastern Dist
102	Georgia Middle Dist	382	Pennsylvania Middle Dist
103	Georgia Southern Dist	383	Pennsylvania Western Dist
104	Georgia Dist of GA	384	Pennsylvania Dist of PA
111	Hawaii Dist of HI	391	Rhode Island Dist of RI
121	Idaho Dist of ID	401	South Carolina Eastern Dist
131	Illinois Northern Dist	402	South Carolina Western Dist
132	Illinois Southern Dist	403	South Carolina Dist of SC
133	Illinois Central Dist	411	South Dakota Dist of SD
134	Illinois Dist of IL	421	Tennessee Eastern Dist
141	Indiana Northern Dist	422	Tennessee Middle Dist
142	Indiana Southern Dist	423	Tennessee Western Dist
143	Indiana Dist of IN	424	Tennessee Dist of TN
151	Iowa Northern Dist	431	Texas Northern Dist
152	Iowa Southern Dist	432	Texas Southern Dist
153	Iowa Dist of IA	433	Texas Eastern Dist
161	Kansas Dist of KS	434	Texas Western Dist
171	Kentucky Eastern Dist	435	Texas Dist of TX
172	Kentucky Western Dist	441	Utah Dist of UT
173	Kentucky Dist of KY	451	Vermont Dist of VT
181	Louisiana Eastern Dist	461	Virginia Eastern Dist
182	Louisiana Middle Dist	462	Virginia Western Dist
183	Louisiana Western Dist	463	Virginia Dist of VA
184	Louisiana Dist of LA	471	Washington Eastern Dist
191	Maine Dist of ME	472	Washington Western Dist
201	Maryland Dist of MD	473	Washington Dist of WA
211	Massachusetts Dist of MA	481	West Virginia Northern Dist
221	Michigan Eastern Dist	482	West Virginia Southern Dist
222	Michigan Western Dist	483	West Virginia Dist of WV
223	Michigan Dist of MI	491	Wisconsin Eastern Dist
231	Minnesota Dist of MN	492	Wisconsin Western Dist
241	Mississippi Northern Dist	493	Wisconsin Dist of WI
242	Mississippi Southern Dist	501	Wyoming Dist of WY
243	Mississippi Dist of MS	511	Puerto Rico Dist of PR
251	Missouri Eastern Dist	521	Virgin Islands Dist of VI
252	Missouri Western Dist	531	Canal Zone Dist of CZ

Code	Label	Code	Label
253	Missouri Dist of MO	541	Guam Dist of GU
261	Montana Dist of MT	551	Washington DC Dist of DC
271	Nebraska Dist of NE	561	N. Mariana Islands Dist of
281	Nevada Dist of NV		

cm_appres

Code	Label	Code	Label
25	MCKINLEY	36	JOHNSON
26	T. ROOSEVELT	37	NIXON
27	TAFT	38	FORD
28	WILSON	39	CARTER
29	HARDING	40	REAGAN
30	COOLIDGE	41	BUSH
31	HOOVER	42	CLINTON
32	F. ROOSEVELT	43	W. BUSH
33	TRUMAN	44	OBAMA
34	EISENHOWER	45	Trump (extension addition)
35	KENNEDY		

cm_gender

Code	Label
0	female
1	male

cm_race

Code	Label
1	white/caucasian
2	African-American/black
3	Latino/Hispanic
4	Asian-American
5	Native American
6	other

7 Working with the data

The examples select district-analysis observations that pass the codability gate and have a mechanical direction. CSV flags are True/False strings; Stata flags are labeled 1/0 values. Replace the relative file path as needed.

Python

```
import pandas as pd
x = pd.read_csv("data/final/district_ai_codes_2013_2019.csv",
                dtype=str, keep_default_na=False)
assert len(x) == 44275 and x.cluster_id.is_unique
d = x.loc[(x.in_district_analysis == "True") &
          (x.codable == "True") & (x.libcon_mechanical != "")].copy()
assert len(d) == 18691
d["direction"] = pd.to_numeric(d.libcon_mechanical)
print(d.direction.mean())
```

R

```
x <- read.csv("data/final/district_ai_codes_2013_2019.csv",
              colClasses="character", na.strings=NULL,
              check.names=FALSE)
stopifnot(nrow(x) == 44275L, !anyDuplicated(x$cluster_id))
d <- subset(x, in_district_analysis == "True" &
               codable == "True" & libcon_mechanical != "")
stopifnot(nrow(d) == 18691L)
mean(as.numeric(d$libcon_mechanical))
```

Stata 14 or later

```
use "data/final/district_ai_codes_2013_2019.dta", clear
isid cluster_id
assert _N == 44275
preserve
keep if in_district_analysis == 1 & codable == 1
keep if !missing(libcon_mechanical)
assert _N == 18691
summarize libcon_mechanical
restore
```

Native dates and external court joins in Stata

```
assert year(date_decided) == year
count if inrange(date_decided, td(01jan2019), td(31dec2019))
format coded_at_utc %tcCCYY-NN-DD_HH:MM:SS
* coded_at_utc is UTC; Stata has no timezone attribute.
decode court_id, generate(court_id_text)
* Join external court tables using court_id_text (e.g. dcd),
* not the local numeric court_id code.
* "neither", "none", "mixed", and False have numeric codes.
* Use decoded labels or the dictionary to select categories.
```

Files and citation

The CSV and Stata editions contain the same observations and variables. The accompanying dictionary JSON provides machine-readable definitions, value labels, and CSV-to-Stata mappings. The manifest JSON identifies the package version and records file hashes.

The data draw on the Carp-Manning U.S. District Court Database (2016 release), CourtListener's June 30, 2026 exports, the FJC judge directory, and judge crosswalk built for an earlier paper. Construction and validation details are in the accompanying paper.

Suggested citation: McKee, Eric, Anne Macy, and Wei Zhang. 2026. *Extending the U.S. District Court Database Past 2012 with a Validated Language-Model Coder*. Working paper. Cite the original Carp-Manning database when using its coding scheme or compatibility variables.