

1. Description

1.1. Project

Project Name	RCtelemetry
Board Name	custom
Generated with:	STM32CubeMX 5.2.0
Date	05/23/2019

1.2. MCU

MCU Series	STM32F3
MCU Line	STM32F303
MCU name	STM32F303CBTx
MCU Package	LQFP48
MCU Pin number	48


3. Pins Configuration

Pin Number LQFP48	Pin Name (function after reset)	Pin Type	Alternate Function(s)	Label
1	VBAT	Power		
5	PF0-OSC_IN	I/O	RCC_OSC_IN	
7	NRST	Reset		
8	VSSA/VREF-	Power		
9	VDDA/VREF+	Power		
10	PA0	I/O	ADC1_IN1	
11	PA1	I/O	ADC1_IN2	
12	PA2	I/O	ADC1_IN3	
13	PA3	I/O	ADC1_IN4	
14	PA4	I/O	SPI1_NSS	
15	PA5	I/O	SPI1_SCK	
16	PA6	I/O	SPI1_MISO	
17	PA7	I/O	SPI1_MOSI	
18	PB0 *	I/O	GPIO_Output	
19	PB1 *	I/O	GPIO_Output	
20	PB2 *	I/O	GPIO_Output	
21	PB10	I/O	USART3_TX	
22	PB11	I/O	USART3_RX	
23	VSS	Power		
24	VDD	Power		
25	PB12	I/O	ADC4_IN3	
27	PB14	I/O	TIM15_CH1	
28	PB15	I/O	TIM15_CH2	
30	PA9	I/O	USART1_TX	
32	PA11	I/O	USB_DM	
33	PA12	I/O	USB_DP	
34	PA13	I/O	TIM4_CH3	
35	VSS	Power		
36	VDD	Power		
37	PA14	I/O	USART2_TX	
38	PA15	I/O	TIM2_CH1	
39	PB3	I/O	TIM2_CH2	
40	PB4 *	I/O	GPIO_Output	
42	PB6	I/O	TIM4_CH1	
43	PB7	I/O	TIM4_CH2	
44	BOOT0	Boot		

Pin Number LQFP48	Pin Name (function after reset)	Pin Type	Alternate Function(s)	Label
46	PB9	I/O	TIM4_CH4	
47	VSS	Power		
48	VDD	Power		

* The pin is affected with an I/O function

4. Clock Tree Configuration



5. Software Project

5.1. Project Settings

Name	Value
Project Name	RCtelemetry
Project Folder	D:\Files\GIT\rctelemetry\sw\workspace_1.0.0
Toolchain / IDE	STM32CubeIDE
Firmware Package Name and Version	STM32Cube FW_F3 V1.10.0

5.2. Code Generation Settings

Name	Value
STM32Cube Firmware Library Package	Copy only the necessary library files
Generate peripheral initialization as a pair of '.c/.h' files	No
Backup previously generated files when re-generating	No
Delete previously generated files when not re-generated	Yes
Set all free pins as analog (to optimize the power consumption)	No

6. Power Consumption Calculator report

6.1. Microcontroller Selection

Series	STM32F3
Line	STM32F303
MCU	STM32F303CBTx
Datasheet	023353_Rev13

6.2. Parameter Selection

Temperature	25
Vdd	3.6

7. IPs and Middleware Configuration

7.1. ADC1

IN1: IN1 Single-ended

IN2: IN2 Single-ended

IN3: IN3 Single-ended

mode: IN4

7.1.1. Parameter Settings:

ADCs_Common_Settings:

Mode Independent mode

ADC_Settings:

Clock Prescaler ADC Asynchronous clock mode

Resolution ADC 12-bit resolution

Data Alignment Right alignment

Scan Conversion Mode Enabled

Continuous Conversion Mode **Enabled ***

Discontinuous Conversion Mode Disabled

DMA Continuous Requests Disabled

End Of Conversion Selection End of single conversion

Overrun behaviour Overrun data overwritten

Low Power Auto Wait Disabled

ADC_Regular_ConversionMode:

Enable Regular Conversions Enable

Number Of Conversion **4 ***

External Trigger Conversion Source Regular Conversion launched by software

External Trigger Conversion Edge None

Rank 1

Channel **Channel 4 ***

Sampling Time 1.5 Cycles

Offset Number No offset

Offset 0

Rank **2 ***

Channel Channel 1

Sampling Time 1.5 Cycles

Offset Number No offset

Offset 0

Rank **3 ***

Channel Channel 1

Sampling Time 1.5 Cycles

Offset Number	No offset
Offset	0
<u>Rank</u>	4 *
Channel	Channel 1
Sampling Time	1.5 Cycles
Offset Number	No offset
Offset	0

ADC_Injected_ConversionMode:

Enable Injected Conversions	Enable
Number Of Conversions	0

Analog Watchdog 1:

Enable Analog WatchDog1 Mode	false
------------------------------	-------

Analog Watchdog 2:

Enable Analog WatchDog2 Mode	false
------------------------------	-------

Analog Watchdog 3:

Enable Analog WatchDog3 Mode	false
------------------------------	-------

7.2. ADC4

IN3: IN3 Single-ended

7.2.1. Parameter Settings:

ADCs_Common_Settings:

Mode	Independent mode
------	------------------

ADC_Settings:

Clock Prescaler	ADC Asynchronous clock mode
Resolution	ADC 12-bit resolution
Data Alignment	Right alignment
Scan Conversion Mode	Disabled
Continuous Conversion Mode	Disabled
Discontinuous Conversion Mode	Disabled
DMA Continuous Requests	Disabled
End Of Conversion Selection	End of single conversion
Overrun behaviour	Overrun data overwritten
Low Power Auto Wait	Disabled

ADC_Regular_ConversionMode:

Enable Regular Conversions	Enable
Number Of Conversion	1
External Trigger Conversion Source	Regular Conversion launched by software
External Trigger Conversion Edge	None

Rank	1
Channel	Channel 3
Sampling Time	1.5 Cycles
Offset Number	No offset
Offset	0

ADC_Injected_ConversionMode:

Enable Injected Conversions	Enable
Number Of Conversions	0

Analog Watchdog 1:

Enable Analog WatchDog1 Mode	false
------------------------------	-------

Analog Watchdog 2:

Enable Analog WatchDog2 Mode	false
------------------------------	-------

Analog Watchdog 3:

Enable Analog WatchDog3 Mode	false
------------------------------	-------

7.3. CRC

mode: Activated

7.3.1. Parameter Settings:

Basic Parameters:

Default Polynomial State	Enable
Default Init Value State	Enable

Advanced Parameters:

Input Data Inversion Mode	None
Output Data Inversion Mode	Disable
Input Data Format	Bytes

7.4. RCC

High Speed Clock (HSE): BYPASS Clock Source

7.4.1. Parameter Settings:

System Parameters:

VDD voltage (V)	3.3
Prefetch Buffer	Enabled
Flash Latency(WS)	1 WS (2 CPU cycle)

RCC Parameters:

HSI Calibration Value	16
-----------------------	----

HSE Startup Timeout Value (ms)	100
LSE Startup Timeout Value (ms)	5000

7.5. SPI1

Mode: Full-Duplex Master

Hardware NSS Signal: Hardware NSS Output Signal

7.5.1. Parameter Settings:

Basic Parameters:

Frame Format	Motorola
Data Size	4 Bits
First Bit	MSB First

Clock Parameters:

Prescaler (for Baud Rate)	128 *
Baud Rate	375.0 KBits/s *
Clock Polarity (CPOL)	Low
Clock Phase (CPHA)	1 Edge

Advanced Parameters:

CRC Calculation	Disabled
NSSP Mode	Enabled
NSS Signal Type	Output Hardware

7.6. SYS

Timebase Source: TIM17

7.7. TIM2

Clock Source : Internal Clock

Channel1: Output Compare CH1

Channel2: Output Compare CH2

7.7.1. Parameter Settings:

Counter Settings:

Prescaler (PSC - 16 bits value)	24000 *
Counter Mode	Up
Counter Period (AutoReload Register - 32 bits value)	2000 *

Internal Clock Division (CKD)	No Division
auto-reload preload	Disable
Trigger Output (TRGO) Parameters:	
Master/Slave Mode (MSM bit)	Disable (Trigger input effect not delayed)
Trigger Event Selection TRGO	Update Event *
Clear Input:	
Clear Input Source	Disable
Output Compare Channel 1:	
Mode	Active Level on match *
Pulse (32 bits value)	0
CH Polarity	High
Output Compare Channel 2:	
Mode	Active Level on match *
Pulse (32 bits value)	0
CH Polarity	High

7.8. TIM3

Clock Source : Internal Clock

7.8.1. Parameter Settings:

Counter Settings:	
Prescaler (PSC - 16 bits value)	0
Counter Mode	Up
Counter Period (AutoReload Register - 16 bits value)	0
Internal Clock Division (CKD)	No Division
auto-reload preload	Disable
Trigger Output (TRGO) Parameters:	
Master/Slave Mode (MSM bit)	Disable (Trigger input effect not delayed)
Trigger Event Selection TRGO	Reset (UG bit from TIMx_EGR)

7.9. TIM4

Clock Source : Internal Clock

Channel1: PWM Generation CH1

Channel2: PWM Generation CH2

Channel3: PWM Generation CH3

Channel4: PWM Generation CH4

7.9.1. Parameter Settings:

Counter Settings:

Prescaler (PSC - 16 bits value)	48000 *
Counter Mode	Up
Counter Period (AutoReload Register - 16 bits value)	0
Internal Clock Division (CKD)	No Division
auto-reload preload	Disable

Trigger Output (TRGO) Parameters:

Master/Slave Mode (MSM bit)	Disable (Trigger input effect not delayed)
Trigger Event Selection TRGO	Reset (UG bit from TIMx_EGR)

Clear Input:

Clear Input Source	Disable
--------------------	---------

PWM Generation Channel 1:

Mode	PWM mode 1
Pulse (16 bits value)	0
Fast Mode	Disable
CH Polarity	High

PWM Generation Channel 2:

Mode	PWM mode 1
Pulse (16 bits value)	0
Fast Mode	Disable
CH Polarity	High

PWM Generation Channel 3:

Mode	PWM mode 1
Pulse (16 bits value)	0
Fast Mode	Disable
CH Polarity	High

PWM Generation Channel 4:

Mode	PWM mode 1
Pulse (16 bits value)	0
Fast Mode	Disable
CH Polarity	High

7.10. TIM15

mode: Clock Source

Channel1: Output Compare CH1

Channel2: Output Compare CH2

7.10.1. Parameter Settings:

Counter Settings:

Prescaler (PSC - 16 bits value)	0
Counter Mode	Up
Counter Period (AutoReload Register - 16 bits value)	0
Internal Clock Division (CKD)	No Division
Repetition Counter (RCR - 8 bits value)	0
auto-reload preload	Disable

Trigger Output (TRGO) Parameters:

Master/Slave Mode (MSM bit)	Disable (Trigger input effect not delayed)
Trigger Event Selection	Reset (UG bit from TIMx_EGR)

Break And Dead Time management - BRK Configuration:

BRK State	Disable
BRK Polarity	High
BRK Filter (4 bits value)	0

Break And Dead Time management - Output Configuration:

Automatic Output State	Disable
Off State Selection for Run Mode (OSSR)	Disable
Off State Selection for Idle Mode (OSSI)	Disable
Lock Configuration	Off

Output Compare Channel 1:

Mode	Frozen (used for Timing base)
Pulse (16 bits value)	0
CH Polarity	High
CH Idle State	Reset

Output Compare Channel 2:

Mode	Frozen (used for Timing base)
Pulse (16 bits value)	0
CH Polarity	High
CH Idle State	Reset

7.11. USART1

Mode: Single Wire (Half-Duplex)

7.11.1. Parameter Settings:

Basic Parameters:

Baud Rate	57600 *
Word Length	8 Bits (including Parity)
Parity	Even *
Stop Bits	2 *

Advanced Parameters:

Data Direction	Receive and Transmit
Over Sampling	16 Samples
Single Sample	Disable

Advanced Features:

Auto Baudrate	Disable
TX Pin Active Level Inversion	Enable *
RX Pin Active Level Inversion	Enable *
Data Inversion	Enable *
TX and RX Pins Swapping	Disable
Overrun	Enable
DMA on RX Error	Enable
MSB First	Disable

7.12. USART2

Mode: Single Wire (Half-Duplex)

7.12.1. Parameter Settings:

Basic Parameters:

Baud Rate	100000 *
Word Length	8 Bits (including Parity)
Parity	Even *
Stop Bits	2 *

Advanced Parameters:

Data Direction	Receive Only *
Over Sampling	16 Samples
Single Sample	Disable

Advanced Features:

Auto Baudrate	Disable
TX Pin Active Level Inversion	Disable
RX Pin Active Level Inversion	Enable *

Data Inversion	Enable *
TX and RX Pins Swapping	Disable
Overrun	Enable
DMA on RX Error	Enable
MSB First	Disable

7.13. USART3

Mode: Asynchronous

7.13.1. Parameter Settings:

Basic Parameters:

Baud Rate	38400
Word Length	8 Bits (including Parity)
Parity	None
Stop Bits	1

Advanced Parameters:

Data Direction	Receive and Transmit
Over Sampling	16 Samples
Single Sample	Disable

Advanced Features:

Auto Baudrate	Disable
TX Pin Active Level Inversion	Disable
RX Pin Active Level Inversion	Disable
Data Inversion	Disable
TX and RX Pins Swapping	Disable
Overrun	Enable
DMA on RX Error	Enable
MSB First	Disable

7.14. USB

mode: Device (FS)

7.14.1. Parameter Settings:

Basic Parameters:

Speed	Full Speed 12MBit/s
Physical interface	Internal Phy

Power Parameters:

Low Power	Disabled
Battery Charging	Disabled

7.15. FREERTOS

Interface: CMSIS_V1

7.15.1. Config parameters:

API:

FreeRTOS API	CMSIS v1
--------------	----------

Versions:

FreeRTOS version	9.0.0
CMSIS-RTOS version	1.02

Kernel settings:

USE_PREEMPTION	Enabled
CPU_CLOCK_HZ	SystemCoreClock
TICK_RATE_HZ	1000
MAX_PRIORITIES	7
MINIMAL_STACK_SIZE	128
MAX_TASK_NAME_LEN	16
USE_16_BIT_TICKS	Disabled
IDLE_SHOULD_YIELD	Enabled
USE_MUTEXES	Enabled
USE_RECURSIVE_MUTEXES	Disabled
USE_COUNTING_SEMAPHORES	Disabled
QUEUE_REGISTRY_SIZE	8
USE_APPLICATION_TASK_TAG	Disabled
ENABLE_BACKWARD_COMPATIBILITY	Enabled
USE_PORT_OPTIMISED_TASK_SELECTION	Enabled
USE_TICKLESS_IDLE	Disabled
USE_TASK_NOTIFICATIONS	Enabled

Memory management settings:

Memory Allocation	Dynamic
TOTAL_HEAP_SIZE	4096 *
Memory Management scheme	heap_4

Hook function related definitions:

USE_IDLE_HOOK	Disabled
USE_TICK_HOOK	Disabled
USE_MALLOC_FAILED_HOOK	Disabled
USE_DAEMON_TASK_STARTUP_HOOK	Disabled

CHECK_FOR_STACK_OVERFLOW Disabled

Run time and task stats gathering related definitions:

GENERATE_RUN_TIME_STATS Disabled

USE_TRACE_FACILITY Disabled

USE_STATS_FORMATTING_FUNCTIONS Disabled

Co-routine related definitions:

USE_CO_ROUTINES Disabled

MAX_CO_ROUTINE_PRIORITIES 2

Software timer definitions:

USE_TIMERS Disabled

Interrupt nesting behaviour configuration:

LIBRARY_LOWEST_INTERRUPT_PRIORITY 15

LIBRARY_MAX_SYSCALL_INTERRUPT_PRIORITY 5

7.15.2. Include parameters:

Include definitions:

vTaskPrioritySet	Enabled
uxTaskPriorityGet	Enabled
vTaskDelete	Enabled
vTaskCleanUpResources	Disabled
vTaskSuspend	Enabled
vTaskDelayUntil	Disabled
vTaskDelay	Enabled
xTaskGetSchedulerState	Enabled
xTaskResumeFromISR	Enabled
xQueueGetMutexHolder	Disabled
xSemaphoreGetMutexHolder	Disabled
pcTaskGetTaskName	Disabled
uxTaskGetStackHighWaterMark	Disabled
xTaskGetCurrentTaskHandle	Disabled
eTaskGetState	Disabled
xEventGroupSetBitFromISR	Disabled
xTimerPendFunctionCall	Disabled
xTaskAbortDelay	Disabled
xTaskGetHandle	Disabled

7.16. USB_DEVICE

Class For FS IP: Communication Device Class (Virtual Port Com)

7.16.1. Parameter Settings:

Basic Parameters:

USBD_MAX_NUM_INTERFACES (Maximum number of supported interfaces)	1
USBD_MAX_NUM_CONFIGURATION (Maximum number of supported configuration)	1
USBD_MAX_STR_DESC_SIZ (Maximum size for the string descriptors)	512
USBD_SUPPORT_USER_STRING (Enable user string descriptor)	Disabled
USBD_SELF_POWERED (Enabled self power)	Enabled
USBD_DEBUG_LEVEL (USBD Debug Level)	0: No debug message

Class Parameters:

USB CDC Rx Buffer Size	1000
USB CDC Tx Buffer Size	1000

7.16.2. Device Descriptor:

Device Descriptor:

VID (Vendor Identifier)	1155
LANGID_STRING (Language Identifier)	English(United States)
MANUFACTURER_STRING (Manufacturer Identifier)	STMicroelectronics

Device Descriptor FS:

PID (Product Identifier)	22336
PRODUCT_STRING (Product Identifier)	STM32 Virtual ComPort
CONFIGURATION_STRING (Configuration Identifier)	CDC Config
INTERFACE_STRING (Interface Identifier)	CDC Interface

* User modified value

8. System Configuration

8.1. GPIO configuration

IP	Pin	Signal	GPIO mode	GPIO pull/up pull down	Max Speed	User Label
ADC1	PA0	ADC1_IN1	Analog mode	No pull up pull down	n/a	
	PA1	ADC1_IN2	Analog mode	No pull up pull down	n/a	
	PA2	ADC1_IN3	Analog mode	No pull up pull down	n/a	
	PA3	ADC1_IN4	Analog mode	No pull up pull down	n/a	
ADC4	PB12	ADC4_IN3	Analog mode	No pull up pull down	n/a	
RCC	PF0-OSC_IN	RCC_OSC_IN	n/a	n/a	n/a	
SPI1	PA4	SPI1_NSS	Alternate Function Push Pull	No pull up pull down	High *	
	PA5	SPI1_SCK	Alternate Function Push Pull	No pull up pull down	High *	
	PA6	SPI1_MISO	Alternate Function Push Pull	No pull up pull down	High *	
	PA7	SPI1_MOSI	Alternate Function Push Pull	No pull up pull down	High *	
TIM2	PA15	TIM2_CH1	Alternate Function Push Pull	No pull up pull down	Low	
	PB3	TIM2_CH2	Alternate Function Push Pull	No pull up pull down	Low	
TIM4	PA13	TIM4_CH3	Alternate Function Push Pull	No pull up pull down	Low	
	PB6	TIM4_CH1	Alternate Function Push Pull	No pull up pull down	Low	
	PB7	TIM4_CH2	Alternate Function Push Pull	No pull up pull down	Low	
	PB9	TIM4_CH4	Alternate Function Push Pull	No pull up pull down	Low	
TIM15	PB14	TIM15_CH1	Alternate Function Push Pull	No pull up pull down	Low	
	PB15	TIM15_CH2	Alternate Function Push Pull	No pull up pull down	Low	
USART1	PA9	USART1_TX	Alternate Function Open Drain	No pull up pull down	High *	
USART2	PA14	USART2_TX	Alternate Function Open Drain	No pull up pull down	High *	
USART3	PB10	USART3_TX	Alternate Function Push Pull	No pull up pull down	High *	
	PB11	USART3_RX	Alternate Function Push Pull	No pull up pull down	High *	
USB	PA11	USB_DM	Alternate Function Push Pull	No pull up pull down	High *	
	PA12	USB_DP	Alternate Function Push Pull	No pull up pull down	High *	
GPIO	PB0	GPIO_Output	Output Push Pull	No pull up pull down	Low	
	PB1	GPIO_Output	Output Push Pull	No pull up pull down	Low	
	PB2	GPIO_Output	Output Push Pull	No pull up pull down	Low	
	PB4	GPIO_Output	Output Push Pull	No pull up pull down	Low	

8.2. DMA configuration

DMA request	Stream	Direction	Priority
ADC1	DMA1_Channel1	Peripheral To Memory	High *

ADC1: DMA1_Channel1 DMA request Settings:

Mode: Normal
Peripheral Increment: Disable
Memory Increment: **Enable ***
Peripheral Data Width: Half Word
Memory Data Width: Half Word

8.3. NVIC configuration

Interrupt Table	Enable	Preenmption Priority	SubPriority
Non maskable interrupt	true	0	0
Hard fault interrupt	true	0	0
Memory management fault	true	0	0
Pre-fetch fault, memory access fault	true	0	0
Undefined instruction or illegal state	true	0	0
System service call via SWI instruction	true	0	0
Debug monitor	true	0	0
Pendable request for system service	true	15	0
System tick timer	true	15	0
DMA1 channel1 global interrupt	true	5	0
USB low priority or CAN_RX0 interrupts	true	5	0
TIM1 trigger, commutation and TIM17 interrupts	true	0	0
PVD interrupt through EXTI line16	unused		
Flash global interrupt	unused		
RCC global interrupt	unused		
ADC1 and ADC2 interrupts	unused		
USB high priority or CAN_TX interrupts	unused		
TIM1 break and TIM15 interrupts	unused		
TIM2 global interrupt	unused		
TIM3 global interrupt	unused		
TIM4 global interrupt	unused		
SPI1 global interrupt	unused		
USART1 global interrupt / USART1 wake-up interrupt through EXTI line 25	unused		
USART2 global interrupt / USART2 wake-up interrupt through EXTI line 26	unused		
USART3 global interrupt / USART3 wake-up interrupt through EXTI line 28	unused		
ADC4 interrupt	unused		
USB high priority interrupt remap	unused		
USB low priority interrupt remap	unused		
Floating point unit interrupt	unused		

* User modified value

9. Software Pack Report