

Accessories

= suitable for this product

= suitable for this product, check max. operating temperature

Note : Crimping tools for VDE-approved connections are available.

Item	Description	Item No.
Self-adhesive tapes and foils		
ELB-01	25m PVC adhesive tape, 19mm wide, max. operating temperature 90	2481800190
ELB-02	20m glass-cloth adhesive tape, 12mm wide, max. operating temperature 140	2486800125
ELB-03	50m cloth-adhesive tape, 12mm wide, max. operating temperature 90	2481800120
ELB-04	50m cloth-adhesive tape, 12mm wide, max. operating temperature 90	2486300200
ELB-06A	50m self-adhesive aluminum foil, 75mm wide, max. operating temperature 80	2701900075
ELB-06B	100m self-adhesive aluminum foil, 1000mm, max. operating temperature 90	2701901000
ELB-06C	50m self-adhesive aluminum foil, 50mm, max. operating temperature 90	2701900050
ELB-06D	100m self-adhesive aluminum foil / PE foil, 75mm, max. operating temperature 140	2701900076
ELB-06E	25m self-adhesive aluminum foil, 500mm, max. operating temperature 150	2701900500
Mechanical fasteners		
ELB-16.10	Plastic fasteners, length 102mm, max. operating temperature 85	2796000001
ELB-16.20	Plastic fasteners, length 200mm, max. operating temperature 85	2796000002
ELB-16.36	Plastic fasteners, length 360mm, max. operating temperature 85	2796000003
ELB-11	Glass-cloth hose 2mm, max. operating temperature 450 , for fastening fiberglass products	2446000201
ELB-21	Quartz-cloth hose 3.5mm, max. operating temperature 1000 , for fastening quartz fabric products	2447000350
ELB-15.02	Clamping collar mat no. 1.4301(ASTM 304), for diameter 16/25 mm, max. operate. temp. 450	2723001016
ELB-15.04	Clamping collar mat no. 1.4301(ASTM 304), for diameter 24/40 mm, max. operate. temp. 450	2723001025
ELB-15.06	Clamping collar mat no. 1.4301(ASTM 304), for diameter 40/60 mm, max. operate. temp. 450	2723001040
ELB-15.09	Clamping collar mat no. 1.4301(ASTM 304), for diameter 70/90 mm, max. operate. temp. 450	2723001070
ELB-15.11	Clamping collar mat no. 1.4301(ASTM 304), for diameter 90/1100 mm, max. operate. temp. 450	2723001090
ELB-19.06	Taut strip, for diameter 60mm, mat no. 1.4301(ASTM 304), max. operating temp. 450 , 10 pcs/package	0931081
ELB-19.09	Taut strip, for diameter 90mm, mat no. 1.4301(ASTM 304), max. operating temp. 450 , 10 pcs/package	0931083
ELB-19.12	Taut strip, for diameter 120mm, mat no. 1.4301(ASTM 304), max. operating temp. 450 , 10 pcs/package	0931085
ELB-19.18	Taut strip, for diameter 180mm, mat no. 1.4301(ASTM 304), max. operating temp. 450 , 10 pcs/package	0931087
ELB-13S1	Pipe attachment bands, 11mm, galvanized steel, max. operating temperature 150	2720301010
ELB-13S2	Lock for ELB-13S1, max. operating temperature 150 , 10pcs/package	2720301011
ELB-13V1	Pipe attachment bands, 11mm, mat no. 1.4301(ASTM 304), max. operating temperature 450	2723001010
ELB-13V2	Lock for ELB-13V1, max. operating temperature 450 , 10pcs/package	2723001011
ELB-12	Pre-punched metal fixing strip, punched at 25mm spacing, mat. no. 1.4301(ASTM 304)	2723001005
ELB-17.10	Wire mesh 10mm x 10mm, mat. no. 1.4301(ASTM 304), 1000mm wide, wire diameter 1mm	2793000010
ELB-17.20	Wire mesh 20mm x 20mm, mat. no. 1.4301(ASTM 304), 1000mm wide, wire diameter 1mm	2793000019
ELB-17.05	Wire with looped ends 0.8/100mm, mat no. 1.4301(ASTM 304), for fastening MI-cable on wire mesh	2723002001
ELB-17.01	Twisting tool for ELB-17.05	2890000001
ELB-09	Metal gauze 50mm x 10m, mat-no. 1.4301(ASTM 304)	2793000050
Heat transfer cement		
ELWZ1	Heat transfer cement 3.81, max. operating temperature 370	2979000640
ELWZ2	Heat transfer cement 18.91, max. operating temperature 370	2979003180
ELWZ3	Heat transfer cement 3.81, max. operating temperature 630	2979000590
ELWZ4	Heat transfer cement 18.91, max. operating temperature 630	2979002950
Warning label		
EL-WS01D	Warning label German "Achtung elektrische Begleitheizung"	2986900002
EL-WS01E	Warning label English "Electric Heat Tracing"	2986900012
Low voltage transformers		
EL-T100	Disconnecting transformer 230/24V 50...60Hz 100VA acc. to VDE 0551	0925501
EL-T300	Disconnecting transformer 230/24V 50...60Hz 100VA acc. to VDE 0551	0925506
Heat resistant cable and cold ends		
ELVB-L11	PTFE-insulated stranded wire 1.5mm, blue, max. operating temperature 220 , with peaks at 250	2215001500
ELVB-L12	PTFE-insulated stranded wire 1.5mm, brown, max. operating temperature 220 , with peaks at 250	2215001501
ELVB-L13	PTFE-insulated stranded wire 1.5mm, green/yellow, max. operating temperature 220 , with peaks at 250	2215001502
ELVB-L14	PTFE-insulated stranded wire 1.5mm, red, max. operating temperature 220 , with peaks at 250	2215001503
ELVB-L15	PTFE-insulated stranded wire 1.5mm, special model for heating cable ELKM-AG	2045511150
ELVB-L01	Fiberglass-insulated stranded nickel wire 1.5mm, max. operating temperature 450 , with peaks at 550	2216301500
ELVB-L02	Fiberglass-insulated stranded nickel wire 2.5mm, max. operating temperature 450 , with peaks at 550	2216302500