

# iOS 雲端服務開發

第五週

# 課程大綱

- 自動化作業：grunt
- 發佈服務至AWS
  - forever
- 效能測試 & 系統狀態監控
- 與iOS App合作
  - Documentation
  - Testing Server ( 通常是CI Server )

# Cluster

- 一個node.js執行緒只會用到一個cpu core
- 最佳化系統資源運用 ex: 共用port
- zero downtime upgrading
  - <http://blog.evantahler.com/blog/production-deployment-with-node-js-clusters.html>

# Cluster

- `cluster.isMaster / isWorker`
- `cluster.fork()`
- `Worker`
  - `id`
  - `process`

# Cluster

```
var cluster = require('cluster');
var os = require('os');

var cpuNums = os.cpus().length;

var workers = {};

if (cluster.isMaster) {
  cluster.on('exit', function(worker) {
    delete workers[worker.process.pid];
    worker = cluster.fork();
    workers[worker.process.pid] = worker;
  });

  for (var i = 0; i < cpuNums; i++) {
    var worker = cluster.fork();
    workers[worker.process.pid] = worker;
  }
} else {
  var app = require('./app');
}

process.on('SIGTERM', function() {
  for (var pid in workers) {
    process.kill(pid);
  }
  process.exit(0);
});
```

# config tips

- 如果設定檔含有機密資訊：`mailer.example.json`

```
{  
  "smtpOption": {  
    "service": "Gmail",  
    "auth": {  
      "user": "",  
      "pass": ""  
    }  
  },  
  "mailOption": {  
    "subject": "MessageBoard Confirmation Mail",  
    "template": "confirmation",  
    "generateTextFromHTML": true  
  }  
}
```

- 複製到`mailer.json`並修改，`mailer.json`放到`.gitignore`, 不要commit，repo裡面永遠只有

# Grunt

- 自動化
  - merge
  - minification/uglify
  - unit testing
  - linting
  - deploy
  - clean
  - shell command

# JSHint

- <http://www.jshint.com/>
- 檢查js檔是否有潛在錯誤
- 非debugger

# JSHint Coding Style

- <http://www.jshint.com/hack/>
- 使用**tab**縮排
- **if, for, while** 後面接一個空白
- 匿名函式需要一個空白: **function () {};**
- 具名函式不需要: **function foo() {};**
- 大量的**option**可自定 ( 所有**option**預設值為**false** )

# JSHint Coding Style

- 變數/屬性指派之縮排

```
// Good
var next = token.peak();
var prev = token.peak(-1);
var cur  = token.current;

var scope = {
  name:  "(global)",
  parent: parentScope,
  vars:   [],
  uses:   []
};

// Bad
var cur        = token.current;
var isSemicolon = cur.isPunctuator(";"');
```

# JSHint Coding Style

- 一次宣告一個變數，但沒有指派值的變數可以一起宣告

```
var token = tokens.find(index);
var scope = scopes.current;
var next, prev, cur;
```

- 使用 === 以及 !==
- 使用分號結尾

# 安裝 Grunt

## • grunt指令

```
#grunt命令列  
~ $ sudo npm install -g grunt-cli
```

## • grunt套件

```
#先更新系統  
~ $ npm install grunt --save-dev
```

# package.json

```
"name": "MessageBoard",
  "version": "0.0.1",
  "dependencies": {
    ...
  },
  "devDependencies": {
    "grunt": "~0.4.1",
    "grunt-contrib-uglify": "~0.2.2",
    "grunt-contrib-jshint": "~0.6.0",
    "grunt-contrib-concat": "~0.3.0",
    "grunt-contrib-watch": "~0.4.4",
    "grunt-mocha-test": "~0.5.0",
    "grunt-shell": "~0.3.0"
  }
}
```

- 📌 **devDependencies:**  
**npm install --production**  
時不會安裝（僅在**develop**環境時安裝）

# Gruntfile.js

- wrapper
- 專案與任務設定
- grunt任務插件載入
- 自定任務

# Gruntfile.js

```
#Gruntfile.js

module.exports = function(grunt) {
  // Project configuration.
  grunt.initConfig({
    pkg: grunt.file.readJSON('package.json'),
    uglify: {
      options: {
        banner: '/*! <%= pkg.name %> <%= grunt.template.today("yyyy-mm-
dd") %> */\n'
      },
      build: {
        src: 'src/<%= pkg.name %>.js',
        dest: 'build/<%= pkg.name %>.min.js'
      }
    }
  });

  // Load the plugin that provides the "uglify" task.
  grunt.loadNpmTasks('grunt-contrib-uglify');

  // Default task(s).
  grunt.registerTask('default', ['uglify']);
};
```

task {



target

# 任務設定

```
grunt.initConfig({
  concat: {
    options: { /* task-level options, not a target */ },
    foo: {
      options: { /*target-level options */ },
      // concat task "foo" target options and files go here.
    },
    bar: {
      // concat task "bar" target options and files go here.
    }
  }
});
```

- **grunt concat** 會執行concat.foo & concat.bar
- **grunt concat:foo** 僅執行concat.foo

# 任務檔案設定

```
grunt.initConfig({
  concat: {
    foo: {
      files: {
        'dest/a.js': ['src/aa.js', 'src/aaa.js'],
        'dest/a1.js': ['src/aa1.js', 'src/aaa1.js'],
      },
    },
    bar: {
      files: [
        {src: ['src/bb.js', 'src/bbb.js'], dest: 'dest/b/', nonull: true},
        {src: ['src/bb1.js', 'src/bbb1.js'], dest: 'dest/b1/', filter: 'isFile'}
      ]
    }
  }
});
```

# 任務檔案設定

- \*: "/" 以外的字元
- ?: 非 "/" 的單一字元
- \*\*: 任何字元，包括 "/"
- {}: 比對裡面的任何一個條件，以逗號分隔。ex:  
{a,b}
- !: not

# 任務檔案設定

```
{src: 'foo/this.js', dest: ...}  
{src: ['foo/this.js', 'foo/that.js', 'foo/the-other.js'], dest: ...}  
{src: 'foo/th*.js', dest: ...}  
  
{src: 'foo/{a,b}*.js', dest: ...}  
{src: ['foo/a*.js', 'foo/b*.js'], dest: ...}  
  
{src: ['foo/*.js'], dest: ...}  
{src: ['foo/bar.js', 'foo/*.js'], dest: ...}  
  
{src: ['foo/*.js', '!foo/bar.js'], dest: ...}  
{src: ['foo/*.js', '!foo/bar.js', 'foo/bar.js'], dest: ...}  
  
{src: ['src/<%= basename %>.js'], dest: 'build/<%= basename %>.min.js'}  
{src: ['foo/*.js', '<%= jshint.all.src %>'], dest: ...}
```

# 動態任務檔案

- **expand: true**
- **cwd:** 設定來源檔根目錄
- **src:** 來源檔**pattern**
- **dest:** 目的檔案/目錄
- **ext:** 目的檔案的附檔名

# 動態任務檔案

```
grunt.initConfig({
  pkg: grunt.file.readJSON('package.json'),
  uglify: {
    dynamic_mappings: {
      files: [{

        expand: true, // Enable dynamic expansion.
        cwd: 'src/', // Src matches are relative to this path.
        src: ['**/*.js'], // Actual pattern(s) to match.
        dest: 'build/', // Destination path prefix.
        ext: '.min.js', // Dest filepaths will have this extension.
      }
    ]
  },
  static_mappings: {
    files: /*static file array*/
  }
})
})
```

# 動態任務檔案

- 注意：如果要針對**target**設定動態檔案，方式又不一樣

```
grunt.initConfig({  
  uglify: {  
    build: {  
      expand: true, // Enable dynamic expansion.  
      cwd: 'src/', // Src matches are relative to this path.  
      src: ['**/*.js'], // Actual pattern(s) to match.  
      dest: 'build/', // Destination path prefix.  
      ext: '.min.js' // Dest filepaths will have this extension.  
    }  
  }  
})
```

# 變數

- <%= key %> : 搜尋config[key]

```
grunt.initConfig({  
  concat: {  
    sample: {  
      options: {  
        banner: '/* <%= baz %> */\n', // /* abcde */\n      },  
        src: ['<%= qux %>', 'baz/*.js'], // [['foo/*.js', 'bar/*.js'],  
'baz/*.js']  
        dest: 'build/<%= baz %>.js', // 'build/abcde.js'  
      },  
    },  
    // Arbitrary properties used in task configuration templates.  
    foo: 'c',  
    bar: 'b<%= foo %>d', // 'bcd'  
    baz: 'a<%= bar %>e', // 'abcde'  
    qux: ['foo/*.js', 'bar/*.js'],  
  });
```

# 載入外部設定

```
grunt.initConfig({
  pkg: grunt.file.readJSON('package.json'),
  uglify: {
    options: {
      banner: '/*! <%= pkg.name %> <%= grunt.template.today("yyyy-mm-dd") %> */\n',
    },
    dist: {
      src: 'src/<%= pkg.name %>.js',
      dest: 'dist/<%= pkg.name %>.min.js'
    }
  }
});
```

# 常用的任務插件

- grunt-contrib-uglify
- grunt-contrib-concat
- grunt-contrib-jshint
- grunt-contrib-watch
- grunt-contrib-clean
- grunt-shell
- grunt-mocha-test

# Grunt for MessageBoard

- 需要的任務：測試、建置、發佈、監控
- 安裝 `grunt-cli`
- 安裝 `grunt` 及 其他task plugin:  
`grunt-contrib-uglify`, `grunt-mocha-test`, `grunt-contrib-concat`, `grunt-contrib-jshint`, `grunt-contrib-watch`, `grunt-shell`
- `Gruntfile.js`

# Gruntfile

```
grunt.loadNpmTasks('grunt-contrib-uglify');
grunt.loadNpmTasks('grunt-contrib-jshint');
grunt.loadNpmTasks('grunt-mocha-test');
grunt.loadNpmTasks('grunt-contrib-watch');
grunt.loadNpmTasks('grunt-contrib-clean');
grunt.loadNpmTasks('grunt-shell');

grunt.registerTask('test', ['jshint', 'mochaTest']);
grunt.registerTask('build', ['jshint', 'mochaTest', 'clean:build', 'uglify']);
grunt.registerTask('deploy', ['build', 'shell:uninstall', 'shell:install']);
grunt.registerTask('default', ['test']);
```

# Gruntfile

```
mochaTest: {  
  test: {  
    options: {  
      reporter: 'spec'  
    },  
    src: ['test/**/*.js']  
  }  
,  
  
jshint: {  
  files: ['gruntfile.js', 'src/**/*.js', 'test/**/*.js'],  
  options: {  
    // options here to override JSHint defaults  
    globals: {  
      console: true,  
      module: true  

```

# Gruntfile

```
clean: {
  build: ["build/"]
},  
  
uglify: {
  options: {
    banner: '/*! <%= pkg.name %> <%= grunt.template.today("dd-mm-yyyy") %> */\n'
  },
  build: {
    expand: true, // Enable dynamic expansion.
    cwd: 'src/', // Src matches are relative to this path.
    src: ['**/*.js'], // Actual pattern(s) to match.
    dest: 'build/', // Destination path prefix.
    ext: '.js' // Dest filepaths will have this extension.
  }
},
```

# Gruntfile

```
shell: {
  install: {
    options: {
      stdout:true,
      stderr: true,
      failOnError: true
    },
    command: [
      'mkdir -p <%= baseDir %>',
      'cp -rf build config public views package.json <%= baseDir %>',
      'cd <%= baseDir %>',
      'npm install --production'
    ].join('&&')
  },
  uninstall: {
    options: {
      stdout:true,
      stderr: true,
      failOnError: true
    },
    command: 'rm -rf <%= baseDir %>'
  }
},
watch: {
  files: ['<%= jshint.files %>'],
  tasks: ['test']
},
```

# AWS

- 登入

```
#ubuntu
~ $ ssh -i <cert.pem> -l ubuntu/ec2user <ip>
```

- 安裝所需軟體

```
#Git
sudo apt-get install git git-core
```

- nvm參考week1講義,
- <http://docs.mongodb.org/manual/tutorial/install-mongodb-on-ubuntu/>

# AWS

- 📌 <https://github.com/joyent/node/wiki/Installing-Node.js-via-package-manager>

```
sudo apt-get update  
sudo apt-get install python-software-properties python g++ make  
sudo add-apt-repository ppa:chris-lea/node.js  
sudo apt-get update  
sudo apt-get -y dist-upgrade  
sudo apt-get install nodejs
```

# Run our project

- 登入EC2

```
~ $ git clone https://github.com/finfin/message-board.git
```

```
~ $ cd message-board  
~ $ npm install  
~ $ grunt build  
~ $ node build/cluster.js
```

- 登出之後就不會執行了怎麼辦？

# Forever

## • 安裝

```
~ $ sudo npm install forever -g
```

```
~ $ forever my-script.js  
~ $ forever start my-script.js
```

```
~ $ forever list  
~ $ forever stop [name]  
~ $ forever stopall  
~ $ forever restart [name]
```

# UPSTART

```
#!upstart
description "myApp server"
author      "Fin Chen"

#開機執行/關機關閉
start on startup
stop on shutdown

# Restart when job dies
respawn

# Give up restart after 5 respawns in 60 seconds
respawn limit 5 60

#設定執行環境參數
env NODE_ENV=production

script
    logger "start running myApp..." #log到syslog
    chdir /data/apps/myApps #切換至App目錄，主要是避免執行node時的目錄抓取問題
    exec /usr/bin/node /data/apps/myApp/lib/app.js > /data/apps/myApp/log/
    app.log 2>&1
end script
```

# UPSTART

- `/etc/init/#{jobName}.conf`
- `sudo start/stop #{jobName}`

# 伺服器效能測試

• <http://httpd.apache.org/docs/2.2/programs/ab.html>

```
#osx, linux server幾乎都有內建  
~ $ ab [options] url
```

```
~$ ab -n 10000 -c 10 http://www.example.com/index.aspx  
~$ ab -n 10000 -c 10 -k http://www.example.com/index.aspx
```

```
# export csv  
ab -e output.csv -n 10000 -c 10 http://www.example.com/index.aspx
```

# 伺服器效能測試

```
→ ~ ab -n 5000 -c 5 http://127.0.0.1:3000/
This is ApacheBench, Version 2.3 <$Revision: 655654 $>
Copyright 1996 Adam Twiss, Zeus Technology Ltd, http://www.zeustech.net/
Licensed to The Apache Software Foundation, http://www.apache.org/

Benchmarking 127.0.0.1 (be patient)
Completed 500 requests
Completed 1000 requests
Completed 1500 requests
Completed 2000 requests
Completed 2500 requests
Completed 3000 requests
Completed 3500 requests
Completed 4000 requests
Completed 4500 requests
Completed 5000 requests
Finished 5000 requests

Server Software:
Server Hostname: 127.0.0.1
Server Port: 3000

Document Path: /
Document Length: 3057 bytes

Concurrency Level: 5
Time taken for tests: 128.581 seconds
Complete requests: 5000
Failed requests: 0
Write errors: 0

Concurrency Level: 5
Time taken for tests: 128.581 seconds
Complete requests: 5000
Failed requests: 0
Write errors: 0
Total transferred: 16778092 bytes
HTML transferred: 15285000 bytes
Requests per second: 38.89 [/sec] (mean)
Time per request: 128.581 [ms] (mean)
Time per request: 25.716 [ms] (mean, across all concurrent requests)
Transfer rate: 127.43 [Kbytes/sec] received

Connection Times (ms)
              min   mean[+/-sd] median   max
Connect:      0     0    0.1     0     2
Processing:  85   128   20.4   123   327
Waiting:     85   128   20.4   123   326
Total:       85   129   20.4   123   327

Percentage of the requests served within a certain time (ms)
 50%   123
 66%   128
 75%   132
 80%   136
 90%   159
 95%   170
 98%   182
 99%   195
100%  327 (longest request)
```

# 效能測試

- 排除頻寬的限制
  - 頻寬花錢就可以解決，且與程式本身無關
- 循序漸進
  - 測試系統在各種狀態下的反映

# 系統狀態監控 nodetime

• <https://nodetime.com/>

• 註冊

```
~ $ npm install nodetime
```

```
require('nodetime').profile({
  accountKey: '180dd7176a33ba89aaa6149e4f434a01e6a4b044',
  appName: 'Message Board'
});
```

• <https://nodetime.com/apps>

# API Documentation

- Server/Client遵照文件開發並測試
- 減少互相等待時間
- <http://weblog.bocoup.com/documenting-your-api/>

# API Documentation

- Title
- URL
- Method
- URL Query
- Data (HTTP Body)
- Success Response
- Error Response
- Sample Call
- Note

# API Documentation

操作功能	操作URL	Method	Query參數	Data	response type	Success Response	Error Response	說明
書籍清單	/api/materials/	GET			JSON	[{"id": \$id, "productID": \$productID, "title": \$title, "description": \$description, "thumbnail": \$thumbnail_url, "thumbnail_big": \$thumbnail_big_url, "price": \$price, "tag": [\$tags...], "type": \$type, "modifiedTime": \$modifiedTime}...]		
書籍清單 by Group	/api/materials/	GET	tag=#{tag}		JSON	[{"id": \$id, "productID": \$productID, "title": \$title, "description": \$description, "thumbnail": \$thumbnail_url, "thumbnail_big": \$thumbnail_big_url, "price": \$price, "tag": [\$tags...], "type": \$type, "modifiedTime": \$modifiedTime}...]		
書籍檔案下載	/api/materials/:id	GET	receipt=#{receipt}		attachment file	Content-disposition="attachment; filename=#{material.filename}" Content-type=#{material.type}	HTTP Status: 404, id not exist HTTP Status: 403, receipt invalid HTTP Status: 400, id do not match	

# API Doc - MessageBoard

- POST /apiLogin
- GET /apiLogout
- GET /api/messages
- POST /api/messages
- GET /api/mymessages
- DELETE /api/messages/:id
- GET /api/users/:name

- Title: 列出訊息
- URL: /api/messages
- Method: GET
- URL Query:  
**name=\$user, page=\$page, size=\$size**

- Data: n/a

- Success:

```
[  
  {  
    "user": "fin",  
    "text": " ddddddd",  
    "type": "public",  
    "id": "51cdc21a81a7420000000001",  
    "date": "2013-06-28T17:04:26.418Z"  
  }, ...  
]
```

- Error: 500

# 功能測試 curl

```
~ $ curl -v [url]
```

```
~ $ curl -d "username=fin&password=1234" http://localhost:3000/login
```

```
~ $ curl -c cookie.txt -d "username=fin&password=1234" http://localhost:3000/login
```

```
~ $ curl -b cookie.txt -d "text=howdy&type=public" http://localhost:3000/messages
```

```
~ $ curl -b cookie.txt -d "_method=DELETE" http://localhost:3000/messages/:id
```

# Continuous Integration

- 主要用於測試用途：自動化與非自動化
- 自動化：testing、code coverage
- 可當成testing server
- 從repo抓取最新的程式碼來執行

# Continuous Integration

## ● Jenkins

```
sudo apt-get install jenkins  
su - jenkins  
git config --global user.name "username"  
git config --global user.email "email"
```

## ● 設定檔在/etc/default/jenkins

```
HTTP_PORT=8080 #改成你要的port
```

## ● jenkins有自己的user，請確保兩邊的開發版本是相同的

# Continuous Integration

http://server\_ip:8080

The screenshot shows the Jenkins dashboard with the following elements:

- Header:** Jenkins logo, search bar, and "allow automatic page refresh" link.
- Left Sidebar:** New Job, Users, Build History, and Manage Jenkins links.
- Job List:** A table showing one job entry:

S	W	Name ↓	上次成功時間	上次失敗時間	上次建置耗費
●	○	bluejob	6 hr 42 min (#13)	12 hr (#11)	2.7 sec
- Build History:** A table showing two build entries:

#	狀態
1	閒置
2	閒置
- Bottom Navigation:** Icons for RSS feeds for all, failed, and latest builds.

# Continuous Integration

- 管理Jenkins -> 管理插件 -> 有效的
- 搜尋(⌘+f) "Git Plugin" -> 勾選 -> 安裝
- New Job -> 輸入Job名稱 -> Build a free-style software project

# CI Job設定

	#11	<a href="#">2013/1/22 下午 11:50:40</a>
	#10	<a href="#">2013/1/22 下午 11:49:41</a>
	#9	<a href="#">2013/1/22 下午 05:59:36</a>
	#8	<a href="#">2013/1/22 下午 05:58:14</a>
	#4	<a href="#">2013/1/21 下午 09:49:33</a>
	#3	<a href="#">2013/1/21 下午 09:49:28</a>
	#2	<a href="#">2013/1/21 下午 09:42:54</a>
	#1	<a href="#">2013/1/21 下午 09:34:58</a>
	RSS 全部	
	RSS 失敗	

## Source Code Management

Git

Repositories

Repository URL

Advanced...

Delete Repository

填入project git url

Branches to build

Branch Specifier (blank for default): develop

Delete  
Branch

新增

Advanced...

Repository browser

bitbucketweb

URL

# CI Job設定

## Build Triggers(使用Cron語法)

- Build after other projects are built
- Trigger builds remotely (e.g., from scripts)
- Build periodically

Schedule

35 4 \* \* \*

- Poll SCM

Schedule

25 4 \* \* \*

## Build

### Execute shell

命令

```
cd week5/messageBoard
npm install
grunt -v deploy
cd /data/apps/MessageBoard
forever stop build/cluster.js || true
forever start -o out.log -e err.log -a build/cluster.js
```

# CI Job 設定

npm install

grunt -v deploy

cd /data/apps/MessageBoard

cp /home/ubuntu/mailer.json ./config/.

cp /home/ubuntu/log4js.json ./config/.

forever stop build/app.js || true

forever start -o out.log -e err.log -a build/app.js

# Server開發大不同

- Concurrency
- Availability
- Scalability
- Security
- Collaboration

# Resources

- ✿ <http://nodejs.tw/> <http://cnodejs.org/>
- ✿ <https://www.facebook.com/NodeJS.tw>
- ✿ <http://book.nodejs.tw/>
- ✿ <http://www.nodebeginner.org/>
- ✿ <http://visionmedia.github.io/masteringnode/>

# Books

- Google御用網頁語言Node.js：一流程式設計師養成精華
- Up and Running with Node.js
- Mixu's Node Book

# Resources by me

- <http://rettamkrad.blogspot.tw/>
- <https://www.facebook.com/thingsaboutwebdev>