



# **RingsForHomalg**

## **Dictionaries of External Rings for the GAP Package homalg**

Version 2015.02.10

February 2015

**Mohamed Barakat**

**Simon Goertzen**

**Markus Kirschmer**

**Markus Lange-Hegermann**

**Oleksandr Motsak**

**Max Neunhöffer**

**Daniel Robertz**

**Hans Schönemann**

**Andreas Steenpaß**

**Vinay Wagh**

*(this manual is still under construction)*

This manual is best viewed as an HTML document. The latest version is available ONLINE at:

<http://homalg.math.rwth-aachen.de/~barakat/homalg-project/RingsForHomalg/chap0.htm>

An OFFLINE version should be included in the documentation subfolder of the package. This package is part of the homalg-project:

<http://homalg.math.rwth-aachen.de/index.php/core-packages/ringsforhomalg>

**Mohamed Barakat**

Email: [barakat@mathematik.uni-kl.de](mailto:barakat@mathematik.uni-kl.de)

Homepage: <http://www.mathematik.uni-kl.de/~barakat/>

Address: Department of Mathematics,  
University of Kaiserslautern,  
67653 Kaiserslautern,  
Germany

**Simon Goertzen**

Email: [simon.goertzen@rwth-aachen.de](mailto:simon.goertzen@rwth-aachen.de)

Homepage: <http://wwwb.math.rwth-aachen.de/~simon/>

Address: Lehrstuhl B für Mathematik,  
RWTH Aachen,  
Templergraben 64,  
52056 Aachen,  
Germany

**Markus Kirschmer**

Email: [markus.kirschmer@math.rwth-aachen.de](mailto:markus.kirschmer@math.rwth-aachen.de)

Homepage: <http://www.math.rwth-aachen.de/~Markus.Kirschmer/>

Address: Lehrstuhl D für Mathematik,  
RWTH Aachen,  
Templergraben 64,  
52056 Aachen,  
Germany

**Markus Lange-Hegermann**

Email: [markus.lange-hegermann@rwth-aachen.de](mailto:markus.lange-hegermann@rwth-aachen.de)

Homepage: <http://wwwb.math.rwth-aachen.de/~markus/>

Address: Lehrstuhl B für Mathematik,  
RWTH Aachen,  
Templergraben 64,  
52056 Aachen,  
Germany

**Oleksandr Motsak**

Email: [motsak@mathematik.uni-kl.de](mailto:motsak@mathematik.uni-kl.de)

Homepage: <http://www.mathematik.uni-kl.de/~motsak/>

Address: Department of Mathematics,  
University of Kaiserslautern,  
67653 Kaiserslautern,  
Germany

**Max Neunhöffer**

Email: [neunhoef@mcs.st-and.ac.uk](mailto:neunhoef@mcs.st-and.ac.uk)

Homepage: <http://www-groups.mcs.st-and.ac.uk/~neunhoef/>

Address: St Andrews University,  
School of Mathematics and Statistics,  
Mathematical Institute,  
North Haugh,  
St Andrews, Fife KY16 9SS,  
Scotland, UK

**Daniel Robertz**

Email: [daniel@momo.math.rwth-aachen.de](mailto:daniel@momo.math.rwth-aachen.de)

Homepage: <http://wwwb.math.rwth-aachen.de/~daniel>

Address: Lehrstuhl B für Mathematik,  
RWTH Aachen,  
Templergraben 64,  
52056 Aachen,  
Germany

**Hans Schönemann**

Email: [hannes@mathematik.uni-kl.de](mailto:hannes@mathematik.uni-kl.de)

Homepage: <http://www.mathematik.uni-kl.de/~hannes/>

Address: Department of Mathematics,  
University of Kaiserslautern,  
67653 Kaiserslautern,  
Germany

**Andreas Steenpaß**

Email: [steenpass@mathematik.uni-kl.de](mailto:steenpass@mathematik.uni-kl.de)

Homepage:

Address: Department of Mathematics,  
University of Kaiserslautern,  
67653 Kaiserslautern,  
Germany

**Vinay Wagh**

Email: [waghoba@gmail.com](mailto:waghoba@gmail.com)

Homepage: <http://www.iitg.ernet.in/vinay.wagh/>

Address: E-102, Department of Mathematics,  
Indian Institute of Technology Guwahati,  
Guwahati, Assam, India.  
PIN: 781 039.

## **Copyright**

© 2007-2015 by Mohamed Barakat, Simon Görtzen, Markus Kirschmer, Markus Lange-Hegermann, Oleksandr Motsak, Max Neunhöffer, Daniel Robertz, and Hans Schönemann.

This package may be distributed under the terms and conditions of the GNU Public License Version 2.

# Contents

<b>1</b>	<b>Introduction</b>	<b>4</b>
1.1	Ring Constructions for Supported External Computer Algebra Systems . . . . .	4
<b>2</b>	<b>Installation of the <code>RingsForHomalg</code> Package</b>	<b>10</b>
<b>3</b>	<b>The Ring Table</b>	<b>11</b>
3.1	An Example for a Ring Table - Singular . . . . .	11
	<b>References</b>	<b>23</b>
	<b>Index</b>	<b>24</b>

# Chapter 1

## Introduction

This package is part of the homalg project [hpa10]. The role of the package is described in the manual of the homalg package.

### 1.1 Ring Constructions for Supported External Computer Algebra Systems

Here are some of the supported ring constructions:

#### 1.1.1 external GAP

Example

```
gap> ZZ := HomalgRingOfIntegersInExternalGAP( );
Z
gap> Display( ZZ );
<An external ring residing in the CAS GAP>
gap> F2 := HomalgRingOfIntegersInExternalGAP( 2, ZZ );
GF(2)
gap> Display( F2 );
<An external ring residing in the CAS GAP>
```

`F2 := HomalgRingOfIntegersInExternalGAP( 2 )` would launch another GAP.

Example

```
gap> Z4 := HomalgRingOfIntegersInExternalGAP( 4, ZZ );
Z/4Z
gap> Display( Z4 );
<An external ring residing in the CAS GAP>
gap> Z_4 := HomalgRingOfIntegersInExternalGAP( ZZ ) / 4;
Z/( 4 )
gap> Display( Z_4 );
<A residue class ring>
gap> Q := HomalgFieldOfRationalsInExternalGAP( ZZ );
Q
gap> Display( Q );
<An external ring residing in the CAS GAP>
```

### 1.1.2 Singular

Example

```
gap> F2 := HomalgRingOfIntegersInSingular( 2 );
GF(2)
gap> Display( F2 );
<An external ring residing in the CAS Singular>
gap> F2s := HomalgRingOfIntegersInSingular( 2, "s", F2 );
GF(2)(s)
gap> Display( F2s );
<An external ring residing in the CAS Singular>
gap> ZZ := HomalgRingOfIntegersInSingular( F2 );
Z
gap> Display( ZZ );
<An external ring residing in the CAS Singular>
gap> Q := HomalgFieldOfRationalsInSingular( F2 );
Q
gap> Display( Q );
<An external ring residing in the CAS Singular>
gap> Qs := HomalgFieldOfRationalsInSingular( "s", F2 );
Q(s)
gap> Display( Qs );
<An external ring residing in the CAS Singular>
gap> Qi := HomalgFieldOfRationalsInSingular( "i", "i^2+1", Q );
Q[i]/(i^2+1)
gap> Display( Qi );
<An external ring residing in the CAS Singular>
```

`Q := HomalgFieldOfRationalsInSingular( )` would launch another Singular.

Example

```
gap> F2xyz := F2 * "x,y,z";
GF(2)[x,y,z]
gap> Display( F2xyz );
<An external ring residing in the CAS Singular>
gap> F2sxyz := F2s * "x,y,z";
GF(2)(s)[x,y,z]
gap> Display( F2sxyz );
<An external ring residing in the CAS Singular>
gap> F2xyzw := F2xyz * "w";
GF(2)[x,y,z][w]
gap> Display( F2xyzw );
<An external ring residing in the CAS Singular>
gap> F2sxyzw := F2sxyz * "w";
GF(2)(s)[x,y,z][w]
gap> Display( F2sxyzw );
<An external ring residing in the CAS Singular>
gap> ZZxyz := ZZ * "x,y,z";
Z[x,y,z]
gap> Display( ZZxyz );
<An external ring residing in the CAS Singular>
gap> ZZxyzw := ZZxyz * "w";
Z[x,y,z][w]
gap> Display( ZZxyzw );
<An external ring residing in the CAS Singular>
```



```

gap> Qxyz := Q * "x,y,z";
Q[x,y,z]
gap> Display( Qxyz );
<An external ring residing in the CAS Singular>
gap> Qsxyz := Qs * "x,y,z";
Q(s)[x,y,z]
gap> Display( Qsxyz );
<An external ring residing in the CAS Singular>
gap> Qixyz := Qi * "x,y,z";
(Q[i]/(i^2+1))[x,y,z]
gap> Display( Qixyz );
<An external ring residing in the CAS Singular>
gap> Qxyzw := Qxyz * "w";
Q[x,y,z][w]
gap> Display( Qxyzw );
<An external ring residing in the CAS Singular>
gap> Qsxyzw := Qsxyz * "w";
Q(s)[x,y,z][w]
gap> Display( Qsxyzw );
<An external ring residing in the CAS Singular>
gap> Dxyz := RingOfDerivations( Qxyz, "Dx,Dy,Dz" );
Q[x,y,z]<Dx,Dy,Dz>
gap> Display( Dxyz );
<An external ring residing in the CAS Singular>
gap> Exyz := ExteriorRing( Qxyz, "e,f,g" );
Q{e,f,g}
gap> Display( Exyz );
<An external ring residing in the CAS Singular>
gap> Dsxyz := RingOfDerivations( Qsxyz, "Dx,Dy,Dz" );
Q(s)[x,y,z]<Dx,Dy,Dz>
gap> Display( Dsxyz );
<An external ring residing in the CAS Singular>
gap> Esxyz := ExteriorRing( Qsxyz, "e,f,g" );
Q(s){e,f,g}
gap> Display( Esxyz );
<An external ring residing in the CAS Singular>
gap> Dixyz := RingOfDerivations( Qixyz, "Dx,Dy,Dz" );
(Q[i]/(i^2+1))[x,y,z]<Dx,Dy,Dz>
gap> Display( Dixyz );
<An external ring residing in the CAS Singular>
gap> Eixyz := ExteriorRing( Qixyz, "e,f,g" );
(Q[i]/(i^2+1)){e,f,g}
gap> Display( Eixyz );
<An external ring residing in the CAS Singular>

```

### 1.1.3 MAGMA

Example

```

gap> ZZ := HomalgRingOfIntegersInMAGMA( );
Z
gap> Display( ZZ );
<An external ring residing in the CAS MAGMA>
gap> F2 := HomalgRingOfIntegersInMAGMA( 2, ZZ );

```

```
GF(2)
gap> Display( F2 );
<An external ring residing in the CAS MAGMA>
```

`F2 := HomalgRingOfIntegersInMAGMA( 2 )` would launch another MAGMA.

Example

```
gap> Z_4 := HomalgRingOfIntegersInMAGMA( ZZ ) / 4;
Z/( 4 )
gap> Display( Z_4 );
<A residue class ring>
gap> Q := HomalgFieldOfRationalsInMAGMA( ZZ );
Q
gap> Display( Q );
<An external ring residing in the CAS MAGMA>
gap> F2xyz := F2 * "x,y,z";
GF(2)[x,y,z]
gap> Display( F2xyz );
<An external ring residing in the CAS MAGMA>
gap> Qxyz := Q * "x,y,z";
Q[x,y,z]
gap> Display( Qxyz );
<An external ring residing in the CAS MAGMA>
gap> Exyz := ExteriorRing( Qxyz, "e,f,g" );
Q{e,f,g}
gap> Display( Exyz );
<An external ring residing in the CAS MAGMA>
```

### 1.1.4 Macaulay2

Example

```
gap> ZZ := HomalgRingOfIntegersInMacaulay2( );
Z
gap> Display( ZZ );
<An external ring residing in the CAS Macaulay2>
gap> F2 := HomalgRingOfIntegersInMacaulay2( 2, ZZ );
GF(2)
gap> Display( F2 );
<An external ring residing in the CAS Macaulay2>
```

`F2 := HomalgRingOfIntegersInMacaulay2( 2 )` would launch another Macaulay2.

Example

```
gap> Z_4 := HomalgRingOfIntegersInMacaulay2( ZZ ) / 4;
Z/( 4 )
gap> Display( Z_4 );
<A residue class ring>
gap> Q := HomalgFieldOfRationalsInMacaulay2( ZZ );
Q
gap> Display( Q );
<An external ring residing in the CAS Macaulay2>
gap> F2xyz := F2 * "x,y,z";
GF(2)[x,y,z]
gap> Display( F2xyz );
```

```

<An external ring residing in the CAS Macaulay2>
gap> Qxyz := Q * "x,y,z";
Q[x,y,z]
gap> Display( Qxyz );
<An external ring residing in the CAS Macaulay2>
gap> Dxyz := RingOfDerivations( Qxyz, "Dx,Dy,Dz" );
Q[x,y,z]<Dx,Dy,Dz>
gap> Display( Dxyz );
<An external ring residing in the CAS Macaulay2>
gap> Exyz := ExteriorRing( Qxyz, "e,f,g" );
Q{e,f,g}
gap> Display( Exyz );
<An external ring residing in the CAS Macaulay2>

```

### 1.1.5 Sage

Example

```

gap> ZZ := HomalgRingOfIntegersInSage( );
Z
gap> Display( ZZ );
<An external ring residing in the CAS Sage>
gap> F2 := HomalgRingOfIntegersInSage( 2, ZZ );
GF(2)
gap> Display( F2 );
<An external ring residing in the CAS Sage>

```

F2 := HomalgRingOfIntegersInSage( 2 ) would launch another Sage.

Example

```

gap> Z_4 := HomalgRingOfIntegersInSage( ZZ ) / 4;
Z/( 4 )
gap> Display( Z_4 );
<A residue class ring>
gap> Q := HomalgFieldOfRationalsInSage( ZZ );
Q
gap> Display( Q );
<An external ring residing in the CAS Sage>
gap> F2x := F2 * "x";
GF(2)[x]
gap> Display( F2x );
<An external ring residing in the CAS Sage>
gap> Qx := Q * "x";
Q[x]
gap> Display( Qx );
<An external ring residing in the CAS Sage>

```

### 1.1.6 Maple

Example

```

gap> ZZ := HomalgRingOfIntegersInMaple( );
Z
gap> Display( ZZ );
<An external ring residing in the CAS Maple>
gap> F2 := HomalgRingOfIntegersInMaple( 2, ZZ );

```

```
GF(2)
gap> Display( F2 );
<An external ring residing in the CAS Maple>
```

`F2 := HomalgRingOfIntegersInMaple( 2 )` would launch another Maple.

Example

```
gap> Z4 := HomalgRingOfIntegersInMaple( 4, ZZ );
Z/4Z
gap> Display( Z4 );
<An external ring residing in the CAS Maple>
gap> Z_4 := HomalgRingOfIntegersInMaple( ZZ ) / 4;
Z/( 4 )
gap> Display( Z_4 );
<A residue class ring>
gap> Q := HomalgFieldOfRationalsInMaple( ZZ );
Q
gap> Display( Q );
<An external ring residing in the CAS Maple>
gap> F2xyz := F2 * "x,y,z";
GF(2)[x,y,z]
gap> Display( F2xyz );
<An external ring residing in the CAS Maple>
gap> Qxyz := Q * "x,y,z";
Q[x,y,z]
gap> Display( Qxyz );
<An external ring residing in the CAS Maple>
gap> Dxyz := RingOfDerivations( Qxyz, "Dx,Dy,Dz" );
Q[x,y,z]<Dx,Dy,Dz>
gap> Display( Dxyz );
<An external ring residing in the CAS Maple>
gap> Exyz := ExteriorRing( Qxyz, "e,f,g" );
Q{e,f,g}
gap> Display( Exyz );
<An external ring residing in the CAS Maple>
```

## Chapter 2

# Installation of the RingsForHomalg Package

To install this package just extract the package's archive file to the GAP pkg directory.

By default the RingsForHomalg package is not automatically loaded by GAP when it is installed. You must load the package with

```
LoadPackage( "RingsForHomalg" );
```

before its functions become available.

Please, send us an e-mail if you have any questions, remarks, suggestions, etc. concerning this package. Also, we would be pleased to hear about applications of this package.

The authors.

## Chapter 3

# The Ring Table

### 3.1 An Example for a Ring Table - Singular

todo: introductory text, mention: transposed matrices, the macros, refer to the philosophy

#### 3.1.1 BasisOfRowModule (in the homalg table for Singular)

▷ BasisOfRowModule( $M$ )

(function)

**Returns:**

This is the entry of the homalg table, which calls the corresponding macro BasisOfRowModule (3.1.2) inside the computer algebra system.

Code

```
BasisOfRowModule :=
function( M )
  local N;

  N := HomalgVoidMatrix(
    "unknown_number_of_rows",
    NrColumns( M ),
    HomalgRing( M )
  );

  homalgSendBlocking(
    [ "matrix ", N, " = BasisOfRowModule(", M, ")" ],
    "need_command",
    HOMALG_IO.Pictograms.BasisOfModule
  );

  return N;

end,
```

#### 3.1.2 BasisOfRowModule (Singular macro)

▷ BasisOfRowModule( $M$ )

(function)

**Returns:**

Code

```
BasisOfRowModule := "\n\
proc BasisOfRowModule (matrix M)\n\
{\n\
  return(std(M));\n\
}\n\n",
```

### 3.1.3 BasisOfColumnModule (in the homalg table for Singular)

▷ BasisOfColumnModule( $M$ ) (function)

**Returns:**

This is the entry of the homalg table, which calls the corresponding macro BasisOfColumnModule (3.1.4) inside the computer algebra system.

Code

```
BasisOfColumnModule :=
function( M )
  local N;

  N := HomalgVoidMatrix(
    NrRows( M ),
    "unknown_number_of_columns",
    HomalgRing( M )
  );

  homalgSendBlocking(
    [ "matrix ", N, " = BasisOfColumnModule(", M, ")" ],
    "need_command",
    HOMALG_IO.Pictograms.BasisOfModule
  );

  return N;

end,
```

### 3.1.4 BasisOfColumnModule (Singular macro)

▷ BasisOfColumnModule( $M$ ) (function)

**Returns:**

Code

```
BasisOfColumnModule := "\n\
proc BasisOfColumnModule (matrix M)\n\
{\n\
  return(Involution(BasisOfRowModule(Involution(M))));\n\
}\n\n",
```

### 3.1.5 DecideZeroRows (in the homalg table for Singular)

▷ DecideZeroRows( $A$ ,  $B$ ) (function)

**Returns:**

This is the entry of the `homalg` table, which calls the corresponding macro `DecideZeroRows` (3.1.6) inside the computer algebra system.

Code

```
DecideZeroRows :=
  function( A, B )
    local N;

    N := HomalgVoidMatrix(
      NrRows( A ),
      NrColumns( A ),
      HomalgRing( A )
    );

    homalgSendBlocking(
      [ "matrix ", N, " = DecideZeroRows(", A, B, ")" ],
      "need_command",
      HOMALG_IO.Pictograms.DecideZero
    );

    return N;

  end,
```

### 3.1.6 DecideZeroRows (Singular macro)

▷ `DecideZeroRows(A, B)`

(function)

**Returns:**

Code

```
DecideZeroRows := "\n\
proc DecideZeroRows (matrix A, module B)\n\
{\n\
  attrib(B,\"isSB\",1);\n\
  return(reduce(A,B));\n\
}\n\n",
```

### 3.1.7 DecideZeroColumns (in the homalg table for Singular)

▷ `DecideZeroColumns(A, B)`

(function)

**Returns:**

This is the entry of the `homalg` table, which calls the corresponding macro `DecideZeroColumns` (3.1.8) inside the computer algebra system.

Code

```
DecideZeroColumns :=
  function( A, B )
    local N;

    N := HomalgVoidMatrix(
      NrRows( A ),
      NrColumns( A ),
      HomalgRing( A )
    );
```



```

homalgSendBlocking(
  [ "matrix ", N, " = DecideZeroColumns(", A, B, ")" ],
  "need_command",
  HOMALG_IO.Pictograms.DecideZero
);

return N;

end,

```

### 3.1.8 DecideZeroColumns (Singular macro)

▷ DecideZeroColumns( $A$ ,  $B$ )

(function)

**Returns:**

Code

```

DecideZeroColumns := "\n\
proc DecideZeroColumns (matrix A, matrix B)\n\
{\n\
  return(Involution(DecideZeroRows(Involution(A),Involution(B))));\n\
}\n\n",

```

### 3.1.9 SyzygiesGeneratorsOfRows (in the homalg table for Singular)

▷ SyzygiesGeneratorsOfRows( $M$ )

(function)

**Returns:**

This is the entry of the homalg table, which calls the corresponding macro SyzygiesGeneratorsOfRows (3.1.10) inside the computer algebra system.

Code

```

SyzygiesGeneratorsOfRows :=
function( M )
  local N;

  N := HomalgVoidMatrix(
    "unknown_number_of_rows",
    NrRows( M ),
    HomalgRing( M )
  );

  homalgSendBlocking(
    [ "matrix ", N, " = SyzygiesGeneratorsOfRows(", M, ")" ],
    "need_command",
    HOMALG_IO.Pictograms.SyzygiesGenerators
  );

  return N;

end,

```

### 3.1.10 SyzygiesGeneratorsOfRows (Singular macro)

▷ SyzygiesGeneratorsOfRows( $M$ )

(function)

**Returns:**

Code

```
SyzygiesGeneratorsOfRows := "\n\
proc SyzygiesGeneratorsOfRows (matrix M)\n\
{\n\
  return(SyzForHomalg(M));\n\
}\n\n",
```

### 3.1.11 SyzygiesGeneratorsOfColumns (in the homalg table for Singular)

▷ SyzygiesGeneratorsOfColumns( $M$ )

(function)

**Returns:**

This is the entry of the `homalg` table, which calls the corresponding macro `SyzygiesGeneratorsOfColumns` (3.1.12) inside the computer algebra system.

Code

```
SyzygiesGeneratorsOfColumns :=
function( M )
  local N;

  N := HomalgVoidMatrix(
    NrColumns( M ),
    "unknown_number_of_columns",
    HomalgRing( M )
  );

  homalgSendBlocking(
    [ "matrix ", N, " = SyzygiesGeneratorsOfColumns(", M, ")" ],
    "need_command",
    HOMALG_IO.Pictograms.SyzygiesGenerators
  );

  return N;

end,
```

### 3.1.12 SyzygiesGeneratorsOfColumns (Singular macro)

▷ SyzygiesGeneratorsOfColumns( $M$ )

(function)

**Returns:**

Code

```
SyzygiesGeneratorsOfColumns := "\n\
proc SyzygiesGeneratorsOfColumns (matrix M)\n\
{\n\
  return(Involution(SyzForHomalg(Involution(M))));\n\
}\n\n",
```

### 3.1.13 BasisOfRowsCoeff (in the homalg table for Singular)

▷ `BasisOfRowsCoeff(M, T)` (function)

**Returns:**

This is the entry of the homalg table, which calls the corresponding macro `BasisOfRowsCoeff` (3.1.14) inside the computer algebra system.

```
Code
BasisOfRowsCoeff :=
function( M, T )
  local v, N;

  v := homalgStream( HomalgRing( M ) )!.variable_name;

  N := HomalgVoidMatrix(
    "unknown_number_of_rows",
    NrColumns( M ),
    HomalgRing( M )
  );

  homalgSendBlocking(
    [
      "list ", v, "l=BasisOfRowsCoeff(", M, "); ",
      "matrix ", N, " = ", v, "l[1]; ",
      "matrix ", T, " = ", v, "l[2]"
    ],
    "need_command",
    HOMALG_IO.Pictograms.BasisCoeff
  );

  return N;

end,
```

### 3.1.14 BasisOfRowsCoeff (Singular macro)

▷ `BasisOfRowsCoeff(M, T)` (function)

**Returns:**

```
Code
BasisOfRowsCoeff := "\n\
proc BasisOfRowsCoeff (matrix M)\n\
{\n\
  matrix B = BasisOfRowModule(M);\n\
  matrix T = lift(M,B);\n\
  list l = B,T;\n\
  return(l)\n\
}\n\n",
```

### 3.1.15 BasisOfColumnsCoeff (in the homalg table for Singular)

▷ `BasisOfColumnsCoeff(M, T)` (function)

**Returns:**

This is the entry of the homalg table, which calls the corresponding macro BasisOfColumnsCoeff (3.1.16) inside the computer algebra system.

Code

```

BasisOfColumnsCoeff :=
function( M, T )
  local v, N;

  v := homalgStream( HomalgRing( M ) )!.variable_name;

  N := HomalgVoidMatrix(
    NrRows( M ),
    "unknown_number_of_columns",
    HomalgRing( M )
  );

  homalgSendBlocking(
    [
      "list ", v, "l=BasisOfColumnsCoeff(", M, "); ",
      "matrix ", N, " = ", v, "l[1]; ",
      "matrix ", T, " = ", v, "l[2]"
    ],
    "need_command",
    HOMALG_IO.Pictograms.BasisCoeff
  );

  return N;

end,

```

### 3.1.16 BasisOfColumnsCoeff (Singular macro)

▷ BasisOfColumnsCoeff( $M$ ,  $T$ )

(function)

**Returns:**

Code

```

BasisOfColumnsCoeff := "\n\
proc BasisOfColumnsCoeff (matrix M)\n\
{\n\
  list l = BasisOfRowsCoeff(Involution(M));\n\
  matrix B = l[1];\n\
  matrix T = l[2];\n\
  l = Involution(B),Involution(T);\n\
  return(l);\n\
}\n\n",

```

### 3.1.17 DecideZeroRowsEffectively (in the homalg table for Singular)

▷ DecideZeroRowsEffectively( $A$ ,  $B$ ,  $T$ )

(function)

**Returns:**

This is the entry of the homalg table, which calls the corresponding macro DecideZeroRowsEffectively (3.1.18) inside the computer algebra system.

Code

```

DecideZeroRowsEffectively :=
function( A, B, T )
  local v, N;

  v := homalgStream( HomalgRing( A ) )!.variable_name;

  N := HomalgVoidMatrix(
    NrRows( A ),
    NrColumns( A ),
    HomalgRing( A )
  );

  homalgSendBlocking(
    [
      "list ", v, "l=DecideZeroRowsEffectively(", A, B, "); ",
      "matrix ", N, " = ", v, "l[1]; ",
      "matrix ", T, " = ", v, "l[2]"
    ],
    "need_command",
    HOMALG_IO.Pictograms.DecideZeroEffectively
  );

  return N;

end,

```

### 3.1.18 DecideZeroRowsEffectively (Singular macro)

▷ DecideZeroRowsEffectively( $A$ ,  $B$ ,  $T$ )

(function)

**Returns:**

Code

```

DecideZeroRowsEffectively := "\n\
proc DecideZeroRowsEffectively (matrix A, module B)\n\
{\n\
  attrib(B,\"isSB\",1);\n\
  matrix M = reduce(A,B);\n\
  matrix T = lift(B,M-A);\n\
  list l = M,T;\n\
  return(l);\n\
}\n\n",

```

### 3.1.19 DecideZeroColumnsEffectively (in the homalg table for Singular)

▷ DecideZeroColumnsEffectively( $A$ ,  $B$ ,  $T$ )

(function)

**Returns:**

This is the entry of the homalg table, which calls the corresponding macro DecideZeroColumnsEffectively (3.1.20) inside the computer algebra system.

Code

```

DecideZeroColumnsEffectively :=
function( A, B, T )

```

```

local v, N;

v := homalgStream( HomalgRing( A ) )!.variable_name;

N := HomalgVoidMatrix(
  NrRows( A ),
  NrColumns( A ),
  HomalgRing( A )
);

homalgSendBlocking(
  [
    "list ", v, "l=DecideZeroColumnsEffectively(", A, B, "); ",
    "matrix ", N, " = ", v, "l[1]; ",
    "matrix ", T, " = ", v, "l[2]"
  ],
  "need_command",
  HOMALG_IO.Pictograms.DecideZeroEffectively
);

return N;

end,

```

### 3.1.20 DecideZeroColumnsEffectively (Singular macro)

▷ DecideZeroColumnsEffectively( $A$ ,  $B$ ,  $T$ )

(function)

**Returns:**

```

Code
DecideZeroColumnsEffectively := "\n\
proc DecideZeroColumnsEffectively (matrix A, matrix B)\n\
{\n\
  list l = DecideZeroRowsEffectively(Involution(A),Involution(B));\n\
  matrix B = l[1];\n\
  matrix T = l[2];\n\
  l = Involution(B),Involution(T);\n\
  return(l);\n\
}\n\n",

```

### 3.1.21 RelativeSyzygiesGeneratorsOfRows (in the homalg table for Singular)

▷ RelativeSyzygiesGeneratorsOfRows( $M$ ,  $M2$ )

(function)

**Returns:**

This is the entry of the homalg table, which calls the corresponding macro RelativeSyzygiesGeneratorsOfRows (3.1.22) inside the computer algebra system.

```

Code
RelativeSyzygiesGeneratorsOfRows :=
function( M, M2 )
  local N;

  N := HomalgVoidMatrix(

```

```

    "unknown_number_of_rows",
    NrRows( M ),
    HomalgRing( M )
);

homalgSendBlocking(
  [ "matrix ", N, " = RelativeSyzygiesGeneratorsOfRows(", M, M2, ")" ],
  "need_command",
  HOMALG_IO.Pictograms.SyzygiesGenerators
);

return N;

end,

```

### 3.1.22 RelativeSyzygiesGeneratorsOfRows (Singular macro)

▷ RelativeSyzygiesGeneratorsOfRows( $M$ ,  $M2$ ) (function)

**Returns:**

```

Code
RelativeSyzygiesGeneratorsOfRows := "\n\
proc RelativeSyzygiesGeneratorsOfRows (matrix M1, matrix M2)\n\
{\n\
  return(BasisOfRowModule(modulo(M1, M2))); \n\
}\n\n",

```

### 3.1.23 RelativeSyzygiesGeneratorsOfColumns (in the homalg table for Singular)

▷ RelativeSyzygiesGeneratorsOfColumns( $M$ ,  $M2$ ) (function)

**Returns:**

This is the entry of the homalg table, which calls the corresponding macro RelativeSyzygiesGeneratorsOfColumns (3.1.24) inside the computer algebra system.

```

Code
RelativeSyzygiesGeneratorsOfColumns :=
function( M, M2 )
  local N;

  N := HomalgVoidMatrix(
    NrColumns( M ),
    "unknown_number_of_columns",
    HomalgRing( M )
  );

  homalgSendBlocking(
    [ "matrix ", N, " = RelativeSyzygiesGeneratorsOfColumns(", M, M2, ")" ],
    "need_command",
    HOMALG_IO.Pictograms.SyzygiesGenerators
  );

  return N;

```

```
end,
```

### 3.1.24 RelativeSyzygiesGeneratorsOfColumns (Singular macro)

▷ RelativeSyzygiesGeneratorsOfColumns( $M$ ,  $M2$ ) (function)

**Returns:**

```
Code
RelativeSyzygiesGeneratorsOfColumns := "\n\
proc RelativeSyzygiesGeneratorsOfColumns (matrix M1, matrix M2)\n\
{\n\
  return(Involution(RelativeSyzygiesGeneratorsOfRows(Involution(M1),Involution(M2))));\n\
}\n\n",
```

### 3.1.25 ReducedSyzygiesGeneratorsOfRows (in the homalg table for Singular)

▷ ReducedSyzygiesGeneratorsOfRows( $M$ ) (function)

**Returns:**

This is the entry of the homalg table, which calls the corresponding macro ReducedSyzygiesGeneratorsOfRows (3.1.26) inside the computer algebra system.

```
Code
ReducedSyzygiesGeneratorsOfRows :=
function( M )
  local N;

  N := HomalgVoidMatrix(
    "unknown_number_of_rows",
    NrRows( M ),
    HomalgRing( M )
  );

  homalgSendBlocking(
    [ "matrix ", N, " = ReducedSyzygiesGeneratorsOfRows(", M, ")" ],
    "need_command",
    HOMALG_IO.Pictograms.SyzygiesGenerators
  );

  return N;

end,
```

### 3.1.26 ReducedSyzygiesGeneratorsOfRows (Singular macro)

▷ ReducedSyzygiesGeneratorsOfRows( $M$ ) (function)

**Returns:**

```
Code
ReducedSyzForHomalg := "\n\
proc ReducedSyzForHomalg (matrix M)\n\
{\n\
  return(matrix(nres(M,2)[2]));\n\
}
```



```

}\n\n",
    ReducedSyzygiesGeneratorsOfRows := "\n\
proc ReducedSyzygiesGeneratorsOfRows (matrix M)\n\
{\n\
    return(ReducedSyzForHomalg(M));\n\
}\n\n",

```

### 3.1.27 ReducedSyzygiesGeneratorsOfColumns (in the homalg table for Singular)

▷ ReducedSyzygiesGeneratorsOfColumns( $M$ ) (function)

**Returns:**

This is the entry of the homalg table, which calls the corresponding macro ReducedSyzygiesGeneratorsOfColumns (3.1.28) inside the computer algebra system.

Code

```

ReducedSyzygiesGeneratorsOfColumns :=
function( M )
    local N;

    N := HomalgVoidMatrix(
        NrColumns( M ),
        "unknown_number_of_columns",
        HomalgRing( M )
    );

    homalgSendBlocking(
        [ "matrix ", N, " = ReducedSyzygiesGeneratorsOfColumns(", M, ")" ],
        "need_command",
        HOMALG_IO.Pictograms.SyzygiesGenerators
    );

    return N;

end,

```

### 3.1.28 ReducedSyzygiesGeneratorsOfColumns (Singular macro)

▷ ReducedSyzygiesGeneratorsOfColumns( $M$ ) (function)

**Returns:**

Code

```

    ReducedSyzygiesGeneratorsOfColumns := "\n\
proc ReducedSyzygiesGeneratorsOfColumns (matrix M)\n\
{\n\
    return(Involution(ReducedSyzForHomalg(Involution(M))));\n\
}\n\n",

```

# References

- [hpa10] T. homalg project authors. *The homalg project*, 2003-2010. <http://homalg.math.rwth-aachen.de/>. 4

# Index

- RingsForHomalg, [4](#)
- BasisOfColumnModule
  - in the homalg table for Singular, [12](#)
  - Singular macro, [12](#)
- BasisOfColumnsCoeff
  - in the homalg table for Singular, [16](#)
  - Singular macro, [17](#)
- BasisOfRowModule
  - in the homalg table for Singular, [11](#)
  - Singular macro, [11](#)
- BasisOfRowsCoeff
  - in the homalg table for Singular, [16](#)
  - Singular macro, [16](#)
- DecideZeroColumns
  - in the homalg table for Singular, [13](#)
  - Singular macro, [14](#)
- DecideZeroColumnsEffectively
  - in the homalg table for Singular, [18](#)
  - Singular macro, [19](#)
- DecideZeroRows
  - in the homalg table for Singular, [12](#)
  - Singular macro, [13](#)
- DecideZeroRowsEffectively
  - in the homalg table for Singular, [17](#)
  - Singular macro, [18](#)
- ReducedSyzygiesGeneratorsOfColumns
  - in the homalg table for Singular, [22](#)
  - Singular macro, [22](#)
- ReducedSyzygiesGeneratorsOfRows
  - in the homalg table for Singular, [21](#)
  - Singular macro, [21](#)
- RelativeSyzygiesGeneratorsOfColumns
  - in the homalg table for Singular, [20](#)
  - Singular macro, [21](#)
- RelativeSyzygiesGeneratorsOfRows
  - in the homalg table for Singular, [19](#)
  - Singular macro, [20](#)
- SyzygiesGeneratorsOfColumns
  - in the homalg table for Singular, [15](#)
  - Singular macro, [15](#)
- SyzygiesGeneratorsOfRows
  - in the homalg table for Singular, [14](#)
  - Singular macro, [15](#)