

Metadata

Course: DS 5100
Module: 11 R Programming 2
Topic: HW on Tidyverse
Author: R.C. Alvarado (adapted)
Date: 7 July 2023 (revised)

Student Info

Name: Finn Mokrzycki
Net ID: qcp6az
File GitHub URL: <https://github.com/finnmok/DS5100-2024-06-R/blob/main/exercises/M11/hw11.Rmd>

Instructions

In your **private course repo** use this notebook to write code that performs the tasks below.

Save your notebook in the M11 directory.

Remember to add and commit these files to your repo.

Then push your commits to your repo on GitHub.

Be sure to fill out the **Student Info** block above.

To submit your homework, save your results as a PDF and upload it to GradeScope.

TOTAL POINTS: 7

Overview

In this homework, you will work with the Abalone dataset from the UCI Machine Learning Repository.

To get started, download and import the `abalone.data` dataset from this URL:

- <https://archive.ics.uci.edu/ml/machine-learning-databases/abalone/abalone.data>

You can pass the URL directly to `read.csv()` and that there is no header row.

Note: The instruction to print in the questions below can be accomplished either through the `print()` function or by displaying a value directly.

TOTAL POINTS: 7

Tasks

Task 0

(0 points)

Get the dataset.

```
# CODE HERE
df <- read.csv('abalone.data.txt', sep=',', header = 0)
head(df)
```

```
##   V1    V2    V3    V4    V5    V6    V7    V8 V9
## 1  M 0.455 0.365 0.095 0.5140 0.2245 0.1010 0.150 15
## 2  M 0.350 0.265 0.090 0.2255 0.0995 0.0485 0.070 7
## 3  F 0.530 0.420 0.135 0.6770 0.2565 0.1415 0.210 9
## 4  M 0.440 0.365 0.125 0.5160 0.2155 0.1140 0.155 10
## 5  I 0.330 0.255 0.080 0.2050 0.0895 0.0395 0.055 7
## 6  I 0.425 0.300 0.095 0.3515 0.1410 0.0775 0.120 8
```

Task 1

(1 point)

Print the number of rows in the dataset.

```
# CODE HERE
nrow(df)
```

```
## [1] 4177
```

Task 2

(1 point)

The rightmost column is the number of rings. Print the maximum number of rings

```
# CODE HERE
max(df$V9)
```

```
## [1] 29
```

Task 3

(1 point)

The leftmost column is the gender with these values: M: male, F: female, I: infant.

Apply the `filter()` function from tidyverse to select only rows where gender is infant, and print the number of records.

```
# CODE HERE
library(tidyverse)
library(dplyr)
```

```
##
## Attaching package: 'dplyr'
##
## The following objects are masked from 'package:stats':
##
##   filter, lag
##
## The following objects are masked from 'package:base':
##
##   intersect, setdiff, setequal, union
df %>% filter(V1 == "I") %>% nrow()
## [1] 1342
```

Task 4

(1 point)

Apply the `filter()` function from `tidyverse` to select only rows where gender is infant or male, and print the number of records.

```
# CODE HERE
df %>% filter(V1 %in% c("M","I")) %>% nrow()

## [1] 2870
```

Task 5

(1 point)

Call the `table()` function on the abalone genders to find out how many of each gender are present.

Print the result.

```
# CODE HERE
table(df$V1)

##
##      F      I      M
## 1307 1342 1528
```

Task 6

(1 point)

Compute the mean value of column 2 (V2) grouped by gender.

V2 is the longest shell measurement.

Requirements: use the `%>%` operator to chain commands, and the `group_by()` and `summarize()` functions.

```
# CODE HERE
df %>% group_by(V1) %>% summarize(mean(V2))

## # A tibble: 3 x 2
##   V1      'mean(V2)'
##   <chr>          <dbl>
## 1 F              0.579
## 2 I              0.428
## 3 M              0.561
```

Task 7

(1 point)

Compute the MEDIAN value of longest shell measurement for only the males.

Requirements: use the `%>%` operator to chain commands.

```
# CODE HERE
df %>% filter(V1 == "M") %>% summarize(median(V2))

##   median(V2)
## 1         0.58
```