

a	C/L of road
Asph ww	Asphalt walkway
bb	Bottom of bank
bch	BC Hydro vault
bctbx	BC Tel box
bmh	Bell manhole
bsmt	Basement elevation
Bt	Bank top (use for ditch bank top as well)
cb	Catch Basin (rectangular)
chk	'Check' Shot on any know point (use for any check shot ie. chk 100)
Conc pad	Concrete pad
Conc ww	Concrete walkway
CONP	Concrete Post set
cr/ cbr	Round Catch Basin
cp	Capped post set
CSE	Catch basin side entry
Inv(size)	Invert, type, pipe size ex.(Invconc30)(invpvc30) (invsteel30)
d	Storm MH
db	Ditch bottom
dt	Ditch Top
dic	Storm rim inspection chamber(IC)
Dt/db	Ditch centerline or bottom
Ea, ec	Edge of asphalt, Edge of concrete
F/ mf	Floor shot/ main floor elev
flag	Flagging shot
fdn	Foundation shot
Fh/hyd	Fire hydrant
g	Ground shot
gv	Gas valve
guy	Guy wire/ anchor for power pole
h	House/building-this is usually on exterior siding(not foundation shots)
hbx	Hydro box
hmh	Hydro manhole
hw	Head wall
hwm	High water mark
hv	Hydro vault
IC	Unknown Inspection chamber(not sure sanitary or storm)
icv	Irrigation control valve
Inv	Invert type size (ex. INV conc 10, Inv pvc 10, Inv steel 10)Leave space after INV!
ip	Iron pin SET
K	Sidewalk
Ld/letdown	Curb letdown
ls	Lamp standard
lp	Lead Plug SET
mh	Manhole miscellaneous(unknown)
mmh	Manhole miscellaneous(unknown)
muv	Misc. utility vault
mv	Misc. valve
mw	Monitoring well
oap	Aluminum pin found
ocl	Closure point
OIP	Iron pin found
OIPNS	Non standard pin(pipe, round) Include diameter IN notes and picture for non standard pins
OIPB	BENT PIN-BASE TIE
omag	Mag nail hub (no tag)
OCN/OCNT	Concrete nail with tag leave space after (ex. Ocn 2345) or (ocnt 2345)

[illegible]

Use coding to differentiate different sides

Ex. EA, EA1 U, U1, K, K1 etc.

Z Prefix (Line)

Z indicates that all points with identical descriptions beginning with Z are to be connected in order of increasing point number. The first point which has the description without the Z prefix, will terminate the sequence. For example, in the following sequence:

Point# Description

- 1 ZSIB
- 2 ZSIB
- 3 ZCURB
- 4 ZSIB
- 5 ZCURB
- 6 SIB
- 7 ZCURB
- 8 ZCURB
- 9 CURB

lines would be drawn from 1 to 2 to 4 to 6 (because the codes all contain "SIB"), and from 3 to 5 to 7 to 8 to 9 (because the codes all contain "CURB"). Point 6 terminated the SIB line because the description didn't contain a leading "Z". Likewise, point 9 terminated the CURB line because the description didn't contain a leading "Z".

The power of this scheme is that many different lines may be specified simultaneously by using different descriptions together with the Z prefix.

X Prefix (Curve)

X identifies points shot on a curve. X-points are connected by curves, with lines connecting the last Z-point to the first X-point and the last X-point to the next Z-point. This is useful for topographic pickup of existing ground for rebuilding or planning. For example, in the sequence:

Point# Description

- 1 ZCURB
- 2 ZCURB
- 3 XCURB
- 4 XCURB
- 5 XCURB
- 6 ZCURB
- 7 CURB

all seven points would be connected in sequence, but points 3-5 would lie on curves.

Y Prefix (Sideshot)

Y identifies sideshot connections. A Y-point will be connected to the last Z- or X-point, but without interrupting the Z/X sequence. For example, in the sequence:

Point# Description

- 1 ZFENCE
- 2 ZFENCE
- 3 YFENCE
- 4 ZFENCE
- 5 FENCE

lines would be drawn from 1 to 2 to 4 to 5, and from 2 to 3.

. Prefix (Close Figure)

The "." will connect the current line back to the first point and the stop the line. For example drawing a building perimeter:

Point# Description

- 25 ZBUILDING
- 26 ZBUILDING
- 32 ZBUILDING
- 33 .BUILDING

This would start at the first corner and join the