

METROVAN QUICKGUIDE for Captivate

Support Toll Free: (855) 414-9453

The followings are the procedures for setting the rover up using the Network GSM/UTMS/GPRS cell network in your area. You will be set to connect to the either NETWORK solution or Nearest solution using MetroVan's GNSS service in your working area.

1. Have your SIM card inserted to CS20 Controller.

2. From the Main Menu, tap **SETTINGS** then **CONNECTIONS, ALL OTHER CONNECTIONS**. Ensure you are in the **CS** connections tab, highlight the **CS Internet** and press **F3 (EDIT)**.
 - 2a. Check *Use Internet connection on CS*. Choose the correct Port (Connect using **CS MODEM**, ensure the *Device* is the Cinterion 3.5G Modem, *Connect to internet using* **Mobile DATA**, and leave *Use user IP & password* unchecked.
Press **OK**
 - 2b. Highlight the **CS Internet** line again and press **F4 (Control)**. Enter the appropriate APN: Bell: *inet.bell.ca*, Telus: *isp.telus.com*, Rogers: *internet.com*. APN and other providers may vary, please check with them to see if APN has changed.
Press **OK**

3. The CS controller modem should now be initialized and you should be connected to the Internet. Please make sure the @ symbol, top right hand corner has no exclamation mark.

4. Page to the **GS** connections tab, Highlight the RTK rover line and press **F3 (Edit)** to configure the RTK Rover settings:
 - 4a. Receive RTK Data: Check
Connect using: **CS Internet 1**, RTK Device: *Internet*
RTK data format: **RTCMV3**
User auto coordinate system, automatically connect: **Uncheck**; Receiver RTK net information: **Show only**
 - 4b. Sensor at base: Automatically detect
Antenna at base: Automatically Detect
RTK base is sending unique ID: uncheck
 - 4c. Use RTK network: Check
Network type: **i-MAX – for network solution**, **Nearest – closest station**
 - 4d. Press **GGA**, and ensure GGA position to send: **Automatically**.
Press **OK**

5. Continue to Highlight the **RTK rover** press **F4 (Control)**. Internet port is set to CS internet 1, then create or select a *Server to use*:
 - 5a. Server to use: Press the ">"
 - 5b. If already created, highlight the correct Server to use (note IP and Port)
 - 5c. To create a new server, press **F2 (New)**
 - 5d. Server name: **MetroVan**,
Address: **gps.metrovancouver.org**.
Port: **9010**
 - 5e. Page other NTRIP tab, *Use NTRIP with this server* is checked
NTRIP user ID: Enter in your personal User ID provided by MetroVan
NTRIP password: Enter in password provided by MetroVan
Press **Store**, then **OK** to return to Internet Port Connection page.
 - 5g. In the Internet Port Connections, Press **F5 (Source)** to pull down a source table.
Select **IMAX_MSM** to use Network solution, or **NEAR_MSM** to connect to nearest station.
Press OK's to return to Main menu:

METROVAN QUICKGUIDE for Captivate
Support Toll Free: (855) 414-9453

<

- Tap the Cellphone icon at the Toolbar, press **Start RTK stream** to connect.