

Preparing Touch Client for USB Deployment

This guide explains how to prepare the Touch Client application for USB deployment.

Prerequisites

1. Development Environment

- macOS or Linux system
- Node.js 20.x installed
- pnpm installed
- Docker installed

Steps to Prepare USB Package

1. Clone and Build Project

```
# Clone the repository
git clone <repository-url> touch-monorepo
cd touch-monorepo

# Install dependencies
pnpm install

# Build the project
pnpm build
```

2. Create Initial Database

```
# Initialize SQLite database
pnpm db:setup
```

3. Test Docker Build

```
# Build Docker image locally
docker-compose build

# Test the build
docker-compose up
```

Verify the application works at `http://localhost:3000`

4. Prepare USB Drive

- Format USB drive (minimum 8GB recommended)
- Name it "TOUCH_CLIENT" for consistency

5. Copy Files to USB

Copy the following to your USB drive:

```
touch-monorepo/  
├─ apps/  
├─ packages/  
├─ data/           # Contains SQLite database  
├─ Dockerfile  
├─ docker-compose.yml  
├─ .dockerignore  
├─ package.json  
├─ pnpm-lock.yaml  
└─ docs/  
    └─ DOCKER-CLIENT-SETUP_EN.md  
        └─ DOCKER-CLIENT-SETUP_ES.md
```

6. Test USB Deployment

- Eject and reinsert USB drive
- Follow instructions in `DOCKER-CLIENT-SETUP_EN.md` to verify everything works
- Test both application startup and data persistence

Important Notes

1. Files to Exclude

- `.git` directory
- `node_modules` directories
- Any environment files (`.env`, etc.)
- Build artifacts (unless specifically needed)

2. Database

- Ensure `data/` directory exists and contains initial SQLite database
- Test database connectivity before distributing

3. Documentation

- Include both English and Spanish setup guides
- Ensure all paths and commands in documentation match the USB structure

Verification Checklist

- ☐ All necessary files copied to USB
- ☐ Docker builds successfully from USB
- ☐ Application runs correctly from USB
- ☐ Database persists between restarts
- ☐ Both language versions of documentation present
- ☐ USB has sufficient free space for Docker images and data