RDP Auto-Unlock Script Kullan■m K■lavuzu

Bu k■lavuz, Windows sistemlerde RDP ba■lant■s■ kesildikten sonra otomatik olarak kilit ekran■n■ kald■ran PowerShell script'inin nas■l kurulaca■■n■ ve yap■land■r■laca■■n■ aç■klar.

1. Amaç

RDP oturumu kapand■■■nda (Disconnect durumu), Windows makinenin ana ekran■ kilitli kal■r. Bu script, RDP oturumu kesildi■i anda 'tscon' komutunu çal■■t■rarak bu kilidi otomatik kald■r■r.

2. Gereksinimler

• Windows 10 veya üzeri i■letim sistemi
• Yönetici (Administrator) yetkileri
• PowerShell 5.1 veya uyumlu sürüm (Windows varsay■lan■)
• Task Scheduler eri■imi

3. Kurulum Ad■mlar■

1■■ `C:\Scripts` klasörünü olu■turun.
2■■ A■a■■daki script kodunu `switch_console_debug.ps1` ad■yla kaydedin.
3■■ Script dosyas■na sa■ t■klay■p **Properties → Unblock** seçene■ini i■aretleyin.
4■■ Yönetici PowerShell aç■n ve script'i test edin:
```powershell powershell.exe -NoProfile -ExecutionPolicy Bypass -File "C:\Scripts\switch_console_debug.ps1" "user" ```
5■■ 'user' yerine kendi Windows kullan■c■ ad■n■z■ yaz■n.

4. Task Scheduler Ayarlar■

1■■ **Task Scheduler** (Görev Zamanlay■c■) uygulamas■n■ aç■n.
2■■ **Create Task** seçene■ini seçin.
3■■ **General** sekmesinde:
• Name: `RDP Auto-Unlock`
• Run with highest privileges i■aretli olsun.
4■■ **Triggers** sekmesinde → **New** → Begin the task: *On disconnect from user session* seçin.
5■■ Specific user: RDP ba■lant■s■ yapt■■■n■z kullan■c■y■ seçin.
6■■ **Actions** sekmesinde → **New** → ■u ■ekilde ayarlay■n:

Program/script	powershell.exe
Add arguments	-NoProfile -ExecutionPolicy Bypass -File "C:\Scripts\switch_console_debug.
Start in (optional)	C:\Scripts
```

7■■ **Conditions** ve **Settings** sekmelerinde herhangi bir k■s■tlama eklemeyin.

8■■ Görevi kaydedin. Art■k her RDP ba■lant■s■ kesildi■inde script otomatik çal■■■r.

5. Script Kodu

```
<#
  switch_console_debug.ps1
  - Diagnostic + robust RDP-to-console switcher (only runs when session is Disconnected)
  - Saves full dumps of query session/qwinsta/quser/query user
  - Detects numeric session ID and runs tscon <id> /dest:console only when state=Disc
  - Run as Administrator for reliable results
#>

param([Parameter(Mandatory=$true)][string]$TargetUser)

$baseDir = "C:\Scripts"
if (-not (Test-Path $baseDir)) { New-Item -Path $baseDir -ItemType Directory | Out-Null }

$logFile  = Join-Path $baseDir "switch_console_debug.log"
$dumpFile = Join-Path $baseDir "switch_console_dump.txt"

function Log($m) {
  $t = Get-Date -Format "yyyy-MM-dd HH:mm:ss"
  "$t  $m" | Out-File -FilePath $logFile -Append -Encoding UTF8
}

function DumpCommand($name, $cmd) {
  Log "=== Dump start: $name ==="
  $out = & $cmd 2>&1
  "$name OUTPUT:" | Out-File -FilePath $dumpFile -Append -Encoding UTF8
  $out | Out-File -FilePath $dumpFile -Append -Encoding UTF8
  Log "=== Dump end: $name (lines: $($out.Count)) ==="
  return ,$out
}

Log "===== DEBUG SCRIPT START for user='$TargetUser' ====="
"Time: $(Get-Date)" | Out-File -FilePath $dumpFile -Append -Encoding UTF8

$q1 = DumpCommand "query session" { query session }
$q2 = DumpCommand "qwinsta"       { qwinsta }
$q3 = DumpCommand "quser"         { quser }
$q4 = DumpCommand "query user"    { query user }

$allLines = @()
$allLines += $q1 + $q2 + $q3 + $q4

function TryExtractId($line, $user) {
  if (-not $line -or $line -notmatch [regex]::Escape($user)) { return $null }
  $s = $line.Trim()
  if ($s -match '^(rdp-tcp[#\d]*\S*)\s+(\S+)\s+(\d{1,4})\s+(Active|Disc)\b') {
    return @{ Id=$matches[3]; Session=$matches[1]; State=$matches[4]; Raw=$s }
  }
  if ($s -match '(\d{1,4})\s+(Active|Disc)\b') {
    return @{ Id=$matches[1]; Session="(unknown)"; State=$matches[2]; Raw=$s }
  }
```

```
  $nums = [regex]::Matches($s, '\d+')
  foreach ($n in $nums) {
    $val = [int]$n.Value
    if ($val -ge 1 -and $val -le 1024) {
      return @{ Id = $val.ToString(); Session="(fuzzy)"; State="Unknown"; Raw=$s }
    }
  }
  return $null
}

$found = $null
foreach ($line in $allLines) {
  if ($line -match '\bDisc\b' -and $line -match [regex]::Escape($TargetUser)) {
    $try = TryExtractId $line $TargetUser
    if ($try) { $found = $try; break }
  }
}

if (-not $found) {
  foreach ($line in $allLines) {
    if ($line -match '\bActive\b' -and $line -match [regex]::Escape($TargetUser)) {
      $try = TryExtractId $line $TargetUser
      if ($try) { $found = $try; break }
    }
  }
}

if (-not $found) {
  foreach ($line in $allLines) {
    if ($line -match [regex]::Escape($TargetUser)) {
      $try = TryExtractId $line $TargetUser
      if ($try) { $found = $try; break }
    }
  }
}

if (-not $found) {
  Log "No candidate session line matched. Exiting."
  exit 0
}

$id = $found.Id
Log "Candidate found -> ID=$id, State=$($found.State)"

if ($found.State -ne "Disc") {
  Log "Session not Disc, skipping tscon."
  exit 0
}

if ($id -match '^\d+$') {
  Log "Running tscon $id /dest:console ..."
  Start-Process -FilePath "tscon.exe" -ArgumentList "$id /dest:console" -Wait -NoNewWindow
  Log "tscon succeeded for session $id."
} else {
  Log "Invalid session ID '$id'. Exiting."
}
Log "===== DEBUG SCRIPT END ====="
```

6. Test Etme

1■■ RDP ile ba■lan■n, ard■ndan ba■lant■y■ kapat■n. 2■■ 5–10 saniye içinde kilit ekran■ otomatik kalkmal■d■r. 3■■ Test sonras■ `C:\Scripts\switch_console_debug.log` ve `switch_console_dump.txt` dosyalar■na bakarak do■ru çal■■t■■■n■ do■rulayabilirsiniz.

7. S■k Kar■■la■■lan Sorunlar

Sorun	Çözüm
Script hiç çal■■m■yor	Task Scheduler tetikleyicisini 'On disconnect from user session' olarak ayarlad■■■n■zdan em
tscon yetki hatas■	Script yönetici (Run as Administrator) olarak çal■■mal■d■r.
Kilidi açm■yor	Kullan■c■ ad■ parametresi do■ru yaz■ld■■■ndan emin olun ('user' yerine kendi ad■n■z■ y

© 2025 - RDP Auto-Unlock Setup Guide. Haz■rlayan: ChatGPT (GPT-5)