

Reference

Setting Different Styles for Elements

Values and units

Setting styles for:

Font

Text

Color

List

Table

Form

Values and Units

■ Value Type

- Number
- Length: A measurement of distance

Relative Lengths, which vary depending on the computer being used. It is generally used in screen style sheets.

| Unit | Name | What it is | example |
|------|----------|--|---------|
| em | EM | Relative to width of the letter M for the font | 3em |
| ex | x-height | Relative to height of the lowercase x of the at font | 5ex |
| px | Pixel | Relative to the monitor's resolution | 12px |

Values and Units

■ Value Type

Absolute Lengths, which remain constant regardless of the hardware and software being used. It is generally used in print style sheets.

| Unit | Name | What it is | example |
|------|-------------|---------------|---------|
| pt | Point | 72pt = 1inch | 12pt |
| pc | Picas | 1pc = 12 inch | 3pc |
| mm | Millimeters | 1mm = .24pc | 25mm |
| cm | Centimeters | 1cm = 10mm | 5.1cm |
| in | Inches | 1in = 2.54cm | 8.25in |

Values and Units

■ Value Type

- Color: A chromatic expression

| Format | What it is | example |
|-----------------|--|---------------------|
| #RRGGBB | Red, green and blue hex-code value of a color (00-99, AA-FF) | #CC33FF or #C3F |
| rgb(R#, G#, B#) | Red, green and blue numeric-values of a color (0-255) | rgb(204, 51, 255) |
| rgb(R%, G%, B%) | Red, green and blue percentage values of a color (0-100%) | rgb(81%, 18%, 100%) |
| <name> | The name of the color | Purple |

- Percentage: A proportion

Adding Comments to CSS

- Like any other part of an HTML document, CSS can have comments.
- A comment does not affect code.
- It only adds notes or gives guidance to anyone viewing your code.

`/* ... */`

```
1  /* Global Styles */
2  h1 {
3      color: #CCFF99;
4      font-size: 1.5em; }
5
6  /* Class Styles */
7  .subHeader {
8      color: #3366CC;
9      font-size: .8em; }
10
11 /* ID Styles */
12 #pageContent {
13     color: #003366;
14     font-size: .75em; }
```

A decorative L-shaped line in a gold color, consisting of a horizontal segment and a vertical segment meeting at a right angle.

Font

A single horizontal line in a gold color, positioned below the word "Font".


Font Properties

- **The fonts you use help to send your (the designer's) message across**
 - **The appearance of fonts help authors guide a visitor's eye around the page.**
 - **Common Techniques**
 - Choosing a Font Family
 - Setting the Font Size
 - Making Text Italic
 - Setting Bold
 - Creating Small Caps
 - Setting Multiple Font Values
-

Choosing a Font Family

- More than one font can be specified, in case the first is not available in your visitor's system.
- Some common font styles are: *Serif*, *Sans-serif*, *Cursive*, *Fantasy*, and *Monospace*.
- Browser-Safe Fonts
<http://www.webbedenvironments.com/dhtml/downloads/BrowserSafeFonts.pdf>

font-family: font1, font2 ...



Choosing a Font Family

7_Fonts.html

```
9         <title>ABC Banking Corporation Limited</title>
10         <link rel="stylesheet" href="../../styles/7_Fonts.css" type="text/css"
      media="all" />
11     </head>
12     <body>
```

Link an external CSS

7_Fonts.css

```
1  /* Global Styles */
2  body {
3      font-family: Verdana, Arial, Helvetica, sans-serif; }
```

Define style for HTML tags


Setting the Font Size

- **The size of the text on the screen can be specified.**
- **Fonts can be set as**
 - ***Absolute Size Keyword:*** It refers to an entry in a table of font sizes computed and kept by the user agent.
[xx-small | x-small | small | medium | large | x-large | xx-large]
 - ***Relative Size Keyword:*** It is interpreted relative to the table of font sizes and the font size of the parent element.
[larger | smaller]
 - ***Length:*** It specifies either an absolute font size (that is independent of the user agent's font table), or a relative font size.
 - Absolute Length Unit [in | cm | mm | pt (point - 1/72 inch) | pc (pica - 12 pt)]
 - Relative Length Unit [em (16px on screen?) | ex (lower case x) | px]
 - ***Percentage:*** It specifies an absolute font size relative to the parent element's font size.

Setting the Font Size

- To enhance the usability and accessibility of your page
 - Avoid small size of content (use 1em or 100% as a basic for your font sizes)
 - Avoid absolute length units for screen display (use *em* or *percentage* for screen stylesheets)
 - Use absolute length units for print stylesheets
 - Go to W3C: Care with Font Size <http://www.w3.org/QA/Tips/font-size> for details.

font-size: size



Setting the Font Size

8_FontSize.css

```
1  /* Global Styles */
2  body {
3      font-family: Verdana, Arial, Helvetica, sans-serif;
4      font-size: 1em; }
5
6  h1 {
7      font-size: 1.5em; }
8
9  h2 {
10     font-size: .9em; }
11
12 h3 {
13     font-size: 1.2em; }
14
15 h4 {
16     font-size: .8em; }
```

Use a semicolon (;) to separate individual declarations in the list


For consistent and versatile page viewing, the best strategy for setting font sizes is to set a relative length size for the <body> tag, and then use absolute font size (such as small) or relative font sizes (such as larger) to adjust the size, based on the body size.

Making Text Italic

- **Italic Font** – It is redesigned with more pronounced serifs and usually a slight slant to the right.
- **Oblique Font** – It is slanted to the right by the computer.
- **Both of them are often used to set off quotations, emphasized text, foreign words, magazine, and much more.**

font-style: italic

font-style: oblique




Making Text Italic

9_TextItalic.html

```
9          <title>ABC Bank</title>
10          <link rel="stylesheet" href="../../styles/9_TextItalic.css" type="text/css"
media="all" />
11      </head>
...      ...
31      <p> <span class="subHeader">Feature:</span> <br /> (1) Forward dated
instructions up to 45 days in advance <br /> (2) Access Bill Payment 24-hour a day
with our online banking </p>
```

9_TextItalic.css

```
25  /* Class Styles */
26  .subHeader {
27      font-size: .8em;
28      font-style: italic; }
```




Define style for classes

Setting Bold

- It is used to set different levels of boldness for text.
 - *bold*: Set the font to boldface
 - *bolder or lighter*: Set the font's weight to be bolder or lighter relative to its parent element's weight
 - *A value from 100 to 900, increments of 100*: Increase the weight, based on alternative versions of the font that are available.
- It is an effective way to make text standout.

font-weight: bold



Setting Bold


10_TextBold.css

```
15  h4 {  
16      font-size:.8em;  
17      font-weight: bold; }  
18  
    ...  
26  /* Class Styles */  
27  .subHeader {  
28      font-size: .8em;  
29      font-style: italic;  
30      font-weight: bold;}
```

Creating Small Caps

- Small caps are useful for emphasizing titles.
- With small caps, lowercase letters are converted to uppercase, but in a slightly smaller size than regular uppercase letters.

font-variant: small-caps



Creating Small Caps

11_TextSmallCaps.css

```
15 h4 {  
16     font-size:.8em;  
17     font-weight: bold;  
18     font-variant: small-caps; }  
  
    ...  
27 /* Class Styles */  
28 .subHeader {  
29     font-size: .8em;  
30     font-style: italic;  
31     font-weight: bold;}
```

Setting Multiple Font Values

- Instead of setting font properties independently, several font attributes can be defined simultaneously in a single declaration.
- The font-style, font-variant, and font-weight properties may be specified in any order or omitted. If they are omitted, they are set to normal.
- The font-size and font-family properties must always be explicitly specified, first the font-size, then the font-family.

```
font: [<font-style> || <font-variant> || <font-weight>]?  
<font-size> [ / <line-height>]? <font-family>
```

Setting Multiple Font Values

12_MultipleFontValue.css

```
2  body {
3      font: 1em Arial, Helvetica, sans-serif; }
4
5  h1 {
6      font-size:1.5em; }
7
8  ...
9
14 h4 {
15     font: small-caps bold .8em Verdana, Arial, Helvetica, sans-serif;
16 }
17
18 ...
19
24 /* Class Styles */
25 .subHeader {
26     font: italic bold .8em Verdana, Arial, Helvetica, sans-serif; }
```

A decorative L-shaped line in a gold color, consisting of a horizontal segment and a vertical segment meeting at a right angle.

Text

A horizontal line in a gold color, positioned below the word 'Text'.

Text Properties


- **Besides the shapes and sizes of the letters being used (the font), the spaces between letters, words, lines, and paragraphs are also important.**
- **The challenge of displaying text on a computer screen is to support a wider audience.**
 - How to enhance legibility?
 - How to draw their interest?
- **Common Techniques**
 - Adjusting Spacing
 - Aligning Text
 - Indenting Paragraphs
 - Decorating Text

Adjusting Spacing

■ Space Between Letters (Tracking)

- ❑ It adds equal space between letters in a word.
- ❑ Appropriated letter spacing can improve the readability of the text.

letter-spacing: <value>



Adjusting Spacing

13_LetterSpacing.css


```
2  body {
3      font: 1em Verdana, Arial, Helvetica, sans-serif;
4      letter-spacing: normal; }
5
6  h1 {
7      font-size: 1.5em;
8      letter-spacing: .2em; }
9
10 h2 {
11     font-size: .9em;
12     letter-spacing: .4em; }
13
14 h3 {
15     font-size: 1.2em;
16     letter-spacing: .2em; }
```


Adjusting Spacing

■ Space Between Lines (Leading)

- It adds space between the baselines (the bottoms of most letters) of lines of text.
- Appropriated line spacing can make reading easier.

line-height: <value>



Adjusting Spacing

13_LineHeight.css

```
2  body {
3      font: 1em Verdana, Arial, Helvetica, sans-serif;
4      letter-spacing: normal;
5      line-height: 100%; }
6
7  h1 {
8      font-size: 1.5em;
9      letter-spacing: .2em;
10     line-height: 2.0; }
11
12  h2 {
13      font-size: .9em;
14      letter-spacing: .4em;
15     line-height: 18px; }
```

Aligning Text

■ Horizontal

- Alignment and justification of the text can be controlled.
[left | right | center | justify]

text-align: <value>


■ Vertical

- The vertical position of one inline element can be specified, relative to the elements around it, either above or below.

Definition List: [super | sub | baseline | <length> | <percentage>]

Relative Values: [top | middle | bottom | text-top | text-bottom]

vertical-align: <value>



Aligning Text

14_TextAligning.css


```
2  body {
3      font: 1em Verdana, Arial, Helvetica, sans-serif;
4      letter-spacing: normal;
4      line-height: 100%;
6      text-align: left; }

    ..
32 /* ID Styles */
33 #footer {
34     font-size:.6em;
35     text-align: right; }
36
```

Indenting Paragraphs

- Extra horizontal space can be specified at the beginning of the first line of text in a paragraph.
- Indenting is commonly used for the printer-friendly versions of your page.

text-indent: <value>



Indenting Paragraphs

15_ParagraphIndenting.html

```
9    <title>ABC Banking Corporation Limited</title>
10    <link rel="stylesheet" href="../styles/15_ParagraphIndentingScreen.css"
      type="text/css" media="screen" />
11    <link rel="stylesheet" href="../styles/15_ParagraphIndentingPrint.css"
      type="text/css" media="print" />
12    </head>
```

Link another style sheet for printing


15_ParagraphIndentingPrint.css

```
28  p {
29      font-size: .75em;
30      line-height: 1.5;
31      text-indent: 2em; }
```

Decorating Text

- The text can be adorned.
Value: [underline | overline | line-through | blink | none]
- It is used to add emphasis, and attract the visitor's eye to important areas on your web page.
- Many visitors do not like blinking text, especially on web pages, where they spend a lot of time.
- The underline in hypertext links can also be removed by setting text-decoration: none.

text-decoration: <value>



Decorating Text

16_TextDecorating.css

```
1  /* Global Styles */
2  body {
3      font: 1em Verdana, Arial, Helvetica, sans-serif;
4      letter-spacing: normal;
5      line-height: 100%;
6      text-align: left;
7      text-decoration: none; }
8
9  ...
10
29  p {
30      font-size: .75em;
31      line-height: 1.5; }
32
33  a {
34      text-decoration: none;
```



A decorative L-shaped line in a gold color, consisting of a horizontal segment and a vertical segment meeting at a right angle.

Color

A horizontal line in a gold color, positioned below the word "Color".

Color & Background Properties

- Color forms the cornerstone of all design, creating the first impression that most people will have of your site.
- Color can guide the visitor's eye around the page, helping you to highlight important areas, while downplaying others.
- Color can be used in the different components.



Color & Background Properties

- ❑ Page background
 - It covers the entire visible area of the browser window.
 - The background should generally provide the most contrast with the foreground text colors.
 - ❑ Content background
 - Different color will be used for the background directly around the content of the pages.
 - This allows the page background color to absorb extra horizontal space in the browser window.
 - ❑ Border/Rule
 - Rulers or contrasting colors will be used around the borders of content areas, headers, navigation blocks, lists, and tables to separate different chunks of content.
 - ❑ Header
 - Color for the section headers clearly contrasts with chosen background color.
-

Color & Background Properties

- ❑ Content (Sentences or Paragraphs of Text)
 - It should have the highest contrast with the background to maximize legibility.
- ❑ Link/Navigation
 - Different colors may be chosen for your site navigation and for links in the copy.
 - The link colors should be easily discernable from other text while still contrasting the background.
- ❑ Link/Table
 - Different background color may be chosen behind lists and tables (or even alternating row colors).
- ❑ Form
 - The border, foreground, and background colors of many form elements can be specified to give them a more distinctive look for your site, apart from the default appearance.

Color & Background Properties

■ **Critical Consideration with Color**

- Web Safe Colors (for people who use 8-bit monitors)
 - It refers the set of colors that both Mac and Windows computer could consistently display (a 216 color subset of the 256).
 - <http://www.cookwood.com/html/colors/websafecolors.html>
- Accessibility (for people who are color-blind)
 - Your web page should
 - Provide enough contrast between foreground and background colors.
 - Make sure that color is not critical for understanding information.
 - W3C Web Content Accessibility Guidelines
<http://www.w3.org/TR/WAI-WEBCONTENT/>

Color Combinations

Unfavorable Blue/Green, Red/Green

Preferable Red/Blue, Orange/Blue, Orange/Purple, Yellow/Purple

Setting (Foreground) Color

- The foreground color (simply means color) of an element can be set.
- Value for the color
 - Name of a color (16-predefined color)
<http://www.cookwood.com/html/colors/sixteencolors.html>

color: [black | blue | gray | ...]

- RGB value set
 - Percentages,


color: rgb (x%, y%, z%)

- Values from 0-255

color: rgb (x, y, z)

- Hexadecimal Code

color: #999999



Setting (Foreground) Color

17_ColorForeground.css

2 body {

...

8 **color: #003366;** }

9

10 h1 {

...

14 **color: #CF9;** }

15

16 h2 {

...

20 **color: rgb(100%, 60%, 20%);**

21

22 h3 {

...

26 **color: rgb(51, 102, 204);** }

#003366 / #036 /
rgb (0%, 10%, 40%) /
rgb(0, 51, 102)

Specific each value only once when specifying hex RGB values in which both color value numbers are the same.

#CCFF99 / #CF9 /
rgb (80%, 100%, 60%) /
rgb(204, 255, 153)

#FF9933 / #F93 /
rgb (100%, 60%, 20%) /
rgb(255, 153, 51)

#3366CC / #36C /
rgb (20%, 40%, 80%) /
rgb(51, 102, 204)

Setting (Foreground) Color : Appearance of Links


#FF6600 / #F60 /
rgb (100%, 40%, 0%) /
rgb (255, 102, 0)

```
38 a {  
39     text-decoration: none;  
40     color: #FF6600;}
```

```
41  
42 a:hover {  
43     color: #3366CC; }
```

Mouse cursor is over the link


#3366CC / #36C /
rgb (20%, 40%, 80%) /
rgb(51, 102, 204)



Setting Background Color

- The background color for entire page and individual elements can be defined.

background-color: <value>



Setting Background Color

18_ColorBackground.html

```
2  body {  
    ...  
9      background-color: #DDEEFF;  
    ...  
47 #mainContainer {  
48     background-color: white;  
49  
50 #header {  
51     background-color: #3366CC;
```

#DDEEFF / #DEF /
rgb (86.67%, 93.33%, 100%) /
rgb (221, 238, 255)

white / #FFFFFF / #FFF /
rgb(100%, 100%, 100%) /
rgb (255, 255, 255)

#3366CC / #36C /
rgb (20%, 40%, 80%) /
rgb(51, 102, 204)



List



Creating Styles for List Items

- **Styles can be applied to the list items directly through a type selector.**

li {

font-size: .75em;

line-height: 1.5;

text-align: left; }




Setting the Bullet Style

- The type of bullet can be specified
- <http://www.w3.org/TR/REC-CSS2/generate.html#propdef-list-style-type>

| Name | Appearance |
|-------------|------------|
| disc | • |
| circle | ○ |
| square | ■ |
| decimal | 1, 2, 3 |
| upper-roman | I, II, III |
| lower-roman | i, ii, iii |
| upper-alpha | A, B, C |
| lower-alpha | a, b, c |

list-style-type: <name>



Setting the Bullet Style


2_BulletStyle.css

```
75  li {  
76      font-size: .75em;  
77      line-height: 1.5;  
78      text-align: left;  
79      list-style-type: square;}
```

Creating Your Own Bullets

- Your own graphics, in GIF, JPEG, and PNG formats, can be used as bullets.

list-style-image: <filename>



Creating Your Own Bullets


2_BulletStyle.css

```
75  li {  
76      font-size: .75em;  
77      line-height: 1.5;  
78      text-align: left;  
79      list-style-type: square; }  
80  
81  li a {  
82      list-style-image: url(../images/mm_arrow.gif); }
```

It is a descendant selector. This style is only applied to the element **<a>**, that is a descendant of a list item ****.

Creating Menu Items with a List


```
28 <!-- Navigation -->
29 <div id="navigation">
30 <ol>
31 <li><a href="#">Deposits</a></li>
32 <li><a href="#">Payments</a></li>
33 <li><a href="#">Transfers</a></li>
34 <li><a href="#">Download</a></li>
35 <li><a href="#">Contact Us</a></li>
36 </ol>
37 </div>
```



Creating Styles for Menu Items: Font, Text & List Style Image

- **Styles can be applied to the list items by applying a descendant selector.**

```
#navigation ol li {  
    font-size: .75em;  
    letter-spacing: .1em;  
    line-height: 1.5;  
    text-align: left;  
    list-style-image:  
url(../images/mm_arrow.gif);
```



Creating Styles for Menu Items: Positioning

- The navigation menu is put to the left hand side of the main content.

#navigation {


padding: 15px 3px;

width: 150px;

float: left; }

#pageContent {


margin: 0px 200px 0px 180px; }



Creating Styles for Menu Items: Link Properties

- **Dynamic pseudo-class selectors** are used to create styles for menu items.
- **When the list item is focused**
 - ❑ Change the font color
 - ❑ Change the background color
 - ❑ Add a bottom border line

```
#navigation ol a:hover {  
    color: #FF6600;  
    background-color: #DDEEFF;  
    border-bottom: 2px solid #C0DFFD; }
```





Table



Creating Styles for a Table

- Styles can be applied to the table either directly through a type selector, or by applying classes or IDs.
- Recalling those *structures* that can help *styling*
 - thead, th, tfoot, tbody, colgp, col

table {

font: .65em Verdana, Arial, Helvetica, sans-serif;

line-height: 1.5;


text-align: center;

color: #003366;

background-color: #FFFFFF;

border: 2px solid #E0E0E0;

}



Creating Styles for a Caption: Font, Text & Color Properties

- **Caption embeds identifying text in a table.**
- **It should contrast the table header and data rows.**

table caption {


font: small-caps bold 1.2em
Verdana, Arial, Helvetica, sans-serif;

letter-spacing: .2em;

color: #FF6600;

background-color: inherit;

padding: 5px; }




Creating Styles for a Caption: Positioning

- The *caption-side* property is used to define the position of a caption, in relation to the table.
- Value: top | bottom | inherit

**** This property may not work in IE ****

caption-side: <value>



Creating Styles for a Header

- The table header cell is used to hold labels that identify the data in a particular column of the table.
- They should contrast the table data rows.

```
table th {  
    color: inherit;  
    background-color: #DDEEFF;  
    padding: 5px 2px;}
```



ABC Banking Corporation Limited - Windows Internet Explorer

http://localhost/C54281/MoreOnHTML/examples/html/

ABC Banking Corporation Limited

ABC Banking Corporation Limited

Online Banking Services

Deposits

Payments

Transfers

Download

Contact Us

Interest Rate

More Kiosk Deposits Deposits Deposits Deposits Deposits

| Deposit Period | HK \$10,000 to HK \$99,999 | HK \$100,000 to HK \$499,999 | HK \$500,000 to HK \$999,999 | HK \$1,000,000 or above |
|----------------|----------------------------|------------------------------|------------------------------|-------------------------|
| 1-day | - | - | - | 2.5000% |
| 1-week | 2.5000% | 2.5000% | 2.5000% | 2.5000% |
| 2-week | 2.5000% | 2.5000% | 2.5000% | 2.5000% |
| 1-month | 2.5000% | 2.5500% | 2.6000% | 2.6500% |
| 2-month | 2.5000% | 2.5500% | 2.6000% | 2.6500% |
| 3-month | 2.5500% | 2.6000% | 2.6500% | 2.7000% |
| 6-month | 2.6000% | 2.6500% | 2.7000% | 2.7500% |
| 9-month | 2.6500% | 2.7000% | 2.7500% | 2.8500% |
| 12-month | 2.7500% | 2.8500% | 2.9500% | 3.0500% |

Copyright. ABC Banking Corporation Limited

Done


Internet

100%

Creating Styles for Table Cells

- Styles can be applied directly to the individual table cells defined by the element `<td>`.

```
table td {  
    padding: 4px; }
```



ABC Banking Corporation Limited - Windows Internet Explorer

http://localhost/C54281/MoreOnXHTML/examples/html/

ABC Banking Corporation Limited

ABC Banking Corporation Limited

Online Banking Services

- Deposits
- Payments
- Transfers
- Download
- Contact Us

Interest Rate

HONG KONG DOLLAR DEPOSIT RATES: FIXED DEPOSIT

| Deposit Period | HK \$10,000 to HK \$99,999 | HK \$100,000 to HK \$499,999 | HK \$500,000 to HK \$999,999 | HK \$1,000,000 or above |
|----------------|----------------------------|------------------------------|------------------------------|-------------------------|
| 1-day | - | - | - | 2.5000% |
| 1-week | 2.5000% | 2.5000% | 2.5000% | 2.5000% |
| 2-week | 2.5000% | 2.5000% | 2.5000% | 2.5000% |
| 1-month | 2.5000% | 2.5500% | 2.6000% | 2.6500% |
| 2-month | 2.5000% | 2.5500% | 2.6000% | 2.6500% |
| 3-month | 2.5500% | 2.6000% | 2.6500% | 2.7000% |
| 6-month | 2.6000% | 2.6500% | 2.7000% | 2.7500% |
| 9-month | 2.6500% | 2.7000% | 2.7500% | 2.8500% |
| 12-month | 2.7500% | 2.8500% | 2.9500% | 3.0500% |

Copyright ABC Banking Corporation Limited

Done Internet 100%


Creating Styles for Table Rows: Color

- Data cells are organized into rows using the element `<tr>`.
- Rows styles can be created by using type selector `<tr>`.
- Specialized row styles can be created by using classes to alternate styles between rows.

```
table tbody tr.evenRow {
```

```
    color: inherit;
```

```
    background-color: #E0E0E0;}
```



ABC Banking Corporation Limited - Windows Internet Explorer

http://localhost/CS4281/MoreOnXHTML/examples/html/

ABC Banking Corporation Limited

ABC Banking Corporation Limited

Online Banking Services

- Deposits
- Payments
- Transfers
- Download
- Contact Us

Interest Rate

HONG KONG DOLLAR DEPOSIT RATES: FIXED DEPOSIT

| Deposit Period | HK \$10,000 to HK \$99,999 | HK \$100,000 to HK \$499,999 | HK \$500,000 to HK \$999,999 | HK \$1,000,000 or above |
|----------------|----------------------------|------------------------------|------------------------------|-------------------------|
| 1-day | - | - | - | 2.5000% |
| 1-week | 2.5000% | 2.5000% | 2.5000% | 2.5000% |
| 2-week | 2.5000% | 2.5000% | 2.5000% | 2.5000% |
| 1-month | 2.5000% | 2.5500% | 2.6000% | 2.6500% |
| 2-month | 2.5000% | 2.5500% | 2.6000% | 2.6500% |
| 3-month | 2.5500% | 2.6000% | 2.6500% | 2.7000% |
| 6-month | 2.6000% | 2.6500% | 2.7000% | 2.7500% |
| 9-month | 2.6500% | 2.7000% | 2.7500% | 2.8500% |
| 12-month | 2.7500% | 2.8500% | 2.9500% | 3.0500% |

Copyright, ABC Banking Corporation Limited

Done Internet 100%

Creating Styles for Table Rows: Alternative Rows


- Styles can be created to the :hover dynamic pseudo-class selector.
- Each row highlights independently when the visitor rolls over the table.

table tbody tr:hover {

color: inherit;

background-color: #FFFFAE;

cursor: pointer;}





Form



Creating Form Structures for Styling

- The `<fieldset>` element can be used to group related elements together and make the form easier to follow.
- The easier it is for visitors to understand the form, the more likely they are to fill it out correctly.
- The `<legend>` element can be used to provide a caption or description for the group of elements.

```
<fieldset>  
  <legend> ... </legend>  
  ... related elements ...  
</fieldset>
```

The screenshot shows a web browser window titled "ABC Banking Corporation Limited - Windows Internet Explorer". The address bar shows "http://localhost/CS4281/MoreOnXHTML/examples/htmlCode". The page content is titled "Contact Us" and includes the instruction "Please complete and submit the following form. All fields are required." The form is divided into two sections, each enclosed in a green border and labeled on the right as "Group 1" and "Group 2".

Group 1: Personal Information

Title: ☒ Mr ☐ Mrs ☐ Ms
Last name:
First name:
Contact number:
Email address:
To be contacted: ☒ By Phone ☐ By Email

Group 2: Message

Category:

Questions/Feedback:

Creating Form Structures for Styling

Screen

ABC Banking Corporation Limited - Windows Internet Explorer

http://localhost/CS4281/MoreOnXHTML/examples/htmlCode

ABC Banking Corporation Limited

Contact Us

Please complete and submit the following form. All fields are required.

Personal Information

Title: ☒ Mr ☐ Mrs ☐ Ms

Last name:

First name:

Contact number:

Email address:

To be contacted: ☒ By Phone ☐ By Email

Message

Category: Deposits

Questions/Feedback:

XHTML Code Design (Organizing)

FieldSet: Personal Information

| | | | | | | |
|-------------|------------------|-------------|------------------|-------------|---------------|-------------|
| Text | Radio1 | Text | Radio2 | Text | Radio3 | Text |
| Text | TextBox1 | | | | | |
| Text | TextBox2 | | | | | |
| Text | TextBox3 | | | | | |
| Text | TextBox4 | | | | | |
| Text | Checkbox1 | Text | Checkbox2 | Text | | |

FieldSet: Message

| | |
|-------------|------------------|
| Text | ListBox1 |
| Text | TextArea1 |

Button1 **Button2** **Button3**

Creating Form Structures for Styling

```
43  <fieldset>
44      <legend> Personal Information </legend>
45      <p>
46
47          Title:
48          <input type="radio" id="mr" name="title" value="Mr" checked="checked" />Mr
49      ...
70  </fieldset>
71  ...
74  <fieldset>
75      <legend> Message </legend>
76      <p>
77
78          Category:
79          <select id="category" name="category">
80      ...
90  </fieldset>
```


Labeling Form Elements

- The `<label>` elements can be used to mark up label text.
- The `for` attribute can be specified to link labels to the associated elements.
- CSS can be used to format labels. (It will be discussed later.)

```
<label for="idname">  
  ... label ...  
</label>
```

Labeling Form Elements

Screen

ABC Banking Corporation Limited - Windows Internet Explorer

http://localhost/C54281/MoreOnHTML/examples/htmlCode

ABC Banking Corporation Limited

Contact Us

Please complete and submit the following form. All fields are required.

Personal Information

Title: ☒ Mr ☐ Mrs ☐ Ms

Last name:

First name:

Contact number:

Email address:

To be contacted: ☒ By Phone ☐ By Email

Message

Category: Deposits

Questions/Feedback:

Submit Reset Print

XHTML Code Design (Labeling)

FieldSet: Personal Information

Label **Radio1** **Label(R1)** **Radio2** **Label(R2)** **Radio3** **Label(R3)**

Label(T1) **TextBox1**

Label(T2) **TextBox2**

Label(T3) **TextBox3**

Label(T4) **TextBox4**

Label **Checkbox1** **Label(C1)** **Checkbox2** **Label(C2)**

FieldSet: Message

Label(LB1) **ListBox1**

Label(TA1) **TextArea1**

Button1 **Button2** **Button3**

Labels are not associated any elements.

47 `<label>Title:</label>`

48 `<input type="radio" id="mr" name="title" value="Mr" checked="checked" />`

49 `<label for="mr">Mr</label>`

50 `<input type="radio" id="mrs" name="title" value="Mrs" />`

51 `<label for="mrs">Mrs</label>`

52 `<input type="radio" id="ms" name="title" value="Ms" />`

53 `<label for="ms">Ms</label>`

54 `
`

Labels are associated with the specified elements.

55
56 `<label for="lastName">Last name:</label>`

57 `<input type="text" id="lastName" name="lastName" value="" />`

...

72 `<label>To be contacted:</label>`

73 `<input type="checkbox" id="byphone" name="byphone" value="byphone" checked="checked" />`

74 `<label for="byphone">By Phone</label>`

75 `<input type="checkbox" id="byemail" name="byemail" value="byemail" />`

76 `<label for="byemail">By Email</label>`

Setting the Tab Order in a Form

- By pressing the Tab key, visitors can move the focus through the fields in the form from top to bottom.
- Depending on the form layout, the tab order can be set, so that the visitor fills out all the fields in a particular group before going on to the next group.

tabindex="n"

$0 \leq n \leq 32767$

Setting the Tab Order in a Form

Screen

ABC Banking Corporation Limited - Windows Internet Explorer

http://localhost/CS4281/MoreOnXHTML/examples/htmlCode

ABC Banking Corporation Limited

Contact Us

Please complete and submit the following form. All fields are required.

Personal Information

Title: ☒ Mr ☐ Mrs ☐ Ms

Last name:

First name:

Contact number:

Email address:

To be contacted: ☒ By Phone ☐ By Email

Message

Category: Deposits

Questions/Feedback:

XHTML Code Design (Tab Order)

FieldSet: Personal Information

1 **Label** 2 **Radio1** 3 **Label(R1)** 4 **Radio2** 5 **Label(R2)** 6 **Radio3** 7 **Label(R3)**

8 **Label(T1)** 9 **TextBox1**

10 **Label(T2)** 11 **TextBox2**

12 **Label(T3)** 13 **TextBox3**

14 **Label(T4)** 15 **TextBox4**

16 **Label** 17 **Checkbox1** 18 **Label(C1)** 19 **Checkbox2** 20 **Label(C2)**

FieldSet: Message

21 **Label(LB1)** 22 **ListBox1**

23 **Label(TA1)** 24 **TextArea1**

25 **Button1** 26 **Button2** 27 **Button3**

28

29

30

```
47 <label>Title:</label>
48 <input type="radio" id="mr" name="title" value="Mr" checked="checked" tabindex="1" />
49 <label for="mr">Mr</label>
50 <input type="radio" id="mrs" name="title" value="Mrs" tabindex="2" />
51 <label for="mrs">Mrs</label>
52 <input type="radio" id="ms" name="title" value="Ms" tabindex="3" />
53 <label for="ms">Ms</label>
54 <br />
55
56 <label for="lastName">Last name:</label>
57 <input type="text" id="lastName" name="lastName" value="" tabindex="4" />
...
72 <label>To be contacted:</label>
73 <input type="checkbox" id="byphone" name="byphone" value="byphone" checked="checked"
    tabindex="8" />
74 <label for="byphone">By Phone</label>
75 <input type="checkbox" id="byemail" name="byemail" value="byemail" tabindex="9" />
76 <label for="byemail">By Email</label>
```

Adding Keyboard Shortcuts

- **Keyboard shortcuts let visitors select form elements and activate links/buttons without using a mouse.**
- **Keyboard shortcuts can be assigned to**
 - Form elements
 - Labels, which are associated with form elements
- **To invoke the keyboard shortcut**
 - On Windows systems, visitors use the **Alt** key plus the letter assigned.
 - On Macs, visitors use the **Control** key plus the letter assigned.
- **Caution**
 - Be sure not to assign to a form elements an access key that is already used by the Web browser.
 - You can tell what access keys are assigned to a Web browser menu by holding down you **Alt** key and examining the menu names.
 - Each menu's access key appears as an underlined letter in the menu name.

accesskey="..."

Adding Keyboard Shortcuts

Screen

ABC Banking Corporation Limited - Windows Internet Explorer

http://localhost/CS4281/MoreOnXHTML/examples/htmlCode

ABC Banking Corporation Limited

Contact Us

Please complete and submit the following form. All fields are required.

Personal Information

Title: ☒ Mr ☐ Mrs ☐ Ms

Last name:

First name:

Contact number:

Email address:

To be contacted: ☒ By Phone ☐ By Email

Message

Category: Deposits

Questions/Feedback:

Submit Reset

XHTML Code Design (Keyboard Shortcuts)

FieldSet: Personal Information

Label

Radio1

Label(R1)

Radio2

Label(R2)

Radio3

Label(R3)

Label(T1)

TextBox1

Label(T2)

TextBox2

Label(T3)

TextBox3

Label(T4)

TextBox4

Label

Checkbox1

Label(C1)

Checkbox2

Label(C2)

FieldSet: Message

Label(LB1)

ListBox1

Label(TA1)

TextArea1

Button1

Button2

Button3


```
47 <label>Title:</label>
48 <input type="radio" id="mr" name="title" value="Mr" checked="checked" tabindex="1" />
49 <label for="mr" accesskey="m">Mr</label>
50 <input type="radio" id="mrs" name="title" value="Mrs" tabindex="2" />
51 <label for="mrs" accesskey="r">Mrs</label>
52 <input type="radio" id="ms" name="title" value="Ms" tabindex="3" />
53 <label for="ms" accesskey="s">Ms</label>
54 <br />
55
56 <label for="lastName" accesskey="l">Last name:</label>
57 <input type="text" id="lastName" name="lastName" value="" tabindex="4" />
...
103 <input type="submit" id="submit" name="submit" value="Submit" tabindex="12"
    accesskey="u" /><span class="space"> | </span>
104 <input type="reset" id="reset" name="reset" value="Reset" tabindex="13" accesskey="e"
    /><span class="space"> | </span>
```

Keyboard shortcut keys are assigned to labels. The associated control will be focused, or selected and deselected when the specified key is pressed.

Keyboard shortcut keys are assigned to the input elements. The button will be activated when the specified key is pressed.

Creating Styles for a Form

- Styles can be applied to the form either directly through an element or attribute selector, or by applying classes or IDs.
- Layout of form is not easy to control, use your imagination and look at others' design

form {

font: 1em Verdana,
Arial, Helvetica, sans-serif;

letter-spacing: normal;

line-height: 100%;

margin: 0;

padding: 0; }

The screenshot shows a web browser window titled "ABC Banking Corporation Limited - Windows Internet Explorer". The address bar shows the URL "http://localhost/CS4281/MoreOnXHTML/examples/htmlCode". The page content includes a "Contact Us" heading, a instruction "Please complete and submit the following form. All fields are required.", and two sections: "Personal Information" and "Message".

Contact Us

Please complete and submit the following form. All fields are required.

Personal Information

Title: ☒ Mr ☐ Mrs ☐ Ms
Last name:
First name:
Contact number:
Email address:
To be contacted: ☒ By Phone ☐ By Email

Message

Category:
Please enter your questions/feedback here.
Questions/Feedback:

Creating Styles for Fieldset & Legend Elements

form fieldset {
 border: 2px solid #E0E0E0;
 margin-right: 100px;
 padding: .5em; }

form legend {
 font-variant: small-caps;
 font-weight: bold;
 font-size: .9em;
 letter-spacing: .2em;
 line-height: 16px;
 text-align: left;
 color: rgb(100%, 60%, 20%);
 background-color: inherit; }

ABC Banking Corporation Limited - Windows Internet Explorer

http://localhost/CS4281/MoreOnXHTML/examples/htmlCode

ABC Banking Corporation Limited

Contact Us

Please complete and submit the following form. All fields are required.

PERSONAL INFORMATION

Title: ☒ Mr ☐ Mrs ☐ Ms

Last name:

First name:

Contact number:

Email address:

To be contacted: ☒ By Phone ☐ By Email

MESSAGE

Category:

Questions/Feedback:

Done Internet 100%

Creating Styles for Labels & Input Elements

- **Styles can be applied to labels and input elements.**

- Font
- Color
- Text declaration

form **label** {

font-weight: bold;

font-size: .9em;

text-align: left;

text-transform: capitalize; }

form input, form textarea,

form **select**{

font-size: .9em;

color: #666;

background-color: inherit; }

The screenshot shows a web browser window titled 'ABC Banking Corporation Limited - Windows Internet Explorer'. The address bar shows 'http://localhost/CS4281/MoreOnXHTML/examples/htmlCode'. The page content includes a 'Contact Us' heading, a message 'Please complete and submit the following form. All fields are required.', and two form sections: 'PERSONAL INFORMATION' and 'MESSAGE'. The 'PERSONAL INFORMATION' section contains fields for Title (radio buttons for Mr, Mrs, Ms), Last Name, First Name, Contact Number, Email Address, and To Be Contacted (checkboxes for By Phone and By Email). The 'MESSAGE' section contains a Category dropdown menu (set to Deposits) and a text area for Questions/Feedback. At the bottom are Submit, Reset, and Print buttons.

Creating Styles for Layout

- Labels are put in the left hand side.
- Input elements are put in the right hand side.

form label {

```
font-weight: bold;  
font-size: .9em;  
text-align: left;  
text-transform: capitalize;  
width: 170px;  
padding-top: .2em;  
position: absolute;  
float: left; }
```

form input, form textarea, form select{

```
font-size: .9em;  
color: #666;  
background-color: inherit;  
margin-left: 180px;  
margin-bottom: .5em;  
margin-right: 5px; }
```

The screenshot shows a web browser window titled "ABC Banking Corporation Limited - Windows Internet Explorer". The address bar shows a local file path. The page content includes a "Contact Us" heading, a instruction to complete the form, and two sections: "PERSONAL INFORMATION" and "MESSAGE".

PERSONAL INFORMATION

Title: ☒ Mr ☐ Mrs ☐ Ms

Last Name:

First Name:

Contact Number:

Email Address:

To Be Contacted: ☒ By Phone ☐ By Email

MESSAGE

Category:

Questions/Feedback:

Buttons: Submit, Reset, Print

Declaring Dimensions of Input Elements

- **Styles can be applied to the form elements through an element or attribute selector.**

```
form textarea {  
    width: 350px;  
    height: 8em; }
```

```
form input[type="text"],  
form input[type="password"] {  
    width: 350px;  
    height: 1.5em; }
```

ABC Banking Corporation Limited - Windows Internet Explorer

http://localhost/CS4281/MoreOnXHTML/exe

Live Search

ABC Banking Corporation Limited

Contact Us

Please complete and submit the following form. All fields are required.

PERSONAL INFORMATION

Title: ☒ Mr ☐ Mrs ☐ Ms

Last Name:

First Name:

Contact Number:

Email Address:

To Be Contacted: ☒ By Phone ☐ By Email

MESSAGE

Category:

Questions/Feedback:

Submit Reset Print

Creating Styles for Buttons

- Styles can be applied to buttons through attribute selectors, or by applying classes selector.

form input[type="submit"],

form input[type="reset"],

form input[type="button"] {

font-weight: bold;

font-size: 1em;

color: inherit;

background-color: #DDEEFF;

width: 80px;

margin-left: 50px; }

form input.second {

margin-left: 80px; }

ABC Banking Corporation Limited - Windows Internet Explorer

http://localhost/CS4281/MoreOnXHTML/ex2

Live Search

ABC Banking Corporation Limited

Contact Us

Please complete and submit the following form. All fields are required.

PERSONAL INFORMATION

Title: ☒ Mr ☐ Mrs ☐ Ms

Last Name:

First Name:

Contact Number:

Email Address:

To Be Contacted: ☒ By Phone ☐ By Email

MESSAGE

Category:

Questions/Feedback:

Submit Reset Print

Copyright. ABC Banking Corporation Limited 2006. All rights reserved.

Reference & Extension Reading

- **Full table of CSS properties and values**
 - <http://www.w3.org/TR/CSS21/propidx.html>
 - **w3schools CSS reference**
 - <http://www.w3schools.com/cssref/default.asp>
-