Can Model Confidence Triage Qualitative Coding?

Decision Models, LLMs, and What a 5% Error Guarantee Actually Costs

Rishi Gulati
Independent researcher*

October 2026 (preprint; models called 10–12 October 2026, UTC)

Abstract

Model-assisted qualitative coding saves effort only if we know which model decisions a human must still check. We ask whether model confidence can select low-error decisions in fixed-codebook coding. Under a prospectively specified analysis plan, we compare seven decision models, APIs that return probabilities for typed questions, with twelve LLM confidence signals on five human-coded tasks: moral foundations in Reddit comments, motivational-interviewing dialogue and K-12 classroom talk. Raw error ranking varies widely, with the open Kev-27B and Claude Sonnet's verbalized confidence best; recalibrating per predicted code narrows most differences, and low calibration error alone does not predict useful selection. A threshold fitted to 5% error on calibration data exceeds 5% on held-out data in about half of re-splits on Reddit comments for most decision models, and thresholds do not transfer across codebooks. A Learn-then-Test rule that treats decisions as independent also fails, because codes and utterances share comments and transcripts. A version that needs only a random sample of hand-coded units bounds the error on the rest of the corpus. After 30% of Reddit comments are hand-coded, it certifies 60–83% of the remaining code decisions for most coders, nearly all of them calls that a code does not apply. On dialogue, with whole transcripts hand-coded at the same budget, it certifies nothing, and could not even for a perfect coder; sampling single utterances removes that obstacle but yields almost no certificates. Without a guarantee, a baseline that reads no text accepts 75% of comment decisions at 3.6% error. Model uncertainty tracks annotator disagreement, and option order changes some models' labels. All models were called on 10–12 October 2026; we release the harness and every model output.

1 Introduction

Deductive qualitative coding applies a fixed codebook to text: each segment of an interview, dialogue or survey answer is read, compared with the code definitions and labelled, often twice to establish reliability [29]. Large language models (LLMs) can apply codebooks with useful accuracy [7, 11, 17, 39, 65, 73], but accuracy alone does not tell a researcher which model labels to trust. The practical promise is *triage*: accept the labels a model is confident about and send the rest to a person.

Consider a researcher with 1,500 counselling utterances to code and time to check 400 by hand. A model labels every utterance and attaches a confidence; a threshold decides which labels are accepted. Three properties of the confidence then matter, and they are easy to conflate. *Error ranking*: do the model's mistakes get lower confidence than its correct labels? *Calibration*: does a stated 90% mean 90% correct? *Selective risk and coverage*: at the chosen threshold, what share of labels is accepted, and what share of those is wrong? A well-calibrated model can rank its errors poorly, and a threshold chosen on 400 hand-coded utterances to give 5% error can give more than 5% on the remaining 1,100. Our question is whether model confidence can select low-error decisions reliably enough for this workflow.

A new class of products is marketed for exactly this. We call them *decision models*: an interface that takes typed questions (yes/no, multiple choice) with criteria and returns a probability for each option, without generating text. TypeSafe's Jev [57] was followed within weeks by OpenAI's Decisions API [42], Cloudflare's

*Correspondence: rg29.work@gmail.com. Code, analysis plan, results and paper source: https://github.com/firish/margin.

Clef [8], Perplexity's pplx-decider [45] and the open Kev models [43]. The interface is new; the underlying idea, probabilistic classification with abstention, is not [16]. Whether these probabilities support triage on real codebooks, with human disagreement, dialogue context and rare codes, is an open question. We study it for the classification step of deductive coding on short segments (comments, utterances, sentences), not for inductive coding or long-form interviews.

We ask three research questions, each with pre-specified contrasts:

- **RQ1 (triage).** Do decision models' probabilities rank their own coding errors better than LLM confidence signals, and what share of decisions can be accepted at $\leq$5% error?
- **RQ2 (disagreement).** Is model uncertainty high where human coders disagree, and how does model agreement with annotators compare with annotators' agreement with each other?
- **RQ3 (robustness).** How much do decisions change under surface changes to the codebook and request, and under removal of context?

Six experimental questions explain the answers: **EQ1**, does calibration error predict triage? **EQ2**, do threshold rules keep their error target, and what does a finite-sample guarantee cost? **EQ3**, what limits triage, ranking or ties at the top? **EQ4**, do related 9B decision models outperform a 9B instruct model's own confidence? **EQ5**, which configurations give the most guaranteed automation per dollar? **EQ6**, are the results artefacts of nondeterminism, prompt choice, memorization or label noise?

The short answer to the title is: on Reddit comments, yes, but much of what is accepted is the easy call that a code does not apply; on dialogue, with whole transcripts hand-coded, our guaranteed rule certified nothing. Two facts drive this. Coding decisions come in clusters (eight codes of one comment, many utterances of one transcript), so an error guarantee must respect how the hand-coded sample was drawn: a rule that treats the decisions of hand-coded transcripts as independent fails, and with whole transcripts of very unequal length as sampling units, our valid procedure cannot certify even a perfect coder at our calibration sizes; for three of the four dialogue tasks its necessary bound exceeds the available corpus. Sampling single utterances instead removes that obstacle, but at our budget the coders' confident dialogue decisions still give too little evidence of $\leq$5% error. And most decisions in a multi-label codebook are negatives, which a baseline that never reads the text accepts at low error.

Relation to concurrent work. Two studies released in the weeks before ours also evaluate decision models: Ibrahim and Zaki [25] compare Jev and small open decision models with 19 LLMs on 15 computational-social-science labelling tasks (accuracy, calibration, coverage at fixed thresholds, cost and cascades), and TypedBench [51] uses synthetic, rule-labelled tasks. Where the designs overlap, our findings agree: Jev trails the strongest LLMs in accuracy, its raw calibration beats most LLM signals but not the frontier models, and cascades save cost. Risk-controlled triage is not new either: HyPAC [70] routes items between models and humans with a PAC guarantee on annotation error, and Zhao and Liu [72] triage qualitative codes by confidence and inter-model diversity. Our contribution is an evaluation, not a new method.

Contributions.

1. **A multi-vendor evaluation.** Seven decision models and twelve LLM confidence signals on five human-coded tasks, under a prospectively specified plan with a deviations log, with every model output released (§3).
2. **Ranking, not calibration error, separates coders.** Raw error ranking varies widely across decision models, low calibration error does not predict it, and per-code recalibration narrows most differences (§4.1, §5.1–§5.3).
3. **Guarantees that respect the sampling design.** The usual rule overshoots its target, and a guarantee that treats decisions as independent fails. A corpus-level rule adapted from betting tests for sampling without replacement certified most comment decisions and, with whole transcripts hand-coded, no dialogue decisions; we separate what the sampling design, the procedure and the coders each contribute to that cost (§3.4, §5.2).
4. **What automation means for coding.** A prevalence baseline, recall of applying codes, the share of segments still read by a person and policy-specific cost give a more honest picture than accepted share alone (§5.5, §6).

2 Related work

LLMs for qualitative and content coding. LLMs have been used to apply codebooks deductively [7, 65], to replace or assist crowd annotation [17, 73], to code open-ended survey responses [40] and to score classroom discourse [60]. Best-practice guidance stresses validation against human labels [44, 55]. Dunivin [12] showed that chain-of-thought prompting can match human coders on some hermeneutic codes; we recompute his reported agreement from his released predictions (§5.6). Recent studies compare prompting strategies [50], benchmark many models against expert adjudication [38], design human–AI workflows for deductive coding [34, 39, 68], and add model self-critique [13]. Zhao and Liu [72] combine self-confidence with inter-model diversity to route segments to review, auto-accepting 35% at under 5% error on their data; we ask whether such thresholds hold on held-out data and across codebooks. Liu et al. [36] show that agreement with human consensus is not the same as coding quality: blind experts often prefer the model's code. Our adjudication finds the same (§5.6).

Decision models. Jev introduced the "System One" interface [57]. Denney and DiGiuseppe [10] compare Jev with LLMs on seven political-science replications for accuracy, cost and calibration. Li et al. [33] use it as an accept-or-escalate judge, and Rafe and Das [48] convert crash narratives into probabilistic variables. Ibrahim and Zaki [25] and TypedBench [51] are closest to our work (§1). Other recent studies show that short, natural-sounding context can flip decision models' answers [67], that rejection thresholds fitted on one dataset fail on another [37], and that decisions can be read from an ordinary LLM's next-token probabilities without retraining, with option-order bias reduced by averaging over rotations [32, 71]. We add the newer hosted and open models [8, 42, 43, 45], qualitative codebooks with human disagreement, threshold validity and guarantees that respect how hand-coded samples are drawn, and a comparison of related 9B systems.

Confidence, calibration and selective prediction. Neural classifiers are often miscalibrated, and temperature scaling [20], Platt scaling [47] and isotonic regression [69] are standard fixes. Whether confidence separates a model's correct from incorrect predictions is a separate question [22]. For LLMs, confidence can be read from token probabilities [27] or elicited verbally [54, 66], and fast black-box estimators are being developed [21]. Selective classification accepts a prediction only above a confidence threshold [16], and cascades send the rest to a stronger model [6]. For such thresholds, conformal risk control [1] bounds an expected monotone loss under exchangeability, and standard Learn-then-Test [3] gives a high-probability bound on population risk from valid tests under assumptions such as i.i.d. calibration data; when observations come in groups, the group becomes the unit of analysis [14]. For a fixed corpus, a finite-population betting test [62] needs only that the hand-coded units, and the order they are visited in, are random; we adapt it to coding decisions, and average over orders using e-values [59]. These guarantees have been applied to LLM judges [5, 26, 31], hybrid LLM–human annotation [70], human verification of LLM labels [61] and calibrated grading [49]. We measure how often the usual non-guaranteed rule breaks its target on real codebooks, show that a guarantee which ignores clustering fails, and measure how much coverage a valid one costs at calibration sizes a research team can realistically hand-code.

Human label variation and downstream inference. Annotators disagree for principled reasons, so a single majority label is an imperfect target [46, 58]. Baan et al. [4] argue that calibration should then be judged against the distribution of human labels, and Lee et al. [30] test whether LLMs reproduce that distribution. Our RQ2 asks the triage version of this question: whether model uncertainty is high where humans split. A complementary line of work does not accept individual labels at all. It corrects downstream estimates, such as code prevalences or regression coefficients, using a hand-coded subsample [2, 15], and can use model confidence to choose which items to hand-code [18].

Contamination. Public benchmarks may be in training data. We adapt the guided-versus-general completion test of Golchin and Surdeanu [19] and add a decoy-name control to separate memory from task framing.

Table 1: Tasks, codebooks and samples. Calib and test are segments; clusters are conversations or transcripts (comments for MFRC). Dunivin is the replication task.

task	unit	codebook	codes	calib	test	clusters	annot./item	human α
MFRC	Reddit comment	multi-label	8	608	1392	2000	3	0.17
AnnoMI client	client utterance	exclusive	3	569	931	128	1 (10 on a subset)	0.47
AnnoMI therapist	therapist utterance	exclusive	4	602	898	132	1 (10 on a subset)	0.74
TalkMoves teacher	teacher sentence	exclusive	7	370	1130	444	1	–
TalkMoves student	student sentence	exclusive	5	383	1117	436	1	–
Dunivin	historical passage	multi-label	9	34	86	120	1	–

Multi-label: one yes/no decision per code; exclusive: one choice among the codes (counts include any 'none' or 'other' option). Dialogue units include the previous turn as context. α: Krippendorff's alpha on multiply-coded items (macro over codes for multi-label); – where items are single-coded. RQ2 uses MFRC and AnnoMI's ten-annotator subset.

3 Study design

3.1 Tasks and codebooks

We use five tasks from three public, human-coded datasets (Table 1).

- **MFRC** [56]: Reddit comments coded for moral foundations with the dataset's guidelines. The codebook is multi-label with 8 codes; 1,988 of the 2,000 sampled comments have three annotators and 12 have two.
- **AnnoMI** [63, 64], full version: transcribed motivational-interviewing demonstrations, with mutually exclusive codes for client talk (change, sustain, neutral) and therapist behaviour (reflection, question, input, other). AnnoMI publishes labels rather than full definitions, so its codebooks combine AnnoMI's labels with MITI 4 wording [41] and the AnnoMI-to-MISC mapping of Sun et al. [52]. A subset is coded by ten annotators.
- **TalkMoves** [53]: K-12 mathematics classroom transcripts coded with the dataset's manual, with mutually exclusive teacher moves (six plus none) and student moves (four plus none).

For dialogue tasks the coder also sees the previous turn. Dunivin's coded passages about W. E. B. Du Bois [12] serve as a replication task. We draw stratified samples of 2,000 comments (MFRC) or 1,500 segments (each dialogue task) that keep rare codes, and weight each segment by its inverse inclusion probability [24]. A hash of the cluster id (comment, transcript or lesson) assigns about 30% of clusters to a calibration split and the rest to a test split; because clusters differ in size, the calibration split holds 25–40% of segments. The reference label is the annotator majority; ties are dropped.

3.2 Coders and confidence

Table 2 lists the models. **Decision models** receive identical requests: the segment and its context, and either one multiple-choice question (exclusive codebooks) or one yes/no question per code (multi-label), whose criteria are the code's definition, inclusion and exclusion rules and examples. OpenAI Decisions receives the same content mapped to its own choice and predicate types; Clef, pplx-decider and Kev accepted Jev's requests unchanged. We self-host Kev on Modal GPUs from the authors' release. **LLMs** receive the same codebook text in one prompt and return JSON with a one-sentence rationale, an answer and a probability from 0 to 100 (per code for multi-label tasks). Appendix D shows both requests.

From outputs to confidence. For decision models, an exclusive decision is the most probable option and its confidence is that probability; a multi-label decision says a code applies if its probability is at least 0.5, with confidence $\max(p, 1-p)$. LLM signals are derived as follows.

- *Verbalized, exclusive:* the chosen option gets the stated probability (at least $1/K$), and the other options share the remainder equally. RQ2's model entropy for these signals therefore comes from a reconstructed, not an elicited, distribution.
- *Verbalized, multi-label:* we read the stated probability as confidence in the stated yes/no answer. Read as "probability that the code applies", it contradicted the answer for 85% of Luna's code decisions (0.2–4.6% for the other LLMs). Confidence is therefore $c = \max(q, 1-q)$, and $p(\text{applies})$ is c for "yes" and $1-c$ for "no".

Table 2: Models and confidence signals, with realized API cost per 1,000 segments (October 2026 prices).

model	kind	confidence signals	sample	USD / 1k segments
Jev	decision model	probability	full	0.047
OpenAI Decisions	decision model	probability	full	0.102
Clef	decision model	probability	full	0.213
Clef-flash	decision model	probability	full	0.080
pplx-decider	decision model	probability	full	0.019
Kev-9B	open decision model	probability	full	0.073
Kev-27B	open decision model	probability	full	0.315
Luna	LLM	verbalized; token prob.; self-consistency (350/task, $0.28)	full	0.107
Haiku	LLM	verbalized	full	1.906
gpt-oss	LLM	verbalized; token prob.	full	0.232
Qwen3.5-9B	LLM	verbalized; token prob.	full	0.176
Sonnet	LLM (frontier)	verbalized	full	1.964
Qwen3.8-2.4T	LLM (frontier)	verbalized; token prob.	270/task	2.481
3-LLM agreement	ensemble	vote share	full	2.245

Kev: estimated serving cost from observed throughput on Modal (Kev-9B 30 calls/s on 2 H100s at $3.95/h; Kev-27B 11 calls/s on 2 B200s at $6.25/h), excluding cold starts and idle time. Model identifiers, settings, versions returned and call dates are in Table 28 (appendix).

- *Token probability:* the probability of the answer token, read after the generated rationale: the option letter for exclusive codebooks and the yes/no token for each multi-label code (Luna, gpt-oss and both Qwen models).
- *3-LLM agreement:* the vote share of the Luna, Haiku and gpt-oss verbal runs; *self-consistency:* the vote share of five Luna samples at temperature 1 on 350 segments per task.

We run reasoning models with minimal reasoning so that answer-token probabilities exist. Sonnet and Qwen3.8-2.4T are the frontier references; Qwen3.8-2.4T runs on a 270-segment-per-task subset. Every model was called on 10–12 October 2026 (UTC), several of them in public beta (Table 28 lists the versions).

3.3 Decisions and metrics

A *decision* is one label to accept or reject: one per segment for exclusive codebooks, one per segment and code for multi-label ones. **Error AUROC** (RQ1, primary) is the probability that a correct decision has higher confidence than an incorrect one, with ties counted as one half [22]. **Coverage@5%** (RQ1, primary) is the share of test decisions accepted by the threshold rule below, reported with the error among them. Secondary metrics are the area under the risk–coverage curve (AURC), expected calibration error (ECE, 10 bins), Cohen's κ [9] and cost. RQ1 and EQ1–EQ5 use design weights, as do RQ3's changes; RQ2's correlations and leave-one-annotator-out κ are unweighted. Pooled estimates are equal-weight means over the five tasks; this describes these five tasks, not a population of codebooks. Confidence intervals come from a cluster bootstrap that resamples calibration and test clusters separately and refits thresholds in every replicate (1,000 replicates), unless stated otherwise.

3.4 Threshold rules

Each rule picks a confidence threshold t from the hand-coded calibration clusters and accepts the other decisions with confidence $\geq t$. We distinguish two targets. The *corpus target* is the design-weighted error among the accepted decisions of the uncoded remainder of the corpus, the quantity a researcher coding their own data cares about. The *population target* is the expected error among accepted decisions for new clusters from the same source. Whether one particular test set has error above 5% is exactly the corpus target when that test set is the uncoded remainder of a random split, and only a diagnostic for the population target.

- **Naive** (the pre-specified primary rule): the lowest threshold whose calibration error is at most 5%. No guarantee.
- **LTT on decisions:** Learn-then-Test [3] with binomial tests of "risk >5%" on decision counts, fixed-sequence from the most confident tie block. With design weights the counts are Kish-effective and frac-




Figure 1: The triage workflow we evaluate. A random sample of the corpus's units (here comments, transcripts or lessons) is coded by hand and by the model; comparing the two fixes a threshold. The model's confidence then decides which labels in the rest of the corpus are accepted and which go to a person. A guaranteed rule bounds the error rate among the accepted labels of the remainder.

tional, so the test is an approximation even for independent decisions. It treats decisions as independent; we show it only for comparison.

- **Corpus LTT** (our guaranteed rule). For each threshold on a grid of 16 values from 0.5 to 1.0, cluster i contributes $Z_i(t) = \sum_j w_{ij}\,\mathbf{1}\{c_{ij} \geq t\}\,(e_{ij} - 0.05)$, so a set of clusters has error at most 5% among its accepted decisions exactly when its Z-sum is at most 0. Rescaled by B, the largest total weight of one cluster in the corpus (known before anything is coded), $Y_i = (Z_i + 0.05B)/B$ lies in $[0, 1]$. A betting test for sampling without replacement [62] visits the hand-coded clusters in random order and asks whether the corpus mean of Y is low enough for the remainder's Z-sum to be at most 0 (Appendix B). So that the result does not depend on one arbitrary order, we average the test's final wealth over 100 random orders. Each threshold is tested at 0.05/16, and the lowest certified one is used.

Proposition (corpus LTT; Appendix B). Suppose the hand-coded clusters are a uniformly random subset of the corpus's clusters, the orders in which the test visits them are uniformly random and independent of the labels, and the confidence scores, the threshold grid and B are fixed before the hand-coded labels are used. Then, with probability at least 0.95 over the random choice of clusters and orders, every certified threshold has error at most 5% among the accepted decisions of the uncoded clusters (counting a remainder with no accepted decision as within the target). No assumption is made about how errors depend on each other within or across clusters.

The construction adapts existing testing machinery to the coding workflow; the statistical tools are not new. Nothing in it requires the unit to be a cluster: any unit can be sampled, such as a comment, a whole transcript, a fixed-size block of turns or a single utterance coded with its context, provided the hand-coded units are a random sample of the corpus's units and B is the largest unit's weight. What the guarantee must respect is how the hand-coded sample was drawn.

In our evaluation, each task's sample is the corpus, its calibration split the hand-coded clusters (assigned by a hash of the cluster id, which we treat as random) and its test split the remainder. The visiting orders come from a pseudo-random generator with a seed recorded before this analysis was run. The guarantee holds for each configuration on its own; picking the best of several certified configurations would need a further correction. Learned scores, such as per-code maps or the prevalence baseline below, are fitted on half of the calibration clusters, frozen, certified on the other half and applied unchanged to the remainder. Multi-stage cascades are certified jointly over all combinations of per-stage thresholds. For the population target we also report the same test with a constant null mean (*LTT on i.i.d. clusters*); it needs clusters to be independent draws, which we assume rather than know, and B to bound every future cluster's weight, which is true for MFRC (eight codes per comment at one weight) but not for transcripts of unbounded length. The **oracle** applies the naive rule to the test split itself: not deployable, an upper bound for comparison.

Analysis plan. The plan fixed the tasks, splits, decision units, metrics, primary rule and RQ1 contrasts before any test-split outcome was computed. Four amendments, each dated before the data it governs, added OpenAI Decisions and a Qwen comparator (v1.1), five more decision models (v1.2), a memorization probe (v1.3) and a prompt-sensitivity check (v1.4). The plan and amendments were kept in the project repository, not registered with an external service, so their timing cannot be verified independently; we call the plan prospectively specified. A claim needs the pooled 95% CI to exclude zero; for the v1.2 family the plan also requires Holm's correction [23], which we apply to the earlier families as a sensitivity analysis. Jev

anchors the confirmatory contrasts because the original plan was written for it; the other decision models were added by amendment. Pooled intervals resample each corpus's clusters jointly, so AnnoMI's two tasks share transcript draws and TalkMoves' two share lesson draws. Sonnet was specified on a nested subset; that result is the confirmatory one, and its later full-sample run is a labelled extension. Everything changed after results were seen, including the corpus guarantee, which replaced decision-level LTT and was revised after external reviews, is labelled exploratory and logged (Appendix A).

Adjudicated reference. Human majority labels contain errors. We sampled 200 items for blinded adjudication from disagreements between the human label and six label sources (Jev in both question formats, Luna, Haiku, gpt-oss and Sonnet's subset run), oversampling high-confidence disagreements, plus hidden controls. A two-family LLM panel (Claude Opus 5.5 and GPT-6 Sol) judged each item. The author adjudicated 36 of the 52 items the panel disputed, plus a 12-item audit of panel-agreed items (agreement 10 of 12); a planned second sitting to measure the author's own consistency was not done. Of the 200 items, 184 were resolved; unresolved items keep the human label. We use this reference as a sensitivity analysis, not as a corrected gold standard.

4 Results: research questions

4.1 RQ1: Does confidence triage qualitative coding?

Table 3 summarizes agreement and ranking for every signal, Table 4 gives the confirmatory contrasts, and Figures 2 and 3 show the contrasts and the per-task risk–coverage curves.

Raw error ranking varies widely among decision models. The open Kev-27B ranks its own errors best among the decision models (error AUROC 0.788), close to Sonnet's verbalized confidence (0.801). pplx-decider (0.764) and Jev (0.756) follow; OpenAI Decisions, Clef, Clef-flash and Kev-9B rank errors worse (0.694–0.736). In the pre-specified contrasts, Jev ranks its errors better than four of the six other decision models: OpenAI Decisions by +0.020 [0.005, 0.035], Clef by +0.036, Clef-flash by +0.045 and Kev-9B by +0.062. Its difference from pplx-decider is not significant (−0.008 [−0.027, 0.010]); pplx-decider accepts more decisions under the naive 5%-target rule (−0.079 [−0.245, −0.047]). Kev-27B beats Jev on both primary metrics (−0.032 AUROC; −0.113 coverage). Among LLM signals, Jev beats every token-probability signal, by 0.20 AUROC for Luna and gpt-oss and by 0.07 for the Qwen models, as well as 3-LLM agreement (+0.087), self-consistency (+0.153) and gpt-oss's verbalized confidence (+0.029). The verbalized confidence of Haiku (−0.026) and Sonnet beats it: −0.048 [−0.082, −0.015] on the pre-specified Sonnet subset ($p = 0.002$) and −0.045 [−0.060, −0.032] on the full-sample extension. Jev's advantage over Luna's verbalized confidence is borderline (+0.016 [0.0004, 0.031], bootstrap $p = 0.046$) and not a claim after Holm adjustment, and the exploratory Qwen3.8-2.4T's verbalized confidence edges out Jev (−0.033 [−0.069, −0.001]). Token probabilities rank errors poorly because they saturate: 96–100% of decisions carry confidence ≥0.99.

How much can be accepted, and what is it? Under the naive rule, Kev-27B, Sonnet and pplx-decider accept 41–44% of all decisions and Jev 33% (Table 5; equal-weight means over the five tasks), but 6.2–7.5% of what they accept is wrong. Acceptance is far higher on MFRC, where these four accept 78–94% of decisions, than on the four dialogue tasks (22–32% on average). Most MFRC decisions are easy negatives: 89% of MFRC test decisions are codes that do not apply. A prevalence baseline that reads no text, predicting "absent" for every code with confidence equal to that code's calibration share of absent labels, accepts 75% of MFRC decisions at 3.6% error under the naive rule (Table 6), although it carries no certificate (§5.5). The models differ in what the baseline cannot do: find the codes that apply. Among accepted decisions, pplx-decider labels 62% of the applying codes correctly, Sonnet 53% and Jev 35%; the rest go to a human or are missed. On the four dialogue tasks, accepted shares are much smaller, and the naive rule's error targets mostly fail (§5.2).

Robustness. Against the adjudicated reference, 39 of the 40 Jev contrasts (20 comparators, two metrics) keep their sign and significance. The exception is the borderline error-ranking contrast with Luna's verbalized

Table 3: RQ1: agreement, calibration and error ranking on the test split (mean over the five tasks, design-weighted). Groups: decision models, verbalized LLM confidence, token probabilities, agreement signals.

signal	sample	κ (weighted)	ECE	error AUROC	AURC	conf $\geq$ 0.99
Jev	full	0.475	0.120	0.756	0.144	0.220
OpenAI Decisions	full	0.449	0.122	0.736	0.155	0.309
Clef (27B)	full	0.377	0.055	0.721	0.228	0.000
Clef-flash (9B)	full	0.369	0.065	0.712	0.234	0.000
pplx-decider	full	0.482	0.052	0.764	0.122	0.084
Kev-9B	full	0.300	0.100	0.694	0.281	0.000
Kev-27B	full	0.474	0.073	0.788	0.105	0.003
Luna verbal	full	0.483	0.180	0.741	0.146	0.226
Haiku verbal	full	0.465	0.154	0.783	0.149	0.003
gpt-oss verbal	full	0.452	0.204	0.727	0.192	0.043
Qwen3.5-9B verbal	full	0.383	0.303	0.646	0.276	0.389
Sonnet verbal	full	0.529	0.051	0.801	0.108	0.026
Qwen3.8-2.4T verbal	270/task	0.499	0.102	0.802	0.122	0.002
Luna logprob	full	0.483	0.243	0.558	0.225	0.990
gpt-oss logprob	full	0.452	0.284	0.558	0.264	0.998
Qwen3.5-9B logprob	full	0.384	0.334	0.684	0.237	0.964
Qwen3.8-2.4T logprob	270/task	0.499	0.248	0.703	0.148	0.961
3-LLM agreement	full	0.493	0.153	0.670	0.193	0.719
Luna self-consistency	350/task	0.506	0.196	0.624	0.197	0.851

Error AUROC: probability that a correct decision is more confident than an incorrect one (ties count half). AURC: area under the risk-coverage curve, lower is better. conf $\geq$ 0.99: share of decisions with confidence $\geq$ 0.99.

confidence, whose interval moves from just above zero to just below it (+0.016 [−0.0001, 0.032]).

4.2 RQ2: Does uncertainty sit where humans disagree?

When annotators disagree, a single majority label is a weak target [4, 46], so we ask whether model uncertainty is high where humans split. The evidence is limited: MFRC has 1,382 test comments with three annotators, but AnnoMI's multi-annotated test items (91 client and 93 therapist utterances) come from only four transcripts, so the AnnoMI results describe those conversations. With that caveat, model uncertainty rises where humans split (Figure 4). For every decision model and the Luna, Haiku, gpt-oss and Sonnet verbal signals, the Spearman correlation between model uncertainty and the entropy of the human labels is 0.24–0.43 on MFRC and 0.33–0.65 on AnnoMI, except Kev-9B on AnnoMI client (0.18). Token probabilities, vote-based agreement and Qwen3.5-9B's verbalized confidence track disagreement weakly or not at all; Luna's token-probability uncertainty is unrelated or inversely related to it (−0.10 and −0.03 on AnnoMI). Coders run on a subset (Qwen3.8-2.4T, self-consistency) have only 20–23 multi-annotated AnnoMI items and are not interpreted.

In a leave-one-annotator-out comparison, each annotator in turn is scored against the majority of the other annotators, and each coder is scored against the same references (the dot is its mean over references). No coder falls below the range of individual annotators, and some fall above it: on AnnoMI therapist, Jev's mean κ (0.891) exceeds all ten annotators' (0.631–0.886), and on MFRC Sonnet exceeds five of six. This is a descriptive comparison with a broad human range, not a test of equivalence to a typical annotator.

4.3 RQ3: How stable are decisions?

We perturbed the request on the test split (Figure 5). Jev, OpenAI Decisions, Clef-flash and pplx-decider ran every arm on all applicable tasks; Kev-9B ran one to four tasks per arm, because its hosting stopped; Luna and Sonnet ran the option-order and label arms on 85 test segments per task. Flip rates and changes in AURC, the two pre-specified outcomes, are design-weighted, with per-task cluster-bootstrap intervals (Table 11).

Table 4: Confirmatory contrasts, Jev minus each comparator X, pooled over the five tasks (paired cluster bootstrap, thresholds refitted in every replicate). Positive values favour Jev. Coverage is the naive rule's share accepted.

family	X	Δ err. AUROC [95% CI]	Holm p	better	Δ cov@5% [95% CI]	Holm p	better
v1.0	Luna verbal	+0.016 [0.0004, 0.031]	0.184	–	+0.128 [-0.044, 0.180]	0.510	–
v1.0	Haiku verbal	-0.026 [-0.043, -0.011]	0.016	X	+0.168 [-0.071, 0.184]	0.510	–
v1.0	gpt-oss verbal	+0.029 [0.011, 0.051]	0.016	Jev	+0.108 [-0.064, 0.155]	0.510	–
v1.0	Luna logprob	+0.198 [0.177, 0.221]	0.016	Jev	+0.329 [0.148, 0.381]	0.016	Jev
v1.0	gpt-oss logprob	+0.198 [0.174, 0.221]	0.016	Jev	+0.317 [0.148, 0.367]	0.016	Jev
v1.0	3-LLM agreement	+0.087 [0.069, 0.103]	0.016	Jev	+0.329 [0.160, 0.382]	0.016	Jev
v1.0	Luna self-consistency	+0.153 [0.118, 0.186]	0.016	Jev	+0.164 [0.160, 0.446]	0.016	Jev
v1.0	Sonnet verbal (v1.0 subset)	-0.048 [-0.082, -0.015]	0.016	X	-0.249 [-0.296, -0.029]	0.110	–
v1.1	OpenAI Decisions	+0.020 [0.005, 0.035]	0.024	Jev	+0.103 [-0.050, 0.187]	0.274	–
v1.2	Clef (27B)	+0.036 [0.017, 0.054]	0.010	Jev	+0.090 [-0.085, 0.135]	1.000	–
v1.2	Clef-flash (9B)	+0.045 [0.024, 0.064]	0.010	Jev	+0.075 [-0.086, 0.128]	1.000	–
v1.2	pplx-decider	-0.008 [-0.027, 0.010]	1.000	–	-0.079 [-0.245, -0.047]	0.010	X
v1.2	Kev-9B	+0.062 [0.041, 0.086]	0.010	Jev	+0.090 [-0.041, 0.158]	0.872	–
v1.2	Kev-27B	-0.032 [-0.047, -0.017]	0.010	X	-0.113 [-0.272, -0.063]	0.010	X
v1.1 (sec.)	Qwen3.5-9B verbal	+0.110 [0.093, 0.129]	–	Jev	+0.295 [0.149, 0.364]	–	Jev
v1.1 (sec.)	Qwen3.5-9B logprob	+0.072 [0.050, 0.093]	–	Jev	+0.236 [0.065, 0.283]	–	Jev
ext.	Sonnet verbal (full sample)	-0.045 [-0.060, -0.032]	–	X	-0.105 [-0.283, -0.055]	–	X

'better' names the winner (Jev, or X for the comparator) when the pooled 95% CI excludes 0 and Holm $p < 0.05$ within the family; – : no claim. Holm is part of the plan's rule for v1.2 and a sensitivity analysis for v1.0 and v1.1. Sonnet enters v1.0 as specified, on its nested subset; the full-sample extension (ext.) is exploratory and outside the family. v1.1 secondary rows are unadjusted. Intervals resample each corpus's clusters jointly for related tasks; coverage intervals are asymmetric because refitted thresholds jump between tie blocks.

Table 5: Threshold policies at a 5% error target on the frozen split (percent): share of test decisions accepted, and error among them. Pooled columns average the five tasks; dialogue columns average the four dialogue tasks.

signal	naive: accepted	naive: error	oracle: accepted	MFRC: LTT on decisions	MFRC: corpus LTT	its error	dialogue: naive	dialogue: LTT on decisions	dialogue: corpus LTT
Jev	32.9	6.8	16.3	74.4	59.8	1.6	21.7	0.0	0.0
OpenAI Decisions	22.7	4.7	17.8	65.6	0.0	–	10.2	0.0	0.0
Clef (27B)	24.0	5.8	20.3	88.4	82.3	3.0	7.4	0.0	0.0
Clef-flash (9B)	25.4	7.0	20.7	86.7	77.9	2.7	9.5	0.0	0.0
pplx-decider	40.8	7.5	32.1	88.5	77.1	2.3	28.0	0.0	0.0
Kev-9B	23.9	6.3	19.2	82.8	67.1	2.4	8.1	0.0	0.0
Kev-27B	44.2	7.0	37.2	91.3	76.6	2.1	31.7	10.6	0.0
Luna verbal	20.2	4.6	16.2	79.5	64.0	2.2	5.3	0.0	0.0
Haiku verbal	16.1	3.2	16.8	74.9	65.8	1.7	1.4	0.0	0.0
gpt-oss verbal	22.1	5.6	20.6	0.0	0.0	–	6.9	0.0	0.0
Sonnet verbal	43.4	6.2	40.1	87.5	82.7	2.5	31.7	6.1	0.0
Qwen3.8-2.4T verbal	37.9	4.3	38.0	74.8	0.0	–	26.8	0.0	0.0

Naive: threshold with calibration error $\leq 5\%$ (the pre-specified rule). Oracle: fitted on test, an unattainable upper bound. LTT on decisions treats decisions as independent and is shown only for comparison; corpus LTT certifies the error of the uncoded remainder (Section 3.4).

- **Option order matters, differently by model.** Averaged over tasks, reversing or shuffling options changes 4% of Jev's labels, 5–7% of pplx-decider's and Sonnet's, 8–11% of OpenAI Decisions' and Luna's, under 1% of Clef-flash's, and 13–31% of Kev-9B's; in single tasks it reaches 55% (Kev-9B, reversed options, TalkMoves teacher). Identical repeated requests already change 2.1% of Jev's labels, 3.3% of Sonnet's and 6.6% of Luna's (§5.6), so part of each order effect is sampling noise.
- **Wording matters a little.** Paraphrased definitions change 3–10% of labels, and replacing code names with neutral identifiers 5–10%. Asking for MFRC codes one at a time instead of together changes at most 4% (Clef-flash); OpenAI Decisions' multi-label answers are exactly invariant to question order and batching.
- **Removing the previous turn removes information.** It changes 15–24% of dialogue labels on average over tasks (up to 39% in one task) and makes the coders worse: κ falls by 0.012–0.041 and AURC rises




Figure 2: RQ1 contrasts: Jev minus each signal, pooled over tasks (grey dots: individual tasks), grouped as decision models, verbalized confidence, token probabilities and agreement signals. Positive values favour Jev. Blue marks a 95% CI that excludes 0 (unadjusted). Left: error AUROC. Right: share accepted under the naive 5%-target rule. *: secondary or exploratory comparison (the Qwen models; Sonnet on the full sample, an extension of its pre-specified subset).

by 0.010–0.037. These flips are mostly a loss of relevant context, not instability, in line with the finding that added context can redirect decision models [67].

- **Question format has model-specific effects.** Asking each exclusive option as a separate yes/no question improves error ranking for Clef-flash (+0.029) and pplx-decider (+0.022), hurts it for Kev-27B (−0.028), and leaves Jev and OpenAI Decisions unchanged.

Changes in AURC under surface perturbations stay within ±0.08 per task for every coder except Kev-9B, whose option-order sensitivity raises AURC by up to 0.23. Jev's flips concentrate on its low-confidence decisions (AUROC 0.82–0.99), so its instability mostly shows up as uncertainty.

5 Experimental questions: what it takes to triage

The analyses in this section were specified in amendments v1.1–v1.4, but their details were fixed after the primary results had been seen, and the corpus guarantee was added and revised after external reviews. All are exploratory (Appendix A).




Figure 3: Risk–coverage on the test split for a subset of coders. Each curve accepts decisions from most to least confident. The dotted line is 5% error, and the shaded band is the region a 5% target accepts. On the dialogue tasks most coders never reach it at any meaningful coverage.

Table 6: MFRC: what the accepted decisions are (percent). 11% of test decisions are codes that apply. The prevalence baseline reads no text: it predicts 'absent' for every code, with confidence equal to that code's share of 'absent' labels.

coder	naive: accepted	naive: error	naive: applying codes found	corpus LTT: accepted	corpus LTT: error	corpus LTT: share 'absent'	corpus LTT: applying codes found	corpus LTT: applying codes deferred
Jev	77.8	3.8	34.6	59.8	1.6	96.6	17.1	75.8
OpenAI Decisions	72.5	4.4	12.9	0.0	–	–	0.0	100.0
Clef (27B)	90.2	4.9	53.8	82.3	3.0	94.6	34.9	48.2
Clef-flash (9B)	89.1	4.7	57.4	77.9	2.7	94.1	35.4	52.3
pplx-decider	91.8	4.9	61.5	77.1	2.3	93.9	38.0	51.7
Kev-9B	87.1	4.7	39.0	67.1	2.4	99.5	2.2	83.9
Kev-27B	94.0	4.9	54.8	76.6	2.1	96.7	21.1	66.6
Luna verbal	79.5	3.9	45.0	64.0	2.2	93.9	30.4	62.6
Haiku verbal	74.9	3.4	30.2	65.8	1.7	96.1	21.3	70.7
gpt-oss verbal	83.0	4.4	39.1	0.0	–	–	0.0	100.0
Sonnet verbal	89.9	4.5	52.8	82.7	2.5	94.6	35.8	50.4
prevalence baseline	75.0	3.6	0.0	0.0	–	–	0.0	100.0

Accepted: share of test decisions; error: among them; share 'absent': accepted decisions that say a code does not apply; applying codes found: applying codes accepted with the right label, over all applying codes; deferred: applying codes left for a person. The baseline's naive scores are fitted on all calibration comments; for corpus LTT they are fitted on half and certified on the other half. Design-weighted.

5.1 EQ1: Does calibration error predict triage?

Raw calibration errors range from 0.05 to 0.33 (Table 3). They are cheap to reduce: a Platt or isotonic map from confidence to accuracy, fitted per task on the calibration split, brings every signal's mean ECE over tasks to 0.03–0.07 (Figure 9 and Table 13, appendix). Platt's map leaves error ranking unchanged for every




Figure 4: RQ2. Left: Spearman correlation between model uncertainty and human label entropy (MFRC: 1,382 comments; AnnoMI: 91–93 utterances from four transcripts). Right: κ against the majority of the other annotators (grey bar: range over individual annotators; tick: median; dots: each model's mean over the same references). Unweighted.




Figure 5: RQ3: share of decisions that change under each perturbation (design-weighted mean over the tasks each cell covers; task counts in brackets). Hatched cells were not run. "No previous turn" removes information rather than rewording the request.

decision model and verbalized signal; only for the near-saturated token probabilities and vote shares, whose confidence carries little signal, can the fitted map flatten or even reverse it. Temperature scaling of the full probability distribution, by contrast, is fragile here: models that output exact zeros and ones make the fit depend on how those are floored before taking logarithms (Table 35). With a floor of 10^{-4}, temperature scaling calibrated Jev well and appeared to lower the token probabilities' error ranking (Luna 0.558 to 0.489); with 10^{-12} it leaves Jev's ECE unchanged and raises Luna's ranking to 0.579. We therefore use Platt maps as the recalibration yardstick and draw no conclusion from temperature scaling. Low aggregate ECE alone does not predict useful selection: Clef has one of the lowest raw ECEs (0.055) but ranks errors worse than Jev (ECE 0.120). The raw reliability curves show how models are miscalibrated: Jev and OpenAI Decisions are overconfident at high confidence, Kev-27B is underconfident, and Sonnet and pplx-decider are close to calibrated. Taken at face value, raw probabilities mislead the overconfident coders: "accept if confidence $\geq$0.95" accepts 36–64% of decisions for Jev, OpenAI Decisions, Luna and gpt-oss at 12–14% error, and almost every decision at 24–33% error for the token probabilities and Qwen3.5-9B's verbalized confidence. The other decision models, Haiku, Sonnet and Qwen3.8-2.4T stay below 5% error, mostly because few of their decisions reach 0.95 (4–31%). ECE here is top-label calibration against the majority label; calibration

against the distribution of human labels [4] is a different target, which RQ2 approaches.

5.2 EQ2: Do threshold rules keep their target, and what does a guarantee cost?

The naive rule overshoots. Over 500 random cluster re-splits per task, the naive rule's held-out error exceeds 5% in 47–52% of MFRC re-splits for Jev, Clef, Clef-flash, pplx-decider and both Kev models, and in 28% for OpenAI Decisions (Figure 6; per-task rates in Tables 15 and 16). A threshold chosen to sit just under 5% on calibration data lands on either side of 5% on new data about equally often. The LLMs' verbalized confidence overshoots less on MFRC (0–19%), probably because its coarse confidence levels put the threshold at a tie boundary with room to spare. On the dialogue tasks, wherever a decision model's naive rule accepts more than 5% of decisions, its held-out error exceeds 5% in 37–85% of re-splits.

A guarantee that ignores clustering fails. LTT on decisions treats the eight codes of a comment, and the utterances of a transcript, as independent. They are not. On MFRC its held-out error exceeds 5% in 5.8–11.2% of re-splits for every decision model, above the nominal 5%. In simulations with calibrated confidence and errors correlated within clusters (Table 30), the population risk of its threshold exceeds 5% in 6% of runs with independent errors, in 14% with strong correlation in MFRC-like clusters of eight, and in 18–31% with dialogue-like clusters; the error on the uncoded remainder exceeds 5% in 10–30% of runs.

The corpus guarantee holds, and shows the cost. Corpus LTT (§3.4) never exceeds 5% held-out error in any re-split of any task. Because each test split is the uncoded remainder of a random split, this is a direct check of its guarantee. LTT on i.i.d. clusters never exceeds it either, and in simulation both exceed 5% in at most 0.3% of runs, for either target. On the frozen MFRC split, corpus LTT certifies 60–83% of decisions for six of the seven decision models and for Luna's, Haiku's and Sonnet's verbalized confidence, at realized test errors of 1.6–3.0% (Table 5). It certifies nothing for OpenAI Decisions (at its highest thresholds its calibration error, 2.5–3.8%, is too close to 5% for a test corrected for 16 thresholds), gpt-oss, Qwen3.8-2.4T (its subset has too few calibration comments), the token probabilities or the agreement signals. The frozen split is one draw: over the re-splits, corpus LTT accepts on average 65–85% of MFRC decisions for the same coders, and 64% for gpt-oss.

With whole transcripts or lessons hand-coded, as in our splits, corpus LTT certifies nothing on the dialogue tasks, for any coder, and with this procedure at our calibration sizes nothing better was possible. The test caps its bets and scales each unit by B, the weight of the largest unit, so an error-free unit multiplies the evidence by at most $1 + 0.05 \times (\text{its weight}/B)$, whatever the order, and the evidence must reach $16/0.05 = 320$ (Appendix B). A typical transcript carries only 8–27% of the largest one's weight. On AnnoMI and TalkMoves student, even a coder that is never wrong could not be certified, whichever transcripts were hand-coded; on TalkMoves teacher fewer than 388 of the 444 lessons cannot suffice (Table 31).

The corpus guarantee allows any dependence, so single utterances drawn at random, each coded with its context, are valid units too. They weigh about the same, and a perfect coder is then certified after a median of 139–163 hand-coded segments. Under that design, with 30% of segments hand-coded, the real coders still certify almost nothing (Table 32): pplx-decider and Kev-27B on AnnoMI therapist obtain a certificate in 2 and 1 of 200 re-splits (accepting about 43% and 39% of decisions when they do), and the other coder–task pairs in none. The confident accepted sets supply too little evidence of $\leq$5% error at this budget. On the first re-split's roughly 430 hand-coded segments, 11 of the 44 coder–task pairs have no grid threshold at or below 5% error against the majority label; 30 have one, but it accepts at most 65 segments (median 9); and the three larger qualifying sets (191–227 segments, on AnnoMI therapist) sit at about 4.5%, too close to 5% for a conservative test to separate. On the same re-splits the naive rule exceeds 5% held-out error in up to 78% of them. On dialogue, then, the binding constraints are the sampling design first and then the amount and accuracy of confident evidence, not dependence among utterances. LTT on decisions appeared to certify 42% (Kev-27B) and 24% (Sonnet) on AnnoMI therapist under the transcript design; those certificates were not valid.

How much hand-coding a guarantee needs. The calibration-budget curves (Figure 10, appendix) draw smaller calibration sets of whole MFRC comments, keeping the test split as the remainder. Corpus LTT certifies nothing with 50, 100 or 200 hand-coded comments, and 2% (Jev) to 78% (Sonnet) with 400.




Figure 6: EQ2 on MFRC, the only task where the guaranteed rules accept anything when whole clusters are hand-coded, over 500 random cluster re-splits. Left: share of re-splits whose held-out error exceeds 5% (dotted: 5%). Right: mean share of test decisions accepted; black ticks mark the oracle on the frozen split. LTT on decisions assumes independent decisions and LTT on i.i.d. clusters independent clusters; corpus LTT assumes only that the hand-coded clusters are a random sample, visited in random orders.

The naive rule accepts as much with 50 comments as with 600, but exceeds 5% held-out error in up to 54% of draws (pplx-decider) and still in 27% with 400. Testing one threshold fixed in advance (0.95) instead of the grid halves the comments a perfect coder needs (64). It certifies gpt-oss (72%) but still not OpenAI Decisions, and it raises Luna's share (64% to 75%); for the other certified coders the fixed threshold is restrictive and certifies less than the grid, for example Jev 17% instead of 60% (Table 34).

Thresholds do not transfer. A threshold fitted on the other four tasks exceeds 5% error in 52 of the 64 task–coder cells where it accepts anything (median 16% on the dialogue tasks), and a fixed "accept $\geq$0.95" rule in 52 of 75. Guarantees do not travel either. Corpus LTT does not apply, because the other tasks are not a sample of the new corpus, and LTT on i.i.d. clusters pooled over the other four tasks certifies nothing at all. This matches Lu and Wu [37], who find that rejection thresholds of typed decision models do not carry across datasets.

5.3 EQ3: Ranking or ties at the top?

Even a threshold fitted on the test set itself (the oracle) accepts only 16% of Jev's decisions at $\leq$5% error, against 40% for Sonnet. Large, error-prone ties at the top contribute to this (Figure 7). On the dialogue tasks Jev places 8–30% of its decisions at exactly its top confidence (1.00), and 6.5–12.3% of those are wrong; OpenAI Decisions behaves the same way (up to 25% of decisions, with up to 12% error). A threshold must accept or reject such a tie as a whole, and for Jev none of the dialogue thresholds reaches 5% empirical error. No other coder puts more than 7.5% of decisions in its top block, and Clef, Kev and pplx-decider put almost none there.

Per-code recalibration fits a separate Platt map for each predicted code (for MFRC, each code) on the calibration split. It splits the ties and improves error ranking for every coder with enough calibration data: by +0.025 (Sonnet, Kev-27B) to +0.12 (Kev-9B, Qwen3.5-9B), and by +0.040 [0.027, 0.054] for Jev (Figure 11, appendix; intervals conditional on the fitted maps). For coders that return exact zeros and ones, the size of the gain depends on the floor applied before the logit: Jev's is +0.053 with a floor of 10^{-4} instead of 10^{-12}, and the token probabilities move by up to 0.024, while the other decision models and verbalized signals change by at most 0.003 (Table 35). Per-code maps also narrow the differences between decision models: six of the seven land within 0.80–0.83 (OpenAI Decisions 0.77), against 0.69–0.79 raw. Part of this




Figure 7: EQ3: top-confidence tie blocks on the dialogue tasks. Top: share of decisions at the coder's maximum confidence. Bottom: error among them; blocks of fewer than 10 decisions are omitted. Above the dotted line, the top block itself exceeds the 5% target.

gain is the information in which code was predicted. Scoring each decision only by the calibration accuracy of its predicted code, with no confidence at all, gives 0.66–0.71 (Table 33); for Kev-9B this alone beats its raw confidence (0.713 vs 0.694). The maps do not make coders equivalent: oracle coverage with them still ranges from 23% (Kev-9B) to 46% (pplx-decider). On identical items, Jev with per-code maps comes close to Sonnet's raw confidence, but the interval does not resolve the difference either way (-0.004 [-0.018, 0.008]), and it trails Sonnet with its own per-code maps (-0.030 [-0.041, -0.019]; significant on MFRC, AnnoMI therapist and TalkMoves student).

Better ranking did not buy certified coverage at our calibration sizes. A learned map must be fitted on clusters that are not then used to certify it, so the maps were fitted on half of the MFRC calibration comments and certified on the other half (304 comments). Corpus LTT then certifies 66–75% for Clef, Clef-flash, pplx-decider and Sonnet, against 77–83% with their raw confidence on all 608 comments, and nothing for the other coders.

5.4 EQ4: Do related 9B decision models outperform a 9B instruct model's confidence?

Clef-flash and Kev-9B are built on Qwen3.5-9B (Kev-9B on the base checkpoint; Clef-flash on a variant Cloudflare does not specify), and we ran the Qwen3.5-9B instruct model as a plain LLM (Table 7; pre-specified secondary). These systems differ in training, read-out and request format, so this compares related systems, not a controlled ablation. Both decision models rank errors better than the instruct model's verbalized confidence (+0.065 and +0.048 AUROC). Against its answer-token probabilities the gain is small: +0.027 [0.004, 0.052] for Clef-flash, and not significant for Kev-9B. Under the naive 5%-target rule both accept 15–22 points more, because their probabilities do not pile up at 1.0. Clef-flash and Kev-9B do not differ significantly.

Our token probabilities are read after a one-sentence rationale, which likely commits the model and contributes to the saturation. Li and Wagle [32] read next-token probabilities over option identifiers directly, without generated text, and find that a 4B base model matches decision models built on the same backbone. Together these results suggest, as a hypothesis, that much of a decision model's advantage comes from reading out a probability rather than from its training; a matched-checkpoint experiment would test it.

Table 7: EQ4: two 9B decision models built on Qwen3.5-9B vs the Qwen3.5-9B instruct model's own confidence (pooled over tasks).

comparison	metric	difference	95% CI	p (bootstrap)
Clef-flash (9B) – Qwen3.5-9B verbal	error AUROC	0.065	[0.048, 0.085]	<0.001
Clef-flash (9B) – Qwen3.5-9B verbal	coverage@5%	0.221	[0.181, 0.297]	<0.001
Clef-flash (9B) – Qwen3.5-9B logprob	error AUROC	0.027	[0.004, 0.052]	0.026
Clef-flash (9B) – Qwen3.5-9B logprob	coverage@5%	0.161	[0.110, 0.211]	<0.001
Kev-9B – Qwen3.5-9B verbal	error AUROC	0.048	[0.030, 0.066]	<0.001
Kev-9B – Qwen3.5-9B verbal	coverage@5%	0.205	[0.152, 0.280]	<0.001
Kev-9B – Qwen3.5-9B logprob	error AUROC	0.010	[-0.018, 0.036]	0.512
Kev-9B – Qwen3.5-9B logprob	coverage@5%	0.146	[0.079, 0.189]	<0.001
Clef-flash (9B) – Kev-9B	error AUROC	0.018	[-0.007, 0.043]	0.142
Clef-flash (9B) – Kev-9B	coverage@5%	0.015	[-0.043, 0.097]	0.560

Coverage is the naive rule's share accepted. Kev-9B starts from the base checkpoint and Clef-flash's exact variant is unspecified, so these contrasts compare related systems with different training and read-out, not a controlled training ablation.

5.5 EQ5: Which configurations give the most guaranteed automation per dollar?

When whole clusters are hand-coded, as in our splits, certificates exist only on MFRC, so we compare configurations there (Figure 8), each at the API cost of its own policy. Table 18 gives the certified results and Table 17 pooled results under the naive rule and the oracle.

- **A coder that reads nothing is not certified.** The prevalence baseline accepts 75% of MFRC decisions at 3.6% error under the naive rule, all of them "absent". Its scores are learned from labels, so they must be fitted on half of the calibration comments and certified on the other half, and corpus LTT then certifies none of its decisions.
- **Single decision models:** pplx-decider certifies 77% at $0.03 per 1,000 comments, Clef-flash 78% at $0.09 and Clef 82% at $0.24; Sonnet certifies 83% at $4.52.
- **A pplx-decider + Kev-27B agreement gate**, which accepts where both give the same label, certifies 81% at $0.34. Its difference from Sonnet is −1.6 [−10.0, +3.8] points: not significant, which is not the same as equivalent.
- **Kev-27B** certifies 77% at an estimated $0.32 per 1,000 comments, significantly more than Jev's 60% (+16.7 [+7.1, +38.2] points).
- **Chains are certified as a whole** (§3.4), and the larger joint test costs power: Kev-27B → Sonnet certifies 82% and Jev → Sonnet 77%, no more than Sonnet alone.
- **The seven-model committee** certifies 84%, slightly more than its best member (Clef, 82%), at four times Clef's cost ($0.97); its difference from Sonnet is +1.8 [−8.3, +2.8] points.

Accepted decisions are not the same as reading saved, or as codes found. A comment leaves the human queue only when all eight of its codes are accepted: under Sonnet's certified policy, 66% of the uncoded remainder's comments still need a person to read at least one code, and under Jev's 93%. Counting the 608 hand-coded calibration comments as well, a person reads 76% and 95% of all comments (Table 18). And 94–99.5% of the certified decisions say that a code does not apply: pplx-decider's certified decisions label 38% of the codes that apply, Sonnet's 36%, Jev's 17% and Kev-9B's 2% (Figure 8, right; Table 6). Costs are list prices for inference only. They exclude the hand-coded calibration sample, which a guarantee requires in any case, and the human reading that remains; Kev's figure is an estimated warm-serving cost. Human reading can dominate: per 1,000 remainder comments, Sonnet costs about $4.49 more than pplx-decider in inference and leaves about 75 fewer comments for a person. Assuming the same cost per human-read comment under both policies, Sonnet has the lower combined inference-plus-reading cost on the remainder once that cost exceeds about $0.06; this is a sensitivity calculation, not a measured reading time.

5.6 EQ6: Are the results artefacts?

Table 8 summarizes four checks; each bounds a specific concern rather than proving validity.




Figure 8: EQ5 on MFRC. Left: share of decisions certified at $\leq$5% error by corpus LTT vs API cost per 1,000 comments under the same policy (log scale); diamonds are two-coder configurations, certified jointly. Right: share of the codes that apply that the certified decisions label correctly. Coders that certify nothing (OpenAI Decisions, gpt-oss, the token probabilities, the agreement signals and the prevalence baseline) are not shown. Kev's cost is an estimated GPU serving cost.

- **Repeatability.** In the repeated requests we tested (100 test segments per task, sent twice), OpenAI Decisions, Clef, Clef-flash and pplx-decider returned identical outputs, and Haiku changed 0.03% of labels. Jev changed 2.1%, almost all at low confidence; Sonnet, which runs at the provider's default sampling settings, 3.3%; and Luna 6.6% despite temperature 0.
- **Prompt sensitivity** (v1.4). One alternative prompt, which asks for a probability for every option [54], does not improve the verbalized baselines: Sonnet −0.034 [−0.056, −0.011], Haiku −0.010 [−0.045, 0.022]. Our canonical prompt does not appear to handicap them, though one alternative cannot rule out a better one.
- **Memorization** (v1.3). Given the first half of 100 items per dataset, no model–dataset pair met the pre-specified completion flag, and naming the dataset never significantly increased overlap with the true continuation. Near-verbatim matches were rare and occurred with and without the name; they include a predictable counting sequence in a TalkMoves item and Du Bois quotations in Dunivin passages (Table 24). Naming the dataset raised label recall in three model–task cells; a decoy name with the same description explains two as task framing, and the third (Luna on MFRC, +0.13 over the decoy) does not raise Luna's coding accuracy on those items. Decision models return no text and could not be probed.
- **Label noise and replication.** When Jev, Luna, Haiku or gpt-oss disagreed with the human label on a sampled, high-confidence-enriched item, adjudication sided with the coder in 55–64% of cases (Table 22); counting only the author's verdicts (the disputed items the author adjudicated and the 12-item audit of panel-agreed items), it did so in 52–62%. This echoes Liu et al. [36], but the sample cannot estimate the overall rate of label error. Our harness recomputes the agreement Dunivin reports for his GPT-4 runs from his released predictions [12], exactly, and Sonnet's mean κ on his test set (0.679) is close to his best reported configuration (0.68).

Table 8: EQ6: validity checks. Run-to-run flips: identical requests sent twice (100 test segments per task; 0 means identical outputs in these repeats); option-order flips: reversed and shuffled options (RQ3 arms); memorization probe with decoy-name control (amendment v1.3, deviation 14). Decision models return no text, so they could not be probed.

coder	run-to-run label flips	flips under option order	verbatim recall (completion)	label recall beyond decoy
Jev	0.021	0.042	not assessed	not assessed
OpenAI Decisions	0.000	0.096	not assessed	not assessed
Clef (27B)	0.000	–	not assessed	not assessed
Clef-flash (9B)	0.000	0.006	not assessed	not assessed
pplx-decider	0.000	0.064	not assessed	not assessed
Kev-9B	–	0.249	not assessed	not assessed
Kev-27B	–	–	not assessed	not assessed
Luna verbal	0.066	0.103	no evidence	MFRC
Haiku verbal	0.000	–	no evidence	no evidence
Sonnet verbal	0.033	0.056	no evidence	no evidence
gpt-oss verbal	–	–	no evidence	no evidence
Qwen3.5-9B verbal	–	–	no evidence	no evidence
Qwen3.8-2.4T verbal	–	–	no evidence	no evidence

Prompt sensitivity (amendment v1.4): a verbalized-distribution prompt changes error AUROC by –0.034 [–0.056, –0.011] for Sonnet and –0.010 (n.s.) for Haiku.

6 Discussion

A recipe for model-assisted coding. For a researcher who wants to code a corpus with a fixed codebook and check only part of it by hand, the results suggest four steps.

1. Hand-code a random sample of units from the corpus itself, and set part of it aside for certification. Units can be comments, transcripts, random fixed-size blocks of turns, or single utterances coded with their context; units of similar weight make a guarantee far cheaper (§5.2). Random selection is what makes the guarantee possible; thresholds from other codebooks, and fixed rules such as "accept $\geq$0.95", did not carry over in our data.
2. On the other part, a pilot sample, choose the coder and its scores. Compare how many decisions each candidate accepts at the target, which after recalibration depends mostly on accuracy; low ECE is not a sufficient criterion (§5.1). Fit any per-code maps here: they improved error ranking for every coder with enough calibration data, but maps fitted on the certification sample would void its guarantee (§5.3). Compare the accepted share with a prevalence baseline that reads no text, and check how many applying codes the accepted decisions contain (§4.1).
3. Freeze the chosen coder, scores and threshold grid, then certify on the set-aside sample with a rule that respects how it was drawn, such as corpus LTT. Each certificate covers one configuration: choosing among configurations by their certification results needs all of them in one testing family. Our version needed about 120 error-free units of similar weight before it certified anything; with whole transcripts of very unequal length it could not certify even a perfect coder (§5.2).
4. Count what a person still has to read, including the hand-coded sample: in multi-label coding, a segment leaves the queue only when all its codes are accepted (§5.5).

In our data, pplx-decider alone gave the most certified automation per inference dollar on comments, and Clef, the pplx-decider + Kev-27B gate and the decision-model committee certified within two points of Sonnet, at 5–21% of its inference cost; the intervals do not resolve those differences. Once human reading is priced in, the ranking can change (§5.5).

What decision models are, and are not. Decision models are marketed as calibrated. In our data four of the seven have raw ECEs of 0.05–0.07 and Jev, OpenAI Decisions and Kev-9B 0.10–0.12; a Platt map per task reduces all of them to 0.03–0.07. What separates them raw is error ranking and resolution at the

top of the scale, where the category ranges from worse than a cheap LLM's verbalized confidence (Kev-9B, Clef-flash) to near-frontier (Kev-27B). Per-code recalibration narrows most of the ranking differences, partly by using which code was predicted, and leaves accuracy as the main differentiator. The comparison with a 9B instruct model, together with Li and Wagle [32], is consistent with the hypothesis that much of a decision model's advantage comes from reading out probabilities rather than generating them. Option order still changes up to 31% of a decision model's labels on average over tasks, and 55% in one task (§4.3); averaging over option rotations [71] is a cheap remedy we did not test.

Human labels are not gold. No coder fell below the range of individual annotators, and adjudication often sided with the model on sampled disagreements. Error measured against a single majority label may therefore overstate some model errors, and a 5% target against such a reference is partly a target against annotator noise [46, 58]. Agreement with annotators, which we measure, is not the same as interpretive validity, which we do not.

From labels to estimates. Triage bounds the error rate among the labels a researcher accepts, in aggregate; it says nothing about any one label. Many qualitative studies go on to report code frequencies or associations between codes. Prediction-powered and design-based estimators correct such quantities using a hand-coded subsample, without per-item guarantees [2, 15], and model confidence can decide which items to hand-code [18]. The calibration sample that triage needs can serve these estimators too, and they do not need a certified threshold, which makes them attractive on dialogue data, where we could certify almost nothing under either sampling design.

7 Limitations and follow-ups

- **Scope.** Five tasks on short segments (comments, utterances, sentences) from three public datasets. We have no long-form interviews: public interview data with applied codes is rare, and a private dataset requires ethics approval. Pooled estimates describe these five tasks, not a population of codebooks.
- **A dated snapshot.** Several APIs were in public beta, and the models will change. We release the harness, the analysis plan and every model output, so every number can be recomputed from the public datasets and the study re-run.
- **Guarantees.** Corpus LTT assumes the hand-coded clusters are a uniformly random subset of the corpus and that the test visits them in random orders; our split assigns clusters by a hash of their id, which we treat as random, and the orders come from a recorded seed. Each certificate covers one configuration. The procedure is conservative (in simulation it accepted less than the best safe threshold), and its cost on dialogue comes from hand-coding whole transcripts and scaling every transcript by the largest one. Sampling single utterances avoids most of that, although at our budget the coders' confident dialogue decisions then still gave too little evidence. The population version additionally needs independent clusters and a true bound on cluster weight. For the corpus guarantee, random re-splits are a direct check (the test split is the uncoded remainder); for the population version they are only a diagnostic.
- **Post-hoc analysis.** The plan was not externally registered. Sonnet was extended to the full sample after subset results were seen, the A3 analyses were revised after their first output, and the corpus guarantee, the prevalence analysis and several controls were added or revised after external reviews. All are labelled exploratory.
- **LLM read-out.** Token probabilities were read after a generated rationale, and multi-label verbalized probabilities were converted under a reading the prompt did not fix (§3); both may disadvantage the LLM baselines. We tested one alternative prompt.
- **Adjudication** covered a stratified, high-confidence-enriched sample of 200 items drawn from disagreements with six label sources; it relied partly on an LLM panel whose families overlap with the coders it judged (Claude Opus with Haiku and Sonnet; GPT-6 Sol with Luna and OpenAI Decisions), and the author, the only human adjudicator, did not repeat a sitting to measure their own consistency.
- **Measurement.** RQ2 rests on four AnnoMI transcripts and is unweighted. ECE is top-label calibration against the majority label. Costs are October 2026 list prices for inference only; Kev's are estimated warm-serving costs.

- **Coverage gaps.** Kev-9B's robustness arms cover one to four tasks, and Kev-27B was run on the main and format arms only. Decision models cannot be probed for memorization; Kev's published training data excludes our datasets.

8 Conclusion

Model confidence can select low-error coding decisions, but less than accepted-decision shares suggest. Low calibration error is not enough: what matters is how well confidence ranks errors and whether the top of the scale is resolved, and per-code recalibration helps with both. Error targets need a guarantee, and a valid guarantee must respect how the hand-coded sample was drawn. With one, models certified most decisions on Reddit comments, nearly all of them calls that a code does not apply. On dialogue they certified nothing when whole transcripts were hand-coded; sampling single utterances made a guarantee possible in principle, but at our budget the coders' confident dialogue decisions gave too little evidence for it. The best decision-model configurations certified about as much as a frontier LLM on comments, at a small fraction of its cost.

Data and code availability

The harness, the analysis plan with its amendments and deviations log, every model output (one row per decision, with the probability and the model version returned), the samples and splits, the adjudication verdicts, a text-free spend ledger (405,339 requests; $78.56 in API fees, plus GPU time for Kev) and the paper source are at https://github.com/firish/margin. The datasets are not redistributed; they are available from their authors under their own terms (MFRC: CC BY 4.0; TalkMoves: CC BY-NC-SA 4.0; AnnoMI and Dunivin: no licence stated).

Ethics statement

All data are public and were collected and annotated by their original authors; we used them only for evaluation. Only these public texts were sent to commercial APIs; no private or newly collected data were used. AnnoMI's counselling conversations are transcribed from publicly available demonstration videos of motivational interviewing. The only human participant was the author, as adjudicator.

Use of AI assistants

The author used an AI coding assistant (Claude) to implement the harness and to draft and edit the manuscript. An external AI reviewer (GPT-6.1) commented on successive drafts, and its comments led to the changes logged as deviations 16–18. LLMs also served as study subjects and as members of the adjudication panel, as described above. The author takes full responsibility for the content.

References

[1] Anastasios N. Angelopoulos, Stephen Bates, Adam Fisch, Lihua Lei, and Tal Schuster. Conformal Risk Control. arXiv preprint arXiv:2208.02814, 2022.

[2] Anastasios N. Angelopoulos, Stephen Bates, Clara Fannjiang, Michael I. Jordan, and Tijana Zrnic. Prediction-Powered Inference. *Science*, 382(6671):669–674, 2023. doi: 10.1126/science.adi6000.

[3] Anastasios N. Angelopoulos, Stephen Bates, Emmanuel J. Candès, Michael I. Jordan, and Lihua Lei. Learn then test: Calibrating predictive algorithms to achieve risk control. *The Annals of Applied Statistics*, 2025. doi: 10.1214/24-aoas1998.

[4] Joris Baan, Wilker Aziz, Barbara Plank, and Raquel Fernández. Stop Measuring Calibration When Humans Disagree. In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pages 1892–1915, 2022. doi: 10.18653/v1/2022.emnlp-main.124.

[5] Sher Badshah, Ali Emami, and Hassan Sajjad. Judge, Retrieve, or Abstain: Uncertainty-Guarded LLM Judging with Provable Risk Guarantees. arXiv preprint arXiv:2608.17994, 2026.

[6] Lingjiao Chen, Matei Zaharia, and James Zou. FrugalGPT: How to Use Large Language Models While Reducing Cost and Improving Performance. *Transactions on Machine Learning Research*, 2024. arXiv:2305.05176.

[7] Robert Chew, John Bollenbacher, Michael Wenger, Jessica Speer, and Annice Kim. LLM-Assisted Content Analysis: Using Large Language Models to Support Deductive Coding. arXiv preprint arXiv:2306.14924, 2023.

[8] Cloudflare. Clef and clef-flash: Decision models on workers AI. https://developers.cloudflare.com/workers-ai/models/clef/, 2026. Released 2026-10-01; weights at https://huggingface.co/Cloudflare/clef; accessed 2026-10-11.

[9] Jacob Cohen. A Coefficient of Agreement for Nominal Scales. *Educational and Psychological Measurement*, 1960. doi: 10.1177/001316446002000104.

[10] Steven Denney and Matthew DiGiuseppe. JEV versus LLMs: Accuracy, Cost and Calibration on Seven Political Science Replications. arXiv preprint arXiv:2610.06625, 2026.

[11] Zackary Okun Dunivin. Scalable Qualitative Coding with LLMs: Chain-of-Thought Reasoning Matches Human Performance in Some Hermeneutic Tasks. arXiv preprint arXiv:2401.15170, 2024.

[12] Zackary Okun Dunivin. Scaling Hermeneutics: A Guide to Qualitative Coding with LLMs for Reflexive Content Analysis. *EPJ Data Science*, 14:28, 2025. doi: 10.1140/epjds/s13688-025-00548-8.

[13] Zackary Okun Dunivin, Mobina Noori, Seth Frey, and Curtis Atkinson. Self-reflection in Automated Qualitative Coding: Improving Text Annotation through Secondary LLM Critique. arXiv preprint arXiv:2601.09905, 2026.

[14] Robin Dunn, Larry Wasserman, and Aaditya Ramdas. Distribution-Free Prediction Sets for Two-Layer Hierarchical Models. *Journal of the American Statistical Association*, 118(544):2491–2502, 2023. doi: 10.1080/01621459.2022.2060112.

[15] Naoki Egami, Musashi Hinck, Brandon M. Stewart, and Hanying Wei. Using Imperfect Surrogates for Downstream Inference: Design-based Supervised Learning for Social Science Applications of Large Language Models. In *Advances in Neural Information Processing Systems 36*, pages 68589–68601, 2023.

[16] Yonatan Geifman and Ran El-Yaniv. Selective Classification for Deep Neural Networks. arXiv preprint arXiv:1705.08500, 2017.

[17] Fabrizio Gilardi, Meysam Alizadeh, and Maël Kubli. ChatGPT outperforms crowd workers for text-annotation tasks. *Proceedings of the National Academy of Sciences*, 2023. doi: 10.1073/pnas.2305016120.

[18] Kristina Gligorić, Tijana Zrnic, Cinoo Lee, Emmanuel Candès, and Dan Jurafsky. Can Unconfident LLM Annotations Be Used for Confident Conclusions? In *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics*, pages 3514–3533, 2025. doi: 10.18653/v1/2025.naacl-long.179.

[19] Shahriar Golchin and Mihai Surdeanu. Time Travel in LLMs: Tracing Data Contamination in Large Language Models. arXiv preprint arXiv:2308.08493, 2023.

[20] Chuan Guo, Geoff Pleiss, Yu Sun, and Kilian Q. Weinberger. On Calibration of Modern Neural Networks. arXiv preprint arXiv:1706.04599, 2017.

[21] Kevin David Hayes, Arka Pal, Haosong Zhang, Tom Goldstein, and Micah Goldblum. Pinocchio: Fast Uncertainty Estimates for Black-Box Language Models. arXiv preprint arXiv:2609.24881, 2026.

[22] Dan Hendrycks and Kevin Gimpel. A Baseline for Detecting Misclassified and Out-of-Distribution Examples in Neural Networks. In *International Conference on Learning Representations*, 2017. arXiv:1610.02136.

[23] Sture Holm. A Simple Sequentially Rejective Multiple Test Procedure. *Scandinavian Journal of Statistics*, 6(2):65–70, 1979.

[24] D. G. Horvitz and D. J. Thompson. A Generalization of Sampling Without Replacement from a Finite Universe. *Journal of the American Statistical Association*, 1952. doi: 10.1080/01621459.1952.10483446.

[25] Hazem Ibrahim and Yasir Zaki. Evaluating Decision Models for Text Annotation in Computational Social Science. arXiv preprint arXiv:2609.24574, 2026.

[26] Jaehun Jung, Faeze Brahman, and Yejin Choi. Trust or Escalate: LLM Judges with Provable Guarantees for Human Agreement. In *International Conference on Learning Representations (ICLR)*, 2025.

[27] Saurav Kadavath, Tom Conerly, Amanda Askell, Tom Henighan, Dawn Drain, Ethan Perez, Nicholas Schiefer, Zac Hatfield-Dodds, Nova DasSarma, Eli Tran-Johnson, Scott Johnston, Sheer El-Showk, Andy Jones, Nelson Elhage, Tristan Hume, Anna Chen, Yuntao Bai, Sam Bowman, Stanislav Fort, Deep Ganguli, Danny Hernandez, Josh Jacobson, Jackson Kernion, Shauna Kravec, Liane Lovitt, Kamal Ndousse, Catherine Olsson, Sam Ringer, Dario Amodei, Tom Brown, Jack Clark, Nicholas Joseph, Ben Mann, Sam McCandlish, Chris Olah, and Jared Kaplan. Language Models (Mostly) Know What They Know. arXiv preprint arXiv:2207.05221, 2022.

[28] Leslie Kish. *Survey Sampling*. Wiley, New York, 1965.

[29] Klaus Krippendorff. *Content Analysis: An Introduction to Its Methodology*. SAGE, 4 edition, 2019.

[30] Noah Lee, Na Min An, and James Thorne. Can Large Language Models Capture Dissenting Human Voices? In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 4569–4585, 2023. doi: 10.18653/v1/2023.emnlp-main.278.

[31] Xinyu Li, Yi Zhou, Guanqun Cao, Zeyu Fu, Tianjin Huang, and Gaojie Jin. Localize-Then-Decide Guarantees for LLM Judgments. arXiv preprint arXiv:2608.25824, 2026.

[32] Yinheng Li and Justin Wagle. LLM-as-Jev: LLMs Are Already Jev-Style Decision Models – When and How to Fine-Tune Them. arXiv preprint arXiv:2610.02076, 2026.

[33] Yubo Li, Yidi Miao, Ramayya Krishnan, and Rema Padman. JEV-as-a-Judge: Accept When Confident, Escalate When Unsure. arXiv preprint arXiv:2609.26550, 2026.

[34] Zijian Li, Luzhen Tang, Mengyu Xia, Xinyu Li, Naping Chen, Dragan Gašević, and Yizhou Fan. When LLMs fall short in Deductive Coding: Model Comparison and Human AI Collaboration Workflow Design. arXiv preprint arXiv:2512.21041, 2025.

[35] Chin-Yew Lin. ROUGE: A package for automatic evaluation of summaries. In *Text Summarization Branches Out*, pages 74–81. Association for Computational Linguistics, 2004. URL https://aclanthology.org/W04-1013/.

[36] Alex Liu, Lief Esbenshade, Michael Xiao, Victor Tian, Zachary Zhang, Kevin He, and Min Sun. Agreement Is Not Quality: Blind Expert Verification of Human and LLM Qualitative Coding When Human Consensus Is Not Ground Truth. arXiv preprint arXiv:2607.28890, 2026.

[37] Jiawen Lu and Tongtong Wu. Benchmarking Candidate Coverage and Rejection Policy Transfer in Typed Decision Models. arXiv preprint arXiv:2610.03387, 2026.

[38] Jerome Marston, Tino Kreutzer, Salomé Garnier, Ella Boone, Phuong N Pham, and Patrick Vinck. Can Large Language Models Reliably Code Qualitative Humanitarian Data? A Benchmark Study Against Human Expert Adjudication. arXiv preprint arXiv:2606.26541, 2026.

[39] Joseph Matveyenko, James Liu, John David Parsons, Ryan A. Brown, Alina Palimaru, and Prateek Puri. Development and Benchmarking of a Blended Human-AI Qualitative Research Assistant. arXiv preprint arXiv:2512.00009, 2025.

[40] Jonathan Mellon, Jack Bailey, Ralph Scott, James Breckwoldt, Marta Miori, and Phillip Schmedeman. Do AIs know what the most important issue is? Using language models to code open-text social survey responses at scale. *Research & Politics*, 2024. doi: 10.1177/20531680241231468.

[41] Theresa B. Moyers, Lauren N. Rowell, Jennifer K. Manuel, Denise Ernst, and Jon M. Houck. The Motivational Interviewing Treatment Integrity Code (MITI 4): Rationale, Preliminary Reliability and Validity. *Journal of Substance Abuse Treatment*, 65:36–42, 2016. doi: 10.1016/j.jsat.2016.01.001.

[42] OpenAI. Decisions API (public beta). https://platform.openai.com/docs/guides/decisions, 2026. Public beta from 2026-10-06; accessed 2026-10-11.

[43] Jared Palmer. Kev: Small jev-like decision models (kev 1.0). https://github.com/jaredpalmer/kev, 2026. Commit 2ecafc4; weights at https://huggingface.co/jaredpalmer; accessed 2026-10-11.

[44] Nicholas Pangakis, Samuel Wolken, and Neil Fasching. Automated Annotation with Generative AI Requires Validation. arXiv preprint arXiv:2306.00176, 2023.

[45] Perplexity. Decisions API: pplx-decider. https://docs.perplexity.ai/api-reference/decisions-post, 2026. Accessed 2026-10-11.

[46] Barbara Plank. The "Problem" of Human Label Variation: On Ground Truth in Data, Modeling and Evaluation. In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pages 10671–10682, 2022. doi: 10.18653/v1/2022.emnlp-main.731.

[47] John C. Platt. Probabilistic Outputs for Support Vector Machines and Comparisons to Regularized Likelihood Methods. In *Advances in Large Margin Classifiers*, pages 61–74. MIT Press, 1999.

[48] Amir Rafe and Subasish Das. Calibrated Decisions at Scale: Converting Police Crash Narratives into Probabilistic Crash Variables with a System One Model (Jev). arXiv preprint arXiv:2609.24052, 2026.

[49] Pranav Raikote, Korbinian Randl, Ioanna Miliou, Athanasios Lakes, and Panagiotis Papapetrou. CHiL(L)Grader: Calibrated Human-in-the-Loop Short-Answer Grading. arXiv preprint arXiv:2603.11957, 2026.

[50] María Jesús Rodríguez-Triana, Luis P. Prieto, Mohamed Saban, Juan I. Asensio-Pérez, Cristina Villa-Torrano, Inmaculada Haba-Ortuño, and Denis Gillet. One Prompt Does Not Fit All: Comparing Uniform and Adaptive Code-Specific Prompting for Deductive Qualitative Coding With Large Language Models. *Journal of Computer Assisted Learning*, 2026. doi: 10.1002/jcal.70334.

[51] Rahul Sharma, Andrew B. Duncan, Gaétan Marceau Caron, and Sebastian J. Vollmer. TypedBench: A Benchmark for Calibration, Framing Sensitivity, and Cost in System One Decision Models. arXiv preprint arXiv:2610.11392, 2026.

[52] Xin Sun, Jiahuan Pei, Jan de Wit, Mohammad Aliannejadi, Emiel Krahmer, Jos T. P. Dobber, and Jos A. Bosch. Eliciting Motivational Interviewing Skill Codes in Psychotherapy with LLMs: A Bilingual Dataset and Analytical Study. In *Proceedings of the 2024 Joint International Conference on Computational Linguistics, Language Resources and Evaluation (LREC-COLING 2024)*, pages 5609–5621, 2024.

[53] Abhijit Suresh, Jennifer Jacobs, Charis Harty, Margaret Perkoff, James H. Martin, and Tamara Sumner. The TalkMoves Dataset: K-12 Mathematics Lesson Transcripts Annotated for Teacher and Student Discursive Moves. In *Proceedings of the Language Resources and Evaluation Conference*, 2022.

[54] Katherine Tian, Eric Mitchell, Allan Zhou, Archit Sharma, Rafael Rafailov, Huaxiu Yao, Chelsea Finn, and Christopher Manning. Just Ask for Calibration: Strategies for Eliciting Calibrated Confidence Scores from Language Models Fine-Tuned with Human Feedback. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, 2023. doi: 10.18653/v1/2023.emnlp-main.330.

[55] Petter Törnberg. Best Practices for Text Annotation with Large Language Models. arXiv preprint arXiv:2402.05129, 2024.

[56] Jackson Trager, Alireza S. Ziabari, Elnaz Rahmati, Aida Mostafazadeh Davani, Preni Golazizian, Farzan Karimi-Malekabadi, Ali Omrani, Zhihe Li, Brendan Kennedy, Georgios Chochlakis, Nils Karl Reimer, Melissa Reyes, Kelsey Cheng, Mellow Wei, Christina Merrifield, Arta Khosravi, Evans Alvarez, and Morteza Dehghani. The Moral Foundations Reddit Corpus. arXiv preprint arXiv:2208.05545, 2022.

[57] TypeSafe. Jev: System one decision model (jev-1.13.0) documentation. https://docs.typesafe.ai, 2026. Accessed 2026-10-11.

[58] Alexandra N. Uma, Tommaso Fornaciari, Dirk Hovy, Silviu Paun, Barbara Plank, and Massimo Poesio. Learning from Disagreement: A Survey. *Journal of Artificial Intelligence Research*, 72:1385–1470, 2021. doi: 10.1613/jair.1.12752.

[59] Vladimir Vovk and Ruodu Wang. E-values: Calibration, combination and applications. *The Annals of Statistics*, 49(3):1736–1754, 2021. doi: 10.1214/20-AOS2020.

[60] Rose E. Wang and Dorottya Demszky. Is ChatGPT a Good Teacher Coach? Measuring Zero-Shot Performance for Scoring and Providing Actionable Insights on Classroom Instruction. In *Proceedings of the 18th Workshop on Innovative Use of NLP for Building Educational Applications*, pages 626–667, 2023. doi: 10.18653/v1/2023.bea-1.53.

[61] Xinru Wang, Hannah Kim, Sajjadur Rahman, Kushan Mitra, and Zhengjie Miao. Human-LLM Collaborative Annotation Through Effective Verification of LLM Labels. In *Proceedings of the CHI Conference on Human Factors in Computing Systems*, 2024. doi: 10.1145/3613904.3641960.

[62] Ian Waudby-Smith and Aaditya Ramdas. Estimating Means of Bounded Random Variables by Betting. *Journal of the Royal Statistical Society Series B: Statistical Methodology*, 86(1):1–27, 2024. doi: 10.1093/jrsssb/qkad009.

[63] Zixiu Wu, Simone Balloccu, Vivek Kumar, Rim Helaoui, Ehud Reiter, Diego Reforgiato Recupero, and Daniele Riboni. Anno-MI: A Dataset of Expert-Annotated Counselling Dialogues. In *ICASSP 2022 - 2022 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, 2022. doi: 10.1109/icassp43922.2022.9746035.

[64] Zixiu Wu, Simone Balloccu, Vivek Kumar, Rim Helaoui, Diego Reforgiato Recupero, and Daniele Riboni. Creation, analysis and evaluation of AnnoMI, a dataset of expert-annotated counselling dialogues. *Future Internet*, 15(3):110, 2023. doi: 10.3390/fi15030110.

[65] Ziang Xiao, Xingdi Yuan, Q. Vera Liao, Rania Abdelghani, and Pierre-Yves Oudeyer. Supporting Qualitative Analysis with Large Language Models: Combining Codebook with GPT-3 for Deductive Coding. In *28th International Conference on Intelligent User Interfaces*, 2023. doi: 10.1145/3581754.3584136.

[66] Miao Xiong, Zhiyuan Hu, Xinyang Lu, Yifei Li, Jie Fu, Junxian He, and Bryan Hooi. Can LLMs Express Their Uncertainty? An Empirical Evaluation of Confidence Elicitation in LLMs. arXiv preprint arXiv:2306.13063, 2023.

[67] Zixiang Xu, Zirui Song, Chiyu Zhang, Xiuying Chen, Xi Liu, Xiyang Hu, and Yue Zhao. JevOut: Natural Context Can Flip Decision Models. arXiv preprint arXiv:2609.30243, 2026.

[68] Boqin Yuan, Xiaoyi Gu, Fiona Li, Chang Wan, Angel Hsing-Chi Hwang, and Jieyu Zhao. CALICO: A Human-Centered, Codebook-Aligned System for Annotation. arXiv preprint arXiv:2609.14726, 2026.

[69] Bianca Zadrozny and Charles Elkan. Transforming classifier scores into accurate multiclass probability estimates. In *Proceedings of the eighth ACM SIGKDD international conference on Knowledge discovery and data mining*, 2002. doi: 10.1145/775047.775151.

[70] Hao Zeng, Huipeng Huang, Xinhao Qu, Jianguo Huang, Bingyi Jing, and Hongxin Wei. Hy-PAC: Cost-Efficient LLMs-Human Hybrid Annotation with PAC Error Guarantees. arXiv preprint arXiv:2602.02550, 2026.

[71] Jiamu Zhang, Tianze Yang, Yucheng Shi, Evan Chen, Zixiang Nie, Kelly Wan, Liangjie Hong, Ninghao Liu, and Liang Wu. AnyJev Technical Report. arXiv preprint arXiv:2610.00831, 2026.

[72] Zhilong Zhao and Yindi Liu. A Confidence-Diversity Framework for Calibrating AI Judgement in Accessible Qualitative Coding Tasks. arXiv preprint arXiv:2508.02029, 2025.

[73] Caleb Ziems, William Held, Omar Shaikh, Jiaao Chen, Zhehao Zhang, and Diyi Yang. Can Large Language Models Transform Computational Social Science? *Computational Linguistics*, 2024. doi: 10.1162/coli_a_00502.

A Analysis plan, amendments and deviations

The analysis plan (v1.0) fixed the tasks, splits, decision units, metrics, primary rule and contrasts before any test-split outcome was computed. Four amendments were each recorded before the data they govern. The plan was kept in the project repository rather than registered externally:

- **v1.1** added OpenAI Decisions as a confirmatory coder, Qwen3.5-9B as a non-reasoning token-probability comparator, and the A3 analyses (recalibration, per-code thresholds, risk control, cascades).
- **v1.2** added Clef, Clef-flash, pplx-decider, Kev-9B and Kev-27B as a confirmatory family, with the same-base contrasts pre-specified as secondary.
- **v1.3** added the memorization probe.
- **v1.4** added the prompt-sensitivity check.

The deviations log records eighteen entries; everything added or changed after results were seen is exploratory. In summary:

1. A response-cache key ignored option order. It was fixed and the affected order arms were re-run before analysis.
2. Adjudication moved from a single human pass to a blinded two-family LLM panel plus the author on disputed items.
3. The author completed 48 of 72 assigned adjudications.
4. The RQ5 code-type labels were assigned by the assistant from definition text, after some per-code results had been seen.
5. OpenAI Decisions collection notes, including its exact invariance to question order on multi-label tasks.
6. The Qwen model was chosen by availability without third-party data sharing; Qwen3.8-2.4T was added on a subset; a null-logprob parse fix was made before any full-run data.
7. The A3 implementation details were fixed after the primary results had been seen.
8. A3 was revised after its first output: a power-based LTT start, oracle thresholds and a restructured per-code head-to-head. All A3 results are therefore exploratory.
9. Sonnet was extended from a nested subset to the full sample after the subset results had been seen.
10. The repeatability check, Sonnet's robustness arms and the Holm sensitivity analysis were added.
11. Kev-27B was limited to the main and format arms.
12. Kev-9B's robustness arms cover one to four tasks per arm: the hosting workspace was disabled partway through.
13. The decision-model committee and new cascades were added, exploratory, and fixed before computation.
14. A decoy-name control was added for flagged memorization cells.
15. The author later reviewed those labels and approved them unchanged, after the RQ5 results had been computed.
16. After an external review of the first draft: a cluster-level guarantee replaced LTT on decisions, with joint certification for cascades and split samples for learned scores; the prevalence analysis, the category-only control, adjudication by verdict source, the feasibility calculation and a text-free spend ledger were added; RQ3 point estimates were design-weighted; three reporting errors were fixed.
17. After a second review: the guarantee was recast for a fixed corpus (corpus LTT), with the earlier test kept as LTT on i.i.d. clusters; related tasks share bootstrap draws; the Sonnet subset contrast is the confirmatory one; the probability floor moved to 10^{-12}, and Platt maps became the recalibration yardstick.
18. After a third review: the betting tests average over random visiting orders; the budget curves, bootstrap streams and prompt-sensitivity intervals were corrected; the feasibility bound and the single-utterance design were added; prose intervals are generated from the results files.

The full log, plan and amendments are in the released repository.

B Guaranteed threshold rules

LTT on decisions. Thresholds are tested from the most confident tie block downwards with binomial tests of "risk $> \varepsilon$" at level $\delta = 0.05$, stopping at the first failure; the sequence starts at the first block with at least 124 decisions. Errors are scaled to Kish's effective sample size [28], which gives fractional counts. The test treats decisions as independent and fails when they are not (Table 30).

Corpus LTT. A corpus has N clusters; n of them, chosen uniformly at random, are hand-coded. Fix the scores, the grid $\{0.5, 0.55, \ldots, 0.9, 0.925, 0.95, 0.97, 0.98, 0.99, 0.995, 1.0\}$ and B, the largest total weight of one cluster in the corpus. For threshold t, every cluster has a fixed value $Y_i = (Z_i + \varepsilon B)/B \in [0,1]$ with $Z_i = \sum_j w_{ij}\mathbf{1}\{c_{ij} \geq t\}(e_{ij} - \varepsilon)$; let μ be their corpus mean and $\bar{Y}$ the mean over the hand-coded clusters. The uncoded remainder has error at most ε among its accepted decisions exactly when its Z-sum is at most 0, that is, when $\mu \leq m^* = ((N-n)\varepsilon + n\bar{Y})/N$.

To test "$\mu \geq m$", visit the hand-coded clusters in a uniformly random order, drawn independently of the labels; the clusters visited are then a uniformly random sample drawn without replacement, in draw order. Under that null, the kth cluster's value has conditional mean $(N\mu - S_{k-1})/(N-k+1) \geq \mu_k(m) = (Nm - S_{k-1})/(N-k+1)$, where S_{k-1} is the sum of the values already seen. So $K_k = \prod_{i \leq k}\big(1 - \nu_i\,(Y_i - \mathrm{clip}(\mu_i(m), 0, 1))\big)$, with predictable bets $\nu_i = \min\{1, \sqrt{2\log(1/\delta')/(n\hat{\sigma}^2_{i-1})}\} \in [0,1]$, is a non-negative supermartingale [62]. The variance estimate is the plug-in rule with a pseudo-observation: $\hat{\sigma}^2_0 = 1/4$ and, for $i \geq 1$, $\hat{\mu}_i = (1/2 + \sum_{j \leq i} Y_j)/(i+1)$ and $\hat{\sigma}^2_i = (1/4 + \sum_{j \leq i}(Y_j - \hat{\mu}_j)^2)/(i+1)$. The bets use only values already seen and do not depend on m; validity needs only that, but power, and hence the feasibility numbers below, depends on this choice. Its final value K_n has expectation at most 1: it is an e-value. The order must be random: a random set visited in a fixed order does not have these conditional means. Rather than rely on one random order, we draw $R = 100$ independent orders and average their final values, $\bar{K}(m) = R^{-1}\sum_r K_n^{(r)}$. An average of e-values is an e-value [59], so $p(m) = \min(1, 1/\bar{K}(m))$ satisfies $P(p(m) \leq \delta') \leq \delta'$ under the null by Markov's inequality. Each $K_n^{(r)}$ increases with m, so $\bar{K}$ does too, and rejecting at m^* implies rejecting at every larger m. If the remainder's error exceeds ε, then $\mu > m^*$, so certifying t requires rejecting at $m = \mu$, a true null, which happens with probability at most δ'. Testing each of the 16 thresholds at $\delta' = \delta/16$ gives the proposition in Section 3.4. The only randomness used is the choice of clusters to hand-code and the visiting orders; dependence among errors is unrestricted. The orders come from a pseudo-random generator with a recorded seed, fixed before this analysis and not chosen by any outcome.

LTT on i.i.d. clusters. For the population target, the same Y_i are tested against the constant null mean ε with the same betting process and the same averaging over orders. This is valid if clusters are independent draws whose weights never exceed B; exchangeability alone is not enough, because a shared latent cause can make every cluster right or every cluster wrong together. For MFRC, B is a genuine bound (eight codes per comment at one weight); for transcripts of unbounded length it is not.

Learned scores and pipelines. Per-code maps and the prevalence baseline are fitted on half of the calibration clusters and frozen; corpus LTT runs on the other half, with the corpus taken as that half plus the test split, and the frozen scores are applied to the test split. A two-stage cascade is one hypothesis per combination of stage thresholds (8 per stage, plus "off" for the second), with Bonferroni over all 72 combinations; the certified combination with the largest calibration coverage is used.

What the procedure needs. For a coder that accepts everything and is never wrong, $Y_i = \varepsilon(1 - r_i)$ with r_i the unit's weight relative to B, and the conditional null mean at m^* is at most ε. Since bets are capped at 1, each unit can multiply the capital by at most $1 + \varepsilon r_i$, whatever the order, and certification with the grid needs the capital to reach $16/0.05 = 320$. Hence $\sum_{\text{coded}} \log(1 + \varepsilon r_i) \geq \log 320$ is necessary for any set of hand-coded units and any visiting order (Table 31, "lower bound"). For MFRC, whose comments all have the same weight, at least 119 comments are needed; our procedure first certifies after a median of 123. With whole transcripts as units, where a typical transcript carries 8–27% of the largest one's weight, the bound rules out certification on AnnoMI (both tasks) and TalkMoves student even if every transcript but one were hand-coded, and on TalkMoves teacher it needs at least 388 of 444 lessons. These requirements belong to this procedure (capped bets, scaling by the largest unit, Bonferroni over the grid) under whole-transcript sampling. Because corpus LTT needs only random selection, not independence, the unit can be smaller: drawing single utterances or sentences at random, with their context, keeps every unit's weight close to B, and a perfect coder is then certified after a median of 139–163 hand-coded segments (Table 31). Table 32 applies that design to the real coders.

C Additional results




Figure 9: EQ1: reliability on the test split before (coloured) and after (dashed grey) a Platt map fitted per task on the calibration split, for four decision models, Sonnet's verbalized confidence and Luna's token probabilities. Tasks are weighted equally; bins with fewer than 20 decisions are omitted.




Figure 10: EQ2: calibration budget on MFRC. Left: mean share of test decisions accepted; right: share of draws whose held-out error exceeds 5%, when only n randomly drawn comments are hand-coded (250 draws; 608 is the full calibration split). Solid: naive rule; dashed: corpus LTT. Corpus LTT certifies nothing for any plotted coder with 200 or fewer comments, and 2% (Jev) to 75% (pplx-decider) with 400. For each draw the corpus is the drawn comments plus the test split, whose decisions are the ones scored. The dialogue tasks are omitted: with whole transcripts hand-coded, corpus LTT certifies nothing there.




Figure 11: EQ3: error AUROC with raw confidence (hollow) and with per-code Platt maps fitted on the calibration split (filled), pooled over tasks, with cluster-bootstrap 95% CIs for the gain, conditional on the fitted maps. Qwen3.8-2.4T ran on a subset whose calibration split is too small for per-code maps.




Figure 12: EQ6: run-to-run repeatability. Identical requests were sent twice for 100 test segments per task. Left: share of decisions whose label changes. Right: mean absolute change in confidence. 0: identical outputs in these repeats.




Figure 13: EQ6: memorization probe. Change in completion overlap (left, ROUGE-L) and label recall (right, accuracy) when the dataset is named, relative to an unnamed prompt. Asterisks mark cells flagged by the pre-specified rule; Table 27 gives the decoy control.

Table 9: RQ2: model uncertainty and human disagreement, by coder (test items with ≥ 3 annotators)

task	signal	Spearman: uncertainty vs human split	AUROC: flags split items	model κ (mean over references)	annotators below model
MFRC	Jev	0.326	0.718	0.269	2 of 6
MFRC	OpenAI Decisions	0.242	0.659	0.260	2 of 6
MFRC	Luna verbal	0.339	0.721	0.250	2 of 6
MFRC	Haiku verbal	0.375	0.742	0.189	1 of 6
MFRC	gpt-oss verbal	0.307	0.673	0.310	3 of 6
MFRC	Luna logprob	0.138	0.582	0.250	2 of 6
MFRC	3-LLM agreement	0.199	0.591	0.280	2 of 6
MFRC	Sonnet verbal	0.427	0.784	0.361	5 of 6
MFRC	Clef (27B)	0.404	0.771	0.282	2 of 6
MFRC	Clef-flash (9B)	0.395	0.764	0.306	3 of 6
MFRC	pplx-decider	0.398	0.767	0.246	1 of 6
MFRC	Kev-9B	0.325	0.717	0.239	2 of 6
MFRC	Kev-27B	0.394	0.764	0.249	2 of 6
AnnoMI client	Jev	0.547	0.859	0.706	7 of 10
AnnoMI client	OpenAI Decisions	0.517	0.812	0.696	7 of 10
AnnoMI client	Luna verbal	0.514	0.803	0.701	7 of 10
AnnoMI client	Haiku verbal	0.568	0.875	0.590	3 of 10
AnnoMI client	gpt-oss verbal	0.522	0.817	0.655	7 of 10
AnnoMI client	Luna logprob	-0.100	0.462	0.701	7 of 10
AnnoMI client	3-LLM agreement	0.324	0.604	0.648	7 of 10
AnnoMI client	Sonnet verbal	0.647	0.872	0.714	9 of 10
AnnoMI client	Clef (27B)	0.636	0.904	0.508	1 of 10
AnnoMI client	Clef-flash (9B)	0.600	0.912	0.483	1 of 10
AnnoMI client	pplx-decider	0.652	0.864	0.738	8 of 10
AnnoMI client	Kev-9B	0.179	0.627	0.462	1 of 10
AnnoMI client	Kev-27B	0.572	0.872	0.672	7 of 10
AnnoMI therapist	Jev	0.574	0.773	0.891	10 of 10
AnnoMI therapist	OpenAI Decisions	0.438	0.729	0.914	10 of 10
AnnoMI therapist	Luna verbal	0.560	0.797	0.899	10 of 10
AnnoMI therapist	Haiku verbal	0.359	0.670	0.834	6 of 10
AnnoMI therapist	gpt-oss verbal	0.379	0.648	0.880	8 of 10
AnnoMI therapist	Luna logprob	-0.030	0.490	0.899	10 of 10
AnnoMI therapist	3-LLM agreement	0.208	0.570	0.898	10 of 10
AnnoMI therapist	Sonnet verbal	0.511	0.738	0.883	8 of 10
AnnoMI therapist	Clef (27B)	0.327	0.664	0.807	4 of 10
AnnoMI therapist	Clef-flash (9B)	0.346	0.691	0.809	4 of 10
AnnoMI therapist	pplx-decider	0.542	0.771	0.908	10 of 10
AnnoMI therapist	Kev-9B	0.435	0.715	0.721	1 of 10
AnnoMI therapist	Kev-27B	0.505	0.766	0.793	3 of 10

Model κ: against the majority of the other annotators, averaged over the leave-one-annotator-out references. The human range for each task is in Table 10.

Table 10: RQ2: agreement of each annotator with the majority of the other annotators (the human range)

task	items	annotators	human κ min	human κ median	human κ max
MFRC	1382	6	0.110	0.295	0.372
AnnoMI client	91	10	0.414	0.607	0.773
AnnoMI therapist	93	10	0.631	0.834	0.886

Leave-one-annotator-out κ on the same items as Table 9. AnnoMI's multi-annotated items come from four transcripts.

Table 11: RQ3: robustness to perturbations (design-weighted within tasks; equal-weight mean over the tasks each arm covers; vs the canonical arm on identical items)

signal	arm	tasks	flip rate	ΔAURC	$\Delta\kappa$	Δ error AUROC	ΔECE	flips at low confidence (AUROC)
Clef-flash (9B)	one code per call	1	0.040	-0.001	-0.074	-0.003	-0.055	0.935
Clef-flash (9B)	neutral labels	5	0.094	-0.008	0.006	0.004	-0.004	0.881
Clef-flash (9B)	no previous turn	4	0.236	0.026	-0.016	-0.026	0.000	0.768
Clef-flash (9B)	paraphrase A	5	0.060	0.001	-0.005	-0.001	0.005	0.908
Clef-flash (9B)	paraphrase B	5	0.096	0.010	-0.019	-0.001	-0.010	0.877
Clef-flash (9B)	options reversed	5	0.008	-0.000	-0.002	0.003	-0.002	0.918
Clef-flash (9B)	shuffle 1	5	0.004	-0.000	0.000	0.002	-0.002	0.953
Clef-flash (9B)	shuffle 2	5	0.004	-0.000	0.001	0.001	-0.002	0.963
Clef-flash (9B)	shuffle 3	5	0.004	-0.000	-0.001	0.002	-0.002	0.954
Jev	one code per call	1	0.008	-0.000	-0.004	0.000	-0.001	0.988
Jev	neutral labels	5	0.050	-0.003	-0.003	0.007	0.002	0.943
Jev	no previous turn	4	0.151	0.037	-0.038	-0.025	0.021	0.816
Jev	paraphrase A	5	0.032	-0.000	-0.006	0.011	-0.001	0.952
Jev	paraphrase B	5	0.036	0.006	-0.007	-0.003	0.001	0.946
Jev	options reversed	5	0.042	0.006	-0.005	0.000	-0.005	0.951
Jev	shuffle 1	5	0.042	0.001	-0.002	0.003	-0.003	0.949
Jev	shuffle 2	5	0.040	0.000	0.000	0.001	-0.005	0.952
Jev	shuffle 3	5	0.041	0.001	0.000	0.001	-0.000	0.950
Kev-9B	one code per call	1	0.002	-0.000	-0.003	0.000	-0.000	0.997
Kev-9B	neutral labels	3	0.102	0.000	-0.000	0.007	-0.013	0.899
Kev-9B	no previous turn	2	0.175	0.010	-0.012	-0.016	-0.020	0.747
Kev-9B	paraphrase A	3	0.064	0.008	-0.021	0.012	0.006	0.926
Kev-9B	paraphrase B	3	0.076	0.004	-0.020	0.009	0.012	0.920
Kev-9B	options reversed	4	0.306	0.119	-0.099	0.046	0.044	0.813
Kev-9B	shuffle 1	4	0.192	0.066	-0.042	-0.006	-0.026	0.842
Kev-9B	shuffle 2	4	0.204	0.072	-0.053	0.007	-0.034	0.843
Kev-9B	shuffle 3	3	0.129	0.035	-0.023	-0.014	-0.002	0.864
Luna verbal	neutral labels	5	0.081	0.016	-0.006	-0.038	0.006	0.805
Luna verbal	options reversed	5	0.100	-0.011	0.031	-0.022	-0.015	0.783
Luna verbal	shuffle 1	5	0.106	-0.004	0.025	-0.026	-0.012	0.785
OpenAI Decisions	one code per call	1	0.000	0.000	0.000	0.000	0.000	–
OpenAI Decisions	neutral labels	5	0.096	-0.005	-0.004	0.001	0.008	0.889
OpenAI Decisions	no previous turn	4	0.188	0.011	-0.040	-0.002	-0.016	0.794
OpenAI Decisions	paraphrase A	5	0.072	-0.002	0.012	-0.005	0.035	0.899
OpenAI Decisions	paraphrase B	5	0.076	0.001	0.017	-0.024	0.026	0.895
OpenAI Decisions	options reversed	5	0.103	-0.005	0.021	-0.014	0.022	0.873
OpenAI Decisions	shuffle 1	5	0.089	-0.005	0.012	-0.001	0.018	0.875
OpenAI Decisions	shuffle 2	5	0.083	-0.004	0.021	-0.018	0.015	0.861
OpenAI Decisions	shuffle 3	5	0.088	0.000	0.017	-0.019	0.015	0.870
pplx-decider	one code per call	1	0.000	0.000	0.000	0.000	0.000	–
pplx-decider	neutral labels	5	0.071	-0.004	-0.002	0.009	0.012	0.890
pplx-decider	no previous turn	4	0.154	0.023	-0.041	-0.012	0.029	0.801
pplx-decider	paraphrase A	5	0.038	-0.001	0.008	-0.007	-0.002	0.932
pplx-decider	paraphrase B	5	0.037	-0.001	0.006	-0.003	0.000	0.930
pplx-decider	options reversed	5	0.064	-0.019	0.012	0.021	0.010	0.875
pplx-decider	shuffle 1	5	0.064	-0.012	-0.002	0.014	0.009	0.853
pplx-decider	shuffle 2	5	0.062	-0.013	0.006	0.009	0.007	0.852
pplx-decider	shuffle 3	5	0.065	-0.012	0.003	0.013	0.008	0.850
Sonnet verbal	neutral labels	5	0.049	-0.002	-0.016	0.011	0.004	0.915
Sonnet verbal	options reversed	5	0.052	-0.003	-0.033	0.016	0.012	0.882
Sonnet verbal	shuffle 1	5	0.059	0.000	-0.020	0.006	-0.002	0.887

Flip rate and ΔAURC are the pre-specified primary outcomes; Table 12 gives per-task 95% intervals for selected arms. 'No previous turn' removes information rather than rewording the request.

Table 12: RQ3 primary outcomes with per-task 95% intervals (cluster bootstrap) for two arms

arm	signal	task	flip rate [95% CI]	ΔAURC [95% CI]
no previous turn	Clef-flash (9B)	AnnoMI client	0.130 [0.104, 0.161]	+0.031 [+0.011, +0.055]
no previous turn	Clef-flash (9B)	AnnoMI therapist	0.121 [0.090, 0.151]	+0.008 [-0.002, +0.020]
no previous turn	Clef-flash (9B)	TalkMoves student	0.306 [0.279, 0.336]	+0.117 [+0.085, +0.151]
no previous turn	Clef-flash (9B)	TalkMoves teacher	0.385 [0.356, 0.416]	-0.052 [-0.085, -0.013]
no previous turn	Jev	AnnoMI client	0.082 [0.065, 0.102]	+0.033 [+0.015, +0.051]
no previous turn	Jev	AnnoMI therapist	0.088 [0.068, 0.105]	-0.001 [-0.013, +0.013]
no previous turn	Jev	TalkMoves student	0.227 [0.204, 0.253]	+0.081 [+0.059, +0.105]
no previous turn	Jev	TalkMoves teacher	0.208 [0.184, 0.231]	+0.033 [+0.013, +0.051]
no previous turn	Kev-9B	AnnoMI client	0.216 [0.189, 0.246]	+0.005 [-0.027, +0.035]
no previous turn	Kev-9B	AnnoMI therapist	0.135 [0.112, 0.159]	+0.014 [-0.002, +0.031]
no previous turn	OpenAI Decisions	AnnoMI client	0.076 [0.059, 0.096]	+0.023 [+0.003, +0.044]
no previous turn	OpenAI Decisions	AnnoMI therapist	0.106 [0.085, 0.124]	+0.012 [+0.001, +0.024]
no previous turn	OpenAI Decisions	TalkMoves student	0.342 [0.315, 0.371]	+0.011 [-0.023, +0.045]
no previous turn	OpenAI Decisions	TalkMoves teacher	0.230 [0.203, 0.257]	-0.004 [-0.026, +0.019]
no previous turn	pplx-decider	AnnoMI client	0.086 [0.068, 0.110]	+0.032 [+0.010, +0.052]
no previous turn	pplx-decider	AnnoMI therapist	0.058 [0.041, 0.074]	+0.004 [-0.006, +0.014]
no previous turn	pplx-decider	TalkMoves student	0.311 [0.282, 0.345]	+0.061 [+0.037, +0.084]
no previous turn	pplx-decider	TalkMoves teacher	0.163 [0.141, 0.186]	-0.006 [-0.024, +0.013]
options reversed	Clef-flash (9B)	AnnoMI client	0.000 [0.000, 0.000]	+0.000 [+0.000, +0.000]
options reversed	Clef-flash (9B)	AnnoMI therapist	0.000 [0.000, 0.000]	+0.000 [+0.000, +0.000]
options reversed	Clef-flash (9B)	MFRC	0.040 [0.037, 0.043]	-0.001 [-0.002, -0.001]
options reversed	Clef-flash (9B)	TalkMoves student	0.000 [0.000, 0.000]	+0.000 [+0.000, +0.000]
options reversed	Clef-flash (9B)	TalkMoves teacher	0.000 [0.000, 0.000]	+0.000 [+0.000, +0.000]
options reversed	Jev	AnnoMI client	0.035 [0.023, 0.044]	+0.002 [-0.003, +0.008]
options reversed	Jev	AnnoMI therapist	0.021 [0.013, 0.029]	-0.008 [-0.015, -0.001]
options reversed	Jev	MFRC	0.009 [0.007, 0.011]	+0.000 [-0.000, +0.000]
options reversed	Jev	TalkMoves student	0.072 [0.057, 0.087]	+0.034 [+0.024, +0.044]
options reversed	Jev	TalkMoves teacher	0.072 [0.056, 0.088]	+0.001 [-0.007, +0.008]
options reversed	Kev-9B	AnnoMI client	0.444 [0.400, 0.483]	+0.180 [+0.137, +0.232]
options reversed	Kev-9B	AnnoMI therapist	0.224 [0.193, 0.255]	+0.067 [+0.038, +0.097]
options reversed	Kev-9B	MFRC	0.002 [0.001, 0.003]	-0.000 [-0.000, +0.000]
options reversed	Kev-9B	TalkMoves teacher	0.555 [0.522, 0.588]	+0.230 [+0.193, +0.268]
options reversed	OpenAI Decisions	AnnoMI client	0.064 [0.050, 0.079]	+0.014 [-0.011, +0.035]
options reversed	OpenAI Decisions	AnnoMI therapist	0.086 [0.067, 0.105]	+0.020 [+0.004, +0.035]
options reversed	OpenAI Decisions	MFRC	0.000 [0.000, 0.000]	+0.000 [+0.000, +0.000]
options reversed	OpenAI Decisions	TalkMoves student	0.212 [0.188, 0.236]	-0.047 [-0.070, -0.023]
options reversed	OpenAI Decisions	TalkMoves teacher	0.152 [0.129, 0.174]	-0.013 [-0.030, +0.004]
options reversed	Sonnet verbal	AnnoMI client	0.040 [0.005, 0.074]	-0.003 [-0.021, +0.019]
options reversed	Sonnet verbal	AnnoMI therapist	0.051 [0.012, 0.105]	+0.001 [-0.006, +0.014]
options reversed	Sonnet verbal	MFRC	0.050 [0.032, 0.069]	+0.003 [+0.001, +0.007]
options reversed	Sonnet verbal	TalkMoves student	0.038 [0.000, 0.084]	+0.001 [-0.018, +0.023]
options reversed	Sonnet verbal	TalkMoves teacher	0.082 [0.026, 0.145]	-0.017 [-0.050, +0.008]
options reversed	pplx-decider	AnnoMI client	0.027 [0.016, 0.042]	-0.006 [-0.014, +0.001]
options reversed	pplx-decider	AnnoMI therapist	0.039 [0.022, 0.057]	-0.001 [-0.005, +0.002]
options reversed	pplx-decider	MFRC	0.000 [0.000, 0.000]	+0.000 [+0.000, +0.000]
options reversed	pplx-decider	TalkMoves student	0.122 [0.104, 0.142]	-0.016 [-0.035, +0.003]
options reversed	pplx-decider	TalkMoves teacher	0.129 [0.113, 0.148]	-0.073 [-0.094, -0.051]

Positive ΔAURC means a larger area under the risk–coverage curve for the perturbed run (worse selective risk); AURC reflects the error rate as well as the ranking of errors.

Table 13: EQ1 (exploratory): recalibration and the fixed rule 'accept if confidence ≥ 0.95' (pooled)

A. Expected calibration error, raw and after recalibration

signal	ECE raw	ECE Platt	ECE isotonic	ECE temperature
Jev	0.120	0.038	0.040	0.120
OpenAI Decisions	0.122	0.073	0.042	0.098
Clef (27B)	0.055	0.041	0.045	0.054
Clef-flash (9B)	0.065	0.043	0.035	0.051
pplx-decider	0.052	0.043	0.048	0.047
Kev-9B	0.100	0.041	0.053	0.069
Kev-27B	0.073	0.032	0.037	0.029
Luna verbal	0.180	0.047	0.040	0.059
Haiku verbal	0.154	0.045	0.035	0.075
gpt-oss verbal	0.204	0.056	0.038	0.075
Qwen3.5-9B verbal	0.303	0.045	0.037	0.099
Luna logprob	0.243	0.038	0.039	0.106
gpt-oss logprob	0.284	0.040	0.045	0.033
Qwen3.5-9B logprob	0.334	0.052	0.054	0.060
Sonnet verbal	0.051	0.034	0.039	0.053
Qwen3.8-2.4T verbal	0.102	0.060	0.061	0.091

B. Error ranking, and the fixed rule 'accept if confidence ≥ 0.95' applied to raw confidence

signal	error AUROC raw	error AUROC Platt	share accepted by '≥ 0.95'	its error
Jev	0.756	0.756	0.364	0.121
OpenAI Decisions	0.736	0.736	0.498	0.115
Clef (27B)	0.721	0.721	0.081	0.007
Clef-flash (9B)	0.712	0.712	0.043	0.001
pplx-decider	0.764	0.764	0.281	0.041
Kev-9B	0.694	0.694	0.041	0.032
Kev-27B	0.788	0.788	0.155	0.034
Luna verbal	0.741	0.741	0.635	0.139
Haiku verbal	0.783	0.783	0.310	0.044
gpt-oss verbal	0.727	0.727	0.523	0.120
Qwen3.5-9B verbal	0.646	0.646	0.966	0.331
Luna logprob	0.558	0.556	0.994	0.241
gpt-oss logprob	0.558	0.539	0.998	0.285
Qwen3.5-9B logprob	0.684	0.684	0.984	0.334
Sonnet verbal	0.801	0.801	0.225	0.021
Qwen3.8-2.4T verbal	0.802	0.802	0.259	0.020

Maps fitted per task on calib. Platt and isotonic maps act on the decision's confidence; temperature scaling acts on the full distribution and is sensitive to how exact 0s and 1s are floored (Table 35; here 1e-12). Errors are among accepted test decisions.

Table 14: EQ2 (exploratory): threshold rules at a 5% target (percent)

A. Frozen split, pooled over tasks

signal	naive: accepted	naive: error	corpus LTT: accepted	corpus LTT: error	oracle: accepted
Jev	32.9	6.8	12.0	1.6	16.3
OpenAI Decisions	22.7	4.7	0.0	–	17.8
Clef (27B)	24.0	5.8	16.5	3.0	20.3
Clef-flash (9B)	25.4	7.0	15.6	2.7	20.7
pplx-decider	40.8	7.5	15.4	2.3	32.1
Kev-9B	23.9	6.3	13.4	2.4	19.2
Kev-27B	44.2	7.0	15.3	2.1	37.2
Luna verbal	20.2	4.6	12.8	2.2	16.2
Haiku verbal	16.1	3.2	13.2	1.7	16.8
gpt-oss verbal	22.1	5.6	0.0	–	20.6
Qwen3.5-9B verbal	3.4	11.4	0.0	–	0.0
Luna logprob	0.0	–	0.0	–	11.8
gpt-oss logprob	1.2	29.7	0.0	–	0.0
Qwen3.5-9B logprob	9.3	7.9	0.0	–	8.2
Sonnet verbal	43.4	6.2	16.5	2.5	40.1
Qwen3.8-2.4T verbal	37.9	4.3	0.0	–	38.0

B. MFRC: share of re-splits with held-out error above 5%, and corpus LTT with per-code maps

signal	naive	LTT on decisions	LTT on i.i.d. clusters	corpus LTT	per-code maps, corpus LTT: accepted
Jev	49.4	6.8	0.0	0.0	0.0
OpenAI Decisions	28.0	5.8	0.0	0.0	0.0
Clef (27B)	47.0	8.4	0.0	0.0	75.4
Clef-flash (9B)	51.8	8.4	0.0	0.0	65.5
pplx-decider	50.0	11.2	0.0	0.0	72.0
Kev-9B	52.4	9.0	0.0	0.0	0.0
Kev-27B	47.0	9.2	0.0	0.0	0.0
Luna verbal	5.2	0.0	0.0	0.0	0.0
Haiku verbal	19.4	6.0	0.0	0.0	0.0
gpt-oss verbal	0.0	0.0	0.0	0.0	0.0
Qwen3.5-9B verbal	0.0	0.0	0.0	0.0	0.0
Luna logprob	0.0	0.0	0.0	0.0	0.0
gpt-oss logprob	15.2	0.0	0.0	0.0	0.0
Qwen3.5-9B logprob	47.2	5.2	0.0	0.0	0.0
Sonnet verbal	6.0	0.0	0.0	0.0	68.9
Qwen3.8-2.4T verbal	5.2	0.6	0.0	0.0	0.0

Panel A: frozen split, equal-weight means over the five tasks; oracle: fitted on test. Panel B: 500 random cluster re-splits of MFRC; for corpus LTT each test split is the uncoded remainder of its re-split, so exceedance there is a direct check of its guarantee. Per-code maps are fitted on half of the calib clusters, frozen, certified on the other half and applied unchanged to test.

Table 15: Naive rule and LTT on decisions by task over 500 cluster re-splits (percent)

signal	task	naive: accepted	naive: none accepted	naive: error > 5%	LTT on decisions: accepted	LTT on decisions: none accepted	LTT on decisions: error > 5%
Clef (27B)	AnnoMI client	7.3	5.0	73.8	0.0	100.0	0.0
Clef (27B)	AnnoMI therapist	18.8	0.0	63.6	0.2	99.4	0.6
Clef (27B)	MFRC	90.2	0.0	47.0	88.3	0.0	8.4
Clef (27B)	TalkMoves student	1.4	0.2	65.4	0.0	100.0	0.0
Clef (27B)	TalkMoves teacher	0.6	0.8	67.8	0.0	100.0	0.0
Clef-flash (9B)	AnnoMI client	11.5	1.2	84.8	0.0	100.0	0.0
Clef-flash (9B)	AnnoMI therapist	10.8	8.2	56.4	0.0	100.0	0.0
Clef-flash (9B)	MFRC	89.8	0.0	51.8	87.1	0.0	8.4
Clef-flash (9B)	TalkMoves student	2.4	0.0	33.2	0.0	100.0	0.0
Clef-flash (9B)	TalkMoves teacher	0.4	6.6	53.2	0.0	100.0	0.0
Jev	AnnoMI client	3.1	91.0	9.0	0.0	100.0	0.0
Jev	AnnoMI therapist	18.0	62.8	37.2	0.1	99.8	0.2
Jev	MFRC	80.8	0.0	49.4	78.3	0.0	6.8
Jev	TalkMoves student	1.7	85.0	15.0	0.0	100.0	0.0
Jev	TalkMoves teacher	2.5	81.0	19.0	0.0	100.0	0.0
Kev-27B	AnnoMI client	15.6	0.2	70.2	0.0	100.0	0.0
Kev-27B	AnnoMI therapist	51.9	0.0	41.8	12.4	68.0	2.0
Kev-27B	MFRC	94.0	0.0	47.0	91.7	0.0	9.2
Kev-27B	TalkMoves student	20.3	0.0	62.8	0.0	100.0	0.0
Kev-27B	TalkMoves teacher	21.9	0.6	72.2	0.0	100.0	0.0
Kev-9B	AnnoMI client	2.8	0.4	68.8	0.0	100.0	0.0
Kev-9B	AnnoMI therapist	14.2	0.0	79.8	0.1	99.6	0.4
Kev-9B	MFRC	87.8	0.0	52.4	56.8	16.0	9.0
Kev-9B	TalkMoves student	0.2	67.0	33.0	0.0	100.0	0.0
Kev-9B	TalkMoves teacher	0.4	5.6	41.6	0.0	100.0	0.0
OpenAI Decisions	AnnoMI client	1.8	91.8	8.2	0.0	100.0	0.0
OpenAI Decisions	AnnoMI therapist	32.1	18.8	51.2	1.4	96.8	3.2
OpenAI Decisions	MFRC	74.3	0.0	28.0	69.6	0.0	5.8
OpenAI Decisions	TalkMoves student	0.9	30.6	69.4	0.0	100.0	0.0
OpenAI Decisions	TalkMoves teacher	0.1	99.6	0.4	0.0	100.0	0.0
pplx-decider	AnnoMI client	17.3	0.0	65.0	0.0	100.0	0.0
pplx-decider	AnnoMI therapist	58.8	0.0	53.4	9.1	80.0	2.6
pplx-decider	MFRC	91.5	0.0	50.0	89.2	0.0	11.2
pplx-decider	TalkMoves student	13.1	0.0	52.0	0.0	100.0	0.0
pplx-decider	TalkMoves teacher	3.4	44.0	56.0	0.0	100.0	0.0
Sonnet verbal	AnnoMI client	12.7	0.2	49.2	0.2	99.2	0.8
Sonnet verbal	AnnoMI therapist	56.0	0.0	38.6	7.7	83.8	3.0
Sonnet verbal	MFRC	89.8	0.0	6.0	88.9	0.0	0.0
Sonnet verbal	TalkMoves student	11.6	10.6	62.0	0.0	100.0	0.0
Sonnet verbal	TalkMoves teacher	39.0	0.0	39.2	1.8	95.4	4.2

Accepted: mean share of test decisions accepted; none accepted: share of re-splits accepting nothing; error > 5%: share of re-splits whose held-out error exceeds 5%. A re-split that accepts nothing cannot exceed 5%; read exceedance with acceptance.

Table 16: LTT on i.i.d. clusters and corpus LTT by task over 500 cluster re-splits (percent)

signal	task	i.i.d.-cluster LTT: accepted	i.i.d.-cluster LTT: none accepted	i.i.d.-cluster LTT: error > 5%	corpus LTT: accepted	corpus LTT: none accepted	corpus LTT: error > 5%
Clef (27B)	AnnoMI client	0.0	100.0	0.0	0.0	100.0	0.0
Clef (27B)	AnnoMI therapist	0.0	100.0	0.0	0.0	100.0	0.0
Clef (27B)	MFRC	82.3	0.0	0.0	81.0	0.0	0.0
Clef (27B)	TalkMoves student	0.0	100.0	0.0	0.0	100.0	0.0
Clef (27B)	TalkMoves teacher	0.0	100.0	0.0	0.0	100.0	0.0
Clef-flash (9B)	AnnoMI client	0.0	100.0	0.0	0.0	100.0	0.0
Clef-flash (9B)	AnnoMI therapist	0.0	100.0	0.0	0.0	100.0	0.0
Clef-flash (9B)	MFRC	79.2	0.0	0.0	77.5	0.0	0.0
Clef-flash (9B)	TalkMoves student	0.0	100.0	0.0	0.0	100.0	0.0
Clef-flash (9B)	TalkMoves teacher	0.0	100.0	0.0	0.0	100.0	0.0
Jev	AnnoMI client	0.0	100.0	0.0	0.0	100.0	0.0
Jev	AnnoMI therapist	0.0	100.0	0.0	0.0	100.0	0.0
Jev	MFRC	69.7	0.0	0.0	67.5	0.0	0.0
Jev	TalkMoves student	0.0	100.0	0.0	0.0	100.0	0.0
Jev	TalkMoves teacher	0.0	100.0	0.0	0.0	100.0	0.0
Kev-27B	AnnoMI client	0.0	100.0	0.0	0.0	100.0	0.0
Kev-27B	AnnoMI therapist	0.0	100.0	0.0	0.0	100.0	0.0
Kev-27B	MFRC	84.8	0.0	0.0	82.4	0.0	0.0
Kev-27B	TalkMoves student	0.0	100.0	0.0	0.0	100.0	0.0
Kev-27B	TalkMoves teacher	0.0	100.0	0.0	0.0	100.0	0.0
Kev-9B	AnnoMI client	0.0	100.0	0.0	0.0	100.0	0.0
Kev-9B	AnnoMI therapist	0.0	100.0	0.0	0.0	100.0	0.0
Kev-9B	MFRC	75.9	0.0	0.0	72.3	0.6	0.0
Kev-9B	TalkMoves student	0.0	100.0	0.0	0.0	100.0	0.0
Kev-9B	TalkMoves teacher	0.0	100.0	0.0	0.0	100.0	0.0
OpenAI Decisions	AnnoMI client	0.0	100.0	0.0	0.0	100.0	0.0
OpenAI Decisions	AnnoMI therapist	0.0	100.0	0.0	0.0	100.0	0.0
OpenAI Decisions	MFRC	14.8	67.0	0.0	0.4	99.0	0.0
OpenAI Decisions	TalkMoves student	0.0	100.0	0.0	0.0	100.0	0.0
OpenAI Decisions	TalkMoves teacher	0.0	100.0	0.0	0.0	100.0	0.0
pplx-decider	AnnoMI client	0.0	100.0	0.0	0.0	100.0	0.0
pplx-decider	AnnoMI therapist	0.0	100.0	0.0	0.0	100.0	0.0
pplx-decider	MFRC	82.7	0.0	0.0	81.1	0.0	0.0
pplx-decider	TalkMoves student	0.0	100.0	0.0	0.0	100.0	0.0
pplx-decider	TalkMoves teacher	0.0	100.0	0.0	0.0	100.0	0.0
Sonnet verbal	AnnoMI client	0.0	100.0	0.0	0.0	100.0	0.0
Sonnet verbal	AnnoMI therapist	0.0	100.0	0.0	0.0	100.0	0.0
Sonnet verbal	MFRC	85.4	0.0	0.0	84.5	0.0	0.0
Sonnet verbal	TalkMoves student	0.0	100.0	0.0	0.0	100.0	0.0
Sonnet verbal	TalkMoves teacher	0.0	100.0	0.0	0.0	100.0	0.0

Accepted: mean share of test decisions accepted; none accepted: share of re-splits accepting nothing; error > 5%: share of re-splits whose held-out error exceeds 5%. A re-split that accepts nothing cannot exceed 5%; read exceedance with acceptance.

Table 17: A3 (exploratory): configurations under the naive and oracle rules, pooled over the five tasks

configuration	naive: accepted	naive: error	naive: USD/1k	oracle: accepted	oracle: USD/1k
Jev → human	32.9	6.8	0.021	16.3	0.008
OpenAI Decisions → human	22.7	4.7	0.046	17.8	0.065
Clef (27B) → human	24.0	5.8	0.213	20.3	0.213
Clef-flash (9B) → human	25.4	7.0	0.080	20.7	0.080
pplx-decider → human	40.8	7.6	0.013	32.1	0.013
Kev-9B → human	23.9	6.3	0.073	19.2	0.058
Kev-27B → human	44.2	7.0	0.315	37.2	0.315
Decision-model committee (7) → human	37.5	7.2	0.849	30.9	0.849
pplx-decider + Kev-27B agree → human	42.7	6.8	0.334	40.5	0.334
Jev + Kev-27B agree → human	42.9	7.0	0.362	36.2	0.362
Kev-27B → Sonnet verbal → human	49.6	6.9	1.406	42.8	1.328
Luna verbal → human	20.2	4.6	0.082	16.2	0.066
Haiku verbal → human	16.1	3.2	1.137	16.8	1.906
Sonnet verbal → human	43.4	6.2	1.700	40.1	1.964
Jev → Haiku verbal → human	33.4	6.7	0.579	17.9	1.741
Haiku verbal → Jev → human	31.6	6.4	1.155	16.9	1.913
Jev + Haiku verbal agree → human	26.0	5.5	1.158	28.4	1.954
Jev + Luna verbal agree → human	34.3	6.6	0.130	17.8	0.131
Jev → Sonnet verbal → human	40.4	6.2	1.327	39.2	1.746
Jev + Sonnet verbal agree → human	43.1	6.5	1.736	39.1	2.011
Haiku verbal + Sonnet verbal agree → human	41.5	6.0	3.870	38.2	3.870

Accepted: percent of decisions auto-accepted; error: percent wrong among accepted decisions (tasks weighted equally); USD/1k: API cost per 1,000 segments under that policy. 'A + B agree' accepts where both give the same label (confidence = the lower).

Table 18: A3 (exploratory): configurations certified by corpus LTT on MFRC (percent; the only task where anything is certified when whole clusters are hand-coded)

configuration	certified: accepted	error	USD per 1k comments	remainder comments still read	all comments still read	overall error vs adjudicated
Jev → human	59.8	1.6	0.042	93.2	95.2	1.1
OpenAI Decisions → human	0.0	–	0.000	100.0	100.0	0.2
Clef (27B) → human	82.3	3.1	0.245	73.3	81.4	2.6
Clef-flash (9B) → human	77.9	2.7	0.092	76.2	83.4	2.2
pplx-decider → human	77.1	2.3	0.029	73.2	81.3	1.9
Kev-9B → human	67.1	2.4	0.073	99.9	99.9	1.8
Kev-27B → human	76.6	2.1	0.315	84.6	89.3	1.7
Decision-model committee (7) → human	84.5	2.9	0.970	68.2	77.8	2.5
pplx-decider + Kev-27B agree → human	81.1	2.6	0.344	74.9	82.5	2.2
Jev + Kev-27B agree → human	75.7	2.2	0.357	78.1	84.7	1.8
Kev-27B → Sonnet verbal → human	82.3	2.5	4.141	74.0	81.9	2.1
Luna verbal → human	64.0	2.2	0.218	93.0	95.1	1.5
Haiku verbal → human	65.8	1.7	3.473	83.5	88.5	1.2
Sonnet verbal → human	82.7	2.5	4.521	65.7	76.1	2.2
Jev → Haiku verbal → human	66.5	1.7	3.513	83.1	88.2	1.3
Haiku verbal → Jev → human	66.5	1.8	3.509	83.1	88.2	1.3
Jev + Haiku verbal agree → human	63.3	1.8	3.516	90.2	93.2	1.3
Jev + Luna verbal agree → human	67.9	2.2	0.260	88.4	91.9	1.6
Jev → Sonnet verbal → human	77.0	1.9	4.479	78.4	85.0	1.5
Jev + Sonnet verbal agree → human	73.5	2.1	4.563	82.5	87.8	1.6
Haiku verbal + Sonnet verbal agree → human	74.2	2.3	7.995	75.3	82.8	1.8

Multi-stage configurations are certified jointly over the pipeline. Accepted, error and remainder comments still read refer to the uncoded remainder (the test split); a comment is still read if at least one of its decisions is left for a person. All comments still read adds the 608 hand-coded calibration comments to the numerator and denominator. Overall error vs adjudicated: certified decisions scored against the adjudicated reference, the rest taken as human-coded; human-only coding of MFRC has 0.2% error against that reference.

Table 19: A3 (exploratory): paired configuration contrasts, accepted share a – b in percentage points [95% CI]

A. Naive rule and oracle, pooled over the five tasks

a	b	naive	oracle
Jev → Luna verbal	Luna verbal	+13.0 [-0.7, +18.4]	+0.4 [-0.9, +10.8]
Jev → Haiku verbal	Haiku verbal	+17.3 [+0.9, +19.1]	+1.1 [-0.9, +9.6]
Jev → Haiku verbal	Jev	+0.5 [+0.0, +10.2]	+1.6 [+0.6, +17.2]
Jev → Haiku verbal	OpenAI Decisions → Haiku verbal	+9.2 [-5.3, +15.5]	-1.9 [-9.1, +5.7]
Jev	OpenAI Decisions	+10.3 [-5.0, +18.7]	-1.5 [-9.2, +4.9]
Jev + Haiku verbal agree	Jev → Haiku verbal	-7.4 [-11.3, +9.6]	+10.5 [-6.1, +10.3]
Jev + Haiku verbal agree	Jev	-6.9 [-10.0, +12.7]	+12.1 [-0.2, +14.7]
Jev + Haiku verbal agree	Haiku verbal	+10.0 [-1.6, +18.6]	+11.7 [-4.3, +12.0]
Jev + Luna verbal agree	Jev	+1.3 [-3.4, +13.4]	+1.5 [-2.0, +11.7]
Jev → Sonnet verbal	Sonnet verbal	-3.0 [-4.5, +2.3]	-0.9 [-2.7, +0.6]
Jev	Sonnet verbal	-10.5 [-28.3, -5.4]	-23.8 [-28.0, -12.1]
Jev + Haiku verbal agree	Sonnet verbal	-17.3 [-25.3, -5.7]	-11.7 [-19.7, -6.1]
Jev + Sonnet verbal agree	Sonnet verbal	-0.2 [-8.9, +3.1]	-1.0 [-4.6, +3.3]
Kev-27B	Jev	+11.3 [+6.3, +27.2]	+20.9 [+11.1, +27.6]
Decision-model committee (7)	Jev	+4.6 [+1.6, +21.1]	+14.6 [+5.2, +20.2]
Decision-model committee (7)	Sonnet verbal	-5.9 [-13.9, +1.6]	-9.2 [-12.8, -0.5]
pplx-decider + Kev-27B agree	Sonnet verbal	-0.7 [-9.5, +7.1]	+0.4 [-6.9, +8.7]

B. Corpus LTT on MFRC

a	b	corpus LTT	USD per 1k, a – b
Jev → Luna verbal	Luna verbal	-4.8 [-64.6, +0.2]	0.04
Jev → Haiku verbal	Haiku verbal	+0.7 [-4.1, +8.1]	0.04
Jev → Haiku verbal	Jev	+6.7 [-3.1, +25.2]	3.47
Jev → Haiku verbal	OpenAI Decisions → Haiku verbal	+4.3 [-4.0, +62.7]	-0.13
Jev	OpenAI Decisions	+59.8 [+42.9, +70.1]	0.04
Jev + Haiku verbal agree	Jev → Haiku verbal	-3.2 [-6.9, +1.7]	0.00
Jev + Haiku verbal agree	Jev	+3.5 [-6.6, +20.1]	3.47
Jev + Haiku verbal agree	Haiku verbal	-2.5 [-3.4, +3.4]	0.04
Jev + Luna verbal agree	Jev	+8.1 [-1.8, +23.3]	0.22
Jev → Sonnet verbal	Sonnet verbal	-5.7 [-9.3, +0.6]	-0.04
Jev	Sonnet verbal	-22.9 [-42.3, -13.1]	-4.48
Jev + Haiku verbal agree	Sonnet verbal	-19.4 [-23.5, -12.5]	-1.01
Jev + Sonnet verbal agree	Sonnet verbal	-9.2 [-16.1, -7.5]	0.04
Kev-27B	Jev	+16.7 [+7.1, +38.2]	0.27
Decision-model committee (7)	Jev	+24.6 [+14.2, +40.9]	0.93
Decision-model committee (7)	Sonnet verbal	+1.8 [-8.3, +2.8]	-3.55
pplx-decider + Kev-27B agree	Sonnet verbal	-1.6 [-10.0, +3.8]	-4.18

1,000 clustered bootstrap replicates with thresholds refitted; related tasks share cluster draws. Naive and oracle: equal-weight means over the five tasks. Corpus LTT: MFRC only, the one task where it certifies anything when whole clusters are hand-coded. Every configuration ends with a person coding what it does not accept; 'A + B agree' accepts where both give the same label.

Table 20: A3 (exploratory): per-code recalibration of confidence (error AUROC on test, pooled)

comparison	AUROC a	AUROC b	a – b	95% CI low	95% CI high
Jev: per-code calibrated - raw	0.797	0.756	0.040	0.027	0.054
OpenAI Decisions: per-code calibrated - raw	0.771	0.736	0.034	0.016	0.049
Clef (27B): per-code calibrated - raw	0.829	0.721	0.108	0.097	0.120
Clef-flash (9B): per-code calibrated - raw	0.801	0.712	0.090	0.077	0.102
pplx-decider: per-code calibrated - raw	0.813	0.764	0.048	0.039	0.056
Kev-9B: per-code calibrated - raw	0.809	0.694	0.115	0.094	0.136
Kev-27B: per-code calibrated - raw	0.814	0.788	0.026	0.020	0.034
Luna verbal: per-code calibrated - raw	0.783	0.741	0.042	0.029	0.055
Haiku verbal: per-code calibrated - raw	0.812	0.783	0.029	0.021	0.037
gpt-oss verbal: per-code calibrated - raw	0.787	0.727	0.060	0.049	0.071
Qwen3.5-9B verbal: per-code calibrated - raw	0.764	0.646	0.118	0.101	0.135
Sonnet verbal: per-code calibrated - raw	0.826	0.801	0.025	0.019	0.032
Qwen3.8-2.4T verbal: per-code calibrated - raw	0.798	0.802	-0.005	-0.012	0.004
Jev per-code (full calib) - Sonnet verbal raw	0.797	0.801	-0.004	-0.018	0.008
Jev raw - Sonnet verbal raw	0.756	0.801	-0.045	-0.060	-0.032
Jev per-code - Sonnet verbal per-code (own calib)	0.797	0.826	-0.030	-0.041	-0.019
Jev per-code (full calib) - Qwen3.8-2.4T verbal raw	0.790	0.802	-0.013	-0.048	0.019
Jev raw - Qwen3.8-2.4T verbal raw	0.769	0.802	-0.033	-0.069	-0.001
Jev per-code - Qwen3.8-2.4T verbal per-code (own calib)	0.790	0.798	-0.008	-0.043	0.024

Per-code Platt maps fitted on calib (codes with ≥ 50 calib decisions; others use the task map). CIs resample test clusters with the fitted maps held fixed, so they are conditional on those maps.

Table 21: Run-to-run repeatability (identical requests sent twice; 100 test segments per task; mean over tasks)

A. How much the outputs change

signal	segments	decisions	label flip rate	share identical	mean $\lvert\Delta p\rvert$	mean $\lvert\Delta$ confidence$\rvert$
Jev	100	240	0.021	0.612	0.008	0.013
OpenAI Decisions	100	240	0.000	1.000	0.000	0.000
Luna verbal	100	240	0.066	0.567	0.030	0.020
Luna logprob	100	240	0.066	0.455	0.031	0.003
Haiku verbal	100	240	0.000	0.989	0.001	0.001
Sonnet verbal	100	240	0.033	0.514	0.016	0.023
Clef (27B)	100	240	0.000	1.000	0.000	0.000
Clef-flash (9B)	100	240	0.000	1.000	0.000	0.000
pplx-decider	100	240	0.000	1.000	0.000	0.000

B. Accuracy in each run, and where the changes fall

signal	accuracy, run 1	accuracy, run 2	flips at low confidence (AUROC)
Jev	0.743	0.741	0.967
OpenAI Decisions	0.723	0.723	–
Luna verbal	0.742	0.742	0.874
Luna logprob	0.742	0.742	0.647
Haiku verbal	0.702	0.703	0.895
Sonnet verbal	0.764	0.765	0.921
Clef (27B)	0.693	0.693	–
Clef-flash (9B)	0.685	0.685	–
pplx-decider	0.759	0.759	–

Flips at low confidence: AUROC of low confidence for the decisions whose label changed (– : no changes).

Table 22: Who was right when a coder disagreed with the human label (adjudicated sample)

coder	verdicts	n	coder right, human wrong	human right, coder wrong	both defensible (codebook under-specified)	neither right
Jev	all	117	0.598	0.325	0.068	0.009
Jev	LLM panel	90	0.622	0.289	0.089	0.000
Jev	author	27	0.519	0.444	0.000	0.037
Luna verbal	all	118	0.644	0.288	0.059	0.008
Luna verbal	LLM panel	84	0.667	0.250	0.083	0.000
Luna verbal	author	34	0.588	0.382	0.000	0.029
Haiku verbal	all	118	0.585	0.314	0.085	0.017
Haiku verbal	LLM panel	89	0.573	0.292	0.112	0.022
Haiku verbal	author	29	0.621	0.379	0.000	0.000
gpt-oss verbal	all	141	0.553	0.390	0.043	0.014
gpt-oss verbal	LLM panel	108	0.556	0.380	0.056	0.009
gpt-oss verbal	author	33	0.545	0.424	0.000	0.030

Shares of adjudicated disagreements on a high-confidence-enriched sample drawn from six label sources (Jev in both formats, Luna, Haiku, gpt-oss and Sonnet's subset run); the four coders shown have enough disagreements to break down. The panel resolved the items on which its two members agreed; the author resolved 36 items the panel disputed plus a 12-item audit of panel-agreed items (deviations 2–3).

Table 23: Top-confidence tie blocks on the dialogue tasks (test split)

task	signal	top confidence	decisions at top	share at top	error at top
AnnoMI client	Jev	1.000	274	0.302	0.123
AnnoMI client	OpenAI Decisions	1.000	176	0.198	0.121
AnnoMI client	Clef (27B)	0.979	1	0.001	0.000
AnnoMI client	pplx-decider	0.998	1	0.001	0.000
AnnoMI client	Kev-27B	0.995	1	0.001	0.000
AnnoMI client	Luna verbal	1.000	6	0.007	0.000
AnnoMI client	Haiku verbal	0.990	1	0.001	0.000
AnnoMI client	Sonnet verbal	0.970	16	0.017	0.000
AnnoMI therapist	Jev	1.000	214	0.225	0.068
AnnoMI therapist	OpenAI Decisions	1.000	117	0.131	0.027
AnnoMI therapist	Clef (27B)	0.963	2	0.002	0.000
AnnoMI therapist	pplx-decider	0.998	1	0.001	0.000
AnnoMI therapist	Kev-27B	0.996	1	0.001	0.000
AnnoMI therapist	Luna verbal	1.000	72	0.074	0.073
AnnoMI therapist	Haiku verbal	0.990	4	0.004	0.000
AnnoMI therapist	Sonnet verbal	0.980	15	0.013	0.000
TalkMoves teacher	Jev	1.000	104	0.082	0.083
TalkMoves teacher	OpenAI Decisions	1.000	271	0.249	0.107
TalkMoves teacher	Clef (27B)	0.948	1	0.000	0.000
TalkMoves teacher	pplx-decider	0.997	1	0.001	1.000
TalkMoves teacher	Kev-27B	0.978	1	0.001	0.000
TalkMoves teacher	Luna verbal	1.000	9	0.009	0.039
TalkMoves teacher	Haiku verbal	0.980	3	0.002	0.000
TalkMoves teacher	Sonnet verbal	0.960	36	0.037	0.000
TalkMoves student	Jev	1.000	119	0.106	0.065
TalkMoves student	OpenAI Decisions	1.000	9	0.009	0.000
TalkMoves student	Clef (27B)	0.945	1	0.000	0.000
TalkMoves student	pplx-decider	0.995	1	0.001	0.000
TalkMoves student	Kev-27B	0.983	1	0.001	0.000
TalkMoves student	Luna verbal	1.000	11	0.011	0.088
TalkMoves student	Haiku verbal	0.990	5	0.005	0.000
TalkMoves student	Sonnet verbal	0.960	16	0.015	0.000

Table 24: Memorization probe: completing the second half of dataset items, overlap with the true continuation (amendment v1.3)

model	dataset	items	ROUGE-L, named	ROUGE-L, unnamed	difference	p (Bonferroni)
Haiku	annomi	100	0.079	0.146	-0.067	1.000
Haiku	dunivin	100	0.080	0.144	-0.063	1.000
Haiku	mfrc	100	0.080	0.105	-0.025	1.000
Haiku	talkmoves	100	0.082	0.155	-0.072	1.000
Luna	annomi	100	0.082	0.156	-0.074	1.000
Luna	dunivin	100	0.095	0.151	-0.055	1.000
Luna	mfrc	100	0.082	0.111	-0.030	1.000
Luna	talkmoves	100	0.063	0.174	-0.111	1.000
gpt-oss-120b	annomi	100	0.057	0.090	-0.034	1.000
gpt-oss-120b	dunivin	100	0.016	0.066	-0.050	1.000
gpt-oss-120b	mfrc	100	0.038	0.055	-0.016	1.000
gpt-oss-120b	talkmoves	100	0.049	0.066	-0.017	1.000
Qwen3.5-9B	annomi	100	0.142	0.137	0.006	1.000
Qwen3.5-9B	dunivin	100	0.143	0.137	0.007	1.000
Qwen3.5-9B	mfrc	100	0.098	0.102	-0.004	1.000
Qwen3.5-9B	talkmoves	100	0.163	0.148	0.015	1.000
Qwen3.8-2.4T	annomi	100	0.083	0.150	-0.067	1.000
Qwen3.8-2.4T	dunivin	100	0.112	0.148	-0.036	1.000
Qwen3.8-2.4T	mfrc	100	0.086	0.101	-0.015	1.000
Qwen3.8-2.4T	talkmoves	100	0.125	0.168	-0.043	1.000
Sonnet	annomi	100	0.098	0.153	-0.055	1.000
Sonnet	dunivin	100	0.099	0.175	-0.076	1.000
Sonnet	mfrc	100	0.089	0.116	-0.027	1.000
Sonnet	talkmoves	100	0.076	0.156	-0.080	1.000

Named: the dataset is named and the exact original text requested. Unnamed: plain continuation. Difference: named – unnamed mean ROUGE-L; p: one-sided Wilcoxon signed-rank test for named > unnamed, Bonferroni-adjusted. Near-verbatim matches are in Table 25.

Table 25: Memorization probe: near-verbatim reproduction (counts of items, amendment v1.3)

model	dataset	items	near-verbatim items, named	near-verbatim items, unnamed	longest run, named (words)	flagged
Haiku	annomi	100	0	0	3	no
Haiku	dunivin	100	0	0	2	no
Haiku	mfrc	100	0	0	3	no
Haiku	talkmoves	100	0	1	3	no
Luna	annomi	100	0	0	2	no
Luna	dunivin	100	1	0	45	no
Luna	mfrc	100	0	0	2	no
Luna	talkmoves	100	0	0	4	no
gpt-oss-120b	annomi	100	0	0	2	no
gpt-oss-120b	dunivin	100	0	0	1	no
gpt-oss-120b	mfrc	100	0	0	2	no
gpt-oss-120b	talkmoves	100	0	0	3	no
Qwen3.5-9B	annomi	100	0	0	6	no
Qwen3.5-9B	dunivin	100	0	0	8	no
Qwen3.5-9B	mfrc	100	0	0	4	no
Qwen3.5-9B	talkmoves	100	1	1	10	no
Qwen3.8-2.4T	annomi	100	0	0	4	no
Qwen3.8-2.4T	dunivin	100	0	1	8	no
Qwen3.8-2.4T	mfrc	100	0	0	4	no
Qwen3.8-2.4T	talkmoves	100	0	0	5	no
Sonnet	annomi	100	0	0	3	no
Sonnet	dunivin	100	0	1	9	no
Sonnet	mfrc	100	0	0	3	no
Sonnet	talkmoves	100	0	0	2	no

Near-verbatim: a run of ≥ 10 identical words covering $\geq 50\%$ of the true continuation; counts of the 100 items. Longest run: the longest identical run under the named prompt only. Flagged: the pre-specified rule (Bonferroni $p < 0.05$ for named > unnamed in Table 24, or ≥ 2 near-verbatim items under the named prompt). Matches include a predictable counting sequence (TalkMoves) and Du Bois quotations (Dunivin).

Table 26: Memorization probe: recalling annotated labels without the codebook (amendment v1.3)

model	task	items	accuracy guided	accuracy general	difference	p (Bonferroni)	evidence of label leakage
Haiku	AnnoMI client	100	0.510	0.620	-0.110	1.000	no
Haiku	AnnoMI therapist	100	0.580	0.560	0.020	1.000	no
Haiku	MFRC	100	0.314	0.174	0.140	0.014	yes
Haiku	TalkMoves student	100	0.440	0.470	-0.030	1.000	no
Haiku	TalkMoves teacher	100	0.160	0.280	-0.120	1.000	no
Luna	AnnoMI client	100	0.580	0.710	-0.130	1.000	no
Luna	AnnoMI therapist	100	0.530	0.560	-0.030	1.000	no
Luna	MFRC	100	0.408	0.220	0.188	0.015	yes
Luna	TalkMoves student	100	0.530	0.520	0.010	1.000	no
Luna	TalkMoves teacher	100	0.520	0.470	0.050	1.000	no
gpt-oss-120b	AnnoMI client	100	0.560	0.510	0.050	1.000	no
gpt-oss-120b	AnnoMI therapist	100	0.680	0.440	0.240	0.004	yes
gpt-oss-120b	MFRC	100	0.260	0.223	0.037	1.000	no
gpt-oss-120b	TalkMoves student	100	0.510	0.410	0.100	0.621	no
gpt-oss-120b	TalkMoves teacher	100	0.200	0.270	-0.070	1.000	no
Qwen3.5-9B	AnnoMI client	100	0.720	0.640	0.080	1.000	no
Qwen3.5-9B	AnnoMI therapist	100	0.570	0.560	0.010	1.000	no
Qwen3.5-9B	MFRC	100	0.174	0.170	0.005	1.000	no
Qwen3.5-9B	TalkMoves student	100	0.420	0.400	0.020	1.000	no
Qwen3.5-9B	TalkMoves teacher	100	0.360	0.300	0.060	1.000	no
Qwen3.8-2.4T	AnnoMI client	100	0.720	0.620	0.100	0.959	no
Qwen3.8-2.4T	AnnoMI therapist	100	0.730	0.700	0.030	1.000	no
Qwen3.8-2.4T	MFRC	100	0.185	0.160	0.026	1.000	no
Qwen3.8-2.4T	TalkMoves student	100	0.490	0.450	0.040	1.000	no
Qwen3.8-2.4T	TalkMoves teacher	100	0.280	0.210	0.070	1.000	no
Sonnet	AnnoMI client	100	0.720	0.740	-0.020	1.000	no
Sonnet	AnnoMI therapist	100	0.730	0.770	-0.040	1.000	no
Sonnet	MFRC	100	0.573	0.518	0.055	1.000	no
Sonnet	TalkMoves student	100	0.590	0.560	0.030	1.000	no
Sonnet	TalkMoves teacher	100	0.630	0.500	0.130	0.287	no

Accuracy against the majority label (Jaccard for MFRC). Guided names the dataset and asks what its annotators assigned.

Table 27: Flagged label-probe cells: decoy-name control and coding accuracy on 'recalled' items

A. Label recall with the real name, a decoy name and no name

model	task	items	real name	decoy name	no name	real – decoy	p (real > decoy)	p (Bonferroni, 3 cells)
Haiku	MFRC	100	0.314	0.246	0.174	0.068	0.021	0.063
Luna	MFRC	100	0.408	0.280	0.220	0.128	0.012	0.035
gpt-oss-120b	AnnoMI therapist	100	0.680	0.650	0.440	0.030	0.304	0.911

B. Coding accuracy on 'recalled' and other items

model	task	recalled items	other items	coding accuracy, recalled	coding accuracy, other	p (recalled > other)
Haiku	MFRC	22	78	0.841	0.782	0.085
Luna	MFRC	35	65	0.868	0.883	0.779
gpt-oss-120b	AnnoMI therapist	33	67	0.970	0.672	0.000

Decoy: the same dataset description with a fictitious name (deviation 14). Memory is supported only if the real name beats the decoy. Recalled items: guided better than no name. Coding accuracy is the model's RQ1 accuracy on those items.

Table 28: Model snapshot: what was called, which version answered, and when

coder	provider	model requested	version returned	calls (all arms)	first call (UTC)	last call (UTC)
Jev	typesafe	jev-1.13.0	jev-1.13.0	65995	2026-10-10	2026-10-11
OpenAI Decisions	openai decisions	gpt-6-luna	gpt-6-luna	65993	2026-10-11	2026-10-11
Clef	cloudflare	@cf/cloudflare/clef	clef	14617	2026-10-11	2026-10-11
Clef-flash	cloudflare	@cf/cloudflare/clef-flash	clef-flash	65993	2026-10-11	2026-10-11
pplx-decider	perplexity	pplx-decider-v1.1-27b	pplx-decider-v1.1-27b	65993	2026-10-11	2026-10-11
Kev-9B	kev	jaredpalmer/kev-9b	kev-latest	51368	2026-10-11	2026-10-11
Kev-27B	kev	jaredpalmer/kev-27b	kev-latest	14117	2026-10-11	2026-10-11
Luna	openai	gpt-6-luna	gpt-6-luna	13905	2026-10-10	2026-10-11
Haiku	anthropic	claude-haiku-4-5	claude-haiku-4-5-20251001	11280	2026-10-10	2026-10-12
Sonnet	anthropic	claude-sonnet-5-5	claude-sonnet-5-5	12437	2026-10-10	2026-10-12
gpt-oss-120b	together	openai/gpt-oss-120b	openai/gpt-oss-120b	10030	2026-10-10	2026-10-11
Qwen3.5-9B	together	Qwen/Qwen3.5-9B	Qwen/Qwen3.5-9B	9930	2026-10-11	2026-10-11
Qwen3.8-2.4T	together	Qwen/Qwen3.8-2.4T-A95B	Qwen/Qwen3.8-2.4T-A95B	3281	2026-10-11	2026-10-11

Several APIs were in public beta (OpenAI Decisions from 2026-10-06; decision models launched September–October 2026). Kev weights: Hugging Face revisions db029f0 (kev-9b) and af0e6d5 (kev-27b), the latest on the call dates; kev package commit fc4a17e. Results describe these versions on these dates; the released harness allows re-running against later versions.

Table 29: LLM prompt sensitivity: verbalized distribution vs canonical prompt (amendment v1.4)

A. Error ranking

task	signal	decisions	err. AUROC canonical	err. AUROC distribution	difference	lo	hi
MFRC	Sonnet verbal	1200	0.933	0.897	-0.036	-0.052	-0.019
MFRC	Haiku verbal	1200	0.942	0.897	-0.045	-0.063	-0.029
AnnoMI client	Sonnet verbal	150	0.750	0.726	-0.024	-0.074	0.018
AnnoMI client	Haiku verbal	150	0.733	0.776	0.043	-0.041	0.136
AnnoMI therapist	Sonnet verbal	150	0.808	0.837	0.029	-0.012	0.083
AnnoMI therapist	Haiku verbal	150	0.770	0.717	-0.053	-0.139	0.014
TalkMoves teacher	Sonnet verbal	150	0.817	0.747	-0.070	-0.135	0.000
TalkMoves teacher	Haiku verbal	150	0.747	0.767	0.021	-0.080	0.120
TalkMoves student	Sonnet verbal	150	0.829	0.758	-0.071	-0.133	-0.012
TalkMoves student	Haiku verbal	150	0.786	0.770	-0.015	-0.082	0.046
Pooled	Sonnet verbal	1800	0.827	0.793	-0.034	-0.056	-0.011
Pooled	Haiku verbal	1800	0.796	0.786	-0.010	-0.045	0.022

B. Agreement and calibration

task	signal	decisions	κ canonical	κ distribution	ECE canonical	ECE distribution
MFRC	Sonnet verbal	1200	0.346	0.365	0.048	0.031
MFRC	Haiku verbal	1200	0.166	0.174	0.128	0.076
AnnoMI client	Sonnet verbal	150	0.413	0.432	0.065	0.079
AnnoMI client	Haiku verbal	150	0.479	0.453	0.118	0.158
AnnoMI therapist	Sonnet verbal	150	0.751	0.715	0.053	0.083
AnnoMI therapist	Haiku verbal	150	0.634	0.661	0.155	0.158
TalkMoves teacher	Sonnet verbal	150	0.590	0.603	0.089	0.045
TalkMoves teacher	Haiku verbal	150	0.554	0.528	0.141	0.215
TalkMoves student	Sonnet verbal	150	0.539	0.548	0.118	0.090
TalkMoves student	Haiku verbal	150	0.445	0.430	0.261	0.330
Pooled	Sonnet verbal	1800	0.528	0.533	0.074	0.066
Pooled	Haiku verbal	1800	0.456	0.449	0.161	0.187

Same test items (first 150 per task). Difference = distribution – canonical error AUROC, paired cluster bootstrap 95% CI; related tasks share cluster draws.

Table 30: LTT on synthetic clustered corpora (300 simulations per row, 30% of clusters hand-coded, $\delta = 0.05$)

clusters in corpus	decisions per cluster	copula loading	within-cluster error correlation	LTT on	P(remainder risk > 5%)	P(population risk > 5%)	mean share accepted
2000	8	0.000	-0.002	decisions	0.103	0.057	0.775
2000	8	0.000	-0.002	i.i.d. clusters	0.000	0.000	0.522
2000	8	0.000	-0.002	corpus	0.000	0.000	0.289
2000	8	0.500	0.070	decisions	0.113	0.067	0.772
2000	8	0.500	0.070	i.i.d. clusters	0.000	0.000	0.477
2000	8	0.500	0.070	corpus	0.000	0.000	0.249
2000	8	0.900	0.364	decisions	0.163	0.137	0.763
2000	8	0.900	0.364	i.i.d. clusters	0.003	0.000	0.362
2000	8	0.900	0.364	corpus	0.003	0.000	0.146
400	10	0.900	0.329	decisions	0.193	0.180	0.616
400	10	0.900	0.329	i.i.d. clusters	0.000	0.000	0.000
400	10	0.900	0.329	corpus	0.000	0.000	0.000
170	30	0.900	0.328	decisions	0.297	0.313	0.656
170	30	0.900	0.328	i.i.d. clusters	0.000	0.000	0.000
170	30	0.900	0.328	corpus	0.000	0.000	0.000

Calibrated confidence conf = 1 − 0.5ůBeta(1, 6); errors correlated within a cluster through a Gaussian copula (the loading is not the error correlation, which is shown). Remainder: the uncoded clusters of the corpus; population: closed form. The best threshold with population risk $\leq 5\%$ accepts 0.841 of decisions.

Table 31: Our corpus LTT procedure: hand-coded units needed before it certifies a coder that is never wrong

A. Grid of 16 thresholds (as used throughout)

task	sampling unit	units in corpus	mean unit weight / B	frozen split certifies it	lower bound	our procedure (median)
MFRC	comment	2000	1.00	yes	119	123
AnnoMI client	transcript	128	0.12	no	unreachable	not reached
AnnoMI client	utterance	1500	0.85	–	119	146.5
AnnoMI therapist	transcript	132	0.13	no	unreachable	not reached
AnnoMI therapist	utterance	1500	0.87	–	119	145
TalkMoves teacher	lesson	444	0.27	no	388	not reached
TalkMoves teacher	sentence	1500	0.78	–	119	163
TalkMoves student	lesson	436	0.08	no	unreachable	not reached
TalkMoves student	sentence	1500	0.90	–	119	139

B. One threshold fixed in advance (0.95)

task	sampling unit	units in corpus	lower bound	our procedure (median)
MFRC	comment	2000	62	64
AnnoMI client	transcript	128	unreachable	not reached
AnnoMI client	utterance	1500	62	75
AnnoMI therapist	transcript	132	unreachable	not reached
AnnoMI therapist	utterance	1500	62	75
TalkMoves teacher	lesson	444	114	not reached
TalkMoves teacher	sentence	1500	62	81.5
TalkMoves student	lesson	436	unreachable	not reached
TalkMoves student	sentence	1500	62	70.5

B: the largest unit's weight. Lower bound: a necessary number over every set of hand-coded units and every visiting order (each unit's bet can multiply the evidence by at most $1 + 0.05 \times$ its weight / B, and certification needs a factor of 320 with the grid, 20 with one threshold); fewer units cannot suffice, and reaching the bound does not guarantee certification. Unreachable: not reached even with every unit but one hand-coded. Our procedure: median number of units at which it first certifies, over 20 random hand-coding sequences (a description of typical runs, not a bound). Transcripts and lessons are the units of our splits; utterances and sentences drawn at random are an alternative design.

Table 32: Dialogue tasks under a different hand-coding design: corpus LTT with single utterances or sentences drawn at random (exploratory; 200 re-splits, 30% hand-coded)

A. Corpus LTT: mean share of the remainder's decisions accepted (percent; re-splits with no certificate count as 0)

signal	AnnoMI client	AnnoMI therapist	TalkMoves teacher	TalkMoves student
Jev	0.0	0.0	0.0	0.0
OpenAI Decisions	0.0	0.0	0.0	0.0
Clef (27B)	0.0	0.0	0.0	0.0
Clef-flash (9B)	0.0	0.0	0.0	0.0
pplx-decider	0.0	0.4	0.0	0.0
Kev-9B	0.0	0.0	0.0	0.0
Kev-27B	0.0	0.2	0.0	0.0
Luna verbal	0.0	0.0	0.0	0.0
Haiku verbal	0.0	0.0	0.0	0.0
gpt-oss verbal	0.0	0.0	0.0	0.0
Sonnet verbal	0.0	0.0	0.0	0.0

B. Corpus LTT: re-splits with any certified threshold

signal	AnnoMI client	AnnoMI therapist	TalkMoves teacher	TalkMoves student
Jev	0 of 200	0 of 200	0 of 200	0 of 200
OpenAI Decisions	0 of 200	0 of 200	0 of 200	0 of 200
Clef (27B)	0 of 200	0 of 200	0 of 200	0 of 200
Clef-flash (9B)	0 of 200	0 of 200	0 of 200	0 of 200
pplx-decider	0 of 200	2 of 200	0 of 200	0 of 200
Kev-9B	0 of 200	0 of 200	0 of 200	0 of 200
Kev-27B	0 of 200	1 of 200	0 of 200	0 of 200
Luna verbal	0 of 200	0 of 200	0 of 200	0 of 200
Haiku verbal	0 of 200	0 of 200	0 of 200	0 of 200
gpt-oss verbal	0 of 200	0 of 200	0 of 200	0 of 200
Sonnet verbal	0 of 200	0 of 200	0 of 200	0 of 200

C. Naive rule: share of re-splits whose accepted decisions exceed 5% error (percent)

signal	AnnoMI client	AnnoMI therapist	TalkMoves teacher	TalkMoves student
Jev	1.0	35.0	15.0	23.0
OpenAI Decisions	6.0	45.5	1.0	67.0
Clef (27B)	70.5	67.5	77.0	67.5
Clef-flash (9B)	74.0	58.5	55.5	38.0
pplx-decider	59.0	51.5	58.0	50.0
Kev-9B	68.0	78.0	48.0	28.0
Kev-27B	72.5	46.5	73.5	57.0
Luna verbal	36.5	19.0	25.5	44.5
Haiku verbal	42.0	31.0	30.0	5.0
gpt-oss verbal	55.5	46.0	22.5	62.0
Sonnet verbal	49.0	37.5	37.5	66.0

Each re-split hand-codes a uniformly random 30% of the task's segments, with their context as the coder saw it; the uncoded segments are the remainder, and the sampling unit is the segment, so B is the largest segment weight. Dependence among segments of one transcript is allowed. Coders tested: the seven decision models and Luna's, Haiku's, gpt-oss's and Sonnet's verbalized confidence (44 coder–task pairs). Corpus LTT's accepted remainder decisions exceeded 5% error in 0% of re-splits in every cell. Panel C: the naive rule on the same re-splits, for comparison.

Table 33: Error AUROC from raw confidence, from the predicted code alone, and from per-code maps (pooled)

signal	raw confidence	predicted code only	per-code maps
Clef (27B)	0.721	0.707	0.829
Clef-flash (9B)	0.712	0.693	0.801
Haiku verbal	0.783	0.696	0.812
Jev	0.756	0.714	0.797
Kev-27B	0.788	0.657	0.814
Kev-9B	0.694	0.713	0.809
Luna verbal	0.741	0.694	0.783
OpenAI Decisions	0.736	0.659	0.771
gpt-oss verbal	0.727	0.692	0.787
pplx-decider	0.764	0.691	0.813
Sonnet verbal	0.801	0.696	0.826

'Predicted code only' scores each decision by the calibration accuracy of its predicted code (multi-label: of its code), with no confidence.

Table 34: MFRC: corpus LTT over the 16-threshold grid vs one threshold fixed in advance (0.95)

signal	grid of 16: accepted	error	one threshold (0.95): accepted	error
Jev	0.598	0.016	0.170	0.006
OpenAI Decisions	0.000	–	0.000	–
Clef (27B)	0.823	0.030	0.365	0.001
Clef-flash (9B)	0.779	0.027	0.213	0.001
pplx-decider	0.771	0.023	0.656	0.013
Kev-9B	0.671	0.024	0.176	0.010
Kev-27B	0.766	0.021	0.294	0.003
Luna verbal	0.640	0.022	0.745	0.034
Haiku verbal	0.658	0.017	0.549	0.008
gpt-oss verbal	0.000	–	0.718	0.026
Sonnet verbal	0.827	0.025	0.624	0.007

On the four dialogue tasks, with the original whole-cluster split, neither version certifies anything for any coder.

Table 35: Temperature scaling and per-code maps depend on how exact 0s and 1s are floored before taking logarithms (pooled)

A. ECE

signal	raw	temperature, floor 1e-4	temperature, floor 1e-12
Jev	0.120	0.046	0.120
Kev-27B	0.073	0.029	0.029
Luna logprob	0.243	0.040	0.106
OpenAI Decisions	0.122	0.040	0.098
gpt-oss logprob	0.284	0.033	0.033
Qwen3.5-9B logprob	0.334	0.055	0.060
Sonnet verbal	0.051	0.053	0.053

B. Error AUROC

signal	raw	temperature, floor 1e-4	temperature, floor 1e-12	per-code Platt, floor 1e-4	per-code Platt, floor 1e-12
Jev	0.756	0.757	0.749	0.809	0.797
Kev-27B	0.788	0.788	0.788	0.814	0.814
Luna logprob	0.558	0.489	0.579	0.670	0.671
OpenAI Decisions	0.736	0.735	0.735	0.785	0.771
gpt-oss logprob	0.558	0.495	0.542	0.698	0.717
Qwen3.5-9B logprob	0.684	0.665	0.666	0.733	0.757
Sonnet verbal	0.801	0.802	0.802	0.826	0.826

One temperature per task, fitted by weighted log-loss on calib. A task-level Platt or isotonic map is monotone and leaves error ranking unchanged at any floor; per-code Platt maps (EQ3) are not monotone across codes, so the floor changes their ranking for coders that return exact 0s and 1s.

D Requests

LLM prompt (canonical; AnnoMI client format; the exchange shown is invented for illustration, since AnnoMI's text is not redistributed). The system prompt carries the codebook; option letters and their order are shared with the decision-model request.

```
SYSTEM:
You are an experienced qualitative researcher applying a fixed codebook (deductive coding). Apply the
  codebook exactly as written.

Task: In this motivational interviewing session, what type of talk is the client's utterance with respect to
  the target behaviour change given in ‘setting‘?
Unit of analysis: one client utterance.

Options (exactly one applies):
A) Change talk
   Definition: The client's own language in favor of the change goal.
   Applies when:
   - Commitment: an agreement, intention, or obligation regarding future change.
   - Taking steps: concrete steps the client has recently taken to make a change.
   - Reason: rationale, basis, justification, or motive to make a change.
   - Other: other statements that clearly reflect an intention to change.
B) Sustain talk
   Definition: The client's language giving reasons against changing or for maintaining the status quo.
   Applies when:
   - Commitment: an agreement, intention, or obligation not to change.
   - Taking steps: concrete steps the client has recently taken away from change.
   - Reason: rationale, basis, justification, or motive not to change.
   - Other: other statements that clearly reflect an intention not to change.
C) Neutral talk
   Definition: No indication of client inclination toward or away from change.
   Applies when:
   - Follow/neutral: responses that show no inclination toward or away from change.
   - Ask: asking for clarification or information.

Respond with JSON only. "rationale": one sentence explaining your decision. "answer": the letter of the
  option that applies. "probability": an integer from 0 to 100, your probability that this answer is
  correct.

USER:
setting: Motivational interviewing session. Target behaviour change: reducing alcohol consumption.

previous_turn (context only, not coded):
Therapist: What do you notice about how the drinking and your mood go together?

segment:
Honestly, when I'm low I reach for a drink, and afterwards I usually feel worse.

Judge only the client utterance in ‘segment‘; ‘previous_turn‘ is context and is not coded.
```

Decision-model request (the same item). Jev, Clef, pplx-decider and Kev receive this exact JSON. OpenAI Decisions receives the same content mapped to its choice and predicate types.

```
{
 "state": {
  "setting": "Motivational interviewing session. Target behaviour change: reducing alcohol consumption.",
  "previous_turn": "Therapist: What do you notice about how the drinking and your mood go together?",
  "segment": "Honestly, when I'm low I reach for a drink, and afterwards I usually feel worse."
 },
 "questions": {
  "code": {
   "type": "choice",
   "instructions": "In this motivational interviewing session, what type of talk is the client's utterance
  with respect to the target behaviour change given in ‘setting‘? Judge only the client utterance in
  ‘segment‘; ‘previous_turn‘ is context and is not coded.",
   "criteria": {
    "Change talk": {
     "definition": "The client's own language in favor of the change goal.",
```

```
    "applies_when": [
     "Commitment: an agreement, intention, or obligation regarding future change.",
     "Taking steps: concrete steps the client has recently taken to make a change.",
     "Reason: rationale, basis, justification, or motive to make a change.",
     "Other: other statements that clearly reflect an intention to change."
    ]
   },
   "Sustain talk": {
    "definition": "The client's language giving reasons against changing or for maintaining the status
  quo.",
    "applies_when": [
     "Commitment: an agreement, intention, or obligation not to change.",
     "Taking steps: concrete steps the client has recently taken away from change.",
     "Reason: rationale, basis, justification, or motive not to change.",
     "Other: other statements that clearly reflect an intention not to change."
    ]
   },
   "Neutral talk": {
    "definition": "No indication of client inclination toward or away from change.",
    "applies_when": [
     "Follow/neutral: responses that show no inclination toward or away from change.",
     "Ask: asking for clarification or information."
    ]
   }
  }
 }
}
```

E Memorization probe

For each of MFRC, AnnoMI, TalkMoves and Dunivin we drew 100 items of at least 30 words (20 for TalkMoves), with a fixed seed. The model saw the first half of the words (plus the previous turn for dialogue). The *guided* prompt named the dataset and its citation and asked for the exact original continuation. The *general* prompt asked only for a continuation [19]. We scored word-level ROUGE-L [35] and the longest common run of words, and called a completion near-verbatim if the run was at least 10 words and covered at least half of the true continuation. The label probe gave the item and the bare code labels, without definitions. The decoy control replaced the dataset name and citation with a fictitious one while keeping the description. Tables 24–27 report all cells.