0.0.1 Using Event Tracing for Windows (ETW)

As mentioned in ?? (??), the goal of this project is to research the possibilities of using built in telemetry, such as ETW, to detect the exploitation of vulnerabilities. Therefore, it is important to discover how ETW can be used to gather telemetry from providers.

One ETW provider that is widely used to detect malicious activity such as exploitation of vulnerabilities is the Microsoft_windows-Threat-Intelligence[1] provider. This is widely used by various Antivirus (AV) engines such as Microsoft's own Endpoint Detection and Response (EDR)/AV tool, Microsoft Defender for Endpoint. While this provider gives insight into Windows Application Programming Interface (API) calls often used in an exploitation process, we will not be focusing on this. As mentioned in ?? (??) and discussed in ?? (??), the project will revolve around detection of CVE-2020-24086, which is a vulnerability in the tcpip.sys driver of Windows. Due to this, we will in this section explore ETW providers relevant to this specific driver.

Finding providers

Getting a list of all available providers in Windows is fairly simply. A few methods exists, such as:

- 1. Using logman query providers
- 2. Using the PowerShell command Get-TraceEtwProvider
- 3. Enumerate registry keys under HKLM\SOFTWARE\Microsoft\Windows\Curre_\
 ntVersion\WINEVT\Publishers

The output from method (3), the registry, is as mentioned in ??, only for manifest-based providers. Therefore, not all providers will be shown here. Figure 1 (Finding ETW providers using Registry Editor) shows how the information available using Registry Editor. As it can be seen the registry contains information about the binary the provider is implemented in, which in our case is tcpip.sys.

Read this section thoroughy as it has been revised a lot ad-hoc



Figure 1: Finding ETW providers using Registry Editor

To find all manifest-based providers we can use the PowerShell script on listing 1, where the output of the command is also shown.

Listing 1: logman query providers output. See appendix ?? for full output

The same information queried using logman query providers can be seen in listing 2. However, the logman query providers command does not display the ResourceFileName as it can be seen on Figure 1.

```
Provider
                                        GUID
2
   ACPI Driver Trace Provider
   Active Directory Domain Services: SAM {8E598056-8993-11D2-819E-0000F875A064}
   Active Directory: Kerberos Client {BBA3ADD2-C229-4CDB-AE2B-57EB6966B0C4}
   Active Directory: NetLogon
                                       {F33959B4-DBEC-11D2-895B-00C04F79AB69}
   ADODB.1
                                        {04C8A86F-3369-12F8-4769-24E484A9E725}
   ADOMD. 1
                                       {7EA56435-3F2F-3F63-A829-F0B35B5CAD41}
   Application Popup
                                        {47BFA2B7-BD54-4FAC-B70B-29021084CA8F}
10
11
   Application-Addon-Event-Provider
                                        {A83FA99F-C356-4DED-9FD6-5A5EB8546D68}
12
13
   {\tt Microsoft-Windows-TCPIP}
                                        {2F07E2EE-15DB-40F1-90EF-9D7BA282188A}
14
15
   TCPIP Service Trace
                                        {EB004A05-9B1A-11D4-9123-0050047759BC}
```

Listing 2: logman query providers output. See appendix ?? for full output

The number of providers registered according to logman query providers is 1162 whereas 972 of these are manifest-based providers according to data from the registry. One example of a non-manifest-based provider that can only be found using logman is the provider TCPIP Service Trace as seen on line 15 in listing 2.

Using the second method, Get-TraceEtwProvider, simply yields a Access Denied error rendering it useless.

To conclude this section, we were able to find two different providers related to the TCP/IP stack on Windows. The first provider, *Microsoft-Windows-TCPIP* is definitely related to tcpip.sys according to the *ResourceFileName* property. The second however is a bit more cumbersome as logman does not provide any more information than the name (*TCPIP Service Trace*) and the GUID.

Starting a trace