

My Project

Generated by Doxygen 1.9.8

1 Topic Index	1
1.1 Topics	1
2 Class Index	3
2.1 Class List	3
3 File Index	5
3.1 File List	5
4 Topic Documentation	7
4.1 C++ bindings	7
4.1.1 Detailed Description	8
4.1.2 Function Documentation	8
4.1.2.1 begin() [1/2]	8
4.1.2.2 begin() [2/2]	8
4.1.2.3 end() [1/2]	8
4.1.2.4 end() [2/2]	9
4.1.2.5 find_line()	9
4.1.2.6 make_chip_iter()	9
5 Class Documentation	11
5.1 gpio::chip Class Reference	11
5.1.1 Detailed Description	12
5.1.2 Member Enumeration Documentation	12
5.1.2.1 anonymous enum	12
5.1.3 Constructor & Destructor Documentation	13
5.1.3.1 chip() [1/3]	13
5.1.3.2 chip() [2/3]	13
5.1.3.3 chip() [3/3]	13
5.1.4 Member Function Documentation	13
5.1.4.1 find_line()	13
5.1.4.2 find_lines()	14
5.1.4.3 get_all_lines()	14
5.1.4.4 get_line()	14
5.1.4.5 get_lines()	15
5.1.4.6 label()	15
5.1.4.7 name()	15
5.1.4.8 num_lines()	15
5.1.4.9 open()	16
5.1.4.10 operator bool()	16
5.1.4.11 operator"!"()	16
5.1.4.12 operator"!="()	16
5.1.4.13 operator=() [1/2]	17
5.1.4.14 operator=() [2/2]	17

5.1.4.15 operator==()	17
5.2 gpiod::chip_iter Class Reference	18
5.2.1 Detailed Description	18
5.2.2 Constructor & Destructor Documentation	19
5.2.2.1 chip_iter() [1/2]	19
5.2.2.2 chip_iter() [2/2]	20
5.2.3 Member Function Documentation	20
5.2.3.1 operator!=()	20
5.2.3.2 operator*()	20
5.2.3.3 operator++()	21
5.2.3.4 operator->()	21
5.2.3.5 operator=() [1/2]	21
5.2.3.6 operator=() [2/2]	21
5.2.3.7 operator==()	22
5.2.4 Friends And Related Symbol Documentation	22
5.2.4.1 make_chip_iter	22
5.3 gpiod::line_bulk::iterator Class Reference	22
5.3.1 Detailed Description	23
5.3.2 Constructor & Destructor Documentation	23
5.3.2.1 iterator() [1/2]	23
5.3.2.2 iterator() [2/2]	23
5.3.3 Member Function Documentation	24
5.3.3.1 operator!=()	24
5.3.3.2 operator*()	24
5.3.3.3 operator++()	24
5.3.3.4 operator->()	25
5.3.3.5 operator=() [1/2]	25
5.3.3.6 operator=() [2/2]	25
5.3.3.7 operator==()	25
5.4 gpiod::line Class Reference	26
5.4.1 Detailed Description	28
5.4.2 Member Enumeration Documentation	28
5.4.2.1 anonymous enum	28
5.4.2.2 anonymous enum	28
5.4.2.3 anonymous enum	28
5.4.3 Constructor & Destructor Documentation	29
5.4.3.1 line() [1/2]	29
5.4.3.2 line() [2/2]	29
5.4.4 Member Function Documentation	29
5.4.4.1 active_state()	29
5.4.4.2 bias()	29
5.4.4.3 consumer()	30

5.4.4.4 direction()	30
5.4.4.5 event_get_fd()	30
5.4.4.6 event_read()	30
5.4.4.7 event_read_multiple()	30
5.4.4.8 event_wait()	30
5.4.4.9 get_chip()	31
5.4.4.10 get_value()	31
5.4.4.11 is_open_drain()	31
5.4.4.12 is_open_source()	31
5.4.4.13 is_requested()	32
5.4.4.14 is_used()	32
5.4.4.15 name()	32
5.4.4.16 offset()	32
5.4.4.17 operator bool()	33
5.4.4.18 operator"!()	33
5.4.4.19 operator"!=(())	33
5.4.4.20 operator==([1/2])	33
5.4.4.21 operator==([2/2])	34
5.4.4.22 operator==()	34
5.4.4.23 request()	34
5.4.4.24 reset()	35
5.4.4.25 set_config()	35
5.4.4.26 set_direction_output()	35
5.4.4.27 set_flags()	35
5.4.4.28 set_value()	36
5.5 gpiod::line_bulk Class Reference	36
5.5.1 Detailed Description	37
5.5.2 Constructor & Destructor Documentation	37
5.5.2.1 line_bulk() [1/3]	37
5.5.2.2 line_bulk() [2/3]	38
5.5.2.3 line_bulk() [3/3]	38
5.5.3 Member Function Documentation	38
5.5.3.1 append()	38
5.5.3.2 begin()	39
5.5.3.3 empty()	39
5.5.3.4 end()	39
5.5.3.5 event_wait()	39
5.5.3.6 get()	40
5.5.3.7 get_values()	40
5.5.3.8 operator bool()	40
5.5.3.9 operator"!()	40
5.5.3.10 operator==([1/2])	41

5.5.3.11 operator=() [2/2]	42
5.5.3.12 operator[]()	42
5.5.3.13 request()	42
5.5.3.14 set_config()	43
5.5.3.15 set_direction_output()	43
5.5.3.16 set_flags()	43
5.5.3.17 set_values()	43
5.5.3.18 size()	44
5.6 gpiod::line_event Struct Reference	44
5.6.1 Detailed Description	45
5.6.2 Member Enumeration Documentation	45
5.6.2.1 anonymous enum	45
5.6.3 Member Data Documentation	45
5.6.3.1 event_type	45
5.6.3.2 source	45
5.6.3.3 timestamp	45
5.7 gpiod::line_iter Class Reference	46
5.7.1 Detailed Description	46
5.7.2 Constructor & Destructor Documentation	46
5.7.2.1 line_iter() [1/3]	46
5.7.2.2 line_iter() [2/3]	47
5.7.2.3 line_iter() [3/3]	47
5.7.3 Member Function Documentation	47
5.7.3.1 operator!=(())	47
5.7.3.2 operator*()	47
5.7.3.3 operator++()	48
5.7.3.4 operator->()	48
5.7.3.5 operator=() [1/2]	48
5.7.3.6 operator=() [2/2]	48
5.7.3.7 operator==(())	49
5.8 gpiod::line_request Struct Reference	49
5.8.1 Detailed Description	50
5.8.2 Member Enumeration Documentation	50
5.8.2.1 anonymous enum	50
5.8.3 Member Data Documentation	50
5.8.3.1 consumer	50
5.8.3.2 FLAG_ACTIVE_LOW	50
5.8.3.3 FLAG_BIAS_DISABLE	51
5.8.3.4 FLAG_BIAS_PULL_DOWN	51
5.8.3.5 FLAG_BIAS_PULL_UP	51
5.8.3.6 FLAG_OPEN_DRAIN	51
5.8.3.7 FLAG_OPEN_SOURCE	51

5.8.3.8 flags	51
5.8.3.9 request_type	51
6 File Documentation	53
6.1 gpiod.hpp File Reference	53
6.2 gpiod.hpp	54
Index	61

Chapter 1

Topic Index

1.1 Topics

Here is a list of all topics with brief descriptions:

C++ bindings	7
------------------------	-------------------

Chapter 2

Class Index

2.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

gpod::chip	Represents a GPIO chip	11
gpod::chip_iter	Allows to iterate over all GPIO chips present on the system	18
gpod::line_bulk::iterator	Iterator for iterating over lines held by line_bulk	22
gpod::line	Represents a single GPIO line	26
gpod::line_bulk	Represents a set of GPIO lines	36
gpod::line_event	Describes a single GPIO line event	44
gpod::line_iter	Allows to iterate over all lines owned by a GPIO chip	46
gpod::line_request	Stores the configuration for line requests	49

Chapter 3

File Index

3.1 File List

Here is a list of all documented files with brief descriptions:

gpiod.hpp	53
-------------------------------------	----

Chapter 4

Topic Documentation

4.1 C++ bindings

Classes

- class `gpiod::chip`
Represents a GPIO chip.
- struct `gpiod::line_request`
Stores the configuration for line requests.
- class `gpiod::line`
Represents a single GPIO line.
- struct `gpiod::line_event`
Describes a single GPIO line event.
- class `gpiod::line_bulk`
Represents a set of GPIO lines.
- class `gpiod::chip_iter`
Allows to iterate over all GPIO chips present on the system.
- class `gpiod::line_iter`
Allows to iterate over all lines owned by a GPIO chip.

Functions

- GPIOD_API `line gpiod::find_line` (const ::std::string &name)
Find a GPIO line by name. Search all GPIO chips present on the system.
- GPIOD_API `chip_iter gpiod::make_chip_iter` (void)
Create a new `chip_iter`.
- GPIOD_API `chip_iter gpiod::begin` (`chip_iter` iter) noexcept
Support for range-based loops for chip iterators.
- GPIOD_API `chip_iter gpiod::end` (const `chip_iter` &iter) noexcept
Support for range-based loops for chip iterators.
- GPIOD_API `line_iter gpiod::begin` (`line_iter` iter) noexcept
Support for range-based loops for line iterators.
- GPIOD_API `line_iter gpiod::end` (const `line_iter` &iter) noexcept
Support for range-based loops for line iterators.

4.1.1 Detailed Description

4.1.2 Function Documentation

4.1.2.1 `begin()` [1/2]

```
GPIOD_API chip_iter gpiod::begin (  
    chip_iter iter ) [noexcept]
```

Support for range-based loops for chip iterators.

Parameters

<i>iter</i>	A chip iterator.
-------------	------------------

Returns

Iterator unchanged.

4.1.2.2 `begin()` [2/2]

```
GPIOD_API line_iter gpiod::begin (  
    line_iter iter ) [noexcept]
```

Support for range-based loops for line iterators.

Parameters

<i>iter</i>	A line iterator.
-------------	------------------

Returns

Iterator unchanged.

4.1.2.3 `end()` [1/2]

```
GPIOD_API chip_iter gpiod::end (  
    const chip_iter & iter ) [noexcept]
```

Support for range-based loops for chip iterators.

Parameters

<i>iter</i>	A chip iterator.
-------------	------------------

Returns

New end iterator.

4.1.2.4 end() [2/2]

```
GPIOD_API line_iter gpiod::end (
    const line_iter & iter ) [noexcept]
```

Support for range-based loops for line iterators.

Parameters

<i>iter</i>	A line iterator.
-------------	------------------

Returns

New end iterator.

4.1.2.5 find_line()

```
GPIOD_API line gpiod::find_line (
    const ::std::string & name )
```

Find a GPIO line by name. Search all GPIO chips present on the system.

Parameters

<i>name</i>	Name of the line.
-------------	-------------------

Returns

Returns a line object - empty if the line was not found.

4.1.2.6 make_chip_iter()

```
GPIOD_API chip_iter gpiod::make_chip_iter (
    void )
```

Create a new [chip_iter](#).

Returns

New chip iterator object pointing to the first GPIO chip on the system.

Note

This function is needed as we already use the default constructor of [gpiod::chip_iter](#) as the return value of [gpiod::end](#).

Chapter 5

Class Documentation

5.1 `gpio::chip` Class Reference

Represents a GPIO chip.

```
#include <gpio.hpp>
```

Public Types

- enum : int {
 [OPEN_LOOKUP](#) = 1 , [OPEN_BY_PATH](#) , [OPEN_BY_NAME](#) , [OPEN_BY_LABEL](#) ,
 [OPEN_BY_NUMBER](#) }
 Affect the way in which [chip::chip](#) and [chip::open](#) will try to open a GPIO chip character device.

Public Member Functions

- GPIO_API **chip** (void)=default
 Default constructor. Creates an empty GPIO chip object.
- GPIO_API **chip** (const ::std::string &device, int how=[OPEN_LOOKUP](#))
 Constructor. Opens the chip using [chip::open](#).
- GPIO_API **chip** (const **chip** &other)=default
 Copy constructor. References the object held by other.
- GPIO_API **chip** (**chip** &&other)=default
 Move constructor. References the object held by other.
- GPIO_API **chip** & **operator=** (const **chip** &other)=default
 Assignment operator. References the object held by other.
- GPIO_API **chip** & **operator=** (**chip** &&other)=default
 Move assignment operator. References the object held by other.
- GPIO_API ~**chip** (void)=default
 Destructor. Unreferences the internal chip object.
- GPIO_API void **open** (const ::std::string &device, int how=[OPEN_LOOKUP](#))
 Open a GPIO chip.
- GPIO_API void **reset** (void) noexcept
 Reset the internal smart pointer owned by this object.
- GPIO_API ::std::string **name** (void) const

- Return the name of the chip held by this object.*
- `GPIOD_API::std::string label` (void) const
Return the label of the chip held by this object.
- `GPIOD_API unsigned int num_lines` (void) const
Return the number of lines exposed by this chip.
- `GPIOD_API line get_line` (unsigned int offset) const
Get the line exposed by this chip at given offset.
- `GPIOD_API line find_line` (const ::std::string &name) const
Get the line exposed by this chip by name.
- `GPIOD_API line_bulk get_lines` (const ::std::vector< unsigned int > &offsets) const
Get a set of lines exposed by this chip at given offsets.
- `GPIOD_API line_bulk get_all_lines` (void) const
Get all lines exposed by this chip.
- `GPIOD_API line_bulk find_lines` (const ::std::vector<::std::string > &names) const
Get a set of lines exposed by this chip by their names.
- `GPIOD_API bool operator==` (const `chip` &rhs) const noexcept
Equality operator.
- `GPIOD_API bool operator!=` (const `chip` &rhs) const noexcept
Inequality operator.
- `GPIOD_API operator bool` (void) const noexcept
Check if this object holds a reference to a GPIO chip.
- `GPIOD_API bool operator!` (void) const noexcept
Check if this object doesn't hold a reference to a GPIO chip.

5.1.1 Detailed Description

Represents a GPIO chip.

Internally this class holds a smart pointer to an open GPIO chip descriptor. Multiple objects of this class can reference the same chip. The chip is closed and all resources freed when the last reference is dropped.

5.1.2 Member Enumeration Documentation

5.1.2.1 anonymous enum

```
anonymous enum : int
```

Affect the way in which `chip::chip` and `chip::open` will try to open a GPIO chip character device.

Enumerator

<code>OPEN_LOOKUP</code>	Open based on the best guess what the supplied string is.
<code>OPEN_BY_PATH</code>	Assume the string is a path to the GPIO chardev.
<code>OPEN_BY_NAME</code>	Assume the string is the name of the chip
<code>OPEN_BY_LABEL</code>	Assume the string is the label of the GPIO chip.
<code>OPEN_BY_NUMBER</code>	Assume the string is the number of the GPIO chip.

5.1.3 Constructor & Destructor Documentation

5.1.3.1 chip() [1/3]

```
GPIOD_API gpiod::chip::chip (
    const ::std::string & device,
    int how = OPEN_LOOKUP )
```

Constructor. Opens the chip using [chip::open](#).

Parameters

<i>device</i>	String describing the GPIO chip.
<i>how</i>	Indicates how the chip should be opened.

5.1.3.2 chip() [2/3]

```
GPIOD_API gpiod::chip::chip (
    const chip & other ) [default]
```

Copy constructor. References the object held by other.

Parameters

<i>other</i>	Other chip object.
--------------	--------------------

5.1.3.3 chip() [3/3]

```
GPIOD_API gpiod::chip::chip (
    chip && other ) [default]
```

Move constructor. References the object held by other.

Parameters

<i>other</i>	Other chip object.
--------------	--------------------

5.1.4 Member Function Documentation

5.1.4.1 find_line()

```
GPIOD_API line gpiod::chip::find_line (
    const ::std::string & name ) const
```

Get the line exposed by this chip by name.

Parameters

<i>name</i>	Line name.
-------------	------------

Returns

Line object.

5.1.4.2 find_lines()

```
GPIOD_API line_bulk gpiod::chip::find_lines (  
    const ::std::vector<::std::string > & names ) const
```

Get a set of lines exposed by this chip by their names.

Parameters

<i>names</i>	Vector of line names.
--------------	-----------------------

Returns

Set of lines held by a [line_bulk](#) object.

5.1.4.3 get_all_lines()

```
GPIOD_API line_bulk gpiod::chip::get_all_lines (  
    void ) const
```

Get all lines exposed by this chip.

Returns

All lines exposed by this chip held by a [line_bulk](#) object.

5.1.4.4 get_line()

```
GPIOD_API line gpiod::chip::get_line (  
    unsigned int offset ) const
```

Get the line exposed by this chip at given offset.

Parameters

<i>offset</i>	Offset of the line.
---------------	---------------------

Returns

Line object.

5.1.4.5 get_lines()

```
GPIOD_API line_bulk gpiod::chip::get_lines (
    const ::std::vector< unsigned int > & offsets ) const
```

Get a set of lines exposed by this chip at given offsets.

Parameters

<i>offsets</i>	Vector of line offsets.
----------------	-------------------------

Returns

Set of lines held by a [line_bulk](#) object.

5.1.4.6 label()

```
GPIOD_API::std::string gpiod::chip::label (
    void ) const
```

Return the label of the chip held by this object.

Returns

Label of the GPIO chip.

5.1.4.7 name()

```
GPIOD_API::std::string gpiod::chip::name (
    void ) const
```

Return the name of the chip held by this object.

Returns

Name of the GPIO chip.

5.1.4.8 num_lines()

```
GPIOD_API unsigned int gpiod::chip::num_lines (
    void ) const
```

Return the number of lines exposed by this chip.

Returns

Number of lines.

5.1.4.9 open()

```
GPIOD_API void gpiod::chip::open (
    const ::std::string & device,
    int how = OPEN_LOOKUP )
```

Open a GPIO chip.

Parameters

<i>device</i>	String describing the GPIO chip.
<i>how</i>	Indicates how the chip should be opened.

If the object already holds a reference to an open chip, it will be closed and the reference reset.

5.1.4.10 operator bool()

```
GPIOD_API gpiod::chip::operator bool (
    void ) const [explicit], [noexcept]
```

Check if this object holds a reference to a GPIO chip.

Returns

True if this object references a GPIO chip, false otherwise.

5.1.4.11 operator"!()

```
GPIOD_API bool gpiod::chip::operator! (
    void ) const [noexcept]
```

Check if this object doesn't hold a reference to a GPIO chip.

Returns

False if this object references a GPIO chip, true otherwise.

5.1.4.12 operator"!=(

```
GPIOD_API bool gpiod::chip::operator!= (
    const chip & rhs ) const [noexcept]
```

Inequality operator.

Parameters

<i>rhs</i>	Right-hand side of the equation.
------------	----------------------------------

Returns

False if rhs references the same chip. True otherwise.

5.1.4.13 operator=() [1/2]

```
GPIOD_API chip & gpiod::chip::operator= (  
    chip && other ) [default]
```

Move assignment operator. References the object held by other.

Parameters

<i>other</i>	Other chip object.
--------------	--------------------

Returns

Reference to this object.

5.1.4.14 operator=() [2/2]

```
GPIOD_API chip & gpiod::chip::operator= (  
    const chip & other ) [default]
```

Assignment operator. References the object held by other.

Parameters

<i>other</i>	Other chip object.
--------------	--------------------

Returns

Reference to this object.

5.1.4.15 operator==()

```
GPIOD_API bool gpiod::chip::operator== (  
    const chip & rhs ) const [noexcept]
```

Equality operator.

Parameters

<i>rhs</i>	Right-hand side of the equation.
------------	----------------------------------

Returns

True if rhs references the same chip. False otherwise.

The documentation for this class was generated from the following file:

- [gpiod.hpp](#)

5.2 gpiod::chip_iter Class Reference

Allows to iterate over all GPIO chips present on the system.

```
#include <gpiod.hpp>
```

Public Member Functions

- **GPIOD_API chip_iter** (void)=default
Default constructor. Creates the end iterator.
- **GPIOD_API chip_iter** (const [chip_iter](#) &other)=default
Copy constructor.
- **GPIOD_API chip_iter** ([chip_iter](#) &&other)=default
Move constructor.
- **GPIOD_API chip_iter & operator=** (const [chip_iter](#) &other)=default
Assignment operator.
- **GPIOD_API chip_iter & operator=** ([chip_iter](#) &&other)=default
Move assignment operator.
- **GPIOD_API ~chip_iter** (void)=default
Destructor.
- **GPIOD_API chip_iter & operator++** (void)
Advance the iterator by one element.
- **GPIOD_API const chip & operator*** (void) const
Dereference current element.
- **GPIOD_API const chip * operator->** (void) const
Member access operator.
- **GPIOD_API bool operator==** (const [chip_iter](#) &rhs) const noexcept
Check if this operator points to the same element.
- **GPIOD_API bool operator!=** (const [chip_iter](#) &rhs) const noexcept
Check if this operator doesn't point to the same element.

Friends

- [chip_iter make_chip_iter](#) (void)
Create a new [chip_iter](#).

5.2.1 Detailed Description

Allows to iterate over all GPIO chips present on the system.

5.2.2 Constructor & Destructor Documentation

5.2.2.1 chip_iter() [1/2]

```
GPIOD_API gpiod::chip_iter::chip_iter (  
    const chip\_iter & other ) [default]
```

Copy constructor.

Parameters

<i>other</i>	Other chip_iter .
--------------	-----------------------------------

5.2.2.2 chip_iter() [2/2]

```
GPIOD_API gpiod::chip_iter::chip_iter (
    chip\_iter && other ) [default]
```

Move constructor.

Parameters

<i>other</i>	Other chip_iter .
--------------	-----------------------------------

5.2.3 Member Function Documentation**5.2.3.1 operator!=(())**

```
GPIOD_API bool gpiod::chip_iter::operator!= (
    const chip\_iter & rhs ) const [noexcept]
```

Check if this operator doesn't point to the same element.

Parameters

<i>rhs</i>	Right-hand side of the equation.
------------	----------------------------------

Returns

True if this iterator doesn't point to the same [chip_iter](#), false otherwise.

5.2.3.2 operator*()

```
GPIOD_API const chip & gpiod::chip_iter::operator* (
    void ) const
```

Dereference current element.

Returns

Current GPIO chip by reference.

5.2.3.3 operator++()

```
GPIOD_API chip_iter & gpiod::chip_iter::operator++ (
    void )
```

Advance the iterator by one element.

Returns

Reference to this iterator.

5.2.3.4 operator->()

```
GPIOD_API const chip * gpiod::chip_iter::operator-> (
    void ) const
```

Member access operator.

Returns

Current GPIO chip by pointer.

5.2.3.5 operator=() [1/2]

```
GPIOD_API chip_iter & gpiod::chip_iter::operator= (
    chip_iter && other ) [default]
```

Move assignment operator.

Parameters

<i>other</i>	Other chip_iter .
--------------	-----------------------------------

Returns

Reference to this iterator.

5.2.3.6 operator=() [2/2]

```
GPIOD_API chip_iter & gpiod::chip_iter::operator= (
    const chip_iter & other ) [default]
```

Assignment operator.

Parameters

<i>other</i>	Other chip_iter .
--------------	-----------------------------------

Returns

Reference to this iterator.

5.2.3.7 operator==()

```
GPIOD_API bool gpiod::chip_iter::operator== (
    const chip\_iter & rhs ) const [noexcept]
```

Check if this operator points to the same element.

Parameters

<i>rhs</i>	Right-hand side of the equation.
------------	----------------------------------

Returns

True if this iterator points to the same [chip_iter](#), false otherwise.

5.2.4 Friends And Related Symbol Documentation**5.2.4.1 make_chip_iter**

```
chip\_iter make_chip_iter (
    void ) [friend]
```

Create a new [chip_iter](#).

Returns

New chip iterator object pointing to the first GPIO chip on the system.

Note

This function is needed as we already use the default constructor of [gpiod::chip_iter](#) as the return value of [gpiod::end](#).

The documentation for this class was generated from the following file:

- [gpiod.hpp](#)

5.3 gpiod::line_bulk::iterator Class Reference

Iterator for iterating over lines held by [line_bulk](#).

```
#include <gpiod.hpp>
```

Public Member Functions

- `GPIOD_API iterator` (void)=default
Default constructor. Builds an empty iterator object.
- `GPIOD_API iterator` (const [iterator](#) &other)=default
Copy constructor.
- `GPIOD_API iterator` ([iterator](#) &&other)=default
Move constructor.
- `GPIOD_API iterator & operator=` (const [iterator](#) &other)=default
Assignment operator.
- `GPIOD_API iterator & operator=` ([iterator](#) &&other)=default
Move assignment operator.
- `GPIOD_API ~iterator` (void)=default
Destructor.
- `GPIOD_API iterator & operator++` (void)
Advance the iterator by one element.
- `GPIOD_API const line & operator*` (void) const
Dereference current element.
- `GPIOD_API const line * operator->` (void) const
Member access operator.
- `GPIOD_API bool operator==` (const [iterator](#) &rhs) const noexcept
Check if this operator points to the same element.
- `GPIOD_API bool operator!=` (const [iterator](#) &rhs) const noexcept
Check if this operator doesn't point to the same element.

5.3.1 Detailed Description

Iterator for iterating over lines held by [line_bulk](#).

5.3.2 Constructor & Destructor Documentation

5.3.2.1 iterator() [1/2]

```
GPIOD_API gpiod::line_bulk::iterator::iterator (
    const iterator & other ) [default]
```

Copy constructor.

Parameters

<i>other</i>	Other line_bulk iterator.
--------------	---

5.3.2.2 iterator() [2/2]

```
GPIOD_API gpiod::line_bulk::iterator::iterator (
    iterator && other ) [default]
```

Move constructor.

Parameters

<i>other</i>	Other line_bulk iterator.
--------------	---

5.3.3 Member Function Documentation

5.3.3.1 `operator!=()`

```
GPIO_API bool gpiod::line_bulk::iterator::operator!= (
    const iterator & rhs ) const [noexcept]
```

Check if this operator doesn't point to the same element.

Parameters

<i>rhs</i>	Right-hand side of the equation.
------------	----------------------------------

Returns

True if this iterator doesn't point to the same GPIO line, false otherwise.

5.3.3.2 `operator*()`

```
GPIO_API const line & gpiod::line_bulk::iterator::operator* (
    void ) const
```

Dereference current element.

Returns

Current GPIO line by reference.

5.3.3.3 `operator++()`

```
GPIO_API iterator & gpiod::line_bulk::iterator::operator++ (
    void )
```

Advance the iterator by one element.

Returns

Reference to this iterator.

5.3.3.4 operator->()

```
GPIOD_API const line * gpiod::line_bulk::iterator::operator-> (
    void ) const
```

Member access operator.

Returns

Current GPIO line by pointer.

5.3.3.5 operator=() [1/2]

```
GPIOD_API iterator & gpiod::line_bulk::iterator::operator= (
    const iterator & other ) [default]
```

Assignment operator.

Parameters

<i>other</i>	Other <code>line_bulk</code> iterator.
--------------	--

Returns

Reference to this iterator.

5.3.3.6 operator=() [2/2]

```
GPIOD_API iterator & gpiod::line_bulk::iterator::operator= (
    iterator && other ) [default]
```

Move assignment operator.

Parameters

<i>other</i>	Other <code>line_bulk</code> iterator.
--------------	--

Returns

Reference to this iterator.

5.3.3.7 operator==()

```
GPIOD_API bool gpiod::line_bulk::iterator::operator== (
    const iterator & rhs ) const [noexcept]
```

Check if this operator points to the same element.

Parameters

<i>rhs</i>	Right-hand side of the equation.
------------	----------------------------------

Returns

True if this iterator points to the same GPIO line, false otherwise.

The documentation for this class was generated from the following file:

- [gpiod.hpp](#)

5.4 gpiod::line Class Reference

Represents a single GPIO line.

```
#include <gpiod.hpp>
```

Public Types

- enum : int { [DIRECTION_INPUT](#) = 1 , [DIRECTION_OUTPUT](#) }
Possible direction settings.
- enum : int { [ACTIVE_LOW](#) = 1 , [ACTIVE_HIGH](#) }
Possible active state settings.
- enum : int { [BIAS_AS_IS](#) = 1 , [BIAS_DISABLE](#) , [BIAS_PULL_UP](#) , [BIAS_PULL_DOWN](#) }
Possible bias settings.

Public Member Functions

- **GPIOD_API line** (void)
Default constructor. Creates an empty line object.
- **GPIOD_API line** (const [line](#) &other)=default
Copy constructor.
- **GPIOD_API line** ([line](#) &&other)=default
Move constructor.
- **GPIOD_API line & operator=** (const [line](#) &other)=default
Assignment operator.
- **GPIOD_API line & operator=** ([line](#) &&other)=default
Move assignment operator.
- **GPIOD_API ~line** (void)=default
Destructor.
- **GPIOD_API unsigned int offset** (void) const
Get the offset of this line.
- **GPIOD_API::std::string name** (void) const
Get the name of this line (if any).
- **GPIOD_API::std::string consumer** (void) const
Get the consumer of this line (if any).

- GPIOD_API int [direction](#) (void) const
Get current direction of this line.
- GPIOD_API int [active_state](#) (void) const
Get current active state of this line.
- GPIOD_API int [bias](#) (void) const
Get current bias of this line.
- GPIOD_API bool [is_used](#) (void) const
Check if this line is used by the kernel or other user space process.
- GPIOD_API bool [is_open_drain](#) (void) const
Check if this line represents an open-drain GPIO.
- GPIOD_API bool [is_open_source](#) (void) const
Check if this line represents an open-source GPIO.
- GPIOD_API void [request](#) (const [line_request](#) &config, int default_val=0) const
Request this line.
- GPIOD_API void [release](#) (void) const
Release the line if it was previously requested.
- GPIOD_API bool [is_requested](#) (void) const
Check if this user has ownership of this line.
- GPIOD_API int [get_value](#) (void) const
Read the line value.
- GPIOD_API void [set_value](#) (int val) const
Set the value of this line.
- GPIOD_API void [set_config](#) (int [direction](#), ::std::bitset< 32 > flags, int value=0) const
Set configuration of this line.
- GPIOD_API void [set_flags](#) (::std::bitset< 32 > flags) const
Set configuration flags of this line.
- GPIOD_API void [set_direction_input](#) () const
Change the direction this line to input.
- GPIOD_API void [set_direction_output](#) (int value=0) const
Change the direction this lines to output.
- GPIOD_API bool [event_wait](#) (const ::std::chrono::nanoseconds &timeout) const
Wait for an event on this line.
- GPIOD_API [line_event](#) [event_read](#) (void) const
Read a line event.
- GPIOD_API ::std::vector< [line_event](#) > [event_read_multiple](#) (void) const
Read multiple line events.
- GPIOD_API int [event_get_fd](#) (void) const
Get the event file descriptor associated with this line.
- GPIOD_API const [chip](#) & [get_chip](#) (void) const
Get the reference to the parent chip.
- GPIOD_API void [update](#) (void) const
Re-read the line info from the kernel.
- GPIOD_API void [reset](#) (void)
Reset the state of this object.
- GPIOD_API bool [operator==](#) (const [line](#) &rhs) const noexcept
Check if two line objects reference the same GPIO line.
- GPIOD_API bool [operator!=](#) (const [line](#) &rhs) const noexcept
Check if two line objects reference different GPIO lines.
- GPIOD_API [operator bool](#) (void) const noexcept
Check if this object holds a reference to any GPIO line.
- GPIOD_API bool [operator!](#) (void) const noexcept
Check if this object doesn't reference any GPIO line.

5.4.1 Detailed Description

Represents a single GPIO line.

Internally this class holds a raw pointer to a GPIO line descriptor and a reference to the parent chip. All line resources are freed when the last reference to the parent chip is dropped.

5.4.2 Member Enumeration Documentation

5.4.2.1 anonymous enum

```
anonymous enum : int
```

Possible direction settings.

Enumerator

DIRECTION_INPUT	Line's direction setting is input.
DIRECTION_OUTPUT	Line's direction setting is output.

5.4.2.2 anonymous enum

```
anonymous enum : int
```

Possible active state settings.

Enumerator

ACTIVE_LOW	Line's active state is low.
ACTIVE_HIGH	Line's active state is high.

5.4.2.3 anonymous enum

```
anonymous enum : int
```

Possible bias settings.

Enumerator

BIAS_AS_IS	Line's bias state is unknown.
BIAS_DISABLE	Line's internal bias is disabled.
BIAS_PULL_UP	Line's internal pull-up bias is enabled.
BIAS_PULL_DOWN	Line's internal pull-down bias is enabled.

5.4.3 Constructor & Destructor Documentation

5.4.3.1 line() [1/2]

```
GPIOD_API gpiod::line::line (  
    const line & other ) [default]
```

Copy constructor.

Parameters

<i>other</i>	Other line object.
--------------	--------------------

5.4.3.2 line() [2/2]

```
GPIOD_API gpiod::line::line (  
    line && other ) [default]
```

Move constructor.

Parameters

<i>other</i>	Other line object.
--------------	--------------------

5.4.4 Member Function Documentation

5.4.4.1 active_state()

```
GPIOD_API int gpiod::line::active_state (  
    void ) const
```

Get current active state of this line.

Returns

Current active state setting.

5.4.4.2 bias()

```
GPIOD_API int gpiod::line::bias (  
    void ) const
```

Get current bias of this line.

Returns

Current bias setting.

5.4.4.3 consumer()

```
GPIOD_API::std::string gpiod::line::consumer (
    void ) const
```

Get the consumer of this line (if any).

Returns

Name of the consumer of this line or an empty string if it is unused.

5.4.4.4 direction()

```
GPIOD_API int gpiod::line::direction (
    void ) const
```

Get current direction of this line.

Returns

Current direction setting.

5.4.4.5 event_get_fd()

```
GPIOD_API int gpiod::line::event_get_fd (
    void ) const
```

Get the event file descriptor associated with this line.

Returns

File descriptor number.

5.4.4.6 event_read()

```
GPIOD_API line_event gpiod::line::event_read (
    void ) const
```

Read a line event.

Returns

Line event object.

5.4.4.7 event_read_multiple()

```
GPIOD_API ::std::vector< line_event > gpiod::line::event_read_multiple (
    void ) const
```

Read multiple line events.

Returns

Vector of line event objects.

5.4.4.8 event_wait()

```
GPIOD_API bool gpiod::line::event_wait (
    const ::std::chrono::nanoseconds & timeout ) const
```

Wait for an event on this line.

Parameters

<i>timeout</i>	Time to wait before returning if no event occurred.
----------------	---

Returns

True if an event occurred and can be read, false if the wait timed out.

5.4.4.9 get_chip()

```
GPIOD_API const chip & gpiod::line::get_chip (  
    void ) const
```

Get the reference to the parent chip.

Returns

Reference to the parent chip object.

5.4.4.10 get_value()

```
GPIOD_API int gpiod::line::get_value (  
    void ) const
```

Read the line value.

Returns

Current value (0 or 1).

5.4.4.11 is_open_drain()

```
GPIOD_API bool gpiod::line::is_open_drain (  
    void ) const
```

Check if this line represents an open-drain GPIO.

Returns

True if the line is an open-drain GPIO, false otherwise.

5.4.4.12 is_open_source()

```
GPIOD_API bool gpiod::line::is_open_source (  
    void ) const
```

Check if this line represents an open-source GPIO.

Returns

True if the line is an open-source GPIO, false otherwise.

5.4.4.13 is_requested()

```
GPIOD_API bool gpiod::line::is_requested (  
    void ) const
```

Check if this user has ownership of this line.

Returns

True if the user has ownership of this line, false otherwise.

5.4.4.14 is_used()

```
GPIOD_API bool gpiod::line::is_used (  
    void ) const
```

Check if this line is used by the kernel or other user space process.

Returns

True if this line is in use, false otherwise.

5.4.4.15 name()

```
GPIOD_API::std::string gpiod::line::name (  
    void ) const
```

Get the name of this line (if any).

Returns

Name of this line or an empty string if it is unnamed.

5.4.4.16 offset()

```
GPIOD_API unsigned int gpiod::line::offset (  
    void ) const
```

Get the offset of this line.

Returns

Offset of this line.

5.4.4.17 operator bool()

```
GPIOD_API gpiod::line::operator bool (
    void ) const [explicit], [noexcept]
```

Check if this object holds a reference to any GPIO line.

Returns

True if this object references a GPIO line, false otherwise.

5.4.4.18 operator"!()

```
GPIOD_API bool gpiod::line::operator! (
    void ) const [noexcept]
```

Check if this object doesn't reference any GPIO line.

Returns

True if this object doesn't reference any GPIO line, true otherwise.

5.4.4.19 operator"!=(()

```
GPIOD_API bool gpiod::line::operator!= (
    const line & rhs ) const [noexcept]
```

Check if two line objects reference different GPIO lines.

Parameters

<i>rhs</i>	Right-hand side of the equation.
------------	----------------------------------

Returns

False if both objects reference the same line, true otherwise.

5.4.4.20 operator=() [1/2]

```
GPIOD_API line & gpiod::line::operator= (
    const line & other ) [default]
```

Assignment operator.

Parameters

<i>other</i>	Other line object.
--------------	--------------------

Returns

Reference to this object.

5.4.4.21 operator=() [2/2]

```
GPIO_API line & gpiod::line::operator= (
    line && other ) [default]
```

Move assignment operator.

Parameters

<i>other</i>	Other line object.
--------------	--------------------

Returns

Reference to this object.

5.4.4.22 operator==()

```
GPIO_API bool gpiod::line::operator== (
    const line & rhs ) const [noexcept]
```

Check if two line objects reference the same GPIO line.

Parameters

<i>rhs</i>	Right-hand side of the equation.
------------	----------------------------------

Returns

True if both objects reference the same line, false otherwise.

5.4.4.23 request()

```
GPIO_API void gpiod::line::request (
    const line_request & config,
    int default_val = 0 ) const
```

Request this line.

Parameters

<i>config</i>	Request config (see gpiod::line_request).
<i>default_val</i>	Default value - only matters for OUTPUT direction.

5.4.4.24 reset()

```
GPIOD_API void gpiod::line::reset (
    void )
```

Reset the state of this object.

This is useful when the user needs to e.g. keep the [line_event](#) object but wants to drop the reference to the GPIO chip indirectly held by the line being the source of the event.

5.4.4.25 set_config()

```
GPIOD_API void gpiod::line::set_config (
    int direction,
    ::std::bitset< 32 > flags,
    int value = 0 ) const
```

Set configuration of this line.

Parameters

<i>direction</i>	New direction.
<i>flags</i>	Replacement flags.
<i>value</i>	New value (0 or 1) - only matters for OUTPUT direction.

5.4.4.26 set_direction_output()

```
GPIOD_API void gpiod::line::set_direction_output (
    int value = 0 ) const
```

Change the direction this lines to output.

Parameters

<i>value</i>	New value (0 or 1).
--------------	---------------------

5.4.4.27 set_flags()

```
GPIOD_API void gpiod::line::set_flags (
    ::std::bitset< 32 > flags ) const
```

Set configuration flags of this line.

Parameters

<i>flags</i>	Replacement flags.
--------------	--------------------

5.4.4.28 set_value()

```
GPIOD_API void gpiod::line::set_value (
    int val ) const
```

Set the value of this line.

Parameters

<i>val</i>	New value (0 or 1).
------------	---------------------

The documentation for this class was generated from the following file:

- [gpiod.hpp](#)

5.5 gpiod::line_bulk Class Reference

Represents a set of GPIO lines.

```
#include <gpiod.hpp>
```

Classes

- class [iterator](#)
Iterator for iterating over lines held by [line_bulk](#).

Public Member Functions

- GPIOD_API [line_bulk](#) (void)=default
Default constructor. Creates an empty [line_bulk](#) object.
- GPIOD_API [line_bulk](#) (const ::std::vector< [line](#) > &lines)
Construct a [line_bulk](#) from a vector of lines.
- GPIOD_API [line_bulk](#) (const [line_bulk](#) &other)=default
Copy constructor.
- GPIOD_API [line_bulk](#) ([line_bulk](#) &&other)=default
Move constructor.
- GPIOD_API [line_bulk](#) & operator= (const [line_bulk](#) &other)=default
Assignment operator.
- GPIOD_API [line_bulk](#) & operator= ([line_bulk](#) &&other)=default
Move assignment operator.
- GPIOD_API ~[line_bulk](#) (void)=default
Destructor.
- GPIOD_API void [append](#) (const [line](#) &new_line)
Add a line to this [line_bulk](#) object.
- GPIOD_API [line](#) & [get](#) (unsigned int offset)
Get the line at given offset.
- GPIOD_API [line](#) & [operator\[\]](#) (unsigned int offset)
Get the line at given offset without bounds checking.

- GPIOD_API unsigned int **size** (void) const noexcept
Get the number of lines currently held by this object.
- GPIOD_API bool **empty** (void) const noexcept
*Check if this **line_bulk** doesn't hold any lines.*
- GPIOD_API void **clear** (void)
Remove all lines from this object.
- GPIOD_API void **request** (const **line_request** &config, const ::std::vector< int > default_vals=::std::vector< int >()) const
Request all lines held by this object.
- GPIOD_API void **release** (void) const
Release all lines held by this object.
- GPIOD_API ::std::vector< int > **get_values** (void) const
Read values from all lines held by this object.
- GPIOD_API void **set_values** (const ::std::vector< int > &values) const
Set values of all lines held by this object.
- GPIOD_API void **set_config** (int direction, ::std::bitset< 32 > flags, const ::std::vector< int > values=::std::vector< int >()) const
Set configuration of all lines held by this object.
- GPIOD_API void **set_flags** (::std::bitset< 32 > flags) const
Set configuration flags of all lines held by this object.
- GPIOD_API void **set_direction_input** () const
Change the direction all lines held by this object to input.
- GPIOD_API void **set_direction_output** (const ::std::vector< int > &values) const
Change the direction all lines held by this object to output.
- GPIOD_API **line_bulk event_wait** (const ::std::chrono::nanoseconds &timeout) const
Poll the set of lines for line events.
- GPIOD_API **operator bool** (void) const noexcept
Check if this object holds any lines.
- GPIOD_API **operator!** (void) const noexcept
Check if this object doesn't hold any lines.
- GPIOD_API **iterator begin** (void) noexcept
Returns an iterator to the first line.
- GPIOD_API **iterator end** (void) noexcept
Returns an iterator to the element following the last line.

Static Public Attributes

- static GPIOD_API const unsigned int **MAX_LINES**
Max number of lines that this object can hold.

5.5.1 Detailed Description

Represents a set of GPIO lines.

Internally an object of this class stores an array of line objects owned by a single chip.

5.5.2 Constructor & Destructor Documentation

5.5.2.1 **line_bulk()** [1/3]

```
GPIOD_API gpiod::line_bulk::line_bulk (
    const ::std::vector< line > & lines )
```

Construct a **line_bulk** from a vector of lines.

Parameters

<i>lines</i>	Vector of gpiod::line objects.
--------------	--

Note

All lines must be owned by the same GPIO chip.

5.5.2.2 `line_bulk()` [2/3]

```
GPIOD_API gpiod::line_bulk::line_bulk (  
    const line\_bulk & other ) [default]
```

Copy constructor.

Parameters

<i>other</i>	Other line_bulk object.
--------------	---

5.5.2.3 `line_bulk()` [3/3]

```
GPIOD_API gpiod::line_bulk::line_bulk (  
    line\_bulk && other ) [default]
```

Move constructor.

Parameters

<i>other</i>	Other line_bulk object.
--------------	---

5.5.3 Member Function Documentation

5.5.3.1 `append()`

```
GPIOD_API void gpiod::line_bulk::append (  
    const line & new_line )
```

Add a line to this [line_bulk](#) object.

Parameters

<i>new_line</i>	Line to add.
-----------------	--------------

Note

The new line must be owned by the same chip as all the other lines already held by this [line_bulk](#) object.

5.5.3.2 begin()

```
GPIOD_API iterator gpiod::line_bulk::begin (  
    void ) [noexcept]
```

Returns an iterator to the first line.

Returns

A [line_bulk](#) iterator.

5.5.3.3 empty()

```
GPIOD_API bool gpiod::line_bulk::empty (  
    void ) const [noexcept]
```

Check if this [line_bulk](#) doesn't hold any lines.

Returns

True if this object is empty, false otherwise.

5.5.3.4 end()

```
GPIOD_API iterator gpiod::line_bulk::end (  
    void ) [noexcept]
```

Returns an iterator to the element following the last line.

Returns

A [line_bulk](#) iterator.

5.5.3.5 event_wait()

```
GPIOD_API line_bulk gpiod::line_bulk::event_wait (  
    const ::std::chrono::nanoseconds & timeout ) const
```

Poll the set of lines for line events.

Parameters

<i>timeout</i>	Number of nanoseconds to wait before returning an empty line_bulk .
----------------	---

Returns

Returns a [line_bulk](#) object containing lines on which events occurred.

5.5.3.6 get()

```
GPIO_API line & gpiod::line_bulk::get (
    unsigned int offset )
```

Get the line at given offset.

Parameters

<i>offset</i>	Offset of the line to get.
---------------	----------------------------

Returns

Reference to the line object.

5.5.3.7 get_values()

```
GPIO_API ::std::vector< int > gpiod::line_bulk::get_values (
    void ) const
```

Read values from all lines held by this object.

Returns

Vector containing line values the order of which corresponds with the order of lines in the internal array.

5.5.3.8 operator bool()

```
GPIO_API gpiod::line_bulk::operator bool (
    void ) const [explicit], [noexcept]
```

Check if this object holds any lines.

Returns

True if this [line_bulk](#) holds at least one line, false otherwise.

5.5.3.9 operator"!()

```
GPIO_API bool gpiod::line_bulk::operator! (
    void ) const [noexcept]
```

Check if this object doesn't hold any lines.

Returns

True if this [line_bulk](#) is empty, false otherwise.

5.5.3.10 operator=() [1/2]

```
GPIOD_API line_bulk & gpiod::line_bulk::operator= (  
    const line_bulk & other ) [default]
```

Assignment operator.

Parameters

<i>other</i>	Other line_bulk object.
--------------	---

Returns

Reference to this object.

5.5.3.11 operator=() [2/2]

```
GPIO_API line\_bulk & gpiod::line_bulk::operator= (
    line\_bulk && other ) [default]
```

Move assignment operator.

Parameters

<i>other</i>	Other line_bulk object.
--------------	---

Returns

Reference to this object.

5.5.3.12 operator[]()

```
GPIO_API line & gpiod::line_bulk::operator[] (
    unsigned int offset )
```

Get the line at given offset without bounds checking.

Parameters

<i>offset</i>	Offset of the line to get.
---------------	----------------------------

Returns

Reference to the line object.

Note

No bounds checking is performed.

5.5.3.13 request()

```
GPIO_API void gpiod::line_bulk::request (
    const line\_request & config,
    const ::std::vector< int > default_vals = ::std::vector< int >() ) const
```

Request all lines held by this object.

Parameters

<i>config</i>	Request config (see gpiod::line_request).
<i>default_vals</i>	Vector of default values. Only relevant for output direction requests.

5.5.3.14 set_config()

```

GPIOD_API void gpiod::line_bulk::set_config (
    int direction,
    ::std::bitset< 32 > flags,
    const ::std::vector< int > values = ::std::vector< int >() ) const

```

Set configuration of all lines held by this object.

Parameters

<i>direction</i>	New direction.
<i>flags</i>	Replacement flags.
<i>values</i>	Vector of values to set. Must be the same size as the number of lines held by this line_bulk . Only relevant for output direction requests.

5.5.3.15 set_direction_output()

```

GPIOD_API void gpiod::line_bulk::set_direction_output (
    const ::std::vector< int > & values ) const

```

Change the direction all lines held by this object to output.

Parameters

<i>values</i>	Vector of values to set. Must be the same size as the number of lines held by this line_bulk .
---------------	--

5.5.3.16 set_flags()

```

GPIOD_API void gpiod::line_bulk::set_flags (
    ::std::bitset< 32 > flags ) const

```

Set configuration flags of all lines held by this object.

Parameters

<i>flags</i>	Replacement flags.
--------------	--------------------

5.5.3.17 set_values()

```

GPIOD_API void gpiod::line_bulk::set_values (

```

```
const ::std::vector< int > & values ) const
```

Set values of all lines held by this object.

Parameters

<i>values</i>	Vector of values to set. Must be the same size as the number of lines held by this line_bulk .
---------------	--

5.5.3.18 size()

```
GPIOD_API unsigned int gpiod::line_bulk::size (
    void ) const [noexcept]
```

Get the number of lines currently held by this object.

Returns

Number of elements in this [line_bulk](#).

The documentation for this class was generated from the following file:


- [gpiod.hpp](#)

5.6 gpiod::line_event Struct Reference

Describes a single GPIO line event.

```
#include <gpiod.hpp>
```

Collaboration diagram for gpiod::line_event:



Public Types

- enum : int { [RISING_EDGE](#) = 1 , [FALLING_EDGE](#) }
- Possible event types.*

Public Attributes

- `::std::chrono::nanoseconds` [timestamp](#)
- `int` [event_type](#)
- `line` [source](#)

5.6.1 Detailed Description

Describes a single GPIO line event.

5.6.2 Member Enumeration Documentation

5.6.2.1 anonymous enum

```
anonymous enum : int
```

Possible event types.

Enumerator

RISING_EDGE	Rising edge event.
FALLING_EDGE	Falling edge event.

5.6.3 Member Data Documentation

5.6.3.1 event_type

```
int gpiod::line_event::event_type
```

Type of the event that occurred.

5.6.3.2 source

```
line gpiod::line_event::source
```

Line object referencing the GPIO line on which the event occurred.

5.6.3.3 timestamp

```
::std::chrono::nanoseconds gpiod::line_event::timestamp
```

Best estimate of time of event occurrence in nanoseconds.

The documentation for this struct was generated from the following file:

- [gpiod.hpp](#)

5.7 gpiod::line_iter Class Reference

Allows to iterate over all lines owned by a GPIO chip.

```
#include <gpiod.hpp>
```

Public Member Functions

- `GPIOD_API line_iter (void)=default`
Default constructor. Creates the end iterator.
- `GPIOD_API line_iter (const chip &owner)`
Constructor. Creates the begin iterator.
- `GPIOD_API line_iter (const line_iter &other)=default`
Copy constructor.
- `GPIOD_API line_iter (line_iter &&other)=default`
Move constructor.
- `GPIOD_API line_iter & operator= (const line_iter &other)=default`
Assignment operator.
- `GPIOD_API line_iter & operator= (line_iter &&other)=default`
Move assignment operator.
- `GPIOD_API ~line_iter (void)=default`
Destructor.
- `GPIOD_API line_iter & operator++ (void)`
Advance the iterator by one element.
- `GPIOD_API const line & operator* (void) const`
Dereference current element.
- `GPIOD_API const line * operator-> (void) const`
Member access operator.
- `GPIOD_API bool operator== (const line_iter &rhs) const noexcept`
Check if this operator points to the same element.
- `GPIOD_API bool operator!= (const line_iter &rhs) const noexcept`
Check if this operator doesn't point to the same element.

5.7.1 Detailed Description

Allows to iterate over all lines owned by a GPIO chip.

5.7.2 Constructor & Destructor Documentation

5.7.2.1 line_iter() [1/3]

```
GPIOD_API gpiod::line_iter::line_iter (
    const chip & owner )
```

Constructor. Creates the begin iterator.

Parameters

<i>owner</i>	Chip owning the GPIO lines over which we want to iterate.
--------------	---

5.7.2.2 line_iter() [2/3]

```
GPIOD_API gpiod::line_iter::line_iter (
    const line_iter & other ) [default]
```

Copy constructor.

Parameters

<i>other</i>	Other line iterator.
--------------	----------------------

5.7.2.3 line_iter() [3/3]

```
GPIOD_API gpiod::line_iter::line_iter (
    line_iter && other ) [default]
```

Move constructor.

Parameters

<i>other</i>	Other line iterator.
--------------	----------------------

5.7.3 Member Function Documentation

5.7.3.1 operator!=(())

```
GPIOD_API bool gpiod::line_iter::operator!=(
    const line_iter & rhs ) const [noexcept]
```

Check if this operator doesn't point to the same element.

Parameters

<i>rhs</i>	Right-hand side of the equation.
------------	----------------------------------

Returns

True if this iterator doesn't point to the same [line_iter](#), false otherwise.

5.7.3.2 operator*()

```
GPIOD_API const line & gpiod::line_iter::operator* (
```

```
void ) const
```

Dereference current element.

Returns

Current GPIO line by reference.

5.7.3.3 operator++()

```
GPIOD_API line_iter & gpiod::line_iter::operator++ (
    void )
```

Advance the iterator by one element.

Returns

Reference to this iterator.

5.7.3.4 operator->()

```
GPIOD_API const line * gpiod::line_iter::operator-> (
    void ) const
```

Member access operator.

Returns

Current GPIO line by pointer.

5.7.3.5 operator=() [1/2]

```
GPIOD_API line_iter & gpiod::line_iter::operator= (
    const line_iter & other ) [default]
```

Assignment operator.

Parameters

<i>other</i>	Other line iterator.
--------------	----------------------

Returns

Reference to this [line_iter](#).

5.7.3.6 operator=() [2/2]

```
GPIOD_API line_iter & gpiod::line_iter::operator= (
```



```
line_iter && other ) [default]
```

Move assignment operator.

Parameters

<i>other</i>	Other line iterator.
--------------	----------------------

Returns

Reference to this [line_iter](#).

5.7.3.7 operator==()

```
GPIOD_API bool gpiod::line_iter::operator== (
    const line_iter & rhs ) const [noexcept]
```

Check if this operator points to the same element.

Parameters

<i>rhs</i>	Right-hand side of the equation.
------------	----------------------------------

Returns

True if this iterator points to the same [line_iter](#), false otherwise.

The documentation for this class was generated from the following file:

- [gpiod.hpp](#)

5.8 gpiod::line_request Struct Reference

Stores the configuration for line requests.

```
#include <gpiod.hpp>
```

Public Types

- enum : int {
[DIRECTION_AS_IS](#) = 1 , [DIRECTION_INPUT](#) , [DIRECTION_OUTPUT](#) , [EVENT_FALLING_EDGE](#) ,
[EVENT_RISING_EDGE](#) , [EVENT_BOTH_EDGES](#) }
Request types.

Public Attributes

- ::std::string [consumer](#)
- int [request_type](#)
- ::std::bitset< 32 > [flags](#)

Static Public Attributes

- static GPIOD_API const ::std::bitset< 32 > [FLAG_ACTIVE_LOW](#)
- static GPIOD_API const ::std::bitset< 32 > [FLAG_OPEN_SOURCE](#)
- static GPIOD_API const ::std::bitset< 32 > [FLAG_OPEN_DRAIN](#)
- static GPIOD_API const ::std::bitset< 32 > [FLAG_BIAS_DISABLE](#)
- static GPIOD_API const ::std::bitset< 32 > [FLAG_BIAS_PULL_DOWN](#)
- static GPIOD_API const ::std::bitset< 32 > [FLAG_BIAS_PULL_UP](#)

5.8.1 Detailed Description

Stores the configuration for line requests.

5.8.2 Member Enumeration Documentation

5.8.2.1 anonymous enum

```
anonymous enum : int
```

Request types.

Enumerator

DIRECTION_AS_IS	Request for values, don't change the direction.
DIRECTION_INPUT	Request for reading line values.
DIRECTION_OUTPUT	Request for driving the GPIO lines.
EVENT_FALLING_EDGE	Listen for falling edge events.
EVENT_RISING_EDGE	Listen for rising edge events.
EVENT_BOTH_EDGES	Listen for all types of events.

5.8.3 Member Data Documentation

5.8.3.1 consumer

```
::std::string gpiod::line_request::consumer
```

Consumer name to pass to the request.

5.8.3.2 FLAG_ACTIVE_LOW

```
GPIOD_API const ::std::bitset<32> gpiod::line_request::FLAG_ACTIVE_LOW [static]
```

Set the active state to 'low' (high is the default).

5.8.3.3 FLAG_BIAS_DISABLE

```
GPIOD_API const ::std::bitset<32> gpiod::line_request::FLAG_BIAS_DISABLE [static]
```

The line has neither pull-up nor pull-down resistor enabled.

5.8.3.4 FLAG_BIAS_PULL_DOWN

```
GPIOD_API const ::std::bitset<32> gpiod::line_request::FLAG_BIAS_PULL_DOWN [static]
```

The line has a configurable pull-down resistor enabled.

5.8.3.5 FLAG_BIAS_PULL_UP

```
GPIOD_API const ::std::bitset<32> gpiod::line_request::FLAG_BIAS_PULL_UP [static]
```

The line has a configurable pull-up resistor enabled.

5.8.3.6 FLAG_OPEN_DRAIN

```
GPIOD_API const ::std::bitset<32> gpiod::line_request::FLAG_OPEN_DRAIN [static]
```

The line is an open-drain port.

5.8.3.7 FLAG_OPEN_SOURCE

```
GPIOD_API const ::std::bitset<32> gpiod::line_request::FLAG_OPEN_SOURCE [static]
```

The line is an open-source port.

5.8.3.8 flags

```
::std::bitset<32> gpiod::line_request::flags
```

Additional request flags.

5.8.3.9 request_type

```
int gpiod::line_request::request_type
```

Type of the request.

The documentation for this struct was generated from the following file:

- [gpiod.hpp](#)


Chapter 6

File Documentation

6.1 gpiod.hpp File Reference

```
#include <bitset>
#include <chrono>
#include <gpiod.h>
#include <memory>
#include <string>
#include <vector>
```

Include dependency graph for gpiod.hpp:



Classes

- class [gpiod::chip](#)
Represents a GPIO chip.
- struct [gpiod::line_request](#)
Stores the configuration for line requests.
- class [gpiod::line](#)
Represents a single GPIO line.
- struct [gpiod::line_event](#)
Describes a single GPIO line event.
- class [gpiod::line_bulk](#)
Represents a set of GPIO lines.
- class [gpiod::line_bulk::iterator](#)
Iterator for iterating over lines held by [line_bulk](#).
- class [gpiod::chip_iter](#)
Allows to iterate over all GPIO chips present on the system.
- class [gpiod::line_iter](#)
Allows to iterate over all lines owned by a GPIO chip.

Functions

- GPIOD_API `line` `gpiod::find_line` (const ::std::string &name)
Find a GPIO line by name. Search all GPIO chips present on the system.
- GPIOD_API `chip_iter` `gpiod::make_chip_iter` (void)
Create a new `chip_iter`.
- GPIOD_API `chip_iter` `gpiod::begin` (`chip_iter` iter) noexcept
Support for range-based loops for chip iterators.
- GPIOD_API `chip_iter` `gpiod::end` (const `chip_iter` &iter) noexcept
Support for range-based loops for chip iterators.
- GPIOD_API `line_iter` `gpiod::begin` (`line_iter` iter) noexcept
Support for range-based loops for line iterators.
- GPIOD_API `line_iter` `gpiod::end` (const `line_iter` &iter) noexcept
Support for range-based loops for line iterators.

6.2 gpiod.hpp

[Go to the documentation of this file.](#)

```

00001 /* SPDX-License-Identifier: LGPL-2.1-or-later */
00002 /*
00003  * This file is part of libgpiod.
00004  *
00005  * Copyright (C) 2017-2018 Bartosz Golaszewski <bartekgola@gmail.com>
00006  */
00007
00008 #ifndef __LIBGPIOD_GPIOD_CXX_HPP__
00009 #define __LIBGPIOD_GPIOD_CXX_HPP__
00010
00011 #include <bitset>
00012 #include <chrono>
00013 #include <gpiod.h>
00014 #include <memory>
00015 #include <string>
00016 #include <vector>
00017
00018 namespace gpiod {
00019
00020 class line;
00021 class line_bulk;
00022 class line_iter;
00023 class chip_iter;
00024 struct line_event;
00025
00042 class chip
00043 {
00044 public:
00045
00049     GPIOD_API chip(void) = default;
00050
00056     GPIOD_API chip(const ::std::string& device, int how = OPEN_LOOKUP);
00057
00062     GPIOD_API chip(const chip& other) = default;
00063
00068     GPIOD_API chip(chip&& other) = default;
00069
00075     GPIOD_API chip& operator=(const chip& other) = default;
00076
00082     GPIOD_API chip& operator=(chip&& other) = default;
00083
00087     GPIOD_API ~chip(void) = default;
00088
00097     GPIOD_API void open(const ::std::string &device, int how = OPEN_LOOKUP);
00098
00102     GPIOD_API void reset(void) noexcept;
00103
00108     GPIOD_API ::std::string name(void) const;
00109
00114     GPIOD_API ::std::string label(void) const;
00115
00120     GPIOD_API unsigned int num_lines(void) const;
00121
00127     GPIOD_API line get_line(unsigned int offset) const;

```

```

00128
00134     GPIOD_API line find_line(const ::std::string& name) const;
00135
00141     GPIOD_API line_bulk get_lines(const ::std::vector<unsigned int>& offsets) const;
00142
00147     GPIOD_API line_bulk get_all_lines(void) const;
00148
00154     GPIOD_API line_bulk find_lines(const ::std::vector<::std::string>& names) const;
00155
00161     GPIOD_API bool operator==(const chip& rhs) const noexcept;
00162
00168     GPIOD_API bool operator!=(const chip& rhs) const noexcept;
00169
00174     GPIOD_API explicit operator bool(void) const noexcept;
00175
00180     GPIOD_API bool operator!(void) const noexcept;
00181
00186     enum : int {
00187         OPEN_LOOKUP = 1,
00189         OPEN_BY_PATH,
00191         OPEN_BY_NAME,
00193         OPEN_BY_LABEL,
00195         OPEN_BY_NUMBER,
00197     };
00198
00199 private:
00200
00201     chip(::gpiod_chip* chip);
00202
00203     void throw_if_noref(void) const;
00204
00205     ::std::shared_ptr<::gpiod_chip> _m_chip;
00206
00207     friend chip_iter;
00208     friend line_iter;
00209 };
00210
00214 struct line_request
00215 {
00219     enum : int {
00220         DIRECTION_AS_IS = 1,
00222         DIRECTION_INPUT,
00224         DIRECTION_OUTPUT,
00226         EVENT_FALLING_EDGE,
00228         EVENT_RISING_EDGE,
00230         EVENT_BOTH_EDGES,
00232     };
00233
00234     GPIOD_API static const ::std::bitset<32> FLAG_ACTIVE_LOW;
00236     GPIOD_API static const ::std::bitset<32> FLAG_OPEN_SOURCE;
00238     GPIOD_API static const ::std::bitset<32> FLAG_OPEN_DRAIN;
00240     GPIOD_API static const ::std::bitset<32> FLAG_BIAS_DISABLE;
00242     GPIOD_API static const ::std::bitset<32> FLAG_BIAS_PULL_DOWN;
00244     GPIOD_API static const ::std::bitset<32> FLAG_BIAS_PULL_UP;
00247     ::std::string consumer;
00249     int request_type;
00251     ::std::bitset<32> flags;
00253 };
00254
00262 class line
00263 {
00264 public:
00265
00269     GPIOD_API line(void);
00270
00275     GPIOD_API line(const line& other) = default;
00276
00281     GPIOD_API line(line&& other) = default;
00282
00288     GPIOD_API line& operator=(const line& other) = default;
00289
00295     GPIOD_API line& operator=(line&& other) = default;
00296
00300     GPIOD_API ~line(void) = default;
00301
00306     GPIOD_API unsigned int offset(void) const;
00307
00312     GPIOD_API ::std::string name(void) const;
00313
00319     GPIOD_API ::std::string consumer(void) const;
00320
00325     GPIOD_API int direction(void) const;
00326
00331     GPIOD_API int active_state(void) const;
00332
00337     GPIOD_API int bias(void) const;
00338

```

```

00344     GPIOD_API bool is_used(void) const;
00345
00350     GPIOD_API bool is_open_drain(void) const;
00351
00356     GPIOD_API bool is_open_source(void) const;
00357
00363     GPIOD_API void request(const line_request& config, int default_val = 0) const;
00364
00368     GPIOD_API void release(void) const;
00369
00374     GPIOD_API bool is_requested(void) const;
00375
00380     GPIOD_API int get_value(void) const;
00381
00386     GPIOD_API void set_value(int val) const;
00387
00394     GPIOD_API void set_config(int direction, ::std::bitset<32> flags,
00395                               int value = 0) const;
00396
00401     GPIOD_API void set_flags(::std::bitset<32> flags) const;
00402
00406     GPIOD_API void set_direction_input() const;
00407
00412     GPIOD_API void set_direction_output(int value = 0) const;
00413
00420     GPIOD_API bool event_wait(const ::std::chrono::nanoseconds& timeout) const;
00421
00426     GPIOD_API line_event event_read(void) const;
00427
00432     GPIOD_API ::std::vector<line_event> event_read_multiple(void) const;
00433
00438     GPIOD_API int event_get_fd(void) const;
00439
00444     GPIOD_API const chip& get_chip(void) const;
00445
00449     GPIOD_API void update(void) const;
00450
00458     GPIOD_API void reset(void);
00459
00465     GPIOD_API bool operator==(const line& rhs) const noexcept;
00466
00472     GPIOD_API bool operator!=(const line& rhs) const noexcept;
00473
00478     GPIOD_API explicit operator bool(void) const noexcept;
00479
00485     GPIOD_API bool operator!(void) const noexcept;
00486
00490     enum : int {
00491         DIRECTION_INPUT = 1,
00493         DIRECTION_OUTPUT,
00495     };
00496
00500     enum : int {
00501         ACTIVE_LOW = 1,
00503         ACTIVE_HIGH,
00505     };
00506
00510     enum : int {
00511         BIAS_AS_IS = 1,
00513         BIAS_DISABLE,
00515         BIAS_PULL_UP,
00517         BIAS_PULL_DOWN,
00519     };
00520
00521 private:
00522
00523     line(::gpiod_line* line, const chip& owner);
00524
00525     void throw_if_null(void) const;
00526     line_event make_line_event(const ::gpiod_line_event& event) const noexcept;
00527
00528     ::gpiod_line* _m_line;
00529     chip _m_chip;
00530
00531     friend chip;
00532     friend line_bulk;
00533     friend line_iter;
00534 };
00535
00541 GPIOD_API line find_line(const ::std::string& name);
00542
00546 struct line_event
00547 {
00551     enum : int {
00552         RISING_EDGE = 1,
00554         FALLING_EDGE,
00556     };

```



```

00557
00558     ::std::chrono::nanoseconds timestamp;
00560     int event_type;
00562     line source;
00564 };
00565
00572 class line_bulk
00573 {
00574 public:
00575
00579     GPIOD_API line_bulk(void) = default;
00580
00586     GPIOD_API line_bulk(const ::std::vector<line>& lines);
00587
00592     GPIOD_API line_bulk(const line_bulk& other) = default;
00593
00598     GPIOD_API line_bulk(line_bulk&& other) = default;
00599
00605     GPIOD_API line_bulk& operator=(const line_bulk& other) = default;
00606
00612     GPIOD_API line_bulk& operator=(line_bulk&& other) = default;
00613
00617     GPIOD_API ~line_bulk(void) = default;
00618
00625     GPIOD_API void append(const line& new_line);
00626
00632     GPIOD_API line& get(unsigned int offset);
00633
00640     GPIOD_API line& operator[](unsigned int offset);
00641
00646     GPIOD_API unsigned int size(void) const noexcept;
00647
00652     GPIOD_API bool empty(void) const noexcept;
00653
00657     GPIOD_API void clear(void);
00658
00665     GPIOD_API void request(const line_request& config,
00666                           const ::std::vector<int> default_vals = ::std::vector<int>()) const;
00667
00671     GPIOD_API void release(void) const;
00672
00678     GPIOD_API ::std::vector<int> get_values(void) const;
00679
00685     GPIOD_API void set_values(const ::std::vector<int>& values) const;
00686
00695     GPIOD_API void set_config(int direction, ::std::bitset<32> flags,
00696                               const ::std::vector<int> values = ::std::vector<int>()) const;
00697
00702     GPIOD_API void set_flags(::std::bitset<32> flags) const;
00703
00707     GPIOD_API void set_direction_input() const;
00708
00714     GPIOD_API void set_direction_output(const ::std::vector<int>& values) const;
00715
00723     GPIOD_API line_bulk event_wait(const ::std::chrono::nanoseconds& timeout) const;
00724
00729     GPIOD_API explicit operator bool(void) const noexcept;
00730
00735     GPIOD_API bool operator!(void) const noexcept;
00736
00740     GPIOD_API static const unsigned int MAX_LINES;
00741
00745     class iterator
00746     {
00747     public:
00748
00752         GPIOD_API iterator(void) = default;
00753
00758         GPIOD_API iterator(const iterator& other) = default;
00759
00764         GPIOD_API iterator(iterator&& other) = default;
00765
00771         GPIOD_API iterator& operator=(const iterator& other) = default;
00772
00778         GPIOD_API iterator& operator=(iterator&& other) = default;
00779
00783         GPIOD_API ~iterator(void) = default;
00784
00789         GPIOD_API iterator& operator++(void);
00790
00795         GPIOD_API const line& operator*(void) const;
00796
00801         GPIOD_API const line* operator->(void) const;
00802
00809         GPIOD_API bool operator==(const iterator& rhs) const noexcept;
00810
00817         GPIOD_API bool operator!=(const iterator& rhs) const noexcept;

```

```

00818
00819     private:
00820
00821         iterator(const ::std::vector<line>::iterator& it);
00822
00823         ::std::vector<line>::iterator _m_iter;
00824
00825         friend line_bulk;
00826     };
00827
00832     GPIOD_API iterator begin(void) noexcept;
00833
00838     GPIOD_API iterator end(void) noexcept;
00839
00840 private:
00841
00842     void throw_if_empty(void) const;
00843     void to_line_bulk(::gpiod_line_bulk* bulk) const;
00844
00845     ::std::vector<line> _m_bulk;
00846 };
00847
00854 GPIOD_API chip_iter make_chip_iter(void);
00855
00861 GPIOD_API chip_iter begin(chip_iter iter) noexcept;
00862
00868 GPIOD_API chip_iter end(const chip_iter& iter) noexcept;
00869
00873 class chip_iter
00874 {
00875 public:
00876
00880     GPIOD_API chip_iter(void) = default;
00881
00886     GPIOD_API chip_iter(const chip_iter& other) = default;
00887
00892     GPIOD_API chip_iter(chip_iter&& other) = default;
00893
00899     GPIOD_API chip_iter& operator=(const chip_iter& other) = default;
00900
00906     GPIOD_API chip_iter& operator=(chip_iter&& other) = default;
00907
00911     GPIOD_API ~chip_iter(void) = default;
00912
00917     GPIOD_API chip_iter& operator++(void);
00918
00923     GPIOD_API const chip& operator*(void) const;
00924
00929     GPIOD_API const chip* operator->(void) const;
00930
00937     GPIOD_API bool operator==(const chip_iter& rhs) const noexcept;
00938
00945     GPIOD_API bool operator!=(const chip_iter& rhs) const noexcept;
00946
00947 private:
00948
00949     chip_iter(::gpiod_chip_iter* iter);
00950
00951     ::std::shared_ptr<::gpiod_chip_iter> _m_iter;
00952     chip _m_current;
00953
00954     friend chip_iter make_chip_iter(void);
00955 };
00956
00962 GPIOD_API line_iter begin(line_iter iter) noexcept;
00963
00969 GPIOD_API line_iter end(const line_iter& iter) noexcept;
00970
00974 class line_iter
00975 {
00976 public:
00977
00981     GPIOD_API line_iter(void) = default;
00982
00987     GPIOD_API line_iter(const chip& owner);
00988
00993     GPIOD_API line_iter(const line_iter& other) = default;
00994
00999     GPIOD_API line_iter(line_iter&& other) = default;
01000
01006     GPIOD_API line_iter& operator=(const line_iter& other) = default;
01007
01013     GPIOD_API line_iter& operator=(line_iter&& other) = default;
01014
01018     GPIOD_API ~line_iter(void) = default;
01019
01024     GPIOD_API line_iter& operator++(void);

```

```
01025
01030     GPIOD_API const line& operator*(void) const;
01031
01036     GPIOD_API const line* operator->(void) const;
01037
01044     GPIOD_API bool operator==(const line_iter& rhs) const noexcept;
01045
01052     GPIOD_API bool operator!=(const line_iter& rhs) const noexcept;
01053
01054 private:
01055
01056     ::std::shared_ptr<::gpiod_line_iter> _m_iter;
01057     line _m_current;
01058 };
01059
01064 } /* namespace gpiod */
01065
01066 #endif /* __LIBGPIOD_GPIOD_CXX_HPP__ */
```


Index

- ACTIVE_HIGH
 - gpiod::line, 28
- ACTIVE_LOW
 - gpiod::line, 28
- active_state
 - gpiod::line, 29
- append
 - gpiod::line_bulk, 38
- begin
 - C++ bindings, 8
 - gpiod::line_bulk, 39
- bias
 - gpiod::line, 29
- BIAS_AS_IS
 - gpiod::line, 28
- BIAS_DISABLE
 - gpiod::line, 28
- BIAS_PULL_DOWN
 - gpiod::line, 28
- BIAS_PULL_UP
 - gpiod::line, 28
- C++ bindings, 7
 - begin, 8
 - end, 8, 9
 - find_line, 9
 - make_chip_iter, 9
- chip
 - gpiod::chip, 13
- chip_iter
 - gpiod::chip_iter, 19, 20
- consumer
 - gpiod::line, 29
 - gpiod::line_request, 50
- direction
 - gpiod::line, 30
- DIRECTION_AS_IS
 - gpiod::line_request, 50
- DIRECTION_INPUT
 - gpiod::line, 28
 - gpiod::line_request, 50
- DIRECTION_OUTPUT
 - gpiod::line, 28
 - gpiod::line_request, 50
- empty
 - gpiod::line_bulk, 39
- end
 - C++ bindings, 8, 9
 - gpiod::line_bulk, 39
- EVENT_BOTH_EDGES
 - gpiod::line_request, 50
- EVENT_FALLING_EDGE
 - gpiod::line_request, 50
- event_get_fd
 - gpiod::line, 30
- event_read
 - gpiod::line, 30
- event_read_multiple
 - gpiod::line, 30
- EVENT_RISING_EDGE
 - gpiod::line_request, 50
- event_type
 - gpiod::line_event, 45
- event_wait
 - gpiod::line, 30
 - gpiod::line_bulk, 39
- FALLING_EDGE
 - gpiod::line_event, 45
- find_line
 - C++ bindings, 9
 - gpiod::chip, 13
- find_lines
 - gpiod::chip, 14
- FLAG_ACTIVE_LOW
 - gpiod::line_request, 50
- FLAG_BIAS_DISABLE
 - gpiod::line_request, 50
- FLAG_BIAS_PULL_DOWN
 - gpiod::line_request, 51
- FLAG_BIAS_PULL_UP
 - gpiod::line_request, 51
- FLAG_OPEN_DRAIN
 - gpiod::line_request, 51
- FLAG_OPEN_SOURCE
 - gpiod::line_request, 51
- flags
 - gpiod::line_request, 51
- get
 - gpiod::line_bulk, 40
- get_all_lines
 - gpiod::chip, 14
- get_chip
 - gpiod::line, 31
- get_line
 - gpiod::chip, 14

- get_lines
 - gpiod::chip, 15
- get_value
 - gpiod::line, 31
- get_values
 - gpiod::line_bulk, 40
- gpiod.hpp, 53
- gpiod::chip, 11
 - chip, 13
 - find_line, 13
 - find_lines, 14
 - get_all_lines, 14
 - get_line, 14
 - get_lines, 15
 - label, 15
 - name, 15
 - num_lines, 15
 - open, 15
 - OPEN_BY_LABEL, 12
 - OPEN_BY_NAME, 12
 - OPEN_BY_NUMBER, 12
 - OPEN_BY_PATH, 12
 - OPEN_LOOKUP, 12
 - operator bool, 16
 - operator!, 16
 - operator!=, 16
 - operator=, 17
 - operator==, 17
- gpiod::chip_iter, 18
 - chip_iter, 19, 20
 - make_chip_iter, 22
 - operator!=, 20
 - operator++, 20
 - operator->, 21
 - operator=, 21
 - operator==, 22
 - operator*, 20
- gpiod::line, 26
 - ACTIVE_HIGH, 28
 - ACTIVE_LOW, 28
 - active_state, 29
 - bias, 29
 - BIAS_AS_IS, 28
 - BIAS_DISABLE, 28
 - BIAS_PULL_DOWN, 28
 - BIAS_PULL_UP, 28
 - consumer, 29
 - direction, 30
 - DIRECTION_INPUT, 28
 - DIRECTION_OUTPUT, 28
 - event_get_fd, 30
 - event_read, 30
 - event_read_multiple, 30
 - event_wait, 30
 - get_chip, 31
 - get_value, 31
 - is_open_drain, 31
 - is_open_source, 31
 - is_requested, 31
 - is_used, 32
 - line, 29
 - name, 32
 - offset, 32
 - operator bool, 32
 - operator!, 33
 - operator!=, 33
 - operator=, 33, 34
 - operator==, 34
 - request, 34
 - reset, 34
 - set_config, 35
 - set_direction_output, 35
 - set_flags, 35
 - set_value, 35
- gpiod::line_bulk, 36
 - append, 38
 - begin, 39
 - empty, 39
 - end, 39
 - event_wait, 39
 - get, 40
 - get_values, 40
 - line_bulk, 37, 38
 - operator bool, 40
 - operator!, 40
 - operator=, 40, 42
 - operator[], 42
 - request, 42
 - set_config, 43
 - set_direction_output, 43
 - set_flags, 43
 - set_values, 43
 - size, 44
- gpiod::line_bulk::iterator, 22
 - iterator, 23
 - operator!=, 24
 - operator++, 24
 - operator->, 24
 - operator=, 25
 - operator==, 25
 - operator*, 24
- gpiod::line_event, 44
 - event_type, 45
 - FALLING_EDGE, 45
 - RISING_EDGE, 45
 - source, 45
 - timestamp, 45
- gpiod::line_iter, 46
 - line_iter, 46, 47
 - operator!=, 47
 - operator++, 48
 - operator->, 48
 - operator=, 48
 - operator==, 49
 - operator*, 47
- gpiod::line_request, 49

- consumer, [50](#)
- DIRECTION_AS_IS, [50](#)
- DIRECTION_INPUT, [50](#)
- DIRECTION_OUTPUT, [50](#)
- EVENT_BOTH_EDGES, [50](#)
- EVENT_FALLING_EDGE, [50](#)
- EVENT_RISING_EDGE, [50](#)
- FLAG_ACTIVE_LOW, [50](#)
- FLAG_BIAS_DISABLE, [50](#)
- FLAG_BIAS_PULL_DOWN, [51](#)
- FLAG_BIAS_PULL_UP, [51](#)
- FLAG_OPEN_DRAIN, [51](#)
- FLAG_OPEN_SOURCE, [51](#)
- flags, [51](#)
- request_type, [51](#)

is_open_drain

- gpiod::line, [31](#)

is_open_source

- gpiod::line, [31](#)

is_requested

- gpiod::line, [31](#)

is_used

- gpiod::line, [32](#)

iterator

- gpiod::line_bulk::iterator, [23](#)

label

- gpiod::chip, [15](#)

line

- gpiod::line, [29](#)

line_bulk

- gpiod::line_bulk, [37](#), [38](#)

line_iter

- gpiod::line_iter, [46](#), [47](#)

make_chip_iter

- C++ bindings, [9](#)
- gpiod::chip_iter, [22](#)

name

- gpiod::chip, [15](#)
- gpiod::line, [32](#)

num_lines

- gpiod::chip, [15](#)

offset

- gpiod::line, [32](#)

open

- gpiod::chip, [15](#)

OPEN_BY_LABEL

- gpiod::chip, [12](#)

OPEN_BY_NAME

- gpiod::chip, [12](#)

OPEN_BY_NUMBER

- gpiod::chip, [12](#)

OPEN_BY_PATH

- gpiod::chip, [12](#)

OPEN_LOOKUP

- gpiod::chip, [12](#)

operator bool

- gpiod::chip, [16](#)
- gpiod::line, [32](#)
- gpiod::line_bulk, [40](#)

operator!

- gpiod::chip, [16](#)
- gpiod::line, [33](#)
- gpiod::line_bulk, [40](#)

operator!=

- gpiod::chip, [16](#)
- gpiod::chip_iter, [20](#)
- gpiod::line, [33](#)
- gpiod::line_bulk::iterator, [24](#)
- gpiod::line_iter, [47](#)

operator++

- gpiod::chip_iter, [20](#)
- gpiod::line_bulk::iterator, [24](#)
- gpiod::line_iter, [48](#)

operator->

- gpiod::chip_iter, [21](#)
- gpiod::line_bulk::iterator, [24](#)
- gpiod::line_iter, [48](#)

operator=

- gpiod::chip, [17](#)
- gpiod::chip_iter, [21](#)
- gpiod::line, [33](#), [34](#)
- gpiod::line_bulk, [40](#), [42](#)
- gpiod::line_bulk::iterator, [25](#)
- gpiod::line_iter, [48](#)

operator==

- gpiod::chip, [17](#)
- gpiod::chip_iter, [22](#)
- gpiod::line, [34](#)
- gpiod::line_bulk::iterator, [25](#)
- gpiod::line_iter, [49](#)

operator[]

- gpiod::line_bulk, [42](#)

operator*

- gpiod::chip_iter, [20](#)
- gpiod::line_bulk::iterator, [24](#)
- gpiod::line_iter, [47](#)

request

- gpiod::line, [34](#)
- gpiod::line_bulk, [42](#)

request_type

- gpiod::line_request, [51](#)

reset

- gpiod::line, [34](#)

RISING_EDGE

- gpiod::line_event, [45](#)

set_config

- gpiod::line, [35](#)
- gpiod::line_bulk, [43](#)

set_direction_output

- gpiod::line, [35](#)
- gpiod::line_bulk, [43](#)

- set_flags
 - gpiod::line, [35](#)
 - gpiod::line_bulk, [43](#)
- set_value
 - gpiod::line, [35](#)
- set_values
 - gpiod::line_bulk, [43](#)
- size
 - gpiod::line_bulk, [44](#)
- source
 - gpiod::line_event, [45](#)
- timestamp
 - gpiod::line_event, [45](#)