

Team Reference Document

Team #define true false, TU München

NWERC 2014

Inhaltsverzeichnis

IO

C++ Input/Output/Limits	
-----------------------------------	--

Computations

Greatest Common Divisor	
Binomial Coefficients	

Data Structures

Union Find	
----------------------	--

Math-Stuff

Euclid-Stuff	
Gauss-Jordan	
Collected Binomials	

Shortest Paths

Floyd-Warshall	
Dijkstra/Java	
Bellman-Ford/Java	

Flow

MaxFlow Push-Relabel	
--------------------------------	--

Matching

Max Bipartite Matching	
----------------------------------	--

Graph Stuff

Strongly Connected Components	
Topological Sort	
BrÄcken - Artikulationspunkte	

Strings

Suffix Array	
Knuth-Morris-Pratt Algorithm	

Geometry

Geometry/C++	
Geometry/Java	
Graham Scan – Konvexe Huelle	
Delaunay Triangulation	

Trees

Binary Indexed Tree	
Segment Tree	
KD-tree	

Misc

Longest Increasing Subsequence	16
Simulated Annealing	16
Simplex Algorithm	16
Dates	17
Primes	18
LatLon	18

1 Theoretical CS Cheat Sheet

19

1 IO

2 C++ Input/Output/Limits

```

1 #include <iostream>
2 #include <iomanip>
3 #include <fstream>
4 #include <sstream>
5 #include <limits>
6 #include <algorithm>
7 #include <math.h>
8 #include <cstdlib>
9
10 #include <queue>
11 #include <vector>
12 #include <set>
13 #include <map>
14 #include <unordered_map>
15 #include <unordered_set>
16
17 using namespace std;
18 const int iMAX = numeric_limits<int>::max();
19 const int iMIN = numeric_limits<int>::min();
20 typedef long long LL;
21
22 int main() {
23     // massively improve cout and cin performance for large streams
24     ios::sync_with_stdio(false);
25     cin.tie(0);
26
27     // Output a specific number of digits past the decimal point, in this case 5
28     cout.setf(ios::fixed); cout << setprecision(5);
29     cout << 100.0/7.0 << endl;
30     cout.unsetf(ios::fixed);
31
32     // Output the decimal point and trailing zeros
33     cout.setf(ios::showpoint);
34     cout << 100.0 << endl;
35
36     // Output a '+' before positive values
37     cout.setf(ios::showpos);
38     cout << 100 << " " << -100 << endl;
39
40     // Output numerical values in hexadecimal
41     cout << hex << 100 << " " << 1000 << " " << 10000 << dec << endl;
42 }
```

Computations

Greatest Common Divisor

```
1 long gcd(long a, long b) {
2     if (b == 0) return a;
3     else return gcd(b, a % b);
4 }
```

Binomial Coefficients

```
1 long binomial(long n, long k) {
2     if (k > n - k) return binomial(n, n - k);
3     long result = 1;
4     if (k > n) return 0;
5     for (long next = 1; next <= k; ++next) {
6         long cancelled = gcd(result, next);
7         result = (result / cancelled) * (n - next + 1);
8         result /= next / cancelled;
9     }
10    return result;
11 }
```

Data Structures

Union Find

```
1 initialize(): for all x, boss[x] = x, rank[x] = 0.
2
3 union(x, y)
4     a = find(x); b = find(y);
5     if (rank(a) < rank(b)) boss[a] = b;
6     if (rank(a) > rank(b)) boss[b] = a;
7     if (rank(a) == rank(b)) {boss[b] = a; rank[a] += 1;}
8
9 find(x)
10    if (boss[x] == x) return x;
11    boss[x] = find(boss[x]); // path compression
12    return boss[x];
```

Math-Stuff

Euclid-Stuff

```
1 // This is a collection of useful code for solving problems that
2 // involve modular linear equations. Note that all of the
3 // algorithms described here work on nonnegative integers.
4
5 typedef vector<int> VI;
6 typedef pair<int, int> PII;
7
8 // return a % b (positive value)
9 int mod(int a, int b) {
10     return ((a%b)+b)%b;
11 }
```

```
12
13 // computes gcd(a,b)
14 int gcd(int a, int b) {
15     int tmp;
16     while(b){a%=b; tmp=a; a=b; b=tmp;}
17     return a;
18 }
19
20 // computes lcm(a,b)
21 int lcm(int a, int b) {
22     return a/gcd(a,b)*b;
23 }
24
25 // returns d = gcd(a,b); finds x,y such that d = ax + by
26 int extended_euclid(int a, int b, int &x, int &y) {
27     int xx = y = 0;
28     int yy = x = 1;
29     while (b) {
30         int q = a/b;
31         int t = b; b = a%b; a = t;
32         t = xx; xx = x-q*xx; x = t;
33         t = yy; yy = y-q*yy; y = t;
34     }
35     return a;
36 }
37
38 // finds all solutions to ax = b (mod n)
39 VI modular_linear_equation_solver(int a, int b, int n) {
40     int x, y;
41     VI solutions;
42     int d = extended_euclid(a, n, x, y);
43     if (!(b%d)) {
44         x = mod(x*(b/d), n);
45         for (int i = 0; i < d; i++)
46             solutions.push_back(mod(x + i*(n/d), n));
47     }
48     return solutions;
49 }
50
51 // computes b such that ab = 1 (mod n), returns -1 on failure
52 int mod_inverse(int a, int n) {
53     int x, y;
54     int d = extended_euclid(a, n, x, y);
55     if (d > 1) return -1;
56     return mod(x,n);
57 }
58
59 // Chinese remainder theorem (special case): find z such that
60 // z % x = a, z % y = b. Here, z is unique modulo M = lcm(x,y).
61 // Return (z,M). On failure, M = -1.
62 PII chinese_remainder_theorem(int x, int a, int y, int b) {
63     int s, t;
64     int d = extended_euclid(x, y, s, t);
65     if (a%d != b%d) return make_pair(0, -1);
66     return make_pair(mod(s*b*x+t*a*y,x*y)/d, x*y/d);
67 }
```

```

67 }
68
69 // Chinese remainder theorem: find z such that
70 // z % x[i] = a[i] for all i. Note that the solution is
71 // unique modulo M = lcm_i (x[i]). Return (z,M). On
72 // failure, M = -1. Note that we do not require the a[i]'s
73 // to be relatively prime.
74 PII chinese_remainder_theorem(const VI &x, const VI &a) {
75     PII ret = make_pair(a[0], x[0]);
76     for (int i = 1; i < x.size(); i++) {
77         ret = chinese_remainder_theorem(ret.second, ret.first, x[i], a[i]);
78         if (ret.second == -1) break;
79     }
80     return ret;
81 }
82
83 // computes x and y such that ax + by = c; on failure, x = y == -1
84 void linear_diophantine(int a, int b, int c, int &x, int &y) {
85     int d = gcd(a,b);
86     if (c%d) {
87         x = y = -1;
88     } else {
89         x = c/d * mod_inverse(a/d, b/d);
90         y = (c-a*x)/b;
91     }
92 }
93
94 int main() {
95
96     // expected: 2
97     cout << gcd(14, 30) << endl;
98
99     // expected: 2 -2 1
100    int x, y;
101    int d = extended_euclid(14, 30, x, y);
102    cout << d << " " << x << " " << y << endl;
103
104    // expected: 95 45
105    VI sols = modular_linear_equation_solver(14, 30, 100);
106    for (int i = 0; i < (int) sols.size(); i++) cout << sols[i] << " ";
107    cout << endl;
108
109    // expected: 8
110    cout << mod_inverse(8, 9) << endl;
111
112    // expected: 23 56
113    //          11 12
114    int xs[] = {3, 5, 7, 4, 6};
115    int as[] = {2, 3, 2, 3, 5};
116    PII ret = chinese_remainder_theorem(VI (xs, xs+3), VI(as, as+3));
117    cout << ret.first << " " << ret.second << endl;
118    ret = chinese_remainder_theorem (VI(xs+3, xs+5), VI(as+3, as+5));
119    cout << ret.first << " " << ret.second << endl;
120
121    // expected: 5 -15

```

```

122 linear_diophantine(7, 2, 5, x, y);
123 cout << x << " " << y << endl;
124 }

```

Gauss-Jordan

```

1 // Gauss-Jordan elimination with full pivoting.
2 //
3 // Uses:
4 // (1) solving systems of linear equations (AX=B)
5 // (2) inverting matrices (AX=I)
6 // (3) computing determinants of square matrices
7 //
8 // Running time: O(n^3)
9 //
10 // INPUT:    a[][] = an nxn matrix
11 //           b[][] = an nxm matrix
12 //
13 // OUTPUT:   X      = an nxm matrix (stored in b[][])
14 //           A^{-1} = an nxn matrix (stored in a[][])
15 //           returns determinant of a[][]
16
17 const double EPS = 1e-10;
18
19 typedef vector<int> VI;
20 typedef double T;
21 typedef vector<T> VT;
22 typedef vector<VT> VVT;
23
24 T GaussJordan(VVT &a, VVT &b) {
25     const int n = a.size();
26     const int m = b[0].size();
27     VI irow(n), icol(n), ipiv(n);
28     T det = 1;
29
30     for (int i = 0; i < n; i++) {
31         int pj = -1, pk = -1;
32         for (int j = 0; j < n; j++) if (!ipiv[j])
33             for (int k = 0; k < n; k++) if (!ipiv[k])
34                 if (pj == -1 || fabs(a[j][k]) > fabs(a[pj][pk])) { pj = j; pk = k; }
35         if (fabs(a[pj][pk]) < EPS) { cerr << "Matrix is singular." << endl; exit(0); }
36         ipiv[pj]++;
37         swap(a[pj], a[pk]);
38         swap(b[pj], b[pk]);
39         if (pj != pk) det *= -1;
40         irow[i] = pj;
41         icol[i] = pk;
42
43         T c = 1.0 / a[pk][pk];
44         det *= a[pk][pk];
45         a[pk][pk] = 1.0;
46         for (int p = 0; p < n; p++) a[pk][p] *= c;
47         for (int p = 0; p < m; p++) b[pk][p] *= c;
48         for (int p = 0; p < n; p++) if (p != pk) {
49             c = a[p][pk];

```

```

50     a[p][pk] = 0;
51     for (int q = 0; q < n; q++) a[p][q] -= a[pk][q] * c;
52     for (int q = 0; q < m; q++) b[p][q] -= b[pk][q] * c;
53 }
54 }
55
56 for (int p = n-1; p >= 0; p--) if (irow[p] != icol[p]) {
57     for (int k = 0; k < n; k++) swap(a[k][irow[p]], a[k][icol[p]]);
58 }
59
60 return det;
61 }
62
63 int main() {
64     const int n = 4;
65     const int m = 2;
66     double A[n][n] = { {1,2,3,4},{1,0,1,0},{5,3,2,4},{6,1,4,6} };
67     double B[n][m] = { {1,2},{4,3},{5,6},{8,7} };
68     VVT a(n), b(n);
69     for (int i = 0; i < n; i++) {
70         a[i] = VT(A[i], A[i] + n);
71         b[i] = VT(B[i], B[i] + m);
72     }
73
74     double det = GaussJordan(a, b);
75
76     // expected: 60
77     cout << "Determinant: " << det << endl;
78
79     // expected: -0.233333 0.166667 0.133333 0.0666667
80     //          0.166667 0.166667 0.333333 -0.333333
81     //          0.233333 0.833333 -0.133333 -0.0666667
82     //          0.05 -0.75 -0.1 0.2
83     cout << "Inverse: " << endl;
84     for (int i = 0; i < n; i++) {
85         for (int j = 0; j < n; j++)
86             cout << a[i][j] << ' ';
87         cout << endl;
88     }
89
90     // expected: 1.63333 1.3
91     //          -0.166667 0.5
92     //          2.36667 1.7
93     //          -1.85 -1.35
94     cout << "Solution: " << endl;
95     for (int i = 0; i < n; i++) {
96         for (int j = 0; j < m; j++)
97             cout << b[i][j] << ' ';
98         cout << endl;
99     }
100 }

```

Collected Binomials

```

1 //Berechnet alle Binomialkoeffizienten (n ueber k) mod m mit n<N

```

```

2 int binom[N][N];
3 void calcbinomials(int m) {
4     for (int n=0; n<N; n++) {
5         binom[n][0] = binom[n][n] = 1;
6         for (int k=1; k<n; k++)
7             binom[n][k] = (binom[n-1][k]+binom[n-1][k-1])%m;
8     }
9 }
10 //Berechnet einzelnen Binomialkoeffizienten in Restklasse O(log n)
11 void calcbinom(int n, int k, int m) {
12     return (fak[n] * inverse(fak[k], m) * inverse(fak[n-k], m))%m;
13 } //fak[n] = (n!)%m
14
15 //Berechnet fuer fixes n fuer alle k (n ueber k) O(n)
16 void calcbinomrow(int n) {
17     binom[n][0] = 1;
18     for (int k=1; k<=n; k++) {
19         binom[n][k] = binom[n][k-1]*(n-k+1)/k; // *inv(k) % MOD
20     }
21 }
22 }

```

Shortest Paths

Floyd-Warshall

Floyd-Warshall kommt mit negativen Gewichten zurecht. All sources, all targets.

```

1 procedure FloydWarshallWithPathReconstruction ()
2     for k := 1 to n
3         for i := 1 to n
4             for j := 1 to n
5                 if (path[i][k] + path[k][j] < path[i][j]) {
6                     path[i][j] := path[i][k]+path[k][j];
7                     next[i][j] := next[i][k];
8                 }
9
10 function Path(i,j)
11     if path[i][j] equals infinity then
12         return "no path";
13     int intermediate := next[i][j];
14     if intermediate equals 'null' then
15         return " ";
16     else
17         return Path(i,intermediate)
18             + intermediate
19             + Path(intermediate , j);

```

Dijkstra/Java

```

1 PriorityQueue<Item> q = new PriorityQueue<Item>();
2
3 Item[] index = new Item[n];
4 for(int i = 0; i < n; ++i) index[i] = new Item(-1, oo);
5
6 index[start] = new Item(-1, 0);

```

```

7 q.add(new Item(start, 0));
8
9 while(!q.isEmpty()) {
10     Item curr = q.poll();
11     if(curr.value > index[curr.node].value) continue;
12     /* if(curr.node == end) break; */
13     ArrayList<Item> edges = v.get(curr.node);
14     for(int i = 0; i < edges.size(); ++i) {
15         int nv = edges.get(i).value + curr.value;
16         int otherNode = edges.get(i).node;
17         Item oi = index[otherNode];
18         if(nv < oi.value) {
19             oi.value = nv;
20             oi.node = curr.node;
21             q.add(new Item(otherNode, nv));
22         }
23     }
24 }
25 return index;

```

```

34     jackpot = true;
35     break;
36 }
37 Item it = index[i];
38 ArrayList<Item> e = v.get(i);
39 for(int x = 0; x < e.size(); ++x) {
40     Item edge = e.get(x);
41     double nv = edge.value + it.value;
42     Item other = index[edge.node];
43     if(nv < other.value) {
44         other.value = nv;
45         if(!inQueue[edge.node]) {
46             q.add(edge.node);
47             if(nextPhaseStart == -1) nextPhaseStart = edge.node;
48             inQueue[edge.node] = true;
49         }
50     }
51 }

```

Bellman-Ford/Java

```

1 static class Item {
2     public int node;
3     public double value;
4 }
5
6 ArrayList<ArrayList<Item>> v = new ArrayList<ArrayList<Item>>(n);
7 for(int i = 0; i < n; ++i) {
8     v.add(new ArrayList<Item>());
9 }
10 // Kanten einfuegen:
11 // v.get(a).add(new Item(b, c));
12 ArrayDeque<Integer> q = new ArrayDeque<Integer>();
13 Item[] index = new Item[n];
14 index[0] = new Item(-1, 0);
15 for(int i = 1; i < n; ++i) {
16     index[i] = new Item(-1, oo);
17 }
18
19 boolean[] inQueue = new boolean[n];
20 inQueue[0] = true;
21 int phase = 0;
22 int nextPhaseStart = -1;
23 q.add(0);
24 boolean jackpot = false; // neg cycle
25 while(!q.isEmpty()) {
26     int i = q.poll();
27     inQueue[i] = false;
28     if(i == nextPhaseStart) {
29         phase++;
30         nextPhaseStart = -1;
31     }
32 if(phase == n-1) {
33     System.out.format("Case \#%d: Jackpot\n", numCase+1);

```

Flow

MaxFlow Push-Relabel

```

1 struct Edge {
2     int from, to, cap, flow, index;
3     Edge(int from, int to, int cap, int flow, int index) :
4         from(from), to(to), cap(cap), flow(flow), index(index) {}
5 };
6
7 struct PushRelabel {
8     int N;
9     vector<vector<Edge> > G;
10    vector<LL> excess;
11    vector<int> dist, active, count;
12    queue<int> Q;
13
14    PushRelabel(int N) : N(N), G(N), excess(N), dist(N), active(N), count(2*N) {}
15
16    void AddEdge(int from, int to, int cap) {
17        G[from].push_back(Edge(from, to, cap, 0, G[to].size()));
18        if (from == to) G[from].back().index++;
19        G[to].push_back(Edge(to, from, 0, 0, G[from].size() - 1));
20    }
21
22    void Enqueue(int v) {
23        if (!active[v] && excess[v] > 0) { active[v] = true; Q.push(v); }
24    }
25
26    void Push(Edge &e) {
27        int amt = int(min(excess[e.from], LL(e.cap - e.flow)));
28        if (dist[e.from] <= dist[e.to] || amt == 0) return;
29        e.flow += amt;
30        G[e.to][e.index].flow -= amt;
31        excess[e.to] += amt;
32        excess[e.from] -= amt;
33        Enqueue(e.to);
34    }
35
36    void Gap(int k) {
37        for (int v = 0; v < N; v++) {
38            if (dist[v] < k) continue;
39            count[dist[v]]--;
40            dist[v] = max(dist[v], N+1);
41            count[dist[v]]++;
42            Enqueue(v);
43        }
44    }
45
46    void Relabel(int v) {
47        count[dist[v]]--;
48        dist[v] = 2*N;
49        for (int i = 0; i < G[v].size(); i++)
50            if (G[v][i].cap - G[v][i].flow > 0)
51                dist[v] = min(dist[v], dist[G[v][i].to] + 1);
52        count[dist[v]]++;

```

```

53    Enqueue(v);
54 }
55
56 void Discharge(int v) {
57     for (int i = 0; excess[v] > 0 && i < G[v].size(); i++) Push(G[v][i]);
58     if (excess[v] > 0) {
59         if (count[dist[v]] == 1)
60             Gap(dist[v]);
61         else
62             Relabel(v);
63     }
64 }
65
66 LL GetMaxFlow(int s, int t) {
67     count[0] = N-1;
68     count[N] = 1;
69     dist[s] = N;
70     active[s] = active[t] = true;
71     for (int i = 0; i < G[s].size(); i++) {
72         excess[s] += G[s][i].cap;
73         Push(G[s][i]);
74     }
75
76     while (!Q.empty()) {
77         int v = Q.front();
78         Q.pop();
79         active[v] = false;
80         Discharge(v);
81     }
82
83     LL totflow = 0;
84     for (int i = 0; i < G[s].size(); i++) totflow += G[s][i].flow;
85     return totflow;
86 }
87 };

```

Matching

Max Bipartite Matching

```

1 typedef vector<int> VI;
2 typedef vector<VI> VVI;
3
4 bool FindMatch(int i, const VVI &w, VI &mr, VI &mc, VI &seen) {
5     for (int j = 0; j < w[i].size(); j++) {
6         if (w[i][j] && !seen[j]) {
7             seen[j] = true;
8             if (mc[j] < 0 || FindMatch(mc[j], w, mr, mc, seen)) {
9                 mr[i] = j;
10                mc[j] = i;
11                return true;
12            }
13        }
14    }
15    return false;

```

```

16 }
17
18 int BipartiteMatching(const VVI &w, VI &mr, VI &mc) {
19     mr = VI(w.size(), -1);
20     mc = VI(w[0].size(), -1);
21
22     int ct = 0;
23     for (int i = 0; i < w.size(); i++) {
24         VI seen(w[0].size());
25         if (FindMatch(i, w, mr, mc, seen)) ct++;
26     }
27     return ct;
28 }

```

```

38     }
39     sccs.push_back(scc);
40 }
41
42 // Aufruf der VISIT Funktion:
43 memset(d, 0, sizeof(d));
44 memset(instack, 0, sizeof(instack));
45 t = 0;
46 for (int v = 0; v < V; v++)
47     if (!d[v])
48         VISIT(v);
49

```

Graph Stuff

Strongly Connected Components

```

1 // Der Graph.
2 vector<int> g[20000];
3 // Anzahl der Knoten im Graphen.
4 int V;
5
6 // Interne Variablen fuer den Algorithmus
7 int d[20000], low[20000];
8 int t;
9 vector<int> stack;
10 bool instack[20000];
11
12 // Ergebnis-Struktur: enthaelt am Ende die starken
13 //Zusammenhangskomponenten (als Listen von Knotenindizes)
14 vector<vector<int> > sccs;
15
16 void VISIT(int v) {
17     d[v] = low[v] = ++t;
18     stack.push_back(v);
19     instack[v] = true;
20     for (vector<int>::iterator w = g[v].begin(); w != g[v].end(); ++w) {
21         if (!d[*w]) {
22             VISIT(*w);
23             low[v] = min(low[v], low[*w]);
24         } else if (instack[*w]) {
25             low[v] = min(low[v], low[*w]);
26         }
27     }
28
29     if (d[v] == low[v]) {
30         vector<int> scc;
31         while(1) {
32             int w = stack.back();
33             stack.pop_back();
34             instack[w] = false;
35             scc.push_back(w);
36             if (v == w)
37                 break;

```

Topological Sort

```

1 void dsf(int x) {
2     if(visited[x] {
3         if(!f[x]) circle = true;
4         return;
5     }
6     visited[x] = true;
7
8     for(Integer curr : list.get(x)) dsf(curr);
9
10    out[tt] = x;
11    tt++;
12    f[x] = true;
13 }

```

Brücken - Artikulationspunkte

```

1 #include <vector>
2 #include <stack>
3 #include <iostream>
4 #include <algorithm>
5 using namespace std;
6
7 vector<bool> visited;
8 int counter = 0;
9 vector<int> id;
10 vector<int> back;
11 vector<vector<int> > g;
12 int n,m;
13
14 void dfs(int v, int parent) {
15     visited[v] = true;
16     id[v] = counter++;
17     back[v] = id[v];
18
19     for(int i = 0; i < g[v].size(); ++i) {
20         int w = g[v][i];
21         if(w == parent) continue;
22
23         if(!visited[w]) { // Vorwaerts-Kante

```

```

24     dfs(w, v);
25     if(back[w] >= id[v]) cout << "Artikulationspunkt: " << v << endl;
26     if(back[w] > id[v]) cout << "Bruecke: " << v << "-" << w << endl;
27     back[v] = min(back[v], back[w]);
28 }
29 else // Rueckwaerts-Kante
30     back[v] = min(back[v], id[w]);
31 }
32 }
33
34 int main()
35 {
36     cin >> n >> m;
37     g.resize(n);
38     visited.resize(n, false);
39     back.resize(n);
40     id.resize(n);
41
42     for(int i = 0; i < m; ++i)
43     {
44         int a,b;
45         cin >> a >> b;
46         g[a].push_back(b);
47     }
48
49     for(int i = 0; i < n; ++i)
50         if(!visited[i])
51             dfs(i, -1);
52 }

```

Strings

Suffix Array

```

1 struct SuffixArray {
2     const int L;
3     string s;
4     vector<vector<int>> > P;
5     vector<pair<pair<int, int>, int> > M;
6
7     SuffixArray(const string &s) : L(s.length()), s(s), P(1, vector<int>(L, 0)), M(L) {
8         for (int i = 0; i < L; i++) P[0][i] = int(s[i]);
9         for (int skip = 1, level = 1; skip < L; skip *= 2, level++) {
10             P.push_back(vector<int>(L, 0));
11             for (int i = 0; i < L; i++)
12                 M[i] = make_pair(make_pair(P[level-1][i],
13                                         i + skip < L ? P[level-1][i + skip] : -1000),
14                                 i);
15             sort(M.begin(), M.end());
16             for (int i = 0; i < L; i++)
17                 P[level][M[i].second] = (i > 0 && M[i].first == M[i-1].first) ?
18                     P[level][M[i-1].second] : i;
19         }
20     }
21 }

```

```

22 vector<int> GetSuffixArray() { return P.back(); }
23
24 // returns the length of the longest common prefix of s[i...L-1] and s[j...L-1]
25 int LongestCommonPrefix(int i, int j) {
26     int len = 0;
27     if (i == j) return L - i;
28     for (int k = P.size() - 1; k >= 0 && i < L && j < L; k--) {
29         if (P[k][i] == P[k][j]) {
30             i += 1 << k;
31             j += 1 << k;
32             len += 1 << k;
33         }
34     }
35     return len;
36 }
37 };
38
39 int main() {
40
41     // bobocel is the 0'th suffix
42     // obocel is the 5'th suffix
43     // bocel is the 1'st suffix
44     // ocel is the 6'th suffix
45     // cel is the 2'nd suffix
46     // el is the 3'rd suffix
47     // l is the 4'th suffix
48     SuffixArray suffix("bobocel");
49     vector<int> v = suffix.GetSuffixArray();
50
51     // Expected output: 0 5 1 6 2 3 4
52     //                  2
53     for (int i = 0; i < v.size(); i++) cout << v[i] << " ";
54     cout << endl;
55     cout << suffix.LongestCommonPrefix(0, 2) << endl;
56 }

```

Knuth-Morris-Pratt Algorithm

```

1 /* Searches for the string w in the string s (of length k). Returns the 0-based
2 index of the first match (k if no match is found).
3 Algorithm runs in O(k) time. */
4
5 typedef vector<int> VI;
6
7 void buildTable(string& w, VI& t)
8 {
9     t = VI(w.length());
10    int i = 2, j = 0;
11    t[0] = -1; t[1] = 0;
12
13    while(i < w.length())
14    {
15        if(w[i-1] == w[j]) { t[i] = j+1; i++; j++; }
16        else if(j > 0) j = t[j];
17        else { t[i] = 0; i++; }
18    }
19 }

```



```

18 }
19 }
20
21 int KMP(string& s, string& w)
22 {
23     int m = 0, i = 0;
24     VI t;
25
26     buildTable(w, t);
27     while(m+i < s.length())
28     {
29         if(w[i] == s[m+i])
30         {
31             i++;
32             if(i == w.length()) return m;
33         }
34         else
35         {
36             m += i-t[i];
37             if(i > 0) i = t[i];
38         }
39     }
40     return s.length();
41 }
42
43 int main()
44 {
45     string a = (string) "The example above illustrates the general technique for assembling
46     "the table with a minimum of fuss. The principle is that of the overall search:
47     "most of the work was already done in getting to the current position, so very
48     "little needs to be done in leaving it. The only minor complication is that the
49     "logic which is correct late in the string erroneously gives non-proper
50     "substrings at the beginning. This necessitates some initialization code.";
51
52     string b = "table";
53
54     int p = KMP(a, b);
55     cout << p << ": " << a.substr(p, b.length()) << " " << b << endl;
56 }

```

Geometry

Geometry/C++

```

1 double INF = 1e100;
2 double EPS = 1e-12;
3
4 struct PT {
5     double x, y;
6     PT() {}
7     PT(double x, double y) : x(x), y(y) {}
8     PT(const PT &p) : x(p.x), y(p.y) {}
9     PT operator + (const PT &p) const { return PT(x+p.x, y+p.y); }
10    PT operator - (const PT &p) const { return PT(x-p.x, y-p.y); }
11    PT operator * (double c) const { return PT(x*c, y*c); }

```

```

12    PT operator / (double c) const { return PT(x/c, y/c); }
13 };
14
15 double dot(PT p, PT q) { return p.x*q.x+p.y*q.y; }
16 double dist2(PT p, PT q) { return dot(p-q,p-q); }
17 double cross(PT p, PT q) { return p.x*q.y-p.y*q.x; }
18 ostream &operator <<(ostream &os, const PT &p) {
19     os << "(" << p.x << "," << p.y << ")";
20 }
21
22 // rotate a point CCW or CW around the origin
23 PT RotateCCW90(PT p) { return PT(-p.y,p.x); }
24 PT RotateCW90(PT p) { return PT(p.y,-p.x); }
25 PT RotateCCW(PT p, double t) {
26     return PT(p.x*cos(t)-p.y*sin(t), p.x*sin(t)+p.y*cos(t));
27 }
28
29 // project point c onto line through a and b
30 // assuming a != b
31 PT ProjectPointLine(PT a, PT b, PT c) {
32     return a + (b-a)*dot(c-a, b-a)/dot(b-a, b-a);
33 }
34
35 // project point c onto line segment through a and b
36 PT ProjectPointSegment(PT a, PT b, PT c) {
37     double r = dot(b-a,b-a);
38     if (fabs(r) < EPS) return a;
39     double r2=dot(c-a, b-a)/r;
40     if (r < 0) return a;
41     if (r > 1) return b;
42     return a + (b-a)*r;
43 }
44
45 // compute distance from c to segment between a and b
46 double DistancePointSegment(PT a, PT b, PT c) {
47     return sqrt(dist2(c, ProjectPointSegment(a, b, c)));
48 }
49
50 // compute distance between point (x,y,z) and plane ax+by+cz=d
51 double DistancePointPlane(double x, double y, double z,
52                             double a, double b, double c, double d)
53 {
54     return fabs(a*x+b*y+c*z-d)/sqrt(a*a+b*b+c*c);
55 }
56
57 // determine if lines from a to b and c to d are parallel or collinear
58 bool LinesParallel(PT a, PT b, PT c, PT d) {
59     return fabs(cross(b-a, c-d)) < EPS;
60 }
61
62 bool LinesCollinear(PT a, PT b, PT c, PT d) {
63     return LinesParallel(a, b, c, d)
64         && fabs(cross(a-b, a-c)) < EPS
65         && fabs(cross(c-d, c-a)) < EPS;
66 }

```

```

67
68 // determine if line segment from a to b intersects with
69 // line segment from c to d
70 bool SegmentsIntersect(PT a, PT b, PT c, PT d) {
71     if (LinesCollinear(a, b, c, d)) {
72         if (dist2(a, c) < EPS || dist2(a, d) < EPS ||
73             dist2(b, c) < EPS || dist2(b, d) < EPS) return true;
74         if (dot(c-a, c-b) > 0 && dot(d-a, d-b) > 0 && dot(c-b, d-b) > 0)
75             return false;
76         return true;
77     }
78     if (cross(d-a, b-a) * cross(c-a, b-a) > 0) return false;
79     if (cross(a-c, d-c) * cross(b-c, d-c) > 0) return false;
80     return true;
81 }
82
83 // compute intersection of line passing through a and b
84 // with line passing through c and d, assuming that unique
85 // intersection exists; for segment intersection, check if
86 // segments intersect first
87 PT ComputeLineIntersection(PT a, PT b, PT c, PT d) {
88     b=b-a; d=c-d; c=c-a;
89     assert(dot(b, b) > EPS && dot(d, d) > EPS);
90     return a + b*cross(c, d)/cross(b, d);
91 }
92
93 // compute center of circle given three points
94 PT ComputeCircleCenter(PT a, PT b, PT c) {
95     b=(a+b)/2;
96     c=(a+c)/2;
97     return ComputeLineIntersection(b, b+RotateCW90(a-b), c, c+RotateCW90(a-c));
98 }
99
100 // determine if point is in a possibly non-convex polygon (by William
101 // Randolph Franklin); returns 1 for strictly interior points, 0 for
102 // strictly exterior points, and 0 or 1 for the remaining points.
103 // Note that it is possible to convert this into an *exact* test using
104 // integer arithmetic by taking care of the division appropriately
105 // (making sure to deal with signs properly) and then by writing exact
106 // tests for checking point on polygon boundary
107 bool PointInPolygon(const vector<PT> &p, PT q) {
108     bool c = 0;
109     for (int i = 0; i < p.size(); i++){
110         int j = (i+1)%p.size();
111         if ((p[i].y <= q.y && q.y < p[j].y ||
112             p[j].y <= q.y && q.y < p[i].y) &&
113             q.x < p[i].x + (p[j].x - p[i].x) * (q.y - p[i].y) / (p[j].y - p[i].y))
114             c = !c;
115     }
116     return c;
117 }
118
119 // determine if point is on the boundary of a polygon
120 bool PointOnPolygon(const vector<PT> &p, PT q) {
121     for (int i = 0; i < p.size(); i++)

```

```

122     if (dist2(ProjectPointSegment(p[i], p[(i+1)%p.size()], q), q) < EPS)
123         return true;
124     return false;
125 }
126
127 // compute intersection of line through points a and b with
128 // circle centered at c with radius r > 0
129 vector<PT> CircleLineIntersection(PT a, PT b, PT c, double r) {
130     vector<PT> ret;
131     b = b-a;
132     a = a-c;
133     double A = dot(b, b);
134     double B = dot(a, b);
135     double C = dot(a, a) - r*r;
136     double D = B*B - A*C;
137     if (D < -EPS) return ret;
138     ret.push_back(c+a+b*(-B+sqrt(D+EPS))/A);
139     if (D > EPS)
140         ret.push_back(c+a+b*(-B-sqrt(D))/A);
141     return ret;
142 }
143
144 // compute intersection of circle centered at a with radius r
145 // with circle centered at b with radius R
146 vector<PT> CircleCircleIntersection(PT a, PT b, double r, double R) {
147     vector<PT> ret;
148     double d = sqrt(dist2(a, b));
149     if (d > r+R || d+min(r, R) < max(r, R)) return ret;
150     double x = (d*d-R*R+r*r)/(2*d);
151     double y = sqrt(r*r-x*x);
152     PT v = (b-a)/d;
153     ret.push_back(a+v*x + RotateCCW90(v)*y);
154     if (y > 0)
155         ret.push_back(a+v*x - RotateCCW90(v)*y);
156     return ret;
157 }
158
159 // This code computes the area or centroid of a (possibly nonconvex)
160 // polygon, assuming that the coordinates are listed in a clockwise or
161 // counterclockwise fashion. Note that the centroid is often known as
162 // the "center of gravity" or "center of mass".
163 double ComputeSignedArea(const vector<PT> &p) {
164     double area = 0;
165     for (int i = 0; i < p.size(); i++) {
166         int j = (i+1) % p.size();
167         area += p[i].x*p[j].y - p[j].x*p[i].y;
168     }
169     return area / 2.0;
170 }
171
172 double ComputeArea(const vector<PT> &p) {
173     return fabs(ComputeSignedArea(p));
174 }
175
176 PT ComputeCentroid(const vector<PT> &p) {

```

```

177 PT c(0,0);
178 double scale = 6.0 * ComputeSignedArea(p);
179 for (int i = 0; i < p.size(); i++){
180     int j = (i+1) % p.size();
181     c = c + (p[i].x*p[j].y - p[j].x*p[i].y);
182 }
183 return c / scale;
184 }
185
186 // tests whether or not a given polygon (in CW or CCW order) is simple
187 bool IsSimple(const vector<PT> &p) {
188     for (int i = 0; i < p.size(); i++) {
189         for (int k = i+1; k < p.size(); k++) {
190             int j = (i+1) % p.size();
191             int l = (k+1) % p.size();
192             if (i == l || j == k) continue;
193             if (SegmentsIntersect(p[i], p[j], p[k], p[l]))
194                 return false;
195         }
196     }
197     return true;
198 }
199
200 int main() {
201
202     // expected: (-5,2)
203     cerr << RotateCCW90(PT(2,5)) << endl;
204
205     // expected: (5,-2)
206     cerr << RotateCW90(PT(2,5)) << endl;
207
208     // expected: (-5,2)
209     cerr << RotateCCW(PT(2,5), M_PI/2) << endl;
210
211     // expected: (5,2)
212     cerr << ProjectPointLine(PT(-5,-2), PT(10,4), PT(3,7)) << endl;
213
214     // expected: (5,2) (7.5,3) (2.5,1)
215     cerr << ProjectPointSegment(PT(-5,-2), PT(10,4), PT(3,7)) << " "
216         << ProjectPointSegment(PT(7.5,3), PT(10,4), PT(3,7)) << " "
217         << ProjectPointSegment(PT(-5,-2), PT(2.5,1), PT(3,7)) << endl;
218
219     // expected: 6.78903
220     cerr << DistancePointPlane(4,-4,3,2,-2,5,-8) << endl;
221
222     // expected: 1 0 1
223     cerr << LinesParallel(PT(1,1), PT(3,5), PT(2,1), PT(4,5)) << " "
224         << LinesParallel(PT(1,1), PT(3,5), PT(2,0), PT(4,5)) << " "
225         << LinesParallel(PT(1,1), PT(3,5), PT(5,9), PT(7,13)) << endl;
226
227     // expected: 0 0 1
228     cerr << LinesCollinear(PT(1,1), PT(3,5), PT(2,1), PT(4,5)) << " "
229         << LinesCollinear(PT(1,1), PT(3,5), PT(2,0), PT(4,5)) << " "
230         << LinesCollinear(PT(1,1), PT(3,5), PT(5,9), PT(7,13)) << endl;
231

```

```

232 // expected: 1 1 1 0
233 cerr << SegmentsIntersect(PT(0,0), PT(2,4), PT(3,1), PT(-1,3)) << " "
234     << SegmentsIntersect(PT(0,0), PT(2,4), PT(4,3), PT(0,5)) << " "
235     << SegmentsIntersect(PT(0,0), PT(2,4), PT(2,-1), PT(-2,1)) << " "
236     << SegmentsIntersect(PT(0,0), PT(2,4), PT(5,5), PT(1,7)) << endl;
237
238 // expected: (1,2)
239 cerr << ComputeLineIntersection(PT(0,0), PT(2,4), PT(3,1), PT(-1,3)) << endl;
240
241 // expected: (1,1)
242 cerr << ComputeCircleCenter(PT(-3,4), PT(6,1), PT(4,5)) << endl;
243
244 vector<PT> v;
245 v.push_back(PT(0,0));
246 v.push_back(PT(5,0));
247 v.push_back(PT(5,5));
248 v.push_back(PT(0,5));
249
250 // expected: 1 1 1 0 0
251 cerr << PointInPolygon(v, PT(2,2)) << " "
252     << PointInPolygon(v, PT(2,0)) << " "
253     << PointInPolygon(v, PT(0,2)) << " "
254     << PointInPolygon(v, PT(5,2)) << " "
255     << PointInPolygon(v, PT(2,5)) << endl;
256
257 // expected: 0 1 1 1 1
258 cerr << PointOnPolygon(v, PT(2,2)) << " "
259     << PointOnPolygon(v, PT(2,0)) << " "
260     << PointOnPolygon(v, PT(0,2)) << " "
261     << PointOnPolygon(v, PT(5,2)) << " "
262     << PointOnPolygon(v, PT(2,5)) << endl;
263
264 // expected: (1,6)
265 // (5,4) (4,5)
266 // blank line
267 // (4,5) (5,4)
268 // blank line
269 // (4,5) (5,4)
270 vector<PT> u = CircleLineIntersection(PT(0,6), PT(2,6), PT(1,1), 5);
271 for (int i = 0; i < u.size(); i++) cerr << u[i] << " "; cerr << endl;
272 u = CircleLineIntersection(PT(0,9), PT(9,0), PT(1,1), 5);
273 for (int i = 0; i < u.size(); i++) cerr << u[i] << " "; cerr << endl;
274 u = CircleCircleIntersection(PT(1,1), PT(10,10), 5, 5);
275 for (int i = 0; i < u.size(); i++) cerr << u[i] << " "; cerr << endl;
276 u = CircleCircleIntersection(PT(1,1), PT(8,8), 5, 5);
277 for (int i = 0; i < u.size(); i++) cerr << u[i] << " "; cerr << endl;
278 u = CircleCircleIntersection(PT(1,1), PT(4.5,4.5), 10, sqrt(2.0)/2.0);
279 for (int i = 0; i < u.size(); i++) cerr << u[i] << " "; cerr << endl;
280 u = CircleCircleIntersection(PT(1,1), PT(4.5,4.5), 5, sqrt(2.0)/2.0);
281 for (int i = 0; i < u.size(); i++) cerr << u[i] << " "; cerr << endl;
282
283 // area should be 5.0
284 // centroid should be (1.1666666, 1.1666666)
285 PT pa[] = { PT(0,0), PT(5,0), PT(1,1), PT(0,5) };
286 vector<PT> p(pa, pa+4);

```

```

287 PT c = ComputeCentroid(p);
288 cerr << "Area: " << ComputeArea(p) << endl;
289 cerr << "Centroid: " << c << endl;
290
291 return 0;
292 }

```

Geometry/Java

```

1 P cross(P o) {
2     return new P(y*o.z-z*o.y, z*o.x-x*o.z, x*o.y-y*o.x);
3 }
4
5 P scalar(P o) {
6     return new P(x*o.x, y * o.y, z * o.z);
7 }
8
9 P r90() {
10    return new P(-y, x, z);
11 }
12
13 P parallel(P p) {
14    return cross(zeroOne).cross(p);
15 }
16
17 Point2D getPoint() {
18    return new Point2D.Double(x / z, y / z);
19 }
20
21 static double computePolygonArea(ArrayList<Point2D.Double> points) {
22    Point2D.Double[] pts = points.toArray(new Point2D.Double[points.size()]);
23    double area = 0;
24    for (int i = 0; i < pts.length; i++) {
25        int j = (i+1) % pts.length;
26        area += pts[i].x * pts[j].y - pts[j].x * pts[i].y;
27    }
28    return Math.abs(area)/2;
29 }

```

Graham Scan – Konvexe Huelle

- Finde p_0 mit min y , Unentschieden: betrachte x
- Sortiere $p_1 \dots p_n$: $p_i < p_j \iff ccw(p_0, p_i, p_j) < 0$
(colinear \rightarrow naechster zuerst)
- Setze $p_{n+1} = p_0$
- Push(p_0); Push(p_1); Push(p_2);
- for $i = 3$ to $n + 1$
 - Solange Winkel der letzten zwei des Stacks und p_i rechtskurve: Pop()
 - Push(p_i)

```

1 int minPoint = 0;
2 for (int i = 1; i < n; ++i) {

```

```

3     if (points[i].y < points[minPoint].y ||
4         (points[i].y == points[minPoint].y &&
5          points[i].x < points[minPoint].x)) {
6         minPoint = i;
7     }
8 }
9 final int mx = points[minPoint].x;
10 final int my = points[minPoint].y;
11 Arrays.sort(points, new Comparator<Point>() {
12     @Override
13     public int compare(Point a, Point b) {
14         int ccw = Line2D.relativeCCW(mx, my, a.x, a.y, b.x, b.y);
15         if (ccw == 0 || Line2D.relativeCCW(mx, my, b.x, b.y, a.x, a.y) == 0) {
16             // gleich...
17             double d1 = a.distance(mx, my);
18             double d2 = b.distance(mx, my);
19             if ((d2 < d1 && d2 != 0) || d1 == 0) {
20                 return 1;
21             } else {
22                 return -1;
23             }
24         } else if (ccw == 1) {
25             // clockwise... -> zuerst b -> a > b
26             return 1;
27         } else if (ccw == -1) {
28             return -1;
29         } else {
30             System.out.println("shouldnt happen");
31             System.exit(1);
32         }
33     }
34     return 0;
35 });
36
37 ArrayList<Integer> stack = new ArrayList<Integer>();
38 stack.add(n-1);
39 for (int i = 0; i < n; ++i) {
40     if (stack.size() < 2) {
41         stack.add(i);
42         continue;
43     }
44     int last = stack.get(stack.size() - 1);
45     int l2 = stack.get(stack.size() - 2);
46     int ccw = Line2D.relativeCCW(points[l2].x, points[l2].y,
47                                 points[last].x, points[last].y, points[i].x, points[i].y);
48     if (ccw != -1) {
49         // clockwise oder gleiche Linie
50         stack.remove(stack.size() - 1);
51         i--;
52     } else {
53         stack.add(i);
54     }
55 }

```

Delaunay Triangulation

```

1 // Slow but simple Delaunay triangulation. Does not handle
2 // degenerate cases (from O'Rourke, Computational Geometry in C)
3 //
4 // Running time: O(n^4)
5 //
6 // INPUT:    x[] = x-coordinates
7 //           y[] = y-coordinates
8 //
9 // OUTPUT:   triples = a vector containing m triples of indices
10 //             corresponding to triangle vertices
11
12 typedef double T;
13
14 struct triple {
15     int i, j, k;
16     triple() {}
17     triple(int i, int j, int k) : i(i), j(j), k(k) {}
18 };
19
20 vector<triple> delaunayTriangulation(vector<T>& x, vector<T>& y) {
21     int n = x.size();
22     vector<T> z(n);
23     vector<triple> ret;
24
25     for (int i = 0; i < n; i++)
26         z[i] = x[i] * x[i] + y[i] * y[i];
27
28     for (int i = 0; i < n-2; i++) {
29         for (int j = i+1; j < n; j++) {
30             for (int k = i+1; k < n; k++) {
31                 if (j == k) continue;
32                 double xn = (y[j]-y[i])*(z[k]-z[i]) - (y[k]-y[i])*(z[j]-z[i]);
33                 double yn = (x[k]-x[i])*(z[j]-z[i]) - (x[j]-x[i])*(z[k]-z[i]);
34                 double zn = (x[j]-x[i])*(y[k]-y[i]) - (x[k]-x[i])*(y[j]-y[i]);
35                 bool flag = zn < 0;
36                 for (int m = 0; flag && m < n; m++)
37                     flag = flag && ((x[m]-x[i])*xn +
38                                     (y[m]-y[i])*yn +
39                                     (z[m]-z[i])*zn <= 0);
40                 if (flag) ret.push_back(triple(i, j, k));
41             }
42         }
43     }
44     return ret;
45 }
46
47 int main()
48 {
49     T xs[]={0, 0, 1, 0.9};
50     T ys[]={0, 1, 0, 0.9};
51     vector<T> x(&xs[0], &xs[4]), y(&ys[0], &ys[4]);
52     vector<triple> tri = delaunayTriangulation(x, y);
53 }

```

```

54 //expected: 0 1 3
55 //           0 3 2
56
57 int i;
58 for(i = 0; i < tri.size(); i++)
59     printf("%d %d %d\n", tri[i].i, tri[i].j, tri[i].k);
60 return 0;
61 }

```

Trees

Binary Indexed Tree

```

1 //binary indexed tree
2 //verwaltet kumulative Summen in log(n)
3
4
5 int tree[1<<N];
6 int MaxVal = (1<<N)-1;
7
8 int readsum(int idx){ //sum_{i in [1;idx]} f[i]
9     int sum = 0;
10    while (idx > 0){
11        sum += tree[idx];
12        idx -= (idx & -idx);
13    }
14    return sum;
15 }
16
17 int suminrange(int a, int b) { //sum_{i in [a;b]} f[i]
18     return readsum(b)-readsum(a-1);
19 }
20
21 void update(int idx ,int val){ //updates f[idx]->val
22     while (idx <= MaxVal){
23         tree[idx] += val;
24         idx += (idx & -idx);
25     }
26 }

```

Segment Tree

```

1 /*Segment Tree*/
2 #include <iostream> using namespace std;
3
4 // TODO: Define num_elems (~N)
5 const int num_elems = 1 << 20;
6 const int seg_size = 2 * num_elems;
7 const int off = num_elems - 1;
8 int segtree[seg_size];
9
10 int left(int x) {return 2 * x + 1;}
11 int right(int x) {return 2 * x + 2;}
12 int parent(int x) {return (x - 1) / 2;}
13

```

```

14 // TOTO: Define Operator. Example: Sum.
15 int op (int a, int b) {return a + b; }
16
17 void update (int pos) {
18     segtree[pos] = op(segtree[ left(pos)], segtree[ right(pos)]);
19     if (parent (pos) != pos) update(parent(pos)); }
20
21 void set (int pos, int data) {
22     segtree[pos + off] = data;
23     update(parent(pos + off)); }
24
25 int query (int i, int j, int l, int r, int curr_node) {
26     if (i <= l && j >= r) return segtree[curr_node];
27     if (i > r || j < l) return 0; // Neutral Element
28     int m = (l + r) / 2;
29     return op(query(i, j, l, m, left(curr_node)),
30             query(i, j, m + 1, r, right(curr_node))); }
31
32 int query(int i, int j) { // op[i, j];
33     return query(i, j, 0, off, 0); }
34
35 int main() {
36     // Initialize
37     fill_n(segtree, seg_size, 0);
38
39     return 0; }

```

KD-tree

```

1 -----
2 // A straightforward, but probably sub-optimal KD-tree implmentation that's
3 // probably good enough for most things (current it's a 2D-tree)
4 //
5 // - constructs from n points in O(n lg^2 n) time
6 // - handles nearest-neighbor query in O(lg n) if points are well distributed
7 // - worst case for nearest-neighbor may be linear in pathological case
8 //
9 // Sonny Chan, Stanford University, April 2009
10 -----
11
12 // number type for coordinates, and its maximum value
13 typedef long long ntype;
14 const ntype sentry = numeric_limits<ntype>::max();
15
16 // point structure for 2D-tree, can be extended to 3D
17 struct point {
18     ntype x, y;
19     point(ntype xx = 0, ntype yy = 0) : x(xx), y(yy) {}
20 };
21
22 bool operator==(const point &a, const point &b)
23 {
24     return a.x == b.x && a.y == b.y;
25 }

```

```

27 // sorts points on x-coordinate
28 bool on_x(const point &a, const point &b)
29 {
30     return a.x < b.x;
31 }
32
33 // sorts points on y-coordinate
34 bool on_y(const point &a, const point &b)
35 {
36     return a.y < b.y;
37 }
38
39 // squared distance between points
40 ntype pdist2(const point &a, const point &b)
41 {
42     ntype dx = a.x-b.x, dy = a.y-b.y;
43     return dx*dx + dy*dy;
44 }
45
46 // bounding box for a set of points
47 struct bbox
48 {
49     ntype x0, x1, y0, y1;
50
51     bbox() : x0(sentry), x1(-sentry), y0(sentry), y1(-sentry) {}
52
53     // computes bounding box from a bunch of points
54     void compute(const vector<point> &v) {
55         for (int i = 0; i < v.size(); ++i) {
56             x0 = min(x0, v[i].x);    x1 = max(x1, v[i].x);
57             y0 = min(y0, v[i].y);    y1 = max(y1, v[i].y);
58         }
59     }
60
61     // squared distance between a point and this bbox, 0 if inside
62     ntype distance(const point &p) {
63         if (p.x < x0) {
64             if (p.y < y0) return pdist2(point(x0, y0), p);
65             else if (p.y > y1) return pdist2(point(x0, y1), p);
66             else return pdist2(point(x0, p.y), p);
67         }
68         else if (p.x > x1) {
69             if (p.y < y0) return pdist2(point(x1, y0), p);
70             else if (p.y > y1) return pdist2(point(x1, y1), p);
71             else return pdist2(point(x1, p.y), p);
72         }
73         else {
74             if (p.y < y0) return pdist2(point(p.x, y0), p);
75             else if (p.y > y1) return pdist2(point(p.x, y1), p);
76             else return 0;
77         }
78     }
79 };
80
81 // stores a single node of the kd-tree, either internal or leaf

```

```

82 struct kdnode
83 {
84     bool leaf;        // true if this is a leaf node (has one point)
85     point pt;         // the single point of this is a leaf
86     bbox bound;       // bounding box for set of points in children
87
88     kdnode *first, *second; // two children of this kd-node
89
90     kdnode() : leaf(false), first(0), second(0) {}
91     ~kdnode() { if (first) delete first; if (second) delete second; }
92
93     // intersect a point with this node (returns squared distance)
94     ntype intersect(const point &p) {
95         return bound.distance(p);
96     }
97
98     // recursively builds a kd-tree from a given cloud of points
99     void construct(vector<point> &vp)
100     {
101         // compute bounding box for points at this node
102         bound.compute(vp);
103
104         // if we're down to one point, then we're a leaf node
105         if (vp.size() == 1) {
106             leaf = true;
107             pt = vp[0];
108         }
109         else {
110             // split on x if the bbox is wider than high (not best heuristic...)
111             if (bound.x1-bound.x0 >= bound.y1-bound.y0)
112                 sort(vp.begin(), vp.end(), on_x);
113             // otherwise split on y-coordinate
114             else
115                 sort(vp.begin(), vp.end(), on_y);
116
117             // divide by taking half the array for each child
118             // (not best performance if many duplicates in the middle)
119             int half = vp.size()/2;
120             vector<point> vl(vp.begin(), vp.begin()+half);
121             vector<point> vr(vp.begin()+half, vp.end());
122             first = new kdnode(); first->construct(vl);
123             second = new kdnode(); second->construct(vr);
124         }
125     }
126 };
127
128 // simple kd-tree class to hold the tree and handle queries
129 struct kdtree
130 {
131     kdnode *root;
132
133     // constructs a kd-tree from a points (copied here, as it sorts them)
134     kdtree(const vector<point> &vp) {
135         vector<point> v(vp.begin(), vp.end());
136         root = new kdnode();

```

```

137         root->construct(v);
138     }
139     ~kdtree() { delete root; }
140
141     // recursive search method returns squared distance to nearest point
142     ntype search(kdnode *node, const point &p)
143     {
144         if (node->leaf) {
145             // commented special case tells a point not to find itself
146             if (p == node->pt) return sentry;
147             //
148             return pdist2(p, node->pt);
149         }
150
151         ntype bfirst = node->first->intersect(p);
152         ntype bsecond = node->second->intersect(p);
153
154         // choose the side with the closest bounding box to search first
155         // (note that the other side is also searched if needed)
156         if (bfirst < bsecond) {
157             ntype best = search(node->first, p);
158             if (bsecond < best)
159                 best = min(best, search(node->second, p));
160             return best;
161         }
162         else {
163             ntype best = search(node->second, p);
164             if (bfirst < best)
165                 best = min(best, search(node->first, p));
166             return best;
167         }
168     }
169
170     // squared distance to the nearest
171     ntype nearest(const point &p) {
172         return search(root, p);
173     }
174 };
175
176 // -----
177 // some basic test code here
178
179 int main()
180 {
181     // generate some random points for a kd-tree
182     vector<point> vp;
183     for (int i = 0; i < 100000; ++i) {
184         vp.push_back(point(rand()%100000, rand()%100000));
185     }
186     kdtree tree(vp);
187
188     // query some points
189     for (int i = 0; i < 10; ++i) {
190         point q(rand()%100000, rand()%100000);
191         cout << "Closest squared distance to (" << q.x << ", " << q.y << ")"

```

```

192         << " is " << tree.nearest(q) << endl;
193     }
194
195     return 0;
196 }
197
198 // -----

```

Misc

Longest Increasing Subsequence

```

1 // Given a list of numbers of length n, this routine extracts a
2 // longest increasing subsequence.
3 //
4 // Running time: O(n log n)
5 //
6 // INPUT: a vector of integers
7 // OUTPUT: a vector containing the longest increasing subsequence
8 typedef vector<int> VI;
9 typedef pair<int, int> PII;
10 typedef vector<PII> VPII;
11
12 #define STRICTLY_INCREASNG
13
14 VI LongestIncreasingSubsequence(VI v) {
15     VPII best;
16     VI dad(v.size(), -1);
17
18     for (int i = 0; i < v.size(); i++) {
19 #ifdef STRICTLY_INCREASNG
20         PII item = make_pair(v[i], 0);
21         VPII::iterator it = lower_bound(best.begin(), best.end(), item);
22         item.second = i;
23 #else
24         PII item = make_pair(v[i], i);
25         VPII::iterator it = upper_bound(best.begin(), best.end(), item);
26 #endif
27         if (it == best.end()) {
28             dad[i] = (best.size() == 0 ? -1 : best.back().second);
29             best.push_back(item);
30         } else {
31             dad[i] = dad[it->second];
32             *it = item;
33         }
34     }
35
36     VI ret;
37     for (int i = best.back().second; i >= 0; i = dad[i])
38         ret.push_back(v[i]);
39     reverse(ret.begin(), ret.end());
40     return ret;
41 }

```

Simulated Annealing

```

1 Random r = new Random();
2 int numChanges = 0;
3 double T = 10000;
4 double alpha = 0.99;
5 int decreaseAfter = 20;
6 int nChanges = 0;
7 for (int i = 0; i < 1000000; ++i) {
8     // calculate newCost (apply 2-opt-step) (swap two things)
9     double delta = newCost - cost;
10    boolean accept = newCost <= cost;
11    if (!accept) {
12        double R = r.nextDouble();
13        double calc = Math.exp(-delta / T);
14        double maxDiff = Math.exp(-10000/T);
15        if (calc < maxDiff && i < 1000000/2) {
16            calc = maxDiff;
17        }
18        //System.out.println(calc);
19        if (calc > R) {
20            accept = true;
21        }
22    }
23    // if (i % 10000 == 0) {
24    //     System.out.println("after " + i + ": " + T);
25    // }
26
27    if (nChanges >= decreaseAfter) {
28        nChanges = 0;
29        T = alpha * T;
30    }
31    if (accept) {
32        cost = newCost;
33        numChanges++;
34        nChanges++;
35    } else {
36        // swap back
37        swap(trip, a, b);
38    }
39 }

```

Simplex Algorithm

```

1 // Two-phase simplex algorithm for solving linear programs of the form
2 //
3 //     maximize    c^T x
4 //     subject to  Ax <= b
5 //                x >= 0
6 //
7 // INPUT: A -- an m x n matrix
8 //         b -- an m-dimensional vector
9 //         c -- an n-dimensional vector
10 //         x -- a vector where the optimal solution will be stored
11 //

```



```

12 // OUTPUT: value of the optimal solution (infinity if unbounded
13 //         above, nan if infeasible)
14 //
15 // To use this code, create an LPSolver object with A, b, and c as
16 // arguments. Then, call Solve(x).
17 typedef long double DOUBLE;
18 typedef vector<DOUBLE> VD;
19 typedef vector<VD> VVD;
20 typedef vector<int> VI;
21
22 const DOUBLE EPS = 1e-9;
23
24 struct LPSolver {
25     int m, n;
26     VI B, N;
27     VVD D;
28
29     LPSolver(const VVD &A, const VD &b, const VD &c) :
30         m(b.size()), n(c.size()), N(n+1), B(m), D(m+2, VD(n+2)) {
31         for (int i = 0; i < m; i++) for (int j = 0; j < n; j++) D[i][j] = A[i][j];
32         for (int i = 0; i < m; i++) { B[i] = n+i; D[i][n] = -1; D[i][n+1] = b[i]; }
33         for (int j = 0; j < n; j++) { N[j] = j; D[m][j] = -c[j]; }
34         N[n] = -1; D[m+1][n] = 1;
35     }
36
37     void Pivot(int r, int s) {
38         for (int i = 0; i < m+2; i++) if (i != r)
39             for (int j = 0; j < n+2; j++) if (j != s)
40                 D[i][j] -= D[r][j] * D[i][s] / D[r][s];
41         for (int j = 0; j < n+2; j++) if (j != s) D[r][j] /= D[r][s];
42         for (int i = 0; i < m+2; i++) if (i != r) D[i][s] /= -D[r][s];
43         D[r][s] = 1.0 / D[r][s];
44         swap(B[r], N[s]);
45     }
46
47     bool Simplex(int phase) {
48         int x = phase == 1 ? m+1 : m;
49         while (true) {
50             int s = -1;
51             for (int j = 0; j <= n; j++) {
52                 if (phase == 2 && N[j] == -1) continue;
53                 if (s == -1 || D[x][j] < D[x][s] || D[x][j] == D[x][s] && N[j] < N[s]) s = j;
54             }
55             if (D[x][s] >= -EPS) return true;
56             int r = -1;
57             for (int i = 0; i < m; i++) {
58                 if (D[i][s] <= 0) continue;
59                 if (r == -1 || D[i][n+1] / D[i][s] < D[r][n+1] / D[r][s] ||
60                     D[i][n+1] / D[i][s] == D[r][n+1] / D[r][s] && B[i] < B[r]) r = i;
61             }
62             if (r == -1) return false;
63             Pivot(r, s);
64         }
65     }
66 }

```

```

67 DOUBLE Solve(VD &x) {
68     int r = 0;
69     for (int i = 1; i < m; i++) if (D[i][n+1] < D[r][n+1]) r = i;
70     if (D[r][n+1] <= -EPS) {
71         Pivot(r, n);
72         if (!Simplex(1) || D[m+1][n+1] < -EPS) return numeric_limits<DOUBLE>::infinity();
73         for (int i = 0; i < m; i++) if (B[i] == -1) {
74             int s = -1;
75             for (int j = 0; j <= n; j++)
76                 if (s == -1 || D[i][j] < D[i][s] || D[i][j] == D[i][s] && N[j] < N[s]) s = j;
77             Pivot(i, s);
78         }
79     }
80     if (!Simplex(2)) return numeric_limits<DOUBLE>::infinity();
81     x = VD(n);
82     for (int i = 0; i < m; i++) if (B[i] < n) x[B[i]] = D[i][n+1];
83     return D[m][n+1];
84 }
85 };
86
87 int main() {
88     const int m = 4;
89     const int n = 3;
90     DOUBLE _A[m][n] = {
91         { 6, -1, 0 },
92         { -1, -5, 0 },
93         { 1, 5, 1 },
94         { -1, -5, -1 }
95     };
96     DOUBLE _b[m] = { 10, -4, 5, -5 };
97     DOUBLE _c[n] = { 1, -1, 0 };
98
99     VVD A(m);
100     VD b(_b, _b + m);
101     VD c(_c, _c + n);
102     for (int i = 0; i < m; i++) A[i] = VD(_A[i], _A[i] + n);
103
104     LPSolver solver(A, b, c);
105     VD x;
106     DOUBLE value = solver.Solve(x);
107
108     cerr << "VALUE: " << value << endl;
109     cerr << "SOLUTION: ";
110     for (size_t i = 0; i < x.size(); i++) cerr << " " << x[i];
111     cerr << endl;
112     return 0;
113 }

```

Dates

```

1 // Routines for performing computations on dates. In these routines,
2 // months are expressed as integers from 1 to 12, days are expressed
3 // as integers from 1 to 31, and years are expressed as 4-digit
4 // integers.
5

```

```

6 string dayOfWeek[] = {"Mon", "Tue", "Wed", "Thu", "Fri", "Sat", "Sun"};
7
8 // converts Gregorian date to integer (Julian day number)
9 int dateToInt (int m, int d, int y){
10     return
11         1461 * (y + 4800 + (m - 14) / 12) / 4 +
12         367 * (m - 2 - (m - 14) / 12 * 12) / 12 -
13         3 * ((y + 4900 + (m - 14) / 12) / 100) / 4 +
14         d - 32075;
15 }
16
17 // converts integer (Julian day number) to Gregorian date: month/day/year
18 void intToDate (int jd, int &m, int &d, int &y){
19     int x, n, i, j;
20
21     x = jd + 68569;
22     n = 4 * x / 146097;
23     x -= (146097 * n + 3) / 4;
24     i = (4000 * (x + 1)) / 1461001;
25     x -= 1461 * i / 4 - 31;
26     j = 80 * x / 2447;
27     d = x - 2447 * j / 80;
28     x = j / 11;
29     m = j + 2 - 12 * x;
30     y = 100 * (n - 49) + i + x;
31 }
32
33 // converts integer (Julian day number) to day of week
34 string intToDay (int jd){
35     return dayOfWeek[jd % 7];
36 }
37
38 int main (int argc, char **argv){
39     int jd = dateToInt (3, 24, 2004);
40     int m, d, y;
41     intToDate (jd, m, d, y);
42     string day = intToDay (jd);
43
44     // expected output:
45     // 2453089
46     // 3/24/2004
47     // Wed
48     cout << jd << endl
49         << m << "/" << d << "/" << y << endl
50         << day << endl;
51 }

```

Primes

```

1 // Other primes:
2 // The largest prime smaller than 10 is 7.
3 // The largest prime smaller than 100 is 97.
4 // The largest prime smaller than 1000 is 997.
5 // The largest prime smaller than 10000 is 9973.
6 // The largest prime smaller than 100000 is 99991.
7 // The largest prime smaller than 1000000 is 999983.

```

```

8 // The largest prime smaller than 10000000 is 9999991.
9 // The largest prime smaller than 100000000 is 99999989.
10 // The largest prime smaller than 1000000000 is 999999937.
11 // The largest prime smaller than 10000000000 is 9999999967.
12 // The largest prime smaller than 100000000000 is 9999999977.
13 // The largest prime smaller than 1000000000000 is 99999999989.
14 // The largest prime smaller than 10000000000000 is 999999999971.
15 // The largest prime smaller than 100000000000000 is 9999999999973.
16 // The largest prime smaller than 1000000000000000 is 99999999999989.
17 // The largest prime smaller than 10000000000000000 is 999999999999937.
18 // The largest prime smaller than 100000000000000000 is 999999999999997.
19 // The largest prime smaller than 1000000000000000000 is 9999999999999989.

```

LatLon

```

1 /* Converts from rectangular coordinates to latitude/longitude and vice
2 versa. Uses degrees (not radians). */
3
4 struct ll {
5     double r, lat, lon;
6 };
7
8 struct rect {
9     double x, y, z;
10 };
11
12 ll convert(rect& P) {
13     ll Q;
14     Q.r = sqrt(P.x*P.x+P.y*P.y+P.z*P.z);
15     Q.lat = 180/M_PI*asin(P.z/Q.r);
16     Q.lon = 180/M_PI*acos(P.x/sqrt(P.x*P.x+P.y*P.y));
17
18     return Q;
19 }
20
21 rect convert(ll& Q) {
22     rect P;
23     P.x = Q.r*cos(Q.lon*M_PI/180)*cos(Q.lat*M_PI/180);
24     P.y = Q.r*sin(Q.lon*M_PI/180)*cos(Q.lat*M_PI/180);
25     P.z = Q.r*sin(Q.lat*M_PI/180);
26     return P;
27 }
28
29 int main() {
30     rect A;
31     ll B;
32
33     A.x = -1.0; A.y = 2.0; A.z = -3.0;
34
35     B = convert(A);
36     cout << B.r << " " << B.lat << " " << B.lon << endl;
37
38     A = convert(B);
39     cout << A.x << " " << A.y << " " << A.z << endl;
40 }

```

Theoretical Computer Science Cheat Sheet

Definitions		Series	
$f(n) = O(g(n))$	iff \exists positive c, n_0 such that $0 \leq f(n) \leq cg(n) \forall n \geq n_0$.	$\sum_{i=1}^n i = \frac{n(n+1)}{2}, \quad \sum_{i=1}^n i^2 = \frac{n(n+1)(2n+1)}{6}, \quad \sum_{i=1}^n i^3 = \frac{n^2(n+1)^2}{4}.$	
$f(n) = \Omega(g(n))$	iff \exists positive c, n_0 such that $f(n) \geq cg(n) \geq 0 \forall n \geq n_0$.	In general:	
$f(n) = \Theta(g(n))$	iff $f(n) = O(g(n))$ and $f(n) = \Omega(g(n))$.	$\sum_{i=1}^n i^m = \frac{1}{m+1} \left[(n+1)^{m+1} - 1 - \sum_{i=1}^n ((i+1)^{m+1} - i^{m+1} - (m+1)i^m) \right]$	
$f(n) = o(g(n))$	iff $\lim_{n \rightarrow \infty} f(n)/g(n) = 0$.	$\sum_{i=1}^{n-1} i^m = \frac{1}{m+1} \sum_{k=0}^m \binom{m+1}{k} B_k n^{m+1-k}.$	
$\lim_{n \rightarrow \infty} a_n = a$	iff $\forall \epsilon > 0, \exists n_0$ such that $ a_n - a < \epsilon, \forall n \geq n_0$.	Geometric series:	
$\sup S$	least $b \in \mathbb{R}$ such that $b \geq s, \forall s \in S$.	$\sum_{i=0}^n c^i = \frac{c^{n+1} - 1}{c - 1}, \quad c \neq 1, \quad \sum_{i=0}^{\infty} c^i = \frac{1}{1-c}, \quad \sum_{i=1}^{\infty} c^i = \frac{c}{1-c}, \quad c < 1,$	
$\inf S$	greatest $b \in \mathbb{R}$ such that $b \leq s, \forall s \in S$.	$\sum_{i=0}^n ic^i = \frac{nc^{n+2} - (n+1)c^{n+1} + c}{(c-1)^2}, \quad c \neq 1, \quad \sum_{i=0}^{\infty} ic^i = \frac{c}{(1-c)^2}, \quad c < 1.$	
$\liminf_{n \rightarrow \infty} a_n$	$\lim_{n \rightarrow \infty} \inf \{a_i \mid i \geq n, i \in \mathbb{N}\}.$	Harmonic series:	
$\limsup_{n \rightarrow \infty} a_n$	$\lim_{n \rightarrow \infty} \sup \{a_i \mid i \geq n, i \in \mathbb{N}\}.$	$H_n = \sum_{i=1}^n \frac{1}{i}, \quad \sum_{i=1}^n iH_i = \frac{n(n+1)}{2} H_n - \frac{n(n-1)}{4}.$	
$\binom{n}{k}$	Combinations: Size k sub-sets of a size n set.	$\sum_{i=1}^n H_i = (n+1)H_n - n, \quad \sum_{i=1}^n \binom{i}{m} H_i = \binom{n+1}{m+1} \left(H_{n+1} - \frac{1}{m+1} \right).$	
$\left[\begin{smallmatrix} n \\ k \end{smallmatrix} \right]$	Stirling numbers (1st kind): Arrangements of an n element set into k cycles.	1. $\binom{n}{k} = \frac{n!}{(n-k)!k!}, \quad 2. \sum_{k=0}^n \binom{n}{k} = 2^n, \quad 3. \binom{n}{k} = \binom{n}{n-k},$	
$\left\{ \begin{smallmatrix} n \\ k \end{smallmatrix} \right\}$	Stirling numbers (2nd kind): Partitions of an n element set into k non-empty sets.	4. $\binom{n}{k} = \frac{n}{k} \binom{n-1}{k-1}, \quad 5. \binom{n}{k} = \binom{n-1}{k} + \binom{n-1}{k-1},$	
$\langle \begin{smallmatrix} n \\ k \end{smallmatrix} \rangle$	1st order Eulerian numbers: Permutations $\pi_1 \pi_2 \dots \pi_n$ on $\{1, 2, \dots, n\}$ with k ascents.	6. $\binom{n}{m} \binom{m}{k} = \binom{n}{k} \binom{n-k}{m-k}, \quad 7. \sum_{k=0}^n \binom{r+k}{k} = \binom{r+n+1}{n},$	
$\langle\langle \begin{smallmatrix} n \\ k \end{smallmatrix} \rangle\rangle$	2nd order Eulerian numbers.	8. $\sum_{k=0}^n \binom{k}{m} = \binom{n+1}{m+1}, \quad 9. \sum_{k=0}^n \binom{r}{k} \binom{s}{n-k} = \binom{r+s}{n},$	
C_n	Catalan Numbers: Binary trees with $n+1$ vertices.	10. $\binom{n}{k} = (-1)^k \binom{k-n-1}{k}, \quad 11. \left\{ \begin{smallmatrix} n \\ 1 \end{smallmatrix} \right\} = \left\{ \begin{smallmatrix} n \\ n \end{smallmatrix} \right\} = 1,$	
14. $\left[\begin{smallmatrix} n \\ 1 \end{smallmatrix} \right] = (n-1)!,$	15. $\left[\begin{smallmatrix} n \\ 2 \end{smallmatrix} \right] = (n-1)!H_{n-1},$	16. $\left[\begin{smallmatrix} n \\ n \end{smallmatrix} \right] = 1,$	17. $\left[\begin{smallmatrix} n \\ k \end{smallmatrix} \right] \geq \left\{ \begin{smallmatrix} n \\ k \end{smallmatrix} \right\},$
18. $\left[\begin{smallmatrix} n \\ k \end{smallmatrix} \right] = (n-1) \left[\begin{smallmatrix} n-1 \\ k \end{smallmatrix} \right] + \left[\begin{smallmatrix} n-1 \\ k-1 \end{smallmatrix} \right],$	19. $\left\{ \begin{smallmatrix} n \\ n-1 \end{smallmatrix} \right\} = \left[\begin{smallmatrix} n \\ n-1 \end{smallmatrix} \right] = \binom{n}{2},$	20. $\sum_{k=0}^n \left[\begin{smallmatrix} n \\ k \end{smallmatrix} \right] = n!,$	21. $C_n = \frac{1}{n+1} \binom{2n}{n},$
22. $\langle \begin{smallmatrix} n \\ 0 \end{smallmatrix} \rangle = \langle \begin{smallmatrix} n \\ n-1 \end{smallmatrix} \rangle = 1,$	23. $\langle \begin{smallmatrix} n \\ k \end{smallmatrix} \rangle = \langle \begin{smallmatrix} n \\ n-1-k \end{smallmatrix} \rangle,$	24. $\langle \begin{smallmatrix} n \\ k \end{smallmatrix} \rangle = (k+1) \langle \begin{smallmatrix} n-1 \\ k \end{smallmatrix} \rangle + (n-k) \langle \begin{smallmatrix} n-1 \\ k-1 \end{smallmatrix} \rangle,$	
25. $\langle \begin{smallmatrix} 0 \\ k \end{smallmatrix} \rangle = \begin{cases} 1 & \text{if } k=0, \\ 0 & \text{otherwise} \end{cases}$	26. $\langle \begin{smallmatrix} n \\ 1 \end{smallmatrix} \rangle = 2^n - n - 1,$	27. $\langle \begin{smallmatrix} n \\ 2 \end{smallmatrix} \rangle = 3^n - (n+1)2^n + \binom{n+1}{2},$	
28. $x^n = \sum_{k=0}^n \langle \begin{smallmatrix} n \\ k \end{smallmatrix} \rangle \binom{x+k}{n},$	29. $\langle \begin{smallmatrix} n \\ m \end{smallmatrix} \rangle = \sum_{k=0}^m \binom{n+1}{k} (m+1-k)^n (-1)^k,$	30. $m! \left\{ \begin{smallmatrix} n \\ m \end{smallmatrix} \right\} = \sum_{k=0}^n \langle \begin{smallmatrix} n \\ k \end{smallmatrix} \rangle \binom{k}{n-m},$	
31. $\langle \begin{smallmatrix} n \\ m \end{smallmatrix} \rangle = \sum_{k=0}^n \left\{ \begin{smallmatrix} n \\ k \end{smallmatrix} \right\} \binom{n-k}{m} (-1)^{n-k-m} k!,$	32. $\langle\langle \begin{smallmatrix} n \\ 0 \end{smallmatrix} \rangle\rangle = 1,$	33. $\langle\langle \begin{smallmatrix} n \\ n \end{smallmatrix} \rangle\rangle = 0 \text{ for } n \neq 0,$	
34. $\langle\langle \begin{smallmatrix} n \\ k \end{smallmatrix} \rangle\rangle = (k+1) \langle\langle \begin{smallmatrix} n-1 \\ k \end{smallmatrix} \rangle\rangle + (2n-1-k) \langle\langle \begin{smallmatrix} n-1 \\ k-1 \end{smallmatrix} \rangle\rangle,$	35. $\sum_{k=0}^n \langle\langle \begin{smallmatrix} n \\ k \end{smallmatrix} \rangle\rangle = \frac{(2n)^n}{2^n},$	36. $\left\{ \begin{smallmatrix} x \\ x-n \end{smallmatrix} \right\} = \sum_{k=0}^n \langle\langle \begin{smallmatrix} n \\ k \end{smallmatrix} \rangle\rangle \binom{x+n-1-k}{2n},$	37. $\left\{ \begin{smallmatrix} n+1 \\ m+1 \end{smallmatrix} \right\} = \sum_k \binom{n}{k} \left\{ \begin{smallmatrix} k \\ m \end{smallmatrix} \right\} = \sum_{k=0}^n \left\{ \begin{smallmatrix} k \\ m \end{smallmatrix} \right\} (m+1)^{n-k},$

Theoretical Computer Science Cheat Sheet

Identities Cont.

$$\begin{aligned}
38. \quad \binom{n+1}{m+1} &= \sum_k \binom{n}{k} \binom{k}{m} = \sum_{k=0}^n \binom{k}{m} n^{\overline{n-k}} = n! \sum_{k=0}^n \frac{1}{k!} \binom{k}{m}, & 39. \quad \begin{bmatrix} x \\ x-n \end{bmatrix} &= \sum_{k=0}^n \left\langle \begin{matrix} n \\ k \end{matrix} \right\rangle \binom{x+k}{2n}, \\
40. \quad \left\{ \begin{matrix} n \\ m \end{matrix} \right\} &= \sum_k \binom{n}{k} \left\{ \begin{matrix} k+1 \\ m+1 \end{matrix} \right\} (-1)^{n-k}, & 41. \quad \begin{bmatrix} n \\ m \end{bmatrix} &= \sum_k \begin{bmatrix} n+1 \\ k+1 \end{bmatrix} \binom{k}{m} (-1)^{m-k}, \\
42. \quad \left\{ \begin{matrix} m+n+1 \\ m \end{matrix} \right\} &= \sum_{k=0}^m k \left\{ \begin{matrix} n+k \\ k \end{matrix} \right\}, & 43. \quad \begin{bmatrix} m+n+1 \\ m \end{bmatrix} &= \sum_{k=0}^m k(n+k) \begin{bmatrix} n+k \\ k \end{bmatrix}, \\
44. \quad \binom{n}{m} &= \sum_k \left\{ \begin{matrix} n+1 \\ k+1 \end{matrix} \right\} \begin{bmatrix} k \\ m \end{bmatrix} (-1)^{m-k}, & 45. \quad (n-m)! \binom{n}{m} &= \sum_k \begin{bmatrix} n+1 \\ k+1 \end{bmatrix} \left\{ \begin{matrix} k \\ m \end{matrix} \right\} (-1)^{m-k}, \quad \text{for } n \geq m, \\
46. \quad \left\{ \begin{matrix} n \\ n-m \end{matrix} \right\} &= \sum_k \binom{m-n}{m+k} \binom{m+n}{n+k} \begin{bmatrix} m+k \\ k \end{bmatrix}, & 47. \quad \begin{bmatrix} n \\ n-m \end{bmatrix} &= \sum_k \binom{m-n}{m+k} \binom{m+n}{n+k} \left\{ \begin{matrix} m+k \\ k \end{matrix} \right\}, \\
48. \quad \left\{ \begin{matrix} n \\ \ell+m \end{matrix} \right\} \binom{\ell+m}{\ell} &= \sum_k \left\{ \begin{matrix} k \\ \ell \end{matrix} \right\} \left\{ \begin{matrix} n-k \\ m \end{matrix} \right\} \binom{n}{k}, & 49. \quad \begin{bmatrix} n \\ \ell+m \end{bmatrix} \binom{\ell+m}{\ell} &= \sum_k \begin{bmatrix} k \\ \ell \end{bmatrix} \begin{bmatrix} n-k \\ m \end{bmatrix} \binom{n}{k}.
\end{aligned}$$

Trees

Every tree with n vertices has $n-1$ edges.

Kraft inequality: If the depths of the leaves of a binary tree are d_1, \dots, d_n :

$$\sum_{i=1}^n 2^{-d_i} \leq 1,$$

and equality holds only if every internal node has 2 sons.

Recurrences

Master method:

$$T(n) = aT(n/b) + f(n), \quad a \geq 1, b > 1$$

If $\exists \epsilon > 0$ such that $f(n) = O(n^{\log_b a - \epsilon})$ then

$$T(n) = \Theta(n^{\log_b a}).$$

If $f(n) = \Theta(n^{\log_b a})$ then

$$T(n) = \Theta(n^{\log_b a} \log_2 n).$$

If $\exists \epsilon > 0$ such that $f(n) = \Omega(n^{\log_b a + \epsilon})$, and $\exists c < 1$ such that $af(n/b) \leq cf(n)$ for large n , then

$$T(n) = \Theta(f(n)).$$

Substitution (example): Consider the following recurrence

$$T_{i+1} = 2^{2^i} \cdot T_i^2, \quad T_1 = 2.$$

Note that T_i is always a power of two.

Let $t_i = \log_2 T_i$. Then we have

$$t_{i+1} = 2^i + 2t_i, \quad t_1 = 1.$$

Let $u_i = t_i/2^i$. Dividing both sides of the previous equation by 2^{i+1} we get

$$\frac{t_{i+1}}{2^{i+1}} = \frac{2^i}{2^{i+1}} + \frac{t_i}{2^i}.$$

Substituting we find

$$u_{i+1} = \frac{1}{2} + u_i, \quad u_1 = \frac{1}{2},$$

which is simply $u_i = i/2$. So we find that T_i has the closed form $T_i = 2^{i2^{i-1}}$.

Summing factors (example): Consider the following recurrence

$$T(n) = 3T(n/2) + n, \quad T(1) = 1.$$

Rewrite so that all terms involving T are on the left side

$$T(n) - 3T(n/2) = n.$$

Now expand the recurrence, and choose a factor which makes the left side “telescope”

$$1(T(n) - 3T(n/2)) = n$$

$$3(T(n/2) - 3T(n/4)) = n/2$$

$$\vdots \quad \vdots \quad \vdots$$

$$3^{\log_2 n - 1} (T(2) - 3T(1)) = 2$$

Let $m = \log_2 n$. Summing the left side we get $T(n) - 3^m T(1) = T(n) - 3^m = T(n) - n^k$ where $k = \log_2 3 \approx 1.58496$.

Summing the right side we get

$$\sum_{i=0}^{m-1} \frac{n}{2^i} 3^i = n \sum_{i=0}^{m-1} \left(\frac{3}{2}\right)^i.$$

Let $c = \frac{3}{2}$. Then we have

$$n \sum_{i=0}^{m-1} c^i = n \left(\frac{c^m - 1}{c - 1} \right)$$

$$= 2n(c^{\log_2 n} - 1)$$

$$= 2n(c^{(k-1)\log_2 n} - 1)$$

$$= 2n^k - 2n,$$

and so $T(n) = 3n^k - 2n$. Full history recurrences can often be changed to limited history ones (example): Consider

$$T_i = 1 + \sum_{j=0}^{i-1} T_j, \quad T_0 = 1.$$

Note that

$$T_{i+1} = 1 + \sum_{j=0}^i T_j.$$

Subtracting we find

$$T_{i+1} - T_i = 1 + \sum_{j=0}^i T_j - 1 - \sum_{j=0}^{i-1} T_j$$

$$= T_i.$$

And so $T_{i+1} = 2T_i = 2^{i+1}$.

Generating functions:

1. Multiply both sides of the equation by x^i .
2. Sum both sides over all i for which the equation is valid.
3. Choose a generating function $G(x)$. Usually $G(x) = \sum_{i=0}^{\infty} x^i g_i$.
3. Rewrite the equation in terms of the generating function $G(x)$.
4. Solve for $G(x)$.
5. The coefficient of x^i in $G(x)$ is g_i .

Example:

$$g_{i+1} = 2g_i + 1, \quad g_0 = 0.$$

Multiply and sum:

$$\sum_{i \geq 0} g_{i+1} x^i = \sum_{i \geq 0} 2g_i x^i + \sum_{i \geq 0} x^i.$$

We choose $G(x) = \sum_{i \geq 0} x^i g_i$. Rewrite in terms of $G(x)$:

$$\frac{G(x) - g_0}{x} = 2G(x) + \sum_{i \geq 0} x^i.$$

Simplify:

$$\frac{G(x)}{x} = 2G(x) + \frac{1}{1-x}.$$

Solve for $G(x)$:

$$G(x) = \frac{x}{(1-x)(1-2x)}.$$

Expand this using partial fractions:


$$\begin{aligned}
G(x) &= x \left(\frac{2}{1-2x} - \frac{1}{1-x} \right) \\
&= x \left(2 \sum_{i \geq 0} 2^i x^i - \sum_{i \geq 0} x^i \right) \\
&= \sum_{i \geq 0} (2^{i+1} - 1) x^{i+1}.
\end{aligned}$$

So $g_i = 2^i - 1$.

Theoretical Computer Science Cheat Sheet					
$\pi \approx 3.14159,$		$e \approx 2.71828,$	$\gamma \approx 0.57721,$	$\phi = \frac{1+\sqrt{5}}{2} \approx 1.61803,$	$\hat{\phi} = \frac{1-\sqrt{5}}{2} \approx -.61803$
i	2^i	p_i	General	Probability	
1	2	2	Bernoulli Numbers ($B_i = 0$, odd $i \neq 1$):	Continuous distributions: If	
2	4	3	$B_0 = 1, B_1 = -\frac{1}{2}, B_2 = \frac{1}{6}, B_4 = -\frac{1}{30},$	$\Pr[a < X < b] = \int_a^b p(x) dx,$	
3	8	5	$B_6 = \frac{1}{42}, B_8 = -\frac{1}{30}, B_{10} = \frac{5}{66}.$	then p is the probability density function of X . If	
4	16	7	Change of base, quadratic formula:	$\Pr[X < a] = P(a),$	
5	32	11	$\log_b x = \frac{\log_a x}{\log_a b}, \quad \frac{-b \pm \sqrt{b^2 - 4ac}}{2a}.$	then P is the distribution function of X . If P and p both exist then	
6	64	13	Euler's number e :	$P(a) = \int_{-\infty}^a p(x) dx.$	
7	128	17	$e = 1 + \frac{1}{2} + \frac{1}{6} + \frac{1}{24} + \frac{1}{120} + \dots$	Expectation: If X is discrete	
8	256	19	$\lim_{n \rightarrow \infty} \left(1 + \frac{x}{n}\right)^n = e^x.$	$E[g(X)] = \sum_x g(x) \Pr[X = x].$	
9	512	23	$\left(1 + \frac{1}{n}\right)^n < e < \left(1 + \frac{1}{n}\right)^{n+1}.$	If X continuous then	
10	1,024	29	$\left(1 + \frac{1}{n}\right)^n = e - \frac{e}{2n} + \frac{11e}{24n^2} - O\left(\frac{1}{n^3}\right).$	$E[g(X)] = \int_{-\infty}^{\infty} g(x)p(x) dx = \int_{-\infty}^{\infty} g(x) dP(x).$	
11	2,048	31	Harmonic numbers:	Variance, standard deviation:	
12	4,096	37	$1, \frac{3}{2}, \frac{11}{6}, \frac{25}{12}, \frac{137}{60}, \frac{49}{20}, \frac{363}{140}, \frac{761}{280}, \frac{7129}{2520}, \dots$	$\text{VAR}[X] = E[X^2] - E[X]^2,$	
13	8,192	41	$\ln n < H_n < \ln n + 1,$	$\sigma = \sqrt{\text{VAR}[X]}.$	
14	16,384	43	$H_n = \ln n + \gamma + O\left(\frac{1}{n}\right).$	For events A and B :	
15	32,768	47	Factorial, Stirling's approximation:	$\Pr[A \vee B] = \Pr[A] + \Pr[B] - \Pr[A \wedge B]$	
16	65,536	53	$1, 2, 6, 24, 120, 720, 5040, 40320, 362880, \dots$	$\Pr[A \wedge B] = \Pr[A] \cdot \Pr[B],$	
17	131,072	59	$n! = \sqrt{2\pi n} \left(\frac{n}{e}\right)^n \left(1 + \Theta\left(\frac{1}{n}\right)\right).$	iff A and B are independent.	
18	262,144	61	Ackermann's function and inverse:	$\Pr[A B] = \frac{\Pr[A \wedge B]}{\Pr[B]}$	
19	524,288	67	$a(i, j) = \begin{cases} 2^j & i = 1 \\ a(i-1, 2) & j = 1 \\ a(i-1, a(i, j-1)) & i, j \geq 2 \end{cases}$	For random variables X and Y :	
20	1,048,576	71	$\alpha(i) = \min\{j \mid a(j, j) \geq i\}.$	$E[X \cdot Y] = E[X] \cdot E[Y],$	
21	2,097,152	73	Binomial distribution:	if X and Y are independent.	
22	4,194,304	79	$\Pr[X = k] = \binom{n}{k} p^k q^{n-k}, \quad q = 1 - p,$	$E[X + Y] = E[X] + E[Y],$	
23	8,388,608	83	$E[X] = \sum_{k=1}^n k \binom{n}{k} p^k q^{n-k} = np.$	$E[cX] = c E[X].$	
24	16,777,216	89	Poisson distribution:	Bayes' theorem:	
25	33,554,432	97	$\Pr[X = k] = \frac{e^{-\lambda} \lambda^k}{k!}, \quad E[X] = \lambda.$	$\Pr[A_i B] = \frac{\Pr[B A_i] \Pr[A_i]}{\sum_{j=1}^n \Pr[A_j] \Pr[B A_j]}.$	
26	67,108,864	101	Normal (Gaussian) distribution:	Inclusion-exclusion:	
27	134,217,728	103	$p(x) = \frac{1}{\sqrt{2\pi}\sigma} e^{-(x-\mu)^2/2\sigma^2}, \quad E[X] = \mu.$	$\Pr\left[\bigvee_{i=1}^n X_i\right] = \sum_{i=1}^n \Pr[X_i] +$	
28	268,435,456	107	The "coupon collector": We are given a random coupon each day, and there are n different types of coupons. The distribution of coupons is uniform. The expected number of days to pass before we to collect all n types is	$\sum_{k=2}^n (-1)^{k+1} \sum_{i_1 < \dots < i_k} \Pr\left[\bigwedge_{j=1}^k X_{i_j}\right].$	
29	536,870,912	109	$nH_n.$	Moment inequalities:	
30	1,073,741,824	113		$\Pr[X \geq \lambda E[X]] \leq \frac{1}{\lambda},$	
31	2,147,483,648	127		$\Pr[X - E[X] \geq \lambda \cdot \sigma] \leq \frac{1}{\lambda^2}.$	
32	4,294,967,296	131		Geometric distribution:	
Pascal's Triangle				$\Pr[X = k] = pq^{k-1}, \quad q = 1 - p,$	
1				$E[X] = \sum_{k=1}^{\infty} kpq^{k-1} = \frac{1}{p}.$	
1 1					
1 2 1					
1 3 3 1					
1 4 6 4 1					
1 5 10 10 5 1					
1 6 15 20 15 6 1					
1 7 21 35 35 21 7 1					
1 8 28 56 70 56 28 8 1					
1 9 36 84 126 126 84 36 9 1					
1 10 45 120 210 252 210 120 45 10 1					

Theoretical Computer Science Cheat Sheet

Trigonometry



Pythagorean theorem:

$$C^2 = A^2 + B^2.$$

Definitions:

$$\sin a = A/C, \quad \cos a = B/C,$$

$$\csc a = C/A, \quad \sec a = C/B,$$

$$\tan a = \frac{\sin a}{\cos a} = \frac{A}{B}, \quad \cot a = \frac{\cos a}{\sin a} = \frac{B}{A}.$$

Area, radius of inscribed circle:

$$\frac{1}{2}AB, \quad \frac{AB}{A+B+C}.$$

Identities:

$$\sin x = \frac{1}{\csc x}, \quad \cos x = \frac{1}{\sec x},$$

$$\tan x = \frac{1}{\cot x}, \quad \sin^2 x + \cos^2 x = 1,$$

$$1 + \tan^2 x = \sec^2 x, \quad 1 + \cot^2 x = \csc^2 x,$$

$$\sin x = \cos\left(\frac{\pi}{2} - x\right), \quad \sin x = \sin(\pi - x),$$

$$\cos x = -\cos(\pi - x), \quad \tan x = \cot\left(\frac{\pi}{2} - x\right),$$

$$\cot x = -\cot(\pi - x), \quad \csc x = \cot \frac{\pi}{2} - \cot x,$$

$$\sin(x \pm y) = \sin x \cos y \pm \cos x \sin y,$$

$$\cos(x \pm y) = \cos x \cos y \mp \sin x \sin y,$$

$$\tan(x \pm y) = \frac{\tan x \pm \tan y}{1 \mp \tan x \tan y},$$

$$\cot(x \pm y) = \frac{\cot x \cot y \mp 1}{\cot x \pm \cot y},$$

$$\sin 2x = 2 \sin x \cos x, \quad \sin 2x = \frac{2 \tan x}{1 + \tan^2 x},$$

$$\cos 2x = \cos^2 x - \sin^2 x, \quad \cos 2x = 2 \cos^2 x - 1,$$

$$\cos 2x = 1 - 2 \sin^2 x, \quad \cos 2x = \frac{1 - \tan^2 x}{1 + \tan^2 x},$$

$$\tan 2x = \frac{2 \tan x}{1 - \tan^2 x}, \quad \cot 2x = \frac{\cot^2 x - 1}{2 \cot x},$$

$$\sin(x + y) \sin(x - y) = \sin^2 x - \sin^2 y,$$

$$\cos(x + y) \cos(x - y) = \cos^2 x - \sin^2 y.$$

Euler's equation:

$$e^{ix} = \cos x + i \sin x, \quad e^{i\pi} = -1.$$

Matrices

Multiplication:

$$C = A \cdot B, \quad c_{i,j} = \sum_{k=1}^n a_{i,k} b_{k,j}.$$

Determinants: $\det A \neq 0$ iff A is non-singular.

$$\det A \cdot B = \det A \cdot \det B,$$

$$\det A = \sum_{\pi} \prod_{i=1}^n \text{sign}(\pi) a_{i,\pi(i)}.$$

2×2 and 3×3 determinant:

$$\begin{vmatrix} a & b \\ c & d \end{vmatrix} = ad - bc,$$

$$\begin{vmatrix} a & b & c \\ d & e & f \\ g & h & i \end{vmatrix} = g \begin{vmatrix} a & b \\ d & e \end{vmatrix} - h \begin{vmatrix} a & c \\ d & f \end{vmatrix} + i \begin{vmatrix} a & b \\ d & e \end{vmatrix}$$

$$= aei + bfg + cdh - ceg - fha - ibd.$$

Permanents:

$$\text{perm } A = \sum_{\pi} \prod_{i=1}^n a_{i,\pi(i)}.$$

Hyperbolic Functions

Definitions:

$$\sinh x = \frac{e^x - e^{-x}}{2}, \quad \cosh x = \frac{e^x + e^{-x}}{2},$$

$$\tanh x = \frac{e^x - e^{-x}}{e^x + e^{-x}}, \quad \text{csch } x = \frac{1}{\sinh x},$$

$$\text{sech } x = \frac{1}{\cosh x}, \quad \coth x = \frac{1}{\tanh x}.$$

Identities:

$$\cosh^2 x - \sinh^2 x = 1, \quad \tanh^2 x + \text{sech}^2 x = 1,$$

$$\coth^2 x - \text{csch}^2 x = 1, \quad \sinh(-x) = -\sinh x,$$

$$\cosh(-x) = \cosh x, \quad \tanh(-x) = -\tanh x,$$

$$\sinh(x + y) = \sinh x \cosh y + \cosh x \sinh y,$$

$$\cosh(x + y) = \cosh x \cosh y + \sinh x \sinh y,$$

$$\sinh 2x = 2 \sinh x \cosh x,$$

$$\cosh 2x = \cosh^2 x + \sinh^2 x,$$

$$\cosh x + \sinh x = e^x, \quad \cosh x - \sinh x = e^{-x},$$

$$(\cosh x + \sinh x)^n = \cosh nx + \sinh nx, \quad n \in \mathbb{Z},$$


$$2 \sinh^2 \frac{x}{2} = \cosh x - 1, \quad 2 \cosh^2 \frac{x}{2} = \cosh x + 1.$$

θ	$\sin \theta$	$\cos \theta$	$\tan \theta$
0	0	1	0
$\frac{\pi}{6}$	$\frac{1}{2}$	$\frac{\sqrt{3}}{2}$	$\frac{\sqrt{3}}{3}$
$\frac{\pi}{4}$	$\frac{\sqrt{2}}{2}$	$\frac{\sqrt{2}}{2}$	1
$\frac{\pi}{3}$	$\frac{\sqrt{3}}{2}$	$\frac{1}{2}$	$\sqrt{3}$
$\frac{\pi}{2}$	1	0	∞

... in mathematics you don't understand things, you just get used to them.

– J. von Neumann

More Trig.



Law of cosines:

$$c^2 = a^2 + b^2 - 2ab \cos C.$$

Area:

$$A = \frac{1}{2}hc, \\ = \frac{1}{2}ab \sin C, \\ = \frac{c^2 \sin A \sin B}{2 \sin C}.$$

Heron's formula:

$$A = \sqrt{s \cdot s_a \cdot s_b \cdot s_c}, \\ s = \frac{1}{2}(a + b + c), \\ s_a = s - a, \\ s_b = s - b, \\ s_c = s - c.$$

More identities:

$$\sin \frac{x}{2} = \sqrt{\frac{1 - \cos x}{2}},$$

$$\cos \frac{x}{2} = \sqrt{\frac{1 + \cos x}{2}},$$

$$\tan \frac{x}{2} = \sqrt{\frac{1 - \cos x}{1 + \cos x}},$$

$$= \frac{1 - \cos x}{\sin x},$$

$$= \frac{\sin x}{1 + \cos x},$$

$$\cot \frac{x}{2} = \sqrt{\frac{1 + \cos x}{1 - \cos x}},$$

$$= \frac{1 + \cos x}{\sin x},$$

$$= \frac{\sin x}{1 - \cos x},$$

$$\sin x = \frac{e^{ix} - e^{-ix}}{2i},$$

$$\cos x = \frac{e^{ix} + e^{-ix}}{2},$$

$$\tan x = -i \frac{e^{ix} - e^{-ix}}{e^{ix} + e^{-ix}},$$

$$= -i \frac{e^{2ix} - 1}{e^{2ix} + 1},$$

$$\sin x = \frac{\sinh ix}{i},$$

$$\cos x = \cosh ix,$$

$$\tan x = \frac{\tanh ix}{i}.$$

v2.02 ©1994 by Steve Seiden

sseiden@acm.org

<http://www.csc.lsu.edu/~seiden>

Theoretical Computer Science Cheat Sheet

Number Theory

The Chinese remainder theorem: There exists a number C such that:

$$C \equiv r_1 \pmod{m_1}$$

$$\vdots \quad \vdots \quad \vdots$$

$$C \equiv r_n \pmod{m_n}$$

if m_i and m_j are relatively prime for $i \neq j$.

Euler's function: $\phi(x)$ is the number of positive integers less than x relatively prime to x . If $\prod_{i=1}^n p_i^{e_i}$ is the prime factorization of x then

$$\phi(x) = \prod_{i=1}^n p_i^{e_i-1} (p_i - 1).$$

Euler's theorem: If a and b are relatively prime then

$$1 \equiv a^{\phi(b)} \pmod{b}.$$

Fermat's theorem:

$$1 \equiv a^{p-1} \pmod{p}.$$

The Euclidean algorithm: if $a > b$ are integers then

$$\gcd(a, b) = \gcd(a \bmod b, b).$$

If $\prod_{i=1}^n p_i^{e_i}$ is the prime factorization of x then

$$S(x) = \sum_{d|x} d = \prod_{i=1}^n \frac{p_i^{e_i+1} - 1}{p_i - 1}.$$

Perfect Numbers: x is an even perfect number iff $x = 2^{n-1}(2^n - 1)$ and $2^n - 1$ is prime.

Wilson's theorem: n is a prime iff

$$(n-1)! \equiv -1 \pmod{n}.$$

Möbius inversion:

$$\mu(i) = \begin{cases} 1 & \text{if } i = 1. \\ 0 & \text{if } i \text{ is not square-free.} \\ (-1)^r & \text{if } i \text{ is the product of } r \text{ distinct primes.} \end{cases}$$

If

$$G(a) = \sum_{d|a} F(d),$$

then

$$F(a) = \sum_{d|a} \mu(d) G\left(\frac{a}{d}\right).$$

Prime numbers:

$$p_n = n \ln n + n \ln \ln n - n + n \frac{\ln \ln n}{\ln n}$$

$$+ O\left(\frac{n}{\ln n}\right),$$

$$\pi(n) = \frac{n}{\ln n} + \frac{n}{(\ln n)^2} + \frac{2!n}{(\ln n)^3}$$

$$+ O\left(\frac{n}{(\ln n)^4}\right).$$

Graph Theory

Definitions:

Loop An edge connecting a vertex to itself.

Directed Each edge has a direction.

Simple Graph with no loops or multi-edges.

Walk A sequence $v_0 e_1 v_1 \dots e_\ell v_\ell$.

Trail A walk with distinct edges.

Path A trail with distinct vertices.

Connected A graph where there exists a path between any two vertices.

Component A maximal connected subgraph.

Tree A connected acyclic graph.

Free tree A tree with no root.

DAG Directed acyclic graph.

Eulerian Graph with a trail visiting each edge exactly once.

Hamiltonian Graph with a cycle visiting each vertex exactly once.

Cut A set of edges whose removal increases the number of components.

Cut-set A minimal cut.

Cut edge A size 1 cut.

k-Connected A graph connected with the removal of any $k-1$ vertices.

k-Tough $\forall S \subseteq V, S \neq \emptyset$ we have $k \cdot c(G-S) \leq |S|$.

k-Regular A graph where all vertices have degree k .

k-Factor A k -regular spanning subgraph.

Matching A set of edges, no two of which are adjacent.

Clique A set of vertices, all of which are adjacent.

Ind. set A set of vertices, none of which are adjacent.

Vertex cover A set of vertices which cover all edges.

Planar graph A graph which can be embedded in the plane.

Plane graph An embedding of a planar graph.

$$\sum_{v \in V} \deg(v) = 2m.$$

If G is planar then $n - m + f = 2$, so

$$f \leq 2n - 4, \quad m \leq 3n - 6.$$

Any planar graph has a vertex with degree ≤ 5 .

Notation:

$E(G)$ Edge set

$V(G)$ Vertex set

$c(G)$ Number of components

$G[S]$ Induced subgraph

$\deg(v)$ Degree of v

$\Delta(G)$ Maximum degree

$\delta(G)$ Minimum degree

$\chi(G)$ Chromatic number

$\chi_E(G)$ Edge chromatic number

G^c Complement graph

K_n Complete graph

K_{n_1, n_2} Complete bipartite graph

$r(k, \ell)$ Ramsey number

Geometry

Projective coordinates: triples (x, y, z) , not all x, y and z zero.

$$(x, y, z) = (cx, cy, cz) \quad \forall c \neq 0.$$

Cartesian Projective

$$(x, y) \quad (x, y, 1)$$

$$y = mx + b \quad (m, -1, b)$$

$$x = c \quad (1, 0, -c)$$

Distance formula, L_p and L_∞ metric:

$$\sqrt{(x_1 - x_0)^2 + (y_1 - y_0)^2},$$


$$[|x_1 - x_0|^p + |y_1 - y_0|^p]^{1/p},$$

$$\lim_{p \rightarrow \infty} [|x_1 - x_0|^p + |y_1 - y_0|^p]^{1/p}.$$

Area of triangle (x_0, y_0) , (x_1, y_1) and (x_2, y_2) :

$$\frac{1}{2} \text{abs} \begin{vmatrix} x_1 - x_0 & y_1 - y_0 \\ x_2 - x_0 & y_2 - y_0 \end{vmatrix}.$$

Angle formed by three points:



$$\cos \theta = \frac{(x_1, y_1) \cdot (x_2, y_2)}{\ell_1 \ell_2}.$$

Line through two points (x_0, y_0) and (x_1, y_1) :

$$\begin{vmatrix} x & y & 1 \\ x_0 & y_0 & 1 \\ x_1 & y_1 & 1 \end{vmatrix} = 0.$$

Area of circle, volume of sphere:

$$A = \pi r^2, \quad V = \frac{4}{3} \pi r^3.$$

If I have seen farther than others, it is because I have stood on the shoulders of giants.

– Issac Newton