

Computational Thinking and Algorithms

159.172


Linked Lists

Amjed Tahir
a.tahir@massey.ac.nz

Previous contributors: Catherine McCartin

Linked lists

A Python list, implemented using an array, provides **constant time** access to a cell by specifying its index.




Linked lists

Inserting at the beginning of an array with n elements takes time $\mathbf{O(n)}$, all elements must move over by one.




Linked lists

Inserting at the beginning of an array with n elements takes time $\mathbf{O(n)}$, all elements must move over by one.




Linked lists

Inserting at the beginning of an array with n elements takes time $\mathbf{O(n)}$, all elements must move over by one.



Linked lists

Deleting the first element of an array with n elements also takes time $\mathbf{O(n)}$, all elements must move **back** by one.




Linked lists

A linked list provides **constant time** insertions and deletions, but accessing an element can take **$O(n)$** time in the worst case.

We use a node structure with a data field (sometimes called the data/cargo) and a **next** field that references the next node in the list.

The next field of the last node has the special value **null** (None).





Linked lists

A linked list is a **recursive data structure**.

A linked list is either:

- the empty list, represented by None, or
- a node that contains a cargo object and a reference to a linked list.




Python Node class

```
class Node:
    def __init__(self, cargo=None, next=None):
        # optional parameters
        self.cargo = cargo
        self.next = next

    def __str__(self):
        #defines a string representation of a Node object
        return str(self.cargo)
```

Python Node class

```
>>> node = Node("test")  
>>> print (node)  
test
```



traversing a list


start at the “head” of the list, traverse it until we reach a nil reference

```
def traverseList(node):  
    current_node = node  
    while current_node is not None:  
        print (current_node)  
        current_node = current_node.next
```

to invoke this function, we pass a reference to the first node:


```
>>> traverseList(node1)
```

1 2 3




traversing a list

```
def traverseList(node):  
    current_node = node  
    while current_node is not None:  
        print(current_node)  
        current_node = current_node.next
```




traversing a list

```
def traverseList(node):  
    current_node = node  
    while current_node is not None:  
        print(current_node)  
        current_node = current_node.next
```



traversing a list


```
def traverseList(node):  
    current_node = node  
    while current_node is not None:  
        print(current_node)  
        current_node = current_node.next
```



traversing a list

```
def traverseList(node):  
    current_node = node  
    while current_node is not None:  
        print(current_node)  
        current_node = current_node.next
```

current_node is None



Lists and recursion

To print a list backwards:


1. separate the list into two pieces:
the first node (called the head); and the rest (called the tail).
1. print the tail backward.
2. print the head.

```
def printBackward(thelist):  
    if thelist == None:    # base case  
        return  
    head = thelist  
    tail = thelist.next  
    printBackward(tail)    # recursive call  
    print (head)
```


Lists and recursion

```
def printBackward(thelist):  
    if thelist == None:    # base case  
        return  
    head = thelist  
    tail = thelist.next  
    printBackward(tail)    # recursive call  
    print (head, end= '')
```


```
>>> printBackward(node1)  
3 2 1
```



Lists and recursion

```
def printBackward(thelist):  
    if thelist == None:    # base case  
        return  
    head = thelist  
    tail = thelist.next  
    printBackward(tail)    # recursive call  
    print(head, end= ' ')
```

```
>>> printBackward(node1)  
3 2 1
```




Lists and recursion

```
def printBackward(thelist):  
    if thelist == None:    # base case  
        return  
    head = thelist  
    tail = thelist.next  
    printBackward(tail)    # recursive call  
    print(head, end = ' ')
```

```
>>> printBackward(node1)
```


```
3 2 1
```



Searching for an item

```
def searchList(node, target):  
    current_node = node  
    while current_node is not None and current_node.cargo != target:  
        current_node = current_node.next  
    if current_node is not None: # WHAT'S A BETTER WAY TO WRITE THIS  
        return True  
    else:  
        return False
```

```
>>> searchList(node1, "3")  
True
```




Searching for an item

```
def searchList(node, target):  
    current_node = node  
    while current_node is not None and current_node.cargo != target:  
        current_node = current_node.next  
    return current_node is not None
```

```
>>> searchList(node1, "3")
```

```
True
```



recursive version

```
def searchList(node, target):  
    if node is None:                # base case  
        return False  
    if node.cargo == target:        # base case  
        return True  
    return searchList(node.next, target) # recursive case
```

```
# BUILD A LIST  
node1 = Node(1)  
node2 = Node(2)  
node3 = Node("dog")  
node1.next = node2  
node2.next = node3
```

```
>>> print searchList(node1, "dog")  
True  
>>> print searchList(node1, 2)  
True  
>>> print searchList(node1, 5)  
False
```

The Linked List class


How can we easily:

- add items to a linked list?
- delete items from a linked list?

We **really** need is a class that creates and manipulates lists of linked Node objects.

```
class LinkedList:  
    def __init__(self):  
        self.length = 0  
        self.head = None
```

```
>>> myList = LinkedList()
```



The Linked List class

addFirst(item) takes an item of cargo as an argument and puts it in a node at the beginning of the list:


```
class LinkedList:
    def __init__(self):
        self.length = 0
        self.head = None

    def addFirst(self, cargo):
        node = Node(cargo)
        node.next = self.head
        self.head = node
        self.length = self.length + 1
```


The Linked List class

```
def addFirst(self, cargo):  
    node = Node(cargo)  
    node.next = self.head  
    self.head = node  
    self.length = self.length + 1
```


```
>>> myList.addFirst(20)
```



The Linked List class

```
def addFirst(self, cargo):  
    node = Node(cargo)  
    node.next = self.head  
    self.head = node  
    self.length = self.length + 1
```


```
>>> myList.addFirst(20)
```



The Linked List class

```
def addFirst(self, cargo):  
    node = Node(cargo)  
    node.next = self.head  
    self.head = node  
    self.length = self.length + 1
```

```
>>> myList.addFirst(20)
```




The Linked List class

Remove a node from the beginning of linked list, return cargo value:

```
def removeFirst(self):  
    cargo = self.head.cargo  
    self.head = self.head.next  
    self.length = self.length - 1  
    return cargo
```

```
>>> listval = myList.removeFirst()
```




The Linked List class

Remove a node from the beginning of linked list, return cargo value:

```
def removeFirst(self):  
    cargo = self.head.cargo  
    self.head = self.head.next  
    self.length = self.length - 1  
    return cargo
```

```
>>> listval = myList.removeFirst()
```




The Linked List class

Remove a node from the beginning of linked list, return cargo value:

```
def removeFirst(self):  
    cargo = self.head.cargo  
    self.head = self.head.next  
    self.length = self.length - 1  
    return cargo
```

```
>>> listval = myList.removeFirst()
```




The Linked List class

Remove a node from the beginning of linked list, return cargo value:

```
def removeFirst(self):  
    cargo = self.head.cargo  
    self.head = self.head.next  
    self.length = self.length - 1  
    return cargo
```

```
>>> listval = myList.removeFirst()
```



The Linked List class

Adding an item to the end of a linked list?

```
def insertLast(self, cargo):  
    node = Node(cargo)  
    node.next = None  
    # if list is empty the new node goes first  
    if self.head == None:  
        self.head = node  
    else:  
        last = self.head      # find the last node in the list  
        while last.next is not None:  
            last = last.next  
        # append the new node  
        last.next = node  
    self.length = self.length + 1
```


The Linked List class

Adding an item to the end of a linked list?

```
>>> mylist.insertLast(20)
```


```
node = Node(cargo)
```

```
node.next = None
```

```
if self.head == None:
```

```
    # if list is empty the new node goes first
```

```
    self.head = node
```



The Linked List class

Adding an item to the end of a linked list?

```
>>> mylist.insertLast(20)
```



```
node = Node(cargo)
```

```
node.next = None
```

```
if self.head == None:
```

```
    # if list is empty the new node goes first
```

```
    self.head = node
```



The Linked List class

Adding an item to the end of a linked list?

```
>>> mylist.insertLast(20)
```


```
node = Node(cargo)
```

```
node.next = None
```

```
if self.head == None:
```

```
    # if list is empty the new node goes first
```

```
    self.head = node
```



The Linked List class

Adding an item to the end of a linked list?

else:

find the last node in the list

last = self.head


while last.next is not None:

last = last.next

append the new node

last.next = node

self.length = self.length + 1



The Linked List class

Adding an item to the end of a linked list?

else:

find the last node in the list

last = self.head


while last.next is not None:

last = last.next

append the new node

last.next = node

self.length = self.length + 1



The Linked List class

Adding an item to the end of a linked list?

else:

find the last node in the list

last = self.head


while last.next is not None:

last = last.next

append the new node

last.next = node

self.length = self.length + 1



The Linked List class

Adding an item to the end of a linked list?

else:

find the last node in the list

last = self.head


while last.next is not None:

last = last.next

append the new node

last.next = node

self.length = self.length + 1



The Linked List class

Adding an item to the end of a linked list?

else:

find the last node in the list

last = self.head


while last.next is not None:

last = last.next

append the new node

last.next = node

self.length = self.length + 1



The Queue ADT

The Queue ADT is defined by the following operations:

__init__()

Initialize a new empty queue.

insert(new_item) or sometimes **enqueue(new_item)**

Add a new item to the queue.

remove() or sometimes **dequeue()**

Remove and return an item from the queue.

The item that is returned is the first one that was added.

isEmpty()

Check whether the queue is empty.

Linked list implementation

```
class Queue:  
    def __init__(self):  
        self.length = 0  
        self.head = None  
  
    def isEmpty(self):  
        return (self.length == 0)
```

Queue Linked list implementation

```
def insert(self, cargo):  
    # same as insertLast() for Linked Lists  
    node = Node(cargo)  
    node.next = None  
    if self.head == None:  
        # if queue is empty the new node goes first  
        self.head = node  
    else:  
        # find the last node in the queue  
        last = self.head  
        while last.next is not None:      # MIGHT TAKE A LONG TIME  
            last = last.next  
        # append the new node  
        last.next = node  
    self.length = self.length + 1
```

Queue Linked list implementation

```
def remove(self):  
    # same as removeFirst() for Linked Lists  
    cargo = self.head.cargo  
    self.head = self.head.next  
    self.length = self.length - 1  
    return cargo
```

Improved linked Queue

We can improve the performance of the insert method if we modify the Queue class so that it maintains a reference to both the first and the **last** node.

```
class ImprovedQueue:
    def __init__(self):
        self.length = 0
        self.head    = None
        self.last    = None

    def isEmpty(self):
        return (self.length == 0)
```

Improved linked Queue

```
def insert(self, cargo):
    node = Node(cargo)
    node.next = None
    if self.length == 0:
        # if list is empty, the new node is head and last
        self.head = self.last = node
    else:
        # find the last node
        last = self.last
        # append the new node
        last.next = node
        self.last = node
    self.length = self.length + 1
```

Improved linked Queue

Adding an item to the end of a Queue?

```
>>> myQueue.insert(20)
```


```
node = Node(cargo)
```

```
node.next = None
```

```
if self.length == 0:
```

```
    # if list is empty, the new node is head and last
```

```
    self.head = self.last = node
```



Improved linked Queue

Adding an item to the end of a Queue?

```
>>> myQueue.insert(20)
```




```
node = Node(cargo)
```

```
node.next = None
```

```
if self.length == 0:
```

```
    # if list is empty, the new node is head and last
```

```
    self.head = self.last = node
```



Improved linked Queue

Adding an item to the end of a Queue?

```
>>> myQueue.insert(20)
```


```
node = Node(cargo)
```

```
node.next = None
```

```
if self.length == 0:
```

```
    # if list is empty, the new node is head and last
```

```
    self.head = self.last = node
```



Improved linked Queue

Adding an item to the end of a Queue?

else:

find the last node


last = self.last

append the new node

last.next = node

self.last = node

self.length = self.length + 1



Improved linked Queue

Adding an item to the end of a Queue?

else:

find the last node


last = self.last

append the new node

last.next = node


self.last = node

self.length = self.length + 1




Improved linked Queue

```
def remove(self):  
    cargo      = self.head.cargo  
    self.head = self.head.next  
    self.length = self.length - 1  
    # if list becomes empty, last must be set to None  
    if self.length == 0:  
        self.last = None  
    return cargo
```




Improved linked Queue

```
def remove(self):  
    cargo      = self.head.cargo  
    self.head = self.head.next  
    self.length = self.length - 1  
    # if list becomes empty, last must be set to None  
    if self.length == 0:  
        self.last = None  
    return cargo
```




Improved linked Queue

```
def remove(self):  
    cargo      = self.head.cargo  
    self.head = self.head.next  
    self.length = self.length - 1  
    # if list becomes empty, last must be set to None  
    if self.length == 0:  
        self.last = None  
    return cargo
```



Improved linked Queue

```
def remove(self):  
    cargo      = self.head.cargo  
    self.head = self.head.next  
    self.length = self.length - 1  
    # if list becomes empty, last must be set to None  
    if self.length == 0:  
        self.last = None  
    return cargo
```



Improved linked Queue

```
def remove(self):  
    cargo      = self.head.cargo  
    self.head = self.head.next  
    self.length = self.length - 1  
    # if list becomes empty, last must be set to None  
    if self.length == 0:  
        self.last = None  
    return cargo
```

