

Translating SQL Queries to Relational Algebra Expressions

Edited by: Muazzam Siddiqui

Original slides by: Dirk Van Gucht

Outline

- **Objective:** Discuss an algorithm that translates a SQL query into an equivalent RA expression
- **Motivation:** Translate a declaratively specified query into a procedurally specified query
- **Restriction:** We do not attempt to get an efficient RA expression. Finding an equivalent efficient RA expression is done during **query optimization**

Strategy

- SQL queries with set predicates will be translated to equivalent SQL queries without set predicates
- WHERE conditions will be eliminated by translating them into FROM clauses using selections and join operations, or by decomposing them into more basic components (then translate these) and then use the set operations union, intersection, and set difference
- These SQL queries will then be translated into RA expressions

Query Forms (Basic case)

```
SELECT  [DISTINCT]  $L(t_1, \dots, t_n)$   
FROM     $R_1 t_1, \dots, R_n t_n$   
WHERE    $C(t_1, \dots, t_n)$ 
```

$L(t_1, \dots, t_n)$ is a list of (named) components of the tuple

- variables t_1 through t_n ¹

R_1 through R_n are either relations or **non-parameterized**

- SQL queries aliased by the tuple variables t_1 through t_n

$C(t_1, \dots, t_n)$ is any valid SQL condition involving the

- components of the variables t_1 through t_n

We do not handle SQL queries with aggregate functions or

- queries with subqueries in the FROM clause

¹There may also appear constants in L ; these need special treatment

Query Forms (queries with set operations)

Assuming that Q , Q_1 , and Q_2 are SQL queries, we consider the following SQL query forms

Q_1
UNION
 Q_2

Q_1
INTERSECT
 Q_2

Q_1
EXCEPT
 Q_2
(Q)

Discussion: interaction between projection π and set operations \cup , \cap , and $-$

- Before we can start with the translation algorithm, it is crucial to discuss how the projection operator π interacts with the set operations \cup , \cap , and $-$.
- Understanding this is vital for the correct translations of SQL **WHERE** clauses that use the **OR**, **AND**, and **NOT** boolean operations
- We will consider the following interactions:
 - Projection π and union \cup
 - Projection π and intersection \cap
 - Projection π and set difference $-$

Projection π distributes over \cup

Given RA expressions E_1 and E_2 , it is the case that

$$\pi_L(E_1 \cup E_2) = \pi_L(E_1) \cup \pi_L(E_2)$$

An application of this is the following: (C_1 and C_2 are some conditions)

$$\pi_L(\sigma_{C_1 \vee C_2}(E)) = \pi_L(\sigma_{C_1}(E) \cup \sigma_{C_2}(E)) = \pi_L(\sigma_{C_1}(E)) \cup \pi_L(\sigma_{C_2}(E))$$

Translating **OR** in **WHERE** clause

```
SELECT   $L(t_1, \dots, t_n)$   
FROM     $R_1 t_1, \dots, R_n t_n$   
WHERE    $C_1(t_1, \dots, t_n)$  OR  $C_2(t_1, \dots, t_n)$ 
```

can be translated to become

```
SELECT   $L(t_1, \dots, t_n)$   
FROM     $R_1 t_1, \dots, R_n t_n$   
WHERE    $C_1(t_1, \dots, t_n)$   
UNION  
SELECT   $L(t_1, \dots, t_n)$   
FROM     $R_1 t_1, \dots, R_n t_n$   
WHERE    $C_2(t_1, \dots, t_n)$ 
```


Projection π does not distributes over \cap

Given RA expressions E_1 and E_2 , it is the case that

$$\pi_L(E_1 \cap E_2) \subseteq \pi_L(E_1) \cap \pi_L(E_2)$$

But there exist cases where

$$\pi_L(E_1 \cap E_2) \neq \pi_L(E_1) \cap \pi_L(E_2)$$

This complexity features in reasoning about the expression $\pi_L(\sigma_{C_1 \wedge C_2}(E))$ since

$$\pi_L(\sigma_{C_1 \wedge C_2}(E)) = \pi_L(\sigma_{C_1}(E) \cap \sigma_{C_2}(E)) \subseteq \pi_L(\sigma_{C_1}(E)) \cap \pi_L(\sigma_{C_2}(E))$$

But there are cases where

$$\pi_L(\sigma_{C_1 \wedge C_2}(E)) \neq \pi_L(\sigma_{C_1}(E)) \cap \pi_L(\sigma_{C_2}(E))$$

Projection π does **not** distribute over intersection \cap

R

a	b	c
1	1	2
1	2	1

$$\pi_a(\sigma_{b=1 \wedge c=1}(R))$$

a

correct

$$\pi_a(\sigma_{b=1}(R) \cap \sigma_{c=1}(R))$$

a

incorrect

$$\pi_a(\sigma_{b=1}(R)) \cap \pi_a(\sigma_{c=1}(R))$$

a
1

Projection π does not distribute over intersection \cap (Predicate Logic)

The underlying reason why projection π does not distribute over intersection \cap is that an existential quantifier \exists does not distribute over a conjunction \wedge in Predicate Logic

$$\begin{aligned} & \pi_a(\sigma_{b=1 \wedge c=1}(R)) \\ &= \\ & \pi_a(\sigma_{b=1}(R) \cap \sigma_{c=1}(R)) \\ &= \\ & \{a \mid \exists b \exists c [(R(a, b, c) \wedge b = 1) \wedge (R(a, b, c) \wedge c = 1)]\} \\ & \quad \subseteq \\ & \{a \mid \exists b \exists c (R(a, b, c) \wedge b = 1) \wedge \exists b \exists c (R(a, b, c) \wedge c = 1)\} \\ &= \\ & \pi_{b=1}(R) \cap \pi_{c=1}(R) \end{aligned}$$

Translating **AND** in **WHERE** clause (Correct)

```
SELECT   $L(t_1, \dots, t_n)$   
FROM     $R_1 t_1, \dots, R_n t_n$   
WHERE    $C_1(t_1, \dots, t_n)$  AND  $C_2(t_1, \dots, t_n)$ 
```

can be translated to become

```
SELECT   $L^q(t_1, \dots, t_n)^2$   
FROM    (  
    SELECT   $t_1.*, \dots, t_n.*$   
    FROM     $R_1 t_1, \dots, R_n t_n$   
    WHERE    $C_1(t_1, \dots, t_n)$   
    INTERSECT  
    SELECT   $t_1.*, \dots, t_n.*$   
    FROM     $R_1 t_1, \dots, R_n t_n$   
    WHERE    $C_2(t_1, \dots, t_n)$   
    ) q
```

² $L^q(t_1, \dots, t_n)$ indicates that the components of t_1 through t_n in L may need to be renamed as components of **q**

Translating **AND** in **WHERE** clause (Incorrect)

```
SELECT   $L(t_1, \dots, t_n)$   
FROM     $R_1 t_1, \dots, R_n t_n$   
WHERE    $C_1(t_1, \dots, t_n)$  AND  $C_2(t_1, \dots, t_n)$ 
```

is **not equivalent**³ with

```
SELECT   $L(t_1, \dots, t_n)$   
FROM     $R_1 t_1, \dots, R_n t_n$   
WHERE    $C_1(t_1, \dots, t_n)$   
INTERSECT  
SELECT   $L(t_1, \dots, t_n)$   
FROM     $R_1 t_1, \dots, R_n t_n$   
WHERE    $C_2(t_1, \dots, t_n)$ 
```

³Projection does not distribute over intersection

Translating **AND** in **WHERE** clause (Correct)

```
SELECT  e.sid
FROM    Enroll e
WHERE   e.cno = 100 AND e.grade = 'A'
```

can be translated to become

```
SELECT  q.sid
FROM    (SELECT      e.sid, e.cno, e.grade
          FROM        Enroll e
          WHERE       e.cno = 100
          INTERSECT
          SELECT      e.sid, e.cno, e.grade
          FROM        Enroll e
          WHERE       e.grade = 'A'
        ) q
```

Translating **AND** in **WHERE** clause (Incorrect)

```
SELECT  e.sid  
FROM    Enroll e  
WHERE   e.cno = 100 AND e.grade = 'A'
```

is **not equivalent**⁴ with

```
SELECT  e.sid  
FROM    Enroll e  
WHERE   e.cno = 100  
INTERSECT  
SELECT  e.sid  
FROM    Enroll e  
WHERE   e.grade = 'A'
```

⁴Projection does not distribute over intersection

Projection π does not distributes over $-$

Given RA expressions E_1 and E_2 , it is the case that

$$\pi_L(E_1 - E_2) \supseteq \pi_L(E_1) - \pi_L(E_2)$$

But there exist cases where

$$\pi_L(E_1 - E_2) \neq \pi_L(E_1) - \pi_L(E_2)$$

This complexity features in reasoning about the expression $\pi_L(\sigma_{\neg C}(E))$ since

$$\pi_L(\sigma_{\neg C}(E)) = \pi_L(E - \sigma_C(E)) \supseteq \pi_L(E) - \pi_L(\sigma_C(E))$$

But there are cases where

$$\pi_L(\sigma_{\neg C}(E)) \neq \pi_L(E) - \pi_L(\sigma_C(E))$$

Projection π does **not** distribute over set difference –

R

a	b
1	1
1	2

$$\pi_a(\sigma_{\neg(b=1)}(R))$$

a
1

correct

$$\pi_a(R - \sigma_{b=1}(R))$$

a
1

incorrect

$$\pi_a(R) - \pi_a(\sigma_{b=1}(R))$$

a

Projection π does not distribute over set difference – (Predicate Logic)

The underlying reason why projection π does not distribute over distribution \cap is that an existential quantifier \exists does not distribute over a conjunction-negation \wedge -sequence in Predicate Logic

$$\begin{aligned} & \pi_a(\sigma_{\neg(b=1)}(R)) \\ &= \\ & \pi_a(R - \sigma_{b=1}(R)) \\ &= \\ & \{a \mid \exists b (R(a, b) \wedge \neg(R(a, b) \wedge b = 1))\} \\ & \quad \supseteq \\ & \{a \mid \exists b R(a, b) \wedge \neg \exists b (R(a, b) \wedge b = 1)\} \\ &= \\ & \pi_a(R) - \pi_a(\sigma_{b=1}(R)) \end{aligned}$$

Translating NOT in WHERE clause (Correct)

```
SELECT  L( $t_1, \dots, t_n$ )  
FROM    R1 t1, ..., Rn tn  
WHERE   NOT C( $t_1, \dots, t_n$ )
```

can be translated to become

```
SELECT  Lq( $t_1, \dots, t_n$ )  
FROM    (SELECT      t1.*, ..., tn.*  
          FROM        R1 t1, ..., Rn tn  
          EXCEPT  
          SELECT      t1.*, ..., tn.*  
          FROM        R1 t1, ..., Rn tn  
          WHERE       C( $t_1, \dots, t_n$ )  
        ) q
```

Translating **NOT** in **WHERE** clause (Incorrect)

```
SELECT   $L(t_1, \dots, t_n)$   
FROM     $R_1 t_1, \dots, R_n t_n$   
WHERE   NOT  $C(t_1, \dots, t_n)$ 
```

is **not equivalent**⁵ with

```
SELECT   $L(t_1, \dots, t_n)$   
FROM     $R_1 t_1, \dots, R_n t_n$   
EXCEPT  
SELECT   $L(t_1, \dots, t_n)$   
FROM     $R_1 t_1, \dots, R_n t_n$   
WHERE    $C(t_1, \dots, t_n)$ 
```

⁵Projection do not distribute over set difference

Translating NOT in WHERE clause (Correct)

```
SELECT  e.sid  
FROM    Enroll e  
WHERE   NOT e.grade = 'A'
```

can be translated to become

```
SELECT  q.sid  
FROM    (SELECT  e.sid, e.cno, e.grade  
          FROM    Enroll e  
          EXCEPT  
          SELECT  e.sid, e.cno, e.grade  
          FROM    Enroll e  
          WHERE   e.grade = 'A'  
        ) q
```

Translating **NOT** in **WHERE** clause (Incorrect)

```
SELECT  e.sid  
FROM    Enroll e  
WHERE   NOT e.grade = 'A'
```

is **not equivalent**⁶ with

```
SELECT  e.sid  
FROM    Enroll e  
EXCEPT  
SELECT  e.sid  
FROM    Enroll e  
WHERE   e.grade = 'A'
```

⁶Projection does not distribute over set difference

Projection π does not distribute over set difference –

R

A	B	C
1	1	2
1	2	1

$$\pi_A(\sigma_{B=1 \wedge \neg(C=1)}(R))$$

A
1

correct

$$\pi_A(\sigma_{B=1}(R) - \sigma_{C=1}(R))$$

A
1

incorrect

$$\pi_A(\sigma_{B=1}(R)) - \pi_A(\sigma_{C=1}(R))$$

A

Translating **AND NOT** in **WHERE** clause (Correct)

```
SELECT   $L(t_1, \dots, t_n)$   
FROM     $R_1 t_1, \dots, R_n t_n$   
WHERE    $C_1(t_1, \dots, t_n)$  AND NOT  $C_2(t_1, \dots, t_n)$ 
```

can be translated to become

```
SELECT   $L^q(t_1, \dots, t_n)$   
FROM    (  
    SELECT   $t_1.*, \dots, t_n.*$   
    FROM     $R_1 t_1, \dots, R_n t_n$   
    WHERE    $C_1(t_1, \dots, t_n)$   
    EXCEPT  
    SELECT   $t_1.*, \dots, t_n.*$   
    FROM     $R_1 t_1, \dots, R_n t_n$   
    WHERE    $C_2(t_1, \dots, t_n)$   
    ) q
```


Translating **AND NOT** in **WHERE** clause (Incorrect)

```
SELECT   $L(t_1, \dots, t_n)$   
FROM     $R_1 t_1, \dots, R_n t_n$   
WHERE    $C_1(t_1, \dots, t_n)$  AND NOT  $C_2(t_1, \dots, t_n)$ 
```

is **not equivalent**⁷ with

```
SELECT   $L(t_1, \dots, t_n)$   
FROM     $R_1 t_1, \dots, R_n t_n$   
WHERE    $C_1(t_1, \dots, t_n)$   
EXCEPT  
SELECT   $L(t_1, \dots, t_n)$   
FROM     $R_1 t_1, \dots, R_n t_n$   
WHERE    $C_2(t_1, \dots, t_n)$ 
```

⁷Projection do not distribute over set difference

Translating **AND NOT** in **WHERE** clause (Correct)

```
SELECT  e.sid  
FROM    Enroll e  
WHERE   e.cno = 100 AND NOT e.grade = 'A'
```

can be translated to become

```
SELECT  q.sid  
FROM    (SELECT  e.sid, e.cno, e.grade  
          FROM    Enroll e  
          WHERE   e.cno = 100  
          EXCEPT  
          SELECT  e.sid, e.cno, e.grade  
          FROM    Enroll e  
          WHERE   e.grade = 'A'  
        ) q
```

Translating **AND NOT** in **WHERE** clause (Incorrect)

```
SELECT  e.sid  
FROM    Enroll e  
WHERE   e.cno = 100 AND NOT e.grade = 'A'
```

is **not equivalent**⁸ with

```
SELECT  e.sid  
FROM    Enroll e  
WHERE   e.cno = 100  
EXCEPT  
SELECT  e.sid  
FROM    Enroll e  
WHERE   e.grade = 'A'
```

⁸Projection does not distribute over set difference

Translating **AND NOT** in **WHERE** clause (Also correct)

```
SELECT   $L(t_1, \dots, t_n)$   
FROM     $R_1 t_1, \dots, R_n t_n$   
WHERE    $C_1(t_1, \dots, t_n)$  AND NOT  $C_2(t_1, \dots, t_n)$ 
```

can be also be translated to become

```
SELECT   $L^q(t_1, \dots, t_n)$   
FROM    (SELECT       $t_1.*, \dots, t_n.*$   
          FROM         $R_1 t_1, \dots, R_n t_n$   
          WHERE         $C_1(t_1, \dots, t_n)$   
          EXCEPT  
          SELECT       $t_1.*, \dots, t_n.*$   
          FROM         $R_1 t_1, \dots, R_n t_n$   
          WHERE         $C_1(t_1, \dots, t_n)$  AND  $C_2(t_1, \dots, t_n)$   
        ) q
```

Translating **AND NOT** in **WHERE** clause (Also correct)

```
SELECT  e.sid  
FROM    Enroll e  
WHERE   e.cno = 100 AND NOT e.grade = 'A'
```

can be translated to become

```
SELECT  q.sid  
FROM    (SELECT  e.sid, e.cno, e.grade  
          FROM    Enroll e  
          WHERE   e.cno = 100  
          EXCEPT  
          SELECT  e.sid, e.cno, e.grade  
          FROM    Enroll e  
          WHERE   e.cno = 100 AND e.grade = 'A'  
        ) q
```

Translating **EXISTS** in **WHERE** clause (Example)

Let $R(a, b)$ and $S(b, c)$ be two relations.

```
SELECT  r.a
FROM    R r
WHERE   EXISTS (SELECT S.c
                  FROM    S s
                  WHERE   r.b = s.b)
```

In Predicate Logic,

$$\begin{aligned} & \{a \mid \exists b (R(a, b) \wedge \{c \mid S(b, c)\} \neq \emptyset)\} \\ &= \\ & \{a \mid \exists b (R(a, b) \wedge \exists c S(b, c))\} \\ &= \\ & \{a \mid \exists b \exists c (R(a, b) \wedge S(b, c))\} \\ &= \\ & \pi_{R.a}(\sigma_{R.b=S.b}(R \times S)) \end{aligned}$$

Translating EXISTS in WHERE clause (Example in Predicate Logic)

$$\begin{aligned} & \{a \mid \exists b (R(a, b) \wedge \{c \mid S(b, c)\} \neq \emptyset)\} \\ & \quad = \\ & \{a \mid \exists b (R(a, b) \wedge \exists c S(b, c))\} \\ & \quad = \\ & \{a \mid \exists b \exists c (R(a, b) \wedge S(b, c))\} \\ & \quad = \\ & \pi_{R.a}(\sigma_{R.b=S.b}(R \times S)) \end{aligned}$$

In SQL,

```
SELECT  DISTINCT r.a  
FROM    R r, S s  
WHERE   r.b = s.b
```

Translating **EXISTS** in **WHERE** clause (Example)

Let $R(a, c)$ and $S(b, c)$ be two relations.

```
SELECT  r.a
FROM    R r
WHERE   EXISTS (SELECT S.c
                  FROM   S s
                  WHERE  r.b = s.b)
```

is translated to

```
SELECT  DISTINCT r.a
FROM    R r, S s
WHERE   r.b = s.b
```


Translating **EXISTS** in **WHERE** clause (General case)

```
SELECT  L( $t_1, \dots, t_n$ )  
FROM     $R_1 t_1, \dots, R_n t_n$   
WHERE   EXISTS (SELECT 1  
                  FROM     $S_1 u_1, \dots, S_m u_m$   
                  WHERE    $C(u_1, \dots, u_m, t_1, \dots, t_n)$ )
```

is translated to

```
SELECT  DISTINCT L( $t_1, \dots, t_n$ )  
FROM     $R_1 t_1, \dots, R_n t_n, S_1 u_1, \dots, S_m u_m$   
WHERE    $C(u_1, \dots, u_m, t_1, \dots, t_n)$ 
```

Translating **EXISTS** in **WHERE** clause

```
SELECT  s.sid
FROM    Student s
WHERE   EXISTS (SELECT 1
                  FROM    Enroll e, Course c
                  WHERE   e.sid = s.sid AND e.cno = c.cno AND c.dept = 'CS')
```

is translated to

```
SELECT  DISTINCT s.sid
FROM    Student s, Enroll e, Course c
WHERE   e.sid = s.sid AND e.cno = c.cno AND c.dept = 'CS'
```

Translating **NOT EXISTS** in **WHERE** clause (Example)

Let $R(a, b)$ and $S(b, c)$ be two relations.

```
SELECT  r.a
FROM    R r
WHERE   NOT EXISTS (SELECT S.c
                    FROM    S s
                    WHERE   r.b = s.b)
```

In Predicate Logic,

$$\begin{aligned} & \{a \mid \exists b (R(a, b) \wedge \{c \mid S(b, c)\} = \emptyset)\} \\ & \quad = \\ & \{a \mid \exists b (R(a, b) \wedge \neg \exists c S(b, c))\} \\ & \quad = \\ & \{a \mid \exists b (R(a, b) \wedge \neg \exists c (R(a, b) \wedge S(b, c)))\} \\ & \quad = \\ & \pi_{R.a}(R - \pi_{R.a, R.b}(\sigma_{R.b=S.b}(R \times S))) \end{aligned}$$

Translating **NOT EXISTS** in WHERE clause (Example)

$$\begin{aligned} & \{a \mid \exists b (R(a, b) \wedge \{c \mid S(b, c)\} = \emptyset)\} \\ & \quad = \\ & \pi_{R.a}(R - \pi_{R.a, R.b}(\sigma_{R.b=S.b}(R \times S))) \end{aligned}$$

In SQL,

```
SELECT DISTINCT q.a
FROM   (SELECT R.a, R.b
        FROM   R r
        EXCEPT
        SELECT R.a, R.b
        FROM   R r, S s
        WHERE  r.b = s.b
      ) q
```

Translating **NOT EXISTS** in **WHERE** clause (Example)

```
SELECT  r.a
FROM    R r
WHERE   NOT EXISTS (SELECT S.c
                    FROM    S s
                    WHERE   r.b = s.b)
```

is translated to

```
SELECT  DISTINCT q.a
FROM    (SELECT      R.a, R.b
        FROM          R r
        EXCEPT
        SELECT        R.a, S.b
        FROM          R r, S s
        WHERE         r.b = s.b
        ) q
```

Translating **NOT EXISTS** in **WHERE** clause (General case)

```
SELECT  L(t1, ..., tn)
FROM    R1 t1, ..., Rn tn
WHERE   NOT EXISTS (SELECT 1
                     FROM    S1 u1, ..., Sm um
                     WHERE   C(u1, ..., um t1, ..., tn))
```

is translated to

```
SELECT  DISTINCT Lq(t1, ..., tn)
FROM    (SELECT      t1.*, ..., tn.*
          FROM        R1 t1, ..., Rn tn
          EXCEPT
          SELECT      t1.*, ..., tn.*
          FROM        R1 t1, ..., Rn tn, S1 u1, ..., Sm um
          WHERE       C(u1, ..., um t1, ..., tn)
        ) q
```

Translating **NOT EXISTS** in **WHERE** clause

```
SELECT    s.sid
FROM      Student s
WHERE     NOT EXISTS (SELECT 1
                        FROM    Enroll e
                        WHERE    e.sid = s.sid AND e.grade = 'A')
```

is translated to

```
SELECT    q.sid
FROM      (SELECT    s.sid, s.sname
            FROM      Student s
            EXCEPT
            SELECT    s.sid, s.sname
            FROM      Student s, Enroll e
            WHERE     e.sid = s.sid AND e.grade = 'A'
          ) q
```

Translating **AND NOT EXISTS** in **WHERE** clause

```
SELECT  s.sid
FROM    Student s
WHERE   s.sname = 'Ann' AND
        NOT EXISTS (SELECT 1
                     FROM    Enroll e
                     WHERE e.sid = s.sid AND e.grade = 'A')
```

is translated to

```
SELECT  q.sid
FROM    (SELECT s.sid, s.sname
         FROM Student s
         WHERE s.sname = 'Ann'
        EXCEPT
        SELECT s.sid, s.sname
         FROM Student s, Enroll e
         WHERE e.sid = s.sid AND e.grade = 'A'
       ) q
```


Translating **AND NOT EXISTS** in **WHERE** clause (Alternative)

```
SELECT  s.sid
FROM    Student s
WHERE   s.sname = 'Ann' AND
        NOT EXISTS (SELECT 1
                     FROM    Enroll e
                     WHERE e.sid = s.sid AND e.grade = 'A')
```

is translated to

```
SELECT  q.sid
FROM    (SELECT s.sid, s.sname
         FROM Student s
         WHERE s.sname = 'Ann'
        EXCEPT
        SELECT s.sid, s.sname
         FROM Student s, Enroll e
         WHERE s.sname='Ann' AND e.sid = s.sid AND e.grade = 'A'
       ) q
```

Translating **IN** in **WHERE** clause

```
SELECT  L(t1, ..., tn)
FROM    R1 t1, ..., Rn tn
WHERE   (ti1.Aj1, ..., tik.Ajk) IN
        (SELECT ul1.Bm1, ..., ulk.Bmk
          FROM  S1 u1, ..., Sm um
          WHERE C(u1, ..., um, t1, ..., tn))
```

is translated to

```
SELECT  DISTINCT L(t1, ..., tn)
FROM    R1 t1, ..., Rn tn, S1 u1, ..., Sm um
WHERE   C(u1, ..., um, t1, ..., tn) AND
        ti1.Aj1 = ul1.Bm1 AND ... AND tik.Ajk = ulk.Bmk
```

Translating **IN** in **WHERE** clause

```
SELECT    s.sid
FROM      Student s
WHERE     s.sid IN (SELECT e.sid
                    FROM   Enroll e
                    WHERE  e.grade = 'A')
```

is translated to

```
SELECT    DISTINCT s.sid
FROM      Student s, Enroll e
Where     e.grade = 'A' AND
          s.sid = e.sid
```

Translating **NOT IN** in **WHERE** clause

```

SELECT  L( $t_1, \dots, t_n$ )
FROM    R1  $t_1, \dots, R_n$   $t_n$ 
WHERE   ( $t_1.A_{j_1}, \dots, t_k.A_{j_k}$ ) NOT IN
        (SELECT  $u_{l_1}.B_{m_1}, \dots, u_{l_k}.B_{m_k}$ 
         FROM    S1  $u_1, \dots, S_m$   $u_m$ 
         WHERE   C( $u_1, \dots, u_m$   $t_1, \dots, t_n$ ))
    
```

is translated to

```

SELECT  Lq( $t_1, \dots, t_n$ )
FROM    (SELECT  $t_1.*, \dots, t_n.*$ 
         FROM    R1  $t_1, \dots, R_n$   $t_n$ 
         EXCEPT
         SELECT  $t_1.*, \dots, t_n.*$ 
         FROM    R1  $t_1, \dots, R_n$   $t_n$ , S1  $u_1, \dots, S_m$   $u_m$ 
         WHERE   C( $u_1, \dots, u_m$   $t_1, \dots, t_n$ ) AND
                  $t_1.A_{j_1} = u_{l_1}.B_{m_1}$  AND  $\dots$  AND  $t_k.A_{j_k} = u_{l_k}.B_{m_k}$ 
        ) q
    
```

Translating **NOT IN** in **WHERE** clause

```
SELECT  s.sid
FROM    Student s
WHERE   s.sid NOT IN (SELECT e.sid
                      FROM   Enroll e
                      WHERE  e.grade = 'A')
```

is translated to

```
SELECT  q.sid
FROM    (SELECT s.sid, s.sname
          FROM Student s
          EXCEPT
          SELECT s.sid, s.sname
          FROM Student s, Enroll e
          WHERE e.grade = 'A' AND s.sid = e.sid
        ) q
```

Translating θ **SOME** in **WHERE** clause

```
SELECT  L( $t_1, \dots, t_n$ )  
FROM     $R_1 t_1, \dots, R_n t_n$   
WHERE    $t_{i_1}.A_{j_1} \theta$  SOME  
        (SELECT  $u_{l_1}.B_{m_1}$   
         FROM     $S_1 u_1, \dots, S_m u_m$   
         WHERE   C( $u_1, \dots, u_m, t_1, \dots, t_n$ ))
```

is translated to

```
SELECT  DISTINCT L( $t_1, \dots, t_n$ )  
FROM     $R_1 t_1, \dots, R_n t_n, S_1 u_1, \dots, S_m u_m$   
WHERE   C( $u_1, \dots, u_m, t_1, \dots, t_n$ ) AND  
         $t_{i_1}.A_{j_1} \theta u_{l_1}.B_{m_1}$ 
```

Translating θ **SOME** in **WHERE** clause

```
SELECT s.sid  
FROM Student  
s  
WHERE s.sid = Some (SELECT e.sid  
                     FROM Enroll e, Course c  
                     WHERE e.cno = c.cno AND c.dept = 'CS')
```

is translated to

```
SELECT DISTINCT s.sid  
FROM Student s, Enroll e, Course c  
WHERE e.cno = c.cno AND c.dept = 'CS' AND  
      s.sid = e.sid
```

Translating θ ALL in WHERE clause

```
SELECT  L(t1, ..., tn)
FROM    R1 t1, ..., Rn tn
WHERE   t1.Aj1  $\theta$  ALL
                                     (SELECT ul1.Bm1
                                      FROM   S1 u1, ..., Sm um
                                      WHERE  C(u1, ..., um t1, ..., tn))
```

is translated to

```
SELECT  Lq(t1, ..., tn)
FROM    (SELECT t1.*, ..., tn*
        FROM  R1 t1, ..., Rn tn
        EXCEPT
        SELECT t1.*, ..., tn*
        FROM  R1 t1, ..., Rn tn, S1 u1, ..., Sm um
        WHERE C(u1, ..., um t1, ..., tn) AND
              NOT t1.Aj1  $\theta$  ul1.Bm1
        ) q
```


Translating θ ALL in WHERE clause

```
SELECT  p.pid
FROM    Person p
WHERE   p.age  $\leq$  ALL
                               (SELECT p1.age
                               FROM    Person p1)
```

is translated to

```
SELECT  DISTINCT q.pid
FROM    (SELECT p.pid, p.age
        FROM Person p
        EXCEPT
        SELECT p.pid, p.age
        FROM Person p, Person p1
        WHERE NOT p.age  $\leq$  p1.age
        ) q
```


Eliminate first-level NOT EXISTS predicate

"Find the sid of each student who is only enrolled in CS courses."

```
SELECT q1.ssid
FROM (SELECT s.sid AS ssid, s.sname
      FROM Student s
      EXCEPT
      SELECT s.sid, s.sname
      FROM Student s, Enroll e
      WHERE e.sid = s.sid AND
            e.cno NOT IN (SELECT c.cno
                          FROM Course c
                          WHERE c.dept = 'CS')) q1
```

Eliminate second-level AND NOT IN

"Find the sid of each student who is only enrolled in CS courses."

```
SELECT  q1.ssid
FROM    (SELECT s.sid AS ssid, s.sname
        FROM    Student s
        EXCEPT
        SELECT q2.ssid, s.sname
        FROM (SELECT s.sid AS ssid, s.sname, e.sid, e.cno, e.grade
              FROM    Student s, Enroll e
              WHERE   e.sid = s.sid
              EXCEPT
              (SELECT s.sid, s.sname, e.sid, e.cno, e.grade
               FROM    Student s, Enroll e, Course c
               WHERE   e.cno = c.cno AND c.dept = 'CS' ) q2) q1
```


Eliminate first-level NOT EXISTS predicate

"Find the sid of each student who is only enrolled in CS courses."

```
SELECT q1.ssid
FROM (SELECT s.sid AS ssid, s.sname
      FROM Student s
      EXCEPT
      SELECT s.sid, s.sname
      FROM Student s, Course c
      WHERE c.dname = 'CS' AND
            c.cno NOT IN (SELECT e.cno
                          FROM Enroll e
                          WHERE e.sid = s.sid)) q1
```

Eliminate second-level AND NOT IN

"Find the sid of each student who is enrolled in all CS courses."

```
SELECT      q1.ssid
FROM        (SELECT s.sid AS ssid, s.sname
             FROM    Student s
             EXCEPT
             SELECT q2.ssid, s.sname
             FROM    (SELECT s.sid AS ssid, s.sname, c.cno, c.dname
                     FROM    Student s, Course c
                     WHERE   c.dname = 'CS'
                     EXCEPT
                     (SELECT s.sid, s.sname, c.cno, c.dname
                      FROM    Student s, Enroll e, Course c
                      WHERE   e.cno = c.cno AND e.sid = s.sid) q2) q1
```

Moving **WHERE** condition to **FROM** clause

- In the previous slides we have shown how set predicates can be translated
- After that process, we will have SQL queries wherein the **WHERE** clauses consist of boolean combinations of conditions of the form
 - $t.A \theta a$; or
 - $t_i.A \theta t_j.B$
- In the following slides we will show how these **WHERE** clauses can be moved to **FROM** clauses
- We might also have queries without a **WHERE** clause and/or without a **FROM** clause; these require special treatment

SQL queries without **WHERE** and **FROM** clauses

SELECT a AS A

This query is translated to the RA expression

$(A : \mathbf{a})$

SQL queries without **WHERE** clause

```
SELECT  L(t1, ..., tn)  
FROM    R1 t1, ..., Rn tn
```

This query is translated to the RA expression

$$\pi_{L(t_1, \dots, t_n)}(R_1 \times \dots \times R_n)$$

Moving **WHERE** condition to **FROM** clause (condition on at least three relations)

Assume that the condition C applies to at least three relations, i.e., the condition is of the form $C(t_{i_1}, t_{i_2}, t_{i_3}, \dots, t_{i_k})$ with $k \geq 3$

```
SELECT  L(t1, ..., tn)  
FROM    R1 t1, R2 t2, R3 t3, ..., Rn tn  
WHERE   C(ti1, ti2, ti3, ..., tik)
```

We can now introduce the **CROSS JOIN** in the **FROM** clause by replacing each ‘,’ with **CROSS JOIN**

```
SELECT  L(t1, ..., tn)  
FROM    R1 t1 CROSS JOIN R2 t2 CROSS JOIN R3 t3 CROSS JOIN ... CROSS JOIN Rn tn  
WHERE   C(ti1, ti2, ti3, ..., tik)
```

In RA,

$$\pi_{L(t_1, \dots, t_n)}(\sigma_{C(t_{i_1}, t_{i_2}, t_{i_3}, \dots, t_{i_k})}(R_1 \times R_2 \times R_3 \times \dots \times R_n))$$

Moving **WHERE** condition to **FROM** clause (condition on at least **three** relations) Example

```
SELECT  L(t1, t2, t3)  
FROM    R1 t1, R2 t2, R3 t3  
WHERE   t1.A1 θ1 t2.A2 OR t2.A3 θ2 t3.A4
```

is translated to

$$\pi_{L(t_1, t_2, t_3)}(\sigma_{t_1.A_1 \theta_1 t_2.A_2 \vee t_2.A_3 \theta_2 t_3.A_4} (R_1 \times R_2 \times R_3))$$

Moving **WHERE** condition to **FROM** clause (condition on single relation)

```
SELECT  L(t1, ..., tn)  
FROM    R1 t1, R2 t2, ..., Ri ti, ..., Rn tn  
WHERE   C(ti) [AND Ct(t1, ..., tk)]
```

Observe that $C(t_i)$ is only a condition on R_i . This query is translated to

```
SELECT  L(t1, ..., tn)  
FROM    R1 t1, R2 t2 ...,  
        (SELECT ti. * FROM Ri WHERE C(ti)) ti, ..., Rn tn  
[WHERE  Ct(t1, ..., tk) ]
```

Moving **WHERE** condition to **FROM** clause (condition on single relation)

```
SELECT L(t1, ..., tn)
FROM   R1 t1, R2 t2, ...,
        (SELECT ti. * FROM Ri WHERE C(ti)) ti, ..., Rn tn
[WHERE C'(ti1, ..., tik) ]
```

We can now introduce the **CROSS JOIN** in the **FROM** clause by replacing each ',' with **CROSS JOIN**

```
SELECT L(t1, ..., tn)
FROM   R1 t1 CROSS JOIN R2 t2 CROSS JOIN ... CROSS JOIN
        (SELECT ti. * FROM Ri WHERE C(ti)) ti CROSS JOIN ... CROSS JOIN Rn tn
[WHERE C'(ti1, ..., tik) ]
```

Which, in the notation of RA, corresponds to the expression

$$\pi_{L(t_1, \dots, t_n)}(\sigma_{C'(t_{i_1}, \dots, t_{i_k})}(R_1 \times R_2 \times \dots \times \sigma_{C(t_i)}(R_i) \times \dots \times R_n))$$

or, when $C'(t_{i_1}, \dots, t_{i_k})$ is missing,

$$\pi_{L(t_1, \dots, t_n)}(R_1 \times R_2 \times \dots \times \sigma_{C(t_i)}(R_i) \times \dots \times R_n)$$

Moving **WHERE** condition to **FROM** clause (condition on **two** relations)

```
SELECT  L( $t_1, \dots, t_n$ )  
FROM     $R_1 t_1, \dots, R_i t_i, \dots, R_j t_j, \dots, R_n t_n$   
WHERE    $C(t_i, t_j)$  [AND  $C^t(t_{i_1}, \dots, t_{i_k})$ ]
```

Observe that $C(t_i, t_j)$ is a condition relating R_i and R_j . This query is translated to

```
SELECT  L( $t_1, \dots, t_n$ )  
FROM     $R_1 t_1, \dots, R_{i-1} t_{i-1}, R_{i+1} t_{i+1}, \dots, R_{j-1} t_{j-1}, R_{j+1} t_{j+1}, \dots, R_n t_n$   
         $R_i t_i$  JOIN  $R_j t_j$  ON  $C(t_i, t_j)$   
[WHERE   $C^t(t_{i_1}, \dots, t_{i_k})$ ]
```

Moving **WHERE** condition to **FROM** clause (condition on **two** relations)

```
SELECT L(t1, ..., tn)  
FROM   R1 t1, ..., Ri-1 tj-1, Ri+1 tj+1, ..., Rj-1 tj-1, Rj+1 tj+1, ..., Rn tn,  
       Ri ti JOIN Rj tj ON C(ti, tj)  
[WHERE C'(ti1, ..., tik)]
```

Recalling that each ‘,’ in the FROM clause corresponds to a CROSS JOIN, this query can be formulated in RA as follows:

$$\pi_{L(t_1, \dots, t_n)}(\sigma_{C'(t_{i_1}, \dots, t_{i_k})}(R_1 \times \dots \times R_{i-1} \times R_{i+1} \times \dots \times R_{j-1} \times R_{j+1} \times \dots \times R_n \times (R_i \bowtie_{C(t_i, t_j)} R_j)))$$

or, when $C'(t_{i_1}, \dots, t_{i_k})$ is missing

$$\pi_{L(t_1, \dots, t_n)}(R_1 \times \dots \times R_{i-1} \times R_{i+1} \times \dots \times R_{j-1} \times R_{j+1} \times \dots \times R_n \times (R_i \bowtie_{C(t_i, t_j)} R_j))$$

Moving **WHERE** condition to **FROM** clause (**natural join** condition)

Assume that A_1, \dots, A_k are the common attributes of R_i and R_j and that $C(t_i, t_j)$ is the condition

$$t_i.A_1 = t_j.A_1 \text{ AND } \dots \text{ AND } t_i.A_k = t_j.A_k$$

then

```
SELECT L(t1, ..., tn)  
FROM   R1 t1, ..., Ri-1 tj-1, Ri+1 tj+1, ..., Rj-1 tj-1, Rj+1 tj+1, ..., Rn tn,  
       Ri ti JOIN Rj tj ON C(ti, tj)  
[WHERE C'(ti1, ..., tik)]
```

is translated to

```
SELECT L(t1, ..., tn)  
FROM   R1 t1, ..., Ri-1 tj-1, Ri+1 tj+1, ..., Rj-1 tj-1, Rj+1 tj+1, ..., Rn tn,  
       Ri ti NATURAL JOIN Rj tj  
[WHERE C'(ti1, ..., tik)]
```

In RA,

$$\pi_{L(t_1, \dots, t_n)}(\sigma_{C'(t_{i_1}, \dots, t_{i_k})}(R_1 \times \dots \times R_{i-1} \times R_{i+1} \times \dots \times R_{j-1} \times R_{j+1} \times \dots \times R_n \times (R_i \bowtie R_j)))$$

SQL queries with set operations UNION, INTERSECT, or EXCEPT

Assuming Q_1 and Q_2 SQL queries, the queries of the form

$$\begin{array}{c} Q_1 \\ \text{UNION [INTERSECT | EXCEPT]} \\ Q_2 \end{array}$$

can be translated to RA as follows

$$E_{Q_1} \text{u}[\text{n} | -] E_{Q_2}$$

where E_{Q_1} and E_{Q_2} are the RA expressions corresponding to Q_1 and Q_2

Example

"Find the sid of each student who is only enrolled in CS courses."

```
SELECT  q1.ssid
FROM    (SELECT s.sid AS ssid, s.sname
        FROM    Student s
        EXCEPT
        SELECT  q2.ssid, s.sname
        FROM    (SELECT s.sid AS ssid, s.sname, e.sid, e.cno
                FROM    Student s, Enroll e
                WHERE   e.sid = s.sid
                EXCEPT
                (SELECT s.sid, s.sname, e.sid, e.cno
                 FROM    Student s, Enroll e, Course c
                 WHERE   e.cno = c.cno AND c.dept = 'CS' ) q2) q1
```

Example

“Find the sid of each student who is only enrolled in CS courses.”

```
SELECT      q1.ssidsid
FROM        (SELECT s.sid AS ssid, s.sname
             FROM    Student s
             EXCEPT
             SELECT q2.ssidsid, s.sname
             FROM    (SELECT s.sid AS ssid, s.sname, e.sid, e.cno
                     FROM    Student s NATURAL JOIN Enroll e
                     EXCEPT
                     (SELECT s.sid, s.sname, e.sid, e.cno
                      FROM    Student s CROSS JOIN Enroll E
                      NATURAL JOIN (SELECT c.* FROM Course c WHERE dept = 'CS') c) q2) q1
```

is translated to

$$\pi_{sid}(\pi_{sid, sname}(S) - \pi_{S.sid, sname}(\pi_{S.sid, sname, E.sid, cno}(S \bowtie E) - \pi_{S.sid, sname, E.sid, cno}(S \times E \bowtie \sigma_{dept='CS'}(C))))$$

where S , E , and C denote Student, Enroll, and Course, respectively.

Example (Optimization)

“Find the sid of each student who is only enrolled in CS courses.”

$$\pi_{sid}(\pi_{sid,sname}(S) - \pi_{sid,sname}(\pi_{sid,sname,E.sid,cno}(S \bowtie E) - \pi_{sid,sname,E.sid,cno}(S \times E \bowtie \sigma_{dept='CS'}(C))))$$

This can be **optimized** to the RA expression

$$\pi_{sid}(S) - \pi_{sid}(\pi_{sid,cno}(E) - \pi_{sid,cno}(E) \bowtie \pi_{cno}(\sigma_{dept='CS'}(C)))$$

Notice that this is the RA expression for the **only** set semijoin
If furthermore the schema of Enroll is (sid,cno), this expression becomes

$$\pi_{sid}(S) - \pi_{sid}(E - E \bowtie CS) = \pi_{sid} - \pi_{sid}(E \overline{\bowtie} CS)$$

where CS denotes the RA expression $\pi_{cno}(\sigma_{dept='CS'}(C))$