

Learning to Program with F#
Exercises
Department of Computer Science
University of Copenhagen

Jon Sparring, Martin Elsmann, Torben Mogensen, Christina Lioma

September 29, 2021

In this assignment, you are to work with a puzzle called Rotate. The puzzle consists of a square board with $n \times n, n \in \{2, 3, 4, 5\}$ fields similarly to a chess-board. Each field has a unique id-number, which we will call the field's position, and on each field is one unique letter from the alphabet 'a', 'b', For example, when $n = 4$, then the board could look like,

h	o	l	k
b	i	g	e
f	m	c	a
j	n	d	p

and the position of the respective fields are

1	2	3	4
5	6	7	8
9	10	11	12
13	14	15	16

The puzzle is solved by rotating the letters in small 2×2 subsquares clockwise until the board reaches the state

a	b	c	d
e	f	g	h
i	j	k	l
m	n	o	p

A rotation is specified by the position of its top-left corner, and all but the right-most column and the bottom-most row are valid inputs to the rotation operation. Let $p_1, p_2, p_3, p_4 \rightarrow q_1, q_2, q_3, q_4$ denote a rotation from p_* to q_* , where p_1 is the top-left corner, then for example, specifying a rotation of subsquare 1 results in $1, 2, 5, 6 \rightarrow 2, 6, 5, 1$, or equivalently,

h	o	l	k		b	h	l	k
b	i	g	e		i	o	g	e
f	m	c	a	→	f	m	c	a
j	n	d	p		j	n	d	p

The overall task of this assignment is to build a program, that will generate rotate-puzzles and allow you to iteratively enter a sequence of positions until the puzzle is solved. Detailed requirements are:

- If your program includes loops, then the loops must be programmed using recursion
- Your program must use lists and not arrays.
- Your program must not use mutable values (variables).
- Your solution must be parametrized by n , the size of the board.
- you must represent your board as a list of letters, e.g., for $n = 4$ the board for a solved puzzle must be ['a' .. 'p']

- Your program must consist of the following files `game.fsx`, `rotate.fsi`, `rotate.fs`, `whiteboxtest.fsx` and `blackboxtest.fsx`. The files `rotate.fsi`, `rotate.fs` must be the interface and implementation of a library with your main types, functions, and values; the file `game.fsx` must be a maximally 10 line program, which defines the value n and starts the game; and `test.fsx` must contain your test for the library.

As part of this assignment, you are to write a maximally 10-page report following `rapport.tex` template.

0.1 Rotate

0.1.1 Opgave(r)

- 0.1.1:** Write the interface file for the library `rotate` with user defined types `Board` which is a list of characters and `Position` which is an integer and with the following functions,

```
create : int -> Board
board2Str : Board -> string
permute : Board -> Board
rotate : Board -> Position -> Board
solved : Board -> bool
```

The function `create` must take an integer n and return a $n \times n$ board in its solved state.

The function `board2Str` must take a board and return a string, containing the board formatted such that it can be printed with the `printfn "%s"` command and formatting string.

The function `permute` must take a board and return another board, where all the elements of the original board are present but have been randomly changed positions.

The function `rotate` must take a board and a position and return another board, where is identical to the original but where a local 2×2 rotation has been performed at the indicated position. If an invalid position is given, then the function must return an empty board.

The function `solved` must take a board and return true or false depending on whether the puzzle has been solved or not.

The interface must include documentation following the documentation standard.

- 0.1.2:** Write a program `blackboxtest.fsx` which performs a blackbox test of the yet to be implemented `rotate` library.
- 0.1.3:** Write the implementation file of the `rotate` library.
- 0.1.4:** Write a program `whiteboxtest.fsx` which performs a whitebox test of the `rotate` library.
- 0.1.5:** Write the a short program, `game`, which defines the size of the board n and starts the game, and which has all the interaction with the user in a game-loop.
- 0.1.6:** Extend your libray and your `whiteboxtest` with a function

```
solutions : Board -> int -> int list list
```

which takes an integer m and seeks possible solutions to a given board within maximally m rotations. The function should return 0 or more lists of possible rotation sequences, of length no longer than m , and which solves the puzzle.