

CHAPTER 3: THE ENHANCED E-R MODEL

Modern Database Management

12th Edition

***Jeff Hoffer, Ramesh Venkataraman,
Heikki Topi***

OBJECTIVES

- ❑ Define terms
- ❑ Understand use of supertype/subtype relationships
- ❑ Use specialization and generalization techniques
- ❑ Specify completeness and disjointness constraints
- ❑ Develop supertype/subtype hierarchies for realistic business situations
- ❑ Develop entity clusters
- ❑ Explain universal (packaged) data model
- ❑ Describe special features of data modeling project using packaged data model

SUPERTYPES AND SUBTYPES

- ❑ **Enhanced ER model:** extends original ER model with new modeling constructs
- ❑ **Subtype:** A subgrouping of the entities in an entity type that has attributes distinct from those in other subgroupings
- ❑ **Supertype:** A generic entity type that has a relationship with one or more subtypes
- ❑ **Attribute Inheritance:**
 - ❑ Subtype entities inherit values of all attributes of the supertype
 - ❑ An instance of a subtype is also an instance of the supertype

Figure 3-1 Basic notation for supertype/subtype notation

a) EER notation






Figure 3-1 Basic notation for supertype/subtype notation (cont.)



Different modeling tools may have different notation for the same modeling constructs.


Figure 3-2 Employee supertype with three subtypes



RELATIONSHIPS AND SUBTYPES

- ❑ Relationships at the **supertype** level indicate that all subtypes will participate in the relationship
- ❑ The instances of a **subtype** may participate in a relationship unique to that subtype. In this situation, the relationship is shown at the subtype level

Figure 3-3 Supertype/subtype relationships in a hospital




GENERALIZATION AND SPECIALIZATION

- ❑ **Generalization:** The process of defining a more general entity type from a set of more specialized entity types. BOTTOM-UP
- ❑ **Specialization:** The process of defining one or more subtypes of the supertype and forming supertype/subtype relationships. TOP-DOWN

Figure 3-4 Example of generalization


a) Three entity types: CAR, TRUCK, and MOTORCYCLE



All these types of vehicles have common attributes

Figure 3-4 Example of generalization (cont.)

b) Generalization to VEHICLE supertype



So we put
the shared
attributes in
a supertype

Note: no subtype for motorcycle, since it has no unique attributes

Figure 3-5 Example of specialization

a) Entity type PART





Figure 3-5 Example of specialization (cont.)

b) Specialization to MANUFACTURED PART and PURCHASED PART




Note: multivalued composite attribute was replaced by an associative entity relationship to another entity

CONSTRAINTS IN SUPERTYPE/SUBTYPE RELATIONSHIPS

Completeness Constraints:

Whether an instance of a supertype ***must*** also be a member of at least one subtype

 Total Specialization Rule: Yes (double line)

 Partial Specialization Rule: No (single line)

Figure 3-6 Examples of completeness constraints

a) Total specialization rule





Figure 3-6 Examples of completeness constraints (cont.)

b) Partial specialization rule



CONSTRAINTS IN SUPERTYPE/SUBTYPE RELATIONSHIPS

❓ ***Disjointness Constraints:***

Whether an instance of a supertype may *simultaneously* be a member of two (or more) subtypes

❓ Disjoint Rule: An instance of the supertype can be only ONE of the subtypes

❓ Overlap Rule: An instance of the supertype could be more than one of the subtypes

Figure 3-7 Examples of disjointness constraints

a) Disjoint rule





Figure 3-7 Examples of disjointness constraints (cont.)

b) Overlap rule



CONSTRAINTS IN SUPERTYPE/SUBTYPE RELATIONSHIPS

❓ **Subtype Discriminator:** An attribute of the supertype whose values determine the target subtype(s)

❓ **Disjoint** – a *simple* attribute with alternative values to indicate the possible subtypes

❓ **Overlapping** – a *composite* attribute whose subparts pertain to different subtypes. Each subpart contains a Boolean value to indicate whether or not the instance belongs to the associated subtype

Figure 3-8 Introducing a subtype discriminator (***disjoint*** rule)




Figure 3-9 Subtype discriminator (**overlap** rule)





Figure 3-10 Example of supertype/subtype hierarchy



ENTITY CLUSTERS

- ❓ EER diagrams are difficult to read when there are too many entities and relationships.
- ❓ Solution: Group entities and relationships into ***entity clusters***.
- ❓ **Entity cluster:** Set of one or more entity types and associated relationships grouped into a single abstract entity type

Figure 3-13a
Possible entity
clusters for Pine
Valley Furniture in
Microsoft Visio

Related
groups of
entities could
become
clusters




Figure 3-13b EER diagram of PVF entity clusters





Figure 3-14 Manufacturing entity cluster



Detail for a single cluster

PACKAGED DATA MODELS


- ❑ Predefined data models
- ❑ Could be universal or industry-specific
- ❑ Universal data model = a generic or template data model that can be reused as a starting point for a data modeling project (also called a “pattern”)

ADVANTAGES OF PACKAGED DATA MODELS

- ❑ Use proven model components
- ❑ Save time and cost
- ❑ Less likelihood of data model errors
- ❑ Easier to evolve and modify over time
- ❑ Aid in requirements determination
- ❑ Easier to read
- ❑ Supertype/subtype hierarchies promote reuse
- ❑ Many-to-many relationships enhance model flexibility
- ❑ Vendor-supplied data model fosters integration with vendor's applications
- ❑ Universal models support inter-organizational systems

Figure 3-15 PARTY, PARTY ROLE, and ROLE TYPE in a universal data model


(a) Basic PARTY universal data model



Packaged data models are generic models that can be customized for a particular organization's business rules.

Figure 3-15 PARTY, PARTY ROLE, and ROLE TYPE in a universal data model

(b) PARTY supertype/subtype hierarchy





This work is protected by United States copyright laws and is provided solely for the use of instructors in teaching their courses and assessing student learning. Dissemination or sale of any part of this work (including on the World Wide Web) will destroy the integrity of the work and is not permitted. The work and materials from it should never be made available to students except by instructors using the accompanying text in their classes. All recipients of this work are expected to abide by these restrictions and to honor the intended pedagogical purposes and the needs of other instructors who rely on these materials.

EXERCISES

- ❑ A rental car agency classifies the vehicles it rents into four categories: compact, midsize, full-size, and sport utility.
- ❑ The agency wants to record the following data for all vehicles: Vehicle ID, Make, Model, Year, and Color.
- ❑ There are no unique attributes for any of the four classes of vehicle. The entity type vehicle has a relationship (named Rents) with a customer entity type. None of the four vehicle classes has a unique relationship with an entity type. Would you consider creating a supertype/subtype relationship for this problem? Why or why not?

EXERCISES

- ❑ At a weekend retreat, the entity type PERSON has three subtypes: CAMPER, BIKER, and RUNNER. Draw a separate EER diagram segment for each of the following situations:
 - ❑ a. At a given time, a person must be exactly one of these subtypes.
 - ❑ b. A person may or may not be one of these subtypes. However, a person who is one of these subtypes cannot at the same time be one of the other subtypes.
 - ❑ c. A person may or may not be one of these subtypes. On the other hand, a person may be any two (or even three) of these subtypes at the same time.
 - ❑ d. At a given time, a person must be at least one of these subtypes