

```
mysql> use mysql;
```

Database changed

```
mysql> CREATE TABLE TopSongs (
```

```
->  song_id INT PRIMARY KEY,
```

```
->  song_title VARCHAR(100),
```

```
->  artist VARCHAR(100),
```

```
->  streams BIGINT,
```

```
->  release_date DATE
```

```
-> );
```

Query OK, 0 rows affected (0.06 sec)

```
mysql> INSERT INTO TopSongs (song_id, song_title, artist, streams, release_date)
VALUES
```

```
-> (1, 'Blinding Lights', 'The Weeknd', 3500000000, '2019-11-29'),
```

```
-> (2, 'Shape of You', 'Ed Sheeran', 3800000000, '2017-01-06'),
```

```
-> (3, 'Levitating', 'Dua Lipa', 2500000000, '2020-03-27'),
```

```
-> (4, 'Stay', 'The Kid LAROI & Justin Bieber', 2800000000, '2021-07-09'),
```

```
-> (5, 'Bad Guy', 'Billie Eilish', 2200000000, '2019-03-29');
```

Query OK, 5 rows affected (0.01 sec)

Records: 5 Duplicates: 0 Warnings: 0

```
mysql> SELECT customer_name, SUM(order_amount) AS total_spent
```

```
-> FROM FoodOrders
```

```
-> GROUP BY customer_name
```

```
-> ORDER BY total_spent DESC
```

```
-> LIMIT 3;
```

ERROR 1146 (42S02): Table 'mysql.foodorders' doesn't exist

```
mysql> CREATE TABLE FoodOrders (
```

```

-> order_id INT PRIMARY KEY,
-> restaurant_name VARCHAR(100),
-> customer_name VARCHAR(100),
-> order_amount DECIMAL(10,2),
-> order_date DATE
-> );

```

Query OK, 0 rows affected (0.04 sec)

```
mysql> INSERT INTO FoodOrders (order_id, restaurant_name, customer_name,
order_amount, order_date) VALUES
```

```

-> (1, 'Dominos', 'Amit', 450.00, '2026-06-20'),
-> (2, 'KFC', 'Riya', 600.00, '2026-06-21'),
-> (3, 'McDonalds', 'Sahil', 300.00, '2026-06-22'),
-> (4, 'Dominos', 'Riya', 500.00, '2026-06-23'),
-> (5, 'KFC', 'Amit', 700.00, '2026-06-24');

```

Query OK, 5 rows affected (0.01 sec)

Records: 5 Duplicates: 0 Warnings: 0

```
mysql> SELECT customer_name, SUM(order_amount) AS total_spent
```

```

-> FROM FoodOrders
-> GROUP BY customer_name
-> ORDER BY total_spent DESC
-> LIMIT 3;

```

```

+-----+-----+
| customer_name | total_spent |
+-----+-----+
| Amit         | 1150.00    |
| Riya         | 1100.00    |

```

Sahil		300.00	
-------	--	--------	--

+-----+-----+

3 rows in set (0.00 sec)

mysql> SELECT restaurant_name,

-> COUNT(order_id) AS number_of_orders,

-> SUM(order_amount) AS total_order_amount

-> FROM FoodOrders

-> GROUP BY restaurant_name

-> ORDER BY total_order_amount DESC;

+-----+-----+-----+

restaurant_name		number_of_orders		total_order_amount	
-----------------	--	------------------	--	--------------------	--

+-----+-----+-----+

KFC		2		1300.00	
-----	--	---	--	---------	--

Dominos		2		950.00	
---------	--	---	--	--------	--

McDonalds		1		300.00	
-----------	--	---	--	--------	--

+-----+-----+-----+

3 rows in set (0.01 sec)

mysql> SELECT 'Average Order Amount' AS kpi_name,

-> AVG(order_amount) AS kpi_value

-> FROM FoodOrders

-> UNION ALL

-> SELECT 'Unique Customers' AS kpi_name,

-> COUNT(DISTINCT customer_name) AS kpi_value

-> FROM FoodOrders;

+-----+-----+

kpi_name		kpi_value	
----------	--	-----------	--

```
+-----+-----+
| Average Order Amount | 510.000000 |
```

```
| Unique Customers    | 3.000000 |
```

```
+-----+-----+
```

2 rows in set (0.01 sec)