

HOMEWORK 7 - FRANCISCO CASTILLO

Contents

- Defined functions
- Solve for $u(x,y,t)$
- Solve for $v(x,y,t)$
- Outlet correction
- Calculate rhs
- Solve Poisson equation, V-cycle multigrid
- Project velocities using Lagrange multiplier
- Next time step
- Filled contour plots, only for $M=128$ and $N=64$
- Probes, only for $M=128$ and $N=64$
- Probes value for u , v and Y at $t=1$
- Plot the probes, only for $M=128$ and $N=64$
- GCI analysis

Defined functions

```
function u=ADI_u(u,M,N,dt,hx,hy,Re)

%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
[a,b,c,d]=uectors(u,M,N,dt,hx,hy,1/Re,1); %Obtain tridiagonal vectors
d=GaussTriSol(a,b,c,d); %Gaussian elimination
% Correspondance with u, obtain u(n+1/2)
for j=2:N+1
    for i=2:M
        u(i,j)=d((j-2)*(M-1)+i-1);
    end
end
% Update top and bottom boundaries (ghost cells), they depend on the
% interior
u(:,N+2)=-u(:,N+1);
u(:,1)=-u(:,2);

%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
[a,b,c,d]=uectors(u,M,N,dt,hx,hy,1/Re,2);
d=GaussTriSol(a,b,c,d);
for i=2:M
    for j=2:N+1
        u(i,j)=d((i-2)*N+j-1);
    end
end
% Update top and bottom boundaries (ghost cells), they depend on the
% interior
u(:,N+2)=-u(:,N+1); % Top
u(:,1)=-u(:,2); % Bottom

end

function v=ADI_v(v,M,N,dt,hx,hy,Re)
xiv=linspace(-hx/2,4+hx/2,M+2);
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
[a,b,c,d]=vectors(v,M,N,dt,hx,hy,1/Re,1); %Obtain tridiagonal vectors
% keyboard
d=GaussTriSol(a,b,c,d); %Gaussian elimination
% keyboard
% Correspondance with v, obtain v(n+1/2)
for j=2:N
    for i=2:M+1
        v(i,j)=d((j-2)*M+i-1);
    end
end
% Update left and right boundaries (ghost cells), as well as the outlet
% Neumann BC, they depend on the interior.
v(1,:)=-v(2,:); % Left
v(M+2,:)=-v(M+1,:); % Right
for i=1:M+2
    if (xiv(i)>=1.5 && xiv(i)<=2.5) % Outlet
        v(i,1)=(4/3)*v(i,2)-(1/3)*v(i,3);
    end
end

%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
[a,b,c,d]=vectors(v,M,N,dt,hx,hy,1/Re,2); %Obtain tridiagonal vectors
% keyboard
```

```

d=GaussTriSol(a,b,c,d); %Gaussian elimination
% keyboard
% Correspondance with v, obtain v(n+1/2)
for i=2:M+1
    for j=2:N
        v(i,j)=d((i-2)*(N-1)+j-1);
    end
end
% Update left and right boundaries (ghost cells), as well as the outlet
% Neumann BC, they depend on the interior.
v(1,:)=v(2,:); % Left
v(M+2,:)=v(M+1,:); % Right
for i=1:M+2
    if (xiv(i)>=1.5 && xiv(i)<=2.5) % Outlet
        v(i,1)=(4/3)*v(i,2)-(1/3)*v(i,3);
    end
end
end

function d=GaussTriSol(a,b,c,d)
    N=length(a);
    for i=2:N
        b(i)=b(i)-c(i-1)*a(i)/b(i-1);
        d(i)=d(i)-d(i-1)*a(i)/b(i-1);
    end
    d(N)=d(N)/b(N);
    for i=N-1:-1:1
        d(i)=(d(i)-c(i)*d(i+1))/b(i);
    end
end

function [u,v]=initialization(M,N,hx,hy)
%% Initialize u
u = zeros(M+1,N+2);
% Impose left and right boundaries, only once, since they do not depend on
% the interior nor they are altered.
yju=linspace(-hy/2,2+hy/2,N+2);
for j=1:N+2
    if (yju(j)>=0.5 && yju(j)<=1) % Inlet 1
        u(1,j)=-48*yju(j)^2+72*yju(j)-24;
    elseif (yju(j)>=1 && yju(j)<=1.5) % Inlet 2
        u(M+1,j)=24*yju(j)^2-60*yju(j)+36;
    end
end
%% Initialize v
v = zeros(M+2,N+1);
% Impose top and bottom boundaries, only once, since they do not depend on
% the interior except the outlet Neumann BC, which will be updated after
% iterations since for the initial condition it is satisfied.
xiv=linspace(-hx/2,4+hx/2,M+2);
for i=1:M+2
    if (xiv(i)>=0.5 && xiv(i)<=1) % Inlet 3
        v(i,N+1)=24*xiv(i)^2-36*xiv(i)+12;
    end
end
end

function [a,b,c,d] = uectors(u,M,N,dt,hx,hy,alpha,step)
dx=alpha*dt/hx^2;
dy=alpha*dt/hy^2;
d1=dx/2;
d2=dy/2;
if step==1
    a = -d1*ones((M-1)*N,1);
    b = (1+2*d1)*ones((M-1)*N,1);
    c = -d1*ones((M-1)*N,1);
    d = zeros((M-1)*N,1);
    for j=2:N+1
        for i=2:M
            if i==2 % Left boundary BCs
                a((j-2)*(M-1)+1)=0;
                d((j-2)*(M-1)+1)=d2*u(2,j-1)+(1-2*d2)*u(2,j)+d2*u(2,j+1)...
                    +d1*u(1,j); %u(1,j) fixed at initialization
            elseif i==M % Right boundary BCs
                c((j-2)*(M-1)+M-1)=0;
                d((j-2)*(M-1)+M-1)=d2*u(i,j-1)+(1-2*d2)*u(i,j)+d2*u(i,j+1)...
                    +d1*u(M+1,j); %u(M+1,j) fixed at initialization
            else % The top and bottom boundaries are imposed by updating the ghost
                % cells accordingly with them.
                d((j-2)*(M-1)+i-1)=d2*u(i,j-1)+(1-2*d2)*u(i,j)+d2*u(i,j+1);
            end
        end
    end
end

```

```

        end
    end
elseif step==2
    a = -d2*ones((M-1)*N,1);
    b = (1+2*d2)*ones((M-1)*N,1);
    c = -d2*ones((M-1)*N,1);
    d = zeros((M-1)*N,1);
    for i=2:M
        for j=2:N+1
            if j==2 % Bottom boundary BCs
                a((i-2)*N+1)=0;
                b((i-2)*N+1)=1+3*d2;
                d((i-2)*N+1)=d1*u(i-1,2)+(1-2*d1)*u(i,2)+d1*u(i+1,2);
            elseif j==N+1 % Top boundary BCs
                b((i-1)*N)=1+3*d2;
                c((i-1)*N)=0;
                d((i-1)*N)=d1*u(i-1,N+1)+(1-2*d1)*u(i,N+1)+d1*u(i+1,N+1);
            else % The left and right boundaries are imposed by initialization,
                % they do not change
                d((i-2)*N+j-1)=d1*u(i-1,j)+(1-2*d1)*u(i,j)+d1*u(i+1,j);
            end
        end
    end
end
end
end
end
end

```

```

function [a,b,c,d] = vvectors(v,M,N,dt,hx,hy,alpha,step)
xi=linspace(-hx/2,4+hx/2,M+2);
yj=linspace(0,2,N+1);
% keyboard
dx=alpha*dt/hx^2;
dy=alpha*dt/hy^2;
d1=dx/2;
d2=dy/2;
if step==1
    a = -d1*ones(M*(N-1),1);
    b = (1+2*d1)*ones(M*(N-1),1);
    c = -d1*ones(M*(N-1),1);
    d = zeros(M*(N-1),1);
    for j=2:N
        for i=2:M+1
            if i==2
                a((j-2)*M+1)=0;
                b((j-2)*M+1)=1+3*d1;
                d((j-2)*M+1)=d2*v(2,j-1)+(1-2*d2)*v(2,j)+d2*v(2,j+1);
            elseif i==M+1
                b((j-1)*M)=1+3*d1;
                c((j-1)*M)=0;
                d((j-1)*M)=d2*v(M+1,j-1)+(1-2*d2)*v(M+1,j)+d2*v(M+1,j+1);
            elseif (j==2 && xi(i)>=1.5 && xi(i)<=2.5)
                d(i-1)=d2*(4*v(i,2)/3-v(i,3)/3)+(1-2*d2)*v(i,2)+d2*v(i,3);
            else
                d((j-2)*M+i-1)=d2*v(i,j-1)+(1-2*d2)*v(i,j)+d2*v(i,j+1);
            end
        end
    end
elseif step==2
    a = -d2*ones(M*(N-1),1);
    b = (1+2*d2)*ones(M*(N-1),1);
    c = -d2*ones(M*(N-1),1);
    d = zeros(M*(N-1),1);
    for i=2:M+1
        for j=2:N
            if j==2
                a((i-2)*(N-1)+1)=0;
                if (xi(i)>=1.5 && xi(i)<=2.5)
                    b((i-2)*(N-1)+1)=1+(2-4/3)*d2;
                    c((i-2)*(N-1)+1)=-(2/3)*d2;
                end
                d((i-2)*(N-1)+1)=d1*v(i-1,2)+(1-2*d1)*v(i,2)+d1*v(i+1,2);
            elseif j==N
                c((i-1)*(N-1))=0;
                d((i-1)*(N-1))=d1*v(i-1,N)+(1-2*d1)*v(i,N)+d1*v(i+1,N)...
                    +d2*v(i,N+1);
            else
                d((i-2)*(N-1)+j-1)=d1*v(i-1,j)+(1-2*d1)*v(i,j)+d1*v(i+1,j);
            end
        end
    end
end
end
end
end
end

```

```

function [a,b,c,d] = vvectors(v,M,N,dt,hx,hy,alpha,step)

```

```

xi=linspace(-hx/2,4+hx/2,M+2);
yj=linspace(0,2,N+1);
% keyboard
dx=alpha*dt/hx^2;
dy=alpha*dt/hy^2;
d1=dx/2;
d2=dy/2;
if step==1
    a = -d1*ones(M*(N-1),1);
    b = (1+2*d1)*ones(M*(N-1),1);
    c = -d1*ones(M*(N-1),1);
    d = zeros(M*(N-1),1);
    for j=2:N
        for i=2:M+1
            if i==2
                a((j-2)*M+1)=0;
                b((j-2)*M+1)=1+3*d1;
                d((j-2)*M+1)=d2*v(2,j-1)+(1-2*d2)*v(2,j)+d2*v(2,j+1);
            elseif i==M+1
                b((j-1)*M)=1+3*d1;
                c((j-1)*M)=0;
                d((j-1)*M)=d2*v(M+1,j-1)+(1-2*d2)*v(M+1,j)+d2*v(M+1,j+1);
            elseif (j==2 && xi(i)>=1.5 && xi(i)<=2.5)
                d(i-1)=d2*(4*v(i,2)/3-v(i,3)/3)+(1-2*d2)*v(i,2)+d2*v(i,3);
            else
                d((j-2)*M+i-1)=d2*v(i,j-1)+(1-2*d2)*v(i,j)+d2*v(i,j+1);
            end
        end
    end
end
elseif step==2
    a = -d2*ones(M*(N-1),1);
    b = (1+2*d2)*ones(M*(N-1),1);
    c = -d2*ones(M*(N-1),1);
    d = zeros(M*(N-1),1);
    for i=2:M+1
        for j=2:N
            if j==2
                a((i-2)*(N-1)+1)=0;
                if (xi(i)>=1.5 && xi(i)<=2.5)
                    b((i-2)*(N-1)+1)=1+(2-4/3)*d2;
                    c((i-2)*(N-1)+1)=- (2/3)*d2;
                end
                d((i-2)*(N-1)+1)=d1*v(i-1,2)+(1-2*d1)*v(i,2)+d1*v(i+1,2);
            elseif j==N
                c((i-1)*(N-1))=0;
                d((i-1)*(N-1))=d1*v(i-1,N)+(1-2*d1)*v(i,N)+d1*v(i+1,N)...
                    +d2*v(i,N+1);
            else
                d((i-2)*(N-1)+j-1)=d1*v(i-1,j)+(1-2*d1)*v(i,j)+d1*v(i+1,j);
            end
        end
    end
end
end
end
end

```

```

function [phi,LinfR] = poisson (phi,rhs,hx,hy,nIterMax,tol)
    r = residual(phi,rhs,hx,hy);
    LinfR=zeros(nIterMax,1);
    LinfR(1)=InfNorm(r);
    for n=1:nIterMax
        phi = multigrid(phi,rhs,hx,hy);
        r = residual(phi,rhs,hx,hy);
        LinfR(n+1,1) = InfNorm(r);
        if LinfR(n+1,1)<tol
            break
        end
    end
    LinfR(n+2:nIterMax)=[];
end

```

```

function phi = multigrid(phi,rhs,hx,hy)
    M=size(phi,1)-2;
    N=size(phi,2)-2;
    phi = GaussSeidel(phi,rhs,hx,hy,1);
    if (M>2 || N>2)
        rh = residual(phi,rhs,hx,hy);
        r2h = restrict(rh);
        e2h = zeros(M/2+2,N/2+2);
        e2h = multigrid(e2h,r2h,2*hx,2*hy);
        eh = prolong(e2h);
        phi = phi+eh;
        phi = GaussSeidel(phi,rhs,hx,hy,1);
    end

```

```
end
```

```
function r2h = restrict(rh)
    M=size(rh,1)-2;
    N=size(rh,2)-2;
    M2h=M/2;
    N2h=N/2;
    r2h=zeros(M2h+2,N2h+2);
    rh(:,[1 end])=[];
    rh([1 end],:)=[];
    for i=1:M2h
        for j=1:N2h
            r2h(i+1,j+1) = 0.25*sum(sum(rh(2*i-1:2*i,2*j-1:2*j)));
        end
    end
    % Update the ghost cells
    r2h(1,:) = r2h(2,:);
    r2h(M2h+2,:) = r2h(M2h+1,:);
    r2h(:,1) = r2h(:,2);
    r2h(:,N2h+2) = r2h(:,N2h+1);
end
```

```
function eh = prolong(e2h)
    M2h=size(e2h,1)-2;
    N2h=size(e2h,2)-2;
    Mh=2*M2h;
    Nh=2*N2h;
    eh=zeros(Mh+2,Nh+2);
    e2h(:,[1 end])=[];
    e2h([1 end],:)=[];
    % Interior
    for i=1:M2h
        for j=1:N2h
            eh(2*i-1+1:2*i+1,2*j-1+1:2*j+1) = e2h(i,j);
        end
    end
    % Calculate the ghost cells
    eh(1,:) = eh(2,:);
    eh(Mh+2,:) = eh(Mh+1,:);
    eh(:,1) = eh(:,2);
    eh(:,Nh+2) = eh(:,Nh+1);
end
```

```
function phi = GaussSeidel (phi,rhs,hx,hy,n)
    for k=1:n
        M=size(phi,1)-2;
        N=size(phi,2)-2;
        h1=hy^2/(2*(hx^2+hy^2));
        h2=hx^2/(2*(hx^2+hy^2));
        h3=hx^2*hy^2/(2*(hx^2+hy^2));
        % Update the interior cells
        for i=2:M+1
            for j=2:N+1
                phi(i,j)=h1*(phi(i+1,j)+phi(i-1,j))...
                    +h2*(phi(i,j+1)+phi(i,j-1))-h3*rhs(i,j);
            end
        end
        % Update the ghost cells
        phi(1,:) = phi(2,:);
        phi(M+2,:) = phi(M+1,:);
        phi(:,1) = phi(:,2);
        phi(:,N+2) = phi(:,N+1);
    end
end
```

```
function r = residual(phi,rhs,hx,hy)
    M = size(phi,1)-2;
    N = size(phi,2)-2;
    r= zeros(size(phi));
    % Calculate the interior cells
    for i=2:M+1
        for j=2:N+1
            r(i,j)=rhs(i,j)-(phi(i+1,j)-2*phi(i,j)+phi(i-1,j))/hx^2 ...
                -(phi(i,j+1)-2*phi(i,j)+phi(i,j-1))/hy^2;
        end
    end
    % calculate the ghost cells
    r(1,:) = r(2,:);
    r(M+2,:) = r(M+1,:);
    r(:,1) = r(:,2);
```

```

        r(:,N+2) = r(:,N+1);
    end

function Linf = InfNorm(x)
    Linf= max(max(abs(x)));
end

function rhs=divV(u,v,M,N,hx,hy,dt)
rhs=zeros(M+2,N+2);
for i=2:M+1
    for j=2:N+1
        rhs(i,j)=(u(i,j)-u(i-1,j))/(hx*dt)+(v(i,j)-v(i,j-1))/(hy*dt);
    end
end
end

function v=outletCorrection(u,v,xv,hx,hy)
s=-sum(u(1,:))*hy+sum(u(end,:))*hy-sum(v(:,1))*hx+sum(v(:,end))*hx;
num=find(xv<=2.5,1,'last')-find(xv>=1.5,1)+1;
vcorr=s/(num*hx);
for i=find(xv>=1.5,1):find(xv<=2.5,1,'last')
    v(i,1)=v(i,1)+vcorr;
end
end

function [u,v]=LagProjection(u,v,phi,dt,hx,hy)
M=size(phi,1)-2;
N=size(phi,2)-2;
for i=1:M+1
    for j=1:N+2
        phix(i,j)=(phi(i+1,j)-phi(i,j))/hx;
    end
end
for i=1:M+2
    for j=1:N+1
        phiy(i,j)=(phi(i,j+1)-phi(i,j))/hy;
    end
end
u=u-dt*phix;
v=v-dt*phiy;
% Apply boundary conditions to ghost cells only
u(:,1)=-u(:,2);
u(:,N+2)=-u(:,N+1);
v(1,:)=-v(2,:);
v(M+2,:)=-v(M+1,:);
end

```

```

clear all; close all; format long; clc
axisSize=14;
markersize=16;
linewidth=3.5;
Lx = 4;
Ly = 2;
Mv = [1 0.5 0.25]*128;
Nv = [1 0.5 0.25]*64;
CFL = 1;
Re = 2;
nIterMax=50;
tol=1e-12;
p1(1)=0;
p2(1)=0;
p3(1)=0;
for i=1:length(Mv)

```

```

    M=Mv(i);
    N=Nv(i);
    if (M==128 && N==64)
        outputTime=[0.1 0.5 1 2];
    else
        outputTime=[0.1 0.5 1];
    end
    endtime=outputTime(end);
    hx = Lx/M;
    hy = Ly/N;
    if hx~=hy
        error('Cells not square')
    end

```

```

time=0;
%      dt=CFL*0.25*hx^2*Re;
dt=5e-3;
n=1;
% Define the points of the different meshes
xu=linspace(0,4,M+1);
yu=linspace(-hy/2,2+hy/2,N+2);
xv=linspace(-hx/2,4+hx/2,M+2);
yv=linspace(0,2,N+1);
% Define initial values
phi=zeros(M+2,N+2);
[u,v]=initialization(M,N,hx,hy);
iter=1;
t=0;
while time < endtime

```

```

    if (time < outputTime(n) && time+dt >= outputTime(n))
        dt=outputTime(n)-time;
        n=n+1;
    else
%          dt=CFL*0.25*hx^2*Re;
        dt=5e-3;
    end

```

Solve for u(x,y,t)

```
u=ADI_u(u,M,N,dt,hx,hy,Re);
```

Solve for v(x,y,t)

```
v=ADI_v(v,M,N,dt,hx,hy,Re);
```

Outlet correction

```
v=outletCorrection(u,v,xv,hx,hy);
```

Calculate rhs

```
rhs=divV(u,v,M,N,hx,hy,dt);
```

Solve Poisson equation, V-cycle multigrid

```
phi = poisson(phi,rhs,hx,hy,nIterMax,tol);
```

Project velocities using Lagrange multiplier

```
[u,v]=LagProjection(u,v,phi,dt,hx,hy);
```

Next time step

```
time=time+dt;
```

Filled contour plots, only for M=128 and N=64

```

if (M==128 && N==64 && ismember(time,outputTime))
% Plot u
figure(n-1)
contourf(xu,yu,u')
hold on
plot(1,0.5,'r.','markersize',markersize,'linewidth',linewidth)
axis([0 4 0 2])
caxis([-1.5 3])
colorbar
xlabel('$x$', 'Interpreter', 'latex')
ylabel('$y$', 'Interpreter', 'latex')
yticks([0 0.25 0.50 0.75 1.0 1.25 1.50 1.75 2.0]);
xticks([0 0.50 1.0 1.50 2.0 2.50 3.0 3.50 4.0]);
set(get(gca,'ylabel'),'rotation',0)
set(gca,'fontsize',axisSize)
pbaspect([2 1 1])
grid on
txt=['Latex/FIGURES/u_' num2str(n-1)];
saveas(gcf,txt,'eps')

```

```

% Plot v
figure(n+3)
contourf(xv,yv,v')
hold on
plot(1,1.5,'r.','markersize',markersize,'linewidth',linewidth)
axis([0 4 0 2])
caxis([-3 1])
colorbar
xlabel('$x$', 'Interpreter', 'latex')
ylabel('$y$', 'Interpreter', 'latex')
yticks([0 0.25 0.50 0.75 1.0 1.25 1.50 1.75 2.0]);
xticks([0 0.50 1.0 1.50 2.0 2.50 3.0 3.50 4.0]);
set(get(gca,'ylabel'),'rotation',0)
set(gca,'fontsize',axisSize)
pbaspect([2 1 1])
grid on
txt=['Latex/FIGURES/v_' num2str(n-1)];
saveas(gcf,txt,'eps')
end

```

Probes, only for M=128 and N=64

```

if (M==128 && N==64 && time<=2*dt)
    iter=iter+1;
    t=[t;time];
    p1(iter) = (u (find(xu==1),find(yu<=0.5,1,'last'))...
        +u (find(xu==1),find(yu>=0.5,1)))/2;
    p2(iter) = (v (find(xv<=1,1,'last'),find(yv==1.5))...
        +v (find(xv>=1,1),find(yv==1.5)))/2;
end

```

Probes value for u, v and Y at t=1

```

if time==1
    p11(i)= (u (find(xu==1),find(yu<=0.5,1,'last'))...
        +u (find(xu==1),find(yu>=0.5,1)))/2;
    p21(i)= (v (find(xv<=1,1,'last'),find(yv==1.5))...
        +v (find(xv>=1,1),find(yv==1.5)))/2;
end

```

```

end

```

Plot the probes, only for M=128 and N=64

```

if (M==128 && N==64)
    figure
    plot(t,p1,'linewidth',2)
    xlim([0 2])
    xlabel('$t$', 'Interpreter', 'latex')
    ylabel('$u(1,0.5,t)$', 'Interpreter', 'latex')
    set(gca,'fontsize',axisSize)
    grid on
    txt='Latex/FIGURES/probe1';
    saveas(gcf,txt,'eps')
    figure
    plot(t,p2,'linewidth',2)
    xlim([0 2])
    xlabel('$t$', 'Interpreter', 'latex')
    ylabel('$v(1,1.5,t)$', 'Interpreter', 'latex')
    set(gca,'fontsize',axisSize)
    grid on
    txt='Latex/FIGURES/probe2';
    saveas(gcf,txt,'eps')
end

```

```

end

```

GCI analysis

```

clc
r=2
Fsec=1.25
% Probe 1
p_u=log((p11(3)-p11(2))/(p11(2)-p11(1)))/log(r)
u_h0=p11(1)+(p11(1)-p11(2))/(r^p_u-1)
GCI21_u=Fsec*(p11(2)-p11(1))/(p11(1)*(r^p_u-1))

```



```
GCI32_u=Fsec*(p11(3)-p11(2))/(p11(2)*(r^p_u-1))
coeff_u=GCI21_u*r^p_u/GCI32_u
percent_u=GCI21_u*100
pause

% Probe 2
p_v=log((p21(3)-p21(2))/(p21(2)-p21(1)))/log(r)
v_h0=p21(1)+(p21(1)-p21(2))/(r^p_v-1)
GCI21_v=Fsec*(p21(2)-p21(1))/(p21(1)*(r^p_v-1))
GCI32_v=Fsec*(p21(3)-p21(2))/(p21(2)*(r^p_v-1))
coeff_v=GCI21_v*r^p_v/GCI32_v
percent_v=GCI21_v*100
% pause
```