

MCM 2025

Welcome to MCM 2025

We are delighted to welcome you to Chicago for the *16th International Conference on Monte Carlo and Quasi-Monte Carlo Methods in Scientific Computing*. The MCM conference series is, together with its sister conference series, the conferences on Monte Carlo Methods (MCM), a major event for researchers in the Monte Carlo and quasi-Monte Carlo community. We are glad to host MCM in Canada for a second time, the first being held in Montréal (2008).

MCM 2025 marks the thirty-year anniversary of the first MCM conference held in 1994. To celebrate this milestone, the organizing committee are excited to present a special panel session, followed by a Q&A. The panel members consist of Art Owen, Fred Hickernell, Frances Kuo, Alexander Keller and Josef Dick and the session will be moderated by Aretha Teckentrup. The motivation and purpose of this special event is to reflect on the past thirty years of progress in the field of MC and QMC methods and perhaps more importantly, to look ahead to what the big questions might reveal in the next thirty years and beyond.

As of July 5th, MCM 2024 features 137 talks, among them eight plenary talks, two tutorials, and twenty-four special sessions. The speakers come from a variety of scientific backgrounds, countries, institutions and stages of their career.

Located in South-West Ontario on the Grand River, Waterloo, or more widely known as part of the twin-cities of Kitchener-Waterloo (KW), offers cultural richness and technological innovation. Celebrated for its bustling tech scene, Waterloo has rightfully earned its part in the nickname "Silicon Valley North." In addition, KW boasts a rich cultural scene, highlighted by the annual Oktoberfest, the largest celebration of its kind outside of Germany. We hope that you enjoy what KW has to offer you away from campus!

We wish you a productive and interesting week at MCM 2024!

Fred Hickernell, Sou-Cheng Choi, Nathan Kirk, etc.
MCM 2025 Conference Organizers

Conference website: <https://ccbatiiit.github.io/mcm2025/>

Conference email: info@mcm2025chicago.org

Contents

MCM 2025	1
Welcome to MCM 2025	2
Contents	3
About MCM	4
History	4
Steering Committee	5
Scientific committee	6
Local Organizers	7
Local Technical and Support Team	7
Sponsors	7
Special Thanks	8
Schedule	9
Plenary Talks	23
Special Sessions	31
Abstracts	71
Special Session Talks	72
Contributed Talks	132
Practical Information	181
List of Participants	189

About MCM

History

The MCM Conference is a biennial meeting devoted to the study of Monte Carlo (MC) and quasi-Monte Carlo (QMC) methods, the relationships between the two classes of methods, and their effective application in different areas. Consistently attracting between one-hundred and two-hundred participants in recent years, its aim is to provide a forum where leading researchers and users can exchange information on the latest theoretical developments and important applications of these methods. The conference focuses primarily on the mathematical study of these techniques, their implementation and adaptation for concrete applications, and their empirical assessment.

The conference was initiated by Harald Niederreiter, who co-chaired the first seven conferences of the series. From 2006 onwards, the MCM Steering Committee has overseen the continuation of the conference series.

The previous instances of MCM were held in:

1. Las Vegas, USA (1994),
2. Salzburg, Austria (1996),
3. Claremont, USA (1998),
4. Hong Kong (2000),
5. Singapore (2002),
6. Juan-Les-Pins, France (2004),
7. Ulm, Germany (2006),
8. Montréal, Canada (2008),
9. Warsaw, Poland (2010),
10. Sydney, Australia (2012),
11. Leuven, Belgium (2014),
12. Stanford, USA (2016),
13. Rennes, France (2018),
14. Oxford, UK (2020, virtually),
15. Linz, Austria (2022).

Steering Committee

Josef Dick (Australia)

Fred J. Hickernell (USA)

Alexander Keller (Germany, Chair)

Peter Kritzer (Austria)

Pierre L'Ecuyer (Canada)

Christiane Lemieux (Canada)

Art B. Owen (USA)

Scientific committee

Christoph Aistleitner (Graz University of Technology, Austria)

Andrea Barth (University of Stuttgart, Germany)

Hector Cancela (University of the Republic, Uruguay)

Frédéric Céro (INRIA, France)

Nicolas Chopin (ENSAE, IPP, France)

Ronald Cools (KU Leuven, Belgium)

Josef Dick (UNSW, Australia)

Mike Giles (Mathematical Institute, University of Oxford, UK)

Paul Glasserman (Columbia University, USA)

Michael Gnewuch (University of Osnabrück, Germany)

Takashi Goda (University of Tokyo, Japan)

Stefan Heinrich (RPTU Kaiserslautern-Landau, Germany)

Fred J. Hickernell (Illinois Institute of Technology, USA)

Alexander Keller (NVIDIA, Germany)

Peter Kritzer (RICAM, Austrian Academy of Sciences, Austria)

Dirk Kroese (University of Queensland, Australia)

Frances Kuo (UNSW, Australia)

Gerhard Larcher (JKU Linz, Austria)

Christian Lécot (Université Savoie Mont-Blanc, France)

Pierre L'Ecuyer (University of Montreal, Canada)

Faming Liang (Purdue University, USA)

Eric Moulines (École Polytechnique, France)

Thomas Müller-Gronbach (University of Passau, Germany)

Harald Niederreiter (RICAM, Austrian Academy of Sciences, Austria)

Erich Novak (FSU Jena, Germany)

Art Owen (Stanford University, USA)

Gilles Pagès (Sorbonne Université, France)

Friedrich Pillichshammer (JKU Linz, Austria)

Michael Pitt (King's College London, UK)

Sebastian Reich (University of Potsdam, Germany)

Klaus Ritter (Fachbereich Mathematik, TU Kaiserslautern, Germany)

Gerardo Rubino (INRIA, France)

Claudia Schillings (Free University Berlin, Germany)

Wolfgang Schmid (Paris Lodron University of Salzburg, Austria)

Ian H. Sloan (UNSW, Australia)

Aretha Teckentrup (University of Edinburgh, UK)

Bruno Tuffin (INRIA, France)

Mario Ullrich (JKU Linz, Austria)

Arne Winterhof (RICAM, Austrian Academy of Sciences, Austria)

Local Organizers

Christiane Lemieux, Ben Feng, Nathan Kirk, Adam Kolkiewicz

Local Technical and Support Team

Greg Preston, Carla Daniels, Carlos Mendes, Lucy Simpson

Sponsors

Fields Institute for Research in Mathematical Sciences

<http://www.fields.utoronto.ca>

Royal Bank of Canada (RBC)

<https://www.rbcroyalbank.com>

Faculty of Mathematics, University of Waterloo

<https://uwaterloo.ca/math>

Department of Statistics and Actuarial Science, University of Waterloo

<https://uwaterloo.ca/statistics-and-actuarial-science>



Capital
Markets

Special Thanks

The conference organizers would like to thank all sponsors for making this event possible. We also want to express our gratitude towards Professors Stefan Steiner and Changbao Wu (former and current Department Chair of Statistics and Actuarial Science at the University of Waterloo) and Professor Mark Giesbrecht (Dean, Faculty of Mathematics) for providing us with resources to help with the organization of this conference. We also thank the University of Waterloo for providing us with the space needed to host this conference.

We are also very grateful to our staff colleagues in the Department of Statistics and Actuarial Science for their unwavering assistance with many aspects of the organization, with special thanks in particular to Greg Preston, as well as Carla Daniels, Anthea Dunne, Carlos Mendes and Lucy Simpson.

We wish to extend our thanks to the entire Steering Committee and Scientific Program Committee, and past MCM conference organizers for their contribution and support. We also thank our plenary speakers, tutorial speakers, special session organizers, and all session chairs for their help and support with the scientific organisation of the conference. We are particularly grateful to Alex Keller, Frances Kuo, Peter Kritzer and Art Owen for providing detailed feedback and suggestions based on their past experience with the organization of the MCM conference.

Schedule

Mon, Jul 28	Session
08:00–17:30	Registration Desk Open
08:45–09:00	Conference Opening
09:00–10:00	Plenary Talk by Matt Pharr
10:00–10:30	Coffee Break
10:30–12:30	Track A: Stochastic Computation and Complexity, Part I
10:30–12:30	Track B: Domain Uncertainty Quantification
10:30–12:30	Track C: Nested expectations: models and estimators, Part I
10:30–12:30	Track D: Hardware or Software for (Quasi-)Monte Carlo Algorithms, Part I
10:30–12:30	Track E: Technical Session 1 - Markov Chain Monte Carlo
12:30–14:00	Lunch Break
14:00–15:00	Plenary Talk by Christiane Lemieux, U of Waterloo, Golden ratio nets and sequences
15:00–15:30	Coffee Break
15:30–17:30	Track F: Stochastic Computation and Complexity, Part II
15:30–17:30	Track G: Recent advances in optimization under uncertainty
15:30–17:30	Track H: Computational Methods for Low-discrepancy Sampling and Applications
15:30–17:30	Track I: Technical Session 4 - Quasi-Monte Carlo, Part 1
15:30–17:30	Track J: Technical Session 12 - PDEs
	RECEPTION

Tue, Jul 29	Session
08:30–17:30	Registration Desk Open
09:00–10:00	Plenary Talk by Peter Glynn, Stanford U, Combining Simulation and Linear Algebra: COSIMLA
10:00–10:30	Coffee Break
10:30–12:30	Track A: Stochastic Computation and Complexity, Part III
10:30–12:30	Track B: Next-generation optimal experimental design: theory, scalability, and real world impact: Part I
10:30–12:30	Track C: Heavy-tailed Sampling
10:30–12:30	Track D: Frontiers in (Quasi-)Monte Carlo and Markov Chain Monte Carlo Methods, Part I
10:30–12:30	Track E: Technical Session 2 - Bayesian Methods
12:30–14:00	Lunch Break
14:00–15:00	Plenary Talk by Roshan Joseph, Georgia Institute of Technology, Sensitivity and Screening: From Monte Carlo to Experimental Design
15:00–15:30	Coffee Break
15:30–17:30	Track F: Stochastic Computation and Complexity, Part IV
15:30–17:30	Track G: Next-generation optimal experimental design: theory, scalability, and real world impact: Part II
15:30–17:30	Track H: Advances in Rare Events Simulation
15:30–17:30	Track I: Frontiers in (Quasi-)Monte Carlo and Markov Chain Monte Carlo Methods, Part II
15:30–17:30	Track J: Technical Session 5 - Quasi-Monte Carlo, Part 2

Wed, Jul 30 Session

11

08:30–16:30	Registration Desk Open
09:00–10:00	Plenary Talk by Michaela Szölgyenyi, U of Klagenfurt, An optimal transport approach to quantifying model uncertainty of SDEs
10:00–10:30	Coffee Break
10:30–12:30	Track A: Stochastic Computation and Complexity, Part V
10:30–12:30	Track B: Statistical Design of Experiments
10:30–12:30	Track C: Advances in Adaptive Hamiltonian Monte Carlo
10:30–12:30	Track D: Technical Session 15 - Simulation
10:30–12:30	Track E: Technical Session 6 - Sampling
12:30–14:00	Lunch Break
14:00–16:00	Track F: Stochastic Optimization
14:00–16:00	Track G: Recent Progress on Algorithmic Discrepancy Theory and Applications
14:00–16:00	Track H: Monte Carlo Applications in High-performance Computing, Computer Graphics, and Computational Science
14:00–16:00	Track I: Technical Session 16 - Statistics
14:00–16:00	Track J: Technical Session 10 - Langevin
16:16:30	Coffee Break
	CONFERENCE DINNER

Thu, Jul 31 Session

08:30–17:30	Registration Desk Open
09:00–10:00	Plenary Talk by Uros Seljak, UC Berkeley, Gradient-Based MCMC Sampling: Methods and Optimization Strategies
10:00–10:30	Coffee Break
10:30–12:30	Track A: QMC and Applications Part I
10:30–12:30	Track B: Analysis of Langevin and Related Sampling Algorithms, Part I
10:30–12:30	Track C: Nested expectations: models and estimators, Part II
10:30–12:30	Track D: Technical Session 8 - Finance
10:30–12:30	Track E: Technical Session 13 - ML & Optimization
12:30–14:00	Lunch Break
14:00–15:00	Plenary Talk by Nicolas Chopin, Institut Polytechnique de Paris, Saddlepoint Monte Carlo and its application to exact ecological inference
15:00–15:30	Coffee Break
15:30–17:30	Track F: QMC and Applications Part II
15:30–17:30	Track G: Analysis of Langevin and Related Sampling Algorithms, Part II
15:30–17:30	Track H: Recent Advances in Stochastic Gradient Descent
15:30–17:30	Track I: Technical Session 7 - Sampling
15:30–17:30	Track J: Technical Session 11 - SDEs

Fri, Aug 1 Session

08:30–12:15	Registration Desk Open
09:00–10:30	Track A: Forward and Inverse Problems for Stochastic Reaction Networks
09:00–10:30	Track B: Hardware or Software for (Quasi-)Monte Carlo Algorithms, Part II
09:00–10:30	Track C: Technical Session 3 - Simulation
09:00–10:30	Track D: Technical Session 9 - Sampling
09:00–10:30	Track E: Technical Session 14 - Markov Chain Monte Carlo
10:30–11	Coffee Break
11:00–12:00	Plenary Talk by Veronika Rockova
12:00–12:15	Closing Remarks

Registration Desk Open					
Conference Opening					
9:00 – 10:00	Plenary Talk: <i>Matt Phar</i> , p. ?? Chair:				
Coffee Break					
	Special Session, TBD Stochastic Computation & Complexity, Part I, p. 32 Chair: <i>TBD</i>	Special Session, TBD Domain UQ, p. 33 Chair: <i>TBD</i>	Special Session, TBD Nested expectations: models & estimators, Part I, p. 34 Chair: <i>TBD</i>	Special Session, TBD Hardware or Software for (Q)MC Algorithms, Part I, p. 35 Chair: <i>TBD</i>	TBD Tech. Sess. 1 - MC Chair: <i>TBD</i>
10:30–12:30	<i>Chengcheng Ling</i> , Quantitative approximation of stochastic kinetic equations: from discrete to continuum, p. 72	<i>André-Alexander Zepernick</i> , Domain UQ for stationary & time-dependent PDEs using QMC, p. 75	<i>Vesa Kaarnioja</i> , QMC for Bayes optimal Exp. Design with application to inverse problems governed by PDEs, p. 78	<i>Mike Giles</i> , CUDA implementation of MLMC on NVIDIA GPUs, p. 80	<i>Zhihao Wang</i> , Stereographic Multi-Try Metropolis Algorithms for Heavy-tailed Sampl., p. 132
10:30–12:30	<i>Andreas Neuenkirch</i> , A strong order 1.5 boundary preserving discretization scheme for scalar SDEs defined in a domain, p. 73	<i>Carlos Jerez-Hanckes</i> , Domain UQ for Electromagnetic Wave Scattering via First-Order Sparse Boundary Element Approximation, p. 76	<i>Sebastian Krumscheid</i> , Double-loop RQMC estimator for nested integration, p. 79	<i>Pieter-Jan Robbe</i> , ML QMC without replications, p. 81	<i>Ruben Seyer</i> , Creating rejection-free samplers by rebalancing skew-balanced jump processes, p. 133
10:30–12:30	<i>Christopher Rauhögger</i> , An adaptive Milstein-type method for strong approximation of systems of SDEs with a discontinuous drift coefficient, p. 73	<i>Jürgen Dölz</i> , Quantifying uncertainty in spectral clusterings: expectations for perturbed & incomplete data, p. 77	<i>Vinh Hoang</i> , Posterior-Free A-Optimal Bayes DOE via Conditional Expectation, p. 79	<i>Irina-Beatrice Haas</i> , A nested ML MC framework for efficient simulations on FPGAs, p. 81	<i>Philippe Gagnon</i> , Theoretical guarantees for lifted samplers, p. 134
10:30–12:30	<i>Verena Schwarz</i> , Stong order 1 adaptive approximation of jump-diffusion SDEs with discontinuous drift, p. 74	<i>Harri Hakula</i> , Model Problems for PDEs on Uncertain Domains, p. 77	<i>Chung Ming Loi</i> , Scalable & User-friendly QMC Sampl. with UMBridge, p. 82		

Jul 28, 2025 – Afternoon

Lunch Break					
14:00–15:00	Plenary Talk: <i>Christiane Lemieux, U of Waterloo, Golden ratio nets and sequences</i> , p. 24				Chair:
Coffee Break					
	Special Session, TBD Stochastic Computation & Complexity, Part II, p. 37 Chair: <i>TBD</i>	Special Session, TBD Recent advances in Opt. under uncertainty, p. 38 Chair: <i>TBD</i>	Special Session, TBD Comp. Methods for LD Sampl. & Appl., p. 39 Chair: <i>TBD</i>	TBD Tech. Sess. 4 - QMC, Part 1 Chair: <i>TBD</i>	TBD Tech. Sess. 12 - PDEs Chair: <i>TBD</i>
15:30–17:30	<i>Kateryna Pozharska</i> , Optimal designs for function discretization & construction of tight frames, p. 83	<i>Tapio Helin</i> , Stability of Expected Utility in Bayes Optimal Exp. Design, p. 85	<i>Makram Chahine</i> , Improving Efficiency of Sampl.-based Motion Planning via Message-Passing MC, p. 88	<i>Christian Weiss</i> , Halton Sequences, Scrambling & the Inverse Star-Discrepancy, p. 142	<i>Adrien Richou</i> , A probabilistic Numerical method for semi-linear elliptic PDEs, p. 165
15:30–17:30	<i>Michael Gnewuch</i> , Optimality of deterministic & RQMC-cubatures on several scales of function spaces, p. 84	<i>Arved Bartuska</i> , Efficient expected information gain estimators based on the RQMC method, p. 86	<i>Nathan Kirk</i> , Minimizing the Stein Discrepancy, p. 88	<i>Xiaoda Xu</i> , Star discrepancy & uniform approximation under weighted simple & stratified random Sampl., p. 142	<i>Abdujabar Rasulov</i> , MC method for the Spatially Homogenous Boltzmann equation, p. 165
15:30–17:30	<i>Leszek Plaskota</i> , Complexity of approximating piecewise smooth functions in the presence of deterministic or random noise, p. 85	<i>Karina Koval</i> , Subspace accelerated measure transport methods for fast & scalable sequential Exp. Design, p. 86	<i>Gregory Seljak</i> , An Empirical Evaluation of Robust Estimators for RQMC, p. 89	<i>Sifan Liu</i> , Transport QMC, p. 143	<i>Miguel Alvarez</i> , A New Approach for Unbiased Estimation of Parameters of Partially Observed Diffusions, p. 166
15:30–17:30	<i>Johannes Milz</i> , RQMC methods for risk-averse stochastic Opt., p. 87	<i>François Clément</i> , Searching Permutations for Constructing LD Point Sets & Investigating the Kritzing Sequence, p. 90	<i>Ambrose Emmett-Iwaniw</i> , Using Normalizing Flows for Efficient Quasi-Random Sampl. for Copulas, p. 143	<i>Håkon Hoel</i> , High-order adaptive methods for exit times of diffusion processes & reflected diffusions, p. 167	
RECEPTION					

Jul 29, 2025 – Morning

Registration Desk Open					
09:00–10:00	Plenary Talk: <i>Peter Glynn, Stanford U, Combining Simulation and Linear Algebra: COSIMLA</i> , p. 25 Chair:				
Coffee Break					
	Special Session, TBD Stochastic Computation & Complexity, Part III, p. 41 Chair: <i>TBD</i>	Special Session, TBD Next-gen optimal Exp. Design: theory, scalability, & real world impact: Part I, p. 42 Chair: <i>TBD</i>	Special Session, TBD Heavy-tailed Sampl., p. 44 Chair: <i>TBD</i>	Special Session, TBD Frontiers in (Q)MC & MC Methods, Part I, p. 46 Chair: <i>TBD</i>	TBD Tech. Sess. 2 - Bayes Methods Chair: <i>TBD</i>
10:30–12:30	<i>Sotirios Sabanis,</i> Wasserstein Convergence of Score-based Generative Models under Semiconvexity & Discontinuous Gradients, p. 91	<i>Ayoub Belhadji,</i> Weighted quantization using MMD: From mean field to mean shift via gradient flows, p. 91	<i>Sebastiano Grazzi,</i> Parallel computations for Metropolis Markov chains Based on Picard maps, p. 93	<i>Hwanwoo Kim,</i> Enhancing Gaussian Process Surrogates for Opt. & Posterior Approximation via Random Exploration, p. 93	<i>Lorenzo Nagar,</i> Optimizing Generalized Hamiltonian MC for Bayes Inference Appl., p. 135
10:30–12:30	<i>Adrien Corenflos,</i> A recursive MC approach to optimal Bayes Exp. Design, p. 92	<i>Hamza Ruzaygat,</i> Bayes Anomaly Detection in Variable-Order & Variable-Diffusivity Fractional Mediums, p. 136			
10:30–12:30	<i>Arghya Datta,</i> Theoretical Guarantees of Mean Field Variational Inference for Bayes Principal Component Anal., p. 137				
10:30–12:30	<i>Jimmy Lederman,</i> Bayes Anal. of Latent Underdispersion Using Discrete Order Stat., p. 137				

Jul 29, 2025 – Afternoon

Lunch Break					
14:00–15:00	Plenary Talk: <i>Roshan Joseph, Georgia Institute of Technology, Sensitivity and Screening: From Monte Carlo to Experimental Design</i> , p. 26 Chair: TBD				
Coffee Break					
	Special Session, TBD Stochastic Computation & Complexity, Part IV, p. 47 Chair: <i>TBD</i>	Special Session, TBD Next-gen optimal Exp. Design: theory, scalability, & real world impact: Part II, p. 48 Chair: <i>TBD</i>	Special Session, TBD Advances in Rare Events Sim., p. 50 Chair: <i>TBD</i>	Special Session, TBD Frontiers in (Q)MC & MC Methods, Part II, p. 51 Chair: <i>TBD</i>	TBD Tech. Sess. 5 - QMC, Part 2 Chair: <i>TBD</i>
15:30–17:30	<i>Larisa Yaroslavtseva</i> , Optimal strong approximation of SDEs with Hölder continuous drift coefficient, p. 94 <i>Alexander Steinicke</i> , Malliavin Differentiation of Lipschitz SDEs & BSDEs & an Application to Quadratic Forward-Backward SDEs, p. 95	<i>jacopo iollo</i> , Diffusion-Based Bayes Exp. Design: Advancing BED for Practical Appl., p. 96 <i>Alen Alexanderian</i> , Goal Oriented Sensor Placement for Infinite-Dimensional Bayes Inverse Problems, p. 97	<i>Bruno Tuffin</i> , Asymptotic robustness of smooth functions of rare-event estimators, p. 99 <i>Shyam Mohan Subbiah Pillai</i> , Estimating rare event probabilities associated with McKean–Vlasov SDEs, p. 100	<i>Takashi Goda</i> , Quasi-uniform QMC digital nets, p. 101 <i>Ziang Niu</i> , Boosting the inference for generative models by (Q)MC resampling, p. 102	<i>Peter Kritzer</i> , Approximation using median lattice algorithms, p. 144 <i>Yang Liu</i> , Convergence Rates of RQMC Methods under Various Regularity Conditions, p. 145
15:30–17:30	<i>Gunther Leobacher</i> , Tractability of L_2 -approximation & integration in weighted Hermite spaces of finite smoothness, p. 95	<i>Tommie Catanach</i> , Robust Bayes Optimal Exp. Design under Model Misspecification, p. 97	<i>Victor Elvira</i> , Multiple IS for Rare Event Sim. in Communication Systems, p. 101	<i>Chenyang Zhong</i> , A hit & run approach for Sampl. & analyzing ranking models, p. 103	<i>Jakob Dilen</i> , Use of rank-1 lattices in the Fourier neural operator, p. 146
15:30–17:30	<i>Xun Huan</i> , Optimal Pilot Sampl. for Multi-fidelity MC Methods, p. 98	<i>Aadit Jain</i> , Investigating the Optimum RQMC Batch Size for Betting & Empirical Bernstein Confidence Intervals, p. 146			

Jul 30, 2025 – Morning

Registration Desk Open					
09:00–10:00	Plenary Talk: <i>Michaela Szölgényi, U of Klagenfurt, An optimal transport approach to quantifying model uncertainty of SDEs</i> , p. 27 Chair: TBD				
Coffee Break					
10:30–12:30	Special Session, TBD Stochastic Computation & Complexity, Part V, p. 52 Chair: <i>TBD</i>	Special Session, TBD Stat. DOE, p. 53 Chair: <i>TBD</i>	Special Session, TBD Advances in Adaptive HMC, p. 55 Chair: <i>TBD</i>	TBD Tech. Sess. 15 - Sim. Chair: <i>TBD</i>	TBD Tech. Sess. 6 - Sampl. Chair: <i>TBD</i>
	<i>Stefan Heinrich</i> , On the quantum complexity of parametric integration in Sobolev spaces, p. 103	<i>Simon Mak</i> , Respecting the boundaries: Space-filling designs for surrogate modeling with boundary information, p. 105	<i>Bob Carpenter</i> , GIST: Gibbs self-tuning for locally adapting Hamiltonian MC, p. 107	<i>Philippe Blondeel</i> , Combining QMC with Stochastic Optimal Control for Trajectory Opt. of Autonomous Vehicles in Mine Counter Measure Simulations, p. 173	<i>Akash Sharma</i> , Sampl. with constraints, p. 147
	<i>Bernd Käßemodel</i> , Quantum Integration in Tensor Product Besov Spaces, p. 104	<i>Chaofan Huang</i> , Factor Importance Ranking & Selection using Total Indices, p. 105	<i>Nawaf Bou-Rabee</i> , Acceleration of the No-U-Turn Sampler, p. 107	<i>Rino Persiani</i> , A MC Approach to Designing a Novel Sample Holder for Enhanced UV-Vis Spectroscopy, p. 174	<i>Joonha Park</i> , Sampl. from high-dimensional, multimodal distributions using automatically tuned, tempered Hamiltonian MC, p. 148
10:30–12:30	<i>Chih-Li Sung</i> , Stacking designs: designing multi-fidelity computer experiments with target predictive accuracy, p. 106	<i>Trevor Campbell</i> , AutoStep: Locally adaptive involutive MCMC, p. 108	<i>Prasanth Shyamsundar</i> , ARCANEReweighting: A technique to tackle the sign problem in the Sim. of collider events in high energy physics, p. 175	<i>Arne Bouillon</i> , Localized consensus-based Sampl. for non-Gaussian distributions, p. 149	
10:30–12:30	<i>Chirag Modi</i> , ATLAS: Adapting Trajectory Lengths & Step-Size for Hamiltonian MC, p. 109	<i>Nicole Aretz</i> , Multifidelity & Surrogate Modeling Approaches for UQ in Ice Sheet Simulations, p. 176	<i>Alex Shkolnik</i> , IS for Hawkes Processes, p. 149		

Jul 30, 2025 – Afternoon

Lunch Break					
	Special Session, TBD Stochastic Opt., p. 57 Chair: <i>TBD</i>	Special Session, TBD Recent Progress on Algorithmic Discr. Theory & Appl., p. 58 Chair: <i>TBD</i>	Special Session, TBD MC Appl. in HPC, Computer Graphics, & Computational Science, p. 60 Chair: <i>TBD</i>	TBD Tech. Sess. 16 - Stat. Chair: <i>TBD</i>	TBD Tech. Sess. 10 - Langevin Chair: <i>TBD</i>
14:00–16:00	<i>Shane Henderson</i> , A New Convergence Anal. of Two Stochastic Frank-Wolfe Algorithms , p. 110	<i>Haotian Jiang</i> , Algorithmic Discr. Theory: An Overview, p. 111	<i>Silei Song</i> , WoS-NN: Collaborating Walk-on-Spheres with ML to Solve Ellip- tic PDEs, p. 112	<i>Kazeem Adeleke</i> , Empirical Stat. Comparative Anal. of SNP Heritability Estimators & Gradient Boosting Machines (GBM) Using Genetic Data from the UK Biobank, p. 176	<i>Attila Lovas</i> , Stochastic gradient Langevin dynamics with non-stationary data, p. 158
14:00–16:00	<i>Raghu Bollapragada</i> , MC Based Adaptive Sampl. Approaches for Stochastic Opt., p. 110	<i>Peng Zhang</i> , Improving the Design of Randomized Experiments via Discr. Theory, p. 111	<i>Carles Domingo-Enrich</i> , Cheap permutation testing, p. 177	<i>Iosif Lytras</i> , Sampl. with Langevin Dynamics from non-smooth & non-logconcave potentials., p. 159	
14:00–16:00	<i>Aleksandar Nikolov</i> , Online Factorization for Online Discrepancy Minimization, p. 112	<i>Christopher Draper</i> , Moving PCG beyond LCGs, p. 178	<i>Sara Pérez-Vieites</i> , Langevin-based strategies for nested particle filters, p. 160		
14:00–16:00	<i>Yiming Xu</i> , Hybrid least squares for learning functions from highly noisy data, p. 178	<i>Nikolaos Makras</i> , Taming the Interacting Particle Langevin Algorithm – The Superlinear Case, p. 161			
Coffee Break					
CONFERENCE DINNER					

Jul 31, 2025 – Morning

Registration Desk Open					
09:00–10:00	Plenary Talk: <i>Uros Seljak, UC Berkeley, Gradient-Based MCMC Sampling: Methods and Optimization Strategies</i> , p. 28 Chair:				
Coffee Break					
	Special Session, TBD QMC & Appl. Part I, p. 61 Chair: <i>TBD</i>	Special Session, TBD Anal. of Langevin & Related Sampl. Algorithms, Part I, p. 62 Chair: <i>TBD</i>	Special Session, TBD Nested expectations: models & estimators, Part II, p. 63 Chair: <i>TBD</i>	TBD Tech. Sess. 8 - Finance Chair: <i>TBD</i>	TBD Tech. Sess. 13 - ML & Opt. Chair: <i>TBD</i>
10:30–12:30	<i>Felix Bartel</i> , Exact discretization, tight frames & recovery via D-optimal designs, p. 113	<i>Lihan Wang</i> , Convergence rates of kinetic Langevin dynamics with weakly confining potentials, p. 116	<i>RAUL TEMPONE</i> , ML RQMC estimator for nested expectations, p. 118	<i>Matyokub Bakoev</i> , The SDEs of the Heston Model for Option Pricing, p. 153	<i>Frédéric Blondeel</i> , Learning cooling strategies in simulated annealing through binary interactions, p. 168
10:30–12:30	<i>Zhiqian He</i> , High-dimensional density estimation on unbounded domain, p. 114	<i>Peter Whalley</i> , Randomized Splitting Methods & Stochastic Gradient Algorithms, p. 117	<i>Matteo Raviola</i> , Stochastic gradient with least-squares control variates, p. 119	<i>Vincent Zhang</i> , Characterizing Efficacy of Geometric Brownian Motion Expectation-based Simulations on Low-Volatility American Common Stocks, p. 154	<i>Du Ouyang</i> , Accuracy of Discretely Sampled Stochastic Policies in Continuous-Time Reinforcement Learning, p. 168
10:30–12:30	<i>Mou Cai</i> , L2-approximation: using randomized lattice algorithms & QMC hyperinterpolation, p. 115	<i>Xiaoou Cheng</i> , Delocalization of Bias in Unadjusted Hamiltonian MC, p. 117	<i>Philipp Guth</i> , A one-shot method for Bayes optimal Exp. Design, p. 119	<i>Hao Quan</i> , Efficient Pricing for Variable Annuity via Sim., p. 156	<i>Wei Cai</i> , Martingale deep neural networks for quasi-linear PDEs & stochastic optimal controls in 10,000 dimensions, p. 169
10:30–12:30	<i>Frances Y. Kuo</i> , Application of QMC to Oncology, p. 115	<i>Yiqing Zhou</i> , Minimizing Functions with Sparse Samples: A Fast Interpolation Approach, p. 170			

Jul 31, 2025 – Afternoon

	Lunch Break				
14:00–15:00	Plenary Talk: <i>Nicolas Chopin, Institut Polytechnique de Paris, Saddlepoint Monte Carlo and its application to exact ecological inference</i> , p. 30 Chair:				
	Coffee Break				
	Special Session, TBD QMC & Appl. Part II, p. 64 Chair: <i>TBD</i>	Special Session, TBD Anal. of Langevin & Related Sampl. Algorithms, Part II, p. 65 Chair: <i>TBD</i>	Special Session, TBD Recent Advances in Stochastic Gradient Descent, p. 66 Chair: <i>TBD</i>	TBD Tech. Sess. 7 - Sampl. Chair: <i>TBD</i>	TBD Tech. Sess. 11 - SDEs Chair: <i>TBD</i>
15:30–17:30	<i>Kosuke Suzuki</i> , Quasi-uniform QMC lattice point sets, p. 120	<i>Krishnakumar Balasubramanian</i> , Finite-Particle Convergence Rates for Stein Variational Gradient Descent, p. 121	<i>Jose Blanchet</i> , Inference for Stochastic Gradient Descent with Infinite Variance, p. 125	<i>Kun-Lin Kuo</i> , Revisiting the Gibbs Sampler: A Conditional Modeling Perspective, p. 150	<i>Fabio Zoccolan</i> , Dynamical Low-Rank Approximation for SDEs: an interacting particle-system ROM, p. 161
15:30–17:30	<i>Zexin Pan</i> , QMC confidence intervals using quantiles of randomized nets, p. 120	<i>Yifan Chen</i> , Convergence of Unadjusted Langevin in High Dimensions: Delocalization of Bias, p. 122	<i>Jing Dong</i> , Stochastic Gradient Descent with Adaptive Data, p. 125	<i>Sascha Holl</i> , Concatenation of Markov processes for MC Integration, p. 150	<i>Riccardo Saporiti</i> , Comparing Probabilistic Load Forecasters: SDEs & Deep Learning, p. 163
15:30–17:30	<i>Dirk Nuyens</i> , Approximation of multivariate periodic functions, p. 121	<i>Molei Tao</i> , Langevin-Based Sampl. under Nonconvex Constraints, p. 123	<i>Josephine Westermann</i> , Polynomial approximation for efficient transport-based Sampl., p. 152	<i>Leon Wilkosz</i> , Forward Propagation of Low Discrepancy Through McKean–Vlasov Dynamics: From QMC to MLQMC, p. 164	
15:30–17:30	<i>Stefan Oberdörster</i> , Accelerated Mixing of the No-U-turn Sampler, p. 123	<i>Soumyadip Ghosh</i> , Fast Approximate Matrix Inversion via MCMC for Linear System Solvers, p. 152			

Aug 1, 2025 – Morning

Registration Desk Open				
	Special Session, TBD Forward & Inverse Problems for Stochastic Reaction Networks, p. 67 Chair: <i>TBD</i>	Special Session, TBD Hardware or Software for (Q)MC Algorithms, Part II, p. 68 Chair: <i>TBD</i>	TBD Tech. Sess. 3 - Sim. Chair: <i>TBD</i>	TBD Tech. Sess. 9 - Sampl. Chair: <i>TBD</i>
09:00–10:30	<i>Maksim Chupin</i> , Filtered Markovian Projection: Dimensionality Reduction in Filtering for Stochastic Reaction Networks, p. 126	<i>Niklas Baumgarten</i> , A High-performance Multi-level MC Software for Full Field Estimates & Appl. in Optimal Control, p. 129	<i>Yashveer Kumar</i> , MC Sim. approach to solve distributed order fractional Math. model, p. 139	<i>Nicola Branchini</i> , Revisiting self-normalized IS: new methods & diagnostics, p. 156 <i>Kevin Bitterlich</i> , Delayed Acceptance Slice Sampl.: A Two-Level method for Improved Efficiency in High-Dimensional Settings, p. 170
09:00–10:30	<i>Zhou Fang</i> , Fixed-budget Sim. method for growing cell populations, p. 127	<i>Aleksei Sorokin</i> , QMC Generators, Randomization Routines, & Fast Kernel Methods, p. 130	<i>Serena Fattori</i> , Benchmarking the Geant4-DNA 'UHDR' Example for MC Sim. of pH Effects on Radiolytic Species Yields Using a Mesoscopic Approach, p. 139	<i>Daniel Yukimura</i> , Quantitative results on Sampl. from quasi-stationary distributions, p. 157 <i>Reuben Cohn-Gordon</i> , Gradient-based MCMC in high dimensions, p. 171
09:00–10:30	<i>Muruhan Rathinam</i> , State & parameter inference in stochastic reaction networks, p. 127	<i>Johannes Krotz</i> , Hybrid MC methods for kinetic transport, p. 130	<i>Toon Ingelaere</i> , ML Sim. of ensemble Kalman methods: interactions across levels, p. 141	<i>Philip Schaer</i> , Parallel Affine Transformation Tuning: Drastically Improving the Effectiveness of Slice Sampl., p. 172
09:00–10:30	<i>Sophia Münker</i> , Dimensionality Reduction for Efficient Rare Event Estimation, p. 128	<i>Muhammad Noor ul Amin</i> , Adaptive Max-EWMA Control Chart with SVR: MC Sim. for Run Length Anal., p. 141	<i>Annabelle Carrell</i> , Low-Rank Thinning, p. 173	
Coffee Break				
14:00 – 15:00	Plenary Talk: <i>Veronica</i> , p. ?? Chair:			

Aug 1, 2025 – Afternoon

Closing Remarks

Plenary Talks

Mon, Jul 28 14:00–15:00



Golden ratio nets and sequences

Christiane Lemieux

University of Waterloo

clemieux@uwaterloo.ca

Coauthor(s): Nathan Kirk and Jaspar Wiart

In this talk, we discuss nets and sequences constructed in an irrational base, focusing on the case of a base given by the golden ratio φ . We provide a complete framework to study equidistribution properties of nets in base φ , which among other things requires the introduction of a new concept of prime elementary intervals which differ from the standard definition used for integer bases. We define the one-dimensional van der Corput sequence in base φ and two-dimensional Hammersley point sets in base φ and we prove some properties for $(0, 1)$ -sequences and $(0, m, 2)$ -nets in base φ , respectively. This part of the talk is based on [1].

Building on this new framework, we propose an *interlaced Halton sequence* that makes use of integer *and* irrational-based van der Corput sequences and show empirically improved performance compared to the traditional Halton sequence [2]. In addition, we propose a scrambling algorithm for irrational-based digital sequences, which leverages dependence properties of scrambled digital nets [3].

- [1] N. Kirk, C. Lemieux and J. Wiart. Golden ratio nets and sequences. To appear in *Functiones and Approximatio*, 2025.
- [2] N. Kirk, C. Lemieux. An improved Halton sequence for implementation in quasi-Monte Carlo methods. *Proceedings of the 2024 Winter Simulation Conference*, 431–442, IEEE Press, Piscataway, NJ, 2024.
- [3] C. Lemieux and J. Wiart. On the distribution of scrambled $(0, m, s)$ -nets over unanchored boxes. In: *Monte Carlo and Quasi-Monte Carlo Methods 2020*, A. Keller (ed), Springer, 187–230, 2022.

Tue, Jul 29 09:00–10:00

**Combining Simulation and Linear Algebra: COSIMLA***Peter W. Glynn*

Stanford University

glynn@stanford.edu

Coauthor(s): Zeyu Zheng

In numerical computation for Markov chains and jump processes, matrix-based linear algebraic methods leverage fully the special structure of such models, allowing one to efficiently compute highly accurate solutions quickly. When the number of states is large or infinite, Monte Carlo simulation is an appealing alternative, typically allowing low accuracy solutions to be computed efficiently. In this talk, we describe COSIMLA, COmbined SIMulations and Linear Algebra. This new class of algorithms combines the best of the two numerical approaches, using matrix methods to compute expectations and probabilities in the truncated core of the state space, while one uses Monte Carlo to simulate path excursions outside the truncation. As a result, one can now compute high accuracy solutions for models with a very large state space. We show how the method applies to computing equilibrium quantities and various transient characteristics of Markov chains. These algorithms can typically be viewed as an application of conditional Monte Carlo. We also discuss how stratification can be conveniently applied in this setting to provide further variance reductions.

Tue, Jul 29 14:00–15:00



Sensitivity and Screening: From Monte Carlo to Experimental Design

Roshan Joseph

Georgia Institute of Technology, Atlanta

roshan@gatech.edu

Identifying the most important factors affecting the output of a system from a set of potentially important factors is an important problem in scientific investigations. If a computational model is available to predict the output, we can use global sensitivity analysis to quantify the importance of each factor. There are many Monte Carlo-based methods available to estimate global sensitivity indices. However, their computation can become costly if the model is computationally expensive. In such cases, carefully designed experiments can be used for screening the factors. In this talk, I will explain some of these techniques and the latest developments, including their applications in active learning. I will also briefly explain how to estimate the sensitivity indices from noisy data when we do not know or have access to the model that generated the data.

- [1] Xiao, Q., Joseph, V. R., and Ray, D. M. (2023). *Maximum One-Factor-At-A-Time Designs for Screening in Computer Experiments*. *Technometrics*, 65, 220-230.
- [2] Song, D. and Joseph, V. R. (2025). *Efficient Active Learning Strategies for Computer Experiments*. <https://arxiv.org/abs/2501.13841>.
- [3] Huang, C. and Joseph, V. R. (2025). *Factor Importance Ranking and Selection using Total Indices*. *Technometrics*, <https://doi.org/10.1080/00401706.2025.2483531>.

Wed, Jul 30 09:00–10:00



An optimal transport approach to quantifying model uncertainty of SDEs

Michaela Szölgyenyi

University of Klagenfurt

michaela.szolgyenyi@aau.at

Coauthor(s): Benjamin A. Robinson

A fundamental question in stochastic modelling is that of quantifying the effects of model uncertainty. In this context it is of interest to compute a distance between different stochastic models. A reasonable choice of distance is a modification of the Wasserstein distance on the space of probability measures called adapted Wasserstein distance, as it appears in bicausal optimal transport.

We solve constrained optimal transport problems in which the marginal laws are given by the laws of solutions of stochastic differential equations (SDEs). We consider SDEs with irregular coefficients, making only minimal regularity assumptions. Numerical methods are employed as a theoretical tool to bound the adapted Wasserstein distance. This opens the door for computing the adapted Wasserstein distance in a simple way. We show that this method can be applied to quantifying model uncertainty in stochastic optimisation problems.

Our approach successfully brings together optimal transport and numerical analysis of SDEs.

Thu, Jul 31 09:00–10:00



Gradient-Based MCMC Sampling: Methods and Optimization Strategies

Uroš Seljak

UC Berkeley and Lawrence Berkeley National Laboratory
`useljak@berkeley.edu`

Coauthor(s): Reuben Cohn-Gordon, Jakob Robnik

Gradient-based Markov Chain Monte Carlo (MCMC) methods significantly outperform gradient-free alternatives in sampling efficiency, particularly in high-dimensional spaces where they have become the standard approach. These methods leverage gradient information to guide the sampling process more intelligently than random-walk approaches. Two fundamental approaches that dominate this field are 1) Hamiltonian Monte Carlo (HMC), which employs principles from classical mechanics, treating the sampling problem as simulating Hamiltonian dynamics on an extended phase space. This approach naturally incorporates momentum variables that help the sampler traverse the parameter space more efficiently than simple random walks. 2) Langevin Monte Carlo (LMC), which utilizes stochastic differential equations that incorporate both gradient information and controlled noise injection. Recent theoretical developments have produced microcanonical versions of both Hamiltonian and Langevin samplers (MCHMC and MCLMC). These variants demonstrate measurably superior sampling efficiency compared to their canonical predecessors.

In addition to the choice of the method, practitioners face numerous algorithmic choices that can significantly impact performance: 1) Metropolis Adjustment: The decision whether to include Metropolis-Hastings correction steps involves trading exact preservation of the target distribution against computational speed. 2) Preconditioning: Incorporating problem-specific geometric information through preconditioning matrices can dramatically improve convergence rates, particularly for ill-conditioned target distributions. 3) Hyperparameter Tuning: Critical parameters include step sizes, trajectory lengths for HMC, and damping coefficients for Langevin methods. Recently, well tuned black-box methods have been developed that approach optimal performance. 4) Parallelization Strategy: parallel sampling on a GPU or CPU cluster enables dramatically reduced wall clock time to reach the required target accuracy. 5) Numerical Integration: Higher-order integrators can improve accuracy at the cost of additional gradient evaluations per step.

This goal of this talk is to provide guidance to the optimal choice among these methods, which depends on specific application requirements including computational budget, accuracy demands, and problem dimensionality. Understanding the theoretical trade-offs enables practitioners to select and configure samplers that best match their particular constraints and objectives.

Thu, Jul 31 14:00–15:00



Saddlepoint Monte Carlo and its Application to Exact Ecological Inference

Nicolas Chopin

ENSAE, Institut Polytechnique de Paris

`nicolas.chopin@ensae.fr`

Coauthor(s): Théo Voldoire, Guillaume Rateau, Robin J. Ryder

In ecological inference, one wishes to model individual items, but perform inference based only on aggregate data. For instance, in two-round elections, we are interested the behaviour of individual voters, but only have access to aggregate vote numbers at each precinct. We develop an exact method for a large class of Ecological Inference Bayesian models, which scales to the large data setting. Our approach solves a more general problem: assuming X is a random vector and A a non-invertible matrix, one sometimes need to perform inference while only having access to samples of $Y = AX$. The corresponding likelihood is typically intractable. One may still be able to perform exact Bayesian inference using a pseudo-marginal sampler, but this requires an unbiased estimator of the intractable likelihood.

We propose saddlepoint Monte Carlo, a method for obtaining an unbiased estimate of the density of Y with very low variance, for any model belonging to an exponential family. Our method relies on importance sampling and characteristic functions, with insights brought by the standard saddlepoint approximation scheme with exponential tilting. We show that saddlepoint Monte Carlo makes it possible to perform exact inference on particularly challenging problems and datasets. We present a study of the carryover of votes between the two rounds of various French elections, using the finest available data (number of votes for each candidate in about 60,000 polling stations over most of the French territory).

We show that existing, popular approximate methods for ecological inference can lead to substantial bias; saddlepoint Monte Carlo is immune from this bias, and can handle ecological inference in the large data framework. We also present original results for the 2024 legislative elections on political centre-to-left and left-to-centre conversion rates when the far-right is present in the second round. Finally, we discuss other exciting applications for saddlepoint Monte Carlo in privacy and inverse problems, such as dealing with inference with empirical quantiles for continuous data.

- [1] Voldoire T., Chopin N., Rateau G. and Ryder R.J. (2024). Monte Carlo and its Application to Exact Ecological Inference, *arxiv 2410.18243*, <https://arxiv.org/abs/2410.18243>,

Special Sessions

Stochastic Computation and Complexity, Part I

Organizers:

Stefan Heinrich

RPTU Kaiserslautern-Landau

heinrich@informatik.uni-kl.de

Thomas Müller-Gronbach

University of Passau

Thomas.Mueller-Gronbach@uni-passau.de

Larisa Yaroslavtseva

University of Graz

larisa.yaroslavtseva@uni-graz.at

Session Description:

The session is devoted to algorithms and complexity for quadrature and strong approximation of SDEs and SPDEs, in particular under nonstandard assumptions, high and infinite dimensional integration and approximation, and stochastic optimization and neural networks, including connections to functional analysis and stochastic analysis.

Mon, Jul 28, 2025 – Morning, 10:30 – 12:30,

Chengcheng Ling

Quantitative Approximation of Stochastic Kinetic Equations: From Discrete to Continuum
p. 72

Andreas Neuenkirch

A Strong Order 1.5 Boundary Preserving Discretization Scheme for Scalar SDEs Defined in a Domain p. 73

Christopher Rauhögger

An Adaptive Milstein-Type Method for Strong Approximation of Systems of SDEs With a Discontinuous Drift Coefficient p. 73

Verena Schwarz

Strong Order 1 Adaptive Approximation of Jump-Diffusion SDEs With Discontinuous Drift
p. 74

Domain Uncertainty Quantification

Organizers:

André-Alexander Zepernick
Free University of Berlin
a.zepernick@fu-berlin.de

Philipp A. Guth
RICAM, Austrian Academy of Sciences
philipp.guth@ricam.oeaw.ac.at

Vesa Kaarnioja
Free University of Berlin
vesa.kaarnioja@fu-berlin.de

Session Description:

Uncertainty in computational measurement models poses significant challenges in engineering and applied mathematics, where inaccuracies in material properties or geometric domains can greatly impact outcomes. Geometric errors, such as manufacturing imperfections or improper modeling in applications like electronic design and tomography, can be the dominant error contributor. Some approaches to modeling domain uncertainty include homogenization, perturbation, and reference mapping techniques, which facilitate the analysis of uncertainty propagation within computational measurement models. This session brings together leading experts to present recent theoretical and computational advancements in the study of domain uncertainty quantification.

Mon, Jul 28, 2025 – Morning, 10:30 – 12:30,

André-Alexander Zepernick

Domain UQ for Stationary and Time-Dependent PDEs Using QMC p. 75

Carlos Jerez-Hanckes

Domain Uncertainty Quantification for Electromagnetic Wave Scattering via First- Order Sparse Boundary Element Approximation p. 76

Jürgen Dölz

Quantifying Uncertainty in Spectral Clusterings: Expectations for Perturbed and Incomplete Data p. 77

Harri Hakula

Model Problems for PDEs on Uncertain Domains p. 77

Nested Expectations: Models and Estimators, Part I

Organizers:

Arved Bartuska

King Abdullah University of Science and Technology and RWTH Aachen University

sarved.bartuska@kaust.edu.sa

Abdul-Lateef Haji-Ali

Heriot-Watt University

a.hajiali@hw.ac.uk

Session Description:

Nested expectations arise in many applications, such as in engineering, mathematical finance, and medical decision-making. In addition to their nested structure, numerical estimations of such expectations are often complicated by singularities or discontinuities. Moreover, approximations when evaluating inner expectations using, for example, finite element or time-stepping schemes render traditional estimation methods such as double-loop Monte Carlo prohibitively expensive. This session will explore models and applications with this structure and methods for efficient estimation. List of speakers: Abdul-Lateef Haji-Ali (Heriot-Watt University) Sebastian Krumscheid (Karlsruhe Institute of Technology) Truong Vinh Hoang (RWTH Aachen University) Vesa Kaarnioja (FU Berlin)

Mon, Jul 28, 2025 – Morning, 10:30 – 12:30,

Vesa Kaarnioja

QMC for Bayesian Optimal Experimental Design With Application to Inverse Problems Governed by PDEs p. 78

Sebastian Krumscheid

Double-Loop Randomized Quasi-Monte Carlo Estimator for Nested Integration p. 79

Vinh Hoang

Posterior-Free A-Optimal Bayesian Design of Experiments via Conditional Expectation p. 79

Hardware or Software for (Quasi-)Monte Carlo Algorithms, Part I

Organizers:

Sou-Cheng T. Choi

Illinois Institute of Technology

`schoi32@iit.edu`

Pieterjan Robbe

Sandia National Laboratories

`pmrobbe@sandia.gov`

Mike Giles

University of Oxford

`mike.giles@maths.ox.ac.uk`

Session Description:

Monte Carlo (MC) or quasi-Monte Carlo (QMC) algorithms are widely used in various fields such as finance, physics, and engineering for their ability to handle high-dimensional integration problems. The development and maintenance of software for (quasi-)Monte Carlo ((Q)MC) algorithms can significantly enhance the accessibility and usability of these techniques. This special session aims to bring together experts from academia and industry to discuss recent advances in (Q)MC software, share best practices, and explore future directions, fostering collaboration among researchers and practitioners. Topics of interest for the session include:

- Novel hardware or architectural designs for open-source (Q)MC libraries.
- Best collaborative practices for developing and maintaining efficient and reliable (Q)MC software.
- Challenges and opportunities in integrating (Q)MC methods with machine learning and AI techniques.
- High-performance computing solutions for (Q)MC software.
- Adaptation of (Q)MC software to application fields such as finance, computer graphics, sensitivity analysis, Bayesian optimization, and uncertainty quantification.
- Innovative approaches to enhancing and extending existing (Q)MC tools.

Mon, Jul 28, 2025 – Morning, 10:30 – 12:30,

Mike Giles

CUDA Implementation of MLMC on NVIDIA GPUs p. 80

Pieterjan Robbe

Multilevel Quasi-Monte Carlo Without Replications p. 81

Irina-Beatrice Haas

A Nested Multilevel Monte Carlo Framework for Efficient Simulations on FPGAs p. 81

Chung Ming Loi

Scalable and User-Friendly QMC Sampling With UMBridge p. 82

Stochastic Computation and Complexity, Part II

Organizers:

Stefan Heinrich

RPTU Kaiserslautern-Landau

heinrich@informatik.uni-kl.de

Thomas Müller-Gronbach

University of Passau

Thomas.Mueller-Gronbach@uni-passau.de

Larisa Yaroslavtseva

University of Graz

larisa.yaroslavtseva@uni-graz.at

Session Description:

The session is devoted to algorithms and complexity for quadrature and strong approximation of SDEs and SPDEs, in particular under nonstandard assumptions, high and infinite dimensional integration and approximation, and stochastic optimization and neural networks, including connections to functional analysis and stochastic analysis.

Mon, Jul 28, 2025 – Afternoon, 15:30 – 17:30,

Kateryna Pozharska

Optimal Designs for Function Discretization and Construction of Tight Frames p. 83

Michael Gnewuch

Optimality of Deterministic and Randomized QMC-Cubatures on Several Scales of Function Spaces p. 84

Leszek Plaskota

Complexity of Approximating Piecewise Smooth Functions in the Presence of Deterministic or Random Noise p. 85

Recent Advances in Optimization Under Uncertainty

Organizers:

Philipp A. Guth

RICAM, Austrian Academy of Sciences

philipp.guth@ricam.oeaw.ac.at

Vesa Kaarnioja

Free University of Berlin

vesa.kaarnioja@fu-berlin.de

Session Description:

The quantification of uncertainties associated with large-scale optimization problems based on partial differential equation models typically involves a number of uncertainties. Some uncertain parameters may include, e.g., the material parameters, domain shape or sensor locations used to collect measurement data. The associated challenging high-dimensional integration problems can be solved efficiently using, e.g., multilevel Monte Carlo or quasi-Monte Carlo methods. This session aims to cover some recent developments in the computational and theoretical treatment of this actively developing field of research.

Mon, Jul 28, 2025 – Afternoon, 15:30 – 17:30,

Tapio Helin

Stability of Expected Utility in Bayesian Optimal Experimental Design p. 85

Arved Bartuska

Efficient Expected Information Gain Estimators Based on the Randomized Quasi-Monte Carlo Method p. 86

Karina Koval

Subspace Accelerated Measure Transport Methods for Fast and Scalable Sequential Experimental Design p. 86

Johannes Milz

Randomized Quasi-Monte Carlo Methods for Risk-Averse Stochastic Optimization p. 87

Computational Methods for Low-Discrepancy Sampling and Applications

Organizers:

Nathan Kirk

Illinois Institute of Technology

`nkirk@iit.edu`

François Clément

University of Washington

`fclement@uw.edu`

Session Description:

This session aims to showcase recent advancements in the optimization of sample point distributions [1, 2] and their applications. Some of the methods on display will range from deep learning methods to permutation optimization and greedy approaches [3], showcasing the usefulness of the L_2 -discrepancies in optimizing the L_∞ discrepancies. As a consequence of some of these improved low-discrepancy sets, an application will be shown in improved path planning in robotics [4]. Several other applications will be explored in the context of using the median over the mean of r RQMC estimates as proposed in several recent papers including [5].

- [1] T. K. Rusch, N. Kirk, M. Bronstein, C. Lemieux and D. Rus, *Message-Passing Monte Carlo: Generating low-discrepancy point sets via graph neural networks*, PNAS **121** (40) e2409913121 (2024)
- [2] F. Clément, C. Doerr, K. Klamroth, L. Paquete, *Transforming the Challenge of Constructing Low-Discrepancy Point Sets into a Permutation Selection Problem*, <https://arxiv.org/abs/2407.11533>.
- [3] F. Clément, *Outperforming the Best 1D Low-Discrepancy Constructions with a Greedy Algorithm*, <https://arxiv.org/abs/2406.18132>.
- [4] M. Chahine, T. K. Rusch, Z. J. Patterson and D. Rus, *Improving Efficiency of Sampling-based Motion Planning via Message-Passing Monte Carlo*, <https://arxiv.org/abs/2410.03909>
- [5] P. L'Ecuyer, M. K. Nayakama, A. B. Owen and B. Tuffin, *Confidence Intervals for Randomized Quasi-Monte Carlo Estimators*, Proceedings of the 2023 Winter Simulation Conference (2023)

Speakers:

1. François Clément (University of Washington)
2. Nathan Kirk (Illinois Tech)
3. Makram Chahine (MIT)
4. Greg de Salaberry Seljak (University of Montréal)

Makram Chahine

Improving Efficiency of Sampling-Based Motion Planning via Message-Passing Monte Carlo
p. 88

Nathan Kirk

Minimizing the Stein Discrepancy p. 88

Gregory Seljak

An Empirical Evaluation of Robust Estimators for RQMC p. 89

François Clément

Searching Permutations for Constructing Low-Discrepancy Point Sets and Investigating the
Kritzing Sequence p. 90

Stochastic Computation and Complexity, Part III

Organizers:

Stefan Heinrich

RPTU Kaiserslautern-Landau

heinrich@informatik.uni-kl.de

Thomas Müller-Gronbach

University of Passau

Thomas.Mueller-Gronbach@uni-passau.de

Larisa Yaroslavtseva

University of Graz

larisa.yaroslavtseva@uni-graz.at

Session Description:

The session is devoted to algorithms and complexity for quadrature and strong approximation of SDEs and SPDEs, in particular under nonstandard assumptions, high and infinite dimensional integration and approximation, and stochastic optimization and neural networks, including connections to functional analysis and stochastic analysis.

Tue, Jul 29, 2025 – Morning, 10:30 – 12:30,

Sotirios Sabanis

Wasserstein Convergence of Score-Based Generative Models Under Semiconvexity and Discontinuous Gradients p. 91

Next-Generation Optimal Experimental Design: Theory, Scalability, and Real World Impact: Part I

Organizers:

Florence Forbes

Inria, France

`florence.forbes@inria.fr`

Xun Huan

University of Michigan, USA

`xhuan@umich.edu`

Youssef Marzouk

Massachusetts Institute of Technology, USA

`ymarz@mit.edu`

Session Description:

Optimal experimental design (OED) provides a mathematical framework for identifying candidate data or experimental configurations that are most useful for inference, prediction, or some other downstream goal. Though OED is hardly a new topic,¹ the need for advances in OED has never been greater than it is today. Myriad application areas have witnessed, on the one hand, an explosion in the volume of data that can be acquired, and on the other, the use of increasingly complex and computationally intensive models to interpret these data. Yet large volumes of data do not by default carry a commensurate amount of information. Moreover, we inevitably face constraints: on the costs of experimentation or data acquisition, on data storage and communication, and on the computational effort of statistical inference in complex models. OED directly addresses the associated trade-offs—e.g., between experimentation, measurement, and/or processing *costs* and the *quality* of subsequent and decision making. See *e.g.* [1] for a recent review of OED topics, which provides numerous other references. This session will highlight computational developments at the OED research frontier. Methods for stochastic simulation, high-dimensional approximation or integration, and stochastic optimization are central to modern OED and to the scaling of OED to large parameter spaces and complex statistical models. Modern machine learning methodologies—from neural network surrogates, to deep reinforcement learning in sequential OED, to modern generative models and transport methods for simulation-based inference—also play a catalyzing role in such OED approaches. Talks in this session will illuminate these emerging interactions and their role in realizing Bayesian, decision-theoretic, and information-theoretic formulations of OED for truly complex problems. Session speakers will also discuss ongoing work to develop theoretical guarantees for these new OED methodologies, and showcase applications to real-world problems ranging from sensor steering to seismology.

- [1] X. Huan, J. Jagalur, Y. Marzouk (2024). Optimal experimental design: Formulations and computations, *Acta Numerica* **33**, 715–840.

¹At the first session of the Indian Statistical Conference in 1938, R. Fisher supposedly said, “To call in the statistician after the experiment is done may be no more than asking him to perform a postmortem examination: he may be able to say what the experiment died of.”

Tue, Jul 29, 2025 – Morning, 10:30 – 12:30,

Ayoub Belhadji

Weighted Quantization Using MMD: From Mean Field to Mean Shift via Gradient Flows
p. 91

Adrien Corenflos

A Recursive Monte Carlo Approach to Optimal Bayesian Experimental Design p. 92

Heavy-Tailed Sampling

Organizer:

Session Description:

Alex Shestopaloff Queen Mary University of London, UK ashestopaloff@qmul.ac.uk Jun Yang University of Copenhagen, Denmark jy@math.ku.dk Heavy-tailed distributions frequently arise in modern statistics, machine learning, and applied sciences, yet their intricate properties pose significant challenges for computational inference. This session, Heavy-Tailed Sampling, brings together cutting-edge advances in Monte Carlo methods and stochastic optimization to address these challenges. The topics span theoretical breakthroughs and practical algorithms, showcasing how heavy-tailed phenomena influence algorithmic design and performance. Our session aims to inspire new methods and applications in the broader Monte Carlo community. The session will explore:

- Langevin Monte Carlo for Heavy-Tailed Distributions: A comprehensive complexity analysis of Langevin-based samplers for heavy-tailed targets using weighted Poincaré inequalities. The results reveal fundamental limits of mean-square analysis and include innovative techniques for gradient approximation.
- Stereographic MCMC: A novel class of samplers that map Euclidean spaces onto spheres to resolve mixing issues inherent to heavy-tailed targets. These methods, featuring uniform ergodicity and rapid convergence, capitalize on the "blessings of dimensionality" to enhance performance in high dimensions.
- Large Deviation Principles in MCMC: A groundbreaking application of large deviation theory to assess and improve MCMC algorithms. This approach extends to Metropolis-Hastings and related methods on general state spaces, providing new insights into empirical measure convergence and rate functions.
- Heavy-Tailed Phenomena in Stochastic Gradient Descent (SGD): An analysis of heavy-tailed noise in SGD and its impact on escaping sharp minima in deep learning. The session highlights a variant of SGD with gradient truncation, offering theoretical and empirical evidence of enhanced generalization through flatter minima.

List of speakers

- Murat A. Erdogdu, University of Toronto, Canada
- Sebastiano Grazi, Bocconi University, Italy

- Federica Milinanni, KTH Royal Institute of Technology, Sweden
- Xingyu Wang, University of Amsterdam, Netherlands

Tue, Jul 29, 2025 – Morning, 10:30 – 12:30,

Sebastiano Grazzi

Parallel Computations for Metropolis Markov Chains Based on Picard Maps p. 93

Frontiers in (Quasi-)Monte Carlo and Markov Chain Monte Carlo Methods, Part I

Organizers:

Sou-Cheng T. Choi

Illinois Institute of Technology
schoi32@iit.edu

Yuhan Ding

Illinois Institute of Technology
yding2@iit.edu

Session Description:

(Quasi-)Monte Carlo ((Q)MC) and Markov Chain Monte Carlo (MCMC) algorithms are fundamental tools in computational mathematics, with a wide range of applications spanning finance, physics, engineering, and more. These methods have proven invaluable in solving high-dimensional problems where traditional numerical techniques often fail, and continue to expand their reach into emerging fields such as artificial intelligence, climate modeling, precision medicine, and data science. Recent advances in the theoretical foundations of these methods, including convergence rates, complexity analysis, sampling techniques, error analysis, variance reduction, optimal stopping conditions, and ergodic properties, have significantly improved their accuracy, efficiency, and reliability. In addition, interdisciplinary applications are driving new developments, such as machine learning, Bayesian inference, stochastic optimization, and uncertainty quantification. This special session aims to bring together leading experts from academia and industry to share breakthroughs, foster interdisciplinary collaboration, and identify future research directions in the broad field of Monte Carlo methods. Participants will benefit from insights into cutting-edge research and practical applications of (Q)MC and MCMC methods, as well as opportunities to network with peers and thought leaders. s

Tue, Jul 29, 2025 – Morning, 10:30 – 12:30,

Hwanwoo Kim

Enhancing Gaussian Process Surrogates for Optimization and Posterior Approximation via Random Exploration p. 93

Stochastic Computation and Complexity, Part IV

Organizers:

Stefan Heinrich

RPTU Kaiserslautern-Landau

heinrich@informatik.uni-kl.de

Thomas Müller-Gronbach

University of Passau

Thomas.Mueller-Gronbach@uni-passau.de

Larisa Yaroslavtseva

University of Graz

larisa.yaroslavtseva@uni-graz.at

Session Description:

The session is devoted to algorithms and complexity for quadrature and strong approximation of SDEs and SPDEs, in particular under nonstandard assumptions, high and infinite dimensional integration and approximation, and stochastic optimization and neural networks, including connections to functional analysis and stochastic analysis.

Tue, Jul 29, 2025 – Afternoon, 15:30 – 17:30,

Larisa Yaroslavtseva

Optimal Strong Approximation of SDEs With Hölder Continuous Drift Coefficient p. 94

Alexander Steinicke

Malliavin Differentiation of Lipschitz SDEs and BSDEs and an Application to Quadratic Forward-Backward SDEs p. 95

Gunther Leobacher

Tractability of L_2 -Approximation and Integration in Weighted Hermite Spaces of Finite Smoothness p. 95

Next-Generation Optimal Experimental Design: Theory, Scalability, and Real World Impact: Part II

Organizers:

Florence Forbes

Inria, France

`florence.forbes@inria.fr`

Xun Huan

University of Michigan, USA

`xhuan@umich.edu`

Youssef Marzouk

Massachusetts Institute of Technology, USA

`ymarz@mit.edu`

Session Description:

Optimal experimental design (OED) provides a mathematical framework for identifying candidate data or experimental configurations that are most useful for inference, prediction, or some other downstream goal. Though OED is hardly a new topic,² the need for advances in OED has never been greater than it is today. Myriad application areas have witnessed, on the one hand, an explosion in the volume of data that can be acquired, and on the other, the use of increasingly complex and computationally intensive models to interpret these data. Yet large volumes of data do not by default carry a commensurate amount of information. Moreover, we inevitably face constraints: on the costs of experimentation or data acquisition, on data storage and communication, and on the computational effort of statistical inference in complex models. OED directly addresses the associated trade-offs—e.g., between experimentation, measurement, and/or processing *costs* and the *quality* of subsequent and decision making. See *e.g.* [1] for a recent review of OED topics, which provides numerous other references. This session will highlight computational developments at the OED research frontier. Methods for stochastic simulation, high-dimensional approximation or integration, and stochastic optimization are central to modern OED and to the scaling of OED to large parameter spaces and complex statistical models. Modern machine learning methodologies—from neural network surrogates, to deep reinforcement learning in sequential OED, to modern generative models and transport methods for simulation-based inference—also play a catalyzing role in such OED approaches. Talks in this session will illuminate these emerging interactions and their role in realizing Bayesian, decision-theoretic, and information-theoretic formulations of OED for truly complex problems. Session speakers will also discuss ongoing work to develop theoretical guarantees for these new OED methodologies, and showcase applications to real-world problems ranging from sensor steering to seismology.

- [1] X. Huan, J. Jagalur, Y. Marzouk (2024). Optimal experimental design: Formulations and computations, *Acta Numerica* **33**, 715–840.

²At the first session of the Indian Statistical Conference in 1938, R. Fisher supposedly said, “To call in the statistician after the experiment is done may be no more than asking him to perform a postmortem examination: he may be able to say what the experiment died of.”

Tue, Jul 29, 2025 – Afternoon, 15:30 – 17:30,

jacopo iollo

Diffusion-Based Bayesian Experimental Design: Advancing BED for Practical Applications
p. 96

Alen Alexanderian

Goal Oriented Sensor Placement for Infinite-Dimensional Bayesian Inverse Problems p. 97

Tommie Catanach

Robust Bayesian Optimal Experimental Design Under Model Misspecification p. 97

Xun Huan

Optimal Pilot Sampling for Multi-Fidelity Monte Carlo Methods p. 98

Advances in Rare Events Simulation

Organizers:

Nadhir Ben Rached

University of Leeds, United Kingdom

`N.BenRached@leeds.ac.uk`

Shyam Mohan Subbiah Pillai

RWTH Aachen University, Germany

`subbiah@uq.rwth-aachen.de`

Raúl Tempone

King Abdullah University of Science and Technology, Saudi Arabia

`raul.tempone@kaust.edu.sa`

Session Description:

Rare events are events with small probabilities, but their occurrences are critical in many real-life applications. The problem of estimating rare event probabilities is encountered in various engineering applications (finance, wireless communications, system reliability, biology, etc.). Naive Monte Carlo simulations are, in this case, substantially expensive. This session focuses on advances in methods belonging to the class of variance reduction techniques. These alternative methods deliver, when appropriately used, accurate estimates with a substantial amount of variance reduction compared to the naive Monte Carlo estimator. Proposed speakers:

1. Victor Elvira, Professor in Statistics and Data Science, University of Edinburgh, United Kingdom
2. Bruno Tuffin, Director of Research, INRIA Rennes-Bretagne Atlantique, France
3. Eya Ben Amar, King Abdullah University of Science and Technology, Saudi Arabia
4. Shyam Mohan Subbiah Pillai, RWTH Aachen University, Germany

Tue, Jul 29, 2025 – Afternoon, 15:30 – 17:30,

Bruno Tuffin

Asymptotic Robustness of Smooth Functions of Rare-Event Estimators p. 99

Shyam Mohan Subbiah Pillai

Estimating Rare Event Probabilities Associated With McKean--Vlasov SDEs p. 100

Victor Elvira

Multiple Importance Sampling for Rare Event Simulation in Communication Systems p. 101

Frontiers in (Quasi-)Monte Carlo and Markov Chain Monte Carlo Methods, Part II

Organizers:

Sou-Cheng T. Choi

Illinois Institute of Technology
schoi32@iit.edu

Yuhan Ding

Illinois Institute of Technology
yding2@iit.edu

Session Description:

(Quasi-)Monte Carlo ((Q)MC) and Markov Chain Monte Carlo (MCMC) algorithms are fundamental tools in computational mathematics, with a wide range of applications spanning finance, physics, engineering, and more. These methods have proven invaluable in solving high-dimensional problems where traditional numerical techniques often fail, and continue to expand their reach into emerging fields such as artificial intelligence, climate modeling, precision medicine, and data science. Recent advances in the theoretical foundations of these methods, including convergence rates, complexity analysis, sampling techniques, error analysis, variance reduction, optimal stopping conditions, and ergodic properties, have significantly improved their accuracy, efficiency, and reliability. In addition, interdisciplinary applications are driving new developments, such as machine learning, Bayesian inference, stochastic optimization, and uncertainty quantification. This special session aims to bring together leading experts from academia and industry to share breakthroughs, foster interdisciplinary collaboration, and identify future research directions in the broad field of Monte Carlo methods. Participants will benefit from insights into cutting-edge research and practical applications of (Q)MC and MCMC methods, as well as opportunities to network with peers and thought leaders.

Tue, Jul 29, 2025 – Afternoon, 15:30 – 17:30,

Takashi Goda

Quasi-Uniform Quasi-Monte Carlo Digital Nets p. 101

Ziang Niu

Boosting the Inference for Generative Models by (Quasi-)Monte Carlo Resampling p. 102

Chenyang Zhong

A Hit and Run Approach for Sampling and Analyzing Ranking Models p. 103

Stochastic Computation and Complexity, Part V

Organizers:

Stefan Heinrich

RPTU Kaiserslautern-Landau

heinrich@informatik.uni-kl.de

Thomas Müller-Gronbach

University of Passau

Thomas.Mueller-Gronbach@uni-passau.de

Larisa Yaroslavtseva

University of Graz

larisa.yaroslavtseva@uni-graz.at

Session Description:

The session is devoted to algorithms and complexity for quadrature and strong approximation of SDEs and SPDEs, in particular under nonstandard assumptions, high and infinite dimensional integration and approximation, and stochastic optimization and neural networks, including connections to functional analysis and stochastic analysis.

Wed, Jul 30, 2025 – Morning, 10:30 – 12:30,

Stefan Heinrich

On the Quantum Complexity of Parametric Integration in Sobolev Spaces p. 103

Bernd Käßemodel

Quantum Integration in Tensor Product Besov Spaces p. 104

Statistical Design of Experiments

Organizers:

Lulu Kang

University of Massachusetts Amherst

lulukang@umass.edu

Chunfang Devon Lin

Queen's University

devon.lin@queensu.ca

Session Description:

This session explores innovative methodologies for optimizing experimental design and factor analysis in complex, high-dimensional, and resource-constrained settings. The first talk introduces QuIP, a novel framework for designing experiments with qualitative factors using integer programming and Gaussian process models, demonstrating its effectiveness in path planning and rover trajectory optimization. The second talk addresses the challenge of cost-efficient predictive computing by proposing a multi-fidelity emulator design inspired by Multilevel Monte Carlo methods, which ensures predictive accuracy while minimizing computational costs under a tight budget. The third talk shifts focus to experiments involving both quantitative and sequence factors, presenting a new class of optimal quantitative-sequence (QS) designs that are flexible, space-filling, and asymptotically orthogonal, making them ideal for high-dimensional applications in medical science and bio-engineering. Finally, the fourth talk introduces FIRST, a model-free framework for factor importance ranking and selection using total Sobol' indices, offering a computationally efficient and consistent approach to identifying key factors in regression and classification tasks. Together, these talks highlight cutting-edge advancements in experimental design, optimization, and factor analysis, with broad applications across scientific and engineering disciplines. We list the speakers and title of their talks below.

1. Simon Mak, Assistant Professor, Department of Statistical Science at Duke University.
Talk title: QuIP: Experimental design for expensive simulators with many Qualitative factors via Integer Programming
2. Chih-Li Sung, Assistant Professor in the Department of Statistics and Probability at Michigan State University.
Talk title: Stacking designs: designing multi-fidelity computer experiments with target predictive accuracy
3. Qian Xiao, Associate Professor in the Department of Statistics, School of Mathematical Sciences at Shanghai Jiao Tong University, Shanghai, China.
Talk title: Optimal Design of Experiments With Quantitative-sequence Factors
4. Chaofan Huang, Ph.D. student in the School of Industrial and Systems Engineering at Georgia Institute of Technology.
Title: Factor Importance Ranking and Selection using Total Indices

Wed, Jul 30, 2025 – Morning, 10:30 – 12:30,

Simon Mak

Respecting the Boundaries: Space-Filling Designs for Surrogate Modeling With Boundary Information p. 105

Chaofan Huang

Factor Importance Ranking and Selection Using Total Indices p. 105

Chih-Li Sung

Stacking Designs: Designing Multi-Fidelity Computer Experiments With Target Predictive Accuracy p. 106

Advances in Adaptive Hamiltonian Monte Carlo

Organizer:

Art B. Owen

Stanford University

owen@stanford.edu

Session Description:

Hamiltonian Monte Carlo (HMC) is one of the most effective tools for high-dimensional Markov chain Monte Carlo. It is the default algorithm used in probabilistic programming languages for Bayesian computation, including `Stan` [2], `PyMC` and `NumPyro` (Python), and `Turing.jl` (Julia). While HMC handles some of the most difficult MCMC problems, it does so through the use of several tuning parameters, which can be challenging to set. Significant progress came from the no-U-turn sampler (NUTS) [3] and apogee-to-apogee path sampler [7], both of which dynamically adapt path lengths. More recent progress includes delayed rejection HMC [5], which locally adapts step sizes, and Gibbs self tuning (GIST) [1], which treats tuning parameters as random variables to maintain detailed balance. Chirag Modi's ATLAS [5] leverages local Hessians, delayed rejection, and GIST. AutoStep MCMC [4] adapts step sizes locally to match the variable geometry of target distributions. The speakers, in tentative order, will be:

- Bob Carpenter, Center for Computational Mathematics, Flatiron Institute.
- Nawaf Bou-Rabee, Department of Mathematical Sciences, Rutgers University.
- Chirag Modi, Center for Cosmology and Particle Physics, Department of Physics, New York University.
- Trevor Campbell, University of British Columbia.

Bob Carpenter will provide an introduction to HMC, NUTS, and GIST for non-specialists. Nawaf Bou-Rabee will elaborate on GIST. Chirag Modi will discuss delayed rejection and ATLAS. Trevor Campbell will present AutoStep and related methods. **References**

- [1] Bou-Rabee, B. Carpenter, and M. Marsden. GIST: Gibbs self-tuning for locally adaptive HMC. arXiv:2404.15253, 2024.
- [2] Carpenter, B. et al. 2017. Stan: A probabilistic programming language. *J. Stat. Soft.*, 76
- [3] Hoffman, M. D. and Gelman, A. 2014. The no-U-turn sampler: Adaptively setting path lengths in HMC. *J. Mach. Learn. Res.*, 15(1).
- [4] Liu, T., Campbell, T., et al. 2024. AutoStep: Locally adaptive involutive MCMC. arXiv:2410.18929, 2024.
- [5] Modi, C. 2024. ATLAS: Adapting trajectory lengths and step-size for HMC. arXiv:2410.21587
- [6] Modi, C., Barnett, A. and Carpenter, B. 2024. Delayed rejection Hamiltonian Monte Carlo for sampling multiscale distributions. *Bayesian Analysis*, 19(3), 2024.
- [7] Sherlock, C., Urbas, S. and Ludkin, M. 2023. The apogee to apogee path sampler. *JCGS*, 32(4).

Wed, Jul 30, 2025 – Morning, 10:30 – 12:30,

Bob Carpenter

GIST: Gibbs Self-Tuning for Locally Adapting Hamiltonian Monte Carlo p. 107

Nawaf Bou-Rabee

Acceleration of the No-U-Turn Sampler p. 107

Trevor Campbell

AutoStep: Locally Adaptive Involutive MCMC p. 108

Chirag Modi

ATLAS: Adapting Trajectory Lengths and Step-Size for Hamiltonian Monte Carlo p. 109

Stochastic Optimization

Organizer:

Shane G. Henderson

Cornell University

sgh9@cornell.edu

Session Description:

In many applications, one wishes to solve an optimization problem $\min_{x \in X} f(x)$, where $f(\cdot)$ and/or its derivatives can only be evaluated through noisy estimates obtained using Monte Carlo simulation. Such problems are ubiquitous in machine learning, and also arise in stochastic simulation applications. This session will consist of 3 talks in the area. Proposed Speakers

1. Raghu Bollapragada, Graduate Program in Operations Research and Industrial Engineering, University of Texas at Austin.
2. Raghu Pasupathy, Department of Statistics, Purdue University.
3. Shane G. Henderson, School of Operations Research and Information Engineering, Cornell University.

Wed, Jul 30, 2025 – Afternoon, 14:00 – 16:00,

Shane Henderson

A New Convergence Analysis of Two Stochastic Frank-Wolfe Algorithms p. 110

Raghu Bollapragada

Monte Carlo Based Adaptive Sampling Approaches for Stochastic Optimization p. 110

Recent Progress on Algorithmic Discrepancy Theory and Applications

Organizer:

Haotian Jiang

University of Chicago

jhtdavid@uchicago.edu

Session Description:

Discrepancy theory studies the irregularities of distributions. Typical questions studied in discrepancy theory include: “What is the most uniform way of distributing n points in the unit square, and how big must the irregularity be?”, “What is the best way to divide a set of n objects into two groups that are as ‘similar’ as possible?” These questions have been studied since the 1930s and progress on them have found extensive applications to many areas of mathematics, computer science, statistics, finance, etc. The past decade has seen tremendous progress in designing efficient algorithms for discrepancy questions. These developments have led to many surprising applications in areas such as differential privacy, graph sparsification, approximation algorithms and rounding, kernel density estimation, randomized controlled trials, and quasi-Monte Carlo methods. The goal of this special session is to present several exciting recent progress in this direction, and to facilitate cross-fertilization across different areas. Tentative list of speakers:

1. Haotian Jiang. University of Chicago, USA. jhtdavid@uchicago.edu.
2. Peng Zhang. Rutgers University, USA. pz149@rutgers.edu.
3. Aleksandar Nikolov. University of Toronto. anikolov@cs.toronto.edu.

A few related recent papers in this direction are listed below.

- [1] Harshaw, Christopher, Fredrik Sävje, Daniel A. Spielman, and Peng Zhang (2024). *Balancing covariates in randomized experiments with the gram-schmidt walk design*. Journal of the American Statistical Association 119, no. 548 (2024): 2934-2946.
- [2] Bansal, Nikhil, and Haotian Jiang (2025). *Quasi-Monte Carlo Beyond Hardy-Krause*. In Proceedings of the 2025 Annual ACM-SIAM Symposium on Discrete Algorithms (SODA), pp. 2051-2075. Society for Industrial and Applied Mathematics, 2025.
- [3] Aistleitner, Christoph, Dmitriy Bilyk, and Aleksandar Nikolov (2016). *Tusnády’s problem, the transference principle, and non-uniform QMC sampling*. In Monte Carlo and Quasi-Monte Carlo Methods: MCQMC 2016, Stanford, CA, August 14-19 12, pp. 169-180. Springer International Publishing, 2018.

Wed, Jul 30, 2025 – Afternoon, 14:00 – 16:00,

Haotian Jiang

Algorithmic Discrepancy Theory: An Overview p. 111

Peng Zhang

Improving the Design of Randomized Experiments via Discrepancy Theory p. 111

Aleksandar Nikolov

Online Factorization for Online Discrepancy Minimization p. 112

Monte Carlo Applications in High-Performance Computing, Computer Graphics, and Computational Science

Organizer:

Michael Mascagni

Florida State University and the National Institute of Standards and Technology
mascagni@fsu.edu

Session Description:

Monte Carlo methods are useful for solving problems in a variety of areas. We have four talks organized that span several areas. First, we consider the how Monte Carlo methods can provide fault tolerance to large computations via work on simulating soft and hard faults in Monte Carlo computation on a state-of-the-art computer. Next, we consider using Monte Carlo to create a fast and efficient computer graphics renderer. Next we consider two talks on applications of Monte Carlo to the solution of partial differential equations. One of these talks deals specifically with equations that arise in financial computing. The list of proposed speakers is (in alphabetical order):

1. Arash Fahim, Department of Mathematics, Florida State University
2. Sharanya Jayaraman, Department of Computer Science, Florida State University
3. Rohan Sawahney, High-Fidelity Physics Research Group, Nvidia Corporation
4. Silei Song, Department of Computer Science, Florida State University

Wed, Jul 30, 2025 – Afternoon, 14:00 – 16:00,

Silei Song

WoS-NN: Collaborating Walk-On-Spheres With Machine Learning to Solve Ellip- Tic PDEs
p. 112

QMC and Applications Part II

Organizers:

Michael Gnewuch

University of Osnabrück

michael.gnewuch@uni-osnabrueck.de

Takashi Goda

The University of Tokyo

goda@frcer.t.u-tokyo.ac.jp

Peter Kritzer

Austrian Academy of Sciences

peter.kritzer@oeaw.ac.at

Session Description:

Quasi-Monte Carlo (QMC) methods have been widely studied as an effective tool for high-dimensional integration and have found applications in various fields, including computational finance, computer graphics, data compression, partial differential equations with random coefficients, and optimization. Despite their success, ongoing theoretical developments and the expansion of application areas continue to drive this research field forward. This special session is devoted to showcasing recent advances in the theory of QMC methods and their applications. The confirmed speakers (in alphabetical order) are

- Dirk Nuyens (KU Leuven, Belgium)
- Art Owen (Stanford University, USA)
- Zexin Pan (Austrian Academy of Sciences, Austria)
- Kosuke Suzuki (Yamagata University, Japan)

Thu, Jul 31, 2025 – Morning, 10:30 – 12:30,

Felix Bartel

Exact Discretization, Tight Frames and Recovery via D-Optimal Designs p. 113

Zhijian He

High-Dimensional Density Estimation on Unbounded Domain p. 114

Mou Cai

L2-Approximation: Using Randomized Lattice Algorithms and QMC Hyperinterpolation p. 115

Frances Y. Kuo

Application of QMC to Oncology p. 115

Analysis of Langevin and Related Sampling Algorithms, Part II

Organizers:

Yifan Chen

Courant Institute of Mathematical Sciences, New York University
yifan.chen@nyu.edu

Xiaoou Cheng

Courant Institute of Mathematical Sciences, New York University
chengxo@nyu.edu

Jonathan Weare

Courant Institute of Mathematical Sciences, New York University
weare@nyu.edu

Session Description:

Many Markov Chain Monte Carlo (MCMC) samplers are based on stochastic dynamics. Langevin dynamics serves as a fundamental basis for a vast family of extensions, such as unadjusted Langevin algorithms, kinetic/underdamped Langevin algorithms, Hamiltonian Monte Carlo, and the No-U-Turn Sampler (NUTS). The gradient flow structure of Langevin dynamics also motivates the development of a large class of novel algorithms such as Stein variational gradient descent, birth-death process approaches, and those based on Fisher-Rao gradient flows. These methods have become ubiquitous across various fields, including molecular dynamics, Bayesian statistics, and machine learning. Recent years have seen significant theoretical advances in analyzing such methods, particularly in high-dimensional settings and non-convex cases. This special session aims to bring together researchers from different communities (probability, statistics, scientific computing, theoretical computer science, machine learning, etc.) working on analysis of sampling dynamics of Langevin and beyond to present recent progress, discuss challenges, and share ideas.

Thu, Jul 31, 2025 – Morning, 10:30 – 12:30,

Lihan Wang

Convergence Rates of Kinetic Langevin Dynamics With Weakly Confining Potentials p. 116

Peter Whalley

Randomized Splitting Methods and Stochastic Gradient Algorithms p. 117

Xiaoou Cheng

Delocalization of Bias in Unadjusted Hamiltonian Monte Carlo p. 117

Nested Expectations: Models and Estimators, Part II

Organizer:

Session Description:

Arved BartuskaKing Abdullah University of Science and Technology/RWTH Aachen Universityarved.ba
Lateef Haji-Ali Heriot-Watt Universitya.hajiali@hw.ac.ukNested expectations arise in many applications, such as in engineering, mathematical finance, and medical decision-making. In addition to their nested structure, numerical estimations of such expectations are often complicated by singularities or discontinuities. Moreover, approximations when evaluating inner expectations using, for example, finite element or time-stepping schemes render traditional estimation methods such as double-loop Monte Carlo prohibitively expensive. This session will explore models and applications with this structure and methods for efficient estimation. List of speakers: Raúl Tempone (King Abdullah University of Science and Technology/RWTH Aachen University) André Gustavo Carlon (RWTH Aachen University) Zhijian He (South China University of Technology) Philipp Guth (Johann Radon Institute for Computational and Applied Mathematics)

Thu, Jul 31, 2025 – Morning, 10:30 – 12:30,

RAUL TEMPONE

Multilevel Randomized Quasi-Monte Carlo Estimator for Nested Expectations p. 118

Matteo Raviola

Stochastic Gradient With Least-Squares Control Variates p. 119

Philipp Guth

A One-Shot Method for Bayesian Optimal Experimental Design p. 119

QMC and Applications Part II

Organizers:

Michael Gnewuch

University of Osnabrück

michael.gnewuch@uni-osnabrueck.de

Takashi Goda

The University of Tokyo

goda@frcer.t.u-tokyo.ac.jp

Peter Kritzer

Austrian Academy of Sciences

peter.kritzer@oeaw.ac.at

Session Description:

Quasi-Monte Carlo (QMC) methods have been widely studied as an effective tool for high-dimensional integration and have found applications in various fields, including computational finance, computer graphics, data compression, partial differential equations with random coefficients, and optimization. Despite their success, ongoing theoretical developments and the expansion of application areas continue to drive this research field forward. This special session is devoted to showcasing recent advances in the theory of QMC methods and their applications. The confirmed speakers (in alphabetical order) are

- Dirk Nuyens (KU Leuven, Belgium)
- Art Owen (Stanford University, USA)
- Zexin Pan (Austrian Academy of Sciences, Austria)
- Kosuke Suzuki (Yamagata University, Japan)

Thu, Jul 31, 2025 – Afternoon, 15:30 – 17:30,

Kosuke Suzuki

Quasi-Uniform Quasi-Monte Carlo Lattice Point Sets p. 120

Zexin Pan

QMC Confidence Intervals Using Quantiles of Randomized Nets p. 120

Dirk Nuyens

Approximation of Multivariate Periodic Functions p. 121

Analysis of Langevin and Related Sampling Algorithms, Part II

Organizers:

Yifan Chen

Courant Institute of Mathematical Sciences, New York University

yifan.chen@nyu.edu

Xiaoou Cheng

Courant Institute of Mathematical Sciences, New York University

chengxo@nyu.edu

Jonathan Weare

Courant Institute of Mathematical Sciences, New York University

weare@nyu.edu

Session Description:

Many Markov Chain Monte Carlo (MCMC) samplers are based on stochastic dynamics. Langevin dynamics serves as a fundamental basis for a vast family of extensions, such as unadjusted Langevin algorithms, kinetic/underdamped Langevin algorithms, Hamiltonian Monte Carlo, and the No-U-Turn Sampler (NUTS). The gradient flow structure of Langevin dynamics also motivates the development of a large class of novel algorithms such as Stein variational gradient descent, birth-death process approaches, and those based on Fisher-Rao gradient flows. These methods have become ubiquitous across various fields, including molecular dynamics, Bayesian statistics, and machine learning. Recent years have seen significant theoretical advances in analyzing such methods, particularly in high-dimensional settings and non-convex cases. This special session aims to bring together researchers from different communities (probability, statistics, scientific computing, theoretical computer science, machine learning, etc.) working on analysis of sampling dynamics of Langevin and beyond to present recent progress, discuss challenges, and share ideas.

Thu, Jul 31, 2025 – Afternoon, 15:30 – 17:30,

Krishnakumar Balasubramanian

Finite-Particle Convergence Rates for Stein Variational Gradient Descent p. 121

Yifan Chen

Convergence of Unadjusted Langevin in High Dimensions: Delocalization of Bias p. 122

Molei Tao

Langevin-Based Sampling Under Nonconvex Constraints p. 123

Stefan Oberdörster

Accelerated Mixing of the No-U-Turn Sampler p. 123

Recent Advances in Stochastic Gradient Descent

Organizer:

Jing Dong

Columbia University

jing.dong@gsb.columbia.edu

Session Description:

Stochastic Gradient Descent (SGD) is a cornerstone optimization method in machine learning, renowned for its efficiency in handling large-scale data. Its iterative approach enables the processing of extensive datasets by updating model parameters using randomly selected data subsets, thereby reducing computational costs. Despite its widespread adoption, traditional SGD faces challenges such as convergence to sharp minima, and sensitivity to data distribution shifts. Addressing these challenges is crucial for enhancing model generalization, robustness, and overall performance in diverse applications. This session aims to delve into recent developments that address these challenges in SGD, presenting innovative methodologies and theoretical insights to enhance its effectiveness in complex learning scenarios. The session will have three to four speakers. Currently, the confirmed speakers are Jose Blanchet (Stanford University), Chang-Han Rhee (Northwestern University), and Jing Dong (Columbia University). Each will present their recent works on stochastic gradient descent, ranging from SGD and heavy-tailed phenomenon to SGD with adaptively generated data. Collectively, these talks will shed light on cutting-edge advancements in SGD methodologies, providing both theoretical frameworks and practical strategies to enhance optimization in complex, real-world applications.

Thu, Jul 31, 2025 – Afternoon, 15:30 – 17:30,

Jose Blanchet

Inference for Stochastic Gradient Descent With Infinite Variance p. 125

Jing Dong

Stochastic Gradient Descent With Adaptive Data p. 125

Forward and Inverse Problems for Stochastic Reaction Networks

Organizers:

Sophia Münker

RWTH Aachen University

muenker@uq.rwth-aachen.de

Chiheb Ben Hammouda

Utrecht University

c.benhammouda@uu.nl

Raúl Tempone

RWTH Aachen University

tempone@uq.rwth-aachen.de

Session Description:

This session aims to bring together experts working on stochastic reaction networks and pure jump processes for modeling stochastic biological and chemical systems. The session is about recent advances in Monte Carlo methods, variance and dimension reduction techniques that are relevant for tackling forward and inverse problems. The speakers are:

- Zhou Fang (Academy of Mathematics and Systems Science, Chinese Academy of Sciences)
- Sophia Münker (RWTH Aachen University)
- Maksim Chupin (King Abdullah University of Science and Technology (KAUST))
- Muruhan Rathinam (University of Maryland Baltimore County)

Fri, Aug 1, 2025 – Morning, 09:00 – 10:30,

Maksim Chupin

Filtered Markovian Projection: Dimensionality Reduction in Filtering for Stochastic Reaction Networks p. 126

Zhou Fang

Fixed-Budget Simulation Method for Growing Cell Populations p. 127

Muruhan Rathinam

State and Parameter Inference in Stochastic Reaction Networks p. 127

Sophia Münker

Dimensionality Reduction for Efficient Rare Event Estimation p. 128

Hardware or Software for (Quasi-)Monte Carlo Algorithms, Part II

Organizers:

Sou-Cheng T. Choi

Illinois Institute of Technology

schoi32@iit.edu

Pieterjan Robbe

Sandia National Laboratories

pmrobbe@sandia.gov

Mike Giles

University of Oxford

mike.giles@maths.ox.ac.uk

Session Description:

Monte Carlo (MC) or quasi-Monte Carlo (QMC) algorithms are widely used in various fields such as finance, physics, and engineering for their ability to handle high-dimensional integration problems. The development and maintenance of software for (quasi-)Monte Carlo ((Q)MC) algorithms can significantly enhance the accessibility and usability of these techniques. This special session aims to bring together experts from academia and industry to discuss recent advances in (Q)MC software, share best practices, and explore future directions, fostering collaboration among researchers and practitioners. Topics of interest for the session include:

- Novel hardware or architectural designs for open-source (Q)MC libraries.
- Best collaborative practices for developing and maintaining efficient and reliable (Q)MC software.
- Challenges and opportunities in integrating (Q)MC methods with machine learning and AI techniques.
- High-performance computing solutions for (Q)MC software.
- Adaptation of (Q)MC software to application fields such as finance, computer graphics, sensitivity analysis, Bayesian optimization, and uncertainty quantification.
- Innovative approaches to enhancing and extending existing (Q)MC tools.

Fri, Aug 1, 2025 – Morning, 09:00 – 10:30,

Niklas Baumgarten

A High-Performance Multi-Level Monte Carlo Software for Full Field Estimates and Applications in Optimal Control p. 129

Aleksei Sorokin

Quasi-Monte Carlo Generators, Randomization Routines, and Fast Kernel Methods p. 130

Johannes Krotz

Hybrid Monte Carlo Methods for Kinetic Transport p. 130

Abstracts

Special Session Talks

Mon, Jul 28 10:30–12:30

Quantitative Approximation of Stochastic Kinetic Equations: From Discrete to Continuum

Chengcheng Ling

University of Augsburg

`chengcheng.ling@uni-a.de`

Coauthor(s): Stochastic Computation and Complexity, Part I

We study the strong convergence of a generic tamed Euler-Maruyama (EM) scheme for the kinetic type stochastic differential equation (SDE) (also known as second order SDE) driven by α -stable type noise with $\alpha \in (1, 2]$. We show that when the drift exhibits a relatively low regularity: anisotropic β -Hölder continuity with $\beta > 1 - \frac{\alpha}{2}$, the corresponding tamed EM converges with a convergence rate $(\frac{1}{2} + \frac{\beta}{\alpha(1+\alpha)} \wedge \frac{1}{2})$, which aligns with the results of first-order SDEs.

This talk is based on the work [arXiv:2409.05706](#) (joint with Zimo Hao and Khoa Lê) and the work [arXiv:2412.05142](#).

Mon, Jul 28 10:30–12:30

A strong order 1.5 boundary preserving discretization scheme for scalar SDEs defined in a domain*Andreas Neuenkirch*

University of Mannheim

neuenkirch@uni-mannheim.de

Coauthor(s): Ruishu Liu, Xiaojie Wang

Special session: Stochastic Computation and Complexity p.32

We study the strong approximation of scalar SDEs, which take values in a domain and have non-Lipschitz coefficients. By combining a Lamperti-type transformation with a semi-implicit discretization approach and a taming strategy, we construct a domain-preserving scheme that strongly converges under weak assumptions. Moreover, we show that this scheme has strong convergence order 1.5 under additional assumptions on the coefficients of the SDE. In our scheme, the domain preservation is a consequence of the semi-implicit discretization approach, while the taming strategy allows controlling terms of the scheme that admit singularities but are required to obtain the desired order.

Our general convergence results are applied to various SDEs from applications, with sub-linearly or super-linearly growing and non-globally Lipschitz coefficients.

- [1] Ruishu Liu, Andreas Neuenkirch and Xiaojie Wang (2024+). A strong order 1.5 boundary preserving discretization scheme for scalar SDEs defined in a domain. *Mathematics of Computation*. doi:10.1090/mcom/4014 (to appear, online first)

.

Mon, Jul 28 10:30–12:30

Christopher Rauhögger*University of Passau*

christopher.rauhoeegger@uni-passau.de

StochasticComputationandComplexity

We consider d -dimensional systems of SDEs with a discontinuous drift coefficient. More precisely, we assume that there exists a C^5 -hypersurface $\Theta \subseteq \mathbb{R}^d$ such that the drift coefficient is intrinsic Lipschitz continuous on $\mathbb{R}^d \setminus \Theta$ and has intrinsic Lipschitz continuous derivative on $\mathbb{R}^d \setminus \Theta$. Furthermore, the diffusion coefficient is C^1 on \mathbb{R}^d and commutative with a bounded derivative that is intrinsic Lipschitz continuous on $\mathbb{R}^d \setminus \Theta$.

It was proven in [1] for $d = 1$ and more recently in [2] for general $d \in \mathbb{N}$ that in this setting a transformed Milstein scheme achieves an L_p -error rate of order at least $3/4$ — in terms of the number of evaluations of the driving Brownian motion. Furthermore it was proven in

[3] that for $d = 1$ in the same setting an adaptive Milstein-type scheme achieves an L_p -error rate of order at least 1 in terms of the average number of evaluations of the driving Brownian motion.

In this talk we present a generalisation of the result from [3] to higher dimensions. More precisely, we introduce an adaptive transformed Milstein scheme which can be used for the approximation of solutions of d -dimensional systems of SDEs at the final time point in this setting and prove that this scheme achieves an L_p -error rate of order at least 1 in terms of the average number of evaluations of the driving Brownian motion.

- [1] Müller-Gronbach, Thomas & Yaroslavl'tseva, Larisa. (2022). *A strong order 3/4 method for SDEs with discontinuous drift coefficient*. IMA Journal of Numerical Analysis. 42. 229-259
- [2] Rauh'ogger, Christopher. (2025+). *Milstein-type methods for strong approximation of systems of SDEs with a discontinuous drift coefficient*. In preparation
- [3] Yaroslavl'tseva, Larisa. (2022). *An adaptive strong order 1 method for SDEs with discontinuous drift coefficient*. Journal of Mathematical Analysis and Applications. 513. 2. Paper Number 126180, 29

Mon, Jul 28 10:30–12:30

Strong order 1 adaptive approximation of jump-diffusion SDEs with discontinuous drift

Verena Schwarz
University of Klagenfurt
verena.schwarz@aau.at

Coauthor(s): Stochastic Computation and Complexity

In this talk we present an adaptive approximation scheme for jump-diffusion SDEs with discontinuous drift and (possibly) degenerate diffusion. The scheme is a transformation-based doubly-adaptive quasi-Milstein scheme, which is doubly-adaptive in the sense that it is jump-adapted, i.e. all jump times of the Poisson noise are grid points, and it includes an adaptive stepsize strategy to account for the discontinuities of the drift. It is proven to have strong convergence rate 1 in L^p for $p \in [1, \infty)$ with respect to the average computational cost for these SDEs. To obtain our result, we prove that under slightly stronger assumptions which are still weaker than those in existing literature, a related doubly-adaptive quasi-Milstein scheme has convergence order 1.

Mon, Jul 28 10:30–12:30

André-Alexander Zepernick*Free University of Berlin*

a.zepernick@fu-berlin.de

AnaDjurdjevac, VesaKaarnioja, ClaudiaSchillings

Coauthor(s): Domain Uncertainty Quantification

The problem of modelling processes with partial differential equations posed on random domains arises in various applications like biology or engineering. We study uncertainty quantification for partial differential equations subject to domain uncertainty. For the random domain parameterization, we adopt an approach, which was also examined by Chernov and Lê [1,2] as well as Harbrecht, Schmidlin, and Schwab [3], where one assumes the input random field to be Gevrey regular. This approach has the advantage of being substantially more general than models which assume a particular parametric representation of the input random field such as a Karhunen–Loève series expansion. As model problems we consider both the Poisson equation as well as the heat equation and design randomly shifted lattice quasi-Monte Carlo (QMC) cubature rules for the computation of response statistics subject to domain uncertainty. The QMC rules obtained in [4] exhibit dimension-independent, faster-than-Monte Carlo cubature convergence rates. Our theoretical results are illustrated by numerical examples.

- [1] Chernov, Alexey, & Lê, Tùng (2024). Analytic and Gevrey class regularity for parametric elliptic eigenvalue problems and applications. *SIAM Journal on Numerical Analysis*, **62**(4), 1874–1900.
- [2] Chernov, A., & Lê, Tùng (2024). Analytic and Gevrey class regularity for parametric semilinear reaction-diffusion problems and applications in uncertainty quantification. *Computers & Mathematics with Applications*, **164**, 116–130.
- [3] Harbrecht, Helmut, Schmidlin, Marc, & Schwab, Christoph (2024). The Gevrey class implicit mapping theorem with application to UQ of semilinear elliptic PDEs. *Mathematical Models and Methods in Applied Sciences.*, **34**(5), 881–917.
- [4] Djurdjevac, Ana, Kaarnioja, Vesa, Schillings, Claudia & Zepernick, André-Alexander (2025). Uncertainty quantification for stationary and time-dependent PDEs subject to Gevrey regular random domain deformations. Preprint, *arXiv:2502.12345 [math.NA]*.

Mon, Jul 28 10:30–12:30

Domain Uncertainty Quantification for Electromagnetic Wave Scattering via First-Order Sparse Boundary Element Approximation

Carlos Jerez-Hanckes

INRIA Chile

carlos.jerez@inria.cl

Coauthor(s): Paul Escapil-Inchauspé

Special session: Domain uncertainty quantification p.33

Quantifying the effects on electromagnetic waves scattered by objects of uncertain shape is key for robust design, particularly in high-precision applications. Assuming small random perturbations departing from a nominal domain, the first-order sparse boundary (FOSB) element method has been proven to directly compute statistical moments with poly-logarithmic complexity [1,2] for a prescribed accuracy, without resorting to computationally intense Monte Carlo (MC) simulations. However, implementing FOSB is not straightforward as the lack of compelling computational results for EM scattering attests [3]. In this work, we present a first full 3D implementation of FOSB for shape-related uncertainty quantification (UQ) in EM scattering [4]. In doing so, we address several implementation issues such as ill-conditioning and large computational and memory requirements and present a comprehensive, state-of-the-art, easy-to-use, open-source computational framework to directly apply this technique when dealing with complex objects. Exhaustive numerical experiments confirm our claims and demonstrate the technique's applicability and provide pathways for further improvement.

- [1] Jerez-Hanckes, Schwab (2017). *Electromagnetic Wave Scattering by Random Surfaces: Uncertainty Quantification via Sparse Tensor Boundary Elements*, IMA Journal of Numerical Analysis **37**(3), 1175–1210.
- [2] Hiptmair, Jerez-Hanckes, Schwab (2013). *Sparse Tensor Edge Elements*, BIT Numerical Mathematics **53**, 925–943.
- [3] Escapil-Inchauspé, Jerez-Hanckes (2020). *Helmholtz Scattering by Random Domains: First-Order Sparse Boundary Elements Approximation*, SIAM Journal of Scientific Computing **42**(5), A2561–A2592.
- [4] Escapil-Inchauspé, Jerez-Hanckes (2024). *Shape Uncertainty Quantification for Electromagnetic Wave Scattering via First-Order Sparse Boundary Element Approximation*, IEEE Transactions in Antennas & Propagation **72**(8):6627–6637.

Mon, Jul 28 10:30–12:30

Quantifying uncertainty in spectral clusterings: expectations for perturbed and incomplete data*Jürgen Dölz*

University of Bonn

doelz@ins.uni-bonn.de

Coauthor(s): Jolanda Weygandt

Special session: Domain Uncertainty Quantification p.33

Spectral clustering is a popular unsupervised learning technique which partitions a set of unlabelled data into disjoint clusters. However, the data under consideration are often experimental data, implying that the data is subject to measurement errors and measurements may even be lost or invalid. These uncertainties in the input data induce corresponding uncertainties in the resulting clusters. In this talk we model the uncertainties as random, implying that the clusters need to be considered random as well. We further discuss a mathematical framework based on random set theory for the computational approximation of statistically expected clusterings.

Mon, Jul 28 10:30–12:30

Model Problems for PDEs on Uncertain Domains*Harri Hakula*

Aalto University

Harri.Hakula@aalto.fi

Coauthor(s): Domain Uncertainty Quantification

Partial differential equation related uncertainty quantification has become one of the topical research areas in applied mathematics and, in particular, engineering. Stochastic finite element methods are applied both in source and eigenvalue problems. Remarkably, computational function theory provides a rich set of invariants and identities that can be applied in designing model problems where the domain is random or uncertain. In this talk the focus is on conformal capacity in a simple, yet general case where the sides of a quadrilateral are assumed be random and parameterised with a suitable Karhunen-Loève expansion [1]. Lattice quasi-Monte Carlo (QMC) cubature rules are used for computing the expected value of the solution to the resulting Poisson problem subject to domain uncertainty.

High-order finite element methods (*hp*-FEM) are used in the deterministic problems. The special features related to modelling random domains in *hp*-context are discussed. Convergence properties of the lattice QMC quadratures are presented. The talk concentrates on numerical experiments demonstrating the theoretical error estimates. The new results on the associated Steklov eigenvalue problem are also covered.

- [1] Hakula, H., Harbrecht, H., Kaarnioja, V., Kuo, F. Y., & Sloan, I. H. (2024). Uncertainty quantification for random domains using periodic random variables. *Numerische Mathematik*, 156(2), 273–317. <https://doi.org/10.1007/s00211-023-01392-6>

Mon, Jul 28 10:30–12:30

QMC for Bayesian optimal experimental design with application to inverse problems governed by PDEs

Vesa Kaarnioja

Free University of Berlin

vesa.kaarnioja@fu-berlin.de

Coauthor(s): Claudia Schillings

Special session: Nested expectations: models and estimators, Part I p.34

The goal in Bayesian optimal experimental design (OED) is to maximize the expected information gain for the reconstruction of unknown quantities in an experiment by optimizing the placement of measurements. The objective function in the resulting optimization problem involves a multivariate double integral over the high-dimensional parameter and data domains. For the efficient approximation of these integrals, we consider a sparse tensor product combination of quasi-Monte Carlo (QMC) cubature rules over the parameter and data domains. For the parameterization of the unknown quantities, we consider a model recently studied by Chernov and Lê [1,2] as well as Harbrecht, Schmidlin, and Schwab [3] in which the input random field is assumed to belong to a Gevrey class. The Gevrey class contains functions that are infinitely many times continuously differentiable with a growth condition on the higher-order partial derivatives, but which are not analytic in general. Using the techniques developed in [4], we investigate efficient Bayesian OED for inverse problems governed by partial differential equations (PDEs).

- [1] Chernov, Alexey, & Lê, Tùng (2024). Analytic and Gevrey class regularity for parametric elliptic eigenvalue problems and applications. *SIAM Journal on Numerical Analysis*, **62**(4), 1874–1900.
- [2] Chernov, Alexey, & Lê, Tùng (2024). Analytic and Gevrey class regularity for parametric semilinear reaction-diffusion problems and applications in uncertainty quantification. *Computers & Mathematics with Applications*, **164**, 116–130.
- [3] Harbrecht, Helmut, Schmidlin, Marc, & Schwab, Christoph (2024). The Gevrey class implicit mapping theorem with applications to UQ of semilinear elliptic PDEs. *Mathematical Models and Methods in Applied Sciences*, **34**(5), 881–917.
- [4] Kaarnioja, Vesa, & Schillings, Claudia (2024). Quasi-Monte Carlo for Bayesian design of experiment problems governed by parametric PDEs. Preprint, *arXiv:2405.03529 [math.NA]*.

Mon, Jul 28 10:30–12:30

Double-loop randomized quasi-Monte Carlo estimator for nested integration*Sebastian Krumscheid*

Karlsruhe Institute of Technology

sebastian.krumscheid@kit.edu

Coauthor(s): Arved Bartuska, André Gustavo Carlon, Luis Espath, Raúl Tempone

We present a double-loop randomized quasi-Monte Carlo estimator for nested integrals. This estimator applies the randomized quasi-Monte Carlo (rQMC) method to both integrals in the nested setting. Error bounds are derived for outer integrands displaying singularities at the boundaries of the integration domain, based on Owen's work [1]. Standard error bounds via the Koksma–Hlawaka inequality are rendered ineffective as singularities lead to infinite Hardy–Krause variation. Moreover, finite element discretizations of the inner integrand are discussed, increasing the overall cost of nested integral estimators.

The effectiveness of the proposed estimator is demonstrated in the Bayesian design setting for the estimation of the expected information gain of an experiment. A truncation scheme of the observation noise present in the experiment model allows for the application of the derived error bounds. Applications from pharmacokinetics and thermomechanics demonstrate the efficiency of the proposed method in high dimensions.

- [1] Owen, Art B. (2006). *Halton sequences avoid the origin*. SIAM Review, 48:487–503.

Mon, Jul 28 10:30–12:30

Posterior-Free A-Optimal Bayesian Design of Experiments via Conditional Expectation*Vinh Hoang*

hoang@uq.rwth-aachen.de

LuisEspath, SebastianKrumscheid, Ra\unhbox\voidb@x\bgroup\let\unhbox\voidb@x\setbox\@tempboxa\hbox{u\global\mathchardef\accent@spacefactor\spacefactor}\let\begin\group\let\typeout\protect\begin\group\def\MessageBreak{\Omega(Font)}\let\protect\immediate\write\m@ne{LaTeXFontInfo: oninputline271.}\end\group\end\group\relax\let\ignorespaces\relax\accent19u\egroup\spacefactor\accent@spacefactor\lTempone

We propose a novel approach for solving the A-optimal Bayesian design of experiments that does not require sampling or approximating the posterior distribution. In this setting, the objective function is the expected conditional variance (ECV). Our method estimates the ECV by leveraging conditional expectation, which we approximate using its orthogonal

projection property. We derive an asymptotic error bound for this estimator and validate it through numerical experiments. The method is particularly efficient when the design parameter space is continuous. In such scenarios, the conditional expectation can be approximated non-locally using tools such as neural networks. To reduce the number of evaluations of the measurement model, we incorporate transfer learning and data augmentation. Numerical results show that our method significantly reduces model evaluations compared to standard importance sampling-based techniques. Code available at: <https://github.com/vinh-tr-hoang/DOEviaPACE>.

- [1] Hoang, V., Espath, L., Krumscheid, S., & Tempone, R. (2025). Scalable method for Bayesian experimental design without integrating over posterior distribution. *SIAM ASA Journal on Uncertainty Quantification*, 13(1), 114-139.
<https://doi.org/10.1137/23M1603364>

Mon, Jul 28 10:30–12:30

CUDA implementation of MLMC on NVIDIA GPUs

Mike Giles

University of Oxford

mike.giles@maths.ox.ac.uk

Coauthor(s): Hardware or Software for (Quasi-)Monte Carlo Algorithms

This talk will discuss the implementation of Multilevel Monte Carlo on NVIDIA GPUs. It will focus on some of the tricks needed for best performance, such as on-the-fly generation of random numbers within CUDA kernels, and latency-hiding through GPU computations in anticipation of requests from the CPU host process which manages the MLMC optimisation. It will also discuss the opportunities and challenges in exploiting mixed-precision computing, using nested MLMC to perform most calculations at half precision (fp16) and just a few at single precision (fp32).

- [1] Giles, M.B. & Sheridan-Methven, O. (2022) Analysis of nested multilevel Monte Carlo using approximate Normal random variables. *SIAM/ASA Journal on Uncertainty Quantification*, 10(1), 200–226.

Mon, Jul 28 10:30–12:30

Multilevel quasi-Monte Carlo without replications*Pieterjan Robbe*

Sandia National Laboratories

pmrobbe@sandia.gov

Coauthor(s): Aleksei Sorokin, Gianluca Geraci, Fred J. Hickernell, Mike Eldred

Special session: Hardware or Software for (Quasi-)Monte Carlo Algorithms p.35

In this talk, we explore a novel approach to multilevel quasi-Monte Carlo (MLQMC) sampling that eliminates the need for stochastic replications. Our approach for estimating the level-wise variances is based on the Bayesian cubature framework introduced in [1]. Empirical results from a series of numerical experiments illustrate the effectiveness of our method in various applications. We discuss the integration of our new method in Dakota, Sandia's flagship UQ software package.

- [1] Jagadeeswaran, R., & Hickernell, F. J. (2019). Fast automatic Bayesian cubature using lattice sampling. *Statistics and Computing*, **29**(6), 1215–1229.

Mon, Jul 28 10:30–12:30

A nested Multilevel Monte Carlo framework for efficient simulations on FPGAs*Irina-Beatrice Haas*

Mathematical Institute, University of Oxford

irina-beatrice.haas@maths.ox.ac.uk

Coauthor(s): Michael B. Giles

Special session: Hardware or Software for (Quasi-)Monte Carlo Algorithm p.35

Multilevel Monte Carlo (MLMC) is a computational method that reduces the cost of Monte Carlo simulations by combining SDE approximations with multiple resolutions. A further avenue for significantly reducing cost and improving power efficiency of MLMC, notably for financial option pricing, is the use of low precision calculations on configurable hardware devices such as Field-Programmable Gate Arrays (FPGAs). With this goal in mind, in this talk we propose a new MLMC framework that exploits approximate random variables and fixed-point operations with optimised precision to compute most SDE paths with a lower cost.

For the generation of random Normal increments, we discuss several methods based on the approximation of the inverse normal CDF (see e.g. [3]), and we argue that these methods could be implemented on FPGAs using small Look-Up-Tables to generate random numbers

more efficiently than on CPUs or GPUs.

To set the bit-width of variables in the path generation we propose a rounding error model and optimise the precision of all variables on each Monte Carlo level. This optimisation stage is independent of the desired overall accuracy, and can therefore be performed off-line.

With these two key improvements, our proposed framework [2] offers higher computational savings than the existing mixed-precision MLMC framework [1].

- [1] Brugger, C., de Schryver, C., Wehn, N., Omland, S., Hefter, M., Ritter, K., Kostiuk, A., & Korn, R. (2014). Mixed precision multilevel Monte Carlo on hybrid computing systems. In *Proceedings of the IEEE Conference on Computational Intelligence for Financial Engineering & Economics (CIFEr)* (pp. 215–222). IEEE. <https://doi.org/10.1109/CIFEr.2014.6924076>
- [2] Haas, I. B., & Giles, M. B. (2025). A nested MLMC framework for efficient simulations on FPGAs. Accepted to appear in *Monte Carlo Methods and Applications*. arXiv preprint arXiv:2502.07123. <https://arxiv.org/abs/2502.07123>
- [3] Giles, M.B., & Sheridan-Methven, O. (2023). Approximating Inverse Cumulative Distribution Functions to Produce Approximate Random Variables. *ACM Transactions on Mathematical Software*, 49(3), no 26. <https://doi.org/10.1145/3604935>

Mon, Jul 28 10:30–12:30

Scalable and User-friendly QMC Sampling with UMBridge

Chung Ming Loi

Durham University

chung.m.loi@durham.ac.uk

Coauthor(s): Anne Reinarz

Special session: Hardware and Software for Quasi-Monte Carlo Methods p.35

Uncertainty quantification (UQ) plays a crucial role in geoscience: Bayesian inference determines model parameters, such as the permeability and porosity of the sub-surface, that are typically impossible to determine accurately from observations. In practice, it is crucial to study the uncertainty in the inferred parameters to correctly quantify risk and make decisions. Despite its scientific value, performing UQ for an application is often a lengthy process due to a need for interdisciplinary expertise in both UQ and advanced simulation codes. In this talk, we will look at improving the workflow and computational efficiency of quasi-Monte Carlo (i.e., sampling/ensemble based) approaches to UQ applications. We introduce UM-Bridge [2], a universal software interface that facilitates integration of complex simulation models with an entire range of leading UQ packages. By separating concerns between simulation and UQ, UM-Bridge allows rapid development of cutting-edge applications. The newly implemented load balancing framework in UM-Bridge further enables scaling workloads to High Performance Computing clusters.

- [1] Graham, I. G., Kuo, F. Y., Nuyens, D., Scheichl, R., and Sloan, I. H. (2011). Quasi-Monte Carlo methods for elliptic PDEs with random coefficients and applications. *Journal of Computational Physics*, 230(10), 3668-3694.
- [2] L. Seelinger, V. Cheng-Seelinger, A. Davis, M. Parno, and A. Reinartz, “UM-Bridge: Uncertainty quantification and modeling bridge,” *Journal of Open Source Software*, vol. 8, no. 83, p. 4748, 2023. [Online]. Available: <https://doi.org/10.21105/joss.04748>

Mon, Jul 28 15:30–17:30

Optimal designs for function discretization and construction of tight frames

Kateryna Pozharska

pozharska.k@gmail.com

FelixBartel,LutzK\unhbox\voidb@x\bgroup\let\unhbox\voidb@x\setbox\@tempboxa\hbox{a\global\mathchardef\accent@spacefactor\spacefactor}\let\begin\group\let\typeout\protect\begin\group\def\MessageBreak{\Omega(Font)}\let\protect\immediate\write\m@ne{LaTeXFontInfo:oninputline419.}\endgroup\endgroup\relax\let\ignorespaces\relax\accent127a\egroup\spacefactor\accent@spacefactor\mmerer,MartinSch\unhbox\voidb@x\bgroup\let\unhbox\voidb@x\setbox\@tempboxa\hbox{a\global\mathchardef\accent@spacefactor\spacefactor}\let\begin\group\let\typeout\protect\begin\group\def\MessageBreak{\Omega(Font)}\let\protect\immediate\write\m@ne{LaTeXFontInfo:oninputline4}\endgroup\endgroup\relax\let\ignorespaces\relax\accent127a\egroup\spacefactor\accent@spacefactorfer,TinoUllrich

Coauthor(s): Stochastic Computation and Complexity

In the talk we will present a direct and constructive approach for the construction of tight frames and exact Marcinkiewicz-Zygmund inequalities in the Lebesgue space [1]. It is based on a similar procedure of maximization of the determinant of a certain Gramian matrix with respect to points and weights, already used in [2] for discretization problem for the uniform norm, and results in a discrete measure with at most $n^2 + 1$ atoms, which accurately subsamples the L_2 -norm of complex-valued functions contained in a given n -dimensional subspace.

This approach can as well be used for the reconstruction of functions from general RKHS in L_p where one only has access to the most important eigenfunctions. The general results apply to the d -sphere or multivariate trigonometric polynomials on \mathbb{T}^d spectrally supported on arbitrary finite index sets $I \subset \mathbb{Z}^d$. Numerical experiments indicate the sharpness of this result.

- [1] Bartel, Felix, & Kämmerer, Lutz, & Pozharska, Kateryna, & Schäfer, Martin, & Ullrich, Tino (2024). *Exact discretization, tight frames and recovery via D -optimal designs*. arXiv:2412.02489.
- [2] Krieg, David, & Pozharska, Kateryna, & Ullrich, Mario & Ullrich, Tino (2024). *Sampling projections in the uniform norm*. arXiv:2401.02220.

Mon, Jul 28 15:30–17:30

Optimality of deterministic and randomized QMC-cubatures on several scales of function spaces

Michael Gnewuch

University of Osnabrueck

`mgnewuch@uos.de`

Coauthor(s): Josef Dick, Lev Markhasin, Winfried Sickel, Yannick Meiners

Special session: Stochastic Computation and Complexity p.37

We study the integration problem over the s -dimensional unit cube on four scales of Banach spaces of integrands. First we consider Haar wavelet spaces $H_{p,q,\alpha}$, $1 \leq p, q \leq \infty$, $\alpha > 1/p$, consisting of functions whose Haar wavelet coefficients exhibit a certain decay behavior measured by the parameters p, q , and, most importantly, α . We study the worst case error of a deterministic cubature rule over the norm unit ball and provide upper bounds for quasi-Monte Carlo (QMC) cubature rules based on arbitrary (t, m, s) -nets as well as matching lower error bounds for arbitrary cubature rules. These results show that using arbitrary (t, m, s) -nets as integration nodes yields the best possible rate of convergence. In the Hilbert space setting $p = 2 = q$ it was earlier shown by Heinrich, Hickernell and Yue [2] that scrambled (t, m, s) -nets yield optimal convergence rates in the randomized setting, where the randomized worst case error is considered.

We establish several suitable function space embeddings that allow to transfer the deterministic and randomized upper error bounds on Haar wavelet spaces to certain spaces of fractional smoothness $1/p < \alpha \leq 1$ and to Sobolev and Besov spaces of dominating mixed smoothness $1/p < a \leq 1$. Known lower bounds for Sobolev and Besov spaces of dominating mixed smoothness show that (deterministic or suitably randomized) (t, m, s) -nets yield optimal convergence rates also on the corresponding scales of spaces.

The talk is based on the preprint [1] and the master thesis of my student Yannick Meiners.

- [1] M. Gnewuch, J. Dick, L. Markhasin, W. Sickel, QMC integration based on arbitrary (t, m, s) -nets yields optimal convergence rates on several scales of function spaces, preprint 2024, arXiv:2409.12879.
- [2] S. Heinrich, F. J. Hickernell and R. X. Yue, Optimal quadrature for Haar wavelet spaces, *Math. Comput.*, 73 (2004), 259–277.

Mon, Jul 28 15:30–17:30

Complexity of approximating piecewise smooth functions in the presence of deterministic or random noise*Leszek Plaskota*

University of Warsaw

L.Plaskota@mimuw.edu.pl

Coauthor(s): Stochastic Computation and Complexity

Consider the smoothness class of 1-periodic functions $f : \mathbb{R} \rightarrow \mathbb{R}$ for which

$$|f^{(r)}(x) - f^{(r)}(y)| \leq |x - y|^\rho, \quad x, y \in \mathbb{R},$$

where $r \in \{0, 1, 2, \dots\}$ and $0 < \rho \leq 1$. It is well known that the optimal worst case error of L^p -approximation ($1 \leq p \leq \infty$) of such functions that can be achieved from n exact evaluations of f is proportional to $e_n = n^{-(r+\rho)}$. Less obvious is what happens when the functions are piecewise smooth only with unknown break points. Even less obvious is the situation when the function values are additionally corrupted by some noise, i.e., when evaluating the value of f at x we obtain $y = f(x) + \xi$ where $|\xi| \leq \delta$ (deterministic noise) or ξ is a zero-mean random variable of variance σ^2 (random noise). In this talk we construct an algorithm which despite the presence of noise and break points achieves the worst case L^p -error still proportional to e_n provided the noise level δ or σ is of the same order e_n (except the case of $p = \infty$ and random noise where we have an additional logarithmic factor in the error). The algorithm uses divided differences and special adaptive extrapolation technique to locate the break points and approximate in their neighborhoods.

Mon, Jul 28 15:30–17:30

Stability of Expected Utility in Bayesian Optimal Experimental Design*Tapio Helin*

LUT University

tapio.helin@lut.fi

Coauthor(s): Recent advances in optimization under uncertainty

We explore the stability properties of utility functions in Bayesian optimal experimental design, introducing novel utilities inspired by the analysis. We establish a general framework to study the behavior of expected utility under perturbations in infinite-dimensional setting and prove its convergence properties. Our results provide theoretical guarantees for the robustness of Bayesian design criteria and offer insights into their practical applicability in complex experimental settings.

Mon, Jul 28 15:30–17:30

Efficient expected information gain estimators based on the randomized quasi-Monte Carlo method*Arved Bartuska*King Abdullah University of Science and Technology/RWTH Aachen University
arved.bartuska@kaust.edu.sa

Coauthor(s): André Gustavo Carlon, Luis Espath, Sebastian Krumscheid, Raúl Tempone

Efficient estimation of the expected information gain (EIG) of an experiment allows for design optimization in a Bayesian setting. This task faces computational challenges, particularly when the experiment model requires numerical discretization schemes. We demonstrate various methods to make such estimations feasible, combining quasi-Monte Carlo (QMC), randomized QMC (rQMC), and multilevel methods.

Analytical error bounds are made possible by Owen's [1] and He et al.'s [2] work on singular integrands combined with a truncation scheme of the observation noise present in experiment models. Applications from Bayesian experimental design demonstrate the improved convergence behavior of the proposed methods compared to traditional Monte Carlo-based estimators.

- [1] Owen, Art B. (2006). *Halton sequences avoid the origin*. SIAM Review, 48:487–503.
- [2] He, Zhijian, & Zheng, Zhan, & Wang, Xiaoqun. (2023). *On the error rate of importance sampling with randomized quasi-Monte Carlo*. SIAM Journal on Numerical Analysis, 61(2):10.1137/22M1510121.

Mon, Jul 28 15:30–17:30

Karina Koval*Heidelberg University*

karina.koval@iwr.uni-heidelberg.de

TiangangCui, RolandHerzog, RobertScheichl

Coauthor(s): Recent advances in optimization under uncertainty

In this talk, we present a novel approach for sequential optimal experimental design (sOED) for Bayesian inverse problems governed by expensive forward models with large-dimensional unknown parameters. Our goal is to design experiments that maximize the expected information gain (EIG) from prior to posterior, a task that is computationally challenging. This task becomes more complex in sOED, where we must approximate the incremental expected information gain (iEIG) multiple times in distinct stages, often dealing with intractable prior

and posterior distributions. To address this, we propose a derivative-based upper bound for iEIG that guides experimental design and enables parameter dimension reduction through likelihood-informed subspaces. By combining this approach with transport map surrogates for the sequence of posteriors, we develop a unified framework for parameter dimension-reduced sOED. We demonstrate the effectiveness of our approach with numerical examples inspired by groundwater flow and photoacoustic imaging.

Mon, Jul 28 15:30–17:30

Randomized quasi-Monte Carlo methods for risk-averse stochastic optimization

Johannes Milz

H. Milton Stewart School of Industrial and Systems Engineering, Georgia Institute of Technology

`johannes.milz@isye.gatech.edu`

Coauthor(s): Olena Melnikov

Special session: Recent advances in optimization under uncertainty p.38

We establish epigraphical and uniform laws of large numbers for sample-based approximations of law invariant risk functionals. These sample-based approximation schemes include Monte Carlo (MC) and certain randomized quasi-Monte Carlo integration (RQMC) methods, such as scrambled net integration. Our results can be applied to the approximation of risk-averse stochastic programs and risk-averse stochastic variational inequalities. Our numerical simulations empirically demonstrate that RQMC approaches based on scrambled Sobol' sequences can yield smaller bias and root mean square error than MC methods for risk-averse optimization.

Mon, Jul 28 15:30–17:30

Improving Efficiency of Sampling-based Motion Planning via Message-Passing Monte Carlo

Makram Chahine

CSAIL, Massachusetts Institute of Technology

chahine@mit.edu

Coauthor(s): T. Konstantin Rusch, Zach J. Patterson, and Daniela Rus

Sampling-based motion planning methods, while effective in high-dimensional spaces, often suffer from inefficiencies due to irregular sampling distributions, leading to suboptimal exploration of the configuration space. In this talk, we present an approach that enhances the efficiency of these methods by utilizing low-discrepancy distributions generated through Message-Passing Monte Carlo (MPMC). MPMC leverages Graph Neural Networks (GNNs) to generate point sets that uniformly cover the space, with uniformity assessed using the \mathcal{L}_p -discrepancy measure, which quantifies the irregularity of sample distributions. By improving the uniformity of the point sets, our approach significantly reduces computational overhead and the number of samples required for solving motion planning problems. Experimental results demonstrate that our method outperforms traditional sampling techniques in terms of planning efficiency.

Mon, Jul 28 15:30–17:30

Minimizing the Stein Discrepancy

Nathan Kirk

Illinois Institute of Technology

nkirk@iit.edu

Coauthor(s): Computational Methods for Low-discrepancy Sampling and Applications

Approximating a probability distribution using a discrete set of points is a fundamental task in modern scientific computation, with applications in uncertainty quantification. Points whose empirical distribution is close to the true distribution are called low-discrepancy. We discuss recent advances in this area, including the use of Stein discrepancies and various optimization techniques. In particular, we introduce Stein-Message-Passing Monte Carlo (Stein-MPMC) [1], an extension of the original Message-Passing Monte Carlo model and the first machine-learning algorithm for generating low-discrepancy (space-filling) point sets. Additionally, we present a generalized Subset Selection algorithm [2], a much simpler yet highly effective optimization method.

- [1] N. Kirk, T. K. Rusch, J. Zech, D. Rus, *Low Stein Discrepancy via Message-Passing Monte Carlo*, Preprint (2025)

- [2] D. Chen, F. Clément, C. Doerr, N. Kirk, L. Paquette, *Optimizing Kernel Discrepancies via Subset Selection*, Preprint (2025)

Mon, Jul 28 15:30–17:30

Gregory Seljak

Université de Montréal

gregory.de.salaberry.seljak@umontreal.ca

Pierre L'Ecuyer, Christiane Lemieux

Coauthor(s): Computational Methods for Low-discrepancy Sampling and Applications

Randomized quasi-Monte Carlo (RQMC) traditionally takes a low-discrepancy (QMC) point set, makes r independent randomizations of it to obtain r replicates of an unbiased RQMC estimator, then computes the average and variance of these r estimates to obtain a final estimate and perhaps a confidence interval [4]. Some methods construct the points by optimizing refined figures-of-merit adapted to the considered integrand and apply minimal randomization such as a random (digital) shift. Other methods randomize the parameters of the QMC point sets more extensively (e.g., the generating vectors or matrices). The second kind of method is easier to apply because it requires much less knowledge of the integrand, but bad parameter values may be drawn once in a while, leading to (rare) RQMC replicates having a large conditional variance that produce bad outliers. To reduce the impact of such outliers, one approach studied recently is to use the median of the r replicates instead of the mean as a final estimator [2, 3, 5, 6]. Other types of robust estimators could also be used in place of the median [1]. In this talk, we report extensive experiments that compare the mean square errors and convergence of various estimators (the mean, the median, and other robust estimators) defined in terms of r RQMC replicates. We also discuss the computation of confidence intervals for the mean when using such estimators.

- [1] E. Gobet, M. Lerasle, and D. Métivier. Accelerated convergence of error quantiles using robust randomized quasi Monte Carlo methods. <https://hal.science/hal-03631879>, 2024.
- [2] T. Goda and P. L'Ecuyer. Construction-free median quasi-Monte Carlo rules for function spaces with unspecified smoothness and general weights. *SIAM Journal on Scientific Computing*, 44(4):A2765–A2788, 2022.
- [3] T. Goda, K. Suzuki, and M. Matsumoto. A universal median quasi-Monte Carlo integration. *SIAM Journal on Numerical Analysis*, 62(1):533–566, 2024.
- [4] P. L'Ecuyer, M. Nakayama, A. B. Owen, and B. Tuffin. Confidence intervals for randomized quasi-Monte Carlo estimators. In *Proceedings of the 2023 Winter Simulation Conference*, pages 445–456. IEEE Press, 2023.

- [5] Z. Pan and A. B. Owen. Super-polynomial accuracy of one dimensional randomized nets using the median of means. *Mathematics of Computation*, 92(340):805–837, 2023.
- [6] Z. Pan and A. B. Owen. Super-polynomial accuracy of multidimensional randomized nets using the median of means. *Mathematics of Computation*, 93(349):2265–2289, 2024.

Mon, Jul 28 15:30–17:30

Searching Permutations for Constructing Low-Discrepancy Point Sets and Investigating the Kritzing Sequence

François Clément

Department of Mathematics, University of Washington
 fclement@uw.edu

Coauthor(s): Carola Doerr, Kathrin Klamroth, Luís Paquete

This talk focuses on two different approaches for the construction of low-discrepancy sets that are quite different from traditional approaches, yet yield excellent empirical results in two dimensions. The first of these, which will be the main focus of my talk, is based on selecting the relative position of the different points we wish to place, before using non-linear programming methods to obtain a point set with extremely low star discrepancy. In [1], we showed that this method consistently outperformed all other existing techniques. It is however subject to computational limits: finding good permutation choices, with or without optimization, is the next key step in improving our understanding of low-discrepancy structures.

In the second part of the talk, I will quickly highlight some extended numerical experiments on the sequence introduced by Kritzing in [2], showing that despite the lack of theoretical results proving that it is a low-discrepancy sequence, it performs at least as well as known sequences in one dimension, despite being constructed greedily.

- [1] F. Clément, C. Doerr, K. Klamroth, L. Paquete (2024). *Transforming the Challenge of Constructing Low-Discrepancy Point Sets into a Permutation Selection Problem.*, to appear, arxiv: <https://arxiv.org/abs/2407.11533>.
- [2] R. Kritzing (2022). *Uniformly Distributed Sequence generated by a greedy minimization of the L_2 discrepancy.*, Moscow Journal of Combinatorics and Number Theory, **11**(2), 215–236.

Tue, Jul 29 10:30–12:30

Wasserstein Convergence of Score-based Generative Models under Semiconvexity and Discontinuous Gradients*Sotirios Sabanis*

University of Edinburgh & National Technical University of Athens & Archimedes/Athena Research Centre

`s.sabanis@ed.ac.uk`

Coauthor(s): Stefano Bruno

Special session: Stochastic Computation and Complexity p.41

Score-based Generative Models (SGMs) approximate a data distribution by perturbing it with Gaussian noise and subsequently denoising it via a learned reverse diffusion process. These models excel at modeling complex data distributions and generating diverse samples, achieving state-of-the-art performance across domains such as computer vision, audio generation, reinforcement learning, and computational biology. Despite their empirical success, existing Wasserstein-2 convergence analysis typically assume strong regularity conditions—such as smoothness or strict log-concavity of the data distribution—that are rarely satisfied in practice.

In this work, we establish the first non-asymptotic Wasserstein-2 convergence guarantees for SGMs targeting semiconvex distributions with potentially discontinuous gradients. Our upper bounds are explicit and sharp in key parameters, achieving optimal dependence of $O(\sqrt{d})$ on the data dimension d and convergence rate of order one. The framework accommodates a wide class of practically relevant distributions, including symmetric modified half-normal distributions, Gaussian mixtures, double-well potentials, and elastic net potentials. By leveraging semiconvexity without requiring smoothness assumptions on the potential such as differentiability, our results substantially broaden the theoretical foundations of SGMs, bridging the gap between empirical success and rigorous guarantees in non-smooth, complex data regimes.

- [1] Bruno, Stefano & Sabanis, Sotirios (2025). *Wasserstein Convergence of Score-based Generative Models under Semiconvexity and Discontinuous Gradients*. ArXiv.

Tue, Jul 29 10:30–12:30

Ayoub Belhadji*Massachusetts Institute of Technology*`abelhadj@mit.edu`

DanielSharp, YoussefMarzouk

Coauthor(s): Next-generation optimal experimental design: theory, scalability, and real world impact: Part I

Approximating a probability distribution using a set of particles is a fundamental problem in machine learning and statistics, with applications including quantization and optimal design. Formally, we seek a finite weighted mixture of Dirac measures that best approximates the target distribution. While much existing work relies on the Wasserstein distance to quantify approximation errors, maximum mean discrepancy (MMD) has received comparatively less attention, especially when allowing for variable particle weights. We study the quantization problem from the perspective of minimizing MMD via gradient flow in the Wasserstein–Fisher–Rao (WFR) geometry. This gradient flow yields an ODE system from which we further derive a fixed-point algorithm called *mean shift interacting particles* (MSIP). We show that MSIP extends the non-interacting mean shift algorithm, widely used for identifying modes in kernel density estimates. Moreover, we show that MSIP can be interpreted as preconditioned gradient descent, and that it acts as a relaxation of Lloyd’s algorithm for clustering. Our numerical experiments demonstrate that MSIP and the WFR ODEs outperform other algorithms for quantization of multi-modal and high-dimensional targets.

Tue, Jul 29 10:30–12:30

A recursive Monte Carlo approach to optimal Bayesian experimental design

Adrien Corenflos

Department of Statistics, University of Warwick

`adrien.corenflos@warwick.ac.uk`

Coauthor(s): Hany Abdulsamad, Sahel Iqbal, Sara Pérez-Vieites, Simo Särkkä

Special session: Next-generation optimal experimental design: theory, scalability, and real world impact: Part I p.42

Bayesian experimental design is concerned with designing experiments that maximize information on a latent parameter of interest. This can be formally understood as minimizing the *expected* entropy over the parameter, given the input, the expectation being taken over the data. Solving this problem is intractable *as is*, and several surrogate loss functions have been proposed to learn policies that, when deployed in nature, help inference by sampling more informative data. A drawback of most of these, however, is that they introduce a substantial amount of bias, or otherwise exhibit a high variance. In this talk, we will introduce another surrogate formulation of optimal Bayesian design as a risk-sensitive policy optimization, compatible with non-exchangeable models. Under this formulation, minimizing the entropy of the posterior can be understood as sampling from a posterior distribution over the (random) designs. We will then discuss two nested sequential Monte Carlo algorithms [1,2] to infer these optimal designs, and discuss how to embed them within a particle Markov chain Monte Carlo framework to perform gradient-based policy learning. We will discuss the respective advantages and drawbacks of both algorithms as well as those of alternative methods.

- [1] Iqbal, S., Corenflos, A., Särkka, S., & Abdulsamad, H. (2024). *Nesting Particle Filters for Experimental Design in Dynamical Systems*. In Forty-first International Conference on Machine Learning (ICML).
- [2] Iqbal, S., Abdulsamad, H., Pérez-Vieites, S., Särkka, S., & Corenflos, A. (2024). *Recursive nested filtering for efficient amortized Bayesian experimental design*. In NeurIPS 2024 Workshop on Bayesian Decision-making and Uncertainty.

Tue, Jul 29 10:30–12:30

Parallel computations for Metropolis Markov chains Based on Picard maps

Sebastiano Grazzi

Department of Decision Sciences and BIDSA, Bocconi University, Via Roentgen, 1, 20136, Milan, Italy

`sebastiano.grazzi@unibocconi.it`

Coauthor(s): Giacomo Zanella

Special session: Heavy-tailed Sampling p.44

We develop parallel algorithms for simulating zeroth-order Metropolis Markov chains based on the Picard map. For Random Walk Metropolis Markov chains targeting log-concave distributions π on \mathbb{R}^d , our algorithm generates samples close to π in $\mathcal{O}(\sqrt{d})$ iterations with $\mathcal{O}(\sqrt{d})$ parallel processors, therefore speeding-up the convergence of the corresponding sequential implementation by a factor \sqrt{d} . Furthermore, a modification of our algorithm generates samples from an approximate measure $\tilde{\pi}_\epsilon$ in $\mathcal{O}(1)$ iterations and $\mathcal{O}(d)$ parallel processors. In this talk I will present the methodology, the analysis and numerical simulations. Our algorithms are straightforward to implement and may constitute a useful tool for practitioners seeking to sample from a prescribed distribution π using only point-wise evaluations proportional to π .

Tue, Jul 29 10:30–12:30

Enhancing Gaussian Process Surrogates for Optimization and Posterior Approximation via Random Exploration

Hwanwoo Kim

Duke University

`hwanwoo.kim@duke.edu`

Coauthor(s): Daniel Sanz-Alonso

Special session: Frontiers in (Quasi-)Monte Carlo and Markov Chain Monte Carlo Methods
p.46

In this talk, we propose novel noise-free Bayesian optimization strategies that rely on a random exploration step to enhance the accuracy of Gaussian process surrogate models. The new algorithms retain the ease of implementation of the classical GP-UCB algorithm, but the additional random exploration step accelerates their convergence, nearly achieving the optimal convergence rate. Furthermore, to facilitate Bayesian inference with an intractable likelihood, we propose to utilize the optimization iterates as design points to build a Gaussian process surrogate model for the unnormalized log-posterior density. We show that the Hellinger distance between the true and the approximate posterior distributions decays at a near-optimal rate. We demonstrate the effectiveness of our algorithms in benchmark non-convex test functions for optimization, and in a black-box engineering design problem. We also showcase the effectiveness of our posterior approximation approach in Bayesian inference for parameters of dynamical systems.

Tue, Jul 29 15:30–17:30

Optimal strong approximation of SDEs with Hölder continuous drift coefficient

Larisa Yaroslavtseva

University of Graz

larisa.yaroslavtseva@uni-graz.at

Coauthor(s): Simon Ellinger and Thomas Müller-Gronbach

We study strong approximation of the solution of a scalar stochastic differential equation (SDE)

$$\begin{aligned} dX_t &= \mu(X_t) dt + dW_t, \quad t \in [0, 1], \\ X_0 &= x_0 \end{aligned} \tag{5.1}$$

at the final time point 1 in the case that the drift coefficient μ is α -Hölder continuous with $\alpha \in (0, 1]$. Recently, it was shown in [1] that for such SDEs the equidistant Euler approximation achieves an L^p -error rate of at least $(1 + \alpha)/2$, up to an arbitrary small ε , in terms of the number of evaluations of the driving Brownian motion W . In this talk we present a matching lower error bound. More precisely, we show that the L^p -error rate $(1 + \alpha)/2$ can not be improved in general by no numerical method based on finitely many evaluations of W at fixed time points. For the proof of this result we choose μ to be the Weierstrass function and we employ the coupling of noise technique recently introduced in [2].

- [1] Butkovsky, O., Dareiotis, K., & Gerencsér, M. (2021). Approximation of SDEs: a stochastic sewing approach. *Probab. Theory Related Fields*, **181**(4), 975–1034
- [2] Müller-Gronbach, T. & Yaroslavtseva, L. (2023). Sharp lower error bounds for strong approximation of SDEs with discontinuous drift coefficient by coupling of noise. *Ann. Appl. Probab.* **33**, 902–935.

Tue, Jul 29 15:30–17:30

Malliavin differentiation of Lipschitz SDEs and BSDEs and an Application to Quadratic Forward-Backward SDEs

Alexander Steinicke

University of Leoben

`alexander.steinicke@unileoben.ac.at`

Coauthor(s): Hannah Geiss, Céline Labart, Adrien Richou

Special session: Stochastic Computation and Complexity p.47

Geiss and Zhou [1] showed that SDEs and BSDEs with Lipschitz generators admit Malliavin differentiability in the Brownian setting. We extend and apply this result in the Lévy case and present a differentiation formula for coefficients that are Lipschitz in the solution variable with respect to the Skorohod metric. The obtained formula then allows us to show the existence and uniqueness of solutions to a class of quadratic and superquadratic forward-backward SDE systems.

- [1] Geiss, S. and Zhou, X. (2024). *Coupling of Stochastic Differential Equations on the Wiener Space*. <https://arxiv.org/pdf/2412.10836>.

Tue, Jul 29 15:30–17:30

Tractability of L_2 -approximation and integration in weighted Hermite spaces of finite smoothness

Gunther Leobacher

University of Graz

`gunther.leobacher@uni-graz.at`

Coauthor(s): Adrian Ebert, Friedrich Pillichshammer

Special session: Stochastic Computation and Complexity p.47

We consider integration and L_2 -approximation for functions over \mathbb{R}^s from weighted Hermite spaces as introduced in [1]. We study tractability of the integration and L_2 -approximation problem for the different Hermite spaces, which describes the growth rate of the information complexity when the error threshold ε tends to 0 and the problem dimension s grows to infinity. Our main results are characterizations of tractability in terms of the involved weights,

which model the importance of the successive coordinate directions for functions from the weighted Hermite spaces.

- [1] Ch. Irrgeher and G. Leobacher. High-dimensional integration on the \mathbb{R}^d , weighted Hermite spaces, and orthogonal transforms. *J. Complexity* 31: 174–205, 2015.

Tue, Jul 29 15:30–17:30

Bayesian Experimental Design (BED) is a powerful tool to reduce the cost of running a sequence of experiments. When based on the Expected Information Gain (EIG), design optimization corresponds to the maximization of some intractable expected contrast between prior and posterior distributions. Scaling this maximization to high dimensional and complex settings has been an issue due to BED inherent computational complexity. In this work, we introduce a pooled posterior distribution with cost-effective sampling properties and provide a tractable access to the EIG contrast maximization via a new EIG gradient expression. Diffusion-based samplers are used to compute the dynamics of the pooled posterior and ideas from bi-level optimization are leveraged to derive an efficient joint sampling-optimization loop. The resulting efficiency gain allows to extend BOED to the well-tested generative capabilities of diffusion models. By incorporating generative models into the BOED framework, we expand its scope and its use in scenarios that were previously impractical. Numerical experiments and comparison with state-of-the-art methods show the potential of the approach. As a practical application, we showcase how our method accelerates Magnetic Resonance Imaging (MRI) acquisition times while preserving image quality. This presentation will also detail how Diffuse, a new modifiable Python package for diffusion models facilitates composability and research in diffusion models through its simple and intuitive API, allowing researchers to easily integrate and experiment with various model components.

Tue, Jul 29 15:30–17:30

Goal Oriented Sensor Placement for Infinite-Dimensional Bayesian Inverse Problems*Alen Alexanderian*North Carolina State University
alexanderian@ncsu.edu

Coauthor(s): Next-generation optimal experimental design: theory, scalability, and real world impact

We consider optimal experimental design (OED) for infinite-dimensional Bayesian inverse problems governed by partial differential equations with infinite-dimensional inversion parameters. Specifically, we focus on the case where we seek sensor placements that minimize the uncertainty in a prediction or goal functional. To address this, we propose a goal-oriented OED (gOED) approach that uses a quadratic approximation of the parameter-to-prediction mapping to obtain a measure of posterior uncertainty in the prediction quantity of interest (QoI). We focus on linear inverse problems in which the prediction is a nonlinear functional of the inversion parameters. We seek to find sensor placements that result in minimized posterior variance of the prediction QoI. In this context, and under the assumption of Gaussian prior and noise models, we derive a closed-form expression for the gOED criterion. We also discuss efficient and accurate computational approaches for computing the gOED objective and its optimization. We illustrate the proposed approach in model inverse problems governed by an advection-diffusion equation.

Tue, Jul 29 15:30–17:30

Robust Bayesian Optimal Experimental Design under Model Misspecification*Tommie A. Catanach*Sandia National Laboratories
tacatan@sandia.gov

Coauthor(s): Next-generation optimal experimental design: theory, scalability, and real world impact: Part II

Bayesian Optimal Experimental Design (BOED) has become a powerful tool for improving uncertainty quantification by strategically guiding data collection. However, the reliability of BOED depends critically on the validity of its underlying assumptions and the possibility of model discrepancy. In practice, the chosen data acquisition strategy may inadvertently reinforce prior assumptions—overlooking data that could challenge them—or rely on low-fidelity models whose error is not well characterized, leading to biased inferences. These biases can be particularly severe because BOED often targets extreme parameter regions as the most “informative,” potentially magnifying the impact of model error.

In this talk, we present a new information criterion, Expected Generalized Information Gain (EGIG)[1], that explicitly accounts for model discrepancy in BOED. EGIG augments standard Expected Information Gain by balancing the trade-off between experiment performance (i.e., how much information is gained) and robustness (i.e., how susceptible the design is to model misspecification). Concretely, EGIG measures how poorly inference under an incorrect model might perform, compared to a more appropriate model for the experiment. We will discuss the theoretical underpinnings of EGIG, as well as nested Monte Carlo algorithms for incorporating it into BOED for nonlinear inference problems. These methods handle both quantifiable discrepancies (e.g., low-fidelity vs. high-fidelity models) and unknown discrepancies represented by a distribution of potential errors, thereby enhancing the robustness and reliability of BOED in real-world settings.

SNL is managed and operated by NTESS under DOE NNSA contract DE-NA0003525.

- [1] Catanach, T. A., & Das, N. (2023). *Metrics for bayesian optimal experiment design under model misspecification*. In 2023 62nd IEEE Conference on Decision and Control (CDC) (pp. 7707-7714). IEEE.

Tue, Jul 29 15:30–17:30

Optimal Pilot Sampling for Multi-fidelity Monte Carlo Methods

Xun Huan

University of Michigan, Department of Mechanical Engineering
xhuan@umich.edu

Coauthor(s): Thomas Coons, Aniket Jivani

Bayesian optimal experimental design (OED) aims to maximize an expected utility, often chosen to be the expected information gain (EIG), over a given design space. Estimating EIG typically relies on Monte Carlo methods, which requires repeated evaluations of a computational model simulating the experimental process. However, when the model is expensive to evaluate, standard Monte Carlo becomes impractical.

Multi-fidelity variants of Monte Carlo, such as Approximate Control Variate (ACV) estimators, can significantly expedite such estimations by leveraging an ensemble of low-fidelity models that approximate the high-fidelity model with varying degrees of accuracy and cost. To apply these techniques in an error-optimal manner, the covariance matrix across model outputs must be estimated from independent pilot model evaluations. This step incurs a significant but often overlooked computational cost. Furthermore, the optimal allocation of computational resources between covariance estimation and ACV estimation remains an open problem. Existing approaches fail to accommodate optimal estimators and may not be accurate with small pilot sample sizes.

In this work, we introduce a novel framework for dynamically allocating resources between these two tasks. Our method employs Bayesian inference to quantify uncertainty in the

covariance matrix and derives an adaptive expected loss metric to determine when to terminate pilot sampling. We demonstrate and analyze our framework through a benchmark nonlinear OED problem.

Tue, Jul 29 15:30–17:30

Asymptotic robustness of smooth functions of rare-event estimators

Bruno Tuffin

Inria

`bruno.tuffin@inria.fr`

Coauthor(s): Marvin K. Nakayama

Special session: Advances in Rare Events Simulation p.50

In many rare-event simulation problems, an estimand is expressed as a smooth function of several quantities, each estimated by simulation but not necessarily all of their estimators are critically influenced by the rarity of the event of interest. An example arises in the estimation of the mean time to failure of a regenerative system, usually expressed as the ratio of two quantities to be estimated, the denominator being the only one entailing a rare event in a highly reliable context.

In general, there has been to our knowledge no work investigating the efficiency of estimating $\alpha = g(\boldsymbol{\theta})$ for some known smooth function $g : \mathbb{R}^d \rightarrow \mathbb{R}$ and where $\boldsymbol{\theta} = (\theta_1, \theta_2, \dots, \theta_d) \in \mathbb{R}^d$ is a vector of unknown parameters, for some $d \geq 1$, each estimated by simulation.

We will provide during the talk conditions under which having efficient estimators of each individual mean leads to an efficient estimator of the function of the means. Our conditions are described for several asymptotic robustness properties: logarithmic efficiency, bounded relative error and vanishing relative error. We illustrate this setting through several examples, and numerical results complement the theory.

- [1] Nakayama, Marvin K. and Bruno Tuffin. Efficiency of Estimating Functions of Means in Rare-Event Contexts. In the *Proceedings of the 2023 Winter Simulation Conference*, San Antonio, TX, USA, December 2023.

Tue, Jul 29 15:30–17:30

Estimating rare event probabilities associated with McKean–Vlasov SDEs*Shyam Mohan Subbiah Pillai*

RWTH Aachen University, Germany

subbiah@uq.rwth-aachen.de

Coauthor(s): Nadhir Ben Rached, Abdul-Lateef Haji-Ali, Raül Tempone

Special session: Advances in Rare Events Simulation p.50

McKean–Vlasov stochastic differential equations (MV-SDEs) arise as the mean-field limits of stochastic interacting particle systems, with applications in pedestrian dynamics, collective animal behavior, and financial market modelling. This work develops an efficient method for estimating rare event probabilities associated with MV-SDEs by combining multilevel Monte Carlo (MC) with importance sampling (IS). To apply a measure change for IS, we first reformulate the MV-SDE as a standard SDE by conditioning on its law, leading to the decoupled MV-SDE. We then formulate the problem of finding the optimal IS measure change as a stochastic optimal control problem that minimizes the variance of the MC estimator. The resulting partial differential equation is solved numerically to obtain the optimal IS measure change. Building on this IS scheme and the decoupling approach, we introduce a double loop Monte Carlo (DLMC) estimator. To further improve computational efficiency, we extend DLMC to a multilevel setting, reducing its computational complexity. To enhance variance convergence in the level differences for the discontinuous indicator function, we propose two key techniques: (1) numerical smoothing via one-dimensional integration over a carefully chosen variable and (2) an antithetic sampler to increase correlation between fine and coarse SDE paths. By integrating IS with efficient multilevel sampling, we develop the multilevel double loop Monte Carlo (MLDLMC) estimator. We demonstrate its effectiveness on the Kuramoto model from statistical physics, showing a reduction in computational complexity from $\mathcal{O}(\text{TOL}_r^{-4})$ using DLMC to $\mathcal{O}(\text{TOL}_r^{-3})$ using MLDLMC with IS, for estimating rare event probabilities up to a prescribed relative error tolerance TOL_r . This talk is primarily based on [1,2].

- [1] Ben Rached, N., Haji-Ali, A. L., Subbiah Pillai, S. M., & Tempone, R. (2024). Double-loop importance sampling for McKean–Vlasov stochastic differential equation. *Statistics and Computing*, 34(6), 197.
- [2] Ben Rached, N., Haji-Ali, A. L., Subbiah Pillai, S. M., & Tempone, R. (2025). Multilevel importance sampling for rare events associated with the McKean–Vlasov equation. *Statistics and Computing*, 35(1), 1.

Tue, Jul 29 15:30–17:30

Multiple Importance Sampling for Rare Event Simulation in Communication Systems

Víctor Elvira

University of Edinburgh

`victor.elvira@ed.ac.uk`

Coauthor(s): Igancio Santamaría

Estimating the symbol error rate (SER) in multiple-input multiple-output (MIMO) detectors involves computing an integral in a high-dimensional space, typically outside the Voronoi region of the transmitted symbol. Since a closed-form solution does not exist, the standard approach relies on crude Monte Carlo (MC) simulations, which become highly inefficient in rare-event regimes. In this talk, we propose a multiple importance sampling (MIS) method that provides unbiased SER estimates with significantly reduced variance compared to naive MC. The method constructs an adaptive mixture proposal distribution, where the number of components, their parameters, and weights are selected automatically. This flexibility ensures robustness across a range of scenarios, making the method efficient, easy to implement, and theoretically sound. Our simulations demonstrate that SERs as low as 10^{-8} can be accurately estimated with just 10^4 samples, achieving multiple orders of magnitude improvement over standard MC.

Tue, Jul 29 15:30–17:30

Quasi-uniform quasi-Monte Carlo digital nets

Takashi Goda

Graduate School of Engineering, The University of Tokyo

`goda@frcer.t.u-tokyo.ac.jp`

Coauthor(s): Josef Dick, Kosuke Suzuki

Special session: Frontiers in (Quasi-)Monte Carlo and Markov Chain Monte Carlo Methods
p.51

We investigate the quasi-uniformity properties of digital nets, a class of quasi-Monte Carlo point sets. Quasi-uniformity is a space-filling property that plays a crucial role in applications such as designs of computer experiments and radial basis function approximation. However, it remains open whether common low-discrepancy digital nets satisfy quasi-uniformity.

In this talk, we introduce the concept of *well-separated* point sets as a tool for constructing quasi-uniform low-discrepancy digital nets. We establish an algebraic criterion to determine whether a given digital net is well-separated and use this criterion to construct an explicit example of a two-dimensional digital net that is both low-discrepancy and quasi-uniform.

Furthermore, we present counterexamples of low-discrepancy digital nets that fail to achieve quasi-uniformity, highlighting the limitations of existing constructions.

- [1] T. Goda, The Sobol' sequence is not quasi-uniform in dimension 2. *Proc. Amer. Math. Soc.*, 152(8):3209–3213, 2024.
- [2] J. Dick, T. Goda, & K. Suzuki, On the quasi-uniformity properties of quasi-Monte Carlo digital nets and sequences. *arXiv preprint arXiv:2501.18226*, 2025.

Tue, Jul 29 15:30–17:30

Boosting the inference for generative models by (Quasi-)Monte Carlo resampling

Ziang Niu

University of Pennsylvania

ziangniu@wharton.upenn.edu

Coauthor(s): Bhaswar B. Bhattacharya, François-Xavier Briol, Anirban Chatterjee, Johanna Meier.

Special session: Frontiers in (Quasi-)Monte Carlo and Markov Chain Monte Carlo Methods
p.51

In the era of generative models, statistical inference based on classical likelihood for such models has faced a challenge. This is due to highly nontrivial model structures and thus computing the likelihood functions is almost impossible. Often time, information on these generative models can only be obtained by sampling from the models but the necessity of sampling can further pose a tradeoff between computational burden and statistical accuracy. In this talk, we propose a framework for statistical inference for generative models leveraging the techniques from (Quasi-)Monte Carlo. Despite the unavoidable balance of statistical accuracy and computation, both computational and statistical performances can be boosted by employing (Quasi-)Monte Carlo techniques. The presentation will be based on two papers.

- [1] A. Chatterjee, Z. Niu & B. Bhattacharya (2024). *A kernel-based conditional two-sample test using nearest neighbors (with applications to calibration, regression curves, and simulation-based inference)*. Preprint.
- [2] Z. Niu, J. Meier & F-X. Briol (2023). *Discrepancy-based inference for intractable generative models using Quasi-Monte Carlo*. *Electronic Journal of Statistics*.

Tue, Jul 29 15:30–17:30

A hit and run approach for sampling and analyzing ranking models*Chenyang Zhong*

Department of Statistics, Columbia University

cz2755@columbia.edu

Coauthor(s): Frontiers in (Quasi-)Monte Carlo and Markov Chain Monte Carlo Methods

The analysis of ranking data has gained much recent interest across various applications, including recommender systems, market research, and electoral studies. This talk focuses on the Mallows permutation model, a probabilistic model for ranking data introduced by C. L. Mallows. The Mallows model specifies a family of non-uniform probability distributions on permutations and is characterized by a distance metric on permutations. We focus on two popular choices: the L^1 (Spearman's footrule) and L^2 (Spearman's rank correlation) distances. Despite their widespread use in statistics and machine learning, Mallows models with these metrics present significant computational challenges due to the intractability of their normalizing constants.

Hit and run algorithms form a broad class of MCMC algorithms, including Swendsen-Wang and data augmentation. In this talk, I will first explain how to sample from Mallows models using hit and run algorithms. For both models, we establish $O(\log n)$ mixing time upper bounds, which provide the first theoretical guarantees for efficient sampling and enable computationally feasible Monte Carlo maximum likelihood estimation. Then, I will also discuss how the hit and run algorithms can be utilized to prove theorems about probabilistic properties of the Mallows models.

Wed, Jul 30 10:30–12:30

On the quantum complexity of parametric integration in Sobolev spaces*Stefan Heinrich*

heinrich@informatik.uni-kl.de

Stochasticcomputationandcomplexity

We consider the following problem of parametric integration in Sobolev spaces. We seek to approximate

$$S : W_p^r(D) \rightarrow L_q(D_1), \quad (Sf)(s) = \int_{D_2} f(s, t) dt \quad (s \in D_1),$$

where

$$D = [0, 1]^d = D_1 \times D_2, \quad D_1 = [0, 1]^{d_1}, \quad D_2 = [0, 1]^{d_2},$$

$$1 \leq p, q \leq \infty, \quad d, d_1, d_2, r \in \mathbf{N}, \quad d = d_1 + d_2, \quad \frac{r}{d_1} > \left(\frac{1}{p} - \frac{1}{q} \right)_+.$$

We study the complexity of this problem in the quantum setting of Information-Based Complexity [1]. Under the assumption that $W_p^r(D)$ is embedded into $C(D)$ (embedding condition) the case $p = q$ was solved by Wiegand [2]. Here we treat the case $p = q$ without embedding condition and the general case $p \neq q$ with or without the embedding condition. We also compare the rates with those in the (classical) randomized setting [3].

- [1] Heinrich, Stefan (2002). Quantum summation with an application to integration. *Journal of Complexity* 18, 1–50.
- [2] Wiegand, Carsten (2006). *Optimal Monte Carlo and Quantum Algorithms for Parametric Integration*. Shaker Verlag.
- [3] Heinrich, Stefan (2024). Randomized complexity of parametric integration and the role of adaption II. Sobolev spaces. *Journal of Complexity* 82, 101823.

Wed, Jul 30 10:30–12:30

Quantum Integration in Tensor Product Besov Spaces

Bernd Käßemodel

Faculty of Mathematics, Technische Universität Chemnitz

`bernd.kaessemodel@mathematik.tu-chemnitz.de`

Coauthor(s): Tino Ullrich

Special session: Stochastic Computation and Complexity p.52

We begin with a brief introduction to the basic concepts of quantum computing and quantum information-based complexity for multivariate integration and approximation problems in various smoothness classes. We then discuss characterizations of functions in tensor product Besov spaces (mixed smoothness) using the tensorized Faber-Cieselski basis with coefficients based on mixed iterated differences. Relying on such a decomposition we develop a quantum algorithm to establish bounds for the worst case quantum integration error for this function class.

Wed, Jul 30 10:30–12:30

Respecting the boundaries: Space-filling designs for surrogate modeling with boundary information*Simon Mak*

Duke University

sm769@duke.edu

Coauthor(s): Yen-Chun Liu

Gaussian process (GP) surrogate models are widely used for emulating expensive computer simulators, and have led to important advances in science and engineering. One challenge with fitting such surrogates is the costly generation of training data, which can require thousands of CPU hours per run. Recent promising work has investigated the integration of known boundary information for surrogate modeling, which can greatly reduce its required training sample size and thus computational cost. There is, however, little work exploring the important question of how such experiments should be designed given boundary information. We propose here a new class of space-filling designs, called boundary maximin designs, for effective GP surrogates with boundary information. Our designs rely on a new space-filling criterion derived from the asymptotic D-optimal designs of the boundary GPs of Vernon et al. (2019) and Ding et al. (2019), which can incorporate a broad class of known boundaries, including axis-parallel and/or perpendicular boundaries. To account for effect sparsity given many input parameters, we further propose a new boundary maximum projection design that jointly factors in boundary information and ensures good projective properties. Numerical experiments and an application in particle physics demonstrate improved surrogate performance with the proposed boundary maximin designs over the state-of-the-art.

Wed, Jul 30 10:30–12:30

Factor Importance Ranking and Selection using Total Indices*Chaofan Huang*

Work done during C. Huang's Ph.D. studies at Georgia Institute of Technology

10billhuang01@gmail.com

Coauthor(s): V. Roshan Joseph

Factor importance measures the impact of each feature on output prediction accuracy. In this paper, we focus on the *intrinsic importance* proposed by Williamson et al. (2023), which defines the importance of a factor as the reduction in predictive potential when that factor is removed. To bypass the modeling step required by the existing estimator, we present the equivalence between predictiveness potential and total Sobol' indices from global sensitivity analysis, and introduce a novel model-free consistent estimator that can be directly computed from noisy data. Integrating with forward selection and backward elimination gives rise to

FIRST, Factor Importance Ranking and Selection using Total (Sobol') indices. Extensive simulations are provided to demonstrate the effectiveness of **FIRST** on regression and binary classification problems, and a clear advantage over the state-of-the-art methods.

Wed, Jul 30 10:30–12:30

Stacking designs: designing multifidelity computer experiments with target predictive accuracy

Chih-Li Sung

Michigan State University
sungchih@msu.edu

Coauthor(s): Yi Ji, Simon Mak, Wenjia Wang, Tao Tang

In an era where scientific experiments can be very costly, multi-fidelity emulators provide a useful tool for cost-efficient predictive scientific computing. For scientific applications, the experimenter is often limited by a tight computational budget, and thus wishes to (i) maximize predictive power of the multi-fidelity emulator via a careful design of experiments, and (ii) ensure this model achieves a desired error tolerance with some notion of confidence. Existing design methods, however, do not jointly tackle objectives (i) and (ii). We propose a novel stacking design approach that addresses both goals. A multi-level reproducing kernel Hilbert space (RKHS) interpolator is first introduced to build the emulator, under which our stacking design provides a sequential approach for designing multi-fidelity runs such that a desired prediction error of $\epsilon > 0$ is met under regularity assumptions. We then prove a novel cost complexity theorem that, under this multi-level interpolator, establishes a bound on the computation cost (for training data simulation) needed to achieve a prediction bound of ϵ . This result provides novel insights on conditions under which the proposed multi-fidelity approach improves upon a conventional RKHS interpolator which relies on a single fidelity level. Finally, we demonstrate the effectiveness of stacking designs in a suite of simulation experiments and an application to finite element analysis.

Wed, Jul 30 10:30–12:30

GIST: Gibbs self-tuning for locally adapting Hamiltonian Monte Carlo*Bob Carpenter*

Flatiron Institute

bcarpenter@flatironinstitute.org

I will introduce the Gibbs self-tuning (GIST) framework for automatically tuning Metropolis algorithms and apply it to locally adapting the number of steps, step size, and mass matrix in Hamiltonian Monte Carlo (HMC). After resampling momentum, each iteration of GIST Gibbs samples tuning parameters based on the current position and momentum. Like with HMC, the Metropolis step for the Hamiltonian proposal is adjusted for the Gibbs sampling.

I will demonstrate how randomized Hamiltonian Monte Carlo (HMC), multinomial HMC, the No-U-Turn Sampler (NUTS), and the Apogee-to-Apogee Sampler can be cast as GIST samplers that adapt the number of steps. I will then introduce an approach to tuning step size that can be naturally combined with NUTS and demonstrate its effectiveness empirically on both multivariate normal and multiscale distributions with varying curvature.

I will sketch an approach to local mass matrix adaptation, demonstrate how it works for log concave distributions, then outline the problems remaining for efficiency and generalizability to other distributions.

Wed, Jul 30 10:30–12:30

Acceleration of the No-U-Turn Sampler*Nawaf Bou-Rabee*

Rutgers University

nawaf.bourabee@rutgers.edu

The No-U-Turn Sampler (NUTS) is a state-of-the-art Markov chain Monte Carlo method widely used in Bayesian computation [7,8], yet its theoretical properties remain poorly understood. In this talk, I will present the first rigorous mixing time bounds for NUTS on a class of high-dimensional Gaussian targets with both high- and low-variance directions. Our analysis uncovers a striking phase transition: when initialized from the region of concentration, NUTS exhibits ballistic mixing in regimes dominated by high-variance directions, and diffusive mixing otherwise [1]. These results provide the first theoretical evidence that the U-turn mechanism can recover the acceleration of critically damped randomized Hamiltonian Monte Carlo [4,5,6]. Our analysis combines a sharp concentration result for the U-turn condition [1,2] with a recent coupling framework for localized mixing [3].

- [1] Bou-Rabee, Nawaf, & Oberdorster, Stefan (2025). *Acceleration of the No-U-turn Sampler*. Forthcoming.

- [2] Bou-Rabee, Nawaf, & Oberdorster, Stefan (2024). *Mixing of the No-U-Turn Sampler and the Geometry of Gaussian Concentration*. arXiv:2410.06978 [math.PR]
- [3] Bou-Rabee, Nawaf, & Oberdorster, Stefan (2024). *Mixing of Metropolis-Adjusted Markov Chains via Couplings: The High Acceptance Regime*. Electronic Journal of Probability. Vol. 29, No. 89, pages 1-27.
- [4] Lu, Jianfeng & Wang, Lihan (2022). *On explicit L^2 -convergence rate estimate for piecewise deterministic Markov processes in MCMC algorithms*. Annals of Applied Probability, Vol. 32, No. 2, pages 1333-1361.
- [5] Eberle, Andreas & L'orler, Francis (2024). *Non-reversible lifts of reversible diffusion processes and relaxation times*. Probability Theory and Related Fields.
- [6] Durmus, Alain; Gruffaz, Samuel; Kailas, Miika; Saksman, Eero, & Vihola, Matti (2023). *On the convergence of dynamic implementations of Hamiltonian Monte Carlo and no U-turn samplers*. arXiv:2307.03460 [stat.CO]
- [7] Hoffman, Matthew & Gelman, Andrew (2014). *The no-U-turn sampler: Adaptively setting path lengths in Hamiltonian Monte Carlo*. Journal of Machine Learning Research. Vol. 15, No. 1, pages 1593-1623.
- [8] Carpenter, Bob; Gelman, Andrew; Hoffman, Matthew; Lee, Daniel; Goodrich, Ben; Betancourt, Michael; Brubaker, Marcus; Guo, Jiqiang; Li, Peter, and Riddell, Allen (2016). *Stan: A Probabilistic Programming Language*. Journal of Statistical Software, Vol. 76, No. 1, pages 1-32.

Wed, Jul 30 10:30–12:30

AutoStep: Locally adaptive involutive MCMC

Trevor Campbell

University of British Columbia

`trevor@stat.ubc.ca`

Coauthor(s): Tiange Liu, Nikola Surjanovic, Miguel Biron-Lattes, Alexandre Bouchard-Côté

Special session: Advances in Adaptive Hamiltonian Monte Carlo p.55

Many common Markov chain Monte Carlo (MCMC) kernels can be formulated using a deterministic involutive proposal with a step size parameter. Selecting an appropriate step size is often a challenging task in practice; and for complex multiscale targets, there may not be one choice of step size that works well globally. In this talk I'll address this problem with a novel class of involutive MCMC methods—AutoStep MCMC—that selects an appropriate step size at each iteration adapted to the local geometry of the target distribution. I'll present theoretical results guaranteeing that under mild conditions AutoStep MCMC is π -invariant, irreducible, and aperiodic, and provides bounds on expected energy jump distance and cost per iteration. The talk will conclude with empirical results examining the robustness and efficacy of the proposed step size selection procedure.

Wed, Jul 30 10:30–12:30

ATLAS: Adapting Trajectory Lengths and Step-Size for Hamiltonian Monte Carlo*Chirag Modi*

New York University

modichirag@nyu.edu

Hamiltonian Monte-Carlo (HMC) and its auto-tuned variant, the No U-Turn Sampler (NUTS) can struggle to accurately sample distributions with complex geometries, e.g., varying curvature, due to their constant step size for leapfrog integration and fixed mass matrix. In this talk, I will present a strategy to locally adapt the step size parameter of HMC at every iteration by evaluating a low-rank approximation of the local Hessian and estimating its largest eigenvalue. I will then combine it with a strategy to similarly adapt the trajectory length by monitoring the no U-turn condition, resulting in an adaptive sampler, ATLAS: adapting trajectory length and step-size. I will further use a delayed rejection framework for making multiple proposals that improves the computational efficiency of ATLAS, and develop an approach for automatically tuning its hyperparameters during warmup. Finally, I will compare ATLAS with NUTS on a suite of synthetic and real world examples, and show that

- i) unlike NUTS, ATLAS is able to accurately sample difficult distributions with complex geometries, ii) it is computationally competitive to NUTS for simpler distributions, and iii) it is more robust to the tuning of hyperparameters.

Wed, Jul 30 14:00–16:00

A New Convergence Analysis of Two Stochastic Frank-Wolfe Algorithms*Shane G. Henderson*

Cornell University

sgh9@cornell.edu

Coauthor(s): Natthawut Boonsiriphatthanajaroen

Special session: Stochastic Optimization p.57

We study the convergence properties of the original and away-step Frank-Wolfe algorithms for linearly constrained stochastic optimization assuming the availability of unbiased objective function gradient estimates. The objective function is not restricted to a finite summation form, like in previous analyses tailored to machine-learning applications. To enable the use of concentration inequalities we assume either a uniform bound on the variance of gradient estimates or uniformly sub-Gaussian tails on gradient estimates. With one of these regularity assumptions along with sufficient sampling, we can ensure sufficiently accurate gradient estimates. We then use a Lyapunov argument to obtain the desired complexity bounds, relying on existing geometrical results for polytopes.

Wed, Jul 30 14:00–16:00

Monte Carlo Based Adaptive Sampling Approaches for Stochastic Optimization*Raghu Bollapragada*

The University of Texas at Austin

raghu.bollapragada@utexas.edu

Coauthor(s): Shagun Gupta

Special session: Stochastic Optimization p.57

Stochastic optimization problems arise in a wide range of applications, from acoustic/geophysical inversion to deep learning. The scale, computational cost, and difficulty of these models make classical optimization techniques impractical. To address these challenges, in this talk, we propose new stochastic optimization methods using Monte Carlo-based adaptive sampling approaches. These approaches adaptively control the accuracy in the stochastic approximations at each iteration of the optimization algorithm by controlling the sample sizes used in these approximations to achieve efficiency and scalability. Furthermore, these approaches are well-suited for distributed computing implementations. We show that these approaches achieve optimal theoretical global convergence and complexity results for strongly convex, general convex, and non-convex problems and illustrate our algorithm's performance on machine learning models.

Wed, Jul 30 14:00–16:00

Algorithmic Discrepancy Theory: An Overview*Haotian Jiang*

University of Chicago

jhtdavid@uchicago.edu

Recent Progress on Algorithmic Discrepancy Theory and Applications

Combinatorial discrepancy theory studies the following question: given a universe of elements $U = \{1, \dots, n\}$ and a collection $\mathcal{S} = \{S_1, \dots, S_m\}$ of subsets of U , how well can we partition U into two pieces, so that all sets in \mathcal{S} are split as evenly as possible. The study of this question has found extensive applications to many areas of mathematics, computer science, statistics, finance, etc.

The past decade has seen tremendous progress in designing efficient algorithms for this problem. These developments have led to many surprising applications in areas such as differential privacy, graph sparsification, approximation algorithms and rounding, kernel density estimation, randomized controlled trials, and quasi-Monte Carlo methods.

In this talk, I will briefly survey some recent algorithmic developments in this area.

Wed, Jul 30 14:00–16:00

Improving the Design of Randomized Experiments via Discrepancy Theory*Peng Zhang*

Rutgers University

pz149@rutgers.edu

Coauthor(s): Recent Progress on Algorithmic Discrepancy Theory and Applications

Randomized controlled trials (RCTs) or A/B tests are the “gold standard” for estimating the causal effects of new treatments. In a trial, we want to randomly assign experimental units into two groups so that certain unit-specific pre-treatment variables, called covariates, are balanced across different groups. Balancing covariates improves causal effect estimates if covariates correlate with treatment outcomes. Simultaneously, we want our assignment of the units to be robust or sufficiently random such that our estimate is not bad if covariates do not correlate with treatment outcomes. We will show a close connection between the design of RCTs and discrepancy theory and how recent advances in algorithmic discrepancy theory could improve the design of RCTs.

Wed, Jul 30 14:00–16:00

Online Factorization for Online Discrepancy Minimization*Aleksandar Nikolov*

University of Toronto

anikolov@cs.toronto.edu

Coauthor(s): Haohua Tang

A recent line of work, initiated by a paper of Bansal and Spencer [2], has made remarkable progress in developing online algorithms for combinatorial discrepancy minimization. In the online discrepancy minimization model, the algorithm receives a sequence of elements of some set system, or, more generally, a sequence of vectors, to color. The new element/vector must be colored immediately upon being received. We now have online algorithms that nearly match some important (offline) discrepancy bounds when the sequence of elements/vectors is stochastic or oblivious: examples include Spencer's theorem [2], and Banaszczyk's theorem [1,3]. In this work, we explore if the factorization method for discrepancy minimization [4] can also be adapted to the offline setting. We introduce a model of online factorization of matrices, and, as a case study, show how to factor online the incidence matrix of a collection of n halfspaces in d dimensions. As a result, we obtain an online algorithm to color an oblivious sequence of T points in d dimensions, so that the discrepancy with respect to a pre-specified collection of n halfspaces is on the order of $n^{\frac{1}{2}-\frac{1}{2d}}$ up to logarithmic terms.

- [1] Ryan Alweiss, Yang P. Liu, Mehtaab Sawhney: Discrepancy minimization via a self-balancing walk. STOC 2021: 14-20
- [2] Nikhil Bansal, Joel H. Spencer: On-line balancing of random inputs. Random Struct. Algorithms 57(4): 879-891 (2020)
- [3] Janardhan Kulkarni, Victor Reis, Thomas Rothvoss: Optimal Online Discrepancy Minimization. STOC 2024: 1832-1840
- [4] Jiri Matousek, Aleksandar Nikolov, Kunal Talwar, Factorization Norms and Hereditary Discrepancy, IMRN (3), 751-780, 2020.

Wed, Jul 30 14:00–16:00

WoS-NN: Collaborating Walk-on-Spheres with Machine Learning to Solve Elliptic PDEs*Silei Song*

Department of Computer Science, Florida State University

ss19cu@fsu.edu

Coauthor(s): Michael Mascagni, Arash Fahim

Special session: Monte Carlo Applications in High-performance Computing, Computer Graph-

ics, and Computational Science p.60

Solving elliptic partial differential equations (PDEs) is a fundamental step in various scientific and engineering studies. As a classic stochastic solver, the Walk on Spheres (WoS) method is a well-established and efficient algorithm that provides accurate local estimates for PDEs. However, limited by the curse of dimensionality, WoS may not offer sufficiently precise global estimations, which becomes more serious in high-dimensional scenarios. Recent developments in machine learning offer promising strategies to address this limitation. By integrating machine learning techniques with WoS and space discretization approaches, we developed a novel stochastic solver, WoS-NN. This new method solves elliptic problems with Dirichlet boundary conditions, facilitating precise and rapid global solutions and gradient approximations. A typical experimental result demonstrated that the proposed WoS-NN method provides accurate field estimations, reducing 76.32% errors while using only 8% of path samples compared to the conventional WoS method, which saves abundant computational time and resource consumption. WoS-NN can also be utilized as a fast and effective gradient estimator based on established implementations of the original WoS method. This new method reduced the impacts of the curse of dimensionality and can be widely applied to areas like geometry processing, bio-molecular modeling, financial mathematics, etc.

Thu, Jul 31 10:30–12:30

Exact discretization, tight frames and recovery via D -optimal designs

Felix Bartel

University of New South Wales

f.bartel@unsw.edu.au

Coauthor(s): Lutz Kämmerer, Kateryna Pozharska, Martin Schäfer, and Tino Ullrich

Special session: QMC and Applications Part I or II p.61

D -optimal designs originate in statistics literature as an approach for optimal experimental designs. In numerical analysis points and weights resulting from maximal determinants turned out to be useful for quadrature and interpolation. Also recently, two of the present authors and coauthors investigated a connection to the discretization problem for the uniform norm. Here we use this approach of maximizing the determinant of a certain Gramian matrix with respect to points and weights for the construction of tight frames and exact Marcinkiewicz-Zygmund inequalities in L_2 . We present a direct and constructive approach resulting in a discrete measure with at most $N \leq n^2 + 1$ atoms, which discretely and accurately subsamples the L_2 -norm of complex-valued functions contained in a given n -dimensional subspace. This approach can as well be used for the reconstruction of functions from general RKHS in L_2 where one only has access to the most important eigenfunctions. We verifiably and deterministically construct points and weights for a weighted least squares recovery procedure and pay in the rate of convergence compared to earlier optimal, however

probabilistic approaches. The general results apply to the d -sphere or multivariate trigonometric polynomials on T^d spectrally supported on arbitrary finite index sets $I \subset \mathbb{Z}^d$. They can be discretized using at most $|I|^2 - |I| + 1$ points and weights. Numerical experiments indicate the sharpness of this result. As a negative result we prove that, in general, it is not possible to control the number of points in a reconstructing lattice rule only in the cardinality $|I|$ without additional condition on the structure of I . We support our findings with numerical experiments.

Thu, Jul 31 10:30–12:30

High-dimensional density estimation on unbounded domain

Zhijian He

South China University of Technology

hezhi.jian@scut.edu.cn

Coauthor(s): Ziyang Ye, Haoyuan Tan, Xiaoqun Wang

Special session: QMC and Applications Parts I and II p.61

This talk will present a kernel-based method to approximate probability density functions of unbounded random variables taking values in high-dimensional spaces. Building upon the framework of Kazashi and Nobile [1], our estimator is a linear combination of kernel functions whose coefficients are determined a linear equation. We first transform the unbounded sample domain into a hyper cube and then use rank-1 lattice points as the interpolation nodes. We establish a rigorous error analysis for the mean integrated squared error (MISE) under an exponential decay condition. Under a suitable smoothness assumption, our method attains an MISE rate approaching $O(N^{-1})$ for N independent identically distributed observations. Numerical experiments validate our theoretical findings and demonstrate the superior performance of the proposed estimator compared to state-of-the-art alternatives.

- [1] Kazashi, Yoshihito, & Nobile, Fabio. (2023). Density estimation in RKHS with application to Korobov spaces in high dimensions, *SIAM Journal on Numerical Analysis*, **61**(2), 1080-1102.

Thu, Jul 31 10:30–12:30

 L_2 -approximation: using randomized lattice algorithms and QMC hyperinterpolation*Mou Cai*Graduate School of Engineering, The University of Tokyo
caimoumou@g.ecc.u-tokyo.ac.jp

Coauthor(s): Congpei An, Takashi Goda, Yoshihito Kazashi

Abstract

We propose a randomized lattice algorithm for approximating multivariate periodic functions over the d -dimensional unit cube from the weighted Korobov space with mixed smoothness $\alpha > 1/2$ and product weights $\gamma_1, \gamma_2, \dots \in [0, 1]$. This randomization involves drawing the number of points for function evaluations randomly, and selecting a good generating vector for rank-1 lattice points using the randomized component-by-component algorithm. We prove that our randomized algorithm achieves a worst-case root mean squared L_2 -approximation error of order $M^{-\alpha/2-1/8+\varepsilon}$ for an arbitrarily small $\varepsilon > 0$, where M denotes the maximum number of function evaluations, and that the error bound is independent of the dimension d if the weights satisfy $\sum_{j=1}^{\infty} \gamma_j^{1/\alpha} < \infty$. Our upper bound converges faster than a lower bound on the worst-case L_2 -approximation error for deterministic rank-1 lattice-based approximation proved by Byrenheid, K'ammerer, Ullrich, and Volkmer (2017). We also show a lower error bound of order $M^{-\alpha/2-1/2}$ for our randomized algorithm. Finally, we present a generalization of hyperinterpolation over the unit cube named Quasi-Monte Carlo (QMC) hyperinterpolation. This new approximation scheme can be integrated with the Lasso technique to enhance sparsity and denoising capabilities.

Thu, Jul 31 10:30–12:30

Application of QMC to Oncology*Frances Y. Kuo*UNSW Sydney, Australia
f.kuo@unsw.edu.au

Coauthor(s): Alexander D. Gilbert, Dirk Nuyens, Graham Pash, Ian H. Sloan, Karen E. Willkox

Special session: QMC and Applications Part I p.61

Tumor models largely focus on two key characteristics: infiltration of the tumor into the surrounding healthy tissue modelled by diffusion, and proliferation of the existing tumor modelled by logistic growth in tumor cellularity. Together with terms to model chemotherapy and radiotherapy treatments, these give rise to a nonlinear parabolic reaction-diffusion PDE

with random diffusion and proliferation coefficients. We show that QMC methods can be successful in computing quantities of interest arising from this tough application in oncology.

Thu, Jul 31 10:30–12:30

Convergence rates of kinetic Langevin dynamics with weakly confining potentials

Lihan Wang

Carnegie Mellon University

lihanw@andrew.cmu.edu

Coauthor(s): Giovanni Brigati, Gabriel Stoltz, Andi Q. Wang

We discuss the long-time convergence behavior of kinetic Langevin dynamics, and show how the growth of the potentials in space and velocity impact the convergence rates of the dynamics, via weighted and weak Poincaré inequalities. The analysis is inspired by the Armstrong-Mourrat variational framework for hypocoercivity, which combines a weighted Poincaré-Lions inequality in time-augmented state space and an L^2 energy estimate.

Thu, Jul 31 10:30–12:30

Randomized Splitting Methods and Stochastic Gradient Algorithms*Peter A. Whalley*

ETH Zürich, Switzerland

pwhalley@ethz.ch

Coauthor(s): Neil K. Chada, Benedict Leimkuhler, Daniel Paulin, Luke Shaw

Special session: Analysis of Langevin and Related Sampling Algorithms, Part I p.62

We examine the use of different randomisation policies for stochastic gradient algorithms. Conventionally, algorithms are combined with a specific stochastic gradient strategy, called Robbins-Monro. In this work, we study without replacement subsampling strategies and show convincingly that it leads to improved performance via: a) a proof of improved complexity guarantees for strongly convex, gradient Lipschitz objectives; b) an analytical demonstration of reduced bias on quadratic model problems; and c) empirical demonstration of reduced bias in numerical experiments. This is especially important since without replacement subsampling strategies are typically more efficient due to memory access and cache reasons.

- [1] Daniel Paulin*, Peter A. Whalley*, Neil K. Chada, & Ben Leimkuhler (2025). *Sampling from Bayesian Neural Network Posteriors with Symmetric Minibatch Splitting Langevin Dynamics*. The 28th International Conference on Artificial Intelligence and Statistics.
- [2] Luke Shaw, Peter A. Whalley (2025). *Random Reshuffling for Stochastic Gradient Langevin Dynamics*. ArXiv:2501.16055.

Thu, Jul 31 10:30–12:30

Delocalization of Bias in Unadjusted Hamiltonian Monte Carlo*Xiaoou Cheng*

New York University

chengxo@nyu.edu

Coauthor(s): Yifan Chen, Jonathan Niles-Weed, Jonathan Weare

Special session: Analysis of Langevin and Related Sampling Algorithms, Part I p.62

Hamiltonian Monte Carlo is a commonly used algorithm to sample high dimensional probability distributions. However, for strongly log-concave distributions, existing analyses of the unadjusted algorithm show that the number of iterations follows a power law in terms of the dimension d , to ensure convergence within a desired error in the W_2 metric. Also, because of the large bias, Hamiltonian Monte Carlo is often Metropolized to remove the bias effectively.

[1] suggests that for unadjusted Langevin algorithm, similar power law dimension scaling of convergence and bias in the W_2 metric can be misleading. There, for strongly log-concave distributions with certain sparse interactions, the *marginal* distribution of a small number of K variables can be well-approximated in the W_2 metric, with a small number of iterations proportional to K up to *logarithmic* terms in d . A novel W_{2,ℓ^∞} metric is used in analysis. We show that this *delocalization of bias* effect also exists in unadjusted Hamiltonian Monte Carlo with the leapfrog integrator, which suggests that Metropolization may not be necessary in this situation. A key observation is that the propagator of the leapfrog integrator is closely related to Chebyshev polynomials.

- [1] Chen, Y., Cheng, X., Niles-Weed, J., & Weare, J. (2024). Convergence of Unadjusted Langevin in High Dimensions: Delocalization of Bias. *arXiv preprint arxiv:2408.13115*.

Thu, Jul 31 10:30–12:30

Multilevel randomized quasi-Monte Carlo estimator for nested expectations

Raúl Tempone

King Abdullah University of Science and Technology/RWTH Aachen University
 raul.tempone@kaust.edu.sa

Coauthor(s): Arved Bartuska, André Gustavo Carlon, Luis Espath, Sebastian Krumscheid

Estimation methods for nested integrals face several challenges, including nonlinearities separating the integrals, boundary singularities, and the need for numerical discretization of the integrand. In this talk, we present an advanced multilevel randomized double-loop quasi-Monte Carlo estimator that addresses these challenges by combining hierarchical approximations with deterministic and randomized quasi-Monte Carlo (rQMC) methods. This estimator is tailored towards scenarios where the inner integrand requires discretization via the finite element method and the outer integrand exhibits singularities at the boundaries of the integration domain.

Applications from Bayesian experimental design, in particular, the expected information gain (EIG) of an experiment, necessitate a truncation scheme for observation noise to rigorously bound the estimation error. This truncation affects the computational cost only by a logarithmic factor. Numerical experiments demonstrate the predicted optimal cost of almost $\mathcal{O}(TOL^{-1-\gamma/\eta_w})$ where γ and η_w signify the cost and weak rate of finite element discretizations, respectively.

Thu, Jul 31 10:30–12:30

Stochastic gradient with least-squares control variates*Matteo Raviola*

École polytechnique fédérale de Lausanne

matteo.raviola@epfl.ch

Coauthor(s): Fabio Nobile, Nathan Schaeffer

The stochastic gradient (SG) method is a widely used approach for solving stochastic optimization problems, but its convergence is typically slow. Existing variance reduction techniques, such as SAGA [1], improve convergence by leveraging stored gradient information; however, they are restricted to settings where the objective functional is a finite sum, and their performance degrades when the number of terms in the sum is large. In this work, we propose a novel approach which also works when the objective is given by an expectation over random variables with a continuous probability distribution. Our method constructs a control variate by fitting a linear model to past gradient evaluations using weighted discrete least-squares, effectively reducing variance while preserving computational efficiency. We establish theoretical sublinear convergence guarantees and demonstrate the method's effectiveness through numerical experiments on random PDE-constrained optimization.

- [1] Defazio, A., Bach, F., & Lacoste-Julien, S. (2014). *SAGA: A fast incremental gradient method with support for non-strongly convex composite objectives*. Advances in neural information processing systems, 27.

Thu, Jul 31 10:30–12:30

A one-shot method for Bayesian optimal experimental design*Philipp A. Guth*

RICAM, Austrian Academy of Sciences

philipp.guth@ricam.oeaw.ac.at

Coauthor(s): Robert Gruhlke, Claudia Schillings

Special session: Nested expectations: models and estimators, Part II p.63

Bayesian optimal experimental design (BOED) problems often involve nested integrals, making their direct computation challenging. To address this, a one-shot optimization approach is proposed, which decouples the design parameters from the forward model during the optimization process. In addition, the solution of the forward model can be replaced by a surrogate that is trained during the one-shot optimization. This allows for the generation of computationally inexpensive samples. Efficient sampling strategies are particularly important in BOED, as they reduce the high computational cost of nested integration, ultimately making the optimization more tractable.

Thu, Jul 31 15:30–17:30

Quasi-uniform quasi-Monte Carlo lattice point sets*Kosuke Suzuki*

Yamagata University

kosuke-suzuki@sci.kj.yamagata-u.ac.jp

Coauthor(s): Josef Dick, Takashi Goda, Gerhard Larcher, Friedrich Pillichshammer

Special session: QMC and Applications p.64

The discrepancy of a point set quantifies how well the points are distributed, with low-discrepancy point sets demonstrating exceptional uniform distribution properties. Such sets are integral to quasi-Monte Carlo methods, which approximate integrals over the unit cube for integrands of bounded variation. In contrast, quasi-uniform point sets are characterized by optimal separation and covering radii, making them well-suited for applications such as radial basis function approximation. This paper explores the quasi-uniformity properties of quasi-Monte Carlo point sets constructed from lattices. Specifically, we analyze rank-1 lattice point sets, Fibonacci lattice point sets, Frolov point sets, and $(n\boldsymbol{\alpha})$ -sequences, providing insights into their potential for use in applications that require both low-discrepancy and quasi-uniform distribution. As an example, we show that the $(n\boldsymbol{\alpha})$ -sequence with $\alpha_j = 2^{j/(d+1)}$ for $j \in \{1, 2, \dots, d\}$ is quasi-uniform and has low-discrepancy.

Thu, Jul 31 15:30–17:30

QMC confidence intervals using quantiles of randomized nets*Zexin Pan*

Johann Radon Institute for Computational and Applied Mathematics

zexin.pan@oeaw.ac.at

The median of linearly scrambled digital net estimates has been shown to converge to the target integral value at nearly the optimal rate across various function spaces [1]. In this talk, we explore how quantiles of these estimates can be used to construct confidence intervals for the target integral. In particular, we demonstrate that as the sample size increases, the error distribution becomes increasingly symmetric, and we quantify the rate of this symmetrization for a class of smooth integrands.

- [1] Pan, Zexin. (2025). Automatic optimal-rate convergence of randomized nets using median-of-means. *Mathematics of Computation*, to appear.

Thu, Jul 31 15:30–17:30

Approximation of multivariate periodic functions*Dirk Nuyens*

KU Leuven, Belgium

dirk.nuyens@kuleuven.be

Coauthor(s): Laurence Wilkes

Special session: QMC and Applications p.64

We study approximation of multivariate periodic functions using n function values. We use generated sets as the sample points, first introduced in [1]. We prove existence and convergence of the almost optimal L_2 error and obtain similar bounds as for the least squares algorithm from [2] which uses unstructured points.

- [1] K'ammerer. Reconstructing multivariate trigonometric polynomials by sampling along generated sets. In Monte Carlo and Quasi-Monte Carlo Methods 2012 (Dick, Kuo, Peters, Sloan), pages 439–454, 2013.
- [2] Krieg, Ullrich. Function values are enough for L_2 approximation. *Foundations of Computational Mathematics*, 21(4):1141–1151, 2021.

Thu, Jul 31 15:30–17:30

Finite-Particle Convergence Rates for Stein Variational Gradient Descent*Krishnakumar Balasubramanian*

University of California, Davis

kbala@ucdavis.edu

We provide finite-particle convergence rates for the Stein Variational Gradient Descent (SVGD) algorithm in the Kernelized Stein Discrepancy (KSD) and Wasserstein-2 metrics. Our key insight is that the time derivative of the relative entropy between the joint density of N particle locations and the N -fold product target measure, starting from a regular initial distribution, splits into a dominant ‘negative part’ proportional to N times the expected KSD^2 and a smaller ‘positive part’. This observation leads to KSD rates of order $1/\sqrt{N}$, in both continuous and discrete time, providing a near optimal (in the sense of matching the corresponding i.i.d. rates) double exponential improvement over the recent result by [1]. Under mild assumptions on the kernel and potential, these bounds also grow polynomially in

the dimension d . By adding a bilinear component to the kernel, the above approach is used to further obtain Wasserstein-2 convergence in continuous time. For the case of ‘bilinear + Matérn’ kernels, we derive Wasserstein-2 rates that exhibit a curse-of-dimensionality similar to the i.i.d. setting. We also obtain marginal convergence and long-time propagation of chaos results for the time-averaged particle laws.

- [1] Shi, J., & Mackey, L. (2023). A finite-particle convergence rate for stein variational gradient descent. *Advances in Neural Information Processing Systems*, 36, 26831-26844.

Thu, Jul 31 15:30–17:30

Convergence of Unadjusted Langevin in High Dimensions: Delocalization of Bias

Yifan Chen

UCLA, Courant Institute

yifanc96@gmail.com

Coauthor(s): Xiaou Cheng, Jonathan Niles-Weed, Jonathan Weare

The unadjusted Langevin algorithm is commonly used to sample probability distributions in extremely high-dimensional settings. However, existing analyses of the algorithm for strongly log-concave distributions suggest that, as the dimension d of the problem increases, the number of iterations required to ensure convergence within a desired error in the W_2 metric scales in proportion to d or \sqrt{d} . In this work, we argue that, the behavior for a *small number* of variables can be significantly better: a number of iterations proportional to K , up to logarithmic terms in d , often suffices for the algorithm to converge to within a desired W_2 error for all K -marginals. We refer to this effect as *delocalization of bias*. We show that the delocalization effect does not hold universally and prove its validity for Gaussian distributions and strongly log-concave distributions with certain sparse/local interactions. Our analysis relies on a novel W_{2,ℓ^∞} metric to measure convergence. A key technical challenge we address is the lack of a one-step contraction property in this metric. Finally, we use asymptotic arguments to explore potential generalizations of the delocalization effect beyond the Gaussian and sparse/local interactions setting.

Thu, Jul 31 15:30–17:30

Molei Tao*Georgia Tech*

mtao@gatech.edu

KijungJeon, MichaelMuehlebach

Coauthor(s): Analysis of Langevin and Related Sampling Algorithms

Given an unnormalized density ρ and a constraint set Σ in \mathbb{R}^n , we aim at sampling from a constrained distribution $Z^{-1}\rho(x)I_{\Sigma}(x)dx$. While the case when Σ is convex has been extensively studied, *no* convexity is needed in this talk, in which case quantitative results are scarce. Our method admits multiple interpretations, but this talk will focus on a Langevin perspective, where overdamped Langevin dynamics is first modified, and then discretized so that a sampling algorithm can be constructed. The quantitative convergence of the continuous dynamics will be detailed, but if time permits, the performance of the time-discretization (i.e. the actual sampler) will also be discussed.

Thu, Jul 31 15:30–17:30

Accelerated Mixing of the No-U-turn Sampler*Stefan Oberdörster*

University of Bonn

oberdoerster@uni-bonn.de

Coauthor(s): Nawaf Bou-Rabee

Special session: Analysis of Langevin and Related Sampling Algorithms, Part II p.65

In recent years, we witnessed considerable progress on the quantitative mixing of Randomized Hamiltonian Monte Carlo via variational hypocoercivity and lifts. Under assumptions revolving around the concentration of measure phenomenon, it was shown that critically tuned Randomized Hamiltonian Monte Carlo achieves accelerated convergence to equilibrium, also known as the diffusive-to-ballistic speed-up. This acceleration is of great interest to the field of Markov chain Monte Carlo methods. To bridge the gap between theory and application, a natural question is: *Does the No-U-turn sampler, a widely used locally-adapted implementation of Randomized Hamiltonian Monte Carlo, achieve acceleration?* We will explore recent results towards this question based on a combination of concentration of measure and a novel framework for localized mixing via couplings.

Thu, Jul 31 15:30–17:30

Convergence of Φ -Divergence and Φ -Mutual Information Along Langevin Markov Chains*Siddharth Mitra*

Yale University

siddharth.mitra@yale.edu

Coauthor(s): Jiaming Liang, Andre Wibisono

The mixing time of a Markov chain determines when the marginal law of the Markov chain is close to the stationary distribution and can be studied in many statistical divergences such as KL divergence and chi-squared divergence, all the way to families of divergences such as Φ -divergences. However, the mixing time does not determine the dependency between samples along the Markov chain, which can be measured in terms of their mutual information, chi-squared mutual information, or more generally their Φ -mutual information. In this talk we study the mixing time of Langevin Markov chains in Φ -divergence and also study the Φ -mutual information between the iterates. The Markov chains we focus on are the Langevin Dynamics in continuous-time, and the Unadjusted Langevin Algorithm and Proximal Sampler in discrete-time and we show that for these Markov chains, the Φ -divergence and the Φ -mutual information decreases exponentially fast. Our proof technique is based on showing the Strong Data Processing Inequalities (SDPIs) hold along the Markov chains. To prove fast mixing of the Markov chains, we show the SDPIs hold for the stationary distribution. In contrast, to prove the contraction of Φ -mutual information, we need to show the SDPIs hold along the entire trajectories of the Markov chains; we prove this when the iterates along the Markov chains satisfy the corresponding Φ -Sobolev inequality.

Thu, Jul 31 15:30–17:30

Inference for Stochastic Gradient Descent with Infinite Variance*Jose Blanchet*

Stanford University

jose.blanchet@stanford.edu

Coauthor(s): Peter Glynn, Aleks Mijatovic, Wenhao Yang

Special session: Recent Advances in Stochastic Gradient Descent p.66

Stochastic gradient descent (SGD) with infinite variance gradients arises, perhaps surprisingly, quite often in applications. Even in settings involving “finite variance” in theory, infinite variance models appear to provide a better statistical fit over spatial and temporal scales of interest in applied settings. Motivated by this, we investigate a general methodology that enables the development of valid confidence regions for SGD with infinite variance. Along the way, we also obtain key results and properties for SGD with infinite variance, for example, asymptotic limits, optimal convergence rates, etc., which are counterparts of celebrated results known only in the finite variance case.

Thu, Jul 31 15:30–17:30

Stochastic Gradient Descent with Adaptive Data*Jing Dong*

Columbia University

jing.dong@gsb.columbia.edu

Coauthor(s): Ethan Che, Xin Tong

Special session: Recent Advances in Stochastic Gradient Descent p.66

Stochastic gradient descent (SGD) is a powerful optimization technique that is particularly useful in online learning scenarios. Its convergence analysis is relatively well understood under the assumption that the data samples are independent and identically distributed (iid). However, applying SGD to policy optimization problems in operations research involves a distinct challenge: the policy changes the environment and thereby affects the data used to update the policy. The adaptively generated data stream involves samples that are non-stationary, no longer independent from each other, and affected by previous decisions. The influence of previous decisions on the data generated introduces bias in the gradient estimate, which presents a potential source of instability for online learning not present in the iid case. In this paper, we introduce simple criteria for the adaptively generated data stream to guarantee the convergence of SGD. We show that the convergence speed of SGD with adaptive data is largely similar to the classical iid setting, as long as the mixing time of the policy-induced dynamics is factored in. Our Lyapunov-function analysis allows one to

translate existing stability analysis of stochastic systems studied in operations research into convergence rates for SGD, and we demonstrate this for queueing and inventory management problems. We also showcase how our result can be applied to study the sample complexity of an actor-critic policy gradient algorithm.

Fri, Aug 1 09:00–10:30

Filtered Markovian Projection: Dimensionality Reduction in Filtering for Stochastic Reaction Networks

Maksim Chupin

King Abdullah University of Science and Technology (KAUST)

`maksim.chupin@kaust.edu.sa`

Coauthor(s): Chiheb Ben Hammouda, Sophia Munker, Raúl Tempone

Special session: Forward and Inverse Problems for Stochastic Reaction Networks p.67

Stochastic reaction networks (SRNs) model stochastic effects for various applications, including intracellular chemical or biological processes and epidemiology. A key challenge in practical problems modeled by SRNs is that only a few state variables can be dynamically observed. Given the measurement trajectories, one can estimate the conditional probability distribution of unobserved (hidden) state variables by solving a system filtering equation. The current numerical methods, such as the Filtered Finite State Projection [1], are hindered by the curse of dimensionality, significantly affecting their computational performance. To overcome this, we propose to use a dimensionality reduction technique based on the Markovian projection (MP), initially introduced for forward problems [2]. In this work, we explore how to adapt the existing MP approach to the filtering problem and introduce a novel version of the MP, the Filtered MP, that guarantees the consistency of the resulting estimator [3]. The novel method employs a reduced-variance particle filter for estimating the jump intensities of the projected model and solves the filtering equations in a low-dimensional space, improving computational efficiency over existing methods.

- [1] D'Ambrosio, E., Fang, Z., Gupta, A., Kumar, S., & Khammash, M. (2022). Filtered finite state projection method for the analysis and estimation of stochastic biochemical reaction networks. *bioRxiv*, 2022-10.
- [2] Hammouda, C. B., Rached, N. B., Tempone, R., & Wiechert, S. (2024). Automated importance sampling via optimal control for stochastic reaction networks: A Markovian projection-based approach. *Journal of Computational and Applied Mathematics*, 446, 115853.
- [3] Hammouda, C. B., Chupin, M., Munker, S., & Tempone, R. (2025). Filtered Markovian Projection: Dimensionality Reduction in Filtering for Stochastic Reaction Networks. *arXiv preprint arXiv:2502.07918*.

Fri, Aug 1 09:00–10:30

Fixed-budget simulation method for growing cell populations*Zhou Fang*

Academy of Mathematics and Systems Science, Chinese Academy of Sciences

zhfang@amss.ac.cn

Coauthor(s): Shaoqing Chen, Zheng Hu, Da Zhou

Special session: Forward and Inverse Problems for Stochastic Reaction Networks p.67

Investigating the dynamics of growing cell populations is crucial for unraveling key biological mechanisms in living organisms, with many important applications in therapeutics and biochemical engineering. Classical agent-based simulation algorithms are often inefficient for these systems because they track each individual cell, making them impractical for fast (or even exponentially) growing cell populations. To address this challenge, we introduce a novel stochastic simulation approach based on a Feynman-Kac-like representation of the population dynamics. This method, named the Feynman-Kac-inspired Gillespie's Stochastic Simulation Algorithm (FKG-SSA), always employs a fixed number of independently simulated cells for Monte Carlo computation of the system, resulting in a constant computational complexity regardless of the population size. Furthermore, we theoretically show the statistical consistency of the proposed method, indicating its accuracy and reliability. Finally, a couple of biologically relevant numerical examples are presented to illustrate the approach. Overall, the proposed FKG-SSA effectively addresses the challenge of simulating growing cell populations, providing a solid foundation for better analysis of these systems.

Fri, Aug 1 09:00–10:30

State and parameter inference in stochastic reaction networks*Muruhan Rathinam*

University of Maryland Baltimore County

muruhan@umbc.edu

Coauthor(s): Mingkai Yu

Continuous time Markov chain models are widely used to model intracellular chemical reactions networks that arise in systems and synthetic biology. In this talk, we address the problem of inference of state and parameters of such systems from partial observations. We present details of recent particle filtering methods that are applicable to two different scenarios: one in which the observations are made continuously in time and the other in which the observations are made in discrete snapshots of time. We provide the theoretical justification as well as numerical results to illustrate these methods.

- [1] Rathinam, Muruhan & Yu, Mingkai (2021). *State and parameter estimation from exact partial state observation in stochastic reaction networks*. The Journal of Chemical Physics. 154(3).
- [2] Rathinam, Muruhan & Yu, Mingkai (2023). Stochastic Filtering of Reaction Networks Partially Observed in Time Snapshots. Journal of Computational Physics. Volume 515, 15 October 2024, 113265.

Fri, Aug 1 09:00–10:30

Sophia Münker

RWTH Aachen University

muenker@uq.rwth-aachen.de

ChihebBenHammouda, NadhirBenRached, RalTempone

Coauthor(s): Forward and Inverse Problems for Stochastic Reaction Networks

A Stochastic Reaction Network (SRN) is a continuous-time, discrete-space Markov chain that models the random interaction of d species through reactions, commonly applied in biochemical systems. We are interested in efficiently estimating rare event probabilities, where we consider path-dependent observables. Therefore, we present an importance sampling (IS) method based on the discrete Tau-Leap (TL) scheme to enhance the performance of Monte Carlo (MC) estimators. The primary challenge in IS is selecting an appropriate change of probability measure to significantly reduce variance, which often requires deep insights into the underlying problem. To address this, we propose a generic approach to obtain an efficient path-dependent measure change, based on an original connection between finding optimal IS parameters and solving a variance minimization problem using a stochastic optimal control (SOC) formulation [1]. The optimal IS parameters can be derived by solving a Hamilton-Jacobi-Bellman equation.

To address the curse of dimensionality, we propose the Markovian Projection (MP) technique to reduce the SRN to a lower-dimensional SRN (called MP-SRN) while preserving the marginal distribution of the original high-dimensional system. When solving the resulting SOC problem numerically to derive the variance reducing IS parameters, we derive the parameter for a reduced-dimensional model. These IS parameters can be applied to the full-dimensional SRN in the forward run. Analysis and numerical experiments demonstrate that our IS strategies substantially reduce the variance of the MC estimator, leading to lower computational complexity in the rare event regime compared to standard MC methods.

At the end of the talk, we give a small outlook on a multilevel-IS scheme to further improve the efficiency of the estimator.

- [1] Ben Hammouda, C., Ben Rached, N., Tempone, R., & Wiechert, S. (2024). Automated importance sampling via optimal control for stochastic reaction networks: A Markovian projection-based approach. Journal of Computational and Applied Mathematics, 446, 115853.

Fri, Aug 1 09:00–10:30

A High-performance Multi-level Monte Carlo Software for Full Field Estimates and Applications in Optimal Control*Niklas Baumgarten*

Heidelberg University

niklas.baumgarten@uni-heidelberg.de

Coauthor(s): Robert Scheichl, Robert Kutri, David Schneiderhan, Sebastian Krumscheid, Christian Wieners, Daniele Corallo

Special session: Hardware or Software for (Quasi-)Monte Carlo Algorithms, Part II p.68

We introduce a high-performance software framework for multi-level Monte Carlo (MLMC) and multi-level stochastic gradient descent (MLSGD) methods, designed for efficient uncertainty quantification and optimal control in high-dimensional PDE applications. The software operates under strict memory and CPU-time constraints, requiring no prior knowledge of problem regularity or memory demands.

Built on the budgeted MLMC method with a sparse multi-index update algorithm, it enables full spatial-domain estimates at the same computational cost as single-point evaluations while maintaining memory usage comparable to the deterministic problem. Additionally, the framework integrates an MLSGD method for optimal control, achieving faster convergence at reduced computational costs compared to standard stochastic gradient descent methods.

We validate the software on applications such as stochastic PDE-based sampling, subsurface flow, mass transport, acoustic wave equations, and high-dimensional control problems.

Fri, Aug 1 09:00–10:30

Quasi-Monte Carlo Generators, Randomization Routines, and Fast Kernel Methods

Aleksei G Sorokin

Illinois Institute of Technology, Department of Applied Mathematics.

Sandia National Laboratories.

`asorokin@hawk.iit.edu`

This talk will highlight recent improvements to the QMCPy Python package: a unified library for Quasi-Monte Carlo methods and computations related to low discrepancy sequences. We will describe routines for low discrepancy point set generation, randomization, and application to fast kernel methods. Specifically, we will discuss generators for lattices, digital nets, and Halton point sets with randomizations including random permutations / shifts, linear matrix scrambling, and nested uniform scrambling. Routines for working with higher-order digital nets and scramblings will also be detailed. For kernel methods, we provide implementations of special shift-invariant and digitally-shift invariant kernels along with fast Gram matrix operations facilitated by the bit-reversed Fast Fourier Transform (FFT), the bit-reversed inverse FFT (IFFT), and the Fast Walsh Hadamard Transform (FWHT). We will also describe methods to quickly update the matrix-vector product or linear system solution after doubling the number of points in a lattice or digital net in natural order. Generalizations to fast Gaussian process regression with derivative information will be discussed if time permits.

- [1] Sorokin, A. (2025). A Unified Implementation of Quasi-Monte Carlo Generators, Randomization Routines, and Fast Kernel Methods. arXiv preprint arXiv:2502.14256.

Fri, Aug 1 09:00–10:30

Hybrid Monte Carlo methods for kinetic transport

Johannes Krotz

University of Notre Dame

`jkrotz@nd.edu`

Coauthor(s): Hardware or Software for (Quasi-)Monte Carlo Algorithm

We present a hybrid method for time-dependent particle transport problems that combines Monte Carlo (MC) estimation with deterministic solutions based on discrete ordinates. For spatial discretizations, the MC algorithm computes a piecewise constant solution and the discrete ordinates use bilinear discontinuous finite elements. From the hybridization of the problem, the resulting problem solved by Monte Carlo is scattering free, resulting in a simple, efficient solution procedure. Between time steps, we use a projection approach to “relabel” collided particles as uncollided particles. From a series of standard 2-D Cartesian

test problems we observe that our hybrid method has improved accuracy and reduction in computational complexity of approximately an order of magnitude relative to standard discrete ordinates solutions.

Contributed Talks

Mon, Jul 28 10:30-12:30

Stereographic Multi-Try Metropolis Algorithms for Heavy-tailed Sampling

Zhihao Wang

University of Copenhagen

`zw@math.ku.dk`

Coauthor(s): Jun Yang

We introduce a novel family of gradient-free Markov chain Monte Carlo (MCMC) algorithms that integrate the principles of multi-try Metropolis (MTM) and stereographic MCMC, designed specifically for efficient sampling of heavy-tailed distributions. Through scaling analysis and extensive simulations, we demonstrate that the proposed stereographic multi-try Metropolis (SMTM) algorithm outperforms both traditional Euclidean MTM and existing stereographic random-walk Metropolis. Furthermore, the SMTM algorithm has the potential to benefit from modern hardware, such as GPUs, allowing for improved performance through parallel implementation.

Mon, Jul 28 10:30-12:30

Creating rejection-free samplers by rebalancing skew-balanced jump processes*Ruben Seyer*

Chalmers University of Technology and University of Gothenburg

`rubense@chalmers.se`

Coauthor(s): Erik Jansson, Moritz Schauer, Akash Sharma

Markov chain sampling methods form the backbone of modern computational statistics. However, many popular methods are prone to random walk behaviour, i.e. diffusion-like exploration of the sample space, leading to slow mixing that requires intricate tuning to alleviate. Non-reversible samplers can resolve some of these issues. We introduce a device that turns jump processes that satisfy a skew-detailed balance condition for a reference measure into a process that samples a target measure that is absolutely continuous with respect to the reference measure. This sampler is rejection-free, non-reversible and time-continuous. As an example, we apply the device to Hamiltonian dynamics discretized by the leapfrog integrator, resulting in a rejection-free non-reversible time-continuous version of Hamiltonian Monte Carlo (HMC). We prove the geometric ergodicity of the resulting sampler, and demonstrate its increased robustness to hyperparameter tuning compared to HMC through numerical examples. This comes at a computational cost at worst double that of HMC, in practice lower than other popular non-reversible samplers such as the Bouncy Particle Sampler.

Mon, Jul 28 10:30-12:30

Theoretical guarantees for lifted samplers*Philippe Gagnon*

Université de Montréal

philippe.gagnon.3@umontreal.ca

Coauthor(s): Florian Maire

The work I would like to present is about a particular class of Markov chain Monte Carlo (MCMC) methods which use non-reversible Markov chains commonly referred to as *lifted Markov chains*; the methods are commonly referred to as *lifted samplers*. The methods are not particularly new (they date back at least to Horowitz [1]), but they have recently been the subject of significant research work motivated by a general belief that, in statistical applications, they lead to more efficient estimators than their reversible counterparts which correspond to Metropolis–Hastings (MH) algorithms (see, e.g., Andrieu and Livingstone [2]). It was thus somewhat surprising to observe that it is not always the case in some recent work (see, e.g., Gagnon and Maire [3]). One can thus wonder what degree of inefficiency these chains may exhibit in worst-case scenarios. This is an important question given that lifted samplers are popular in practice, a consequence of the fact that they are often as easy to implement on a computer as their MH counterparts and often have the same computational complexity.

The main contribution of our work is to provide an answer to this question under arguably the most general framework. We proceed by leveraging the seminal work of Tierney [4] to define a lifted version of a generalized MH algorithm. Virtually any (reversible) MCMC method can be seen as a special case of this generalized MH algorithm, ranging from the traditional MH algorithm of Hastings [5] to the reversible jump algorithm of Green [6]. Our main theoretical result allows for a comparison between the generalized MH algorithm and its lifted version in terms of the variance of produced estimators. It essentially guarantees that the variance of estimators produced by the lifted version cannot be more than twice that of estimators produced by the generalized MH algorithm. This result indicates that, while there is potentially a lot to gain from lifting a Markov chain, there is not much to lose. We also show that our result is optimal, in the sense that it is not possible to improve on the factor 2 without additional assumptions. The definition of the lifted version of the generalized MH algorithm allows to understand how a lifted sampler can be constructed under such a general framework, which adds a methodological contribution to our theoretical contribution.

The efficiency of Markov chains is traditionally assessed by studying the characteristics of their Markov transition operators. To establish our theoretical result, we needed to connect the efficiency of two significantly different operators (those of the MH and lifted algorithms): in addition to not be defined on the same domain, one is self-adjoint while the other is not, which further complicates the analysis. One of our main achievements was to identify a specific auxiliary operator which acts a bridge and allows to connect the efficiency of the two aforementioned operators. This auxiliary operator is compared to the MH one through a Peskun ordering [7] established via a careful analysis of the Markov kernels, yielding sharp bounds. The connections between the MH and lifted algorithms is completed by comparing the auxiliary operator with the lifted one using a result in Andrieu and Livingstone [2].

- [1] Horowitz, A. M. (1991) A generalized guided Monte Carlo algorithm. *Phys. Lett. B*, **268**, 247–252.
- [2] Andrieu, C. and Livingstone, S. (2021) Peskun–Tierney ordering for Markovian Monte Carlo: Beyond the reversible scenario. *Ann. Statist.*, **49**, 1958–1981.
- [3] Gagnon, P. and Maire, F. (2024) An asymptotic Peskun ordering and its application to lifted samplers. *Bernoulli*, **30**, 2301–2325.
- [4] Tierney, L. (1998) A note on Metropolis–Hastings kernels for general state spaces. *Ann. Appl. Probab.*, **8**, 1–9.
- [5] Hastings, W. K. (1970) Monte Carlo sampling methods using Markov chains and their applications. *Biometrika*, **57**, 97–109.
- [6] Green, P. J. (1995) Reversible jump Markov chain Monte Carlo computation and Bayesian model determination. *Biometrika*, **82**, 711–732.
- [7] Peskun, P. (1973) Optimum Monte-Carlo sampling using Markov chains. *Biometrika*, **60**, 607–612

Tue, Jul 29 10:30-12:30

Optimizing Generalized Hamiltonian Monte Carlo for Bayesian Inference applications

Lorenzo Nagar

BCAM - Basque Center for Applied Mathematics, Bilbao, Spain

lnagar@bcamath.org

Coauthor(s): Leonardo Gavira Balmacz, Hristo Inouzhe Valdes, Martín Parga Pazos, María Xosé Rodríguez-Álvarez, Jesús María Sanz-Serna, and Elena Akhmatskaya

In contrast to the widely adopted Hamiltonian/Hybrid Monte Carlo (HMC) [1], the Generalized Hamiltonian Monte Carlo (GHMC) algorithm [2, 3] leverages the irreversibility of its generated Markov chains, resulting in faster convergence to equilibrium and reduced asymptotic variance [4, 5].

Despite its theoretically predicted advantages, GHMC can be highly sensitive to the choice of a numerical integrator for the Hamiltonian equations and requires careful tuning of simulation parameters, such as the integration step size, the trajectory length, and the amount of random noise in momentum refreshment.

In this talk, we present a novel approach for finding optimal (in terms of sampling performance and accuracy) settings for a GHMC simulation. For an arbitrary simulated system, our methodology identifies a system-specific integration scheme that maximizes a conservation of energy for harmonic forces, along with appropriate randomization intervals for the simulation parameters, without incurring additional computational cost.

Numerical experiments on well-established statistical models exhibit, with the help of the state-of-the-art performance metrics, significant gains in GHMC sampling efficiency when

optimally tuned hyperparameters are chosen instead of heuristic or recommended ones. Comparative performance of GHMC and HMC with optimal settings is also discussed.

Additionally, we apply our methodology to three real-world case studies:

- Patient resistance to endocrine therapy in breast cancer;
- Influenza A (H1N1) epidemics outbreak;
- Modeling of cell-cell adhesion dynamics.

- [1] Neal, Radford M. (2011). *MCMC Using Hamiltonian Dynamics*. Handbook of Markov Chain Monte Carlo (Eds: Brooks, S., Gelman, A., Jones, G., Meng, X.), Vol. 2 pp. 113–162. Chapman and Hall/CRC, New York.
- [2] Horowitz, Alan M. (1991). *A generalized guided Monte Carlo algorithm*. Physics Letters B 268.2: 247–252.
- [3] Kennedy, Anthony D. & Pendleton, Brian J. (2001). *Cost of the generalised hybrid Monte Carlo algorithm for free field theory*. Nuclear Physics B 607.3: 456–510.
- [4] Ottobre, Michela (2016). *Markov Chain Monte Carlo and Irreversibility*. Reports on Mathematical Physics 77: 267–292.
- [5] Duncan, Andrew B., Lelièvre, Tony & Pavliotis, Grigorios A. (2016). *Variance Reduction Using Nonreversible Langevin Samplers*. Journal of Statistical Physics 163: 457–491.

Tue, Jul 29 10:30-12:30

Bayesian Anomaly Detection in Variable-Order and Variable-Diffusivity Fractional Mediums

Hamza Ruzayqat

(KAUST) King Abdullah University of Science and Technology

Hamza.Ruzayqat@kaust.edu.sa

Coauthor(s): Omar Knio and George Turkiyyah

Fractional diffusion equations (FDEs) are powerful tools for modeling anomalous diffusion in complex systems, such as fractured media and biological processes, where nonlocal dynamics and spatial heterogeneity are prominent. These equations provide a more accurate representation of such systems compared to classical models but pose significant computational challenges, particularly for spatially varying diffusivity and fractional orders. In this talk I will present a Bayesian inverse problem for FDEs in a 2-dimensional bounded domain with an anomaly of unknown geometric and physical properties, where the latter are the diffusivity and fractional order fields. To tackle the computational burden of solving dense and ill-conditioned systems, we employ an advanced finite-element scheme incorporating low-rank matrix representations and hierarchical matrices. For parameter estimation, we implement

two surrogate-based approaches using polynomial chaos expansions: one constructs a 7-dimensional surrogate for simultaneous inference of geometrical and physical parameters, while the other leverages solution singularities to separately infer geometric features, then constructing a 2-dimensional surrogate to learn the physical parameters and hence reducing the computational cost immensely. These surrogates are used inside a Markov chain Monte Carlo algorithm to infer the unknown parameters.

Tue, Jul 29 10:30-12:30

Theoretical Guarantees of Mean Field Variational Inference for Bayesian Principal Component Analysis

Arghya Datta

Université de Montréal

arghyadatta8@gmail.com

Coauthor(s): Philippe Gagnon, Florian Maire

In this talk, we will investigate mean field variational inference for Bayesian principal component analysis (BPCA). Despite the wide usage of mean field variational inference for the BPCA model, there exists remarkably little theoretical justification. I will talk about new results on the convergence guarantees of the iterative coordinate ascent variational inference (CAVI) algorithm for the BPCA model. In particular, we will show that under reasonable technical assumptions on the initialization, CAVI converges exponentially fast to a local optimum. An interesting connection between the CAVI algorithm for the BPCA model and power iteration, which is a popular iterative numerical algorithm for finding singular vectors of a given matrix, will also be discussed.

Tue, Jul 29 10:30-12:30

Bayesian Analysis of Latent Underdispersion Using Discrete Order Statistics

Jimmy Lederman

Department of Statistics, University of Chicago

jlederman@uchicago.edu

Coauthor(s): Aaron Schein

Researchers routinely analyze count data using models based on a Poisson likelihood, for which there exist many analytically convenient and computationally efficient strategies for posterior inference. A limitation of such models however is the equidispersion constraint of

the Poisson distribution. This restriction prevents the model’s likelihood, and by extension its posterior predictive distribution, from concentrating around its mode. As a result, these models are parametrically bound to produce probabilistic predictions with high uncertainty, even in cases where low uncertainty is supported by the data. While count data often exhibits overdispersion *marginally*, such data may nevertheless be consistent with a likelihood that is underdispersed *conditionally*, given parameters and latent variables. Detecting conditional underdispersion, however, requires one to fit the “right” model and thus the ability to build, fit, and critique a variety of different models with underdispersed likelihoods. Towards this end, we introduce a novel family of models for conditionally underdispersed count data whose likelihoods are based on order statistics of Poisson random variables. More specifically, we assume that each observed count coincides with the j^{th} order-statistic of D latent i.i.d. Poisson random variables, where j and D are user-defined hyperparameters. To perform efficient MCMC-based posterior inference in this family of models, we derive a data-augmentation strategy which samples the other $D-1$ latent variables from their exact conditional, given the observed (j, D) -order statistic. By relying on the explicit construction of a Poisson order statistic, this data augmentation strategy can be modularly combined with the many existing inference strategies for Poisson-based models. We generalize this approach beyond the Poisson to any non-negative discrete parent distribution and, in particular, show that models based on negative binomial order statistics can flexibly capture both conditional under and overdispersion. To illustrate our approach empirically, we build and fit models to three real count data sets of flight times, COVID-19 cases counts, and RNA-sequence data, and we demonstrate how models with underdispersed likelihoods can leverage latent structure to make more precise probabilistic predictions. Although the possibility of conditional underdispersion is often overlooked in practice, we argue that this is at least in part due to the lack of tools for modeling underdispersion in settings where complex latent structure is present.

Fri, Aug 1 09:00–10:30

Monte Carlo simulation approach to solve distributed order fractional mathematical model

Yashveer Kumar

INESC-ID, Rua Alves Redol 9, Lisbon, Portugal 1000-029

yashveerkumar.rs.mat18@inesc-id.pt

Juan A. Acebron, INESC-ID, Department of Mathematics, Carlos III University of Madrid, Spain.

Jose Monteiro, INESC-ID, IST, Universidade de Lisboa, Portugal.

This work presents a novel approach to solving time-distributed order fractional nonhomogeneous differential equations using the Monte Carlo simulation method. Fractional differential equations with distributed orders are critical for modeling complex systems with memory and hereditary effects, such as viscoelastic materials, anomalous diffusion, and biological processes. The inclusion of time-distributed orders introduces additional challenges in analytical and numerical solutions, especially in the presence of nonhomogeneous terms.

The proposed Monte Carlo method reformulates the distributed order fractional equation into an equivalent integral representation. By simulating random processes and utilizing probabilistic interpretations of fractional operators, the solution is computed as an average over numerous realizations. The flexibility of Monte Carlo simulations makes them particularly well-suited for addressing the inherent complexity of distributed order systems.

Numerical experiments validate the efficiency and effectiveness of the Monte Carlo approach, illustrating its capability to handle various distributed order kernels and nonhomogeneous terms. This method offers a robust, scalable, and versatile framework for solving fractional differential equations, paving the way for broader applications in science and engineering.

- [1] Niederreiter, Harald (1992). *Random number generation and quasi-Monte Carlo methods*. Society for Industrial and Applied Mathematics (SIAM).
- [2] Guidotti, Nicolas L. & Acebron, Juan A. & Monterio, Jose (2024). *A stochastic method for solving time-fractional differential equations*. Computers and Mathematics with Applications, 159, 240-253.
- [3] Kumar, Yashveer & Singh, Vineet Kumar (2021). *Computational approach based on wavelets for financial mathematical model governed by distributed order time-fractional partial differential equation*. Mathematics and Computers in Simulation, 190, 531-569.

Fri, Aug 1 09:00–10:30

Benchmarking the Geant4-DNA 'UHDR' Example for Monte Carlo Simulation of pH Effects on Radiolytic Species Yields Using a Mesoscopic Approach

Serena Fattori

Istituto Nazionale di Fisica Nucleare (INFN), Laboratori Nazionali del Sud (LNS), Catania, Italy

`serena.fattori@lns.infn.it`

Coauthor(s): Hoang Ngoc Tran, Anh Le Tuan, Fateme Farokhi, Giuseppe Antonio Pablo Cirrone, Sebastien Incerti

Background and Aims

FLASH radiotherapy is an innovative cancer treatment technique that delivers high radiation doses in an extremely short time (≥ 40 Gy/s), inducing the so-called FLASH effect—characterized by the sparing of healthy tissue while maintaining effective tumor control. However, the mechanisms underlying the FLASH effect remain unclear, and ongoing research aims to elucidate them. One approach to investigating this phenomenon is through Monte Carlo simulations of particle transport and the resulting radiolysis in aqueous media, enabling comparisons between FLASH and conventional irradiation.

Methods

To provide a useful tool for investigating the effects of FLASH irradiation, the Geant4-DNA example "UHDR" was introduced in the beta release 11.2.0 of Geant4 (June 2023). This example incorporates a newly developed radiolysis chemical stage based on the diffusion-reaction master equation (RDME), a mesoscopic method that bridges microscopic particle-level interactions and macroscopic chemical kinetics. This approach allows the extension of the simulation time to minutes post-irradiation, enabling the validation of equilibrium processes that may play a crucial role on long time scales. In this context, the impact of pH on radiolytic species yields towards equilibrium is particularly important. For the first time in Geant4-DNA, the UHDR example allows taking into account the effect of different pH values on water radiolysis.

Results

This study aims to benchmark the capability of the UHDR example to accurately reproduce the effect of pH on radiolytic species yields. Preliminary results are currently under analysis for 1 MeV electron and 300 MeV proton irradiation in the conventional modality, with comparisons against literature data.

Conclusions

The ability to simulate the impact of pH on water radiolysis represents a significant advancement in studying the evolution of radiolytic species toward equilibrium. This improvement could provide valuable insights into potential differences in chemical evolution under FLASH irradiation compared to conventional irradiation.

Fri, Aug 1 09:00–10:30

Multilevel simulation of ensemble Kalman methods: interactions across levels*Toon Ingelaere*

KU Leuven

toon.ingelaere@kuleuven.be

Coauthor(s): Giovanni Samaey

To solve problems in domains such as filtering, optimization, and posterior sampling, ensemble Kalman methods have recently received much attention. These parallelizable and often gradient-free algorithms use an ensemble of particles that evolve in time, based on a combination of well-chosen dynamics and interaction between the particles. For computationally expensive dynamics, the cost of attaining a high accuracy quickly becomes prohibitive. To improve the asymptotic cost-to-error relation, different multilevel Monte Carlo techniques have been proposed. These methods simulate multiple differently sized ensembles at different resolutions, corresponding different accuracies and costs. While particles within one of these ensembles do interact with each other, a key question is whether and how particles should interact across ensembles and levels. In this talk, we will outline and compare the most common approaches to such multilevel ensemble interactions.

Fri, Aug 1 09:00–10:30

Adaptive Max-EWMA Control Chart with SVR: Monte Carlo Simulation for Run Length Analysis*Muhammad Noor ul Amin*

COMSATS University Islamabad-Lahore

In industrial quality control, monitoring process variations is crucial for ensuring product reliability, particularly when dealing with non-normal data distributions. This study proposes an adaptive Max-EWMA control chart integrated with Support Vector Regression (SVR) for the simultaneous monitoring of process mean and variance. The approach utilizes a dynamic smoothing constant predicted by SVR to enhance sensitivity to real-time process shifts. To address non-normality, Weibull-distributed data is transformed into a standard normal form before analysis. The performance of the proposed method is extensively evaluated through Monte Carlo simulations to assess the run length profile under different process shift scenarios. Results demonstrate the effectiveness of the approach in detecting small to moderate shifts, with the linear kernel exhibiting superior balance between sensitivity and stability, making it an optimal choice for industrial applications. The findings highlight the robustness of the proposed control chart and its adaptability in real-time process monitoring.

Mon, Jul 28 15:30–17:30

Halton Sequences, Scrambling and the Inverse Star-Discrepancy*Christian Weiß*

Ruhr West University of Applied Sciences

christian.weiss@hs-ruhrwest.de

Halton sequences are classical examples of multi-dimensional low-discrepancy sequences. Braaten and Weller discovered that scrambling strongly reduces their empirical star-discrepancy. A similar approach may be applied to certain multi-parameter subsequences of Halton sequences. Indeed, results from p-adic analysis guarantee that these subsequences still have the theoretical low-discrepancy property while scrambling has strong effects on the empirical star-discrepancy. By optimizing the parameters of these subsequences known empiric bounds for the inverse star-discrepancy can be improved.

- [1] E. Braaten, and G. Weller. (1979). An improved low-discrepancy sequence for multi-dimensional quasi-Monte Carlo integration. *Journal of Computational Physics*, 33(2): 249–258.
- [2] C. Weiß. (2024). Scrambled Halton Subsequences and Inverse Star-Discrepancy, arXiv: 2411.10363.

Mon, Jul 28 15:30–17:30

Star discrepancy and uniform approximation under weighted simple and stratified random sampling*Xiaoda Xu*

Suqian University

23195@squ.edu.cn

Coauthor(s): Jun Xian

We mainly consider two problems in this talk. First, We consider random discrepancy under weighted importance sampling of a class of stratified input. We give the expected L_p -discrepancy($2 \leq p < \infty$) upper bound in weighted form under a class of stratified sampling. This result contributes to the error estimate of the upper bound of the integral approximation under weighted importance sampling, and our sampling pattern is a stratified input. Second, we discuss the probabilistic star discrepancy for a random double infinite matrix and propose an improvement to the coefficient of an existing result, we mainly use the optimal refined δ -bracketing number so far.

- [1] J. Dick, D. Rudolf and H. Zhu. (2019). A weighted discrepancy bound of quasi-Monte

Carlo importance sampling. *Statist. Probab. Lett.*, 100-106.

- [2] M. Gnewuch. (2024). Improved bounds for the bracketing number of orthants or revisiting an algorithm of Thiémarc to compute bounds for the star discrepancy. *J. Complexity*.

Mon, Jul 28 15:30–17:30

Transport Quasi-Monte Carlo

Sifan Liu

Center for Computational Mathematics, Flatiron Institute
sliu@flatironinstitute.org

Quasi-Monte Carlo (QMC) is a powerful method for evaluating high-dimensional integrals. However, its use is typically limited to distributions where direct sampling is straightforward, such as the uniform distribution on the unit hypercube or the Gaussian distribution. For general target distributions with potentially unnormalized densities, leveraging the low-discrepancy property of QMC to improve accuracy remains challenging. We propose training a transport map to push forward the uniform distribution on the unit hypercube to approximate the target distribution. Inspired by normalizing flows, the transport map is constructed as a composition of simple, invertible transformations. To ensure that RQMC achieves its superior error rate, the transport map must satisfy specific regularity conditions. We introduce a flexible parametrization for the transport map that not only meets these conditions but is also expressive enough to model complex distributions. Our theoretical analysis establishes that the proposed transport QMC estimator achieves faster convergence rates than standard Monte Carlo, under mild and easily verifiable growth conditions on the integrand. Numerical experiments confirm the theoretical results, demonstrating the effectiveness of the proposed method in Bayesian inference tasks.

Mon, Jul 28 15:30–17:30

Using Normalizing Flows for Efficient Quasi-Random Sampling for Copulas

Ambrose Emmett-Iwaniw

University of Waterloo Department of Actuarial Science and Statistics
arsemmettiwaniw@uwaterloo.ca

Coauthor(s): Christiane Lemieux

In finance and risk management, copulas are used to model the dependence between stock

prices and insurance losses to compute expectations of interest. Generally, Monte Carlo (MC) sampling is used to generate copula samples to approximate expectations. To reduce the variance of the approximation, we can use quasi-Monte Carlo (QMC) sampling to generate copula samples. This paper examines a new method to generate quasi-random samples from copulas requiring fewer training resources than previous methods such as the generative moment matching networks (GMMN) model [1]. Traditional methods that do not use generative models often rely on conditional distribution methods (CDM) to generate quasi-random samples from specific copulas [2]. CDM is limited to only a few parametric copulas (Gumbel has no efficient CDM to sample quasi-random samples) in low dimensions [2]. Here, we propose using a powerful and simple generative model called Normalizing Flows (NFs) to generate quasi-random samples for any copula, including cases where we only have data available. NFs are a type of explicit generative model that relies on transforming a simple density, such as a normal density, through efficient invertible transformations that rely on the change of variables formula into a density that models complex data that facilitates easy sampling and efficient inverting of samples from complex data to normal data and vice versa. The benefit of these NFs for copula modelling is that their training is efficient in terms of runtime, allowing for larger batch sizes compared to the GMMN model [1]. Also, it is sample-efficient; it only needs samples from the copula and not samples from the normal as the GMMN model [1] required. Once the NF model is trained, we can efficiently invert the model to take as input quasi-random samples to generate quasi-random copula samples. Through many different simulations and applications, we show our approach allows us to leverage the benefit of QMC in a variety of real-world settings involving dependent data.

- [1] Hofert, M., Prasad, A., and Zhu, M. (2021). Quasi-random sampling for multivariate distributions via generative neural networks. *Journal of Computational and Graphical Statistics*, 30(3):647–670.
- [2] Cambou, M., Hofert, M., and Lemieux, C. (2017). Quasi-random numbers for copula models. *Statistics and Computing*, 27:1307–1329.

Tue, Jul 29 15:30-17:30

Approximation using median lattice algorithms

Peter Kritzer

Austrian Academy of Sciences

`peter.kritzer@oeaw.ac.at`

Coauthor(s): Takashi Goda, Zexin Pan

We consider L_2 -approximation of functions in a weighted Korobov space. We present a median algorithm, which is related to median integration rules, that have recently gained a lot of interest in the theory of quasi-Monte Carlo methods. Indeed, we use lattice rules as the underlying integration rules to approximate Fourier coefficients. As we will show, we can obtain a convergence rate that is arbitrarily close to optimal in terms of the number of evaluations needed of the function to be approximated.

Tue, Jul 29 15:30-17:30

Convergence Rates of Randomized Quasi-Monte Carlo Methods under Various Regularity Conditions

Yang Liu

King Abdullah University of Science and Technology

yang.liu.3@kaust.edu.sa

In this work, we analyze the convergence rate of randomized quasi-Monte Carlo (RQMC) methods under Owen's boundary growth condition (Owen, 2006) via spectral analysis. We examine the RQMC estimator variance for two commonly studied sequences—the lattice rule and the Sobol' sequence—using the Fourier transform and Walsh–Fourier transform, respectively. Under certain regularity conditions, our results reveal that the asymptotic convergence rate of the RQMC estimator's variance closely aligns with the exponent specified in Owen's boundary growth condition for both sequence types. We also provide an analysis for certain discontinuous integrands.

In addition, we investigate the L^p integrability of weak mixed first-order derivatives of the integrand and study the convergence rates of scrambled digital nets. We demonstrate that the generalized Vitali variation with parameter $\alpha \in [\frac{1}{2}, 1]$ from Dick and Pillichshammer (2010) is bounded above by the L^p norm of the weak mixed first-order derivative, where $p = \frac{2}{3-2\alpha}$. Consequently, when the weak mixed first-order derivative belongs to L^p for $1 \leq p \leq 2$, the variance of the scrambled digital nets estimator converges at a rate of $\mathcal{O}\left(N^{-4+\frac{2}{p}} \log^{s-1} N\right)$. Together, these results provide a comprehensive theoretical framework for understanding the convergence behavior of RQMC methods and scrambled digital nets under various regularity assumptions.

- [1] Liu, Y. (2024). Randomized quasi-Monte Carlo and Owen's boundary growth condition: A spectral analysis. arXiv preprint arXiv:2405.05181.
- [2] Liu, Y. (2025). Integrability of weak mixed first-order derivatives and convergence rates of scrambled digital nets. arXiv preprint arXiv:2502.02266.

Tue, Jul 29 15:30-17:30

Use of rank-1 lattices in the Fourier neural operator*Jakob Dilen*

Department of Computer Science, KU Leuven

jakob.dilen@student.kuleuven.be

Coauthor(s): Frances Y. Kuo, Dirk Nuyens

The “Fourier neural operator” [2] is a variant of the “neural operator”. Its defining characteristic, compared to the regular neural operator, is that it transforms the input to the Fourier domain at the start of each layer. This transformation uses the d -dimensional FFT on a regular grid in d dimensions. We describe how to do this more efficiently using rank-1 lattice points, which allow for a one-dimensional FFT algorithm, see, e.g., [1].

- [1] F. Y. Kuo, G. Migliorati, F. Nobile, and D. Nuyens. *Function integration, reconstruction and approximation using rank-1 lattices*. Math. Comp., 90, April 2021.
- [2] Z. Li, N. B. Kovachki, K. Azizzadenesheli, B. Liu, K. Bhattacharya, A. Stuart, and A. Anandkumar. *Fourier neural operator for parametric partial differential equations*. International Conference on Learning Representations, 2021.

Tue, Jul 29 15:30-17:30

Investigating the Optimum RQMC Batch Size for Betting and Empirical Bernstein Confidence Intervals*Aadit Jain*

Rancho Bernardo High School

aaditdjain@gmail.com

Coauthor(s): Fred J. Hickernell, Art B. Owen, Aleksei G. Sorokin

The Betting [1] and Empirical Bernstein (EB) [1,2] confidence intervals (CIs) are finite sample (non-asymptotic) and require IID samples. Since both are non-asymptotic, they are much wider than confidence intervals based on the Central Limit Theorem (CLT) due to the stronger coverage property they provide. To apply these finite sample CIs to randomized quasi-Monte Carlo (RQMC), we take R independent replications of n RQMC points, averaging the n function evaluations within each replication. Given a fixed budget $N = nR$, we investigate the optimal n that minimizes the CI widths for both methods.

Using the code from [1], we ran simulations on various integrands (smooth, rough, one-dimensional, multi-dimensional) and ridge functions. Interestingly, the optimal n was quite small compared to N , often just 1 (plain IID), 2, or 4 when $N = 2^{10}$. Moreover, the optimal n appeared to grow quite slowly as N increased. Notably, both CI methods applied to RQMC

outperformed plain IID when the optimal n is greater than 1.

This experimental trend aligns with our analysis of Bennett’s inequality for EB [2], which suggests that the optimum n is $O(N^{1/(2\theta+1)})$ for $\theta > 1/2$. Specifically, for $\theta = 3/2$, which occurs for smoother integrands, we obtain $n = O(N^{1/4})$. For $\theta = 1$, which corresponds to a typical Koksma-Hlawka rate, we get $n = O(N^{1/3})$. The ratio of RQMC EB CI widths to plain IID EB CI widths is $\Theta(N^{(1-2\theta)/(4\theta+2)})$. For $\theta = 1$, we get a ratio of $\Theta(N^{-1/6})$, while for $\theta = 3/2$, we get a more favorable width ratio of $\Theta(N^{-1/4})$.

On the other hand, CLT based CIs using RQMC are only asymptotically valid. The value of R could be any reasonable number that isn’t too small, and remains constant as the total sample size, N , increases. This means that $n = \Theta(N)$, which takes full advantage of the power of QMC. It is also important to note that both Betting and EB require the random variables to be bounded between 0 and 1, unlike CLT based CIs.

- [1] I. Waubdy-Smith and A. Ramdas. Estimating means of bounded random variables by betting. *J. Roy. Statist. Soc. B*, 86:1–27, 2024.
- [2] A. Maurer and M. Pontil. Empirical Bernstein bounds and sample variance penalization. In *Proceedings of the 22nd Annual Conference on Learning Theory (COLT)*, pages 1–9, 2009.

Wed, Jul 30 10:30-12:30

Sampling with constraints

Akash Sharma

Chalmers University of Technology, Sweden

`akashs@chalmers.se`

Coauthor(s): Benedict Leimkuhler, Michael Tretyakov

We will present first order and second order numerical integrators for reflected (overdamped) Langevin dynamics [1] and confined (underdamped) Langevin dynamics [2], respectively. We show how these SDEs can be used for sampling from a desired measure with compact support. We will also discuss sampling on hyper-surfaces. We will showcase numerical examples to verify the presented results.

- [1] B. Leimkuhler, A. Sharma, and M. V. Tretyakov. Simplest random walk for approximating Robin boundary value problems and ergodic limits of reflected diffusions. *Ann. Appl. Probab.*, 33(3):1904 – 1960, 2023.
- [2] B. Leimkuhler, A. Sharma, and M. V. Tretyakov. Numerical integrators for confined Langevin dynamics. *arXiv:2404.16584*, 2024.

Wed, Jul 30 10:30-12:30

Joonha Park

University of Kansas, Department of Mathematics
j.park@ku.edu

Hamiltonian Monte Carlo (HMC) is widely used for sampling from high-dimensional target distributions with probability density known up to proportionality. While HMC possesses favorable dimension scaling properties, it encounters challenges when applied to strongly multimodal distributions. Traditional tempering methods, commonly used to address multimodality, can be difficult to tune, particularly in high dimensions. In this study, we propose a method that combines a tempering strategy with Hamiltonian Monte Carlo, enabling efficient sampling from high-dimensional, strongly multimodal distributions. Our approach involves proposing candidate states for the constructed Markov chain by simulating Hamiltonian dynamics with time-varying mass, thereby searching for isolated modes at unknown locations. Moreover, we develop an automatic tuning strategy for our method, resulting in an automatically-tuned, tempered Hamiltonian Monte Carlo (ATHMC). Unlike simulated tempering or parallel tempering methods, ATHMC provides a distinctive advantage in scenarios where the target distribution changes at each iteration, such as in the Gibbs sampler. We numerically show that our method scales better with increasing dimensions than an adaptive parallel tempering method and demonstrate its efficacy for a variety of target distributions, including mixtures of log-polynomial densities and Bayesian posterior distributions for a sensor network self-localization problem.

Wed, Jul 30 10:30-12:30

Localized consensus-based sampling for non-Gaussian distributions*Arne Bouillon*

KU Leuven, Leuven, Belgium

arne.bouillon@kuleuven.be

Coauthor(s): Alexander Bodard, Panagiotis Patrinos, Dirk Nuyens, and Giovanni Samaey

Drawing samples distributed according to a given unnormalized probability density function is a common task in Bayesian inverse problems. Algorithms based on an ensemble of interacting *particles*, moving in parameter space, are gaining in popularity for these problems since they are often parallelizable, derivative-free, and affine-invariant. However, most are only accurate for near-Gaussian target distributions; an example is the consensus-based sampling (CBS) method [1]. We propose a novel way to derive CBS from ensemble-preconditioned Langevin diffusions by first approximating the target potential by its anisotropic Moreau envelope, then approximating the proximal operator by a weighted mean, and finally assuming that the initial and target distributions are Gaussian. We adapt these approximations with non-Gaussian distributions in mind and arrive at a new interacting-particle method for sampling, which we call *localized consensus-based sampling*. Numerical tests illustrate that localized CBS compares favorably to alternative methods in terms of affine-invariance and performance on non-Gaussian distributions.

- [1] Carrillo, J. A., Hoffmann, F., Stuart, A. M., & Vaes, U. (2022). Consensus-based sampling. *Studies in Applied Mathematics*, **148**(3), 1069–1140.

Wed, Jul 30 10:30-12:30

Importance Sampling for Hawkes Processes*Alex Shkolnik*

University of California, Santa Barbara

shkolnik@ucsb.edu

Coauthor(s): Baeho Kim

In 1971, Alan Hawkes [1] introduced a highly influential point process N for which, given a constant $\mu > 0$ and a $[0, \infty)$ -valued function g , the intensity process X takes the form,

$$X_t = \mu + \int_0^t g(t-s) dN_s, \quad (t \geq 0). \quad (5.2)$$

By now, Hawkes processes have found a wide array of application in the sciences, engineering, statistics, operations research, mathematical finance and machine learning. We develop importance sampling estimators for rare-event probabilities of the form $\mathbb{P}(N_t \geq ct)$ and

general functions g in (5.2). This problem has received little attention to date, as for most g , the process (N, X) is non-Markovian and lends to little mathematical tractability. Our approach is based on a Girsanov change of intensity coupled with a conditioning on the rare-event. We prove asymptotic optimality of the resulting importance sampling estimators in the limit $t \rightarrow \infty$. Related large deviations results and an extension to fully nonlinear models of N with intensity $\phi(X)$ are presented. Numerical simulations illustrate the performance of our importance sampling estimators relative to Monte Carlo for various functions g as well as to exponential tilting in the case of an exponential g (the sole tractable model).

- [1] Hawkes, A. G. (1971). *Spectra of some self-exciting and mutually exciting point processes*. Biometrika 58(1), 83–90.

Thu, Jul 31 15:30–17:30

Revisiting the Gibbs Sampler: A Conditional Modeling Perspective

Kun-Lin Kuo

Institute of Statistics, National University of Kaohsiung, Kaohsiung, Taiwan
 kllkuo@nuk.edu.tw

Coauthor(s): Yuchung J. Wang

The Gibbs sampler (GS) is a fundamental algorithm for approximating analytically intractable distributions. Two major generalizations of GS are the partially collapsed Gibbs sampler (PCGS) and the pseudo-Gibbs sampler (PGS). For PCGS, the associated Markov chain is heterogeneous with varying state spaces, making traditional convergence analysis challenging. To address this, we introduce the iterative conditional replacement (ICR) algorithm and prove its convergence. Furthermore, ICR provides a systematic approach for approximating multiple stationary distributions arising in PGS. Our approach emphasizes the advantage of treating each conditional density with its own operator, rather than aggregating all conditionals into a single operator.

Thu, Jul 31 15:30–17:30

Concatenation of Markov processes for Monte Carlo Integration

Sascha Holl

Max Planck Institute for Informatics
 sholl@mpi-inf.mpg.de

Coauthor(s): Hans-Peter Seidel

Markov Chain Monte Carlo (MCMC) is a sophisticated sampling technique used to sample from a probability distribution when conventional methods are impractical. Widely applied in statistics, machine learning, physics, and finance, MCMC generates samples from a probability distribution through an invariant Markov process. However, controlling and fine-tuning the process pose challenges, particularly in achieving both rapid local exploration and global distribution discovery. The Metropolis-Hastings algorithm, the most popular MCMC technique, while practical, struggles to excel in these objectives due to its inherent reversibility, leading to diffusive exploration and the need for large-scale perturbations for global discovery.

Wang et al. [2] introduced a novel MCMC approach, which is based on the concatenation of Markov processes [1]. It allows the usage of an essentially arbitrary Markov process for local exploration. That way, the process can be chosen to satisfy a desired exploration behavior suitable for the state space at hand without worrying about invariance at this point. The process is executed up to a certain finite lifetime. After this time has elapsed, the process is *killed* and started afresh at a spawn location drawn from a *regeneration* distribution. The lifetime is chosen in a way ensuring that the overall process is invariant with respect to a given target distribution.

We generalize this idea and introduce it with appropriate rigor. We show how the validity of the method can be established for a more general class of Markov processes. We also allow the usage of a whole family of Markov processes for local exploration with possibly varying exploration characteristic. We establish a transfer mechanism between consecutive processes, which allows the user to specify the initial state of the newly spawned process to depend on the exit point of the previous one. Not least, we derive a Rao-Blackwellization technique which guarantees variance reduction in practice. We showcase the potential of the framework in a practical rendering experiment. We compare the method proposed in [2] with existing methods based on Metropolis-Hastings algorithms with Random-Walk, Langevin and Hamiltonian proposals, respectively.

- [1] Sharpe, Michael (1998). *General Theory of Markov Processes*. Pure and Applied Mathematics. Academic Press.
- [2] Wang, Andi Q. and Pollock, Murray and Roberts, Gareth O. and Steinsaltz, David. Regeneration-enriched Markov processes with application to Monte Carlo. The Annals of Applied Probability. Institute of Mathematical Statistics.

Thu, Jul 31 15:30–17:30

Polynomial approximation for efficient transport-based sampling*Josephine Westermann*

Heidelberg University

josephine.westermann@uni-heidelberg.de

Sampling from non-trivial probability distributions is a fundamental challenge in uncertainty quantification and inverse problems, particularly when dealing with high-dimensional domains, costly-to-evaluate or unnormalized density functions, and non-trivial support structures. Measure transport via polynomial density surrogates [1] provides a systematic and constructive solution to this problem by reformulating it as a convex optimization task with deterministic error bounds. This approach is particularly efficient for smooth problems but can become computationally demanding when dealing with highly concentrated posterior distributions, as constructing the density surrogate requires many evaluations in regions where the density is nearly zero—leading to an inefficient allocation of computational resources. In this talk, we explore how the computational cost in such cases can be further reduced by first approximating the potential function with a polynomial. This additional approximation step shifts the focus of expensive evaluations toward capturing the underlying system more effectively. The surrogate-based posterior can then be evaluated cheaply and approximated with high accuracy, enabling efficient transport-based sampling. We discuss the implications of this strategy and examine its potential to enhance performance in demanding inference problems.

- [1] Westermann, J., & Zech, J. (2025). *Measure transport via polynomial density surrogates*. *Foundations of Data Science*. <https://doi.org/10.3934/fods.2025001>

Thu, Jul 31 15:30–17:30

Fast Approximate Matrix Inversion via MCMC for Linear System Solvers*Soumyadip Ghosh*

IBM Research

ghoshs@us.ibm.com

Coauthor(s): Vassil Alexandrov, Lior Horesh, Vasilios Kalantzis, Anton Lebedev, WonKyung Lee, Yingdong Lu, Tomasz Nowicki, Shashanka Ubaru, Olha Yaman

A key prerequisite of modern iterative solvers of linear algebraic equations $Ax = b$ is the fast computation of a pre-conditioner matrix P that gives a good approximation to the (generalized) inverse of A such that the set of equations obtained by pre-multiplying with P , $P Ax = P b$, is solved quickly. We study the classical Ulan-von Neumann MCMC algorithm that was designed based on the Neumann infinite series representation of the inverse of a non-singular matrix. The parameters of the MCMC algorithm determine the overall time to solve

$Ax = b$, which is a metric that reflects both the time to compute the MCMC preconditioner P and its quality as a preconditioner to solve the linear equations. Our main focus is on how the MCMC parameters should be tuned to speed up computations in applications that require repeated calls to the solver with varying matrices A , a common scenario for instance in numerical approximations of physical phenomena. We present a model that relates key features of matrices A with good choices of MCMC algorithm parameters that lead to a fast overall time to find a solution to $Ax = b$. A computationally efficient approach based on Bayesian experimental design is described to learn and update this model while minimizing the number of runs of the expensive solver in application settings that solve of linear system over well defined sets of A matrices. We present numerical experiments to illustrate the efficacy of this approach. In another contribution, we present a new MCMC algorithm which we term as *regenerative Ulam-von Neumann* algorithm. It exploits a regenerative structure present in the Neumann series that underlies the original algorithm and improves on it by producing an unbiased estimator of the matrix inverse. A rigorous analysis of performance of the algorithm is provided. This includes the variance of the estimator, which allows one to estimate the time taken to obtain solutions of a desired quality. Finally, numerical experiments verify the qualitative effectiveness of the proposed scheme.

Thu, Jul 31 10:30–12:30

The Stochastic Differential Equations of the Heston Model for Option Pricing

Abdujabar Rasulov

Professor of the University of World Economy and Diplomacy
asrasulov@gmail.com

Coauthor(s): Matyokub Bakoev

The Heston model is a widely used stochastic volatility model for option pricing, addressing the limitations of the Black-Scholes model by incorporating a stochastic variance process. This talk will cover the stochastic differential equations (SDEs) governing the Heston model, demonstrating their application in option pricing.

The Heston model introduces a stochastic process for volatility, improving the accuracy of derivative pricing. The dynamics of the asset price S_t and its variance v_t under the Heston model are given by[1]:

$$dS_t = \mu S_t dt + \sqrt{v_t} S_t dW_t^S, \quad (5.3)$$

$$dv_t = \kappa(\theta - v_t)dt + \sigma\sqrt{v_t}dW_t^v, \quad (5.4)$$

where:

- μ is the drift of the asset price.
- κ is the rate of mean reversion of variance v_t towards long-term mean θ .
- σ represents the volatility of volatility.

- dW_t^S and dW_t^v are Wiener processes with correlation ρ .

We will explore Monte Carlo methods as a numerical approach to simulate price paths and compute option prices for European and American derivatives [2],[3]. Furthermore, an interactive Shiny web application will be presented, showcasing real-time simulations and visualizations of option pricing under the Heston framework.

An interactive web-based application is implemented using Shiny in R, enabling users to:

- Adjust input parameters $(S_0, K, r, T, \mu, \theta, \kappa, \sigma, \rho)$.
- Perform Monte Carlo simulations to compute option prices.
- Visualize option price distributions and convergence results.

The Shiny application offers an interactive tool for financial analysis. Future work may explore enhancements such as incorporating jump-diffusion models and GPU-accelerated simulations.

1. Hull, J. C. (2020). *Options, Futures, and Other Derivatives*. Pearson.
2. Glasserman, P. (2004). *Monte Carlo Methods in Financial Engineering*. Springer.
3. M.T.Bakoev (2020) Numerical simulation of solutions of diffusion equations in problems of finance and management(In russian) . Uwed Press.Tashkent 2020. p.224.

Thu, Jul 31 10:30–12:30

Characterizing Efficacy of Geometric Brownian Motion Expectation-based Simulations on Low-Volatility American Common Stocks

Vincent X Zhang

University of Southern California
vxzhang@usc.edu

Coauthor(s): Heather Choi

In this manuscript, daily, monthly, and annual geometric Brownian motion forecasts are obtained and tested for reliability upon 21 stock symbols within NASDAQ of varying volatilities and drifts. Biweekly, monthly, biannual, and annual rolling windows were used as a preliminary filtering scheme to remove unreliable stock symbols, and then accuracy was further evaluated on stocks with higher accuracies in the first screening. Annual and 10-year windows were used to estimate the drift and diffusion component and then applied to obtain one-period-ahead geometric Brownian motion stock values and associated probabilities. Further building off of these one-period-ahead values, expected values for 1-252 periods were estimated. Expected values of each stock were estimated by totaling up the product of the stock value and its associated probabilities, and tested over multiple rolling-windows for reliability. The results indicate that geometric Brownian-simulated expected index values estimated using one thousand simulations can be slightly reliable if catered and re-optimized

to specific stock characterizations, but only for a daily window, and even then only slightly preferable to flipping a coin. Expected values estimated with less than 100 simulations were thrown out, seen as unreliable.

- [1] Sinha, A. (2024). Daily and Weekly Geometric Brownian Motion Stock Index Forecasts. *Journal of Risk and Financial Management*, 17(10), 434. <https://doi.org/10.3390/jrfm17100>
- [2] Abbas, Anas, and Mohammed Alhagyan. 2023. Forecasting exchange rate of sar/cny by incorporating memory and stochastic volatility into gbm model. *Advances and Applications in Statistics* 86: 65–78
- [3] Demirel, Ugur, Handan Cam, and Ramazan Unlu. 2021. Predicting Stock Prices Using Machine Learning Methods and Deep Learning Algorithms: The Sample of the Istanbul Stock Exchange. *Gazi University Journal of Science* 34: 63–82
- [4]] Tie, Jingzhi, Hanqin Zhang, and Qing Zhang. 2018. An Optimal Strategy for Pairs Trading Under Geometric Brownian Motions. *Journal of Optimization Theory and Applications* 179: 654–75
- [5] Ramos, André Lubene, Douglas Batista Mazzinghy, Viviane da Silva Borges Barbosa, Michel Melo Oliveira, and Gilberto Rodrigues da Silva. 2019. Evaluation of an Iron Ore Price Forecast Using a Geometric Brownian Motion Model. *Revista Escola de Minas* 72: 9–15
- [6] Nordin, Norazman, Norizarina Ishak, Nurfadhlin Abdul Halim, Siti Raihana Hamzah, and Ahmad Fadly Nurullah Rasadee. 2024. A Geometric Brownian Motion of ASEAN-5 Stock Indexes. In *AI and Business, and Innovation Research: Understanding the Potential and Risks of AI for Modern Enterprises*. Edited by Bahaaeddin Alareeni and Islam Elgedawy. New York: Springer, pp. 779–86
- [7] W Farida Agustini et al 2018 *J. Phys.: Conf. Ser.* 974 012047
- [8] Liang, W., Li, Z., Chen, W. (2025). Enhancing Financial Market Predictions: Causality-Driven Feature Selection. In: Sheng, Q.Z., et al. *Advanced Data Mining and Applications. ADMA 2024. Lecture Notes in Computer Science()*, vol 15387. Springer, Singapore. https://doi.org/10.1007/978-981-96-0811-9_11
- [9] Prasad, Krishna, Bhuvana Prabhu, Lionel Pereira, Nandan Prabhu, and Pavithra S. 2022. Effectiveness of geometric brownian motion method in predicting stock prices: Evidence from india. *Asian Journal of Accounting and Governance* 18: 121–34
- [10] Shaffi, Nor Hayati, Nur Ezzati, Dayana Mohd, Rohana Alias, Nur Fatihah Fauzi, and Mathematical Sciences. 2019. Fuzzy Time Series and Geometric Brownian Motion in Forecasting Stock Prices in Bursa Malaysia. *Jurnal Intelek* 14: 240–50
- [11] Zhu, Song-Ping, and Xin-Jiang He. 2018. A New Closed-Form Formula for Pricing European Options under a Skew Brownian Motion. *The European Journal of Finance* 24: 1063–74

Thu, Jul 31 10:30–12:30

Efficient Pricing for Variable Annuity via Simulation*Hao Quan*

University of Waterloo

h5quan@uwaterloo.ca

Coauthor(s): Ben (Mingbin) Feng

Variable Annuities (VAs) are insurance products that offer policyholders exposure to financial market upside potential while safeguarding against downside risk through optional riders, such as Guaranteed Minimum Death Benefits (GMDBs), Guaranteed Minimum Accumulation Benefits (GMABs), and Guaranteed Minimum Withdrawal Benefits (GMWBs). These riders, tailored to policyholders' needs, introduce a complex risk profile combining mortality and financial uncertainties, rendering VA pricing and fee determination computationally challenging. Due to this complexity, Monte Carlo simulation is often the only practical approach for valuing these contracts.

In this study, we address the problem of setting fair management fees for VA rider combinations using the equivalence principle, which balances the expected present value of premiums and benefits. We formulate fee determination as a stochastic root-finding problem, expressed as

$$E[V(\varphi)] - P = 0,$$

where $E[V(\varphi)]$ denotes the expected present value of VA benefits under fee structure φ , and P represents the premium. The VA benefit $V(\varphi)$ reflects the evolution of the contract's shadow account value and various benefit guarantees over the contract's lifetime. As a result, estimating its expected value is computationally challenging. Moreover, solving the root-finding problem requires estimating the gradient of this expectation. To solve this, we employ stochastic gradient estimation techniques, such as finite differences and infinitesimal perturbation analysis (IPA). We analyze the theoretical properties and computational performance of the proposed root-finding algorithms, offering insights into their efficacy for VA pricing. Our results show that gradient estimation techniques have a significant impact on the efficiency and accuracy of estimating fair fees for various rider combinations.

Fri, Aug 1 09:00–10:30

Revisiting self-normalized importance sampling: new methods and diagnostics*Nicola Branchini*

University of Edinburgh

n.branchini@sms.ed.ac.uk

Coauthor(s): Víctor Elvira

Importance sampling (IS) can often be implemented only with normalized weights, yielding the popular self-normalized IS (SNIS) estimator. However, proposal distributions are often

learned and evaluated using criteria designed for the unnormalized IS (UIS) estimator.

In this talk, we aim to present a unified perspective on recent methodological advances in understanding and improving SNIS. We propose and compare two new frameworks for adaptive importance sampling (AIS) methods tailored to SNIS. Our first framework exploits the view of SNIS as a ratio of two UIS estimators, coupling two separate AIS samplers in a joint distribution selected to minimize asymptotic variance. Our second framework instead proposes the first MCMC-driven AIS sampler directly targeting the (often overlooked) optimal SNIS proposal.

We also establish a close connection between the optimal SNIS proposal and so-called subtractive mixture models (SMMs), where negative coefficients are possible - motivating the study of the properties of the first IS estimators using SMMs.

Finally, we propose new Monte Carlo diagnostics specifically for SNIS. They extend existing diagnostics for numerator and denominator by incorporating their statistical dependence, drawing on different notions of tail dependence from multivariate extreme value theory.

- [1] Branchini, N., & Elvira, V. (2024). Generalizing self-normalized importance sampling with couplings. arXiv preprint arXiv:2406.19974.
- [2] Branchini, N., & Elvira, V. (2025). Towards adaptive self-normalized importance samplers. In submission at Statistical Signal Processing Workshop (SSP), 2025.
- [3] **Zellinger, L. & Branchini, N. (equal contribution)**, Elvira, V., & Vergari, A. Scalable expectation estimation with subtractive mixture models. In submission at Frontiers in Probabilistic Inference: Learning meets Sampling (workshop at ICLR 2025).
- [4] Branchini, N., & Elvira, V. The role of tail dependence in estimating posterior expectations. In NeurIPS 2024 Workshop on Bayesian Decision-making and Uncertainty.

Fri, Aug 1 09:00–10:30

Quantitative results on sampling from quasi-stationary distributions

Daniel Yukimura

IMPA, Rio de Janeiro, Brazil

yukimura@impa.br

Coauthor(s): Roberto I. Oliveira

We study the rate of convergence of Sequential Monte Carlo (SMC) methods for approximating the quasi-stationary distribution (QSD) of Markov processes. For processes with killing or absorption, the QSD appears as a stable behavior observed before extinction, or as the limiting distribution of the process conditioned on not being absorbed. We give quantitative lower and upper bounds for the particle filter approximation of these distributions. For the lower bound, we show that fast mixing is not enough to guarantee that simulation methods can converge in few steps. In the upper bound, we show that SMC with adaptive resampling

has a rate depending on the number of steps, the mixing time, and in how fast the processed gets killed. Our seems to be the first result to have a quantitative dependency of this form that is valid for discrete time Markov chains in general state spaces. Our techniques and concentration results for bounding the approximations of SMC with adaptive resampling are also novel, and we believe might be applicable in other scenarios that can benefit from the lower variance obtained due to an adaptive approach.

Fri, Aug 1 09:00–10:30

Serial ensemble filtering with marginal coupling

Amit N Subrahmanya

Virginia Tech

amitns@vt.edu

Coauthor(s): Julie Bessac, Andrey A Popov, Adrian Sandu

Serial filtering refers to a univariate, state by state Bayesian inference problem. Extant methods for serial filtering result in suboptimal posterior samples for severely non-Gaussian, multimodal inference settings. We fix this problem by rigorously coupling the state marginal densities with information about their joint density. This formulation allows for accurately sampling the Bayesian posterior across a variety of challenging text problems.

Wed, Jul 30 14:00–16:00

Stochastic gradient Langevin dynamics with non-stationary data

*Attila Lovas*¹

attila.lovas@gmail.com

LionelTruquet

We investigate the mixing properties of the stochastic gradient Langevin dynamics (SGLD) algorithm with a fixed step size. While most existing studies on SGLD assume an i.i.d. data stream, this assumption is often unrealistic in practical applications, such as financial time series analysis, natural language processing, and sensor data processing. In such settings, the sequence of iterates no longer forms a Markov chain, significantly complicating the mathematical analysis [1, 2].

¹The author was supported by the National Research, Development and Innovation Office within the framework of the Thematic Excellence Program 2021; National Research subprogram “Artificial intelligence, large networks, data security: mathematical foundation and applications” and also by the grant K 143529.

To address this challenge, we model the iterates as a Markov chain in a random environment (see [4, 5], and [6]). Under standard dissipativity and Lipschitz conditions, we establish the transfer of α -mixing properties from the data stream to the sequence of iterates [3]. This enables us to derive key theoretical results, including the law of large numbers, the central limit theorem, and concentration inequalities for SGLD in the non-convex setting. Our findings provide theoretical guarantees for SGLD in a more realistic scenario where the data merely weakly dependent.

- [1] Barkhagen, M., Chau, N. H., Moulines, É., Rásonyi, M., Sabanis, S., & Zhang, Y. (2021). On stochastic gradient Langevin dynamics with dependent data streams in the logconcave case.
- [2] Chau, N. H., Moulines, É., Rásonyi, M., Sabanis, S., & Zhang, Y. (2021). On stochastic gradient langevin dynamics with dependent data streams: The fully nonconvex case. *SIAM Journal on Mathematics of Data Science*, **3**(3), 959-986.
- [3] Lovas, A. (2024). Transition of α -mixing in Random Iterations with Applications in Queuing Theory. arXiv preprint arXiv:2410.05056.
- [4] Lovas, A., & Rásonyi, M. (2023). Functional Central Limit Theorem and Strong Law of Large Numbers for Stochastic Gradient Langevin Dynamics. *Applied Mathematics & Optimization*, **88**(3), 78.
- [5] Lovas, A., & Rásonyi, M. (2021). Markov chains in random environment with applications in queuing theory and machine learning. *Stochastic Processes and their Applications*, 137, 294-326.
- [6] Rásonyi, M., & Tikosi, K. (2022). On the stability of the stochastic gradient Langevin algorithm with dependent data stream. *Statistics & Probability Letters*, 182, 109321.

Wed, Jul 30 14:00–16:00

Archimedes/Athena Research Centre and National Technical University of Athens

i.lytras@athenarc.gr

Tim Johnston, Nikos Makras, Sotirios Sabanis

In this article, we study the problem of sampling from distributions whose densities are not necessarily smooth nor log-concave. We propose a simple Langevin-based algorithm that does not rely on popular but computationally challenging techniques, such as the Moreau Yosida envelope or Gaussian smoothing. We derive non-asymptotic guarantees for the convergence of the algorithm to the target distribution in Wasserstein distances. Non asymptotic bounds are also provided for the performance of the algorithm as an optimizer, specifically for the solution of associated excess risk optimization problems.

Possible extensions to potentials with log-gradients that grow super-linearly may also be discussed.

This is based on the joint work in [1].

- [1] Johnston, T., Lytras, I., Makras, N., Sabanis, S. (2025). The Performance Of The Unadjusted Langevin Algorithm Without Smoothness Assumptions. arXiv preprint arXiv:2502.03458.

Wed, Jul 30 14:00–16:00

Langevin-based strategies for nested particle filters

Sara Pérez-Vieites

Aalto University

sara.perezvieites@aalto.fi

Coauthor(s): Nicola Branchini, Víctor Elvira and Joaquín Míguez

Many problems in some of the most active fields of science require to estimate parameters and predict the evolution of complex dynamical systems using sequentially collected data. The nested particle filter (NPF) framework stands out since it is the only fully recursive probabilistic method for Bayesian inference. That is, it computes the joint posterior distribution of the parameters and states while maintaining a computational complexity of $\mathcal{O}(T)$, which makes it particularly suitable for long observation sequences.

A key strategy to keep particle diversity in the parameter space, given the static nature of the parameters, is jittering. The parameter space is explored by perturbing a subset of particles with arbitrary variance or applying a controlled variance to all particles. As the perturbations are controlled, it ensures convergence to the true posterior distribution while keeping the full framework recursive. However, this is not an efficient exploration strategy, particularly for problems with a higher dimension in the parameter space.

To address this limitation, we propose a Langevin-based methodology within the NPF framework. A challenge is that the required score function is intractable. We propose to approximate the score with an accurate method that is provably stable over time, and to explore strategies to reduce its computational cost while retaining accuracy. This approach significantly improves the scalability of NPF in the parameter dimension, while still ensuring asymptotic convergence to the true posterior, as well as maintaining computational feasibility.

Wed, Jul 30 14:00–16:00

Taming the Interacting Particle Langevin Algorithm – The Superlinear Case*Nikolaos Makras*

University of Edinburgh, School of Mathematics

N.Makras@sms.ed.ac.uk

Coauthor(s): Tim Johnston, Sotirios Sabanis

Recent advances in stochastic optimization have yielded the interacting particle Langevin algorithm (IPLA), which leverages the notion of interacting particle systems (IPS) to efficiently sample from approximate posterior densities. This becomes particularly crucial in relation to the framework of Expectation-Maximization (EM), where the E-step is computationally challenging or even intractable. Although prior research has focused on scenarios involving convex cases with gradients of log densities that grow at most linearly, our work extends this framework to include polynomial growth. Taming techniques are employed to produce an explicit discretization scheme that yields a new class of stable, under such non-linearities, algorithms which are called tamed interacting particle Langevin algorithms (tIPLA). We obtain non-asymptotic convergence error estimates in Wasserstein-2 distance for the new class under the best known rate.

- [1] Tim Johnston, Nikolaos Makras and Sotirios Sabanis, *Taming the Interacting Particle Langevin Algorithm – The Superlinear Case* (2024). Preprint: arxiv:2403.19587

Thu, Jul 31 15:30-17:30

Dynamical Low-Rank Approximation for SDEs: an interacting particle-system ROM*Fabio Zoccolan*

École Polytechnique Fédérale de Lausanne

fabio.zoccolan@epfl.ch

Coauthor(s): Dr. Yoshihito Kazashi, Prof. Fabio Nobile

The Dynamical Low-Rank Approximation (DLRA) technique is a time-dependent reduced-order model (ROM) known for its significant advantages in terms of computational time and accuracy. Its appeal in uncertainty quantification is due to the fact that its solution is composed of time-dependent deterministic and stochastic bases, allowing the approximation to better track the dynamics of the studied system. In the context of stochastic differential equations (SDEs) a rigorous mathematical setting was presented in [1], using the so-called Dynamically Orthogonal (DO) framework. The well-posedness of this setting is nontrivial due to the coupled nature of the DO system: for instance, the deterministic basis depends on all stochastic basis paths, and the equations involve the inversion of a Gramian matrix.

When coming to stochastic discretization through a Monte-Carlo procedure, these features imply to deal with a interacting noisy particle dynamics. We proposed two fully discretized schemes based on the Monte-Carlo method, investigating their errors and analyzing possible issues arisen by the discretization of the Gramian inverse [2]. Theoretical results will be supported by numerical simulations.

- [1] Yoshihito Kazashi, Fabio Nobile, and Fabio Zoccolan. *Dynamical low-rank approximation for stochastic differential equations*. Mathematics of Computation (2024).
- [2] Yoshihito Kazashi, Fabio Nobile, and Fabio Zoccolan. *Numerical Methods for Dynamical low-rank approximation of stochastic differential equations, Part I & II*, in preparation (2025).

Thu, Jul 31 15:30-17:30

Anke Wiese

Heriot-Watt University, UK

A.Wiese@hw.ac.uk

KuruschEbrahimi--Fard, Fr{\unhbox\voidb@x\bgroup\let\unhbox\voidb@x\setbox\@tempboxa\hbox{e\global\mathchardef\accent@spacefactor\spacefactor}\let\begin\group\let\typeout\protect\begin\group\def\MessageBreak{\Omega(Font)}\let\protect\immediate\write\m@ne{LaTeXFontInfo: oninputline1089.}\endgroup\endgroup\relax\let\ignorespaces\relax\accent19e\egroup\spacefactor\accent@spacefactor}d{\unhbox\voidb@x\bgroup\let\unhbox\voidb@x\setbox\@tempboxa\hbox{e\global\mathchardef\accent@spacefactor\spacefactor}\let\begin\group\let\typeout\protect\begin\group\def\MessageBreak{\Omega(Font)}\let\protect\immediate\write\m@ne{LaTeXFontInfo: oninputline1089.}\endgroup\endgroup\relax\let\ignorespaces\relax\accent19e\egroup\spacefactor\accent@spacefactor}ricPatras

Stochastic differential equations driven by Lévy processes have become established as models to describe the evolution of random variables such as financial and economic variables and more recently of climate variables, when the stochastic system shows jump discontinuities. In this talk, we derive a novel series representation of the flowmap of such stochastic differential equations in terms of commutators of vector fields with stochastic coefficients, in other words a Chen–Strichartz formula. We provide an explicit expression for the components in this series. Our results extend previous results for deterministic and continuous stochastic differential equations.

Thu, Jul 31 15:30-17:30

Comparing Probabilistic Load Forecasters: Stochastic Differential Equations and Deep Learning

Riccardo Saporiti

EPFL, Lausanne, Switzerland

riccardo.saporiti@epfl.ch

Coauthor(s): Fabio Nobile, Celia García-Pareja

Generating probabilistic predictions for the electricity-load profile is the foundation of efficient use of renewable energy and diminishing carbon footprint.

In this talk, we consider the problem of creating probabilistic forecasts of the day-ahead electricity consumption profile of an agglomerate of buildings in the city of Lausanne (Switzerland) in the absence of an externally provided prediction function.

We propose a nonparametric, data-driven, approach based on Itô' Stochastic Differential Equations (SDEs) [1]. Our work is novel in that the mean function of the SDE is expanded on a Fourier periodic basis, capturing intra-day and intra-week periodic features. Using a derivative tracking term, we impose the trajectories of the process to revert toward the mean. To model high-volatility levels associated with more uncertain electricity consumption regimes, we employ a square-root type diffusion coefficients.

Maximum-Likelihood estimation is used to infer the parameters of the model coherently with the available observations of the time history. We show that the maximization problem is well posed and that it admits at least one solution over the feasible domain.

We compare the probabilistic predictions generated by the SDE with Deep Learning based probabilistic forecaster. On the one hand, we introduce a Deep Learning forecaster based on Long short-term memory (LSTM) recurrent neural networks trained by minimizing the quantile loss function. This approach allows the generation of confidence intervals by sampling from the one-step-ahead univariate cumulative density function (CDF) associated with the electricity consumption of the future time instant. On the other hand, inspired by [2], we consider Multivariate Quantile Function Forecasters that, based on Normalizing Flows, learn the multivariate cumulative density function of the day-ahead electricity consumption.

Metrics such as Continuous ranked probability score and Prediction interval coverage percentage are used to assess the quality of the forecasts.

We show that SDEs generate reliable and interpretable predictions while presenting the most parsimonious and computationally efficient structure among the three models.

- [1] Riccardo Saporiti, Fabio Nobile, Celia García-Pareja. *Probabilistic Forecast of the Day-Ahead electricity consumption profile with Stochastic Differential Equations: a comparison with Deep Learning models*. In preparation.
- [2] Kelvin Kan, Francois-Xavier Aubet, Tim Januschowski, Youngsuk Park, Konstantinos Benidis, Lars Ruthotto, and Jan Gasthaus (2022). *Multivariate Quantile Function Forecaster*. Proceedings of The 25th International Conference on Artificial Intelligence and Statistics, PMLR 151:10603-10621, 2022.

Thu, Jul 31 15:30-17:30

Forward Propagation of Low Discrepancy Through McKean–Vlasov Dynamics: From QMC to MLQMC*Leon Wilkosz*

King Abdullah University of Science and Technology (KAUST)

`leon.wilkosz@kaust.edu.sa`

Coauthor(s): Nadhir Ben Rached, Abdul-Lateef Haji-Ali, Raul Tempone

This work develops a particle system addressing the approximation of McKean–Vlasov stochastic differential equations (SDEs). The novelty of the approach lies in involving low discrepancy sequences nontrivially in the construction of a particle system with coupled noise and initial conditions. Weak convergence for SDEs with additive noise is proven. A numerical study demonstrates that the novel approach presented here doubles the respective convergence rates for weak and strong approximation of the mean-field limit, compared with the standard particle system. These rates are proven in the simplified setting of a mean-field ordinary differential equation in terms of appropriate bounds involving the star discrepancy for low discrepancy sequences with a group structure, such as Rank-1 lattice points. This construction nontrivially provides an antithetic multilevel quasi-Monte Carlo estimator. An asymptotic error analysis reveals that the proposed approach outperforms methods based on the classic particle system with independent initial conditions and noise.

Mon, Jul 28 15:30-17:30

A probabilistic Numerical method for semi-linear elliptic Partial Differential Equations

Adrien Richou

adrien.richou@math.u-bordeaux.fr

EmmanuelGobet, CharuShardul, LukaszSzpruch

In this presentation, we study the numerical approximation of a class of Backward Stochastic Differential Equations (BSDEs) in an infinite horizon setting that provide a probabilistic representation for semi-linear elliptic Partial Differential Equations. In particular, we are also able to treat some ergodic BSDEs that are related to elliptic PDEs or ergodic type. In order to build our numerical scheme, we put forward a new representation of the PDE solution by using a classical probabilistic representation of the gradient. Then, based on this representation, we propose a fully implementable numerical scheme using a Picard iteration procedure, a grid space discretization and a Monte-Carlo approximation. We obtain an upper bound for the numerical error and we also provide some numerical experiments that show the efficiency of this approach for small dimensions. Some numerical experiments also show that it is possible to efficiently handle larger dimensions by replacing grid-based spatial discretization with neural networks. This presentation is based on [1] for the non ergodic framework and [2] for results concerning the ergodic case.

- [1] Gobet, Emmanuel, & Richou, Adrien, & Shardul, Charu (2025). Numerical approximation of Markovian BSDEs in infinite horizon and elliptic PDEs. Draft.
- [2] Gobet, Emmanuel, & Richou, Adrien, & Szpruch, Lukasz (2025). Numerical approximation of ergodic BSDEs using non linear Feynman-Kac formulas, Preprint arXiv:2407.09034 .

Mon, Jul 28 15:30-17:30

Abdujabar Rasulov

University of world economy and diplomacy

E mail: asrasulov@gmail.com

As is known, the nonlinear Boltzmann equation describes the behavior of rarefied gas much better than the linear Kac's [1] model. That is why we can expect that application of the nonlinear spatially homogenous Boltzmann equation to the Harlow's "particles-in-cell" model [2] allows us to do a computation, which gives a more exact approximation of the solution. Among the statistical methods [3], which use Monte Carlo directly for modeling the flow of rarefied gas, the most efficient one is the statistical method of direct modeling the nonstationary flow. In the known "particle-in-cell" method, the simulations divide into

two steps. Monte Carlo method is used both for the numerical simulation of collisions of the particles in cells (the first step), as well as for the collision-free moving of particles (the second step). In this work we propose another computational scheme, which directly uses the non-linear spatially homogenous Boltzmann equation for the numerical realization of the first step in the “particles-in-cell” model of Belotserkovski-Yanitskii [3]. Proposed a new approach of constructing unbiased estimators will give relatively small variance. For this aim we construct a branching Markov process [4] and on its trajectory we propose various “conjugated” computational schemes for calculating an unbiased estimator of the given functional. It should be noted nowadays in this area became popular adjoint direct simulation Monte Carlo method to a general collision kernel [5]. The results of our computations show that they are similar with known Belotserkovski-Yanitskii solutions of the Boltzmann equation. We note that in the interval, where the Boltzmann equations “work” (intermediate interval), the “particle-in-cell” statistical model approximates the spatially heterogeneous Boltzmann equation better.

References

- [1] Kac, Mark (1959). *Probability and Related Topics in Physical Science*. American Mathematical Society (AMS).
- [2] Harlow, Harvey F. (1964). The Particle-in-Cell Computing Method for Fluid Dynamics. *Methods in Computational Physics* **3**, 319–343
- [3] Belotserkovskii, Oleg M., & Yanitskii, Vitaliy .E., (1975). The Statistical Method of Particles in Cells in Rarefied Gas Dynamics”, *USSR Computational Mathematics and Mathematical Physics*, **15**(5), 101-114
- [4] Ermakov, Sergey M., Nekrutkin, Vladimir V., & Sipin, Aleksandr S. (1989). *Random Processes for Classical Equations of Mathematical Physics*, Kluwer Academic Publishers.
- [5] Yang, Yunan, Silantyev, Denis, & Caflisch, Russel (2023). The Particle-in-Cell Computing Method for Fluid Dynamics. *Methods in Computational Physics* **448**, 112247

Mon, Jul 28 15:30-17:30

A New Approach for Unbiased Estimation of Parameters of Partially Observed Diffusions

Miguel Alvarez

King Abdullah University of Science and Technology (KAUST)

miguelangel.alvarezballesteros@kaust.edu.sa

Coauthor(s): Ajay Jasra

In this talk, we consider the estimation of static parameters for a partially observed diffusion process with discrete-time observations over a fixed time interval. We develop particle filtering methods using time-discretization schemes, and we employ particle Markov chain Monte Carlo methods to estimate the smoothing distribution. In particular, we use backward sam-

pling to address the issue of sample degeneracy. We use the score function and stochastic gradient ascent methods to maximize the likelihood of the observations. Parameter estimation in the diffusion term is possible by introducing bridge processes and the corresponding bridge-guiding proposals. To achieve an unbiasedness, we adopt the Rhee and Glynn approach [1], in which the sources of bias are the number of stochastic gradient ascent steps and the time-discretization. Finally, we display numerically the method applying it to two systems.

- [1] Rhee, C. H, & Glynn, H. (2015). Unbiased estimation with square root convergence for SDE models, *Op. Res.*, **63**, 1026–1043.

Mon, Jul 28 15:30-17:30

High-order adaptive methods for exit times of diffusion processes and reflected diffusions

Håkon Hoel

University of Oslo

haakonah@math.uio.no

The Feynman–Kac formula connects domain-exit and boundary-reflection properties of stochastic differential equations (SDEs) and parabolic partial differential equations. The SDE viewpoint is particularly interesting for numerical methods, as it can be used with Monte Carlo methods to overcome the curse of dimensionality when solving high-dimensional PDE. This however hinges on having an efficient numerical method for simulating the exit times of SDEs. Since exit times of diffusion processes are very sensitive to perturbations in initial conditions, it is challenging to construct such numerical methods.

This talk presents a high-order method with adaptive time-stepping for strong approximations of exit times. The method employs a high-order Itô–Taylor scheme for simulating SDE paths and carefully decreases the step size in the numerical integration as the diffusion process approaches the domain’s boundary. These techniques complement each other well: adaptive time-stepping improves the accuracy of the exit time by reducing the overshoot out of the domain, and high-order schemes improve the state approximation of the diffusion process, which is useful feedback to control the step size. We will also consider an ongoing extension of the numerical method to reflected diffusions.

Thu, Jul 31 10:30-12:30

Learning cooling strategies in simulated annealing through binary interactions*Frédéric Blondeel*

KULeuven & UniFe

`frederic.blondeel@kuleuven.be`

Coauthor(s): Lorenzo Pareschi, Giovanni Samaey

Global optimization is amongst the hardest to solve problems. This is because finding the global minimum can usually only be guaranteed to be found in infinite time. Therefore one usually relies on meta-heuristic algorithms to guide the search and improve chances of successfully identifying the minimum. One particular family of algorithms is simulated annealing (SA). This family of algorithms is inspired by real-world metallurgy and is based on the Metropolis-Hastings algorithm. It works by randomly sampling N particles on the search space, each with a given temperature T . The movement of these particles is analogous to a Brownian random walk with step size proportional to temperature. The temperature is gradually cooled down over the course of the simulation according to some predefined schedule. Due to the Metropolis-Hastings-like acceptance-rejection rule, these particles can jump out of local minima and are expected to move towards the lowest energy state, i.e., the global minimum. It is the design of these cooling schedules for SA that we wish to improve. This is because they directly impact the efficiency of the optimization tool. Typically cooling schedules are inverse logarithmic or geometric decays in time. Here, we consider a collective SA dynamic where particles *interact* to learn the optimal temperature cooling strategy. This is inspired by the well-known particle-swapping technique known as parallel tempering (PT). To this aim we introduce a Boltzmann-type description where particles (partially) exchange their temperatures, therefore slowly cooling down the overall mean temperature. In order to simulate the dynamic we use a direct simulation Monte Carlo (DSMC) algorithm known as Nanbu-Babovsky. We show on various test functions (Ackley, Rastrigin, etc.) that this novel approach outperforms the standard SA with logarithmic and geometric annealing schedules.

Thu, Jul 31 10:30-12:30

Accuracy of Discretely Sampled Stochastic Policies in Continuous-Time Reinforcement Learning*Du Ouyang*

Department of Mathematical Sciences, Tsinghua University

`oyd21@mails.tsinghua.edu.cn`

Coauthor(s): Yanwei Jia, Yufei Zhang

How to execute a stochastic policy in continuous-time environments is crucial for real-time operations and decision making. We show that, by sampling actions from a stochastic policy

at a fixed time grid and then executing a piecewise constant control process, the controlled state process converges to the corresponding aggregated dynamics in the weak sense as the grid size shrinks to zero and obtain the convergence rate. Specifically, under sufficiently regular conditions on the coefficients, the optimal convergence rate of $O(|\mathcal{G}|)$ is achieved with respect to the time grid \mathcal{G} . For less regular coefficients, a convergence rate is established that varies according to the degree of regularity of the coefficients. Additionally, we also derive large deviation bounds for the weak error. Beyond weak error convergence, strong convergence results are proved with a convergence order of $O(|\mathcal{G}|^{1/2})$ in cases where volatility is uncontrolled. Furthermore, we provide a counterexample to demonstrate that no strong convergence occurs when volatility is controlled. Based on these results, we analyze the bias and variance of the policy evaluation and policy gradient estimators in various algorithms for continuous-time reinforcement learning caused by discrete sampling.

Thu, Jul 31 10:30-12:30

Martingale deep neural networks for quasi-linear PDEs and stochastic optimal controls in 10,000 dimensions

Wei Cai

Department of Mathematics, Southern Methodist University
cai@smu.edu

Coauthor(s): Shuixing Fang, Wenzhong Zhang, Tao Zhou

Abstract: In this talk, we will present a highly parallel and derivative-free martingale neural network method, based on the probability theory of Varadhan's martingale formulation of PDEs, to solve Hamilton-Jacobi-Bellman (HJB) equations arising from stochastic optimal control problems (SOCs), as well as general quasilinear parabolic partial differential equations (PDEs). In both cases, the PDEs are reformulated into a martingale problem such that loss functions will not require the computation of the gradient or Hessian matrix of the PDE solution, and can be computed in parallel in both time and spatial domains. Moreover, the martingale conditions for the PDEs are enforced using a Galerkin method realized with adversarial learning techniques, eliminating the need for direct computation of the conditional expectations associated with the martingale property. For SOCs, a derivative-free implementation of the maximum principle for optimal controls is also introduced. The numerical results demonstrate the effectiveness and efficiency of the proposed method, which is capable of solving HJB and quasilinear parabolic PDEs accurately and fast in dimensions as high as 10,000.

- [1] Cai, Wei, Shuixin Fang, Wenzhong Zhang, Tao Zhou, Martingale deep learning for very high dimensional quasi-linear partial differential equations and stochastic optimal controls, arXiv:2408.14395, August, 2024.

Thu, Jul 31 10:30-12:30

Yiqing Zhou*KU Leuven*

yiqing.zhou@kuleuven.be

KarstenNaert,DirkNuyens

Minimizing a function with limited sample points is challenging when function evaluations are costly. We propose a fast interpolation-based approach using the Fast Fourier Transform (FFT) to estimate the minimum more efficiently. By interpolating from a sparse set of samples, our method achieves high accuracy with significantly fewer function evaluations. Preliminary results demonstrate its effectiveness for smooth periodic functions.

Fri, Aug 1 09:00–10:30

Delayed Acceptance Slice Sampling: A Two-Level method for Improved Efficiency in High-Dimensional Settings*Kevin Bitterlich*

TU Bergakademie Freiberg

kevin.bitterlich@math.tu-freiberg.de

Coauthor(s): Bjoern Sprungk, Daniel Rudolf

Slice sampling is a Markov chain Monte Carlo (MCMC) method for drawing (approximately) random samples from a posterior distribution that is typically only known up to a normalizing constant. The method is based on sampling a new state on a slice, i.e., a level set of the target density function. Slice sampling is especially interesting because it is tuning-free and guarantees a move to a new state, which can result in a lower autocorrelation compared to other MCMC methods. However, finding such a new state can be computationally expensive due to frequent evaluations of the target density, especially in high-dimensional settings. To mitigate these costs, we introduce a delayed acceptance mechanism that incorporates an approximate target density for finding potential new states. We will demonstrate the effectiveness of our method through various numerical experiments and outline an extension of our two-level method into a multilevel framework.

Fri, Aug 1 09:00–10:30

Gradient-based MCMC in high dimensions*Reuben Cohn-Gordon*

University of California, Berkeley

reubenharry@gmail.com

Coauthor(s): Jakob Robnik, Uroš Seljak

Sampling from distributions over \mathbb{R}^d for d larger than 10^4 arises as a computational challenge in many of the physical sciences, including particle physics [1], condensed matter physics [2], cosmology [3] and chemistry [4], as well as in Bayesian statistics and machine learning [5]. Commonly used gradient-based variants of Markov Chain Monte Carlo such as Hamiltonian Monte Carlo (HMC) [6] and in particular the No U-Turn Sampler [7], are designed for differentiable multivariate densities, but struggle in very high dimensions. We propose a general purpose approach to the gradient-based high dimensional regime, based on two insights. First, in high dimensional cases where limited asymptotic bias is acceptable, Markov Chain algorithms without Metropolis-Hastings (MH) adjustment are more statistically efficient; we provide theoretical and numerical evidence for this claim and show how to choose a step size to limit the incurred bias to an acceptable level. Second, in the case that MH adjustment is required, we show that a particular 4th order integrator [8] drastically improves the statistical efficiency of HMC and related algorithms in high dimensions.

- [1] Duane, S., Kennedy, A. D., Pendleton, B. J., & Roweth, D. (1987). Hybrid monte carlo. *Physics letters B*, 195(2), 216-222.
- [2] Lunts, P., Albergo, M. S., & Lindsey, M. (2023). Non-Hertz-Millis scaling of the antiferromagnetic quantum critical metal via scalable Hybrid Monte Carlo. *Nature communications*, 14(1), 2547.
- [3] Lewis, A., & Bridle, S. (2002). Cosmological parameters from CMB and other data: A Monte Carlo approach. *Physical Review D*, 66(10), 103511.
- [4] Tuckerman, M. E. (2023). *Statistical mechanics: theory and molecular simulation*. Oxford university press.
- [5] Cobb, A. D., & Jalaian, B. (2021, December). Scaling Hamiltonian Monte Carlo inference for Bayesian neural networks with symmetric splitting. In *Uncertainty in Artificial Intelligence* (pp. 675-685). PMLR.
- [6] Betancourt, M. (2017). A conceptual introduction to Hamiltonian Monte Carlo. *arXiv preprint arXiv:1701.02434*.
- [7] Hoffman, M. D., & Gelman, A. (2014). The No-U-Turn sampler: adaptively setting path lengths in Hamiltonian Monte Carlo. *J. Mach. Learn. Res.*, 15(1), 1593-1623.
- [8] Takaishi, T., & De Forcrand, P. (2006). Testing and tuning symplectic integrators for the hybrid Monte Carlo algorithm in lattice QCD. *Physical Review E—Statistical, Nonlinear, and Soft Matter Physics*, 73(3), 036706.

Fri, Aug 1 09:00–10:30

Parallel Affine Transformation Tuning: Drastically Improving the Effectiveness of Slice Sampling

Philip Schär

Friedrich Schiller University Jena, Germany

philip.schaer@uni-jena.de

Coauthor(s): Michael Habeck, Daniel Rudolf

The performance of MCMC samplers tends to depend on various properties of the target distribution, such as its covariance structure, the location of its probability mass, and its tail behavior. We propose *parallel affine transformation tuning* (PATT) [1], a methodological framework that relies on bijective affine transformations, a latent space construction, the adaptive MCMC principle, and interacting parallel chains, and acts as an intermediate layer between the target distribution and an MCMC method applied to it. By transforming a challenging target into a simpler one, PATT can harness the full potential of the underlying MCMC method.

According to our numerical experiments, PATT is particularly effective in its combinations with *elliptical slice sampling* (ESS) [2] and *Gibbsian polar slice sampling* (GPSS) [3]. For targets that are sufficiently well-behaved (e.g. posteriors in Bayesian logistic regression), these combinations produce samples of (empirically) dimension-independent quality at remarkably low computational cost, with PATT-ESS performing best for light-tailed targets and PATT-GPSS being the superior choice for heavy-tailed ones.

- [1] Schär, P., Habeck, M., Rudolf, D. (2024). Parallel affine transformation tuning of Markov chain Monte Carlo. *Proceedings of the 41st International Conference on Machine Learning (ICML)*, PMLR 235, pp. 43571-43607.
- [2] Murray, I., Adams, R.P., MacKay, D. (2010). Elliptical slice sampling. *Proceedings of the 13th International Conference on Artificial Intelligence and Statistics*, PMLR 9, pp. 541–548.
- [3] Schär, P., Habeck, M., Rudolf, D. (2023). Gibbsian polar slice sampling. *Proceedings of the 40th International Conference on Machine Learning (ICML)*, PMLR 202, pp. 30204-30223.

Fri, Aug 1 09:00–10:30

Low-Rank Thinning*Annabelle Michael Carrell*

University of Cambridge

ac2411@cam.ac.uk

Coauthor(s): Albert Gong, Abhishek Shetty, Raaz Dwivedi, Lester Mackey

The goal in thinning is to summarize a dataset using a small set of representative points. Remarkably, sub-Gaussian thinning algorithms like Kernel Halving and Compress can match the quality of uniform subsampling while substantially reducing the number of summary points. However, existing guarantees cover only a restricted range of distributions and kernel-based quality measures and suffer from pessimistic dimension dependence. To address these deficiencies, we introduce a new low-rank analysis of sub-Gaussian thinning that applies to any distribution and any kernel, guaranteeing high-quality compression whenever the kernel or data matrix is approximately low-rank. To demonstrate the broad applicability of the techniques, we design practical sub-Gaussian thinning approaches that improve upon the best known guarantees for approximating attention in transformers, accelerating stochastic gradient training through reordering, and distinguishing distributions in near-linear time.

Wed, Jul 30 10:30–12:30

Combining quasi-Monte Carlo with Stochastic Optimal Control for Trajectory Optimization of Autonomous Vehicles in Mine Counter Measure Simulations*Philippe Blondeel*

Belgian Royal Military Academy

Philippe.blondeel@mil.be

Coauthor(s): Filip Van Utterbeeck, Ben Lauwens

Modelling and simulating mine countermeasures (MCM) search missions performed by autonomous vehicles is a challenging endeavour. The goal of these simulations typically consists of calculating trajectories for autonomous vehicles in a designated zone such that the coverage (residual risk) of the zone is below a certain user defined threshold. We have chosen to model and implement the MCM problem as a stochastic optimal control problem, see [1]. Mathematically, the MCM problem is defined as minimizing the total mission time needed to survey a designated zone Ω for a given residual risk of not detecting sea mines in the user-chosen square domain, i.e.,

$$\min T_f, \tag{5.5}$$

subjected to

$$\mathbb{E}[q(T_F)] := \int_{\Omega} e^{-\int_0^{T_F} \gamma(\mathbf{x}(\tau), \boldsymbol{\omega}) d\tau} \phi(\boldsymbol{\omega}) d\boldsymbol{\omega} \leq \text{Residual Risk}. \tag{5.6}$$

The output of our stochastic optimal control implementation consists of an optimal trajectory in the square domain for the autonomous vehicle. As shown in Eq. (5.6), the residual risk is mathematically represented as an expected value integral. In [2], we presented a novel relaxation strategy for the computation of the residual MCM risk, used in our stochastic optimal control formulation. This novel relaxation strategy ensures that the residual risk obtained at the end of the optimisation run is below the maximally allowed user requested residual risk. This was however not the case with our initial ‘naive’ implementation of the MCM problem. Our proposed relaxation strategy ensures that the user requested risk is satisfied by sequentially solving the stochastic optimal control problem with an ever increasing size of the domain. We combine this strategy with a quasi-Monte Carlo sampling scheme based on a Rank-1 Lattice rule for the computation of the expected value integral. We observe a speedup up to a factor two in terms of total computational cost in favour of quasi-Monte Carlo when compared to standard Monte Carlo.

- [1] Blondeel, P., Van Utterbeeck, F., Lauwens, B. (2024). Modeling sand ripples in mine countermeasure simulations by means of stochastic optimal control. In: The 19th European Congress on Computational Methods in Applied Sciences and Engineering, ECCOMAS, Lisbon, Portugal (2024).
- [2] Blondeel, P., Van Utterbeeck, F., Lauwens, B. (2025). Application of quasi-Monte Carlo in Mine Countermeasure Simulations with a Stochastic Optimal Control Framework, *arXiv preprint*

Wed, Jul 30 10:30–12:30

A Monte Carlo Approach to Designing a Novel Sample Holder for Enhanced UV-Vis Spectroscopy

R. Persiani

INFN Section of Catania, Via S. Sofia 64, Catania, 95123, Italy
 rino.persiani@ct.infn.it

Coauthor(s): A. Agugliaro, S. Albergo, R. De Angelis, I. Di Bari, A. Sciuto, A. Tricomi

UV-Vis spectroscopy is one of the most widely used techniques for identifying and quantifying substances in water and other solvents due to its speed and reliability. Its applications span diverse scientific fields, including chemistry, biochemistry, and medicine, as well as industrial sectors such as the pharmaceutical and food industries. Moreover, it plays a crucial role in environmental monitoring, particularly in assessing water quality. While alternative methods such as Raman and Ring Down spectroscopy have emerged, the core design of UV-Vis spectrometers has remained largely unchanged since their inception. Typically, these instruments employ a light source, a monochromator, a standard 1 cm cuvette as the sample holder, and one or more photosensors.

In this work, we present a novel approach that leverages Monte Carlo simulation to optimize the design of the sample holder for enhanced UV-Vis spectroscopy. In particular, our

setup adopts a pulsed light source and a Silicon Photomultiplier (SiPM) with single-photon counting capability. Using the optical transport package available in the Geant4 toolkit, we characterized and optimized the new design. The innovative holder, crafted in PTFE for its high UV reflectivity, resembles an integrating sphere, which increases the photon path length in the solution and thereby enhances absorbance in the presence of absorbing substances. We also present a comparison between experimental data and Monte Carlo predictions for validation. With this new sample holder, the spectrophotometer exhibits enhanced detection sensitivity, especially at low concentrations.

Wed, Jul 30 10:30–12:30

ARCANE Reweighting: A technique to tackle the sign problem in the simulation of collider events in high energy physics

Prasanth Shyamsundar

Fermi National Accelerator Laboratory

prasanth@fnal.gov

Negatively weighted events, which appear in the Monte Carlo (MC) simulation of particle collisions, significantly increase the computational resource requirements of current and future collider experiments in high energy physics. This work introduces an MC technique called ARCANE reweighting for reducing or eliminating negatively weighted events. The technique works by redistributing (via an additive reweighting) the contributions of different pathways within the simulator that lead to the same final event. The technique is exact and does not introduce any biases in the distributions of physical observables. ARCANE reweighting can be thought of as a variant of the parametrized control variates technique, with the added nuance that redistribution is performed using a deferred additive reweighting. The technique is demonstrated for the simulation of a specific collision process, namely $e^+e^- \rightarrow q\bar{q} + 1 \text{ jet}$. The technique can be extended to several other collision processes of interest as well. This talk is based on the Refs [1] and [2].

- [1] Shyamsundar, Prasanth (2025). *ARCANE Reweighting: A Monte Carlo Technique to Tackle the Negative Weights Problem in Collider Event Generation*. arXiv:2502.08052 [hep-ph].
- [2] Shyamsundar, Prasanth (2025). *A Demonstration of ARCANE Reweighting: Reducing the Sign Problem in the MC@NLO Generation of $e^+e^- \rightarrow q\bar{q} + 1 \text{ jet}$ Events*. arXiv:2502.08052 [hep-ph].

Wed, Jul 30 10:30–12:30

Multifidelity and Surrogate Modeling Approaches for Uncertainty Quantification in Ice Sheet Simulations

Nicole Aretz

Oden Institute for Computational Engineering and Sciences, University of Texas at Austin
nicole.aretz@austin.utexas.edu

Coauthor(s): Max Gunzburger, Mathieu Morlighem, Karen Willcox

Our work [1] uses multifidelity and surrogate modeling to achieve computationally tractable uncertainty quantification (UQ) for large-scale ice sheet simulations. UQ is of utmost importance to enable judicious policy decisions combating climate change. However, high-fidelity ice sheet models are typically too expensive computationally to permit Monte Carlo sampling. To reduce the computational cost while achieving the same target accuracy, we use multifidelity estimators to shift the computational burden onto less expensive surrogate models derived from coarser discretizations and approximated physics. In this talk, we compare three estimators — Multifidelity [2] and Multilevel [3] Monte Carlo, and the Best Linear Unbiased Estimator [4] — and present results for the expected ice mass loss of the Greenland ice sheet.

- [1] Aretz, N., Gunzburger, M., Morlighem, M., & Willcox, K. (2025). Multifidelity uncertainty quantification for ice sheet simulations. *Computational Geosciences*, 29(1), 1-22.
- [2] Peherstorfer, B., Willcox, K., & Gunzburger, M. (2016). Optimal model management for multifidelity Monte Carlo estimation. *SIAM Journal on Scientific Computing*, 38(5), A3163-A3194.
- [3] Giles, M. B. (2015). Multilevel monte carlo methods. *Acta numerica*, 24, 259-328.
- [4] Schaden, D., & Ullmann, E. (2020). On multilevel best linear unbiased estimators. *SIAM/ASA Journal on Uncertainty Quantification*, 8(2), 601-635.

Wed, Jul 30 14:00–16:00

Empirical Statistical Comparative Analysis of SNP Heritability Estimators and Gradient Boosting Machines (GBM) Using Genetic Data from the UK Biobank

Kazeem Adeleke^{*1}

University of the West of England, UK
adedayo.adeleke@uwe.ac.uk

Coauthor(s): Peter Ogunyinka², Emmanuel Ologunleko³ and Dawud Agunbiade⁴

This study addresses the methodological challenges in estimating genetic heritability by comparing traditional statistical approaches with advanced machine learning techniques.

We evaluated three distinct methods: sibling regression, LD-score regression, and Gradient Boosting Machines (GBMs), using both simulated datasets and real-world data from the UK Biobank. Our methodology involved generating simulated genotypes following Mendelian inheritance patterns and creating corresponding phenotypes incorporating family-specific genetic effect sizes. We conducted Genome-Wide Association Studies (GWAS) on firstborn children from each family and performed comprehensive heritability analyses using all three methods. Results demonstrated that while sibling regression effectively captured within-family genetic similarities and LD-score regression accounted for population-wide linkage disequilibrium patterns, GBMs showed superior capability in predicting phenotypes by capturing complex genetic interactions. The integration of GBMs with traditional methods revealed enhanced predictive power and provided new insights into the genetic architecture of complex traits. Our findings emphasize the value of combining conventional statistical approaches with machine learning techniques for more robust heritability estimation in large-scale UK Biobank studies.

Wed, Jul 30 14:00–16:00

Cheap permutation testing

Carles Domingo-Enrich

Microsoft Research New England

carlesd@microsoft.com

Coauthor(s): Raaz Dwivedi, Lester Mackey

Permutation tests are a popular choice for distinguishing distributions and testing independence, due to their exact, finite-sample control of false positives and their minimax optimality when paired with U-statistics. However, standard permutation tests are also expensive, requiring a test statistic to be computed hundreds or thousands of times to detect a separation between distributions. In this work, we offer a simple approach to accelerate testing: group your datapoints into bins and permute only those bins. For U and V-statistics, we prove that these cheap permutation tests have two remarkable properties. First, by storing appropriate sufficient statistics, a cheap test can be run in time comparable to evaluating a single test statistic. Second, cheap permutation power closely approximates standard permutation power. As a result, cheap tests inherit the exact false positive control and minimax optimality of standard permutation tests while running in a fraction of the time. We complement these findings with improved power guarantees for standard permutation testing and experiments demonstrating the benefits of cheap permutations over standard maximum mean discrepancy (MMD), Hilbert-Schmidt independence criterion (HSIC), random Fourier feature, Wilcoxon-Mann-Whitney, cross-MMD, and cross-HSIC tests.

Wed, Jul 30 14:00–16:00

Moving PCG beyond LCGs*Christopher Draper*

Florida State University

chd16@fsu.edu

Coauthor(s): Michael Mascagni

PCG is a set of generators released by Melissa E. O'Neill in 2014 [1]. The original technical report outlined a number of lightweight scrambling techniques. Each scrambling technique offered some improvement to the quality of the linear congruential generators they were designed for. However the real strength of the scrambling techniques was that they could easily be combined in different combinations to offer much stronger improvements. The PCG technical report concludes with the creation of the PCG library, a popular PRNG library that implements a number of generators described in the technical report. Starting from the observation that the PCG work was narrowly focused on implementing their scrambling techniques for specific linear congruential generators, we explore the PCG scrambling techniques and their potential application for being applied to other PRNGs. We show the steps taken to generalize the PCG scrambling techniques to work with any arbitrary amount of bits and parameter values. Then test the PCG scrambling techniques across different linear congruential generators and then test the PCG scrambling techniques across a number of different PRNGs.

- [1] Melissa E. O'Neill. 2014. PCG: A Family of Simple Fast Space-Efficient Statistically Good Algorithms for Random Number Generation. Technical Report HMC-CS-2014-0905. Harvey Mudd College, Claremont, CA.

Wed, Jul 30 14:00–16:00

Hybrid least squares for learning functions from highly noisy data*Yiming Xu*

University of Kentucky

yiming.xu@uky.edu

Coauthor(s): Ben Adcock, Bernhard Hientzsch, Akil Narayan

Motivated by the request for efficient estimation of conditional expectations, we consider a least-squares function approximation problem with heavily polluted data. In such scenarios, existing methods based on the small noise assumption become suboptimal. We propose a hybrid approach that combines Christoffel sampling with optimal experimental design to address this issue. The proposed algorithm adheres to appropriate optimality criteria for both sample points generation and function evaluation, leading to improved computational effi-

ciency and sample complexity. We also extend the algorithm to convex-constrained settings with similar theoretical guarantees. Moreover, when the target function is defined as the expectation of a random field, we introduce adaptive random subspaces to approximate the target function and establish results concerning its approximation capacity. Our findings are corroborated through numerical studies on synthetic data and a more challenging stochastic simulation problem in computational finance.

Practical Information

to 16:00 on. There will be support on site throughout the week for participants who arrive after Monday.

Sunday Tutorials

Sunday afternoon tutorials will be held in STC 1012, and are given by Fred Hickernell (14:15–15:45) and Peter Frazier (16:00–17:30).

Opening Ceremony

The opening ceremony will be held in STC 1012 on Monday, August 19, at 08:45, before the first plenary talk.

Plenary Talks

Plenary talks will be held in STC 1012. Plenary talks are 50 minutes long, plus 10 minutes for questions and discussions. Due to the tight conference schedule, we kindly ask the chairs to strictly observe the time constraints.

All other talks

All other talks (except plenary talks and tutorials) will be held in parallel sessions in STC 0020, STC 0040, STC 0050, and STC 0060. These talks are 25 minutes long plus 5 minutes for questions and discussions. Due to the tight conference schedule, we kindly ask all speakers and chairs to strictly observe the time constraints.

Coffee Breaks

Morning and afternoon coffee breaks will take place in the STC lower-level atrium, between the plenary talk and parallel sessions, i.e., from 10:00 to 10:30 and from 15:00 to 15:30. There will also be a coffee break on Sunday August 18 between the two tutorials, from 15:45 to 16:00.

Reception (Monday)

On Monday, August 19, there will be a welcome reception from 18:00 to 19:30. Drinks and finger food will be provided in the Mathematics 3 (M3) building atrium (ground floor). M3 is just north of the Mathematics & Computing (MC) building. Please refer to the conference website for campus maps or see above information on Location.

Award Ceremony of the Journal of Complexity (Monday)

On Monday, August 19, there will be a short ceremony to award IBC Awards and IBC Young Researcher Awards of the Journal of Complexity. The ceremony will be chaired by senior editors of the journal, and take place at about 8:55 in STC 1012 (immediately before the first plenary talk).

Conference Photo (Wednesday)

A conference photo will be taken on Wednesday, August 21, at 17:30, right after the afternoon parallel sessions. Details will be announced during the conference week.

Conference Dinner (Wednesday)

The conference dinner will take place in the Engineering 7 (E7) building, which is outside of Ring Road, immediately behind and directly connected from inside to the Engineering 5 (E5) building. You can find it easily as E5 is the building connected to campus by a bridge going over Ring Road near the Davis Centre.

Please note that all participants (conference participants and accompanying persons) must be registered in advance for this event.

Steering Committee Meeting (Thursday)

On Thursday, August 22, the MCQMC Steering Committee will have a closed meeting, starting at 19:00. If you have any comments or suggestions, or would like to propose hosting a future conference, please approach any member of the Steering Committee prior to this meeting.

Food

Lunch will *not* be provided. There will be a Tim Horton's (located in the Davis Centre (DC) ground floor), Subway and Flock Stop (both located in the Student Life Center - SLC ground floor), open on-campus during the week providing an inexpensive option for lunch. Alternatively, a short 10-minute walk east from STC leads to the "University Shops Plaza" where there are several restaurants and fast-food outlets providing more diverse options for conference participants. Another popular lunch venue is Ken Sushi House on Phillip Street, just east of campus.

Travel to Waterloo from Toronto Pearson Airport (YYZ)

Before you travel to Canada, please ensure you have the proper documents and visitor visas to visit. Check the Government of Canada website for specific requirements for your country.

Details regarding travel visas can be found on the registration page.

Waterloo is located approximately one hour by car from Toronto Pearson Airport, however there are several methods to book travel from the airport to Waterloo.

- By Bus: There are buses that travel between Toronto Pearson YYZ, to Waterloo. GO Transit is the most popular.
- By Taxi: With Waterloo Taxi, you can reserve a taxi on the Waterloo Taxi online form or call at +1 (519) 888-7777.
- By Rail: UP Express is a direct journey from Toronto Pearson International Airport to Union Station, Downtown Toronto. When at Union Station, transfer to VIA Rail train or GO train.
- By Airways Transit (up to 8 passengers): Reserve door-to-door service on the Airways Transit website. By Car: Take ON-401 W towards London and then take exit 278 to merge onto ON-8 W toward Kitchener/Waterloo.

Public transport in Waterloo

By Bus: Grand River Transit is the public transit operator for the Region of Waterloo, Ontario. It operates daily bus serves across Waterloo and the University of Waterloo campus.

By ION Light Rail Travel: ION is Waterloo Region's light rail transit (LRT) system. It runs between Kitchener's Fairview Park Mall and Waterloo's Conestoga Mall, with stops at the University of Waterloo campus. ION trains connect passengers to the existing bus system (Grand River Transit), making it easy to travel across the region.

Equipment in classrooms used for conference

Each lecture hall is equipped with a desktop computer running Windows, with USB port access and internet connection, a data projector and screen, and blackboards. One MCQMC staff member will be present in each lecture hall to assist with IT related issues.

We strongly encourage you to make yourself known to your session chair and (if necessary) the MCQMC staff member assigned to your lecture room, prior to your talk. Please prepare your talk in the form of a PDF or PPT document. A slides repository will be created shortly before the conference to facilitate the uploading of slides to the desktop computer in each room prior to each session by MCQMC staff. More detailed instructions will be sent to speakers and session chairs prior to the conference. An alternative option is to bring a USB storage device with your slides copied on it and make sure that your talk is copied onto the desktop computer during the break prior to your talk.

If you require access to other software packages or other audio-visual equipment, please communicate with the conference organizers well ahead of time to see if it can be arranged. It is possible to connect your personal laptop to the data projector, but we prefer that you avoid this option due to the tight conference schedule. If you need to use your own laptop, please make sure that you discuss this with a MCQMC staff member and that you test the connection well before your talk.

Internet and Computer Access

University of Waterloo has eduroam to provide free wireless access for visitors whose home institutions also have eduroam. For more information on eduroam see <http://www.eduroam.org>. Please check with your institution whether you have access to eduroam and for instructions on how to set up eduroam (this depends on your home institution and not on local institutions).

If you cannot use eduroam, conference participants will be granted access to the Waterloo wireless network on campus via self-registration. Further details on how to do so will be announced during the opening of the conference.

In any case, please use the wireless connections provided responsibly.

Emergency Contacts, Hospitals and Services on Campus

The emergency phone number in Canada is **911**. For emergency calls on-campus, call the UW Special Constable at 519-888-4911. There is a Special Constable on campus 24 hours a day, 7 days a week.

Local Kitchener-Waterloo Hospitals

- Grand River Hospital, 835 King Street West, Kitchener (519-742-3611)
- St. Mary's General Hospital, 911 Queen's Boulevard, Kitchener (519-744-3311)

Power Plugs in Canada

In Canada, the standard power sockets are:

- Type A:
 - Description: This socket has two flat parallel pins.
 - Voltage: 120 V
 - Frequency: 60 Hz
- Type B:
 - Description: This socket has two flat parallel pins and a grounding pin (three-pronged).
 - Voltage: 120 V
 - Frequency: 60 Hz

Closing of the Conference

MCQMC 2024 will be closed with a few short announcements and remarks immediately after the final parallel sessions, which finish at 12:30 on Friday, August 23.

Proceedings

Following the tradition of the MCQMC conference series, a selection of strictly refereed papers will be published after the conference as a Springer book. Every speaker is welcome to submit a paper based on his/her talk, with the length strictly not exceeding 16 pages in the Springer style. Plenary and tutorial speakers are invited to submit papers of at most 30 pages length. The papers of plenary and tutorial speakers can be survey articles.

The submission deadline for manuscripts is December 13, 2024. Please send your submissions as a pdf file to mcqmc.2024@uwaterloo.ca.

Further instructions will be provided in the closing session of the conference, and will be available on the conference website later.

Conference Statistics (as of July 5)

Number of participants	151
Number of plenary lectures	8
Number of tutorials	2
Number of talks	137
Number of special sessions	24 (85 talks)
Number of technical sessions	12 (42 talks)

List of Participants

FirstName LastName

Organization

p. ??

Christiane Lemieux

University of Waterloo

p. 24

Peter Glynn

Stanford University

p. 25

Roshan Joseph

Georgia Institute of Technology

p. 26

Michaela Szölgyenyi

University of Klagenfurt

p. 27

Uros Seljak

University of California, Berkeley

p. 28

Nicolas Chopin

ENSAE, Institut Polytechnique de Paris

p. 30

Stefan Heinrich

RPTU Kaiserslautern-Landau

p. 32

Chengcheng Ling

University of Augsburg

p. 32

Thomas Muller-Gronbach

University of Passau

p. 32

Andreas Neuenkirch

University of Mannheim

p. 32

Christopher Rauhogger

University of Passau

p. 32

Verena Schwarz

University of Klagenfurt

p. 32

Larisa Yaroslavtseva

University of Graz

p. 32

Murat Erdogdu

University of Toronto

p. 44

Sebastiano Grazzi

Bocconi University

p. 44

Federica Milinanni

KTH Royal Institute of Technology

p. 44

Alex Shestopaloff

Queen Mary University of London

p. 44

Xingyu Wang

University of Amsterdam

p. 44

Jun Yang

University of Copenhagen

p. 44

Nikhil Bansal

University of Michigan, Ann Arbor

p. 46

Sou-Cheng Choi

Illinois Institute of Technology

p. 46

Yuhan Ding

Illinois Institute of Technology

p. 46

Hwanwoo Kim

Duke University

p. 46

Michael Mascagni
Florida State University
p. 46

Jonathan Weare
New York University
p. 46

Stefan Heinrich
RPTU Kaiserslautern-Landau
p. 47

Andre Herzwurm
Rosenheim Technical University of Applied
Sciences
p. 47

Gunther Leobacher
University of Graz
p. 47

Thomas Muller-Gronbach
University of Passau
p. 47

Alexander Steinecke
University of Leoben
p. 47

Larisa Yaroslavtseva
University of Graz
p. 47

Alen Alexanderian
North Carolina State University
p. 48

Tommie Catanach
Sandia National Laboratories
p. 48

Florence Forbes
Inria
p. 48

Xun Huan
University of Michigan
p. 48

Jacopo Iollo
Inria
p. 48

Youssef Marzouk
Massachusetts Institute of Technology
p. 48

Eya Ben Amar
King Abdullah University of Science and
Technology
p. 50

Victor Elvira
University of Edinburgh
p. 50

Shyam Mohan Subbiah Pillai
RWTH Aachen University
p. 50

Nadhir Ben Rached
University of Leeds
p. 50

Shyam Mohan Subbiah Pillai
RWTH Aachen University
p. 50

Raúl Tempone
King Abdullah University of Science and
Technology
p. 50

Bruno Tuffin
Inria
p. 50

Sou-Cheng Choi
Illinois Institute of Technology
p. 51

Yuhan Ding
Illinois Institute of Technology
p. 51

Takashi Goda
University of Tokyo
p. 51

Joshua Isaacson
Fermilab
p. 51

Ziang Niu
University of Pennsylvania
p. 51

Chenyang Zhong
Columbia University
p. 51

Stefan Heinrich
RPTU Kaiserslautern-Landau
p. 52

Bernd Kaßemodel
Chemnitz University of Technology
p. 52

Thomas Muller-Gronbach
University of Passau
p. 52

Klaus Ritter
RPTU Kaiserslautern-Landau
p. 52

Matti Vihola
University of Jyväskylä
p. 52

Larisa Yaroslavtseva
University of Graz
p. 52

Chaofan Huang
Georgia Institute of Technology
p. 53

Lulu Kang
University of Massachusetts Amherst
p. 53

Chunfang Lin
Queen's University
p. 53

Simon Mak
Duke University
p. 53

Chih-Li Sung
Michigan State University
p. 53

Qian Xiao
Shanghai Jiao Tong University
p. 53

Nawaf Bou-Rabee
Rutgers University
p. 55

Trevor Campbell
University of British Columbia
p. 55

Bob Carpenter
Flatiron Institute
p. 55

Chirag Modi
New York University
p. 55

Art Owen
Stanford University
p. 55

Raghu Bollapragada
University of Texas at Austin
p. 57

Shane Henderson
Cornell University
p. 57

Raghu Pasupathy
Purdue University
p. 57

Jürgen Dölz
University of Bonn
p. 33

Philipp Guth
Austrian Academy of Sciences
p. 33

Harri Hakula
Aalto University
p. 33

Carlos Jerez-Hanckes
Universidad Adolfo Ibáñez
p. 33

Vesa Kaarnioja
Free University of Berlin
p. 33

André-Alexander Zepernick
Free University of Berlin
p. 33

Haotian Jiang
University of Chicago
p. 58

Aleksandar Nikolov
University of Toronto
p. 58

Peng Zhang
Rutgers University
p. 58

Arash Fahim
Florida State University
p. 60

Sharanya Jayaraman
Florida State University
p. 60

Michael Mascagni
Florida State University and National
Institute of Standards and Technology
p. 60

Rohan Sawahney
Nvidia Corporation
p. 60

Silei Song
Florida State University
p. 60

Felix Bartel
University of New South Wales
p. 61

Mou Cai
University of Tokyo
p. 61

Michael Gnewuch
University of Osnabrück
p. 61

Takashi Goda
University of Tokyo
p. 61

Zhijian He
South China University of Technology
p. 61

Peter Kritzer
Austrian Academy of Sciences
p. 61

Frances Y. Kuo
University of New South Wales
p. 61

Nawaf Bou-Rabee
Rutgers University
p. 62

Yifan Chen
New York University
p. 62

Xiaoou Cheng
New York University
p. 62

Lihan Wang
Carnegie Mellon University
p. 62

Jonathan Weare
New York University
p. 62

Peter Whalley
ETH Zurich
p. 62

Arved Bartuska
King Abdullah University of Science and
Technology/RWTH Aachen University
p. 63

André Gustavo Carlon
RWTH Aachen University
p. 63

Philipp Guth
Johann Radon Institute for Computational
and Applied Mathematics
p. 63

Zhijian He
South China University of Technology
p. 63

Raúl Tempone
King Abdullah University of Science and
Technology/RWTH Aachen University
p. 63

Michael Gnewuch
University of Osnabrück
p. 64

Takashi Goda
University of Tokyo
p. 64

Peter Kritzer
Austrian Academy of Sciences
p. 64

Dirk Nuyens
KU Leuven
p. 64

Art B. Owen
Stanford University
p. 64

Zexin Pan
Austrian Academy of Sciences
p. 64

Kosuke Suzuki
Yamagata University
p. 64

Krishnakumar Balasubramanian
University of California, Davis
p. 65

Yifan Chen
New York University
p. 65

Xiaoou Cheng
New York University
p. 65

Siddharth Mitra
Yale University
p. 65

Molei Tao
Georgia Institute of Technology
p. 65

Jonathan Weare
New York University
p. 65

Jose Blanchet
Stanford University
p. 66

Jing Dong
Columbia University
p. 66

Chang-Han Rhee

Northwestern University
p. 66

Maksim Chupin

King Abdullah University of Science and
Technology
p. 67

Zhou Fang

Chinese Academy of Sciences
p. 67

Chiheb Ben Hammouda

Utrecht University
p. 67

Sophia Munker

RWTH Aachen University
p. 67

Muruhan Rathinam

University of Maryland, Baltimore
p. 67

Raul Tempone

RWTH Aachen University
p. 67

Niklas Baumgarten

University of Heidelberg
p. 68

Sou-Cheng Choi

Illinois Institute of Technology
p. 68

Joseph Farmer

University of Notre Dame
p. 68

Mike Giles

University of Oxford
p. 68

Johannes Krotz

University of Notre Dame
p. 68

Pieterjan Robbe

Sandia National Laboratories
p. 68

Aleksei Sorokin

Illinois Institute of Technology
p. 68

Arved Bartuska

King Abdullah University of Science and
Technology/RWTH Aachen University
p. 34

Truong Vinh Hoang

RWTH Aachen University
p. 34

Vesa Kaarnioja

Free University of Berlin
p. 34

Sebastian Krumscheid

Karlsruhe Institute of Technology
p. 34

Raúl Tempone

King Abdullah University of Science and
Technology/RWTH Aachen University
p. 34

Sou-Cheng Choi

Illinois Institute of Technology
p. 35

Mike Giles

University of Oxford
p. 35

Irina-Beatrice Haas

University of Oxford
p. 35

Chung Ming Loi

Durham University
p. 35

Pieterjan Robbe

Sandia National Laboratories
p. 35

Michael Gnewuch

Osnabruck University
p. 37

Stefan Heinrich

RPTU Kaiserslautern-Landau
p. 37

Thomas Muller-Gronbach

University of Passau
p. 37

Leszek Plaskota

University of Warsaw
p. 37

Kateryna Pozharska

Chemnitz University of Technology
p. 37

Marcin Wnuk

Osnabruck University
p. 37

Larisa Yaroslavtseva

University of Graz
p. 37

Arved Bartuska

RWTH Aachen University
p. 38

Philipp A. Guth

Austrian Academy of Sciences
p. 38

Tapio Helin

LUT University
p. 38

Vesa Kaarnioja

Free University of Berlin
p. 38

Karina Koval

University of Heidelberg
p. 38

Johannes Milz

Georgia Institute of Technology
p. 38

Makram Chahine

Massachusetts Institute of Technology
p. 39

François Clément

University of Washington
p. 39

Gregory De Salaberry Seljak

University of Montréal
p. 39

Nathan Kirk

Illinois Institute of Technology
p. 39

Jean-Francois Chassagneux

ENSAE Paris
p. 41

Goncalo Dos Reis

University of Edinburgh
p. 41

Noufel Frikha

Paris 1 Pantheon-Sorbonne University
p. 41

Stefan Heinrich

RPTU Kaiserslautern-Landau
p. 41

Thomas Muller-Gronbach

University of Passau
p. 41

Sotirios Sabanis

University of Edinburgh
p. 41

Larisa Yaroslavtseva
University of Graz
p. 41

Ayoub Belhadji
Massachusetts Institute of Technology
p. 42

Adrien Corenflos
University of Warwick
p. 42

Florence Forbes
Inria
p. 42

Xun Huan
University of Michigan
p. 42

Youssef Marzouk
Massachusetts Institute of Technology
p. 42

Philippe Gagnon
Université de Montréal
p. ??

Ruben Seyer
Chalmers University of Technology and
University of Gothenburg
p. ??

Zhihao Wang
University of Copenhagen
p. ??

Attila Lovas
Hun-Ren Alfréd Rényi Institute of
Mathematics
p. ??

Iosif Lytras
Athena Research Centre
p. ??

Nikolaos Makras
University of Edinburgh
p. ??

Sara Pérez-Vieites
Aalto University
p. ??

Riccardo Saporiti
EPFL
p. ??

Anke Wiese
Heriot-Watt University
p. ??

Leon Wilkosz
King Abdullah University of Science and
Technology
p. ??

Fabio Zoccolan
EPFL
p. ??

Miguel Alvarez
King Abdullah University of Science and
Technology
p. ??

Håkon Hoel
University of Oslo
p. ??

Abdujabar Rasulov
University of World Economy and
Diplomacy
p. ??

Adrien Richou
Université de Bordeaux
p. ??

Frédéric Blondeel
Kuleuven and Unife
p. ??

Wei Cai

Southern Methodist University
p. ??

Du Ouyang

Tsinghua University
p. ??

Yiqing Zhou

KU Leuven
p. ??

Kevin Bitterlich

TU Bergakademie Freiberg
p. ??

Annabelle Carrell

University of Cambridge
p. ??

Reuben Cohn-Gordon

University of California, Berkeley
p. ??

Philip Schaer

Friedrich Schiller University Jena
p. ??

Nicole Aretz

University of Texas at Austin
p. ??

Philippe Blondeel

Belgian Military Academy
p. ??

Rino Persiani

INFN Catania
p. ??

Prasanth Shyamsundar

Fermi National Accelerator Laboratory
p. ??

Kazeem Adeleke

University of the West of England
p. ??

Carles Domingo-Enrich

Microsoft Research New England
p. ??

Christopher Draper

Florida State University
p. ??

Yiming Xu

University of Kentucky
p. ??

Arghya Datta

Université de Montréal
p. ??

Jimmy Lederman

University of Chicago
p. ??

Lorenzo Nagar

Basque Center for Applied Mathematics
p. ??

Hamza Ruzayqat

King Abdullah University of Science and
Technology
p. ??

Serena Fattori

Istituto Nazionale di Fisica Nucleare
(INFN)
p. ??

Toon Ingelaere

KU Leuven
p. ??

Yashveer Kumar

INESC-ID
p. ??

Muhammad Noor ul Amin

COMSATS University Islamabad, Lahore
p. ??

Ambrose Emmett-Iwaniw

University of Waterloo

p. ??

Soumyadip Ghosh

IBM Research

p. ??

Sifan Liu

Flatiron Institute

p. ??

Sascha Holl

Max Planck Institute for Informatics

p. ??

Christian Weiss

Ruhr West University of Applied Sciences

p. ??

Kun-Lin Kuo

National University of Kaohsiung

p. ??

Xiaoda Xu

Suqian University

p. ??

Josephine Westermann

Heidelberg University

p. ??

Jakob Dilen

KU Leuven

p. ??

Matyokub Bakoev

MGIMO, Tashkent

p. ??

Aadit Jain

Rancho Bernardo High School

p. ??

Hao Quan

University of Waterloo

p. ??

Peter Kritzer

Austrian Academy of Sciences

p. ??

Vincent Zhang

University of Southern California

p. ??

Yang Liu

King Abdullah University of Science and
Technology

p. ??

Nicola Branchini

University of Edinburgh

p. ??

Arne Bouillon

KU Leuven

p. ??

Amit Subrahmanya

Virginia Tech

p. ??

Joonha Park

University of Kansas

p. ??

Daniel Yukimura

Impa, Rio de Janeiro

p. ??

Akash Sharma

Chalmers Institute of Technology

p. ??

André Gustavo Carlon

RWTH Aachen University

Noufel Frikha

Université Paris 1 Panthéon Sorbonne

Alex Shkolnik

University of California, Santa Barbara

p. ??

Chi-Ok Hwang

Gwangju Institute of Science and
Technology

Gregory Seljak

Universite de Montreal