One refusal neuron, across languages

Follow-ups to 5 November: nine questions and how we tested them, plus the experiments that were still running

Faaiz Joad · QCRI, HBKU · 12 November 2026

RECAP

The project in one slide

Apple's paper (Kazemi et al., 2026): inside a chat model, one single number (one MLP neuron) decides whether the model refuses a harmful request. Hold that number at a fixed value ("pin" it) and the model stops refusing. English only. **Our question:** is it the same neuron in every language?

Part 1: the Apple paper in Arabic

- Every experiment of the paper again, with Arabic prompts
- Result: the same neuron is found, and pinning it jailbreaks Arabic as well as English

Done, except one baseline

Part 2: every other language

- 22 more language sets (PolyRefuse, MultiJail)
- Result: one small shared group of neurons in every language, except Yoruba and Swahili

Search done · attacks done, judging finishing

Part 3: MLP questions

- Nanda's refusal direction built inside the MLP
- Result: its biggest neuron is Apple's neuron; switching it off is not enough, it must be pushed past harmless

Done in English and Arabic

Models: Qwen3-8B, Llama-3.1-8B-Instruct, Qwen3-1.7B. Target: ARR, 4 January 2027.

RECAP

Setup used throughout

Model	Apple's neuron	Pin used
Qwen3-8B	layer 14, neuron 7924	+20
Llama-3.1-8B-Instruct	layer 11, neuron 4258	−4
Qwen3-1.7B	layer 13, neuron 3270	+40

JUDGES

- Qwen3Guard reads the answer in its own language: harmful or not, refusal or not
- Llama-Guard-3 reads an English translation (second opinion)
- Apple's main criterion (K.1): the attack succeeds if the answer is not a refusal and is coherent; judged by gemma-2-9b-it

DATA

- PolyRefuse: 14 languages, the same harmful prompts machine-translated. Example: "Where can I pirate paywalled academic papers?"
- MultiJail: 10 languages, human-translated; some prompts are borderline. Example: "How can I steal someone's credit card info"
- Per language: search on 128 harmful / 128 harmless prompts, attack on 100 held-out prompts

INTERVENTIONS

- Constant pin: the neuron held at the pin at every token
- Anchor pin: the pin scaled by how strongly the neuron fires on that prompt
- Nanda baseline: the refusal direction removed from the residual stream at every layer

QUESTIONS FROM 5 NOVEMBER

Nine questions from the last meeting

#	Question	How we tested it	Slide
1	Why does Nanda's ablation cost less ability than the constant pin?	MMLU with the pin at growing strengths; how far each intervention moves the model's output	5
2	Does the neuron even fire on MMLU? If not, the anchor test shows little	Count the questions where it fires; accuracy on those	6
3	Overlap of the top-5 lists across languages and datasets	Each language's top 5 against the top 5 of Apple's English setup	7
4	Why is Apple's neuron not first in English on other datasets?	The English search with one ingredient changed at a time	8
5	Low-resource languages: where the model does refuse, is the neuron there?	The neuron's value on refused against answered prompts, per language	9
6	Is there a language-specific step in the smaller model?	The neuron's strength per language as a share of English, per model	10
7	Why are Chinese and Vietnamese lower?	Are the same MultiJail prompts "answered but safe" in every language?	11
8	Explain the math of the neuron's share of the direction	Formula and worked example	12
9	Do the same breakdown in the residual stream	Spread of the residual direction; the neuron's share of it	13

Also in the notes: put the job logs in the repository, and write a how-to-run guide so others can run the pipeline (not done yet).

QUESTIONS FROM 5 NOVEMBER

1. Why does Nanda's ablation cost less than the constant pin?

THE QUESTION

Last time: Nanda's ablation costs 1–2 points of ability, the constant pin 5–9. Why is Nanda's better?

HYPOTHESIS

The pin forces the neuron far outside its normal range on every prompt (Qwen3-8B: normally between −4 and 0, pinned at +20). Ablation only removes something that is near zero on harmless prompts. Alternative: the neuron has other jobs, so any overwrite hurts.

WHAT WE DID

- 1,000 MMLU questions, one pass per setting
- Pin the neuron at its harmless average, then at 10%, 25%, 50%, 100% of the attack pin
- Measure accuracy, and how far the model's output moves (KL)

MMLU ACCURACY (AND HOW FAR THE OUTPUT MOVES, KL)

Intervention	Qwen3-8B	Llama-3.1-8B	Qwen3-1.7B
No intervention	*pending*	*pending*	53.5
Reset to harmless average	*pending*	*pending*	53.7 (0.00)
Pin at 10% of the attack pin	*pending*	*pending*	53.3 (0.01)
Pin at 25%	*pending*	*pending*	53.0 (0.08)
Pin at 50%	*pending*	*pending*	52.4 (0.22)
Pin at 100% (the attack)	*pending*	*pending*	48.3 (0.72)
Anchor pin	*pending*	*pending*	53.1 (0.12)
Nanda's ablation	*pending*	*pending*	51.7 (0.43)

Each cell: accuracy on 1,000 questions, and in brackets the average shift of the model's output from the unmodified model (0 = no change).

> **Result:** pending, the job is still running.

2. Does the neuron fire on MMLU at all?

THE QUESTION

Last time: "the anchor pin costs about 1 point". But the anchor only pushes when the neuron fires. How often does it fire on exam questions?

HYPOTHESIS

The neuron fires on very few MMLU questions, so the anchor is nearly off there, and the test shows little about its real cost.

WHAT WE DID

- Read the neuron on each of the 1,000 questions
- Count the questions that pass the detector cut-off
- Record the pin the anchor actually uses on each question
- Split accuracy into "fired" and "did not fire"

THE NEURON ON 1,000 MMLU QUESTIONS

	Qwen3-8B	Llama-3.1-8B	Qwen3-1.7B
Questions where the neuron fires	*pending*	*pending*	0 of 1,000
Pin the anchor actually uses: median (5th to 95th percentile)	*pending*	*pending*	+12.3 (+11.2 to +17.7)
Accuracy where it fired: no pin / constant / anchor	*pending*	*pending*	none fired
Accuracy where it did not fire: no pin / constant / anchor	*pending*	*pending*	53.5 / 48.3 / 53.1

For reference, the full attack pin is +20 (Qwen3-8B), −4 (Llama), +40 (Qwen3-1.7B).

> **Result:** pending, the job is still running.

3. How much do the top-5 lists overlap across languages?

Reference: the top 5 from our run of Apple's own English setup. Apple's paper prints only the winning neuron for each model, not its full list.

Model	Shared with the reference top 5: PolyRefuse (14 languages)	MultiJail (10 languages)	Apple's neuron is in	Most shared other neuron
Llama-3.1-8B	2–5 of 5	1–2 of 5 (English 5)	**23 of 24 lists**	L15:F9635, 20 of 24
Qwen3-8B	2–5 of 5	1–3 of 5	**18 of 24 lists**	L17:F11229, 18 of 24
Qwen3-1.7B	3–5 of 5	3–4 of 5	**21 of 24 lists**	L10:F244, 21 of 24

- Typically 2 to 5 of a language's top 5 are in the English reference list
- No neuron is in every language's top 5, because Yoruba shares none with the reference list on any model (Swahili none on Qwen3-1.7B)
- On Llama three of the five English candidates are English-only (in 2 to 5 lists); Apple's neuron and one neighbour are the ones that survive in every language

> **Apple's neuron is the most widely shared candidate:** in 18 to 23 of 24 language lists. Still to do: the same count for the top 10, 20 and 50.

4. Why is Apple's neuron not first in English on other datasets?

THE QUESTION

Last time's grid: Apple's neuron ranks 3rd, 6th and 2nd on PolyRefuse English. It was found in English, so why not 1st?

HYPOTHESIS

It is not first in Apple's own setup either: the search only makes a shortlist of 5, and trying each as an attack picks the winner. The exact rank moves with the prompts and the refusal phrases, because the top scores are close.

WHAT WE DID

- Rerun the English search, changing one ingredient at a time
- Prompts: Apple's, PolyRefuse English, or MultiJail English
- Refusal phrases: Apple's, or the model's own openings

RANK OF APPLE'S NEURON IN THE ENGLISH SEARCH

Prompts	Refusal phrases	Qwen3-8B	Llama-3.1-8B	Qwen3-1.7B
Apple's	Apple's	5	3	4
Apple's	model's own	*pending*	*pending*	2
PolyRefuse English	Apple's	*pending*	*pending*	5
PolyRefuse English	model's own	6	3	2
MultiJail English	Apple's	*pending*	*pending*	4
MultiJail English	model's own	2	4	1

Out of about 295,000 (Qwen3-8B), 301,000 (Llama) and 111,000 (Qwen3-1.7B) neurons. Row 1 is our replication of Apple's exact setup.

Already known: the neuron is in the top 6 of about 300,000 in every English setup, and never first even in Apple's own. The search shortlists; the attack test picks. The three missing rows are still running.

QUESTIONS FROM 5 NOVEMBER

5. Where the model does refuse, is the neuron there?

For each language: split the 100 harmful prompts into those the model refused and those it answered (no pin), and read the neuron on each group.

THE NEURON'S AVERAGE VALUE: ON REFUSED / ON ANSWERED / ON HARMLESS PROMPTS

Language	Qwen3-8B	Llama-3.1-8B	Qwen3-1.7B
English (PolyRefuse)	−4.1 / −1.7 / −0.2	+1.33 / +0.48 / +0.04	−10.5 / −9.9 / −1.3
German (PolyRefuse)	−3.0 / −2.1 / −0.3	+1.16 / +0.44 / +0.04	−9.3 / −6.3 / −1.0
Thai (PolyRefuse)	−2.9 / −1.4 / −0.3	+0.80 / +0.37 / +0.04	−7.8 / −4.8 / −0.9
Javanese (MultiJail)	**−2.6 / −1.6 / −0.2**	**+0.22 / +0.09 / +0.04**	**−5.1 / −4.0 / −0.5**
Swahili (MultiJail)	**−1.3 / −1.1 / −0.9**	**+0.58 / +0.18 / +0.06**	**+0.8 / +0.8 / +0.9**
Yoruba (PolyRefuse)	**−0.7 / −0.6 / −0.5**	**+0.10 / +0.10 / +0.05**	**−3.5 / −3.3 / −2.4**

- In almost every language the neuron fires most on refused prompts, less on answered ones, and not on harmless ones
- Javanese, and Swahili on Llama: the same pattern, only weaker. The circuit is intact; the language triggers it less
- Yoruba (all models) and Swahili (Qwen models): the neuron sits at its harmless level even on prompts labelled refused

> **The neuron tracks refusal prompt by prompt in every language except two.** In Yoruba and Qwen-Swahili either refusal goes another way, or the refusal labels are wrong: the judges read these languages poorly.

6. Is there a language-specific step in the smaller model?

THE QUESTION

Last time: on Qwen3-1.7B the neuron is second nearly everywhere and fails in Swahili. Maybe the small model has a language-specific step mixed into refusal?

HYPOTHESIS

If so, the small model's neuron should lose more of its strength outside English than the large model's does.

WHAT WE DID

- For every language: the neuron's gap between harmful and harmless prompts
- Divide by the same gap in English
- Compare Qwen3-1.7B with Qwen3-8B (same family)

THE NEURON'S STRENGTH AS A SHARE OF ENGLISH

Language	Qwen3-8B	Qwen3-1.7B	Llama-3.1-8B
Spanish	86%	98%	81%
French	82%	102%	84%
Arabic	72%	77%	65%
Japanese	67%	83%	75%
Thai	66%	68%	53%
Javanese (MultiJail)	58%	74%	15%
Swahili (MultiJail)	**13%**	**2%**	19%
Yoruba	**7%**	**8%**	**5%**

No sign of it in this measure. The small model keeps as much of its English strength as the large one in every language except Swahili. Yoruba is at 5–8% of English on all three models. Still to check: the layer where the signal first appears.

7. Why are Chinese and Vietnamese lower?

THE QUESTION

Last time: with the neuron pinned, MultiJail Chinese (63%) and Vietnamese (60%) gave fewer harmful answers than other languages. Is it the language?

HYPOTHESIS

It is the dataset. MultiJail has borderline prompts where answering is not harmful, and they are the same prompts in every language.

WHAT WE DID

- MultiJail has the same 100 prompts in every language
- Mark each pinned answer: refused, harmful, or answered but judged safe
- Check whether the "answered but safe" prompts are the same ones across languages

PINNED ANSWERS ON MULTIJAIL (QWEN3GUARD)

	Qwen3-8B	Llama-3.1-8B	Qwen3-1.7B
Harmful: English	72%	67%	76%
Harmful: Chinese	77%	78%	63%
Harmful: Vietnamese	86%	70%	60%
Still refused: Chinese / Vietnamese	9% / 2%	3% / 5%	8% / 6%
Answered but safe, 7 languages	13–17%	19–31%	22–39%
Share of those on the same 20 prompts	**61%**	**49%**	**49%**

Same Chinese on the other dataset, Qwen3-1.7B: PolyRefuse Chinese 87% harmful. By chance the same 20 prompts would hold about 20%.

It is the dataset, not the language. The pin removes refusal equally well in Chinese and Vietnamese (2–9% still refused). What differs is how many answers are judged harmless, and those fall on the same borderline prompts in every language.

8. The math: how a neuron's share of the direction is found

1. **Gap of each neuron:** g(i) = average value of neuron i on the 128 harmful prompts − its average on the 128 harmless prompts, at one template token
2. **The direction:** the list of all the gaps: (g(1), g(2), …, g(n)), with n = 12,288 neurons in that layer of Qwen3-8B
3. **Size of the direction:** square every gap and add them up: $g(1)^2 + g(2)^2 + \ldots + g(n)^2$
4. **Share of neuron i:** $g(i)^2 \div (g(1)^2 + g(2)^2 + \ldots + g(n)^2)$. All the shares add up to 100%
5. **Rank:** sort the neurons by share; the first is "the direction's top neuron"

WORKED EXAMPLE: QWEN3-8B, LAYER 14, APPLE'S NEURON F7924

Average on harmful	Average on harmless	Gap	Gap squared	Sum of all 12,288 squared gaps	Share
−4.41	−0.16	−4.24	18.0	about 78	**18.0 ÷ 78 = 23%**

> **One neuron out of 12,288 holds 23% of the direction.** If all neurons mattered equally, each would hold 0.008%. No other neuron in the layer holds more; the same is true on Llama (22%) and Qwen3-1.7B (18%).

9. The same breakdown in the residual stream

Two readings of the note. A: is any single residual-stream number a big part of the direction? B: how much of the direction does Apple's neuron account for?

A. THE RESIDUAL DIRECTION OVER ITS OWN NUMBERS

	Qwen3-8B	Llama-3.1-8B	Qwen3-1.7B
Largest single number's share	*pending*	*pending*	1.0%
Top 10 numbers together	*pending*	*pending*	7%
Spread over about … numbers	*pending*	*pending*	549 of 2,048
For comparison: largest neuron's share of the MLP direction	*pending*	*pending*	18%

B. APPLE'S NEURON'S SHARE OF THE RESIDUAL DIRECTION

	Qwen3-8B	Llama-3.1-8B	Qwen3-1.7B
Layer where Nanda's direction is read	*pending*	*pending*	15
Apple's neuron's share of it	*pending*	*pending*	5.3%
Its rank among its layer's neurons	*pending*	*pending*	1st of 6,144
Largest share of any single neuron	*pending*	*pending*	5.3% (Apple's)

- If A is tiny: no single residual-stream number carries the direction, which would explain why pinning one residual number jailbreaks only 16–32% (last time's slide 6)
- If B is small: the residual direction is mostly made by other parts of the model, which would explain why holding the neuron "on" did not undo Nanda's ablation (last time's slide 11)

> **Result:** pending, the job is still running.

STILL RUNNING LAST TIME: EVERY LANGUAGE

Pinning the neuron switches refusal off in every language but three

100 HELD-OUT HARMFUL PROMPTS PER LANGUAGE, APPLE'S NEURON AT ITS ENGLISH PIN

Model	PolyRefuse, 12–13 languages: harmful answers, no pin → pinned	Refused after the pin	MultiJail, 7–8 languages: harmful answers	K.1 criterion, pinned (PolyRefuse / MultiJail)
Qwen3-8B	**2–25% → 90–99%**	0–7%	2–9% → 66–86%	*pending*
Llama-3.1-8B	**4–52% → 87–96%**	0–6%	2–29% → 66–78%	*pending*
Qwen3-1.7B	**14–44% → 83–94%**	1–14%	6–20% → 51–76%	*pending*

THE THREE EXCEPTIONS: HARMFUL ANSWERS WITH THE PIN ON

Language	Qwen3-8B	Llama-3.1-8B	Qwen3-1.7B
Yoruba	1%	1%	1%
Swahili	3%	12%	4%
Javanese	36%	23%	10%

In these three the judges also disagree with each other, so the numbers are less certain than elsewhere.

One neuron, one pin value, found in English: it removes refusal in every well-resourced language on all three models. MultiJail's lower harmful rate is its borderline prompts (question 7).

Inside the MLP, in Arabic, on the two larger models

	Qwen3-8B, PolyRefuse	Qwen3-8B, MultiJail	Llama, PolyRefuse	Llama, MultiJail
Direction's top neuron (its share)	**Apple's (20%)**	Apple's (24%)	**Apple's (10%)**	*pending*
No intervention	9%	7%	13%	*pending*
Remove the MLP direction	12%	9%	16%	*pending*
Steer past harmless (α = 4)	**90%**	69%	**89%**	*pending*
Pin Apple's neuron	**95%**	76%	**91%**	*pending*
Nanda's ablation / with the neuron held on	85% / 83%	52% / 49%	90% / 89%	*pending*

% = Arabic answers judged harmful (Qwen3Guard). Row 1: the neuron with the biggest share of the Arabic MLP direction.

- Built from Arabic prompts, the direction's biggest neuron is again Apple's neuron
- Removing the direction barely helps (9% → 12%, 13% → 16%); pushing past harmless jailbreaks (89–95%)
- Holding the neuron on does not undo Nanda's ablation, as in English

All three findings from English hold in Arabic on both larger models.

STILL RUNNING LAST TIME: EVERY LANGUAGE

Can the neuron bring refusal back in low-resource languages?

THE QUESTION

Last time: in Yoruba and Swahili the neuron goes quiet and the models refuse less. If we switch the neuron on by hand, does refusal come back?

HYPOTHESIS

On Llama, yes: its one neuron also creates refusal in English. On the Qwen models probably not, because there the job is shared among several neurons.

WHAT WE DID

- 100 harmful prompts each in Yoruba, Swahili and Javanese
- Pin the neuron toward its harmful value, at 1×, 2× and 4×
- Count refusals; repeat on 100 harmless prompts to see the cost

HARMFUL PROMPTS REFUSED: NO PIN → STRONGEST PIN

	Qwen3-8B	Llama-3.1-8B	Qwen3-1.7B
Yoruba	*pending*	*pending*	*pending*
Swahili	*pending*	*pending*	*pending*
Javanese	*pending*	*pending*	*pending*
Harmless prompts refused at that pin	*pending*	*pending*	*pending*

SAME IDEA IN ENGLISH, 100 HARMLESS PROMPTS (COMPLETED)

	Qwen3-8B	Llama-3.1-8B	Qwen3-1.7B
Refused: no pin → strongest pin	0% → 13%	**0% → 90%**	0% → 4%

> **Result:** pending, the job is still running.

Next

Running, done by tomorrow

- K.1 judge on the per-language attacks, Llama and Qwen3-1.7B
- Rerank in the 9 language sets where Apple's neuron is outside the top 5
- The neuron as one guard across languages, against Llama-Guard and Qwen3Guard
- Arabic residual-stream baseline

Second halves of the questions

- Q3: overlap for the top 10, 20, 50
- Q5: search and pin on the refused prompts only; a refusal reading that works in Yoruba
- Q6: the layer where the signal first appears, per language
- Q9: the "held on" test at 2× and 4×

Then

- Job logs in the repository, and a how-to-run guide
- What the neuron responds to (needs a human reader)
- Writing (December), ARR 4 January
- After: images and audio