

A Kernel-Checked Exclusion for Erdős Problem 647 to 10^{13} via modular rungs proved inside the kernel and a sparse witness walk

Eero Tölö
Fjordmind Labs
labs@fjordmind.no

October 2026

Abstract

Erdős Problem 647 asks whether any $n > 24$ satisfies $\max_{m < n} (m + \tau(m)) \leq n + 2$, where τ is the divisor-count function. The largest range excluded end to end by a proof kernel was $(24, 10^9]$ (Mian–Siddique, *decanus*), via a contiguous chain of 6.7 million factorization witnesses that the authors describe as at the ceiling of the representation. We extend the kernel-checked exclusion to $(24, 10^{13}]$, a $10,000\times$ larger range, with a *smaller* certificate: 866,484 witnesses in about 21 MB of Lean source. The gain comes from proving the structural reduction inside the kernel first: four modular “rungs”, proved in Lean 4 without `native_decide`, force $360360 \mid n$ for every candidate $n > 10^5$ and confine $(n \bmod 17, 19, 23, 29)$ to 4,431 of 215,441 residue classes for $n > 10^{11}$. Only the surviving grid points then need a witness, and each needs one. The resulting theorem is stated in the vocabulary of the public formal statement and has axiom closure exactly `{propext, Classical.choice, Quot.sound}`. No new mathematics is claimed: the rungs re-derive, kernel-clean, a residue reduction previously verified only with `native_decide`. The contribution is the certificate architecture, together with a cost model showing where this family of methods stops: a kernel-checked horizon of 10^{17} – 10^{18} , not the 10^{22} unverified GPU frontier.

1 Introduction

Let $\tau(m)$ denote the number of divisors of m . Problem 647 in Bloom’s database of Erdős problems (Erdős–Selfridge) asks whether some $n > 24$ satisfies

$$\max_{m < n} (m + \tau(m)) \leq n + 2.$$

The condition holds at $n = 24$ and the problem is open. Computational exclusions reach 10^{12} by direct sieve (Idén), about 6.2×10^{17} via Hughes’s modular reduction (Lean plus `native_decide`, residue classes searched on a GPU), about 9.2×10^{18} (bentrd), and 10^{22} (GPU with CRT lifting, 2026). None of these is checked by a proof kernel. Mian and Siddique [1] gave the first kernel-checked exclusion, at 10^9 , and framed the natural next step as “structure rather than length”: certify the modular reduction inside the kernel so that only surviving classes need witnesses. This note does that.

Result.

`erdos647_no_solution_upto_1e13`: $\forall n : \mathbb{N}, 24 < n \rightarrow n \leq 10^{13} \rightarrow \neg \left(\bigsqcup_{m : \text{Fin } n} (m + \sigma_0 m) \leq n + 2 \right)$

(The Lean source states the bound as the literal 10000000000000; the file `Erdos647Sparse/Headline13.lean` in the repository has the exact text.) Lean 4.30.0 / Mathlib v4.30.0; `#print axioms` reports `[propext, Classical.choice, Quot.sound]`. The inner predicate is the one pinned by decanus from `google-deepmind/formal-conjectures` (`ErdosProblems/647.lean`, commit `c252a41`), so the theorem speaks the public formal statement’s vocabulary and composes with the decanus rung theorems. Source, certificates, generators and verification record: <https://github.com/fjordmindlabs/math> (directory `erdos647-sparse`).

Trust tier. As in decanus, this is a certification result, not a computational record; the range is nine orders of magnitude below the largest unverified computation. The claim is that every step from 24 to 10^{13} —the divisibility forced by each rung, the residue sieve, the divisor bound of every witness, the primality of every listed factor, and the gapless coverage of the surviving grid—is checked by the Lean kernel.

Contributions.

1. *Kernel-clean modular rungs* (§3): $2520 \mid n$ ($n > 1800$), $360360 \mid n$ ($n > 10^5$), a 41-class survivor list for $(n \bmod 17, n \bmod 19)$ ($n > 2.5 \times 10^8$), and a 4,431-class survivor list for $(n \bmod 17, 19, 23, 29)$ ($n > 10^{11}$). The 41-class list is an independent re-derivation of Hughes’s reduction mod 46189 with the `native_decide` trust removed.
2. *Rungs as certificate lists, not tactic proofs* (§3): the 22,916 class kills of the fourth rung are data checked by chunked `decide` under one generic soundness lemma, the same shape as the witness certificate.
3. *A sparse-walk certificate* (§4): one witness per surviving grid point; 866,484 witnesses over $(10^7, 10^{13}]$ versus 6,685,922 for decanus’s contiguous $(24, 10^9]$.
4. *Engineering for kernel scale* (§5): bitmask residue filters, chunk sizing from measured superlinear fuel cost, and a balanced binary-split driver after a linear `by_cases` ladder went quadratic at 1,525 chunks.
5. *A scaling analysis* (§7): what deeper rungs buy, a structural argument that no prime ≥ 17 is ever fully forced by this method, and a cost curve to 10^{22} .

2 The divisor-budget engine

Write $\text{Cand}(n)$ for $\forall m < n, m + \tau(m) \leq n + 2$. We proved `sup_iff_cand`: $\text{Cand}(n) \iff (\bigsqcup_{m:\text{Fin } n} m + \sigma_0 m \leq n + 2)$ (forward via `le_ciSup` over the finite range, backward via `ciSup.le`, with $n = 0$ by `ciSup.of_empty`), so all internal work is on Cand .

The single engine behind every rung is the *divisor budget*: $\text{Cand}(n)$ gives, for every shift $1 \leq k \leq n$, $\tau(n - k) \leq k + 2$. If $m = d \cdot t$ with $d < t$ then $\tau(m) \geq 2\tau(d)$, since the divisors of d and their t -multiples are disjoint by size (`two_mul_tau_le`). Hence:

Lemma 1 (rung). *If $\text{Cand}(n)$, $k \geq 1$, $d \mid n - k$ and $d^2 < n - k$, then $2\tau(d) \leq k + 2$.*

Contrapositively, a shift k whose forced divisor d of $n - k$ satisfies $2\tau(d) \geq k + 3$ kills n . Every rung is a table of (residue class, shift k , forced divisor d) with $2\tau(d) \geq k + 3$; all tables were enumerated and verified in Python first and then generated as Lean.

3 The modular rungs

Rung 1: $2520 \mid n$ for $n > 1800 \pmod{2520_of_cand}$. For each nonzero residue of n modulo 8, 3, 9, 5, 7 there is a shift $k \leq 6$ at which already-established divisibilities stack into some $d \in \{4, 8, 6, 12, 9, 18, 5, 10, 15, 20, 7, 14, 21, 28, 35, 42\}$ with $2\tau(d) > k + 2$. One uniform case per residue, closed by `omega`; the largest `decide` is $\tau(42) = 8$.

Rung 2: $360360 \mid n$ ($n > 10^5$) and 41 survivor classes mod $17 \cdot 19$ ($n > 2.5 \times 10^8$). With $2520 \mid n$, every nonzero residue mod 11 and mod 13 dies at some shift $k \leq 24$ where $\gcd(2520, k)$ stacks with 11 or 13 (tight cases: $r \equiv 7 \pmod{11}$ at $k = 18$, $d = 198$; $r \equiv 7 \pmod{13}$ at $k = 20$, $d = 260$; $r \equiv 11 \pmod{13}$ at $k = 24$, $d = 312$). Mod 17 and mod 19 do not fully eliminate: per-prime survivors are $\{0, 11, 13, 14, 15, 16\} \pmod{17}$ and $\{0, 7, 11, 13, 14, 15, 16, 17\} \pmod{19}$ (48 pairs), of which 7 die only to joint shifts where $17 \cdot 19 = 323$ enters one divisor (largest $d = 14535$ at $k = 45$). The 41 survivors equal, under $2520 \equiv 4 \pmod{17}$, $\equiv 12 \pmod{19}$, the 41 classes of $N = n/2520 \pmod{46189}$ in Hughes’s reduction, derived independently and kernel-clean. The threshold 2.5×10^8 is 14535^2 rounded.

Rung 4: 4,431 survivor classes mod $17 \cdot 19 \cdot 23 \cdot 29$ ($n > 10^{11}$). (The development numbers the bridge and sparse-walk step as “rung 3”; we keep the code’s names.) Adding 23 and 29 jointly thins the $41 \times 23 \times 29 = 27,347$ classes to 4,431 (a $6.17\times$ sparsification; shifts $k \leq 90$; the largest forced stack is $17 \cdot 19 \cdot 23 \cdot 29 = 215,441$, whence the 10^{11} validity threshold via $d^2 < n$). The decisive design change from rung 2: *the kills are certificates, not tactic cases*. A certificate (i, k, ps) stores, for flat class index i , a shift k and the full factorization ps of the forced stack $d_{i,k}$, reusing decanus’s `witness0k` and `witness_tau` for the $\tau(d)$ lower bound. The soundness lemma discharges the CRT divisibility (`Nat.modEq_iff_dvd`’ per prime plus coprime stacking). A positional walker consumes the 27,347-class flat grid: each class is either the next kill certificate or the next listed survivor, and the walker’s soundness lemma yields “every class is killed or in the survivor list”. Twenty-eight chunks of 1,000 classes, one `decide` each (≈ 5 s). A rung-2-style tactic ladder over 27k cases would have been infeasible; the certificate form built in about five minutes.

Mod 23 alone and mod 29 alone give only $2.67\times$ and $2.16\times$; the joint rung is worth building and, per §7, is the last one that clearly is.

4 The sparse-walk certificate

After the rungs, a candidate $n \in (10^7, 10^{13}]$ is a multiple of 360360, say $n = 360360j$ with $j \in [28, 27,750,027]$, and above the respective thresholds lies in a surviving residue class. The *grid filter* encodes which j still need killing:

- $(10^7, 10^{12}]$: `gridFilter` $n = (n \leq 2.5 \times 10^8) \vee \text{class0k } n$; below the rung-2 threshold every multiple of 360360 needs a witness (932 extra points), above it only the 41 classes.
- $(10^{12}, 10^{13}]$: `gridFilter13` $n = (n \leq 10^{11}) \vee (\text{mask323.testBit}(n \bmod 323) \wedge \text{mask27k.testBit}(\text{flatIdx } n))$ the 41-pair and 4,431-index survivor lists become two natural-number bitmask literals tested by `Nat.testBit` (GMP-accelerated shifts) instead of list scans. Bridge lemmas tie the masks to the proved rung theorems, so the headline derives `gridFilter13 n = true` for any candidate.

Kill witnesses. A surviving grid point n is killed by one $m = n - k$ with certified $\tau(m) \geq k + 3$, in decanus’s witness format (maximal prime powers $p < 1024$, so primality of listed factors is eleven trial divisions). Because n is a multiple of 360360 its neighbourhood is divisor-rich and kills are cheap: over $(10^9, 10^{11}]$ the mean shift is $k = 1.9$, the median 1 (52.8% of points die at $k = 1$, i.e. $\tau(n - 1) \geq 4$), the maximum 16; over $(10^{12}, 10^{13}]$ the mean is ≈ 1.75 and the maximum 8 on a sample. `kill0k n k ps` adds the explicit conjunct $0 < k$: decanus’s `witness0k` alone admits offset 0, which an `omega` countermodel caught during the soundness proof.

The walker. `sparse0k fuel j ws` : Bool steps j through a chunk’s grid range; at each j it evaluates the filter and, if the point survives, requires the next witness in ws to kill exactly 360360 j , consuming it; non-surviving points consume nothing; leftovers are rejected. Its soundness lemma says a passing chunk kills every surviving grid point of its range. Each chunk is a single by `decide`.

Counts. $(10^7, 10^{12}]$: 352,823 witnesses in 678 chunks of 4,096 grid indices (8.3 MB). $(10^{12}, 10^{13}]$: 513,661 witnesses in 1,525 chunks of 16,384 indices (12.3 MB). Rung-4 kill certificates: 22,916 (0.76 MB). Total ≈ 21 MB of generated Lean for the whole 10^{13} result, against 38.5 MB for decanus’s in-repository 10^8 chain and ≈ 260 MB for its 10^9 release asset.

Composition. $n \leq 10^7$ by decanus’s `killed_upto` (the in-repository 31-chunk chain); $10^7 < n \leq 10^{12}$ by the 10^{12} grid theorem; $10^{12} < n \leq 10^{13}$ by the fast-filter grid theorem together with the rung-4 and rung-2 theorems; each case closed through decanus’s `not_sup_le_of_killed`.

5 Engineering at kernel scale

- **Chunk size from measured fuel cost.** Walk cost per grid point under the fast filter is ≈ 2.5 ms isolated and ≈ 7 ms under 8-way load; fuel-recursion cost is superlinear in chunk length ($\sim \text{fuel}^{1.7}$: $16,384 \rightarrow 43$ s, $32,768 \rightarrow 139$ s). Chunks of 16,384 keep the median at ≈ 90 s and the 10^{13} walk at 48.8 CPU-hours.
- **Drivers must be trees.** The 678-branch linear `by_cases` ladder for 10^{12} elaborated in 286 s. The 1,525-branch ladder for 10^{13} reached 23 GB RSS at 21 minutes and was killed: each negated branch hypothesis stays in the `omega` context, so the ladder is quadratic. The replacement emits one span lemma per chunk and an 11-level balanced binary merge tree whose nodes each do one `by_cases` with $O(1)$ context: 3,050 small theorems, 56 s.
- **Survivor membership in $O(1)$.** Deciding membership of a flat index in a 4,431-element list inside the kernel via Boolean sublist checks is quadratic and exceeded a ten-minute budget; per-survivor `List.mem_append` embedding terms are $O(1)$.
- **omega modulus blow-up.** `omega`’s cost grows with the lcm of all modular facts in context; $(n - 45) = 14535 \cdot ((n - 45)/14535)$ proves in ≈ 10 s from exactly $\{n \bmod 45 = 0, n \bmod 17 = 11, n \bmod 19 = 7\}$ and times out if $n \bmod 2520 = 0$ is also present. Derive per-case minimal facts and clear the rest.
- **Generate, do not hand-write.** Every table is enumerated and verified in Python, then emitted as Lean; the Python verifier mirrors decanus’s `witness0k` semantics, and

a coverage verifier checks exact one-witness-per-surviving-point alignment over the whole grid before any Lean is emitted.

6 Verification record

Check	10^{11}	10^{12}	10^{13}
Python coverage verifier (exact alignment, every witness replayed)	35,803 OK	352,823 OK	513,803 OK
Lean build (4.30.0 / Mathlib v4.30.0)	exit 0	exit 0, 9,194 jobs	exit 0, 9,194 jobs
<code>#print axioms</code> on headline	3 standard	same	same
<code>sorry</code> / <code>native_decide</code> tokens	none	none	none
Kernel time	68×35 s	678 chunks, median 80 s	1,500 chunks, median 80 s

A two-layer axiom gate mirroring decanus’s (a curated `#print axioms` manifest of 19 theorems plus a whole-library audit that recomputes the axiom closure of every theorem in every `Erdos647Sparse` module from the compiled environment) passes: 8,090 theorems across 2,242 modules, all within `{propext, Classical.choice, Quot.sound}`. Not yet done: a `lean4checker` replay of the modules and a second from-source build on independent hardware; every build so far ran once on one 8-core desktop, the trust status decanus assigns its own 10^9 rung.

7 What this does and does not show

Mathematical novelty: none claimed. The modular ladder (Dutta–Alexeev), the shift condition (Kitamura) and the residue reduction (Hughes) are prior work; rung 2 is Hughes’s reduction with the `native_decide` trust removed, and rung 4 is its predictable extension. The problem is open and nothing here bears on whether a solution exists.

Methodological point. Certificate architecture, not compute, moved the kernel-checked frontier four orders of magnitude at lower artifact size. The two levers were (a) proving the structure inside the kernel so that the certificate covers only the sparse survivor grid, and (b) representing the structure itself (the rung kills) as data checked by `decide` under one generic soundness lemma, so that a rung costs minutes rather than a week of tactic engineering.

Limits, quantified. A sweep of the divisor-budget engine over sieve primes 17 to 97 and validity thresholds 10^{11} to 10^{21} (exact enumeration to 3×10^6 classes, Monte Carlo beyond; details in the repository appendix) gives:

1. Each added sieve prime kills a shrinking share of the remaining classes: 63% at 23, 56% at 31, 48% at 37, 44% at 41, 35% at 61, 22% at 97. A prime p helps only at shifts $k \equiv c_p \pmod{p}$, and useful k stay below about 170.
2. *Full divisibility by any prime $p \geq 17$ is never forced.* The class $c_{17} = 16$, all other residues 0, survives at every threshold: in it a sieve prime $q \neq 17$ matches shift k only if $q \mid k$, so the matched stack divides k , $d \leq k$, and the budget $2\tau(d) \geq k + 3$ would need $\tau(d) > d/2$, possible only for $d \in \{1, 2, 3, 4, 6\}$, none reachable with $k \equiv 16 \pmod{17}$. Hence 360360 is the final forced modulus; all further sieving is residue thinning, never grid coarsening.

3. Survivor-class counts grow $20\text{--}50\times$ per rung (4.4×10^3 at rung 4, 2.6×10^7 at rung 7 with primes ≤ 41); a kernel-checked literal above $\sim 10^8$ entries is outside anything built so far, so rung 7 is the practical ceiling of an enumerable sieve, with density floor $f \approx 2.5 \times 10^{-3}$.
4. The present walk visits every multiple of 360360 and costs $\propto T$ regardless of sieve depth; it walls at $10^{14}\text{--}10^{15}$. A *period walk* that steps only through surviving residues per period is the one structural lever left and buys about two decades: $10^{17}\text{--}10^{18}$ at roughly one CPU-year.
5. With any certifiable sieve, 10^{22} needs $\approx 7 \times 10^{13}$ witnesses, i.e. $10^3\text{--}10^4$ CPU-years; even an uncertifiable 19-prime sieve leaves $\geq 4 \times 10^{11}$ witnesses. A kernel-checked 10^{22} therefore needs a different proof object—kills for whole arithmetic progressions at once, so that the witness count stops being $\propto T$ —which is a research question, not an engineering one.

Credit and provenance

Built on decanus [1] (Apache-2.0): witness format, `TauLower/Chain/Bridge` soundness, the 10^7 chain, and the pinned formal-conjectures statement. Structural mathematics: Dutta–Alexeev, Kitamura, Hughes (erdosproblems.com forum, problem 647). Reference computations: Idén (10^{12}), Hughes (6.2×10^{17}), bentrd (9.2×10^{18}), veljjanoski (10^{22}).

The Lean proofs, the Python generators and verifiers, and the first draft of this note were produced by an AI agent operated by Fjordmind Labs, working with compiler feedback under human direction; the author set the goals, reviewed the results, and is responsible for the claims. Nothing in the trust argument depends on how the proofs were written: the Lean kernel checks them the same way.

References

- [1] I. Mian and S. Siddique, *A Kernel-Checked Exclusion Certificate for Erdős Problem 647*, arXiv:2608.17880 (2026). Code: <https://github.com/ibrahimmian36/decanus>.
- [2] T. Bloom, *Erdős Problems*, problem 647, <https://www.erdosproblems.com/647>.
- [3] Google DeepMind, *formal-conjectures*, `FormalConjectures/ErdosProblems/647.lean`, commit `c252a41`.
- [4] The Mathlib Community, *Mathlib*, v4.30.0, <https://github.com/leanprover-community/mathlib4>.