

Chapter 5: Process Scheduling





Chapter 5: Process Scheduling

Basic Concepts

Scheduling Criteria

Scheduling Algorithms

Thread Scheduling


Multiple-Processor Scheduling

Real-Time CPU Scheduling

Operating Systems Examples

Algorithm Evaluation





Objectives


To introduce CPU scheduling, which is the basis for multiprogrammed operating systems

To describe various CPU-scheduling algorithms

To discuss evaluation criteria for selecting a CPU-scheduling algorithm for a particular system

To examine the scheduling algorithms of several operating systems





Basic Concepts

Maximum CPU utilization obtained with multiprogramming

CPU-I/O Burst Cycle – Process execution consists of a cycle of CPU execution and I/O wait

CPU burst followed by I/O burst

CPU burst distribution is of main concern

load store add store read from file

wait for I/O

store increment index write to file

wait for I/O

load store add store read from file

wait for I/O

•

CPU burst


I/O burst

CPU burst


I/O burst

CPU burst

· I/O burst



Histogram of CPU-burst Times







CPU Scheduler

Short-term scheduler selects from among the processes in ready queue, and allocates the CPU to one of them

Queue may be ordered in various ways

CPU scheduling decisions may take place when a process:

- 1. Switches from running to waiting state
- 2. Switches from running to ready state
- 3. Switches from waiting to ready
- 4. Terminates

Scheduling under 1 and 4 is nonpreemptive

All other scheduling is preemptive

Consider access to shared data

Consider preemption while in kernel mode

Consider interrupts occurring during crucial OS activities





Dispatcher

Dispatcher module gives control of the CPU to the process selected by the short-term scheduler; this involves:

switching context

switching to user mode

jumping to the proper location in the user program to restart that program

Dispatch latency – time it takes for the dispatcher to stop one process and start another running





Scheduling Criteria

CPU utilization – keep the CPU as busy as possible


Throughput – # of processes that complete their execution per time unit

Turnaround time – amount of time to execute a particular process

Waiting time – amount of time a process has been waiting in the ready queue

Response time – amount of time it takes from when a request was submitted until the first response is produced, not output (for time-sharing environment)





Scheduling Algorithm Optimization Criteria

Max CPU utilization


Max throughput

Min turnaround time

Min waiting time

Min response time






First-Come, First-Served (FCFS) Scheduling

| <u>Process</u> | Burst Time |
|----------------|-------------------|
| P_1 | 24 |
| P_2 | 3 |
| P_3 | 3 |


Suppose that the processes arrive in the order: P_1 , P_2 , P_3 The Gantt Chart for the schedule is:



Waiting time for $P_1 = 0$; $P_2 = 24$; $P_3 = 27$

Average waiting time: (0 + 24 + 27)/3 = 17






FCFS Scheduling (Cont.)

Suppose that the processes arrive in the order:

$$P_2$$
, P_3 , P_1

The Gantt chart for the schedule is:




Waiting time for $P_1 = 6$; $P_2 = 0$; $P_3 = 3$

Average waiting time: (6 + 0 + 3)/3 = 3

Much better than previous case

Convoy effect - short process behind long process

Consider one CPU-bound and many I/O-bound processes



Shortest-Job-First (SJF) Scheduling

Associate with each process the length of its next CPU burst


Use these lengths to schedule the process with the shortest time

SJF is optimal – gives minimum average waiting time for a given set of processes

The difficulty is knowing the length of the next CPU request

Could ask the user






Example of SJF

| <u>Process</u> | Burst Time |
|----------------|------------|
| P_1 | 6 |
| P_2 | 8 |
| P_3 | 7 |
| P_4 | 3 |

SJF scheduling chart



Average waiting time = (3 + 16 + 9 + 0) / 4 = 7





Determining Length of Next CPU Burst

Can only estimate the length – should be similar to the previous one Then pick process with shortest predicted next CPU burst


Can be done by using the length of previous CPU bursts, using exponential averaging

- 1. $t_n = \text{actual length of } n^{th} \text{ CPU burst}$
- 2. τ_{n+1} = predicted value for the next CPU burst
- 3. α , $0 \le \alpha \le 1$
- 4. Define: $\tau_{n=1} = \alpha t_n + (1-\alpha)\tau_n$.


Commonly, α set to $\frac{1}{2}$

Preemptive version called **shortest-remaining-time-first**







Prediction of the Length of the Next CPU Burst



CPU burst (t_i) 6 4 6 4 13 13 ...

"guess" (τ_i) 10 8 6 6 5 9 11 12 ...





Examples of Exponential Averaging

$$\alpha = 0$$

$$\tau_{n+1} = \tau_n$$

Recent history does not count

$$\alpha = 1$$

$$\tau_{n+1} = \alpha t_n$$


Only the actual last CPU burst counts

If we expand the formula, we get:

$$\tau_{n+1} = \alpha t_n + (1 - \alpha)\alpha t_n - 1 + \dots + (1 - \alpha)^j \alpha t_{n-j} + \dots + (1 - \alpha)^{n+1} \tau_0$$

Since both α and (1 - α) are less than or equal to 1, each successive term has less weight than its predecessor






Example of Shortest-remaining-time-first

Now we add the concepts of varying arrival times and preemption to the analysis


| <u>Process</u> | <u>Arrival Time</u> | Burst Time |
|----------------|---------------------|------------|
| P_1 | 0 | 8 |
| P_2 | 1 | 4 |
| P_3 | 2 | 9 |
| P_4 | 3 | 5 |

Preemptive SJF Gantt Chart



Average waiting time = [(10-1)+(1-1)+(17-2)+5-3)]/4 = 26/4 = 6.5 msec





Priority Scheduling

A priority number (integer) is associated with each process

The CPU is allocated to the process with the highest priority (smallest integer ≡ highest priority)

Preemptive


Nonpreemptive

SJF is priority scheduling where priority is the inverse of predicted next CPU burst time

Problem = Starvation – low priority processes may never execute

Solution \equiv Aging – as time progresses increase the priority of the process





Example of Priority Scheduling

| <u>Process</u> | Burst Time | <u>Priority</u> |
|----------------|------------|-----------------|
| P_1 | 10 | 3 |
| P_2 | 1 | 1 |
| P_3 | 2 | 4 |
| P_4 | 1 | 5 |
| P_5 | 5 | 2 |

Priority scheduling Gantt Chart

| | P ₂ | P ₅ | | P ₁ | P ₃ | P ₄ | |
|---|----------------|----------------|---|----------------|----------------|----------------|---------|
| 0 | 1 | | 6 | 1 | 6 1 | 8 | _ 19 |

Average waiting time = 8.2 msec





Round Robin (RR)

Each process gets a small unit of CPU time (time quantum q), usually 10-100 milliseconds. After this time has elapsed, the process is preempted and added to the end of the ready queue.

If there are n processes in the ready queue and the time quantum is q, then each process gets 1/n of the CPU time in chunks of at most q time units at once. No process waits more than (n-1)q time units.

Timer interrupts every quantum to schedule next process

Performance

 $q \text{ large} \Rightarrow \text{FIFO}$

 $q \text{ small} \Rightarrow q \text{ must be large with respect to context switch, otherwise overhead is too high$





Example of RR with Time Quantum = 4

| <u>Process</u> | Burst Time |
|----------------|-------------------|
| P_1 | 24 |
| P_2 | 3 |
| P_3 | 3 |


The Gantt chart is:

| | P ₁ | P ₂ | P ₃ | P ₁ |
|---|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|
| 0 | 4 | | 7 1 | 0 ′ | 14 1 | 8 22 | 26 | 30 |


Typically, higher average turnaround than SJF, but better *response* q should be large compared to context switch time q usually 10ms to 100ms, context switch < 10 usec




Time Quantum and Context Switch Time








Turnaround Time Varies With The Time Quantum



| process | time |
|---------|------|
| P_1 | 6 |
| P_2 | 3 |
| P_3 | 1 |
| P_4 | 7 |

80% of CPU bursts should be shorter than q





Multilevel Queue

Ready queue is partitioned into separate queues, eg:

foreground (interactive)

background (batch)

Process permanently in a given queue

Each queue has its own scheduling algorithm:

foreground – RR

background – FCFS

Scheduling must be done between the queues:

Fixed priority scheduling; (i.e., serve all from foreground then from background). Possibility of starvation.

Time slice – each queue gets a certain amount of CPU time which it can schedule amongst its processes; i.e., 80% to foreground in RR


20% to background in FCFS






Multilevel Queue Scheduling

highest priority



lowest priority





Multilevel Feedback Queue

A process can move between the various queues; aging can be implemented this way

Multilevel-feedback-queue scheduler defined by the following parameters:


number of queues

scheduling algorithms for each queue

method used to determine when to upgrade a process

method used to determine when to demote a process

method used to determine which queue a process will enter when that process needs service





Example of Multilevel Feedback Queue

Three queues:

 Q_0 – RR with time quantum 8 milliseconds

Q₁ – RR time quantum 16 milliseconds

 $Q_2 - FCFS$


Scheduling

A new job enters queue Q_0 which is served FCFS


- When it gains CPU, job receives 8 milliseconds
- If it does not finish in 8 milliseconds, job is moved to queue Q₁

At Q_1 job is again served FCFS and receives 16 additional milliseconds

If it still does not complete, it is preempted and moved to queue Q₂








Thread Scheduling


Distinction between user-level and kernel-level threads

When threads supported, threads scheduled, not processes

Many-to-one and many-to-many models, thread library schedules user-level threads to run on LWP Known as process-contention scope (PCS) since scheduling competition is within the process Typically done via priority set by programmer

Kernel thread scheduled onto available CPU is system-contention scope (SCS) – competition among all threads in system





Pthread Scheduling


API allows specifying either PCS or SCS during thread creation

PTHREAD_SCOPE_PROCESS schedules threads using PCS scheduling

PTHREAD_SCOPE_SYSTEM schedules threads using SCS scheduling

Can be limited by OS – Linux and Mac OS X only allow PTHREAD_SCOPE_SYSTEM






Pthread Scheduling API

```
#include <pthread.h>
#include <stdio.h>
#define NUM THREADS 5
int main(int argc, char *argv[]) {
   int i, scope;
  pthread t tid[NUM THREADS];
  pthread attr t attr;
   /* get the default attributes */
   pthread attr init(&attr);
   /* first inquire on the current scope */
   if (pthread attr getscope(&attr, &scope) != 0)
      fprintf(stderr, "Unable to get scheduling scope\n");
   else {
      if (scope == PTHREAD SCOPE PROCESS)
         printf("PTHREAD SCOPE PROCESS");
      else if (scope == PTHREAD SCOPE SYSTEM)
         printf("PTHREAD SCOPE SYSTEM");
      else
         fprintf(stderr, "Illegal scope value.\n");
```





Pthread Scheduling API

```
/* set the scheduling algorithm to PCS or SCS */
  pthread attr setscope(&attr, PTHREAD SCOPE SYSTEM);
   /* create the threads */
   for (i = 0; i < NUM THREADS; i++)
      pthread create(&tid[i],&attr,runner,NULL);
   /* now join on each thread */
   for (i = 0; i < NUM THREADS; i++)
     pthread join(tid[i], NULL);
/* Each thread will begin control in this function */
void *runner(void *param)
   /* do some work ... */
  pthread exit(0);
```



Multiple-Processor Scheduling

CPU scheduling more complex when multiple CPUs are available

Homogeneous processors within a multiprocessor

Asymmetric multiprocessing – only one processor accesses the system data structures, alleviating the need for data sharing

Symmetric multiprocessing (SMP) – each processor is self-scheduling, all processes in common ready queue, or each has its own private queue of ready processes


Currently, most common

Processor affinity – process has affinity for processor on which it is currently running soft affinity


hard affinity

Variations including processor sets





NUMA and CPU Scheduling



Note that memory-placement algorithms can also consider affinity



Multiple-Processor Scheduling – Load Balancing


If SMP, need to keep all CPUs loaded for efficiency

Load balancing attempts to keep workload evenly distributed

Push migration – periodic task checks load on each processor, and if found pushes task from overloaded CPU to other CPUs

Pull migration – idle processors pulls waiting task from busy processor





Multicore Processors

Recent trend to place multiple processor cores on same physical chip

Faster and consumes less power


Multiple threads per core also growing


Takes advantage of memory stall to make progress on another thread while memory retrieve happens





Multithreaded Multicore System







Real-Time CPU Scheduling


Can present obvious challenges

Soft real-time systems – no guarantee as to when critical real-time process will be scheduled


Hard real-time systems – task must be serviced by its deadline

Two types of latencies affect performance

- Interrupt latency time from arrival of interrupt to start of routine that services interrupt
- Dispatch latency time for schedule to take current process off CPU and switch to another









Real-Time CPU Scheduling (Cont.)

Conflict phase of dispatch latency:

- Preemption of any process running in kernel mode
- Release by low-priority process of resources needed by high-priority processes







Priority-based Scheduling

For real-time scheduling, scheduler must support preemptive, priority-based scheduling

But only guarantees soft real-time


For hard real-time must also provide ability to meet deadlines

Processes have new characteristics: periodic ones require CPU at constant intervals


Has processing time *t*, deadline *d*, period *p*

$$0 \le t \le d \le p$$

Rate of periodic task is 1/p







Virtualization and Scheduling

Virtualization software schedules multiple guests onto CPU(s)

Each guest doing its own scheduling


Not knowing it doesn't own the CPUs

Can result in poor response time

Can effect time-of-day clocks in guests

Can undo good scheduling algorithm efforts of guests






Rate Montonic Scheduling


A priority is assigned based on the inverse of its period

Shorter periods = higher priority;


Longer periods = lower priority

 P_1 is assigned a higher priority than P_2 .





Missed Deadlines with Rate Monotonic Scheduling







Earliest Deadline First Scheduling (EDF)

Priorities are assigned according to deadlines:

the earlier the deadline, the higher the priority; the later the deadline, the lower the priority






Proportional Share Scheduling

T shares are allocated among all processes in the system

An application receives N shares where N < T

This ensures each application will receive N/T of the total processor time





POSIX Real-Time Scheduling

The POSIX.1b standard

API provides functions for managing real-time threads

Defines two scheduling classes for real-time threads:

- SCHED_FIFO threads are scheduled using a FCFS strategy with a FIFO queue. There is no time-slicing for threads of equal priority
- 2. SCHED_RR similar to SCHED_FIFO except time-slicing occurs for threads of equal priority

Defines two functions for getting and setting scheduling policy:

- pthread attr getsched policy(pthread attr t *attr, int *policy)
- 2. pthread attr setsched policy(pthread attr t *attr, int policy)





POSIX Real-Time Scheduling API


```
#include <pthread.h>
#include <stdio.h>
#define NUM THREADS 5
int main(int argc, char *argv[])
   int i, policy;
   pthread t tid[NUM THREADS];
  pthread attr t attr;
   /* get the default attributes */
  pthread attr init(&attr);
   /* get the current scheduling policy */
   if (pthread attr getschedpolicy(&attr, &policy) != 0)
      fprintf(stderr, "Unable to get policy.\n");
   else {
      if (policy == SCHED OTHER) printf("SCHED OTHER\n");
      else if (policy == SCHED RR) printf("SCHED RR\n");
      else if (policy == SCHED FIFO) printf("SCHED FIFO\n");
```





```
/* set the scheduling policy - FIFO, RR, or OTHER */
   if (pthread attr setschedpolicy(&attr, SCHED FIFO) != 0)
      fprintf(stderr, "Unable to set policy.\n");
   /* create the threads */
   for (i = 0; i < NUM THREADS; i++)
      pthread create(&tid[i], &attr, runner, NULL);
   /* now join on each thread */
   for (i = 0; i < NUM THREADS; i++)
      pthread join(tid[i], NULL);
/* Each thread will begin control in this function */
void *runner(void *param)
{
   /* do some work ... */
   pthread exit(0);
```





Operating System Examples

Linux scheduling

Windows scheduling

Solaris scheduling



Linux Scheduling Through Version 2.5

Prior to kernel version 2.5, ran variation of standard UNIX scheduling algorithm Version 2.5 moved to constant order *O*(1) scheduling time

Preemptive, priority based

Two priority ranges: time-sharing and real-time

Real-time range from 0 to 99 and nice value from 100 to 140

Map into global priority with numerically lower values indicating higher priority

Higher priority gets larger q

Task run-able as long as time left in time slice (active)

If no time left (expired), not run-able until all other tasks use their slices

All run-able tasks tracked in per-CPU runqueue data structure

- Two priority arrays (active, expired)
- Tasks indexed by priority
- When no more active, arrays are exchanged

Worked well, but poor response times for interactive processes





Completely Fair Scheduler (CFS)

Scheduling classes

Each has specific priority

Scheduler picks highest priority task in highest scheduling class

Rather than quantum based on fixed time allotments, based on proportion of CPU time

2 scheduling classes included, others can be added

- 1. default
- 2. real-time

Quantum calculated based on nice value from -20 to +19

Lower value is higher priority

Calculates target latency – interval of time during which task should run at least once

Target latency can increase if say number of active tasks increases


CFS scheduler maintains per task virtual run time in variable vruntime

Associated with decay factor based on priority of task – lower priority is higher decay rate

Normal default priority yields virtual run time = actual run time


To decide next task to run, scheduler picks task with lowest virtual run time






CFS Performance

The Linux CFS scheduler provides an efficient algorithm for selecting which task to run next. Each runnable task is placed in a red-black tree—a balanced binary search tree whose key is based on the value of vruntime. This tree is shown below:



When a task becomes runnable, it is added to the tree. If a task on the tree is not runnable (for example, if it is blocked while waiting for I/O), it is removed. Generally speaking, tasks that have been given less processing time (smaller values of vruntime) are toward the left side of the tree, and tasks that have been given more processing time are on the right side. According to the properties of a binary search tree, the leftmost node has the smallest key value, which for the sake of the CFS scheduler means that it is the task with the highest priority. Because the red-black tree is balanced, navigating it to discover the leftmost node will require O(lgN) operations (where N is the number of nodes in the tree). However, for efficiency reasons, the Linux scheduler caches this value in the variable rb_leftmost, and thus determining which task to run next requires only retrieving the cached value.





Linux Scheduling (Cont.)

Real-time scheduling according to POSIX.1b

Real-time tasks have static priorities

Real-time plus normal map into global priority scheme


Nice value of -20 maps to global priority 100

Nice value of +19 maps to priority 139

| | Real-Time | | No | ormal |
|--------------------|-----------|----------|-----|-------|
| 0 | | 99 | 100 | 139 |
| ← Higher | | Priority | | Lower |

6.52





Windows Scheduling

Windows uses priority-based preemptive scheduling

Highest-priority thread runs next

Dispatcher is scheduler

Thread runs until (1) blocks, (2) uses time slice, (3) preempted by higher-priority thread

Real-time threads can preempt non-real-time

32-level priority scheme

Variable class is 1-15, real-time class is 16-31

Priority 0 is memory-management thread

Queue for each priority

If no run-able thread, runs idle thread





Windows Priority Classes

Win32 API identifies several priority classes to which a process can belong

REALTIME_PRIORITY_CLASS, HIGH_PRIORITY_CLASS, ABOVE_NORMAL_PRIORITY_CLASS, NORMAL_PRIORITY_CLASS, BELOW_NORMAL_PRIORITY_CLASS, IDLE_PRIORITY_CLASS

All are variable except REALTIME

A thread within a given priority class has a relative priority

TIME_CRITICAL, HIGHEST, ABOVE_NORMAL, NORMAL, BELOW_NORMAL, LOWEST, IDLE

Priority class and relative priority combine to give numeric priority

Base priority is NORMAL within the class

If quantum expires, priority lowered, but never below base

If wait occurs, priority boosted depending on what was waited for

Foreground window given 3x priority boost

Windows 7 added user-mode scheduling (UMS)

Applications create and manage threads independent of kernel

For large number of threads, much more efficient


UMS schedulers come from programming language libraries like C++ Concurrent Runtime (ConcRT) framework





Windows Priorities

| | real- time | high | above normal | normal | below normal | idle priority |
|---------------|---------------|------|-----------------|--------|-----------------|------------------|
| time-critical | 31 | 15 | 15 | 15 | 15 | 15 |
| highest | 26 | 15 | 12 | 10 | 8 | 6 |
| above normal | 25 | 14 | 11 | 9 | 7 | 5 |
| normal | 24 | 13 | 10 | 8 | 6 | 4 |
| below normal | 23 | 12 | 9 | 7 | 5 | 3 |
| lowest | 22 | 11 | 8 | 6 | 4 | 2 |
| idle | 16 | 1 | 1 | 1 | 1 | 1 |





Solaris

Priority-based scheduling

Six classes available

Time sharing (default) (TS)

Interactive (IA)

Real time (RT)

System (SYS)

Fair Share (FSS)

Fixed priority (FP)


Given thread can be in one class at a time

Each class has its own scheduling algorithm

Time sharing is multi-level feedback queue

Loadable table configurable by sysadmin






Solaris Dispatch Table

| priority | time quantum | time quantum expired | return from sleep |
|----------|-----------------|----------------------------|-------------------------|
| 0 | 200 | 0 | 50 |
| 5 | 200 | 0 | 50 |
| 10 | 160 | 0 | 51 |
| 15 | 160 | 5 | 51 |
| 20 | 120 | 10 | 52 |
| 25 | 120 | 15 | 52 |
| 30 | 80 | 20 | 53 |
| 35 | 80 | 25 | 54 |
| 40 | 40 | 30 | 55 |
| 45 | 40 | 35 | 56 |
| 50 | 40 | 40 | 58 |
| 55 | 40 | 45 | 58 |
| 59 | 20 | 49 | 59 |






Solaris Scheduling







Solaris Scheduling (Cont.)


Scheduler converts class-specific priorities into a per-thread global priority

Thread with highest priority runs next

Runs until (1) blocks, (2) uses time slice, (3) preempted by higher-priority thread

Multiple threads at same priority selected via RR





Algorithm Evaluation

How to select CPU-scheduling algorithm for an OS?

Determine criteria, then evaluate algorithms

Deterministic modeling

Type of analytic evaluation

Takes a particular predetermined workload and defines the performance of each algorithm for that workload

Consider 5 processes arriving at time 0:


| Process | Burst Time | | |
|---------|------------|--|--|
| P_1 | 10 | | |
| P_2 | 29 | | |
| P_3 | 3 | | |
| P_4 | 7 | | |
| P_5 | 12 | | |






Deterministic Evaluation


For each algorithm, calculate minimum average waiting time
Simple and fast, but requires exact numbers for input, applies only to those inputs
FCS is 28ms:





Non-preemptive SFJ is 13ms:



RR is 23ms:







Queueing Models

Describes the arrival of processes, and CPU and I/O bursts probabilistically

Commonly exponential, and described by mean


Computes average throughput, utilization, waiting time, etc

Computer system described as network of servers, each with queue of waiting processes

Knowing arrival rates and service rates

Computes utilization, average queue length, average wait time, etc





Little's Formula

n = average queue length

W = average waiting time in queue

 λ = average arrival rate into queue

Little's law – in steady state, processes leaving queue must equal processes arriving, thus $n = \lambda \times W$

Valid for any scheduling algorithm and arrival distribution

For example, if on average 7 processes arrive per second, and normally 14 processes in queue, then average wait time per process = 2 seconds





Simulations

Queueing models limited

Simulations more accurate

Programmed model of computer system


Clock is a variable

Gather statistics indicating algorithm performance


Data to drive simulation gathered via


- Random number generator according to probabilities
- Distributions defined mathematically or empirically
- Trace tapes record sequences of real events in real systems





Evaluation of CPU Schedulersby Simulation





Implementation

Even simulations have limited accuracy

Just implement new scheduler and test in real systems

High cost, high risk

Environments vary

Most flexible schedulers can be modified per-site or per-system

Or APIs to modify priorities

But again environments vary

