

Message-ID: <1628080584.6383.1419417800402.JavaMail.svc_confluence_prod@node471.prod.inf.atlassian.com>
Subject: Exported From Confluence
MIME-Version: 1.0
Content-Type: multipart/related;
boundary="----=_Part_6382_1984292753.1419417800401"

-----=_Part_6382_1984292753.1419417800401

Content-Type: text/html; charset=UTF-8
Content-Transfer-Encoding: quoted-printable
Content-Location: file:///C:/exported.html

```
<html xmlns:o=3D'urn:schemas-microsoft-com:office:office'
  xmlns:w=3D'urn:schemas-microsoft-com:office:word'
  xmlns:v=3D'urn:schemas-microsoft-com:vml'
  xmlns=3D'urn:w3-org-ns:HTML'>
<head>
  <meta http-equiv=3D"Content-Type" content=3D"text/html; charset=3Dutf-8=
">
  <title>Configuring raw file download settings</title>
  <!--[if gte mso 9]>
  <xml>
    <o:OfficeDocumentSettings>
      <o:TargetScreenSize>1024x640</o:TargetScreenSize>
      <o:PixelsPerInch>72</o:PixelsPerInch>
      <o:AllowPNG/>
    </o:OfficeDocumentSettings>
    <w:WordDocument>
      <w:View>Print</w:View>
      <w:Zoom>90</w:Zoom>
      <w:DoNotOptimizeForBrowser/>
    </w:WordDocument>
  </xml>
  <![endif]-->
  <style>
    <!--
    @page Section1 {
      size: 8.5in 11.0in;
      margin: 1.0in;
      mso-header-margin: .5in;
      mso-footer-margin: .5in;
      mso-paper-source: 0;
    }

    td {
      page-break-inside: avoid;
    }

    tr {
      page-break-after: avoid;
    }

    div.Section1 {
      page: Section1;
    }

    /* Confluence print stylesheet. Common to all themes for print medi=
a */
    /* Full of !important until we improve batching for print CSS */

    #main {
      padding-bottom: 1em !important; /* The default padding of 6em is too mu=
ch for printouts */
    }
```

```

body {
    font-family: Arial, Helvetica, FreeSans, sans-serif;
    font-size: 10pt;
    line-height: 1.2;
}

body, #full-height-container, #main, #page, #content, .has-personal-sidebar=
#content {
    background: #fff !important;
    color: #000 !important;
    border: 0 !important;
    width: 100% !important;
    height: auto !important;
    min-height: auto !important;
    margin: 0 !important;
    padding: 0 !important;
    display: block !important;
}

a, a:link, a:visited, a:focus, a:hover, a:active {
    color: #000;
}

#content h1,
#content h2,
#content h3,
#content h4,
#content h5,
#content h6 {
    font-family: Arial, Helvetica, FreeSans, sans-serif;
    page-break-after: avoid;
}

pre {
    font-family: Monaco, "Courier New", monospace;
}

#header,
.aui-header-inner,
#navigation,
#sidebar,
.sidebar,
#personal-info-sidebar,
.ia-fixed-sidebar,
.page-actions,
.navmenu,
.ajs-menu-bar,
.noprint,
.inline-control-link,
.inline-control-link a,
a.show-labels-editor,
.global-comment-actions,
.comment-actions,
.quick-comment-container,
#addcomment {
    display: none !important;
}

.comment .date::before {
    content: none !important; /* remove middot for print view */
}

h1.pagetitle img {
    height: auto;
}

```

```

width: auto;
}

.print-only {
display: block;
}
#footer {
position: relative !important; /* CONF-17506 Place the footer at end of=
the content */
margin: 0;
padding: 0;
background: none;
clear: both;
}

#poweredby {
border-top: none;
background: none;
}

#poweredby li.print-only {
display: list-item;
font-style: italic;
}

#poweredby li.noprint {
display: none;
}

/* no width controls in print */
.wiki-content .table-wrap,
.wiki-content p,
.panel .codeContent,
.panel .codeContent pre,
.image-wrap {
overflow: visible !important;
}

/* TODO - should this work? */
#children-section,
#comments-section .comment,
#comments-section .comment .comment-body,
#comments-section .comment .comment-content,
#comments-section .comment p {
page-break-inside: avoid;
}

#page-children a {
text-decoration: none;
}

/**
hide twixies

the specificity here is a hack because print styles
are getting loaded before the base styles. */
#comments-section.pageSection .section-header,
#comments-section.pageSection .section-title,
#children-section.pageSection .section-header,
#children-section.pageSection .section-title,
.children-show-hide {
padding-left: 0;

```

```

    margin-left: 0;
}

.children-show-hide.icon {
    display: none;
}

/* personal sidebar */
.has-personal-sidebar #content {
    margin-right: 0px;
}

.has-personal-sidebar #content .pageSection {
    margin-right: 0px;
}
-->
</style>
</head>
<body>
    <h1>Configuring raw file download settings</h1>
    <div class=3D"Section1">
        <p>This page describes how to configure FishEye to either immediate=
ly display downloaded files in the browser, or show the browser's &quot;Sav=
e As&quot; dialog.<span style=3D"line-height: 1.5625;">&nbsp;</span></p>
<h3 id=3D"Configuringrawfiledownloadsettings-Configuration">Configuration</=
h3>
<p>As a FishEye administrator:</p>
<ol>
<li>Log in to the admin area and click <strong>Server</strong> (under 'Glob=
al Settings').&nbsp;</li>
<li><p>Click <strong>Edit Details</strong> under 'File Download Setting' an=
d choose a setting:<br /><br /></p>
<div class=3D"table-wrap">
<table class=3D"confluenceTable">
<tbody>
<tr>
<th class=3D"confluenceTh"><p>Mode</p></th>
<th class=3D"confluenceTh"><p>Characteristics</p></th>
</tr>
<tr>
<td class=3D"confluenceTd"><p><strong>Smart</strong> (default)</p></td>
<td class=3D"confluenceTd"><p>Files that can safely be displayed inline in =
the browser, will be. Files that are on FishEye's default list of file exte=
nsions that are considered dangerous, will always be accessed via the &quot;=
Save As&quot; dialog. For files that are considered dangerous, but consist=
of only plain text (such as .html files), this mode will attempt to force =
the browser to show (but not execute) the file.</p></td>
</tr>
<tr>
<td colspan=3D"1" class=3D"confluenceTd"><p><strong>Secure</strong></p></td=
>
<td colspan=3D"1" class=3D"confluenceTd"><p>All files, regardless of whethe=
r they are considered dangerous or not, are forced to be always accessed vi=
a the &quot;Save As&quot; dialog instead of being displayed inline.</p></td=
>
</tr>
<tr>
<td class=3D"confluenceTd"><p><strong>Insecure</strong></p></td>
<td class=3D"confluenceTd"><p>All files downloaded via FishEye will be disp=
layed in the browser after clicking.</p></td>
</tr>
</tbody>
</table>

```

```

</div></li>
</li><strong>Update</strong>.&nbsp;</li>
</ol>
<p><img class=3D"emoticon emoticon-information" src=3D"c4a3a128140f72f37f97=
5d788985e7a0" data-emoticon-name=3D"information" alt=3D"(info)" width=3D"16=
" height=3D"16" /> Internet Explorer versions 8 and 9 will not display safe=
content as plain text.</p>
<h3 id=3D"Configuringrawfiledownloadsettings-DefaultfileextensionsthatFishE=
yewillconsiderasexecutableinthebrowser">Default file extensions that FishEy=
e will consider as executable in the browser</h3>
<p>In Smart mode, downloading files with any of the following extensions wi=
ll always trigger the&nbsp;<span>&quot;Save As&quot;</span> dialog, instead=
of displaying the contents of the file in the browser directly, except in =
FireFox, Safari and Chrome.</p>
<div class=3D"table-wrap">
<table class=3D"confluenceTable">
<tbody>
<tr>
<th class=3D"confluenceTh"><p>File Extensions</p></th>
<th colspan=3D"1" class=3D"confluenceTh">Comments</th>
</tr>
<tr>
<td class=3D"confluenceTd"><p>.txt</p></td>
<td colspan=3D"1" class=3D"confluenceTd">Normally these are just text files=
, but a malicious user could write html in this file, and cause XSS inject =
attacks if the browser executes the content instead of displaying it. Can b=
e made to be <span>safely </span>displayed in all supported browsers, excep=
t Internet Explorer.</td>
</tr>
<tr>
<td class=3D"confluenceTd"><p>.htm , .html, <span>.xhtml, .xml, <span>.svg<=
/span> </span></p></td>
<td colspan=3D"1" class=3D"confluenceTd">Similar to .txt, these are text fi=
les, but contains html. <span>Can be made to be <span>safely </span>display=
ed in all supported browsers, except Internet Explorer.</span></td>
</tr>
<tr>
<td colspan=3D"1" class=3D"confluenceTd">.swf, <span>.flv , <span>.f4v, <sp=
an>.f4p, .f4b</span> </span> </span></td>
<td colspan=3D"1" class=3D"confluenceTd">Flash object file.</td>
</tr>
<tr>
<td colspan=3D"1" class=3D"confluenceTd">.cab</td>
<td colspan=3D"1" class=3D"confluenceTd">Windows Cabinet File.</td>
</tr>
</tbody>
</table>
</div>
<p>&nbsp;</p>
<p>To add items to the default list in FishEye, please contact Atlassian Su=
pport.</p>
</div>
</body>
</html>

```

-----= Part 6382 1984292753.1419417800401

Content-Type: image/png

Content-Transfer-Encoding: base64

Content-Location: file:///C:/c4a3a128140f72f37f975d788985e7a0

[illegible]

ABR0RVh0Q3JIYXRpb24gVGltZQA2LzEvMTM4qUXQAAAARklEQVQImWNgYFDu6DBiAALRDIAIZGBg
zAAx2gQYWDvAIIBBo6OjvaKjo4nBA8JoYeiAAhADJIKNAVcM1w43EG4F3FKYMwD5VTVUBOW+rQAA
AABJRU5ErkJggg==
-----=_Part_6382_1984292753.1419417800401--

