

The l3pdfutils package pdf-utilities

The L^AT_EX3 Project*

Released XXXX-XX-XX

1 l3pdfutils documentation

This module contains a number of commands to create xforms.

| | |
|---------------------------------|---|
| <code>\pdf_xform_new:nnn</code> | <code>\pdf_xform_new:nnn {<name>} {<attributes>} {<content>}</code> |
|---------------------------------|---|

New: 2019-08-05

This command create a new formXObject that can be used as appearance or directly later. If the *<content>* contains BDC-marks it should *not* be given as a previously typeset box, but directly so that the names of the BDC-marks can be added to the resources of the xform. The xform will automatically include the resources of the current page. The content will be typeset in a hbox. With pdf_latex and luatex the surrounding color is *not* stored in the XObject but should be if wanted added e.g. with `\color_select:n{.}`. This keeps the option of color injection open.

| | |
|-------------------------------|--|
| <code>\pdf_xform_use:n</code> | <code>\pdf_xform_use:n {<name>}</code> |
|-------------------------------|--|

New: 2019-08-05

This command uses (typesets) a previously created form XObject. If the surrounding color is different, it is injected in the XObject with the engines pdf_ltex or luatex.

| | |
|---------------------------------|--|
| <code>\pdf_xform_ref:n *</code> | <code>\pdf_xform_ref:n {<name>}</code> |
|---------------------------------|--|

New: 2019-08-05

Inserts the appropriate information to reference the xform *<name>* in for example appearance dictionaries.

| | |
|--------------------------------|---|
| <code>\pdf_xform_wd:n *</code> | <code>\pdf_xform_wd:n {<name>}</code> |
|--------------------------------|---|

| |
|--------------------------------|
| <code>\pdf_xform_ht:n *</code> |
|--------------------------------|

| |
|--------------------------------|
| <code>\pdf_xform_dp:n *</code> |
|--------------------------------|

New: 2019-08-05

These command give back the sizes of the XObject. The values are stored in tl-variables with the unit pt and not in dimensions!

| | |
|--|---|
| <code>\pdf_xform_if_exist_p:n *</code> | <code>\pdf_xform_if_exist_p:n {<name>}</code> |
|--|---|

| | |
|--|--|
| <code>\pdf_xform_if_exist:nTF *</code> | <code>\pdf_xform_if_exist:NTF <name> {<true code>} {<false code>}</code> |
|--|--|

New: 2020-04-29

These command tests if an xform with name *{<name>}* has been already defined.

*E-mail: latex-team@latex-project.org

2 l3pdfutils implementation

```

1 \*package
2 \<@=pdf
3 \ProvidesExplPackage {l3pdfutils} {2020-12-04} {0.2}
4   {command to create xforms}

```

2.1 FormXObject (pdfxform)

2.1.1 FormXObject / management

```

5 \*package
6 \cs_new_protected:Npn \pdf_xform_new:nnn #1 #2 #3
7   {
8     \__pdf_backend_xform_new:nnnn { #1 } { #2 } { } { #3 }
9   }
10
11 \cs_new_protected:Npn \pdf_xform_use:n #1
12   {
13     \__pdf_backend_xform_use:n { #1 }
14   }
15 % expansion?
16 \cs_new:Npn \pdf_xform_ref:n #1
17   {
18     \__pdf_backend_xform_ref:n { #1 }
19   }
20
21 \cs_generate_variant:Nn \pdf_xform_ref:n {o}
22
23 \cs_new:Npn \pdf_xform_wd:n #1
24   {
25     \tl_use:c { c__pdf_backend_xform_wd_ \tl_to_str:n { #1 } _tl }
26   }
27
28 \cs_new:Npn \pdf_xform_ht:n #1
29   {
30     \tl_use:c { c__pdf_backend_xform_ht_ \tl_to_str:n { #1 } _tl }
31   }
32
33 \cs_new:Npn \pdf_xform_dp:n #1
34   {
35     \tl_use:c { c__pdf_backend_xform_dp_ \tl_to_str:n { #1 } _tl }
36   }
37 \</package>

```

Index

The italic numbers denote the pages where the corresponding entry is described, numbers underlined point to the definition, all others indicate the places where it is used.

| | |
|--------------------------------------|---------------------------------------|
| C | \cs_new:Npn 16, 23, 28, 33 |
| cs commands: | |
| \cs_generate_variant:Nn 21 | \cs_new_protected:Npn 6, 11 |

| P | | | |
|-------------------------|-----------|------------------------------|------------|
| pdf commands: | | pdf internal commands: | |
| \pdf_xform_dp:n | 1, 33 | \pdf_xform_wd:n | 1, 23 |
| \pdf_xform_ht:n | 1, 28 | _pdf_backend_xform_new:nnnn | 8 |
| \pdf_xform_if_exist:NTF | 1 | _pdf_backend_xform_ref:n | 18 |
| \pdf_xform_if_exist:nTF | 1 | _pdf_backend_xform_use:n | 13 |
| \pdf_xform_if_exist_p:n | 1 | \ProvidesExplPackage | 3 |
| \pdf_xform_new:nnn | 1, 6 | | |
| \pdf_xform_ref:n | 1, 16, 21 | | |
| \pdf_xform_use:n | 1, 11 | | |
| | | T | |
| | | tl commands: | |
| | | \tl_to_str:n | 25, 30, 35 |
| | | \tl_use:N | 25, 30, 35 |