

The **l3pdf**file package

Embedding and referencing files in a PDF

PDFmanagement bundle (testphase)

The L^AT_EX Project*

Version 0.95a, released 2021-02-22

1 **l3pdf**file documentation

1.1 Introduction

1.1.1 Background

External files can be referenced from a PDF in three ways:

1. through an annotation of type Link,
2. by referencing a local file in the file system,
3. by embedding the file directly into the PDF

Case 1 (Links) are created with the `\pdfannot` commands. This module handles the two other cases. Actually from the view of the PDF format they are quite similar: Case 2 is case 3 without the stream object and without the `/EF` entry in the `/FileSpec` dictionary (this points to the stream object of the file). Not embedding the file makes the PDF smaller. But it is also less portable: the files can only be found if they are in the right location relative to the PDF. The normal case is to embed the file.

The tasks to embed and reference such a file are

1. Embed the file in a stream.
2. Create a FileSpec dictionary which references the stream object in the `/EF` dictionary:

```
<<
  /Type /Filespec
  /F (l3pdffile.dtx)
  /UF (l3pdffile.dtx)
  /AFRelationship /Source
  /EF <</F 21 0 R /UF 21 0 R>>   %case 3, embedded file
>>
```

*E-mail: latex-team@latex-project.org

The file names in the `/UF` and `/F` value don't need to be identical to the name of file on the disc. It is quite possible to embed a `zzz.tex` and name it `blub.tex`. The second name is then what the user will see in the attachment list or in the properties of an annotation.

3. Reference the `FileSpec` dictionary so that the user can access the file. This can be done in various way:

- (a) With an annotation (`/Subtype/FileAttachment`). This is done by `attachfile`, `attachfile2` and `intopdf`. Typical entries of such an annotation are:

key	value type	notes
<code>/FS</code>	object reference	(<code>FileSpec</code> dictionary)
<code>/Name</code>	name	<code>/Graph</code> , <code>/PushPin</code> , <code>/Paperclip</code> , <code>/Tag</code>
<code>/Contents</code>	text string	optional but recommended
<code>/F</code>	integer	Flags
<code>/AP</code>	dictionary	Appearance (required if rectangle >0)
<code>/AS</code>	name	

The `/AP` takes precedence over `Border` and similar keys.

- (b) Through an entry in the `/EmbeddedFiles` name tree. This is what `embedfiles` does.

```
20 0 obj %Document Name tree
  <</EmbeddedFiles 21 0 R>>
endobj
21 0 obj %Embedded Files Name dictionary
  <</Names [(AcmeCustomCrypto Protected PDF.pdf) 17 0 R]>>
endobj
```

The strings (keys) in the `/Names` dictionary must be sorted lexically. But they don't have to be the file name or anything related to the file name. The resource management code uses `l3emb0001`, `l3emb0002` ..., which allows up to 9999 files. The key can be needed to identify the start file in a collection, so their relation to the files are stored in a property list.

- (c) Through the `/AF` key in various objects (pdf 2.0). The value is normally an array of object references, but it can also be a name which is mapped to an array in `/Properties`:

```
/AF /NamedAF BDC
/Properties <</NamedAF [12 0 R]
```

The related `/FileSpec` dictionary should contain an `/AFRelationship` key in this case (but it doesn't harm to add it by default anyway). The values of this key is describe in table 1.

1.1.2 Task 1: Embedding a file

Embedding an existing file is in most cases quite straightforward. This module offers commands, but it can also be done with the basic commands from the `l3pdf` module `\pdf_object_unnamed_write:nn` or `\pdf_object_new:nn/\pdf_object_write:nn` or primitive commands to create objects. The object number should be stored for the reference in the `/FileSpec` dictionary.

Table 1: Values of the <code>/AFRelationship</code> key	
Source	shall be used if this file specification is the original source material for the associated content.
Data	shall be used if this file specification represents information used to derive a visual presentation – such as for a table or a graph.
Alternative	shall be used if this file specification is an alternative representation of content, for example audio.
Supplement	shall be used if this file specification represents a supplemental representation of the original source or data that may be more easily consumable (e.g., A MathML version of an equation).
EncryptedPayload	shall be used if this file specification is an encrypted payload document that should be displayed to the user if the PDF processor has the cryptographic filter needed to decrypt the document.
FormData	shall be used if this file specification is the data associated with the AcroForm (see 12.7.3, “Interactive form dictionary”) of this PDF.
Schema	shall be used if this file specification is a schema definition for the associated object (e.g. an XML schema associated with a metadata stream).
Unspecified	(default value) shall be used when the relationship is not known or cannot be described using one of the other values.
Other names	Second-class names (see Annex E, “(normative) PDF Name Registry”) should be used to represent other types of relationships.

```

\pdf_object_unnamed_write:nx {fstream}
{
  {
    /Type /EmbeddedFile
    /Subtype /application\c_hash_str2Fpostscript
    /Params
    <<
      /ModDate ~ (\file_timestamp:n{example-image.eps})
      /Size ~ \file_size:n {example-image.eps}
      /Checksum ~ (\file_md5five_hash:n {example-image.eps})
    >>
  }
  {example-image.eps}
}
\tl_set:Nx \l_my_fileobj_tl {\pdf_object_ref_last:}

```

- The `/Params` dictionary is not always required, but the commands of these module will prefill them as shown in the examples. A `/CreationDate` entry has to be added explicitly as there is no sensible way to retrieve this automatically.
- The mimetype (in the `/Subtype`) should be properly escaped. This module contains a property list with maps a number of file extensions to mimetypes and the commands try to detect and fill the mimetype automatically.
- The dictionary can contain additional keys (`/Filter`, `/DecodeParms`), see the pdf reference.

1.1.3 Task 2: Creating the `/FileSpec` dictionary

The `/FileSpec` dictionary is a simple dictionary object, and can also be created in various ways. If it refers to an embedded file it should reference it in the `/EF` key.

1.1.4 Task 3: Referencing the `/FileSpec` dictionary

Using the dictionary reference in annotations and `/AF` keys is unproblematic.



But to add it to the `/EmbeddedFiles` name tree so that it appears in the attachment panel requires special care: This name tree is a global resource and uncoordinated access can lead to clashes and files that are not visible or inaccessible. The access here is managed by the `l3pdfmanagement` module:

```
\pdfmanagement_add:nnx{Catalog/Names}{EmbeddedFiles}{\objref}
```

1.2 Commands and tools of these module

`file`
`file/Params`
`file/streamParams`
`file/FileSpec`

The module predefines and uses a number of local dictionaries for the components of the stream and the `/FileSpec` object. These dictionaries are then used by the `\pdffile_embed_XX`. The content of these dictionaries can be changed by users with the commands from the `l3pdfdict` module, but it should be done only locally to avoid side effects on uses by other packages/commands.

The preset values of these dictionaries are shown in table 2.

Table 2: Preset values in the file dictionaries

dictionary	key	value
<code>l_pdffile</code>	Type	<code>/EmbeddedFile</code>
<code>l_pdffile/Params</code>	Size	<code>\file_size:n{\l_pdffile_source_name_str}</code>
<code>l_pdffile/Params</code>	ModDate	<code>(\file_timestamp:n {\l_pdffile_source_name_str})</code>
<code>l_pdffile/Params</code>	Checksum	<code>(\file_md5five_hash:n{\l_pdffile_source_name_str})</code>
<code>l_pdffile/streamParams</code>		empty (used with <code>\pdffile_embed_stream:nnn</code>)
<code>l_pdffile/FileSpec</code>	Type	<code>/FileSpec</code>
<code>l_pdffile/FileSpec</code>	AFRelationship	Unspecified

`\pdffile_embed_file:nnn` `\pdffile_embed_file:nnn {<source filename>} {<target filename>} {<object name >}`

This command embeds the file `<source filename>` in the PDF, and creates a `/FileSpec` dictionary object named `<object name>`. The object name must be unique. The command uses the content of the local dictionaries `l_pdffile`, `l_pdffile/Params` and `l_pdffile/FileSpec` to setup the dictionary entries of the stream object and the `/FileSpec` dictionary. The `/F` and `/UF` entry are filled with `<target filename>`.

It is an error if both `<target filename>` and `<source filename>` are empty.

If `<target filename>` is empty `<source filename>` is used instead.

If `<source filename>` is empty, only a `/FileSpec` dictionary is created.

If the `l_pdffile` dictionary doesn't contain a Subtype entry with the mimetype, the command tries to guess it from the file extension of `<source filename>`. Unknown file extensions can be added (or known extension be changed) by adding to or changing the value in the property `\g_pdffile_mimetypes_prop`, see below.

When using `dvips` and `pstopdf` the actual embedding is done by `pstopdf`. `pstopdf` will embed files only if used with the option `-dNOSAFER` and will not be able to use files which are found with `kpathsea`.

`<target filename>` doesn't need to be a file name with an extension, but it is recommended as security settings in the pdf viewer can restrict access to known file types.

`\pdffile_embed_stream:nnn` `\pdffile_embed_stream:nnn {<content>} {<target filename>} {<object name >}`

This command embeds the `<content>` in the PDF in a stream objects and creates a `/FileSpec` dictionary object named `<object name>`. `<content>` is wrapped in a `\exp_not:n`. The object name must be unique. The command uses the content of the local dictionaries `l_pdffile`, `l_pdffile/streamParams` and `l_pdffile/FileSpec` to setup the dictionary entries of the stream object and the `/FileSpec` dictionary. The `/F` and `/UF` entry are filled with `<target filename>`. If `<target filename>` is empty the fix name `stream.txt` is used instead.

If the `l_pdffile` dictionary doesn't contain a Subtype entry with the mimetype, the command tries to guess it from the file extension of `<target filename>`.

`<target filename>` doesn't need to be a file name with an extension, but it is recommended as security settings in the pdf viewer can restrict access to known file types.

The stream should not be too long, at least PS imposes a size limit for strings.

<u>\g_pdffile_mimetypes_prop</u>	<p>This property contains a list of extensions and their mimetypes. Values can be added or changed with the standard commands:</p> <pre>\prop_gput:Nnn \g_pdffile_mimetypes_prop {.abc}{text/plain}</pre> <p>The extension should start with a period, the mimetype should be given as plain text (it will be escaped internally). Extensions with two periods are not supported.</p>
<u>\l_pdffile_source_name_str</u>	<p>This variable is set at the begin of <code>\pdffile_embed_file:nnn</code>. It can be (and is) used in the file dictionaries, see table 2 for examples.</p>
<u>\g_pdffile_embed_prop</u>	<p>This property holds a list of embedded files. It is used by the following show command. The keys are the object names, the argument holds a key word, the source file name and the target file name.</p>
<u>\pdffile_embed_show:</u>	<p>This shows the embedded files with their source and target name.</p>

1.3 Example

```

\group_begin:
%set the relationship:
\pdfdict_put:nnn {l_pdffile/FileSpec} {AFRelationship}{/Source}
%set the description key. The text must first be converted:
\pdf_string_from_unicode:nnN {utf16/string}
  {this~is~an~odd~description~with~öäü}
  \l_tmpa_str
\pdfdict_put:nnx {l_pdffile/FileSpec} {Desc}{\l_tmpa_str}
%embeds testinput.txt and calls it grüße.txt
\pdffile_embed_file:nnn {testinput.txt}{grüße.txt}{file:example1}
%reference it in the panel
\pdfmanagement_add:nnx
  {Catalog/Names}
  {EmbeddedFiles}
  {\pdf_object_ref:n{file:example1}}
\group_end:

```

2 l3pdffile implementation

```

1 <*header>
2 \ProvidesExplPackage {l3pdffile} {2021-02-22} {0.95a}
3   {embedding and referencing files in PDF---PDFmanagement bundle (testphase)}
4 \RequirePackage{l3pdftools} %temporarily!!
5 </header>
6 <*package>
7 <@@=pdffile>
8 \cs_new_protected:Npn \__pdffile_filename_convert_to_print:nN #1 #2
9   {\pdf_string_from_unicode:nnN {utf16/hex}{#1}{#2}}

```

2.1 Messages

```

10 \msg_new:nnn { pdf file } { file-not-found }
11 {
12   File~'\tl_to_str:n{#1}'~not~found
13 }
14
15 \msg_new:nnn { pdf file } { mimetype-missing }
16 {
17   Mime~type~not~set~for~file~'\tl_to_str:n{#1}'
18 }
19
20 \msg_new:nnn { pdf file } { target-name-missing }
21 {
22   a~target~name~for~the~/FileSpec~dictionary~is~missing.
23 }
24
25 \msg_new:nnn { pdf file } { object-exists }
26 {
27   object~name~'#1'~is~already~used.
28 }
29
30 \msg_new:nnn { pdf file } { show-files }
31 {
32   The~following~files~have~been~embedded\\
33   #1
34 }

```

`\l__pdffile_tmpa_tl` temporary variables: generic, for extension, subtype, to store the ref.

`\l__pdffile_tmpb_tl`

`\l__pdffile_tmpa_str` (End definition for `\l__pdffile_tmpa_tl` and others.)

`\l__pdffile_tmpb_str`

`\l__pdffile_ext_str`

`\l__pdffile_automimetype_tl`

`\l__pdffile_embed_ref_tl`

```

35 \tl_new:N \l__pdffile_tmpa_tl
36 \tl_new:N \l__pdffile_tmpb_tl
37 \str_new:N \l__pdffile_tmpa_str
38 \str_new:N \l__pdffile_tmpb_str
39 \str_new:N \l__pdffile_ext_str
40 \tl_new:N \l__pdffile_automimetype_tl
41 \tl_new:N \l__pdffile_embed_ref_tl

```

`\g_pdffile_mimetypes_prop`

This variable holds common mimetypes. The key is an extension with (one) period, the value the description, e.g. `text/csv`.

(End definition for `\g_pdffile_mimetypes_prop`. This variable is documented on page 6.)

```

42 \prop_new:N \g_pdffile_mimetypes_prop
43 \prop_set_from_keyval:Nn \g_pdffile_mimetypes_prop
44 {
45   ,.csv = text/csv
46   ,.html= text/html
47   ,.dtx = text/plain %or application/x-tex, not in iana.org list
48   ,.eps = application/postscript
49   ,.jpg = image/jpeg
50   ,.mp4 = video/mp4
51   ,.pdf = application/pdf
52   ,.png = image/png
53   ,.tex = text/plain %or application/x-tex, not in iana.org list

```

```

54     ,.txt = text/plain
55     ,.sty = text/plain
56 }

```

\l_pdffile_source_name_str \l_pdffile_source_name_str will be set at the begin of the command and contains the full file name and can be used e.g. with \file_timestamp:n.

(End definition for \l_pdffile_source_name_str. This variable is documented on page 6.)

```

57 \str_new:N \l_pdffile_source_name_str

```

Here we define and setup the local dictionaries.

```

58 \pdfdict_new:n { l_pdffile }
59 \pdfdict_put:nnn { l_pdffile }{Type}{/EmbeddedFile}
60 \pdfdict_new:n { l_pdffile/Params }
61 \pdfdict_put:nnn { l_pdffile/Params }
62   {ModDate} { (\file_timestamp:n { \l_pdffile_source_name_str }) }
63 \pdfdict_put:nnn { l_pdffile/Params }
64   {Size} { \file_size:n { \l_pdffile_source_name_str } }
65 \pdfdict_put:nnn { l_pdffile/Params }
66   {Checksum} { (\file_md5_hash:n { \l_pdffile_source_name_str }) }
67 \pdfdict_new:n { l_pdffile/streamParams }
68 \pdfdict_new:n { l_pdffile/FileSpec }
69 \pdfdict_put:nnn { l_pdffile/FileSpec }
70   {Type} { /FileSpec }
71 \pdfdict_put:nnn { l_pdffile/FileSpec }
72   {AFRelationship} { /Unspecified }
73

```

\g_pdffile_embed_prop we record here the relation
 $\langle object\ name \rangle \Rightarrow \{ \langle file/stream\ or\ empty \rangle \} \{ \langle sourcename \rangle \} \{ \langle targetname \rangle \}$

```

74 \prop_new:N \g_pdffile_embed_prop

```

(End definition for \g_pdffile_embed_prop. This variable is documented on page 6.)

\pdffile_embed_show:

```

75 \cs_new_protected:Npn \pdffile_embed_show:
76 {
77   \msg_show:nnx
78   {pdffile}{show-files}
79   {
80     \prop_map_function:NN {\g_pdffile_embed_prop} \msg_show_item:nn
81   }
82 }

```

(End definition for \pdffile_embed_show:. This function is documented on page 6.)

\pdffile_embed_file:nnn At first a command to set the mimetype. It either uses the current value in the file
\pdffile_embed_stream:nnn dictionary, or tries to guess it from the extension.

```

83 %\1 file name,
84 %\2 t1 to return the (printed) value for the guessed mimetype
85 \cs_new_protected:Npn \__pdffile_mimetype_set:nN #1 #2
86 {
87   \__pdffile_mimetype_set:nN
88   \__pdffile_mimetype_set:VN
89   \__pdffile_fstream_write:nN
90   \__pdffile_fstream_write:VN
91   \__pdffile_stream_write:nN
92   \__pdffile_stream_write:VN

```



```

87 \file_parse_full_name:nNNN
88 {#1}
89 \l__pdffile_tmpa_str %unused
90 \l__pdffile_tmpb_str %unused
91 \l__pdffile_ext_str
92 %check if Subtype has been set
93 \pdfdict_get:nnN { l__pdffile}{Subtype}\l__pdffile_tmpa_tl
94 %if not look up in the prop:
95 \quark_if_no_value:NT \l__pdffile_tmpa_tl
96 {
97     \prop_get:NVNTF
98     \g_pdffile_mimetypes_prop
99     \l__pdffile_ext_str
100     \l__pdffile_tmpb_tl
101     {
102         \tl_set:Nx #2 {/Subtype-\pdf_name_from_unicode_e:V \l__pdffile_tmpb_tl}
103     }
104     {
105         \msg_warning:nnx { pdf file }{ mimetype-missing} {#1}
106         \tl_clear:N #2
107     }
108 }
109 }
110
111 \cs_generate_variant:Nn \__pdffile_mimetype_set:nN {VN}
112
113 % #1 file name,
114 % #2 tl, should be empty or contain /Subtype /mimetype
115 % e.g. result from \__pdffile_mimetype_set:NN
116 \cs_new_protected:Npn \__pdffile_fstream_write:nN #1 #2
117 {
118     \pdf_object_unnamed_write:nx { fstream }
119     {
120         {
121             #2
122             \pdfdict_use:n { l__pdffile}
123             \pdfdict_if_empty:nF { l__pdffile/Params}
124             {
125                 /Params
126                 <<
127                 \pdfdict_use:n { l__pdffile/Params}
128                 >>
129             }
130         }
131         { #1 }
132     }
133     \tl_clear:N \l__pdffile_automimetype_tl
134 }
135
136 \cs_generate_variant:Nn \__pdffile_fstream_write:nN {VN}
137
138 % #1 file content
139 % #2 tl, should be empty or contain /Subtype /mimtype
140 % e.g. result from \__pdffile_mimetype_set:NN

```

```

141 \cs_new_protected:Npn \__pdffile_stream_write:nN #1 #2
142 {
143   \pdf_object_unnamed_write:nx { stream }
144   {
145     {
146       #2
147       \pdfdict_use:n { l_pdffile}
148       \pdfdict_if_empty:nF { l_pdffile/streamParams}
149       {
150         /Params
151         <<
152         \pdfdict_use:n { l_pdffile/streamParams}
153         >>
154       }
155     }
156     { \exp_not:n { #1 } }
157   }
158   \tl_clear:N \l__pdffile_automimetype_tl
159 }
160
161 \cs_generate_variant:Nn \__pdffile_stream_write:nN {VN}
162
163 % #1 symbolic name of dict object
164 % #2 target file name,
165 % #3 object ref of the file stream.
166 \cs_new_protected:Npn \__pdffile_filespec_write:nnn #1 #2 #3
167 {
168   \tl_if_blank:nT { #2 }
169   {
170     \msg_error:nn {pdffile}{target-name-missing}
171   }
172   {
173     \pdf_object_new:nn { #1 } {dict}
174     \group_begin:
175     \__pdffile_filename_convert_to_print:nN { #2 } \l__pdffile_tmpa_str
176     \pdfdict_put:nnx {l_pdffile/FileSpec}{F} { \l__pdffile_tmpa_str }
177     \pdfdict_put:nnx {l_pdffile/FileSpec}{UF}{ \l__pdffile_tmpa_str }
178     \pdf_object_write:nx { #1 }
179     {
180       \pdfdict_use:n { l_pdffile/FileSpec}
181       \tl_if_empty:nF { #3 }
182       {
183         /EF <</F~#3 /UF~#3>>
184       }
185     }
186     \group_end:
187   }
188 }
189
190
191 % #1 {source filename}
192 % #2 {target filename}
193 % #3 { filespec object name } (will internally get a prefix!)
194 \cs_new_protected:Npn \pdffile_embed_file:nnn #1 #2 #3

```

```

195 { %          if #1 empty => only filespec
196 %          if #2 empty => = #1
197 \pdf_object_if_exist:nTF { #3 }
198 {
199     \msg_error:nnn { pdffile }{ object-exists } { #3 }
200 }
201 {
202     \tl_if_blank:nTF { #1 }
203     {
204         \tl_set:Nn \l__pdffile_embed_ref_tl {}
205     }
206     {
207         \file_get_full_name:nTF {#1} \l_pdffile_source_name_str
208         {
209             \__pdffile_mimetype_set:VN
210             \l_pdffile_source_name_str
211             \l__pdffile_automimetype_tl
212             \__pdffile_fstream_write:VN
213             \l_pdffile_source_name_str
214             \l__pdffile_automimetype_tl
215             \tl_set:Nx \l__pdffile_embed_ref_tl { \pdf_object_ref_last: }
216         }
217         {
218             \msg_error:nnn { pdffile }{ file-not-found }{ #1 }
219         }
220     }
221 }
222 \prop_gput:Nnx
223 \g_pdffile_embed_prop
224 { #3 }
225 {
226     { \tl_if_blank:nTF { #1 } {filespec}{file} }
227     {\l_pdffile_source_name_str}
228     {
229         \tl_if_blank:nTF { #2 }
230         { \l_pdffile_source_name_str }
231         { \tl_to_str:n{#2}}
232     }
233 }
234 \tl_if_blank:nTF { #2 }
235 {
236     \exp_args:Nnnx
237     \__pdffile_filespec_write:nnn
238     %#1 dict, #2 target file name, #3 object ref
239     { #3 }
240     { #1 }
241     {\l__pdffile_embed_ref_tl}
242 }
243 {
244     \exp_args:Nnnx
245     \__pdffile_filespec_write:nnn
246     %#1 dict, #2 target file name, #3 object ref
247     { #3 }
248     { #2 }

```

```

249         {\l__pdffile_embed_ref_tl}
250     }
251 }
252 }
253
254
255 %1{stream content}
256 %2{target filename}
257 %3{file object name }
258 \cs_new_protected:Npn \pdffile_embed_stream:nnn #1 #2 #3
259 {
260     % if #2 empty => error
261     \pdf_object_if_exist:nTF { #3 }
262     {
263         \msg_error:nnn { pdffile }{ object-exists } { #3 }
264     }
265     {
266         \prop_gput:Nnx
267         \g_pdffile_embed_prop
268         { #3 }
269         {{stream}}{\tl_if_blank:nTF {#2}{stream.txt}{\exp_not:n{#2}}}}
270     \tl_if_blank:nTF {#2}
271     { \__pdffile_mimetype_set:nN {stream.txt}\l__pdffile_automimetype_tl}
272     { \__pdffile_mimetype_set:nN { #2 } \l__pdffile_automimetype_tl }
273     \__pdffile_stream_write:nN
274     { #1 }
275     \l__pdffile_automimetype_tl
276     \tl_set:Nx \l__pdffile_embed_ref_tl { \pdf_object_ref_last: }
277     \exp_args:Nnxx
278     \__pdffile_filespec_write:nnn
279     %1 dict, #2 target file name, #3 object ref
280     { #3 }
281     { \tl_if_blank:nTF {#2}{stream.txt}{\exp_not:n{#2}} }
282     {\l__pdffile_embed_ref_tl}
283 }
284 }
285
286

```

(End definition for `\pdffile_embed_file:nnn` and others. These functions are documented on page 5.)

```

287 \endpackage

```

Index

The italic numbers denote the pages where the corresponding entry is described, numbers underlined point to the definition, all others indicate the places where it is used.

Symbols

C

cs commands:

	<code>\cs_generate_variant:Nn</code>	111 , 136 , 161
<code>\</code>	<code>\cs_new_protected:Npn</code>	32

.... 8, 75, 85, 116, 141, 166, 194, 258
E
 exp commands:
 \exp_args:Nnnx 236, 244
 \exp_args:Nnxx 277
 \exp_not:n 5, 156, 269, 281
F
 file 4
 file commands:
 \file_get_full_name:nNTF 207
 \file_md5five_hash:n 66
 \file_parse_full_name:nNNN 87
 \file_size:n 64
 \file_timestamp:n 8, 62
 file/FileSpec 4
 file/Params 4
 file/streamParams 4
G
 group commands:
 \group_begin: 174
 \group_end: 186
M
 msg commands:
 \msg_error:nn 170
 \msg_error:nnn 199, 218, 263
 \msg_new:nnn 10, 15, 20, 25, 30
 \msg_show:nnn 77
 \msg_show_item:nn 80
 \msg_warning:nnn 105
P
 pdf commands:
 \pdf_name_from_unicode_e:n 102
 \pdf_object_if_exist:nTF 197, 261
 \pdf_object_new:nn 2, 173
 \pdf_object_ref_last: 215, 276
 \pdf_object_unnamed_write:nn ...
 2, 118, 143
 \pdf_object_write:nn 2, 178
 \pdf_string_from_unicode:nnN 9
 \pdfannot 1
 pdfdict commands:
 \pdfdict_get:nnN 93
 \pdfdict_if_empty:nTF 123, 148
 \pdfdict_new:n 58, 60, 67, 68
 \pdfdict_put:nnn
 59, 61, 63, 65, 69, 71, 176, 177
 \pdfdict_use:n 122, 127, 147, 152, 180
 pdffile commands:
 \pdffile_embed_file:nnn . 5, 6, 83, 194
 \g_pdffile_embed_prop
 6, 74, 80, 223, 267
 \pdffile_embed_show: 6, 75, 75
 \pdffile_embed_stream:nnn 5, 5, 83, 258
 \pdffile_embed_XX 4
 \g_pdffile_mimetypes_prop
 5, 6, 42, 42, 43, 98
 \l_pdffile_source_name_str
 6, 8, 57,
 57, 62, 64, 66, 207, 210, 213, 227, 230
 pdffile internal commands:
 \l__pdffile_automimetype_tl . 35,
 40, 133, 158, 211, 214, 271, 272, 275
 \l__pdffile_embed_ref_tl
 .. 35, 41, 204, 215, 241, 249, 276, 282
 \l__pdffile_ext_str ... 35, 39, 91, 99
 __pdffile_filename_convert_to_-
 print:nN 8, 175
 __pdffile_filespec_write:nnn ...
 166, 237, 245, 278
 __pdffile_fstream_write:nN
 83, 116, 136, 212
 __pdffile_mimetype_set:NN . 115, 140
 __pdffile_mimetype_set:nN
 83, 85, 111, 209, 271, 272
 __pdffile_stream_write:nN
 83, 141, 161, 273
 \l__pdffile_tmpa_str
 35, 37, 89, 175, 176, 177
 \l__pdffile_tmpa_tl ... 35, 35, 93, 95
 \l__pdffile_tmpb_str 35, 38, 90
 \l__pdffile_tmpb_tl . 35, 36, 100, 102
 prop commands:
 \prop_get:NnNTF 97
 \prop_gput:Nnn 222, 266
 \prop_map_function:NN 80
 \prop_new:N 42, 74
 \prop_set_from_keyval:Nn 43
 \ProvidesExplPackage 2
Q
 quark commands:
 \quark_if_no_value:NNTF 95
R
 \RequirePackage 4
S
 str commands:
 \str_new:N 37, 38, 39, 57
T
 tl commands:
 \tl_clear:N 106, 133, 158
 \tl_if_blank:nTF
 168, 202, 226, 229, 234, 269, 270, 281
 \tl_if_empty:nTF 181
 \tl_new:N 35, 36, 40, 41
 \tl_set:Nn 102, 204, 215, 276
 \tl_to_str:n 12, 17, 231