

Nordic Process Control Workshop 2023  
Norwegian University of Science and Technology, August 17-18, 2023

# A System-Level Approach to Closed-Loop Best Response Dynamics


Otacílio B. L. Neto<sup>1</sup>, Michela Mulas<sup>2</sup>, Francesco Corona<sup>1</sup>

<sup>1</sup> School of Chemical Engineering, Department of Chemical and  
Metallurgical Engineering, Aalto University, Finland

<sup>2</sup> Department of Teleinformatics Engineering,  
Federal University of Ceará, Fortaleza-CE, Brazil

# Intro, (large-scale) cyber-physical systems

- ▶ We are interested in the control of modern **Cyber-Physical Systems (CPS)**



- ↪ Large-scale decentralized network of subsystems
- ↪ Non-cooperative decision-making agents
- ↪ Information exchange often asymmetric

The centralized approach for controller design becomes unsuitable!

**Game theory:** A framework for computing competitive equilibria in multi-agent settings

**(Almost) Complete theory:**  
2-players, finite-duration, unconstrained

**Extremely challenging:**  
 $N$ -players, infinite-duration, constrained  
(specially under dynamic information structures)

We study a (straightforward) approach to computing equilibrium strategies in  $N$ -players non-cooperative games

# Intro, non-cooperative games and Nash equilibria

We consider  $N_P$ -players nonzero-sum stochastic difference-games (NZS-SDG)

↪ Simultaneous play; closed-loop perfect state (CLPS) information; stage-additive costs

$$\forall p \in \underbrace{\{1, \dots, N_P\}}_{\mathcal{P}} : \begin{cases} \min_{u_p := K_p(x)} & \lim_{T \rightarrow \infty} \mathbb{E} \left[ \sum_{t=0}^T L_p(x(t), u_p(t), u_{-p}(t)) \right] := J_p(u_1, \dots, u_{N_P}) \\ \text{s.t.} & x(t+1) = f(x(t), u_1(t), \dots, u_{N_P}(t)) + w(t), \quad x(0) \text{ given,} \\ & x(t) \in \mathcal{X}, \quad u_p(t) \in \mathcal{U}_p \end{cases}$$

$$(w / \mathbb{E}[w(t)] = 0 \text{ and } \mathbb{E}[w(t)w(t')^T] = \delta(t-t')I_{N_x})$$

## Nash Equilibrium (NE)

A strategy profile  $K^* = (K_1^*, \dots, K_{N_P}^*)$  is a NE iff

$$u_p^* := K_p^*(x) \\ \implies J_p(u_p^*, u_{-p}^*) \leq J_p(u_p, u_{-p}^*), \quad (\forall p \in \mathcal{P})$$

for all strategies  $\{u_p(t) = K_p(x(0), \dots, x(t)) \in \mathcal{U}_p\}_{t=0}^T$   
and resulting state-trajectories  $\{x(t) \in \mathcal{X}\}_{t=0}^T$ .

**Issues:** Existence  $\rightarrow$  Uniqueness

## Computation:

- ▶ [A]DP (coupled Ricatti equations);
- ▶ PMP (HJ-equation, coupled costates);
- ▶ Numerically? (open-loop,  $T < \infty$ );

# Intro, non-cooperative games and Nash equilibria

We consider  $N_P$ -players nonzero-sum stochastic difference-games (NZS-SDG)

↪ Simultaneous play; closed-loop perfect state (CLPS) information; stage-additive costs

$$\forall p \in \underbrace{\{1, \dots, N_P\}}_{\mathcal{P}} : \begin{cases} \min_{u_p := K_p(x)} & \lim_{T \rightarrow \infty} \mathbb{E} \left[ \sum_{t=0}^T L_p(x(t), u_p(t), u_{-p}(t)) \right] := J_p(u_1, \dots, u_{N_P}) \\ \text{s.t.} & x(t+1) = f(x(t), u_1(t), \dots, u_{N_P}(t)) + w(t), \quad x(0) \text{ given,} \\ & x(t) \in \mathcal{X}, \quad u_p(t) \in \mathcal{U}_p \end{cases}$$

$$(w / \mathbb{E}[w(t)] = 0 \text{ and } \mathbb{E}[w(t)w(t')^T] = \delta(t-t')I_{N_x})$$

## Nash Equilibrium (NE)

A strategy profile  $K^* = (K_1^*, \dots, K_{N_P}^*)$  is a **NE** iff

$$u_p^* := K_p^*(x) \\ \implies J_p(u_p^*, u_{-p}^*) \leq J_p(u_p, u_{-p}^*), \quad (\forall p \in \mathcal{P})$$

for all strategies  $\{u_p(t) = K_p(x(0), \dots, x(t)) \in \mathcal{U}_p\}_{t=0}^T$   
and resulting state-trajectories  $\{x(t) \in \mathcal{X}\}_{t=0}^T$ .

**Issues:** Existence  $\rightarrow$  Uniqueness

## Computation:

- ▶ [A]DP (coupled Ricatti equations);
- ▶ PMP (HJ-equation, coupled costates);
- ▶ Numerically? (open-loop,  $T < \infty$ );

# Intro, non-cooperative games and Nash equilibria

We consider  $N_P$ -players nonzero-sum stochastic difference-games (NZS-SDG)

↪ Simultaneous play; closed-loop perfect state (CLPS) information; stage-additive costs

$$\forall p \in \underbrace{\{1, \dots, N_P\}}_{\mathcal{P}} : \left\{ \begin{array}{ll} \min_{u_p := K_p * x} & \lim_{T \rightarrow \infty} \mathbb{E} \left[ \sum_{t=0}^T \left( \|Q^{1/2} x(t)\|_2^2 + \sum_{\bar{p} \in \mathcal{P}} \|R_{p\bar{p}}^{1/2} u_{\bar{p}}(t)\|_2^2 \right) \right] \\ \text{s.t.} & x(t+1) = Ax(t) + \sum_{\bar{p} \in \mathcal{P}} B_{\bar{p}} u_{\bar{p}}(t) + w(t), \quad x(0) \text{ given,} \\ & H_x x(t) \leq h_x, \quad H_{u,p} u_p(t) \leq h_{u,p} \end{array} \right.$$

(w/  $\mathbb{E}[w(t)] = 0$  and  $\mathbb{E}[w(t)w(t')^T] = \delta(t-t')I_{N_x}$ )

## Nash Equilibrium (NE)

A strategy profile  $K^* = (K_1^*, \dots, K_{N_P}^*)$  is a **NE** iff

$$u_p^* := K_p^*(x) \\ \implies J_p(u_p^*, u_{-p}^*) \leq J_p(u_p, u_{-p}^*), \quad (\forall p \in \mathcal{P})$$

for all strategies  $\{u_p(t) = K_p(x(0), \dots, x(t)) \in \mathcal{U}_p\}_{t=0}^T$   
and resulting state-trajectories  $\{x(t) \in \mathcal{X}\}_{t=0}^T$ .

**Issues:** Existence  $\rightarrow$  Uniqueness

**Computation:**

- ▶ [A]DP (coupled Ricatti equations);
- ▶ PMP (HJ-equation, coupled costates);
- ▶ Numerically? (open-loop,  $T < \infty$ );









# SLS Approach to BRD

A System-Level Approach to Best Response Dynamics  
March 18, 2022

# System Level Synthesis, overview

- **System Level Synthesis (SLS)**: A novel approach for (robust + optimal) controller design

↪ Consider centralized dynamics and state-feedback controller  $K \in \mathcal{RH}_\infty$

$$x(t+1) = Ax(t) + Bu(t) + w(t)$$

$$u(t) = (K * x)(t)$$

## Theorem. (SLP, [1])

Assume  $(A, B)$  stabilizable. The following are true:

- $[zI - A \quad B] \Phi = I$  parametrizes all responses achievable by a stabilizing controller  $K$ ;
- A given response  $\Phi = (\Phi_x, \Phi_u)$  satisfying (a.) is achieved by the controller  $K = \Phi_u \Phi_x^{-1}$ .

# System Level Synthesis, overview

- **System Level Synthesis (SLS)**: A novel approach for (robust + optimal) controller design

↪ Consider centralized dynamics and state-feedback controller  $K \in \mathcal{RH}_\infty$

$$\begin{aligned} z\mathbf{x} &= A\mathbf{x} + B\mathbf{u} + \mathbf{w} \\ \mathbf{u} &= K\mathbf{x} \end{aligned}$$

## Theorem. (SLP, [1])

Assume  $(A, B)$  stabilizable. The following are true:

- $[zI - A \quad B] \Phi = I$  parametrizes all responses achievable by a stabilizing controller  $K$ ;
- A given response  $\Phi = (\Phi_x, \Phi_u)$  satisfying (a.) is achieved by the controller  $K = \Phi_u \Phi_x^{-1}$ .

# System Level Synthesis, overview

- **System Level Synthesis (SLS)**: A novel approach for (robust + optimal) controller design

↪ Consider centralized dynamics and state-feedback controller  $K \in \mathcal{RH}_\infty$

$$x = (zI - (A+BK))^{-1}w$$

$$u = K(zI - (A+BK))^{-1}w$$

## Theorem. (SLP, [1])

Assume  $(A, B)$  stabilizable. The following are true:

- $[zI - A \quad B] \Phi = I$  parametrizes all responses achievable by a stabilizing controller  $K$ ;
- A given response  $\Phi = (\Phi_x, \Phi_u)$  satisfying (a.) is achieved by the controller  $K = \Phi_u \Phi_x^{-1}$ .

# System Level Synthesis, overview

- **System Level Synthesis (SLS)**: A novel approach for (robust + optimal) controller design

- ↪ Consider centralized dynamics and state-feedback controller  $K \in \mathcal{RH}_\infty$

$$x = \Phi_x w$$

$$u = \Phi_u w$$

- ↪ Mappings  $\Phi = (\Phi_x, \Phi_u)$  are *system-level responses* to disturbances  $w$

## Theorem. (SLP, [1])

Assume  $(A, B)$  stabilizable. The following are true:

- $[zI - A \quad B] \Phi = I$  parametrizes all responses achievable by a stabilizing controller  $K$ ;
- A given response  $\Phi = (\Phi_x, \Phi_u)$  satisfying (a.) is achieved by the controller  $K = \Phi_u \Phi_x^{-1}$ .

# System Level Synthesis, overview

- **System Level Synthesis (SLS)**: A novel approach for (robust + optimal) controller design

- ↪ Consider centralized dynamics and state-feedback controller  $K \in \mathcal{RH}_\infty$

$$x = \Phi_x w$$

$$u = \Phi_u w$$

- ↪ Mappings  $\Phi = (\Phi_x, \Phi_u)$  are *system-level responses* to disturbances  $w$

## Theorem. (SLP, [1])

Assume  $(A, B)$  stabilizable. The following are true:

- $[zI - A \quad B] \Phi = I$  parametrizes all responses achievable by a stabilizing controller  $K$ ;
- A given response  $\Phi = (\Phi_x, \Phi_u)$  satisfying (a.) is achieved by the controller  $K = \Phi_u \Phi_x^{-1}$ .

# System Level Synthesis, overview

- **System Level Synthesis (SLS)**: A novel approach for (robust + optimal) controller design

- ↪ Consider centralized dynamics and state-feedback controller  $K \in \mathcal{RH}_\infty$

$$x = \Phi_x w$$

$$u = \Phi_u w$$

- ↪ Mappings  $\Phi = (\Phi_x, \Phi_u)$  are *system-level responses* to disturbances  $w$

## Theorem. (SLP, [1])

Assume  $(A, B)$  stabilizable. The following are true:

- $\begin{bmatrix} zI - A & B \end{bmatrix} \Phi = I$  parametrizes all responses achievable by a stabilizing controller  $K$ ;
- A given response  $\Phi = (\Phi_x, \Phi_u)$  satisfying (a.) is achieved by the controller  $K = \Phi_u \Phi_x^{-1}$ .

# System Level Synthesis, overview

- **System Level Synthesis (SLS)**: A novel approach for (robust + optimal) controller design

- ↪ Consider centralized dynamics and state-feedback controller  $K \in \mathcal{RH}_\infty$

$$x = \Phi_x w$$

$$u = \Phi_u w$$

- ↪ Mappings  $\Phi = (\Phi_x, \Phi_u)$  are *system-level responses* to disturbances  $w$

## Theorem. (SLP, [1])

Assume  $(A, B)$  stabilizable. The following are true:

- $\begin{bmatrix} zI - A & B \end{bmatrix} \Phi = I$  parametrizes all responses achievable by a stabilizing controller  $K$ ;
- A given response  $\Phi = (\Phi_x, \Phi_u)$  satisfying (a.) is achieved by the controller  $K = \Phi_u \Phi_x^{-1}$ .



# System Level Synthesis, overview

- **System Level Synthesis (SLS)**: A novel approach for (robust + optimal) controller design

↪ Consider centralized dynamics and state-feedback controller  $K \in \mathcal{RH}_\infty$

$$x = \Phi_x w$$

$$u = \Phi_u w$$

↪ Mappings  $\Phi = (\Phi_x, \Phi_u)$  are *system-level responses* to disturbances  $w$

## Theorem. (SLP, [1])

Assume  $(A, B)$  stabilizable. The following are true:

- $[zI - A \quad B] \Phi = I$  parametrizes all responses achievable by a stabilizing controller  $K$ ;
- A given response  $\Phi = (\Phi_x, \Phi_u)$  satisfying (a.) is achieved by the controller  $K = \Phi_u \Phi_x^{-1}$ .

## LQG (or $\mathcal{H}_2$ ) Control Problem via SLS

$$\begin{aligned} \min_{\Phi} \quad & \left\| \begin{bmatrix} Q^{\frac{1}{2}} & \\ & R^{\frac{1}{2}} \end{bmatrix} \begin{bmatrix} \Phi_x \\ \Phi_u \end{bmatrix} \right\|_{\mathcal{H}_2}^2 \\ \text{s.t.} \quad & z\Phi_x = I + A\Phi_x + B\Phi_u, \\ & \Phi_x \in \mathbf{C}_x, \quad \Phi_u \in \mathbf{C}_u \end{aligned}$$

↪ Design  $K$  by a LQR-like problem  
(Using  $\Phi = \sum_{n=1}^{\infty} \Phi(n) z^{-n}$ )

↪ Structure of  $K$  encoded by  $(\mathbf{C}_x, \mathbf{C}_u)$   
(e.g., spatiotemporal info. structures encoded by sparsity constraints)

# System Level Synthesis, overview

- **System Level Synthesis (SLS)**: A novel approach for (robust + optimal) controller design

↪ Consider centralized dynamics and state-feedback controller  $K \in \mathcal{RH}_\infty$

$$x = \Phi_x w$$

$$u = \Phi_u w$$

↪ Mappings  $\Phi = (\Phi_x, \Phi_u)$  are *system-level responses* to disturbances  $w$

## Theorem. (SLP, [1])

Assume  $(A, B)$  stabilizable. The following are true:

- $\begin{bmatrix} zI - A & B \end{bmatrix} \Phi = I$  parametrizes all responses achievable by a stabilizing controller  $K$ ;
- A given response  $\Phi = (\Phi_x, \Phi_u)$  satisfying (a.) is achieved by the controller  $K = \Phi_u \Phi_x^{-1}$ .

## LQG (or $\mathcal{H}_2$ ) Control Problem via SLS

$$\min_{\Phi(\cdot)} \sum_{n=1}^{\infty} \left( \|Q^{1/2} \Phi_x(n)\|_F^2 + \|R^{1/2} \Phi_u(n)\|_F^2 \right)$$

$$\text{s.t. } \begin{aligned} \Phi_x(n+1) &= A\Phi_x(n) + B\Phi_u(n), & \Phi_x(1) &= I_{N_x} \\ \Phi_x(n) &\in \mathcal{C}_x(n), & \Phi_u(n) &\in \mathcal{C}_u(n) \end{aligned}$$

↪ Design  $K$  by a LQR-like problem  
(Using  $\Phi = \sum_{n=1}^{\infty} \Phi(n) z^{-n}$ )

↪ Structure of  $K$  encoded by  $(\mathbf{C}_x, \mathbf{C}_u)$   
(e.g., spatiotemporal info. structures encoded by sparsity constraints)

# SLS for Linear Quadratic Games

## (Potential) Linear Quadratic Games - SLS Approach

$$\forall p \in \mathcal{P} : \left\{ \begin{array}{ll} \min_{u_p := K_p * x} & \lim_{T \rightarrow \infty} \mathbb{E} \left[ \sum_{t=0}^T \left( \|Q^{1/2} x(t)\|_2^2 + \|R_p^{1/2} u_p(t)\|_2^2 \right) \right] \\ \text{s.t.} & x(t+1) = Ax(t) + \sum_{\bar{p} \in \mathcal{P}} B_{\bar{p}} u_{\bar{p}}(t) + w(t), \quad x(0) \text{ given,} \\ & H_x x(t) \leq h_x, \quad H_{u,p} u_p(t) \leq h_{u,p}, \\ & K_p \in \mathbf{C}_p \cap \mathcal{RH}_{\infty} \end{array} \right.$$

► System-level parametrization (SLP)

$$\begin{aligned} [zI - A - B_1 \cdots B_{N_P}] \Phi &= I \\ \Rightarrow z\Phi_x &= I + A\Phi_x + \sum_{p \in \mathcal{P}} B_p \Phi_{u,p} \end{aligned}$$

► System-level constraints (SLCs)

$$\begin{aligned} x(t) \in \mathcal{X} &\Rightarrow (\Phi_x * w)(n) \in \mathcal{X} \\ u_p(t) \in \mathcal{U}_p &\Rightarrow (\Phi_{u,p} * w)(n) \in \mathcal{U}_p \end{aligned}$$

► Finite-impulse response (FIR) approximation  
(Given a horizon  $\bar{N} < \infty$ )

$$\mathbf{C}_x := \mathbf{C}_x \cap \left\{ \Phi_x \in \mathcal{RH}_{\infty} : \sum_{n=1}^{\bar{N}} z^{-n} \Phi_x(n) \right\}$$

► Relaxed "terminal" constraint  
(Given weighting matrix  $Q_f = Q_f^T \succeq 0$ )

$$\Phi_x(\bar{N}+1) = 0 \Rightarrow \min J_p + \left\| Q_f^{1/2} \Phi_x(\bar{N}+1) \right\|_F^2$$

# SLS for Linear Quadratic Games

## (Potential) Linear Quadratic Games - SLS Approach

$$\forall p \in \mathcal{P} : \left\{ \begin{array}{l} \min_{\Phi_{u,p}(\cdot)} \quad \lim_{N \rightarrow \infty} \sum_{n=1}^N \left( \|Q^{1/2} \Phi_x(n)\|_F^2 + \|R_p^{1/2} \Phi_{u,p}(n)\|_F^2 \right) \\ \text{s.t.} \quad \Phi_x(n+1) = A\Phi_x(n) + B_p \Phi_{u,p}(n) + z_{-p}(n), \quad \Phi_x(1) = I_{N_x}, \\ H_x(\Phi_x * w)(n) \leq h_x, \quad H_{u,p}(\Phi_{u,p} * w)(n) \leq h_{u,p}, \\ \Phi_x(n) \in \mathcal{C}_x(n), \quad \Phi_{u,p}(n) \in \mathcal{C}_{u,p}(n) \end{array} \right.$$

Letting  $z_{-p} = \sum_{\bar{p} \in \mathcal{P} \setminus \{p\}} B_{\bar{p}} \Phi_{u,\bar{p}}$  denote other players' strategies

- System-level parametrization (SLP)

$$\begin{aligned} & \begin{bmatrix} zI - A & B_1 \cdots B_{N_P} \end{bmatrix} \Phi = I \\ \Rightarrow & z\Phi_x = I + A\Phi_x + \sum_{p \in \mathcal{P}} B_p \Phi_{u,p} \end{aligned}$$

- System-level constraints (SLCs)

$$\begin{aligned} x(t) \in \mathcal{X} & \Rightarrow (\Phi_x * w)(n) \in \mathcal{X} \\ u_p(t) \in \mathcal{U}_p & \Rightarrow (\Phi_{u,p} * w)(n) \in \mathcal{U}_p \end{aligned}$$

- Finite-impulse response (FIR) approximation  
(Given a horizon  $\bar{N} < \infty$ )

$$\mathcal{C}_x := \mathcal{C}_x \cap \left\{ \Phi_x \in \mathcal{RH}_\infty : \sum_{n=1}^{\bar{N}} z^{-n} \Phi_x(n) \right\}$$

- Relaxed “terminal” constraint  
(Given weighting matrix  $Q_f = Q_f^\top \gg 0$ )

$$\Phi_x(\bar{N}+1) = 0 \Rightarrow \min J_p + \|Q_f^{1/2} \Phi_x(\bar{N}+1)\|_F^2$$

# SLS for Linear Quadratic Games

## (Potential) Linear Quadratic Games - SLS Approach

$$\forall p \in \mathcal{P} : \begin{cases} \min_{\Phi_{u,p}(\cdot)} & \sum_{n=1}^{\bar{N}} \left( \|Q^{1/2} \Phi_x(n)\|_F^2 + \|R_p^{1/2} \Phi_{u,p}(n)\|_F^2 \right) \\ \text{s.t.} & \Phi_x(n+1) = A\Phi_x(n) + B_p\Phi_{u,p}(n) + z_{-p}(n), \quad \Phi_x(1) = I_{N_x}, \quad \Phi_x(\bar{N}+1) = 0 \\ & H_x(\Phi_x * w)(n) \leq h_x, \quad H_{u,p}(\Phi_{u,p} * w)(n) \leq h_{u,p}, \\ & \Phi_x(n) \in \mathcal{C}_x(n), \quad \Phi_{u,p}(n) \in \mathcal{C}_{u,p}(n) \end{cases}$$

Letting  $z_{-p} = \sum_{\bar{p} \in \mathcal{P} \setminus \{p\}} B_{\bar{p}} \Phi_{u,\bar{p}}$  denote other players' strategies

- System-level parametrization (SLP)

$$\begin{aligned} & \begin{bmatrix} zI - A & B_1 \cdots B_{N_P} \end{bmatrix} \Phi = I \\ \Rightarrow & z\Phi_x = I + A\Phi_x + \sum_{p \in \mathcal{P}} B_p \Phi_{u,p} \end{aligned}$$

- System-level constraints (SLCs)

$$\begin{aligned} x(t) \in \mathcal{X} & \Rightarrow (\Phi_x * w)(n) \in \mathcal{X} \\ u_p(t) \in \mathcal{U}_p & \Rightarrow (\Phi_{u,p} * w)(n) \in \mathcal{U}_p \end{aligned}$$

- Finite-impulse response (FIR) approximation  
(Given a horizon  $\bar{N} < \infty$ )

$$\mathcal{C}_x := \mathcal{C}_x \cap \left\{ \Phi_x \in \mathcal{RH}_\infty : \sum_{n=1}^{\bar{N}} z^{-n} \Phi_x(n) \right\}$$

- Relaxed “terminal” constraint  
(Given weighting matrix  $Q_f = Q_f^T \gg 0$ )

$$\Phi_x(\bar{N}+1) = 0 \Rightarrow \min J_p + \|Q_f^{1/2} \Phi_x(\bar{N}+1)\|_F^2$$

# SLS for Linear Quadratic Games

## (Potential) Linear Quadratic Games - SLS Approach

$$\forall p \in \mathcal{P} : \begin{cases} \min_{\Phi_{u,p}(\cdot)} & \sum_{n=1}^{\bar{N}} \left( \|Q^{1/2} \Phi_x(n)\|_F^2 + \|R_{pp}^{1/2} \Phi_{u,p}(n)\|_F^2 \right) + \|Q_f^{1/2} \Phi_x(\bar{N}+1)\|_F^2 \\ \text{s.t.} & \Phi_x(n+1) = A\Phi_x(n) + B_p\Phi_{u,p}(n) + z_{-p}(n), \quad \Phi_x(1) = I_{N_x}, \\ & H_x(\Phi_x * w)(n) \leq h_x, \quad H_{u,p}(\Phi_{u,p} * w)(n) \leq h_{u,p}, \\ & \Phi_x(n) \in \mathcal{C}_x(n), \quad \Phi_{u,p}(n) \in \mathcal{C}_{u,p}(n) \end{cases}$$

Letting  $z_{-p} = \sum_{\bar{p} \in \mathcal{P} \setminus \{p\}} B_{\bar{p}} \Phi_{u,\bar{p}}$  denote other players' strategies

- System-level parametrization (SLP)

$$\begin{aligned} & [zI - A \quad B_1 \cdots B_{N_P}] \Phi = I \\ \Rightarrow & z\Phi_x = I + A\Phi_x + \sum_{p \in \mathcal{P}} B_p \Phi_{u,p} \end{aligned}$$

- System-level constraints (SLCs)

$$\begin{aligned} x(t) \in \mathcal{X} & \Rightarrow (\Phi_x * w)(n) \in \mathcal{X} \\ u_p(t) \in \mathcal{U}_p & \Rightarrow (\Phi_{u,p} * w)(n) \in \mathcal{U}_p \end{aligned}$$

- Finite-impulse response (FIR) approximation  
(Given a horizon  $\bar{N} < \infty$ )

$$\mathcal{C}_x := \mathcal{C}_x \cap \left\{ \Phi_x \in \mathcal{RH}_\infty : \sum_{n=1}^{\bar{N}} z^{-n} \Phi_x(n) \right\}$$

- Relaxed “terminal” constraint  
(Given weighting matrix  $Q_f = Q_f^T \gg 0$ )

$$\Phi_x(\bar{N}+1) = 0 \Rightarrow \min J_p + \|Q_f^{1/2} \Phi_x(\bar{N}+1)\|_F^2$$

# SLS for Linear Quadratic Games, overview

## Algorithm: System-Level Best-Response Dynamics (SL-BRD)

Initialize  $\Phi_u^{(0)} := (\Phi_{u,1}^{(0)}, \dots, \Phi_{u,N_p}^{(0)})$ ,  $K^{(0)} := \Phi_u^{(0)} \Phi_x^{(0)-1}$  and  $t := 0$ ;

**while**  $K^{(t)}$  is not an  $\epsilon$ -NE **do**

    /\* Players observe  $x(t)$  and decide  $u_1(t), \dots, u_{N_p}(t)$  \*/

    Choose a player  $p \in \mathcal{P}$ ; // (e.g., "clockwise")

    Update  $\Phi_{u,p}^{(t+1)} := BR_p(\Phi_{u,-p}^{(t)}) = \arg \min_{\Phi_{u,p}} J_p(\Phi_{u,p}, \Phi_{u,-p}^{(t)})$ ;

**for**  $p \in \mathcal{P}$  **do**

        Update  $z_{-p} = \sum_{\bar{p} \in \mathcal{P} \setminus \{p\}} B_{\bar{p}} \Phi_{u,\bar{p}}$  and compute  $\Phi_x^{(t+1)}$ ;

        Update  $K_p^{(t+1)} := \Phi_{u,p}^{(t+1)} \Phi_x^{(t+1)-1}$ ;

$t := t + 1$  ;

- ✓ Closed-loop NE via open-loop game
- ✓ Operational and structural constraints
- ✓ Learning dynamics not affected by  $w$
- ✗ Slow convergence rates
- ✗  $(\mathcal{X}, \mathcal{U})$ -constraints as functions of  $w$
- ✗ Relaxed FIR approximation


# Example

A System-Level Approach to Best Response Dynamics

March 18, 2022



## Example, $N$ -chain system w/ communication constraints



↪ **Dynamics:**  $z\mathbf{x} = \mathbf{A}\mathbf{x} + \mathbf{B}\mathbf{u} + \mathbf{w}$ ,

$$\mathbf{A} = \begin{bmatrix} 1 & 0.2 & & \\ -0.2 & \ddots & \ddots & \\ & \ddots & \ddots & 0.2 \\ & & -0.2 & 1 \end{bmatrix}_{N_x \times N_x}$$

$$\mathbf{B} = \begin{bmatrix} I_2 & & \\ \underbrace{\quad}_{B_1} & \underbrace{\quad}_{B_2} & \underbrace{I_2}_{B_3} \end{bmatrix}_{N_x \times N_u}$$

↪ **Cost parameters:**

$$\mathbf{Q} = I_{N_x}, \quad \mathbf{Q}_f = 10^3 I_{N_x}, \quad \mathbf{R}_{pp} = I_{N_u^p}$$

↪ **Operational constraints:**

$$\mathcal{X} = \mathbb{R}^{N_x}, \quad \mathcal{U}_p = \mathbb{R}^{N_u^p} \quad (\forall p \in \mathcal{P})$$

↪ **Structural constraints:**



$$\bar{N} = 20 \quad (\text{FIR Horizon})$$

$$\mathcal{C}_x(n) = \{\Phi_x \in \mathbb{R}^{N_x \times N_x} : \text{sp } \Phi_x = \text{sp } A^{n-1}\}$$

$$\mathcal{C}_{u,p}(n) = \{\Phi_{u,p} \in \mathbb{R}^{N_u^p \times N_x} : \text{sp } \Phi_{u,p} = \text{sp } B_p^\top A^{n-1}\}$$

Considering  $w(t) \stackrel{iid}{\sim} \mathcal{N}(0, I_{N_x})$ ,  $t = 0, 1, \dots$

## Example, $N$ -chain system w/ communication constraints (cont.)



↪ **Equilibrium gap:**  $\epsilon = J_p - J_p^* \approx \{0.12, 0.11, 0.09\}$

↪ **FIR soft-constraint:**  $\|\Phi_x(T+1)\|_F^2 \approx 10^{-5}$

The SLS-BRD yields a **closed-loop  $\epsilon$ -NE** of control policies which are **stabilizing** and **satisfy dynamic information patterns**

# Thank you!



otacilio.neto@aalto.fi



@tiominho



@\_tioMinho



tiominho.github.io



## Questions?