12. Foundations of Statics

Mechanics of Manipulation

Matt Mason

matt.mason@cs.cmu.edu

http://www.cs.cmu.edu/~mason

Carnegie Mellon

1.5 Bibliographic notes 8 Exercises 8 Chapter 2 Kinematics 11 2.1 Preliminaries 11 2.2 Planar kinematics 15 2.3 Spherical kinematics 20 2.4 Spatial kinematics 22 2.5 Kinematic constraint 25 2.6 Kinematic mechanisms 34 2.7 Bibliographic notes 36 Exercises 37 Chapter 3 Kinematic Representation 41 3.1 Representation of spatial rotations 41 3.2 Representation of spatial displacements 58 3.3 Kinematic constraints 68

Chapter 4 Kinematic Manipulation 77

4.3 Kinematic models of contact 86

4.2 Path planning for nonholonomic systems 84

3.4 Bibliographic notes 72 Exercises 72

4.4 Bibliographic notes 88

Exercises 88

4.1 Path planning 77

Chapter 1 Manipulation 1

1.3 Issues in manipulation 5

1.1 Case 1: Manipulation by a human 11.2 Case 2: An automated assembly system 3

1.4 A taxonomy of manipulation techniques 7

5.1	Forces acting on rigid bodies 93		
5.2	Polyhedral convex cones 99		
5.3	Contact wrenches and wrench cones 102		
5.4	Cones in velocity twist space 104		
5.5	The oriented plane 105		
5.6	Instantaneous centers and Reuleaux's method 10		
5.7	Line of force; moment labeling 110		
5.8	Force dual 112		
5.9	Summary 117		
5.10	Bibliographic notes 117		
	Exercises 118		
Chapter 6 Friction 121			

Chapter 5 Rigid Body Statics 93

6.1	Coulomb's Law 121			
6.2	Single degree-of-freedom problems 123			
6.3	Planar single contact problems 126			
6.4	Graphical representation of friction cones	127		
6.5	Static equilibrium problems 128			
6.6	Planar sliding 130			
6.7	Bibliographic notes 139			
	Exercises 139			
Chapter 7 Quasistatic Manipulation 143				

7.1 Grasping and fixturing 143 7.2 Pushing 147 7.3 Stable pushing 153 7.4 Parts orienting 162 7.5 Assembly 168 7.6 Bibliographic notes 173 Exercises 175

3.1	Newton's laws 181
3.2	A particle in three dimensions 181
3.3	Moment of force; moment of momentum 183
3.4	Dynamics of a system of particles 184
3.5	Rigid body dynamics 186
3.6	The angular inertia matrix 189
3.7	Motion of a freely rotating body 195
3.8	Planar single contact problems 197
3.9	Graphical methods for the plane 203
3.10	Planar multiple-contact problems 205
3.11	Bibliographic notes 207
	Exercises 208

9.1 A particle 211 9.2 Rigid body impact 217 9.3 Bibliographic notes 223 Exercises 223

Chapter 9 Impact 211

Chapter 8 Dynamics 181

10.1	Quasidynamic manipulation 225	
10.2	Brie y dynamic manipulation 229	
10.3	Continuously dynamic manipulation	230
10.4	Bibliographic notes 232	
	Exercises 235	

Chapter 10 Dynamic Manipulation 225

Appendix A Infinity 237

Outline.

Summary:

- According to Newton, particles interact through forces.
- Rigid bodies interact through wrenches.
- Wrenches and twists are dual.

Outline:

- 1. Foundations.
- 2. Equivalence theorems.
- 3. Line of action.
- 4. Poinsot's theorem.
- 5. Wrenches.

What is force?

You cannot measure force, only its effects: deformation of structures, acceleration.

We could start from Newton's laws, but instead we hypothesize:

A force applied to a particle is a vector.

Motion is determined by vector sum.

A particle remains at rest only if total force acting on it is zero.

Moment of force

Moment of force about a line:

Let l be line through origin with direction $\hat{\mathbf{l}}$,

Let f act at x.

moment of force or **torque** of f about l:

$$n_l = \hat{\mathbf{l}} \cdot (\mathbf{x} \times \mathbf{f})$$

Moment of force

Moment of force about a line:

Let l be line through origin with direction $\hat{\mathbf{l}}$,

Let f act at x.

moment of force or **torque** of f about l:

$$n_l = \hat{\mathbf{l}} \cdot (\mathbf{x} \times \mathbf{f})$$

Moment of force about a point:

moment of force or **torque** of f about O:

$$\mathbf{n}_O = (\mathbf{x} - \mathbf{O}) \times \mathbf{f}$$

If the origin is O this reduces to $n = x \times f$.

If \mathbf{n} is moment about the origin, and n_l is moment about l through the origin,

$$n_l = \hat{\mathbf{l}} \cdot \mathbf{n}$$

Rigid body force

Consider a rigid body, and a set of forces $\{f_i\}$ acting at $\{x_i\}$ resp.

Total force F: sum of all external forces.

Total moment N: sum of all corresponding moments.

$$\mathbf{F} = \sum \mathbf{f}_i$$
 $\mathbf{N} = \sum \mathbf{x}_i imes \mathbf{f}_i$

Two systems of forces are **equivalent** if they have equal **F** and **N**.

(Equivalent, specifically, because they would have the same effect on a rigid body, according to Newton.

Resultant

Resultant of a system of forces: a system comprising a single force, equivalent to the given system.

Line of action

Consider a force f applied at some point x_1 .

Total force: $\mathbf{F} = \mathbf{f}$

Total moment: $N = x_1 \times f$.


Consider line parallel to f through x_1 , and a second point x_2 on the line.

Force f through x_2 is equivalent to force f through x_1 .

So *point* of application is more than you need to know . . .

Line of action of a force: line through point of application parallel to force.

Bound vector, free vector, line vector, point vector.




Resultant of two forces

Let \mathbf{f}_1 and \mathbf{f}_2 act along L_1 and L_2 respectively.

Slide \mathbf{f}_1 and \mathbf{f}_2 along their respective lines of action to the intersection (if any)

Resultant: the vector sum $\mathbf{f}_1 + \mathbf{f}_2$, acting at the intersection.

Lecture 12.



Change of reference

Using reference Q or R, a system is described by

$$\mathbf{F}_Q = \sum f_i$$
 $\mathbf{N}_Q = \sum (\mathbf{x}_i - \mathbf{Q}) \times \mathbf{f}_i$ $\mathbf{F}_R = \sum f_i$ $\mathbf{N}_R = \sum (\mathbf{x}_i - \mathbf{R}) \times \mathbf{f}_i$

From which it follows

$$\mathbf{F}_R = \mathbf{F}_Q$$
 $\mathbf{N}_R - \mathbf{N}_Q = \sum (\mathbf{Q} - \mathbf{R}) \times \mathbf{f}_i$

which gives

$$\mathbf{N}_R = \mathbf{N}_Q + (\mathbf{Q} - \mathbf{R}) \times \mathbf{F}$$

Couple

Is a moment like a force? Can you apply a moment? Does it have a line of action?

A **couple** is a system of forces whose total force $\mathbf{F} = \sum \mathbf{f}_i$ is zero.

I.e. a pure moment.

Notice that the moment **N** of a couple is independent of reference point.

For an arbitrary couple, can you construct an equivalent system of just two forces?

Couple


Is a moment like a force? Can you apply a moment? Does it have a line of action?

A **couple** is a system of forces whose total force $\mathbf{F} = \sum \mathbf{f}_i$ is zero.

I.e. a pure moment.

Notice that the moment N of a couple is independent of reference point.

For an arbitrary couple, can you construct an equivalent system of just two forces?



Equivalence theorems

Our goal: defining *wrench*, and showing every system of forces is equivalent to some wrench.

Analogous to the program for kinematics, resulting in definition of screw.

Theorem: For any reference point Q, any system of forces is equivalent to a single force through Q, plus a couple. Proof:

Let **F** be the total force;

let N_Q be the total moment about Q.

Apply \mathbf{F} at Q;

construct a couple with moment N_Q .

Two forces are sufficient

Theorem: Every system of forces is equivalent to a system of just two forces.

Proof:

Given arbitrary **F** and **N**, construct equivalent force and couple, comprising three forces in total.

Move couple so that one of its forces acts at same point as **F**.

Replace those two forces with their resultant.

Planar system with nonzero F has a resultant

Theorem: A system consisting of a single non-zero force plus a couple in the same plane, i.e. a torque vector perpendicular to the force, has a resultant.


Proof:

Let \mathbf{F} be the force, acting at P.

Let N be the moment of the couple.

Construct an equivalent couple as in the figure.

Translate the couple so $-\mathbf{F}$ is applied at P.



Poinsot's theorem

Every system of forces is equivalent to a single force, plus a couple with moment parallel to the force.

Proof:

Let **F** and **N** be the given force and moment.

Decompose the moment: N_{\parallel} parallel to F, and N_{\perp} perpendicular to F.

Since planar system with nonzero force has a resultant, replace \mathbf{F} and \mathbf{N}_{\perp} by a single force \mathbf{F}' parallel to \mathbf{F} .

Now we construct a couple with moment \mathbf{N}_{\parallel} to obtain the desired result: a force and a couple with moment parallel to the force.

Wrench

Wrench: a screw plus a scalar magnitude, giving a force along the screw axis plus a moment about the screw axis.

The force magnitude is the wrench magnitude, and the moment is the twist magnitude times the pitch.

Thus the pitch is the ratio of moment to force.

Poinsot's theorem is succinctly stated: every system of rigid body forces reduces to a wrench along some screw.

Screw coordinates for wrenches

Let f be the magnitude of the force acting along a line l,

Let n be the magnitude of the moment about l.

The magnitude of the wrench is f.

Recall definition in terms of Plücker coordinates:

$$\mathbf{w} = f\mathbf{q}$$
$$\mathbf{w}_0 = f\mathbf{q}_0 + fp\mathbf{q}$$

where $(\mathbf{q}, \mathbf{q}_0)$ are the normalized Plücker coordinates of the wrench axis l, and p is the pitch, which is defined to be

$$p = n/f$$

Screw coordinates for wrenches demystified

Let **r** be some point on the wrench axis

$$\mathbf{q}_0 = \mathbf{r} \times \mathbf{q}$$

With some substitutions . . .

$$\mathbf{w} = \mathbf{f}$$
 $\mathbf{w}_0 = \mathbf{r} \times \mathbf{f} + \mathbf{n}$

which can be written:

$$\mathbf{w} = \mathbf{f}$$
$$\mathbf{w}_0 = \mathbf{n}_0$$

where \mathbf{n}_0 is just the moment of force at the origin.

Screw coordinates of a wrench are actually a familiar representation $(\mathbf{f},\mathbf{n}_0)$.

Reciprocal product of twist and wrench

Reciprocal product:

$$(\omega, \mathbf{v}_0) * (\mathbf{f}, \mathbf{n}_0) = \mathbf{f} \cdot \mathbf{v}_0 + \mathbf{n}_0 \cdot \omega$$

The power produced by the wrench $(\mathbf{f}, \mathbf{n}_0)$ and differential twist (ω, \mathbf{v}_0) .

A differential twist is reciprocal to a wrench if and only if no power would be produced.

Repelling if and only if positive power.

Contrary if and only if negative power.

Force versus motion

Wrench coordinates and twist coordinates seem to use different conventions.

Rotation or translation first? Pitch is translation over rotation, or its inverse?

Not just a peculiar convention. Roles of translation and rotation are reversed!

Example: rotation axis versus line of action.

Comparing motion and force

Motion

A zero-pitch twist is a pure rotation.

For a pure translation, the direction of the axis is determined, but the location is not.

A differential translation is equivalent to a rotation about an axis at infinity.

In the plane, any motion can be described as a rotation about some point, possibly at infinity.

Force

A zero-pitch wrench is a pure force.

For a pure moment, the direction of the axis is determined, but the location is not.

A couple is equivalent to a force along a line at infinity.

In the plane, any system of forces reduces to a single force, possibly at infinity.

1.5 Bibliographic notes 8 Exercises 8

Chapter 2 Kinematics 11

Chapter 1 Manipulation 1

1.3 Issues in manipulation 5

1.1 Case 1: Manipulation by a human 1

1.2 Case 2: An automated assembly system 3

1.4 A taxonomy of manipulation techniques 7

- 2.1 Preliminaries 11
- 2.2 Planar kinematics 15
- 2.3 Spherical kinematics 20
- 2.4 Spatial kinematics 22
- 2.5 Kinematic constraint 25
- 2.6 Kinematic mechanisms 34
- 2.7 Bibliographic notes 36 Exercises 37

Chapter 3 Kinematic Representation 41

- 3.1 Representation of spatial rotations 41
- 3.2 Representation of spatial displacements 58
- 3.3 Kinematic constraints 68
- 3.4 Bibliographic notes 72 Exercises 72

Chapter 4 Kinematic Manipulation 77

- 4.1 Path planning 77
- 4.2 Path planning for nonholonomic systems 84
- 4.3 Kinematic models of contact 86
- 4.4 Bibliographic notes 88
 Exercises 88

Chapter 5 Rigid Body Statics 93

- 5.1 Forces acting on rigid bodies 93
- 5.2 Polyhedral convex cones 99
- 5.3 Contact wrenches and wrench cones 102
- 5.4 Cones in velocity twist space 104
- 5.5 The oriented plane 105
- 5.6 Instantaneous centers and Reuleaux's method 109
- 5.7 Line of force; moment labeling 110
- 5.8 Force dual 112
- 5.9 Summary 117
- 5.10 Bibliographic notes 117
 Exercises 118

Chapter 6 Friction 121

- 6.1 Coulomb's Law 121
- 6.2 Single degree-of-freedom problems 123
- 6.3 Planar single contact problems 126
- 6.4 Graphical representation of friction cones 127
- 6.5 Static equilibrium problems 128
- 6.6 Planar sliding 130
- 6.7 Bibliographic notes 139 Exercises 139

Chapter 7 Quasistatic Manipulation 143

- 7.1 Grasping and fixturing 143
- 7.2 Pushing 147
- 7.3 Stable pushing 153
- 7.4 Parts orienting 162
- 7.5 Assembly 168

Lecture 12.

7.6 Bibliographic notes 173 Exercises 175

Chapter 8 Dynamics 181

- 8.1 Newton's laws 181
- 8.2 A particle in three dimensions 181
- 8.3 Moment of force; moment of momentum 183
- 8.4 Dynamics of a system of particles 184
- 8.5 Rigid body dynamics 186
- 8.6 The angular inertia matrix 189
- 8.7 Motion of a freely rotating body 195
- 8.8 Planar single contact problems 197
- 8.9 Graphical methods for the plane 203
- 8.10 Planar multiple-contact problems 205
- 8.11 Bibliographic notes 207 Exercises 208

Chapter 9 Impact 211

- 9.1 A particle 211
- 9.2 Rigid body impact 217
- 9.3 Bibliographic notes 223 Exercises 223

Chapter 10 Dynamic Manipulation 225

- 10.1 Quasidynamic manipulation 225
- 10.2 Brie y dynamic manipulation 229
- 10.3 Continuously dynamic manipulation 230
- 10.4 Bibliographic notes 232 Exercises 235

Appendix A Infinity 237

Mechanics of Manipulation – p.22