

# 8. Representing displacements

## *Mechanics of Manipulation*

Matt Mason

`matt.mason@cs.cmu.edu`

`http://www.cs.cmu.edu/~mason`

Carnegie Mellon

**Chapter 1 Manipulation 1**

- 1.1 Case 1: Manipulation by a human 1
- 1.2 Case 2: An automated assembly system 3
- 1.3 Issues in manipulation 5
- 1.4 A taxonomy of manipulation techniques 7
- 1.5 Bibliographic notes 8
- Exercises 8

**Chapter 2 Kinematics 11**

- 2.1 Preliminaries 11
- 2.2 Planar kinematics 15
- 2.3 Spherical kinematics 20
- 2.4 Spatial kinematics 22
- 2.5 Kinematic constraint 25
- 2.6 Kinematic mechanisms 34
- 2.7 Bibliographic notes 36
- Exercises 37

**Chapter 3 Kinematic Representation 41**

- 3.1 Representation of spatial rotations 41
- 3.2 Representation of spatial displacements 58
- 3.3 Kinematic constraints 68
- 3.4 Bibliographic notes 72
- Exercises 72

**Chapter 4 Kinematic Manipulation 77**

- 4.1 Path planning 77
- 4.2 Path planning for nonholonomic systems 84
- 4.3 Kinematic models of contact 86
- 4.4 Bibliographic notes 88
- Exercises 88

**Chapter 5 Rigid Body Statics 93**

- 5.1 Forces acting on rigid bodies 93
- 5.2 Polyhedral convex cones 99
- 5.3 Contact wrenches and wrench cones 102
- 5.4 Cones in velocity twist space 104
- 5.5 The oriented plane 105
- 5.6 Instantaneous centers and Reuleaux's method 109
- 5.7 Line of force; moment labeling 110
- 5.8 Force dual 112
- 5.9 Summary 117
- 5.10 Bibliographic notes 117
- Exercises 118

**Chapter 6 Friction 121**

- 6.1 Coulomb's Law 121
- 6.2 Single degree-of-freedom problems 123
- 6.3 Planar single contact problems 126
- 6.4 Graphical representation of friction cones 127
- 6.5 Static equilibrium problems 128
- 6.6 Planar sliding 130
- 6.7 Bibliographic notes 139
- Exercises 139

**Chapter 7 Quasistatic Manipulation 143**

- 7.1 Grasping and fixturing 143
- 7.2 Pushing 147
- 7.3 Stable pushing 153
- 7.4 Parts orienting 162
- 7.5 Assembly 168
- 7.6 Bibliographic notes 173
- Exercises 175

**Chapter 8 Dynamics 181**

- 8.1 Newton's laws 181
- 8.2 A particle in three dimensions 181
- 8.3 Moment of force; moment of momentum 183
- 8.4 Dynamics of a system of particles 184
- 8.5 Rigid body dynamics 186
- 8.6 The angular inertia matrix 189
- 8.7 Motion of a freely rotating body 195
- 8.8 Planar single contact problems 197
- 8.9 Graphical methods for the plane 203
- 8.10 Planar multiple-contact problems 205
- 8.11 Bibliographic notes 207
- Exercises 208

**Chapter 9 Impact 211**

- 9.1 A particle 211
- 9.2 Rigid body impact 217
- 9.3 Bibliographic notes 223
- Exercises 223

**Chapter 10 Dynamic Manipulation 225**

- 10.1 Quasidynamic manipulation 225
- 10.2 Brie y dynamic manipulation 229
- 10.3 Continuously dynamic manipulation 230
- 10.4 Bibliographic notes 232
- Exercises 235

**Appendix A Infinity 237**

# Outline.

- Review of spatial displacements
- Homogeneous coordinates
- Plücker coordinates of a line
- Screw coordinates

# Review of spatial displacements

Definition: rigid motion

Theorem 2.2: any displacement of  $\mathbf{E}^n$  can be represented as a rotation composed with a translation.

Definition: a **screw** is a line plus a pitch.

Definition: a **twist** is a motion along a screw.

Theorem 2.7 (Chasles's theorem): every displacement of  $\mathbf{E}^3$  is a twist.

These can guide design of representations.

# Homogeneous coordinates

Recall theorem 2.2: a displacement can be decomposed into a rotation followed by a translation.

$$\mathbf{x}' = R\mathbf{x} + \mathbf{d}$$

We can write it more compactly. Add a fourth component to points:

$$\mathbf{x} = \begin{pmatrix} x_1 \\ x_2 \\ x_3 \\ 1 \end{pmatrix}$$

(Remember, we did this before. If the fourth element is 0 we get points at infinity. Now we're focusing on ordinary points.)

# Transforms using homogeneous coords

Define the *homogeneous coordinate transform matrix*  $T$ :

$$T = \left( \begin{array}{ccc|c} & & & \\ & R & & \mathbf{d} \\ & & & \\ \hline & & & \\ 0 & 0 & 0 & 1 \end{array} \right)$$

And write

$$\mathbf{x}' = T\mathbf{x}$$

It's just a more compact way of writing:

$$\mathbf{x}' = R\mathbf{x} + \mathbf{d}$$

Especially useful for expressions such as  $\mathbf{x}' = T_3T_2T_1\mathbf{x}$ .

# Plücker coordinates

Screw coordinates are built on top of Plücker coordinates, which are a way of representing lines.

Let  $\mathbf{p}$  be a point on the line;


Let  $\mathbf{q}$  be the **direction vector**;

Let  $\mathbf{q}_0 = \mathbf{p} \times \mathbf{q}$ , the **moment vector**;

Then  $(\mathbf{q}, \mathbf{q}_0)$  gives the six **Plücker coordinates**;

(Note choice of  $\mathbf{p}$  doesn't matter:

$$\begin{aligned}\mathbf{p}' \times \mathbf{q} &= \mathbf{p} \times \mathbf{q} + (\mathbf{p}' - \mathbf{p}) \times \mathbf{q} \\ &= \mathbf{p} \times \mathbf{q}\end{aligned}$$



# Plücker's excess numbers

Plücker coordinates give six numbers. A line requires only four.

First, since  $\mathbf{q}_0 = \mathbf{p} \times \mathbf{q}$ , there is a constraint:

$$\mathbf{q} \cdot \mathbf{q}_0 = 0$$

Second, scaling gives same the line

$$(\mathbf{q}, \mathbf{q}_0) \equiv k(\mathbf{q}, \mathbf{q}_0)$$


(So, why not normalize, scaling by  $1/|\mathbf{q}|$ ? Sometimes, as we shall see,  $|\mathbf{q}| = 0$ !)



# Reading Plücker coordinates: generic case


Nonzero  $\mathbf{q}_0$  is orthogonal to a plane containing the line.

Magnitude  $|\mathbf{q}_0|/|\mathbf{q}|$  gives distance to line.



# Plücker coords of line through origin

Zero  $\mathbf{q}_0$ : Line passes through origin.




# Plücker coords of line at infinity


Nonzero  $\mathbf{q}_0$  is orthogonal to a plane containing the line.

Magnitude of  $|\mathbf{q}_0|/|\mathbf{q}|$  gives distance to line.

Work it out as a limiting process. Hold  $\mathbf{q}_0$  constant as line goes to infinity.



$\mathbf{q} = \mathbf{0}$



# Using Plücker coordinates

Direction of line :  $\mathbf{q}$ .

Distance of line from  $O$ :  $|\mathbf{q}_0|/|\mathbf{q}|$ .

Point-on-line test for point  $x$ :

$$(\mathbf{x} - \mathbf{p}) \times \mathbf{q} = 0$$

$$\mathbf{x} \times \mathbf{q} - \mathbf{p} \times \mathbf{q} = 0$$

$$\mathbf{x} \times \mathbf{q} = \mathbf{q}_0$$

Find point on line closest to  $O$ :

$$\mathbf{q} \times \mathbf{q}_0 / \mathbf{q} \cdot \mathbf{q}, \quad \text{for } \mathbf{q} \neq 0$$

# A topical example.




Fig. 2. Lateral and top drawings of a pipe crawling robot getting into a curve.

the authors report the design of a quadruped walking robot with passive articulated feet that adapt to the ground, thus being able to detect the orientation of the local ground surface by means of two angle sensors integrated at each robot's ankle.

Most tactile sensors, whether based on conductive silicone rubber, pressure-sensitive semiconductors, or piezoelectric elements, detect contact position using surface-mounted arrays of force-sensitive elements [24]. In this paper, a simpler system for the estimation of the normal vectors using a five-axis force/torque sensor is presented. This use of force sensors was first pointed out by Salisbury [30] in the context of manipulation systems. It is usually called *intrinsic* contact sensing for the use of internal force and torque measurements [1], [2], [6]. Force-based contact sensors have been actually implemented in robotic hands [4], [21], [35] and object shape detection systems [33]. To the authors' best knowledge, no existing legged robots implement this technique.




Fig. 3. Problem statement and reference system.

where

$$\mathbf{r}_0 = \frac{\mathbf{F} \times \mathbf{M}}{\|\mathbf{F}\|^2}. \quad (5)$$

The line of action of the force or wrench axis is a line through  $\mathbf{r}_0$  and parallel to  $\mathbf{F}$  parameterized by  $\lambda$ . This line intersects the foot surface in two locations: one corresponding to a force pulling out of the surface and one corresponding to a force pushing into the surface. Because adhesive forces are not allowed, the contact point is determined as the intersection point for which the contact force points inwardly at the foot surface, that is


# Moment about a point

Moment of a line  $l_2$  about a point  $p_1$ .  
In analogy with unit force in direction  $\mathbf{q}_2$ . What would the torque be?

$$(\mathbf{p}_2 - \mathbf{p}_1) \times \left( \frac{\mathbf{q}_2}{|\mathbf{q}_2|} \right)$$

$$\frac{\mathbf{p}_2 \times \mathbf{q}_2 - \mathbf{p}_1 \times \mathbf{q}_2}{|\mathbf{q}_2|}$$

$$\frac{\mathbf{q}_{02} - \mathbf{p}_1 \times \mathbf{q}_2}{|\mathbf{q}_2|}$$



# Moment about a line

Moment of a line  $l_2$  about a line  $l_1$ .

Think of the torque at  $\mathbf{p}_1$ , and take the component in the  $\mathbf{q}_1$  direction:

$$\frac{\mathbf{q}_1}{|\mathbf{q}_1|} \cdot \frac{\mathbf{q}_{02} - \mathbf{p}_1 \times \mathbf{q}_2}{|\mathbf{q}_2|}$$


$$\frac{\mathbf{q}_1 \cdot \mathbf{q}_{02} - \mathbf{q}_1 \cdot \mathbf{p}_1 \times \mathbf{q}_2}{|\mathbf{q}_1 \mathbf{q}_2|}$$

$$\frac{\mathbf{q}_1 \cdot \mathbf{q}_{02} + \mathbf{q}_2 \cdot \mathbf{p}_1 \times \mathbf{q}_1}{|\mathbf{q}_1 \mathbf{q}_2|}$$

$$\frac{\mathbf{q}_1 \cdot \mathbf{q}_{02} + \mathbf{q}_2 \cdot \mathbf{q}_{01}}{|\mathbf{q}_1 \mathbf{q}_2|}$$

It's symmetric. Moment of  $l_1$  about  $l_2$   
= moment of  $l_2$  about  $l_1$ .

This interesting product has *LOTS* of  
uses ...



# Reciprocal product / virtual product

Define **reciprocal product**, or **virtual product**:

$$(\mathbf{q}_1, \mathbf{q}_{01}) * (\mathbf{q}_2, \mathbf{q}_{02}) = \mathbf{q}_1 \cdot \mathbf{q}_{02} + \mathbf{q}_2 \cdot \mathbf{q}_{01}$$

For normalized Plücker coordinates, reciprocal product gives moment between the two lines.



# More uses for Plücker coordinates

Look at moment geometrically. Distance between the lines times sine of the angle.

$$d \sin \alpha = (\mathbf{q}_1, \mathbf{q}_{01}) * (\mathbf{q}_2, \mathbf{q}_{02}) / |\mathbf{q}_1 \mathbf{q}_2|$$

Note we can also get the angle by

$$\sin \alpha = \mathbf{q}_1 \times \mathbf{q}_2 / |\mathbf{q}_1 \mathbf{q}_2|$$


So to get the (signed) distance between two lines:

$$d = \frac{(\mathbf{q}_1, \mathbf{q}_{01}) * (\mathbf{q}_2, \mathbf{q}_{02})}{|\mathbf{q}_2 \times \mathbf{q}_1|}$$

To tell if two lines intersect, check if reciprocal product is zero.  
(Parallel lines intersect at infinity!)

# Example: using Plücker

Find the angle and distance between the two lines:



# Screw coordinates

A screw is a line plus a scalar pitch. Seven numbers?

No! We aren't really using those six numbers. Plenty of room to sneak pitch in.

Given a line  $(\mathbf{q}, \mathbf{q}_0)$ , and pitch  $p$ . Define the screw coordinates to be  $(\mathbf{s}, s_0)$ , where

$$\mathbf{s} = \mathbf{q}$$

$$s_0 = \mathbf{q}_0 + p\mathbf{q}$$

Why does this work? Recall  $\mathbf{q} \cdot \mathbf{q}_0$  is zero.

To get the pitch back

$$\mathbf{s} \cdot \mathbf{s}_0 = \mathbf{q} \cdot \mathbf{q}_0 + p\mathbf{q} \cdot \mathbf{q}$$

$$p = \frac{\mathbf{s} \cdot \mathbf{s}_0}{\mathbf{s} \cdot \mathbf{s}}$$

# Special case screws

Zero pitch: just like Plücker coordinates.

Infinite pitch:  $s = 0$ .

# Representing a twist

A twist is a screw plus a magnitude. Seven numbers?

No! Remember Plücker coordinates don't use scale. So take Plücker coordinates, normalize them, and scale.

Let  $\theta$  be the angle of rotation,  $d$  the distance of translation, both nonzero.

Let  $p = d/\theta$  be the pitch.

$$\left( \theta \frac{\mathbf{s}}{|\mathbf{s}|}, \theta \frac{\mathbf{s}_0}{|\mathbf{s}|} \right)$$

Substituting the definition of screw coordinates, we obtain

$$\begin{aligned} \left( \theta \frac{\mathbf{s}}{|\mathbf{s}|}, \theta \frac{\mathbf{s}_0}{|\mathbf{s}|} \right) &= \frac{1}{|\mathbf{q}|} (\theta \mathbf{q}, \theta \mathbf{q}_0 + \theta p \mathbf{q}) \\ &= \frac{1}{|\mathbf{q}|} (\theta \mathbf{q}, \theta \mathbf{q}_0 + d \mathbf{q}) \end{aligned}$$

# Twists of zero or infinite pitch

Infinite pitch is translation:

$$(\mathbf{s}, \mathbf{s}_0) = \frac{1}{|\mathbf{q}|} (\mathbf{0}, d\mathbf{q})$$

Zero pitch is rotation, identical to scaled Plücker coordinates:

$$\theta(\mathbf{s}, \mathbf{s}_0) = \theta(\mathbf{q}, \mathbf{q}_0).$$

assuming Plücker coordinates were normalized.

# Twists of zero or infinite pitch

Here is an interesting and instructive ambiguity. Somebody gives you, for example, a twist with screw coordinates:

$$(0, 0, 0, 1, 0, 0)$$

Is it a zero pitch screw with axis at infinity? I.e. a rotation about an axis at infinity?

Or is it an infinite pitch twist? I.e. a translation in the  $z$  direction?

Both!

# Consider the extremes

Translation: infinite pitch.  $(\mathbf{t}, \mathbf{t}_0) = (0, \mathbf{O}')$ . A very nice way to represent a translation.

Rotation through origin: zero pitch.

$$\begin{aligned}(\mathbf{t}, \mathbf{t}_0) &= \theta\left(\frac{\mathbf{s}}{|\mathbf{s}|}, \frac{\mathbf{s}_0}{|\mathbf{s}|}\right) \\&= \theta\left(\frac{\mathbf{q}}{|\mathbf{q}|}, \frac{\mathbf{q}_0}{|\mathbf{q}|}\right) \\&= (\theta \hat{\mathbf{n}}, 0)\end{aligned}$$

Angle times axis. We didn't cover it, but some people like it. Behaves well at small  $\theta$ , but doesn't extend to one-to-one smooth map. Obviously.



# Differential twists

Consider velocity  $v$  along  $l$  and angular velocity  $\omega$  about  $l$ .

Let  $\mathbf{p}$  be any point on  $l$ .


Plücker coordinates of  $l$  are

$$(\mathbf{q}, \mathbf{q}_0) = (\omega, \mathbf{p} \times \omega)$$

Pitch is  $|\mathbf{v}|/|\omega|$  so screw coordinates are

$$(\mathbf{s}, \mathbf{s}_0) = (\omega, \mathbf{p} \times \omega + \frac{|\mathbf{v}|}{|\omega|}\omega)$$

$$(\mathbf{s}, \mathbf{s}_0) = (\omega, \mathbf{p} \times \omega + \mathbf{v})$$




# Differential twists

The vector  $\mathbf{s}_0$  gives vel of origin  $\mathbf{v}_0$

$$(\mathbf{s}, \mathbf{s}_0) = (\omega, \mathbf{v}_0)$$

So, for differential twists, screw coords are close to standard practice.

Important corollary. *Screw coordinates for differential twists form a vector space.* We can add differential twist screw coordinates, and we can multiply them by scalars.



**Chapter 1 Manipulation 1**

- 1.1 Case 1: Manipulation by a human 1
- 1.2 Case 2: An automated assembly system 3
- 1.3 Issues in manipulation 5
- 1.4 A taxonomy of manipulation techniques 7
- 1.5 Bibliographic notes 8
- Exercises 8

**Chapter 2 Kinematics 11**

- 2.1 Preliminaries 11
- 2.2 Planar kinematics 15
- 2.3 Spherical kinematics 20
- 2.4 Spatial kinematics 22
- 2.5 Kinematic constraint 25
- 2.6 Kinematic mechanisms 34
- 2.7 Bibliographic notes 36
- Exercises 37

**Chapter 3 Kinematic Representation 41**

- 3.1 Representation of spatial rotations 41
- 3.2 Representation of spatial displacements 58
- 3.3 Kinematic constraints 68
- 3.4 Bibliographic notes 72
- Exercises 72

**Chapter 4 Kinematic Manipulation 77**

- 4.1 Path planning 77
- 4.2 Path planning for nonholonomic systems 84
- 4.3 Kinematic models of contact 86
- 4.4 Bibliographic notes 88
- Exercises 88

**Chapter 5 Rigid Body Statics 93**

- 5.1 Forces acting on rigid bodies 93
- 5.2 Polyhedral convex cones 99
- 5.3 Contact wrenches and wrench cones 102
- 5.4 Cones in velocity twist space 104
- 5.5 The oriented plane 105
- 5.6 Instantaneous centers and Reuleaux's method 109
- 5.7 Line of force; moment labeling 110
- 5.8 Force dual 112
- 5.9 Summary 117
- 5.10 Bibliographic notes 117
- Exercises 118

**Chapter 6 Friction 121**

- 6.1 Coulomb's Law 121
- 6.2 Single degree-of-freedom problems 123
- 6.3 Planar single contact problems 126
- 6.4 Graphical representation of friction cones 127
- 6.5 Static equilibrium problems 128
- 6.6 Planar sliding 130
- 6.7 Bibliographic notes 139
- Exercises 139

**Chapter 7 Quasistatic Manipulation 143**

- 7.1 Grasping and fixturing 143
- 7.2 Pushing 147
- 7.3 Stable pushing 153
- 7.4 Parts orienting 162
- 7.5 Assembly 168
- 7.6 Bibliographic notes 173
- Exercises 175

**Chapter 8 Dynamics 181**

- 8.1 Newton's laws 181
- 8.2 A particle in three dimensions 181
- 8.3 Moment of force; moment of momentum 183
- 8.4 Dynamics of a system of particles 184
- 8.5 Rigid body dynamics 186
- 8.6 The angular inertia matrix 189
- 8.7 Motion of a freely rotating body 195
- 8.8 Planar single contact problems 197
- 8.9 Graphical methods for the plane 203
- 8.10 Planar multiple-contact problems 205
- 8.11 Bibliographic notes 207
- Exercises 208

**Chapter 9 Impact 211**

- 9.1 A particle 211
- 9.2 Rigid body impact 217
- 9.3 Bibliographic notes 223
- Exercises 223

**Chapter 10 Dynamic Manipulation 225**

- 10.1 Quasidynamic manipulation 225
- 10.2 Brie y dynamic manipulation 229
- 10.3 Continuously dynamic manipulation 230
- 10.4 Bibliographic notes 232
- Exercises 235

**Appendix A Infinity 237**