

Protokoll

Router 1

```
Router#show ipv6 route
IPv6 Routing Table - 9 entries
Codes: C - Connected, L - Local, S - Static, R - RIP, B - BGP
       U - Per-user Static route, M - MIPv6
       I1 - ISIS L1, I2 - ISIS L2, IA - ISIS interarea, IS - ISIS summary
       ND - ND Default, NDp - ND Prefix, DCE - Destination, NDR - Redirect
       O - OSPF intra, OI - OSPF inter, OE1 - OSPF ext 1, OE2 - OSPF ext 2
       ON1 - OSPF NSSA ext 1, ON2 - OSPF NSSA ext 2
       D - EIGRP, EX - EIGRP external
C    2024:DB8:1:1::/64 [0/0]
    via GigabitEthernet0/1, directly connected
L    2024:DB8:1:1::1/128 [0/0]
    via GigabitEthernet0/1, receive
C    2024:DB8:1:3::/64 [0/0]
    via GigabitEthernet0/0, directly connected
L    2024:DB8:1:3::1/128 [0/0]
    via GigabitEthernet0/0, receive
C    2024:DB8:1:10::/64 [0/0]
    via GigabitEthernet0/2, directly connected
L    2024:DB8:1:10::1/128 [0/0]
    via GigabitEthernet0/2, receive
S    2024:DB8:1:20::/64 [1/0]
    via 2024:DB8:1:1::2
S    2024:DB8:1:30::/64 [1/0]
    via 2024:DB8:1:3::2
L    FF00::/8 [0/0]
    via Null0, receive
```

Router2

```
Router#show ipv6 route
IPv6 Routing Table - 9 entries
Codes: C - Connected, L - Local, S - Static, R - RIP, B - BGP
       U - Per-user Static route, M - MIPv6
       I1 - ISIS L1, I2 - ISIS L2, IA - ISIS interarea, IS - ISIS summary
       ND - ND Default, NDp - ND Prefix, DCE - Destination, NDR - Redirect
       O - OSPF intra, OI - OSPF inter, OE1 - OSPF ext 1, OE2 - OSPF ext 2
       ON1 - OSPF NSSA ext 1, ON2 - OSPF NSSA ext 2
       D - EIGRP, EX - EIGRP external
C    2024:DB8:1:2::/64 [0/0]
    via GigabitEthernet0/1, directly connected
L    2024:DB8:1:2::2/128 [0/0]
    via GigabitEthernet0/1, receive
C    2024:DB8:1:3::/64 [0/0]
    via GigabitEthernet0/0, directly connected
L    2024:DB8:1:3::2/128 [0/0]
    via GigabitEthernet0/0, receive
S    2024:DB8:1:10::/64 [1/0]
    via 2024:DB8:1:3::1
S    2024:DB8:1:20::/64 [1/0]
    via 2024:DB8:1:2::1
C    2024:DB8:1:30::/64 [0/0]
    via GigabitEthernet0/2, directly connected
L    2024:DB8:1:30::1/128 [0/0]
    via GigabitEthernet0/2, receive
L    FF00::/8 [0/0]
    via Null0, receive
```

Router3

```
Router#show ipv6 route
IPv6 Routing Table - 9 entries
Codes: C - Connected, L - Local, S - Static, R - RIP, B - BGP
       U - Per-user Static route, M - MIPv6
       I1 - ISIS L1, I2 - ISIS L2, IA - ISIS interarea, IS - ISIS summary
       ND - ND Default, NDP - ND Prefix, DCE - Destination, NDR - Redirect
       O - OSPF intra, OI - OSPF inter, OE1 - OSPF ext 1, OE2 - OSPF ext 2
       ON1 - OSPF NSSA ext 1, ON2 - OSPF NSSA ext 2
       D - EIGRP, EX - EIGRP external
C  2024:DB8:1:1::/64 [0/0]
   via GigabitEthernet0/1, directly connected
L  2024:DB8:1:1::2/128 [0/0]
   via GigabitEthernet0/1, receive
C  2024:DB8:1:2::/64 [0/0]
   via GigabitEthernet0/0, directly connected
L  2024:DB8:1:2::1/128 [0/0]
   via GigabitEthernet0/0, receive
S  2024:DB8:1:10::/64 [1/0]
   via 2024:DB8:1:1::1
C  2024:DB8:1:20::/64 [0/0]
   via GigabitEthernet0/2, directly connected
L  2024:DB8:1:20::1/128 [0/0]
   via GigabitEthernet0/2, receive
S  2024:DB8:1:30::/64 [1/0]
   via 2024:DB8:1:2::2
L  FF00::/8 [0/0]
   via Null0, receive
```

ICMPv6

Fire	Last Status	Source	Destination	Type	Color	Time(sec)	Periodic	Num	Edit	Delete
	Successful	Laptop1	2024:DB...	ICMPv6		1.000	N	0	(edit)	(delete)
	Successful	Laptop1	Laptop2	ICMPv6		0.000	N	1	(edit)	(delete)
	Successful	Laptop3	Laptop2	ICMPv6		0.000	N	2	(edit)	(delete)
	Successful	Laptop1	Laptop2	ICMPv6		0.000	N	3	(edit)	(delete)
	Successful	Laptop1	Laptop3	ICMPv6		0.000	N	4	(edit)	(delete)