

2nd CSI

Development of hybrid finite element/neural network methods to help create digital surgical twins

Michel Duprez¹, Emmanuel Franck², Frédérique Lecourtier¹ and Vanessa Lleras³

¹Project-Team MIMESIS, Inria, Strasbourg, France

²Project-Team MACARON, Inria, Strasbourg, France


³IMAG, University of Montpellier, Montpellier, France

June 12, 2025

★ - Update 2025

Scientific context

Context : Create real-time digital twins of an organ (e.g. liver).



Objective : Develop an hybrid finite element / neural network method.
accurate quick + parameterized

★ **Parametric elliptic convection/diffusion PDE :** For one or several $\mu \in \mathcal{M}$, find $u : \Omega \rightarrow \mathbb{R}$ such that

$$\mathcal{L}(u ; \boldsymbol{x}, \boldsymbol{\mu}) = f(\boldsymbol{x}, \boldsymbol{\mu}), \quad (\mathcal{P})$$

where \mathcal{L} is the parametric differential operator defined by


$$\mathcal{L}(\cdot ; \boldsymbol{x}, \boldsymbol{\mu}) : u \mapsto R(\boldsymbol{x}, \boldsymbol{\mu})u + C(\boldsymbol{\mu}) \cdot \nabla u - \frac{1}{\text{Pe}} \nabla \cdot (D(\boldsymbol{x}, \boldsymbol{\mu}) \nabla u),$$

and some Dirichlet, Neumann or Robin BC (which can also depend on $\boldsymbol{\mu}$).

Pipeline of the Enriched FEM

Enriched FEM = Combination of 2 standard methods

- **PINNs** : Physics Informed Neural Networks Appendix 1.1
- **FEMs** : Finite Element Methods Appendix 1.2



Remark : The PINN prediction enriched Finite element approximation spaces.

Enriched finite element method

Additive approach

★ Numerical results

This section is based on [Lecourtier et al., 2025].

Enriched finite element method

Additive approach

★ Numerical results

Additive approach

Variational Problem : Let $u_\theta \in H^{k+1}(\Omega) \cap H_0^1(\Omega)$.

$$\text{Find } p_h^+ \in V_h^0 \text{ such that, } \forall v_h \in V_h^0, a(p_h^+, v_h) = I(v_h) - a(u_\theta, v_h), \quad (\mathcal{P}_h^+)$$



with the **enriched trial space** V_h^+ defined by

$$V_h^+ = \{u_h^+ = u_\theta + p_h^+, \quad p_h^+ \in V_h^0\}.$$

General Dirichlet BC : If $u = g$ on $\partial\Omega$, then

$$p_h^+ = g - u_\theta \quad \text{on } \partial\Omega,$$

with u_θ the PINN prior.



Convergence analysis

Theorem 1: Convergence analysis of the standard FEM [Ern and Guermond, 2004]

We denote $u_h \in V_h$ the solution of (\mathcal{P}_h) with V_h the standard trial space. Then,

$$|u - u_h|_{H^1} \leq C_{H^1} h^k |u|_{H^{k+1}},$$

$$\|u - u_h\|_{L^2} \leq C_{L^2} h^{k+1} |u|_{H^{k+1}}.$$

Theorem 2: Convergence analysis of the enriched FEM [Lecourtier et al., 2025]

We denote $u_h^+ \in V_h^+$ the solution of (\mathcal{P}_h^+) with V_h^+ the enriched trial space. Then,

$$|u - u_h^+|_{H^1} \leq \boxed{\frac{|u - u_\theta|_{H^{k+1}}}{|u|_{H^{k+1}}}} (C_{H^1} h^k |u|_{H^{k+1}}),$$

$$\|u - u_h^+\|_{L^2} \leq \boxed{\frac{|u - u_\theta|_{H^{k+1}}}{|u|_{H^{k+1}}}} (C_{L^2} h^{k+1} |u|_{H^{k+1}}).$$

Gains of the additive approach.

LECOURTIER Frédérique

Enriched finite element method

Additive approach

★ Numerical results

1st problem considered

Problem statement: Considering an **Anisotropic Elliptic problem with Dirichlet BC**:

$$\begin{cases} -\operatorname{div}(D\nabla u) = f, & \text{in } \Omega, \\ u = 0, & \text{on } \partial\Omega, \end{cases}$$

with $\Omega = [0, 1]^2$ and $\mathcal{M} = [0.4, 0.6] \times [0.4, 0.6] \times [0.01, 1] \times [0.1, 0.8]$ ($p = 4$).

Right-hand side :

$$f(\mathbf{x}, \boldsymbol{\mu}) = \exp\left(-\frac{(x - \mu_1)^2 + (y - \mu_2)^2}{0.025\sigma^2}\right).$$

Diffusion matrix : (symmetric and positive definite)


$$D(\mathbf{x}, \boldsymbol{\mu}) = \begin{pmatrix} \epsilon x^2 + y^2 & (\epsilon - 1)xy \\ (\epsilon - 1)xy & x^2 + \epsilon y^2 \end{pmatrix}.$$

PINN training: Imposing BC exactly with a level-set function.

Numerical results

Error estimates : 1 set of parameters.


$$\mu = (0.51, 0.54, 0.52, 0.55)$$



Numerical results

Error estimates : 1 set of parameters.

$$\mu = (0.51, 0.54, 0.52, 0.55)$$



—■— FEM \mathbb{P}_1	—●— FEM \mathbb{P}_2	—▲— FEM \mathbb{P}_3
- - ■ - - Add \mathbb{P}_1	- - ● - - Add \mathbb{P}_2	- - ▲ - - Add \mathbb{P}_3

Gains achieved : $n_p = 50$ sets of parameters.

$$\mathcal{S} = \left\{ \mu^{(1)}, \dots, \mu^{(n_p)} \right\}$$

Gains in L^2 rel error of our method w.r.t. FEM			
k	min	max	mean
1	7.12	82.57	35.67
2	3.54	35.88	18.32
3	1.33	26.51	8.32

$$N = 20$$

$$\text{Gain : } \|u - u_h\|_{L^2} / \|u - u_h^+\|_{L^2}$$

Cartesian mesh : N^2 nodes.

2nd problem considered

Problem statement: Considering the Poisson problem with mixed BC:

$$\begin{cases} -\Delta u = f, & \text{in } \Omega \times \mathcal{M}, \\ u = g, & \text{on } \Gamma_E \times \mathcal{M}, \\ \frac{\partial u}{\partial n} + u = g_R, & \text{on } \Gamma_I \times \mathcal{M}, \end{cases}$$

with $\Omega = \{(x, y) \in \mathbb{R}^2, 0.25 \leq x^2 + y^2 \leq 1\}$ and $\mathcal{M} = [2.4, 2.6]$ ($\rho = 1$).

Analytical solution :

$$u(\mathbf{x}; \boldsymbol{\mu}) = 1 - \frac{\ln(\mu_1 \sqrt{x^2 + y^2})}{\ln(4)},$$

Boundary conditions :

$$g(\mathbf{x}; \boldsymbol{\mu}) = 1 - \frac{\ln(\mu_1)}{\ln(4)} \quad \text{and} \quad g_R(\mathbf{x}; \boldsymbol{\mu}) = 2 + \frac{4 - \ln(\mu_1)}{\ln(4)}.$$


PINN training: Imposing mixed BC exactly in the PINN¹.

¹[Sukumar and Srivastava, 2022]

Numerical results

Error estimates : 1 set of parameters.

$$\mu = 2.51$$



Gains achieved : $n_p = 50$ sets of parameters.

$$\mathcal{S} = \left\{ \boldsymbol{\mu}^{(1)}, \dots, \boldsymbol{\mu}^{(n_p)} \right\}$$

**Gains in L^2 rel error
of our method w.r.t. FEM**


k	min	max	mean
1	15.12	137.72	55.5
2	31	77.46	58.41
3	18.72	21.49	20.6

$$h = 1.33 \cdot 10^{-1}$$


$$\text{Gain : } \|u - u_h\|_{L^2} / \|u - u_h^+\|_{L^2}$$

Numerical solutions

1st problem : $\mu = (0.46, 0.52, 0.05, 0.12)$



2nd problem : $\mu = 2.51$



New lines of research

Complex geometries

★ Posteriori error estimates

★ Non linear PDEs

New lines of research

Complex geometries

★ Posteriori error estimates

★ Non linear PDEs

Learn a regular levelset

Theorem 3: [Clémot and Digne, 2023]

If we have a boundary domain Γ , the SDF is solution to the Eikonal equation:

$$\begin{cases} \|\nabla\phi(x)\| = 1, & x \in \mathcal{O} \\ \phi(x) = 0, & x \in \Gamma \\ \nabla\phi(x) = n, & x \in \Gamma \end{cases}$$



with \mathcal{O} a box which contains Ω completely and n the exterior normal to Γ .

Objective: Move on to complex geometries by using a levelset function to







- Sample points in the domain Ω for the PINN training.
- Impose exactly the boundary condition in PINN [Sukumar and Srivastava, 2022].

How to learn a regular levelset ? with a PINN by adding a regularization term,

$$J_{reg} = \int_{\mathcal{O}} |\Delta\phi|^2,$$

and a sample of boundary points that considers the curvature of Γ . ★

Numerical results



New lines of research

Complex geometries


★ Posteriori error estimates

★ Non linear PDEs

Adaptive mesh refinement

Adaptive refinement loop using Dorfler marking strategy. Appendix 2

Standard FEM



Local residual estimator (in L^2 norm): Let T be a cell of \mathcal{T}_h .


$$\eta_{res,T}^2 = h_T^4 \|\Delta u_h + f_h\|_{L^2(T)}^2 + \frac{1}{2} \sum_{E \in \partial T} h_E^2 \|[\nabla u_h \cdot n]\|_{L^2(E)}^2$$

with h_\bullet the size of \bullet and considering the Poisson problem.

Adaptive mesh refinement

Adaptive refinement loop using Dorfler marking strategy.

Additive Approach



Local residual estimator (in L^2 norm): Let T be a cell of \mathcal{T}_h .





$$\eta_{res,T}^2 = h_T^4 \| (\Delta u_\theta)_h + \Delta p_h^+ + f_h \|_{L^2(T)}^2 + \frac{1}{2} \sum_{E \in \partial T} h_E^2 \| [\nabla p_h^+ \cdot n] \|_{L^2(E)}^2$$

with h_\bullet the size of \bullet and considering the Poisson problem.

Adaptive mesh refinement

Adaptive refinement loop using Dorfler marking strategy.

Additive Approach - No resolution





Local residual estimator (in L^2 norm): Let T be a cell of \mathcal{T}_h .

$$\eta_{res,T}^2 = h_T^4 \|(\Delta u_\theta)_h + f_h\|_{L^2(T)}^2$$

with h_\bullet the size of \bullet and considering the Poisson problem.

Numerical results



⚠ Results obtained on a laptop GPU (probably due to external factors).

Ideas for improving results : Additive approach (no resolution).

- ↗ time Interpolate only mesh points added in the refinement process.
- ↗ mesh Use another metric such as curvature, rather than residual error.

$$\Delta u_\theta + f \quad \neq \quad u - u_\theta$$

New lines of research

Complex geometries

★ Posteriori error estimates

★ Non linear PDEs



Problem considered

TODO

Numerical results

TODO


Introduction



Enriched finite element method



New lines of research



Supplementary work



Conclusion



References

Supplementary work

LECOURTIER Frédérique

Development of an hybrid finite element and neural network method

Supplementary work I

Teaching

- ▶ 2024/2025 :
 - ▶ 64h of Computer Science Practical Work - L1S2 and L2S3 (Python) / L3S6 (C++)
 - ▶ 3 days supervising a group of high school girls in RJMI ("Rendez-vous des Jeunes Mathématiciennes et Informaticiennes")
- ▶ 2023/2024 : 50h of Computer Science Practical Work - L2S3 (Python) / L3S6 (C++)

Training courses (Total : 176h35)

- ▶ A dozen seminars organized by IRMA ($\approx 10h$)
- ▶ 1 Deep Learning introductory course - FIDLE ($\approx 40h$)
- ▶ 2 workshops on Scientific Machine Learning ($\approx 2 \times 21h$)
- ▶ 1 summer school on "New Trend in computing" ($\approx 27h$)
- ▶ several cross-disciplinary courses - Methodology, scientific English, etc. ($\approx 58h$)

Supplementary work II

Talks

- ▶ **ICOSAHOM 2025, Montréal** - July 2025 (*Coming soon...*)
"Enriching continuous Lagrange finite element approximation spaces using neural networks"
- ▶ **DTE & AICOMAS 2025, Paris** - February 20, 2025
"Combining Finite Element Methods and Neural Networks to Solve Elliptic Problems on 2D Geometries"
- ▶ **Exama project, WP2 reunion** - March 26, 2024
"How to work with complex geometries in PINNs ?"
- ▶ **Retreat (Macaron/Tonus)** - February 6, 2024
"Mesh-based methods and physically informed learning"
- ▶ **Team meeting (Mimesis)** - December 12, 2023
"Development of hybrid finite element/neural network methods to help create digital surgical twins"

Supplementary work III

Posters

- ▶ **EMS-TAG-SciML 2025, Milan** - March 24, 2025 - "Enriching continuous Lagrange finite element approximation spaces using neural networks"
- ▶ **CJC-MA 2024, Lyon** - October 29, 2024 - "Combining Finite Element Methods and Neural Networks to Solve Elliptic Problems on 2D Geometries"
- ▶ **MSII poster day, Strasbourg** - October 24, 2024
- ▶ **SciML 2024, Strasbourg** - July 08, 2024

Publications

- ▶ Enriching continuous lagrange finite element approximation spaces using neural networks. (*submitted in February 2025, M2AN journal*)
H. Barucq, M. Duprez, F. Faucher, E. Franck, **F. Lecourtier**, V. Lleras, V. Michel-Dansac, and N. Victorion.

Conclusion

TODO (parler de data-driven / multiplicative approach)

References

- Mark Ainsworth and J. Tinsley Oden. A posteriori error estimation in finite element analysis. *Computer Methods in Applied Mechanics and Engineering*, March 1997. doi: [10.1016/S0045-7825\(96\)01107-3](https://doi.org/10.1016/S0045-7825(96)01107-3).
- Clémot and Digne. Neural skeleton: Implicit neural representation away from the surface. *Computers and Graphics*, 2023.
- Willy Dörfler. A convergent adaptive algorithm for poisson's equation. *SIAM Journal on Numerical Analysis*, 33(3):1106–1124, 1996. doi: [10.1137/0733054](https://doi.org/10.1137/0733054).
- A. Ern and J.-L. Guermond. *Theory and Practice of Finite Elements*. Springer New York, 2004.
- E. Franck, V. Michel-Dansac, and L. Navoret. Approximately well-balanced Discontinuous Galerkin methods using bases enriched with Physics-Informed Neural Networks. *J. Comput. Phys.*, 512:113144, 2024. ISSN 0021-9991.
- I. E. Lagaris, A. Likas, and D. I. Fotiadis. Artificial neural networks for solving ordinary and partial differential equations. *IEEE Trans. Neural Netw.*, 9(5):987–1000, 1998. ISSN 1045-9227.
- F. Lecourtier, H. Barucq, M. Duprez, F. Faucher, E. Franck, V. Lleras, V. Michel-Dansac, and N. Victorion. Enriching continuous lagrange finite element approximation spaces using neural networks, 2025.
- M. Raissi, P. Perdikaris, and G. E. Karniadakis. Physics-informed neural networks: A deep learning framework for solving forward and inverse problems involving nonlinear partial differential equations. *J. Comput. Phys.*, 378:686–707, 2019.
- N. Sukumar and A. Srivastava. Exact imposition of boundary conditions with distance functions in physics-informed deep neural networks. *Comput. Method. Appl. M.*, 389:114333, 2022. ISSN 0045-7825.
- M. Tancik, P. Srinivasan, and al. Fourier Features Let Networks Learn High Frequency Function in Inherently Low Dimensional Domains. In *Advances in Neural Information Processing Systems*, volume 33, pages 7537–7547. Curran Associates, Inc., 2020.

Appendix 1 : Standard methods

A1.1 – Physics-Informed Neural Networks

Standard PINNs¹ (Weak BC) : Find the optimal weights θ^* , such that

$$\theta^* = \operatorname{argmin}_{\theta} (\omega_r J_r(\theta) + \omega_b J_b(\theta)), \quad (\mathcal{P}_\theta)$$

with

residual loss

$$J_r(\theta) = \int_{\mathcal{M}} \int_{\Omega} |\mathcal{L}(u_\theta(\mathbf{x}, \boldsymbol{\mu}); \mathbf{x}, \boldsymbol{\mu}) - f(\mathbf{x}, \boldsymbol{\mu})|^2 d\mathbf{x} d\boldsymbol{\mu},$$

boundary loss

$$J_b(\theta) = \int_{\mathcal{M}} \int_{\partial\Omega} |u_\theta(\mathbf{x}, \boldsymbol{\mu}) - g(\mathbf{x}, \boldsymbol{\mu})|^2 d\mathbf{x} d\boldsymbol{\mu},$$

where u_θ is a neural network, $g = 0$ is the Dirichlet BC.

In (\mathcal{P}_θ) , ω_r and ω_b are some weights.

Monte-Carlo method : Discretize the cost functions by random process.

¹[Raissi et al., 2019]

A1.1 – Physics-Informed Neural Networks

Improved PINNs¹ (Strong BC) : Find the optimal weights θ^* such that

$$\theta^* = \operatorname{argmin}_{\theta} (\omega_r J_r(\theta) + \cancel{\omega_b J_b(\theta)}),$$

with $\omega_r = 1$ and


residual loss

$$J_r(\theta) = \int_{\mathcal{M}} \int_{\Omega} |\mathcal{L}(u_{\theta}(\mathbf{x}, \boldsymbol{\mu}); \mathbf{x}, \boldsymbol{\mu}) - f(\mathbf{x}, \boldsymbol{\mu})|^2 d\mathbf{x} d\boldsymbol{\mu},$$

$$\partial\Omega = \{\varphi = 0\}$$

where u_{θ} is a neural network defined by

$$u_{\theta}(\mathbf{x}, \boldsymbol{\mu}) = \varphi(\mathbf{x}) w_{\theta}(\mathbf{x}, \boldsymbol{\mu}) + g(\mathbf{x}, \boldsymbol{\mu}),$$



with φ a level-set function, w_{θ} a NN and $g = 0$ the Dirichlet BC.

Thus, the Dirichlet BC is imposed exactly in the PINN : $u_{\theta} = g$ on $\partial\Omega$.

¹[Lagaris et al., 1998; Franck et al., 2024]

A1.2 – Finite Element Methods¹

Variational Problem :

Find $u_h \in V_h^0$ such that, $\forall v_h \in V_h^0, a(u_h, v_h) = l(v_h)$, (P_h)


with h the characteristic mesh size, a and l the bilinear and linear forms given by

$$a(u_h, v_h) = \frac{1}{\text{Pe}} \int_{\Omega} D \nabla u_h \cdot \nabla v_h + \int_{\Omega} R u_h v_h + \int_{\Omega} v_h C \cdot \nabla u_h, \quad l(v_h) = \int_{\Omega} f v_h,$$

and V_h^0 the finite element space defined by

$$V_h^0 = \left\{ v_h \in C^0(\Omega), \forall K \in \mathcal{T}_h, v_h|_K \in \mathbb{P}_k, v_h|_{\partial\Omega} = 0 \right\},$$

where \mathbb{P}_k is the space of polynomials of degree at most k .



Linear system : Let $(\phi_1, \dots, \phi_{N_h})$ a basis of V_h^0 .

Find $U \in \mathbb{R}^{N_h}$ such that $AU = b$

with

$$A = (a(\phi_i, \phi_j))_{1 \leq i, j \leq N_h} \quad \text{and} \quad b = (l(\phi_j))_{1 \leq j \leq N_h}.$$

$$\mathcal{T}_h = \{K_1, \dots, K_{N_e}\}$$

(N_e : number of elements)

¹[Ern and Guermond, 2004]

Appendix 2 : Adaptive mesh refinement

A2.1 – Dorfler marking strategy

TODO