

# Investigating the Impact of Syntactic Features for Semantic Dependency Parsing

---

Maximilian Pfundstein

January 10, 2020

Linköpings University

# Table of contents

1. Introduction

2. Overview

3. Objectives

4. Results

5. Outlook

# Introduction

---

- Syntactic and Semantic Dependency Parsing (SDP)
- Acyclic Graphs
- Research Question: To what extent does predicted syntax help for semantic dependency parsing?

- Theoretical baseline model by Dozat and Manning [Zeman et al., 2017]
- Implementation by Daniel Roxbo [Roxbo, 2019]
- Extension to learn syntactic graphs

Semantic Only	Gold Syntax	Predicted Syntax
87.40%	90.90%	89.30%

**Table 1:** Semantic  $F_1$  scores, test, out-of-domain.

# Introduction - Multitask Learning

- Multitask Learning
- Presumption by [Kurtz et al., 2019] shows that there might be an information overlap
- Other research shows, that multitask learning might help [Peng et al., 2017]

# Overview

---

- Allow to import the data from the `.conllu` format
- Increase the performance during the pre-processing by using caching to save computation time
- Implement multitask learning to simultaneously learn syntactic and semantic graphs and investigate the results



# Objectives

---

- Separate files for syntax (.cnpn) and semantic (.sdp)
- Combined file format CoNLL-U from [Buchholz and Marsi, 2006]

- Preprocessing is conducted every time the source code is being invoked
- Main functions:
  - `parse_conllu_labels`
  - `parse_conllu_sentences`
  - `parse_conllu_targets`

# Objectives | Multitask Learning





Figure 1: Flowchart, with red representing the feedback loop.

## Results


---

# Results | Performance Improvement




# Results | Multitask Learning

Syntactic  $F_1$  Scores




# Multitask Learning






# Multitask Learning

Syntactic  $F_1$  Scores (last 50 epochs without Syn Dev Multi)




# Results | Multitask Learning

Semantic  $F_1$  Scores



# Results | Multitask Learning



Setting	In-Domain				Out-Of-Domain	
	Syn Dev	Sem Dev	Syn Test	Sem Test	Syn Test	Sem Test
Sem Only	o	92.68%	o	92.39%	o	<b>87.50%</b>
Multitask Raw	94.54%	92.90%	-	-	90.92%	<b>87.80%</b>
Multitask Single	94.27%	92.54%	94.64%	92.60%	90.81%	87.41%
Multitask Multi	6.52%	92.64%	-	-	7.39%	87.71%
Multitask Loop	94.42%	93.01%	94.29%	92.51%	90.96%	<b>87.87%</b>

**Table 2:**  $F_1$  scores for the different setups.

# Outlook

---

- Presumption by [Kurtz et al., 2019] confirmed, at least for this data set
- Bidirectional Encoder Representations from Transformers (BERT)
- Combine BERT and multitask learning

## References

---



Buchholz, S. and Marsi, E. (2006).

**Conll-x shared task on multilingual dependency parsing.**

In *Proceedings of the Tenth Conference on Computational Natural Language Learning, CoNLL-X '06*, page 149–164, USA. Association for Computational Linguistics.



Kurtz, R., Roxbo, D., and Kuhlmann, M. (2019).

**Improving semantic dependency parsing with syntactic features.**

In *Proceedings of the First NLPL Workshop on Deep Learning for Natural Language Processing*, pages 12–21, Turku, Finland. Linköping University Electronic Press.





Peng, H., Thomson, S., and Smith, N. A. (2017).  
**Deep multitask learning for semantic dependency parsing.**

*In Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 2037–2048, Vancouver, Canada. Association for Computational Linguistics.



Roxbo, D. (2019).  
**A detailed analysis of semantic dependency parsing with deep neural networks.**

Master's thesis, Linköping University, Human-Centered systems.

## References iii



Zeman, D., Popel, M., Straka, M., Hajič, J., Nivre, J., Ginter, F., Luotolahti, J., Pyysalo, S., Petrov, S., Potthast, M., Tyers, F., Badmaeva, E., Gokirmak, M., Nedoluzhko, A., Cinková, S., Hajič jr., J., Hlaváčová, J., Kettnerová, V., Urešová, Z., Kanerva, J., Ojala, S., Missilä, A., Manning, C. D., Schuster, S., Reddy, S., Taji, D., Habash, N., Leung, H., de Marneffe, M.-C., Sanguinetti, M., Simi, M., Kanayama, H., de Paiva, V., Droганова, K., Martínez Alonso, H., Çöltekin, Ç., Sulubacak, U., Uszkoreit, H., Macketanz, V., Burchardt, A., Harris, K., Marheinecke, K., Rehm, G., Kayadelen, T., Attia, M., Elkahky, A., Yu, Z., Pitler, E., Lertpradit, S., Mandl, M., Kirchner, J., Alcalde, H. F., Strnadová, J., Banerjee, E., Manurung, R.,

Stella, A., Shimada, A., Kwak, S., Mendonça, G., Lando, T., Nitisaroj, R., and Li, J. (2017).

**CoNLL 2017 shared task: Multilingual parsing from raw text to universal dependencies.**

*In Proceedings of the CoNLL 2017 Shared Task: Multilingual Parsing from Raw Text to Universal Dependencies*, pages 1–19, Vancouver, Canada. Association for Computational Linguistics.