

Hands-on Lab: Get familiar with fork and pull requests



Estimated time needed: 30 mins

Objectives

After completing this lab, you will be able to:

1. Use git commands to manage upstream repositories
2. Create a personal access token
3. Fork existing repository using the UI
4. Clone forked repository in the lab environment
5. Create a new branch
6. Make changes locally
7. Add and commit to the local branch
8. Push changes to the forked repository
9. Create a pull request to the upstream repository

Pre-requisites

This lab is designed to run on Skills Network - Cloud IDE which runs on a Linux system in the cloud and already has git installed. If you intend to run this lab on your own system, please ensure you have git (on Linux or macOS) or GitBash (on Windows) installed.

Note: While the lab allows you to copy-paste the commands, the best way to learn is to type the command yourselves. The instructors highly recommend the same.

Exercise 1: Generate personal access token

The first step is to generate an access token from GitHub.com. Follow the lab named [Generate GitHub personal access token](#) and copy the access token to use as a password in the upcoming exercises.


03.ref01-Hands-on Lab-Generate GitHub personal access token

Exercise 2: Fork the repository

To fork a source repository, complete the following steps:

1. Log in to GitHub and go to this project's [sample source repository](#). This is the upstream repository for your project.
2. At the top right of the screen, click Fork and select your own GitHub account as the destination for the fork.

<https://github.com/ibm-developer-skills-network/gkpbt-css-circle> -----> <https://github.com/ismartio/mrnam-demogit>


 **ibm-developer-skills-network / gkpbt-css-circle** Public







generated from [ibm-developer-skills-network/coding-project-template](#)


Unwatch 2 Fork 1

[Code](#) [Issues](#) [Pull requests](#) [Actions](#) [Projects](#) [Wiki](#) [Security](#) [Insights](#) [Settings](#)

main 1 branch 0 tags Go to file Add file Code

 **upkarliddar** Automatically close PRs 729ceb2 2 days ago 5 commits






 .github/workflows	Automatically close PRs	2 days ago
 .gitignore	Initial commit	3 days ago
 LICENSE	Initial commit	3 days ago
 README.md	Update README.md	3 days ago
 circle.html	Create circle.html	3 days ago
 style.css	Create style.css	3 days ago

README.md 

Readme

About

css-circle

-  Readme
-  Apache-2.0 License
-  0 stars
-  2 watching
-  1 fork


Releases

No releases published
[Create a new release](#)

Packages



No packages published
[Publish your first package](#)

A copy of the source repository has now been added as one of your GitHub repositories. This is the origin repository.

 upkarliddler / gkpbt-css-circle Public


forked from ibm-developer-skills-network/gkpbt-css-circle







[Code](#) [Pull requests](#) [Actions](#) [Projects](#) [Wiki](#) [Security](#) [Insights](#) [Settings](#)


main  1 branch  0 tags

[Go to file](#) [Add file](#) [Code](#)

This branch is up to date with ibm-developer-skills-network:main. [Contribute](#) [Fetch upstream](#)

 **upkarliddler** Automatically close PRs 729ceb2 · 2 days ago 5 commits

 .github/workflows	Automatically close PRs	2 days ago
 .gitignore	Initial commit	3 days ago
 LICENSE	Initial commit	3 days ago
 README.md	Update README.md	3 days ago
 circle.html	Create circle.html	3 days ago
 style.css	Create style.css	3 days ago

README.md 

Readme

About

css-circle

[Readme](#)

[Apache-2.0 License](#)

0 stars

0 watching

1 fork

Releases

No releases published

[Create a new release](#)

Packages

No packages published

[Publish your first package](#)

Languages

HTML 69.9%

CSS 30

Exercise 3: Clone the forked repository

A clone is a local copy of a repository. Before you can clone the forked repository, you first need its HTTPS URL, which provides secure access to it.

To clone the forked repository, complete the following steps:

1. In your list of repositories, click the forked repository. On the repository's main page, click the **Code** button.
2. Click the clipboard icon to copy the URL. Make sure the HTTPS tab is active.

The screenshot shows a GitHub repository page for 'upkarliddier / gkpbt-css-circle'. The repository is public and forked from 'ibm-developer-skills-network/gkpbt-css-circle'. The main branch is 'main'. A 'Code' button is highlighted with a red box. A 'Clone' dropdown menu is open, showing 'HTTPS', 'SSH', and 'GitHub CLI' options. The 'HTTPS' option is highlighted with a red box. The URL 'https://github.com/upkarliddier/gkpbt-css-circle' is displayed. A 'Download ZIP' button is also visible. The repository contains files: '.github/workflows', '.gitignore', 'LICENSE', 'README.md', 'circle.html', and 'style.css'. The 'README.md' file is selected, showing its content. The right sidebar shows repository statistics: 0 stars, 0 watching, 1 fork, and 1 release.

upkarliddier / gkpbt-css-circle Public

forked from ibm-developer-skills-network/gkpbt-css-circle

Code Pull requests Actions Projects Wiki Security Insights Settings

main 1 branch 0 tags

This branch is up to date with ibm-developer-skills-network:main

upkarliddier Automatically close PRs

File	Commit	Time
.github/workflows	Automatically close PRs	3 days ago
.gitignore	Initial commit	3 days ago
LICENSE	Initial commit	3 days ago
README.md	Update README.md	3 days ago
circle.html	Create circle.html	3 days ago
style.css	Create style.css	3 days ago

Clone

HTTPS SSH GitHub CLI

https://github.com/upkarliddier/gkpbt-css-circle

Use Git or checkout with SVN using the web URL.

Download ZIP

README.md

Readme

About

css-circle

Readme

Apache-2.0 License

0 stars

0 watching

1 fork

Releases

No releases published

Create a new release

Packages

No packages published


Publish your first package

Languages

HTML 69.9%

See LAB install git in VS Code

3. Open the terminal in the lab environment by using the menu in the editor: Terminal > New Terminal.



4. Let's export the copied URL in an environment variable so it's available for us to use in the later steps, run the following command in terminal:

```
1. 1  
1. export ORIGIN=<your repository HTTPS URL> export ORIGIN=https://github.com/ismartio/mrnam-demogit.git
```

Copied!

Replace <your repository HTTPS URL> with the URL you copied in step 2.

5. Run the following command with the HTTPS URL you copied earlier:

```
1. 1  
1. git clone $ORIGIN git clone $ORIGIN
```

Copied!

```
Problems theia@theia-ulidder: /home/project X

theia@theia-ulidder:/home/project$ export ORIGIN=https://github.com/upkarlidder/gkpbt-css-circle.git
theia@theia-ulidder:/home/project$ git clone $ORIGIN

Cloning into 'gkpbt-css-circle'...
remote: Enumerating objects: 22, done.
remote: Counting objects: 100% (22/22), done.
remote: Compressing objects: 100% (17/17), done.
remote: Total 22 (delta 5), reused 7 (delta 1), pack-reused 0
Unpacking objects: 100% (22/22), done.
theia@theia-ulidder:/home/project$ ls -la ls -la


total 16
drwxrwsrwx 3 root  users 4096 Jan 18 16:41 
drwxrwxr-x 1 root  root  4096 Jan 10 21:57 ..
drwxr-sr-x 4 theia  users 4096 Jan 18 16:41 gkpbt-css-circle
```

The command clones the repository that is on GitHub into your current directory.


Exercise 4: Explore the cloned repo

To become familiar with the cloned repo, complete the following steps:

1. Click the Explorer icon as shown in the following image:




2. Click Project and expand the folder of the project you just cloned. You can open the files in the editor, on the right side, by clicking on the file name.



Exercise 5: Create the feature-circle-500 branch

We will now add a new feature to the source code. We will increase the circle's size to 500x500 pixels. Before we make this change, we will create a new branch.

1. Navigate to our repository using this command `cd gkpbt-css-circle` **cd mrnam-demogit**
2. Create a new branch using the `git checkout -b feature-circle-500` command. Notice that we used a single command instead of creating a branch and then checking it out. The `-b` flag creates the branch if it does not already exist. **git checkout -b feature-circle-500**
3. You can check that you are in the new branch by using the `git branch` command. **git branch**



Exercise 6: Make required code changes

1. Let's change the width and height to 500px each. Open the `style.css` file from the file explorer and change the code as follows:

```

1. 1
2. 2
3. 3
4. 4
5. 5
6. 6
7. 7
8. 8
1. .blue {
2.     background-color:blue
3. }
4. .circle{
5.     border-radius:50%;
6.     width:500px;
7.     height:500px;
8. }

```

width:500px;
height:500px;

Copied!

2. If you do a `git status` at this point, you will see a change is shown. This change is not staged at this point, but Git is aware of it.

1. 1
1. git status **git status**

Copied! Executed!


```

theia@theia-ulidder:/home/project/gkpbt-css-circle$ git status
On branch feature-circle-500
Changes not staged for commit:
  (use "git add <file>..." to update what will be committed)
  (use "git checkout -- <file>..." to discard changes in working directory)

        modified:   style.css

no changes added to commit (use "git add" and/or "git commit -a")

```

3. Optionally, you can use the `git diff` command to see the detailed changes:

1. 1

1. `git diff ./style.css` `git diff ./style.css`

Copied! Executed!

```

Problems theia@theia-ulidder: /home/project/gkpbt-css-circle X
theia@theia-ulidder:/home/project/gkpbt-css-circle$ git diff ./style.css
diff --git a/style.css b/style.css
index bla4e3b..2309246 100644
--- a/style.css
+++ b/style.css
@@ -3,6 +3,6 @@
 }
 .circle{
     border-radius:50%;
-    width:300px;
-    height:300px;
+    width:500px;
+    height: 500px;
 }

```

Notice the text in red was deleted and the text in green was added. Essentially, we changed the height and width from 300px to 500px each.

Note: To exit the `git diff` command, simply press the "Q" key. **Q**

Exercise 7: Add and commit your changes

A commit is Git's way of recording your file changes, similar to how you might save an edited document. To commit the change that you made in the previous exercise, you first need to add it to a staging area. Git will then take the staged snapshot of changes and commit them to the project. Remember, Git will never change files unless you explicitly ask it to.

To commit your new file, complete the following steps:

1. To move the changes from your working project directory to the staging area, type the following command in the Terminal window:

1. 1
1. `git add .` `git add .`
Copied!

The `git add` command has several options. The single `.` adds all untracked files in the current directory and subdirectories to the staging area. Alternatively, you can add the single file you created by using the `git add style.css` command. Finally, you can use `git add -A` to recursively add all files from the top level git folder.

2. If you check the status at this point, you will see the file has changed from Untracked to Changes to be committed:

```

Problems theia@theia-ulidder: /home/project/gkpbt-css-circle X
theia@theia-ulidder:/home/project/gkpbt-css-circle$ git add .
theia@theia-ulidder:/home/project/gkpbt-css-circle$ git status
On branch feature-circle-500
Changes to be committed:
  (use "git reset HEAD <file>..." to unstage)

        modified:   style.css

```

`git status`

3. To commit the new file to the local repository, you need to first tell git who you are. Type in the following commands to set your email and username. The email should be the same as your GitHub email.

Set your email:

1. 1
1. `git config --global user.email "email@example.com"` `git config --global user.email "giangdayit@gmail.com"`
Copied!

Set your name:

```
1. 1
1. git config --global user.name "Your Name" git config --global user.name "MR. NAM"
```

Copied!

```
Problems theia@theia-ulidder: /home/project/gkpbt-css-circle X
theia@theia-ulidder: /home/project/gkpbt-css-circle$ git config --global user.email "email.example.com"
theia@theia-ulidder: /home/project/gkpbt-css-circle$ git config --global user.name "Upkar Lidder"
```

4. Type the following command in the Terminal window to commit the file.

Note: It's always a good practice to add a description for the commit so you can remember what the change was if you have to refer to it later.

- **-m flag:** It is used in Git commit commands to specify the commit message directly in the command line, allowing you to provide a brief description of the changes you are committing.

```
1. 1
1. git commit -m "Changing the height and the width of the circle" git commit -m "Changing the height and the width of the circle"
```

Copied!

```
Problems theia@theia-ulidder: /home/project/gkpbt-css-circle X
theia@theia-ulidder: /home/project/gkpbt-css-circle$ git commit -m "Changing the height and the width of the circle"
[feature-circle-500 4a5a882] Changing the height and the width of the circle
1 file changed, 2 insertions(+), 2 deletions(-)
theia@theia-ulidder: /home/project/gkpbt-css-circle$ git status
On branch feature-circle-500
nothing to commit, working tree clean
```

As you can see, `git status` now says there is nothing to commit and the working tree is clean. The new file is now ready to be pushed from your local system to origin on GitHub.

`git status`

Exercise 8: Merge your branch back into main branch

If you are happy with your changes in the `feature-circle-500` branch, you can now merge it back into your local `main` branch by following these steps:

1. Confirm that you are currently in the `feature-circle-500` branch.

```
Problems theia@theia-ulidder: /home/project/gkpbt-css-circle X
theia@theia-ulidder: /home/project/gkpbt-css-circle$ git branch
* feature-circle-500
main
```

`git branch`

2. Check out the `main` branch

```
1. 1
1. git checkout main git checkout main
```

Copied!

If you run `git branch` again, you should see the `*` against the `main` branch.

```
Problems theia@theia-ulidder: /home/project/gkpbt-css-circle X
theia@theia-ulidder: /home/project/gkpbt-css-circle$ git checkout main
Switched to branch 'main'
Your branch is up to date with 'origin/main'.
theia@theia-ulidder: /home/project/gkpbt-css-circle$ git branch
feature-circle-500
* main
```

`git branch`

3. Merge the `feature-circle-500` branch into `main`.

```
1. 1
1. git merge feature-circle-500
```

Copied!

```
theia@theia-ulidder:/home/project/gkpbt-css-circle$ git merge feature-circle-500
Updating 729ceb2..4a5a882
Fast-forward
 style.css | 4 ++--
 1 file changed, 2 insertions(+), 2 deletions(-)
```

4. Confirm the change was merged by using the `git log` command. We are using `--oneline` flag to display logs more concisely. [git log --oneline](#)

```
theia@theia-ulidder:/home/project/gkpbt-css-circle$ git log --oneline
4a5a882 (HEAD -> main, origin/feature-circle-500, feature-circle-500) Changing the height and the width
729ceb2 (origin/main, origin/HEAD) Automatically close PRs
0169944 Update README.md
8f09fd1 Create style.css
2d31fb1 Create circle.html
11bec50 Initial commit
```

Note: To exit the `git log` command, simply press the "Q" key. This action will close the log view and bring you back to the command prompt.

Exercise 9: Delete the feature-circle-500 branch

Since you are done making the change, let's delete the `feature-circle-500` branch by following these steps:

1. Ensure you are on the `main` branch. If not, check it out first

```
1. 1
1. git checkout main git checkout main
```

Copied!

2. Delete the `feature-circle-500` branch, the common flag used is `-d` (lowercase), which stands for "delete"

```
1. 1
1. git branch -d feature-circle-500 git branch -d feature-circle-500
```

Copied!

3. You can confirm the branch was deleted by listing all branches

```
1. 1
1. git branch git branch
```

Copied!

```
theia@theia-ulidder:/home/project/gkpbt-css-circle$ git branch -d feature-circle-500
Deleted branch feature-circle-500 (was 4a5a882).
theia@theia-ulidder:/home/project/gkpbt-css-circle$ git branch
* main
```

Exercise 10: Push your changes to origin

This push will synchronize all the changes you made on your local system with your fork repository on GitHub.

To push your update to GitHub, complete the following steps:

1. In the Terminal window, run the following command:


```
1. 1
1. git push origin main git push origin main
```

Copied!


Once you submit that command, Cloud IDE will display a dialog in the lower right corner, requesting permission to sign in using GitHub. Click "Allow"

Note : If you don't see the dialog box below, you will be asked to enter your GitHub username and password in the terminal. Your PAT (Personal Access Token) will be hidden when you type or paste it in the terminal for security reasons. So, make sure you enter or paste it correctly before hitting 'Enter'.






Note: If you come across a message like the one in the screenshot below, which says "Sign in failed: Error: Invalid scheme 'theia'", please ignore this error.




Subsequently, another dialog will appear at the top of the screen, prompting you to enter your username and password. The username is your email you used to sign into GitHub and the password is the Personal access token you created in **Exercise 1 - This is not your GitHub password**.



If your username and password were accepted, you should see the changes pushed to GitHub in the terminal.

```
Problems theia@theia-ulidder: /home/project/gkpbt-css-circle X
theia@theia-ulidder:/home/project/gkpbt-css-circle$ git push origin main
Counting objects: 3, done.
Delta compression using up to 16 threads.
Compressing objects: 100% (3/3), done.
Writing objects: 100% (3/3), 379 bytes | 379.00 KiB/s, done.
Total 3 (delta 1), reused 0 (delta 0)
remote: Resolving deltas: 100% (1/1), completed with 1 local object.
To https://github.com/upkarliddler/gkpbt-css-circle.git
729ceb2..4a5a882 main -> main
```

2. Go to the fork repository in your GitHub account and verify that the local changes have now been added to the main branch.



upkarliddler / gkpbt-css-circle Public

forked from ibm-developer-skills-network/gkpbt-css-circle

<> Code Pull requests Actions Projects Wiki Security Insights Settings

main gkpbt-css-circle / style.css

Upkar Liddler Changing the height and the width of the circle ... Latest commit

1 contributor

8 lines (8 sloc) | 102 Bytes

```
1 .blue {
2     background-color:blue
3 }
4 .circle{
5     border-radius:50%;
6     width:500px;
7     height: 500px;
8 }
```

Exercise 11: Create a pull request

The final step is to request the original project pull in the changes you've made to your fork. To merge your changes to the original repository, you need to create a pull request.

To create a pull request, complete the following steps:

1. Ensure you are on the **Code** tab. Click **Contribute** and then **Open pull request**.

The screenshot shows a GitHub repository page for 'upkarliddler / gkpbt-css-circle'. The repository is public and was forked from 'ibm-developer-skills-network/gkpbt-css-circle'. The main navigation bar includes links for Code, Pull requests, Actions, Projects, Wiki, Security, Insights, and Settings. The repository is currently on the 'main' branch, which is 1 commit ahead of the upstream repository. A dropdown menu for the 'main' branch shows '1 branch' and '0 tags'. A 'Contribute' button is visible, which has opened a modal dialog. The modal dialog states 'This branch is 1 commit ahead of ibm-developer-skills-network:main.' and provides an 'Open pull request' button. The repository's commit history is shown, listing files like '.github/workflows', '.gitignore', 'LICENSE', 'README.md', 'circle.html', and 'style.css' with their respective commit messages and timestamps. The README section is also visible, showing the title 'Readme'.

upkarliddler / gkpbt-css-circle Public

forked from ibm-developer-skills-network/gkpbt-css-circle

<> Code Pull requests Actions Projects Wiki Security Insights Settings

main 1 branch 0 tags

Go to file Add file Code

This branch is 1 commit ahead of ibm-developer-skills-network:main.

Contribute Fetch upstream

This branch is 1 commit ahead of ibm-developer-skills-network:main.
Open a pull request to contribute your changes upstream.

Open pull request


Upkar Liddler Changing the height and the w hour ago 6 commits

.github/workflows	Auto	2 days ago
.gitignore	Initia	3 days ago
LICENSE	Initial commit	3 days ago
README.md	Update README.md	3 days ago
circle.html	Create circle.html	3 days ago
style.css	Changing the height and the width of the circle	1 hour ago

README.md

Readme

2. In the "Comparing changes" panel, GitHub shows you that it is comparing the main branch of your fork to that of the original repository, and that your changes can be merged. Click the **Create pull request** button.

 **ibm-developer-skills-network / gkpbt-css-circle** Public

generated from [ibm-developer-skills-network/coding-project-template](#)

< Code

Issues

Pull requests

Actions

Projects

Wiki


Security

Insights

Settings

Comparing changes

Choose two branches to see what's changed or to start a new pull request. If you need to, you can also [compare across forks](#).

 base repository: [ibm-developer-skills-network/gk...](#) base: [main](#)

←

head repository: [upkarliddar/gkpbt-css-circle](#) compare: [main](#)

✓ **Able to merge.** These branches can be automatically merged.

Discuss and review the changes in this comparison with others. [Learn about pull requests](#)

1 commit

1 file changed

Commits on Jan 17, 2022

Changing the height and the width of the circle ...
Upkar Liddar committed 1 hour ago

Showing **1 changed file** with **2 additions** and **2 deletions**.

style.css

3 }
4 .circle{
5 border-radius:50%;
6 - width:300px;
7 - height:300px;
8 }

3 }
4 .circle{
5 border-radius:50%;
6 + width:500px;
7 + height: 500px;
8 }

3. You are taken to the **Open pull request** screen. Notice that your commit message appears as the title of the pull request. Click the **Create pull request** button.

about:blank

14/17

**Add a title**

Changing the height and the width of the circle

Add a description

Write

Preview

H B I

Add your description here...

Markdown is supported

Paste, drop, or click to add files

☒ Allow edits by maintainers

Create pull request

Note: For the purposes of this lab, your pull request will be processed and closed automatically. **Copy the URL of this pull request as you will need to submit it for peer review.**

You should see the following message in your pull request after a few minutes:

ibm-developer-skills-network / gkpbt-css-circle Public

generated from ibm-developer-skills-network/coding-project-template

<> Code Issues Pull requests 1 Actions Projects Wiki Security Insights Settings

Changing the height and the width of the circle #2

Closed upkarliddar wants to merge 1 commit into `ibm-developer-skills-network:main` from `upkarliddar:main`

Conversation 0 Commits 1 Checks 0 Files changed 1

upkarliddar commented 14 seconds ago Collaborator

Signed-off-by: Upkar Liddar <email.example.com>

Changing the height and the width of the circle 4a5a882

github-actions bot commented now

Congratulations! You have completed the lab. Closing for maintainence purpose.

github-actions bot closed this now

Pull request closed

If you wish, you can delete this fork of `ibm-developer-skills-network/gkpbt-css-circle` in the [settings](#).

Write Preview

Leave a comment

Attach files by dragging & dropping, selecting or pasting them.

Record a Loom Reopen pull request Comment

Reviewers
No reviews

Assignees
No one—assign yo

Labels
None yet

Projects
None yet

Milestone
No milestone

Linked issues
Successfully mergi
issues.
None yet

Notifications
You're receiving no
this repository.

1 participant

Exercise 12: Practice on your own

1. Create a new branch called `feature-add-color`.

► Click here for the solution

2. Make `feature-add-color` the active branch.

► Click here for the solution

3. Add another css rule as follows:

```
1. 1
2. 2
3. 3
1. .red {
```

```
2. background-color:red
3. }
```

Copied!

- 4. Stage this change.
 - ▶ Click here for the solution
- 5. Commit the changes in your `feature-add-color`.
 - ▶ Click here for the solution
- 6. Merge the changes in `feature-add-color` into `main`.
 - ▶ Click here for the solution
- 7. Delete the `feature-add-color` branch.
 - ▶ Click here for the solution
- 8. Create a new pull request for this feature in the upstream repository using the GitHub UI.

Summary

In this lab, you have learned how to fork an upstream repository into your own account and then clone it locally in the lab environment. You then learned how to synchronize changes in your local repository with remote GitHub repositories using pull requests.

Author(s)

Upkar Lidder

Other Contributor(s)

Richard Ye

Changelog

Date	Version	Changed by	Change Description
2022-01-17	1.0	Upkar Lidder	Initial version created
2022-01-27	1.1	Richard Ye	Corrected and added instructions
2023-04-03	1.2	Lavanya Rajalingam	Updated new SN Logo
2023-10-18	1.3	Rajashree Patil	Corrected and added instructions
2023-12-22	1.3	Ritika Joshi	Updates based on Beta feedback