

Product Specifications

Item	CFD-X02-A
Electrical Specifications	
Electrical safety class	Class III
Power supply	5 V DC
Current consumption (max)	0.5 A
Power consumption (max)	2.5 W
Signal Specifications	
Input Connections	1x SMA
Input polarity	positive or negative
Input pulse width	>700 ps
Rise time	>350 ps
Minimum input pulse height (abs)	100 mV
Maximum input pulse height (abs)	5 V limited
Output pulse width	from 5 ns to 250 ns
Output connections and type	2x SMA: 2.5 V digital LVTTTL at 50 Ω 2x USB Type-C: LVDS
Timing jitter	<15 ps
Time walk	± 100 ps ^a
Maximum operating frequency	100 MHz
Length of delay line	adjustable based on external cable length (30 cm ~1ns)
Impedance	50 Ω
Physical Specifications	
Dimensions (L x W x H)	87 mm x 87 mm x 40 mm
Weight	225 g
Protection rating	IP40
Environmental Specifications	
Operating temperature	0 °C to +40°C
Storage temperature	-20 °C to +70°C
Humidity	80% non-condensing

^a Measurement conditions: input pulse amplitude = -100 mV to -4.5 V, fall time = 1 ns, pulse width = 2.5 ns, CFD delay = 1 ns