

Product Specifications

Item	PLD-XXX-SM-FC-30-U
Electrical Specifications	
Electrical safety class	Class III
Power supply	USB Type-C, 5 V DC
Maximum current consumption	3 A
Maximum power consumption	15 W
Optical and Laser Specifications	
Laser type	Solid-state diode laser
Available wavelengths in nm	405 445 488 520 635 808 850
Wavelength bandwidth	±10 nm
Operating modes	CW or pulsed
Maximum output power	1.4 mW
Power stability	<1%
Pulse repetition frequency	5 MHz, 10 MHz, 20 MHz, 40 MHz, 80 MHz
Pulse duration in ps	50 55 80 80 80 90 90
Output fiber core diameter	≥ 4 μm
M ² value	1.06 ¹
Polarization	Random
Optical output	FC/PC fiber connector
Signal Specifications	
Manual command mode	Selectable repetition frequency
External synchronization input	TTL, 2.5 V, 50 Ω
Synchronization outputs	TTL, 2.5 V, 50 Ω
Physical Specifications	
Dimensions (L x W x H)	135 mm x 110 mm x 50 mm
Weight	550 g
Environmental Specifications	
Operating temperature	10°C to +40°C
Storage temperature	-20°C to +70°C
Relative humidity	80% non-condensing

¹using 4 μm core fiber