

- Home
- SQL Worksheet
- My Session
- Schema
- Design
- My Scripts
- Code Library

SQL Worksheet

Clear

View Session

Reset

Save

Run

```
1 CREATE TABLE Bank (B# varchar(10) PRIMARY KEY, Name varchar(10), City varchar(10));
2 CREATE TABLE Customer (C# varchar(10) PRIMARY KEY, Name varchar(10), Age int, City varchar(10));
3 CREATE TABLE Account (C# varchar(10), B# varchar(10), Balance int, FOREIGN KEY (B#) REFERENCES Bank(B#), FOREIGN KEY (C#) REFERENCES Customer(C#), PRIMARY KEY(C#, B#));
4 INSERT INTO Bank VALUES ('B1', 'England', 'London');
5 INSERT INTO Bank VALUES ('B2', 'America', 'New York');
6 INSERT INTO Bank VALUES ('B3', 'Royal', 'Toronto');
7 INSERT INTO Bank VALUES ('B4', 'France', 'Paris');
8 INSERT INTO Customer VALUES ('C1', 'Adams', 20, 'London');
9 INSERT INTO Customer VALUES ('C2', 'Blake', 30, 'Paris');
10 INSERT INTO Customer VALUES ('C3', 'Clark', 25, 'Paris');
11 INSERT INTO Customer VALUES ('C4', 'Jones', 20, 'London');
12 INSERT INTO Customer VALUES ('C5', 'Smith', 30, 'Toronto');
13 INSERT INTO Account VALUES ('C1', 'B1', 1000);
14 INSERT INTO Account VALUES ('C1', 'B2', 2000);
15 INSERT INTO Account VALUES ('C1', 'B3', 3000);
16 INSERT INTO Account VALUES ('C1', 'B4', 4000);
17 INSERT INTO Account VALUES ('C2', 'B1', 2000);
18 INSERT INTO Account VALUES ('C2', 'B2', 3000);
19 INSERT INTO Account VALUES ('C2', 'B3', 4000);
20 INSERT INTO Account VALUES ('C3', 'B1', 3000);
21 INSERT INTO Account VALUES ('C3', 'B2', 4000);
22 INSERT INTO Account VALUES ('C4', 'B1', 4000);
23 INSERT INTO Account VALUES ('C4', 'B2', 5000);
```

Table created.

Table created.

Table created.








1 row(s) inserted.

1 row(s) inserted.

1 row(s) inserted.

1 row(s) inserted.

1 row(s) inserted.

-  Home
-  SQL Worksheet
-  My Session ▼
-  Schema
-  Design
-  My Scripts
-  Code Library

SQL Worksheet

 Clear View Session Reset Save Run






```
1 select C.Name from Customer C
2 where exists
3 (select * from Account A
4 where C.C# = A.C#);
```

NAME
Adams
Blake
Clark
Jones

[Download CSV](#)

4 rows selected.

SQL Worksheet

 Clear  View Session  Reset  Save  Run

```
1 select C.Name, B.Name from Customer C, Bank B
2 where not exists
3 (select * from Account A
4 where C.C# = A.C# and A.B# = B.B#);
```

NAME	NAME
Smith	England
Smith	America
Clark	Royal
Jones	Royal
Smith	Royal
Blake	France
Clark	France
Jones	France
Smith	France

[Download CSV](#)
9 rows selected.



Home



SQL Worksheet



My Session ▼



Schema



Design



My Scripts



Code Library

SQL Worksheet

Clear

View Session

Reset

Save

Run

```
1 select C.Name from Customer C
2 where not exists
3 (select * from Account A
4 where C.C# = A.C#);
```

NAME

Smith

[Download CSV](#)

- Home
- SQL Worksheet
- My Session
- Schema
- Design
- My Scripts
- Code Library

SQL Worksheet

Clear View Session Reset Save Run

```
1 select B.Name from Bank B
2 where exists
3 (select * from Account A, Customer C
4  where C.Name = 'Blake' and C.C# = A.C# and A.B# = B.B#)
5 union
6 select B.Name from Bank B
7 where exists
8 (select * from Account A, Customer C
9  where C.Name = 'Clark' and C.C# = A.C# and A.B# = B.B#);
```

NAME
America
England
Royal

Download CSV
3 rows selected.



Home



SQL Worksheet



My Session ▼



Schema



Design



My Scripts



Code Library

SQL Worksheet

Clear

View Session

Reset

Save

Run

```
1 select C.Name from Customer C
2 where not exists
3 (select * from Bank B
4  where not exists
5      (select * from Account A
6       where C.C# = A.C# and A.B# = B.B#));
```

NAME

Adams

[Download CSV](#)

SQL Worksheet

 Clear

 View Session

 Reset

 Save

Run
 

1

select C.Name from Customer C where not exists

2

(select * from Bank B where

3

(B.Name NOT IN ('Royal','France')

4

OR EXISTS

5

(select * from Account A where C.C# = A.C# and A.B# = B.B#))

6

and

7

(B.Name IN ('Royal', 'France') or not exists

8

(select * from Account A where C.C# = A.C# and A.B# = B.B#)))

NAME

Clark

Jones

[Download CSV](#)

2 rows selected.

ORACLE® Live SQL

Part 1: NUMBER 7

Feedback

Help

Profile

Account

Home

SQL Worksheet

My Session

Schema

Design

My Scripts

Code Library

SQL Worksheet

Clear

View Session

Reset

Save

Run

1

2

3

4

5

select C3.Name from Customer C3, Customer C

where C3.Name != 'Clark' and C.Name = 'Clark' and exists

(select * from Bank B, Account A1, Account A

where C.C# = A.C# and A.B# = B.B#

and C3.C# = A1.C# and A1.B# = B.B#);

NAME








Adams

Blake

Jones

Download CSV

3 rows selected.

-  Home
-  SQL Worksheet
-  My Session ▼
-  Schema
-  Design
-  My Scripts
-  Code Library

SQL Worksheet

 Clear  View Session  Reset  Save  Run

```
1 select C3.Name from Customer C3, Customer C
2 where C3.Name != 'Clark' and C.Name = 'Clark' and NOT exists
3     (select * FROM Bank B
4       WHERE EXISTS
5         (SELECT * FROM Account A
6          where C.C# = A.C# and A.B# = B.B#)
7       and not exists
8         (select * from Account A1, Account A
9          where C.C# = A.C# and A.B# = B.B#
10         and C3.C# = A1.C# and A1.B# = B.B#));
```

NAME
Adams
Blake
Jones

[Download CSV](#)
3 rows selected.



Home



SQL Worksheet



My Session ▼



Schema



Design



My Scripts



Code Library

SQL Worksheet

Clear

View Session

Reset

Save

Run

```
1 select distinct C.Name
2 from Customer C, Account A1, Account A2
3 where C.C# = A1.C#
4 and C.C# = A2.C#
5 and A1.B# !=A2.B#;
```

NAME

Adams

Blake

Clark

Jones

[Download CSV](#)

4 rows selected.

4 rows selected.

SQL Worksheet

```

1 select *
2 from Customer FULL OUTER JOIN Account USING (C#)
3 FULL OUTER JOIN Bank USING(B#);
4 union
5 select C.Name
6 from Customer C, Account A1 where C.C# = A1.C#
7 group by C.Name Having count(A1.B#)=1;
8
    
```

B#	C#	NAME	AGE	CITY	BALANCE	NAME	CITY
B1	C1	Adams	20	London	1000	England	London
B2	C1	Adams	20	London	2000	America	New York
B3	C1	Adams	20	London	3000	Royal	Toronto
B4	C1	Adams	20	London	4000	France	Paris
B1	C2	Blake	30	Paris	2000	England	London
B2	C2	Blake	30	Paris	3000	America	New York
B3	C2	Blake	30	Paris	4000	Royal	Toronto
B1	C3	Clark	25	Paris	3000	England	London
B2	C3	Clark	25	Paris	4000	America	New York
B1	C4	Jones	20	London	4000	England	London
B2	C4	Jones	20	London	5000	America	New York
-	C5	Smith	30	Toronto	-	-	-

ORACLE®

Live SQL

Part 1: NUMBER 12

Feedback

Help

samueldiamantstein@gmail.carleton.ca

Home

SQL Worksheet

My Session

Schema

Design

My Scripts

Code Library

SQL Worksheet

Clear

View Session

Reset

Save

Run

1select Name, SUM(Balance)

2from Customer FULL OUTER JOIN Account USING (C#)

3group by C#, Name;

NAME	SUM(BALANCE)
Clark	7000
Adams	10000
Blake	9000
Jones	9000
Smith	-

Download CSV

5 rows selected.