

ComplexGitSync 0002.29– User Guide

Nicolas Flipó

September 3, 2026

Contents

1	User Guide	2
2	CLI Overview	2
3	Lifecycle Contract	2
4	Commands	3
4.1	initialise	3
4.2	bootstrap	4
4.3	discover	4
4.4	configure	5
4.5	create-cgs	5
4.6	clean-init	5
4.7	purge	6
4.8	pull	6
4.9	pull-force	6
4.10	clone	7
4.11	checkout	7
4.12	add	7
4.13	rm	7
4.14	commit	7
4.15	push	8
4.16	freeze-release	8
4.17	freeze	8
4.18	import-submodules	9
4.19	verify	10
4.20	launch-release	10
4.21	view-tree	10
4.22	status	11
5	Document Formats	11
5.1	Local Authoring Spec (.cgs)	11
5.2	Repository Placement and Nested Discovery	13
5.3	Git Tree State Snapshot (.gts)	13
5.4	Local Git Register and Sync Ledger (.lgr)	14

6	Worked Examples: From CGSi11 to cawaqsviz	14
6.1	Level 1 — CGSi11: the minimal synthetic topology	15
6.2	Level 2 — cawaqs: the same minimal style, at scale	16
6.3	Level 3 — cawaqsviz: three ways to the same .cgs	16
6.3.1	3a — Write it by hand	16
6.3.2	3b — Derive it with <code>discover</code> (autodiscover mode)	17
6.3.3	3c — Migrate it with <code>import-submodules</code>	17
6.3.4	A shared caveat across all three	18
7	Configuration and Environment	18
8	Error Reference	18
9	Troubleshooting	18

1 User Guide

This chapter is the authoritative reference for every user-facing command, configuration option, document format, and error condition exposed by `ComplexGitSync`.

2 CLI Overview

The single entry-point is the `cgitsync` command.

cgitsync is a Pixi task, not a globally installed executable. This project is developed and run exclusively through Pixi (`pixi install` once, per checkout) — there is no `pip install` that puts a bare `cgitsync` on `$PATH`. Every invocation shown in this chapter as `pixi run cgitsync ...` must be typed exactly that way; a bare `cgitsync ...` will not be found by the shell.

```
$ pixi run cgitsync <command> [options]
```

Running `cgitsync` without a command prints a help summary and exits with code 0.

`ComplexGitSync` stores no credentials of its own and has no private-repository authentication story: every git operation — `clone`, `pull`, `push`, and the remote lookups behind `checkout`’s branch/tag fallback — runs against whatever the ambient environment already has cached (`ssh-agent`, an HTTPS credential helper, a stored personal-access-token). When that ambient credential is missing or stale, the operation fails immediately with a normal, catchable error rather than sitting silently on a terminal or GUI credential prompt that will never arrive — every git subprocess `ComplexGitSync` runs sets `GIT_TERMINAL_PROMPT=0` and a no-op `GIT_ASKPASS` for exactly this reason. Fix the ambient credential (switch the remote to `ssh`, refresh the token) and re-run the command; nothing needs to be undone first.

3 Lifecycle Contract

This guide follows the simplified canonical lifecycle:

1. `initialise(.cgs)` → clone all repos → **READY** (*new project*)
`initialise(.gts)` → restore from snapshot → **READY** (*existing project*)
2. `pull(.cgs|.gts)` → resync an existing tree
3. `checkout(.gts)` / `add` / `commit` / `push` / `tag` → git operations on the tree

4. **freeze** → emit the next **.gts** id and update **<Project_name>.lgr**

The project-local **.lgr** register and sync ledger are both active (T24, T32). Every synchronisation operation is automatically recorded as an immutable DAG event in the **[[ledger]]** section of the **.lgr** file.

4 Commands

The CLI exposes three command groups once a **GitTree** is **READY**. The minimalist level is **initialise**, **bootstrap**, **clean-init**, **freeze-release**, **freeze-release-force**, **status**, **view-tree**, and **launch-release**. The expert level exposes the individual operations: **branch**, **checkout**, **purge**, **validate**, **clone**, **pull**, **pull-force**, **add**, **commit**, **push**, **tag**, **freeze**, **import-submodules**, and **verify**. The configuration level, **discover**, **configure** and **create-cgs**, authors a **.cgs** specification without requiring existing state. Redundant inspection aliases such as **print**, **view-operation**, and **validate-topology** are not part of the public CLI surface.

4.1 initialise

```
$ pixi run cgitsync initialise <spec.cgs> [--output-path DIR] [--commit-  
gitignore]  
    [--force-gitignore-sync] [--git-user-name NAME] [--git-user-email  
    EMAIL]  
    [--force-protocol {ssh,https}]  
$ pixi run cgitsync initialise <snapshot.gts>  
$ pixi run cgitsync initialise --project NAME --repo PROVIDER:OWNER/REPO  
    [--repo ...] [--output-path DIR]
```

Unified initialisation entry point. Dispatches on file extension:

- **.cgs** source (clone mode): clones the full repository tree. The optional **-output-path** controls **CGSPATH**; **CGSHOME** is derived as **CGSPATH/<project-name>**. When omitted, **CGSPATH** defaults to **../...** On success, ends in **READY**. If clone setup fails because stale generated state is still present, the CLI prints **Try clean-init method**.
- **.gts** source (restore mode): loads a saved snapshot directly. On success, ends in the lifecycle state recorded in the snapshot.
- Direct CLI authoring: requires **-project** and at least one repeatable **-repo**. It is mutually exclusive with a source file. The CLI collects values only and calls **ComplexGitSyncClient.configure()**; that reusable Python API delegates parsing, normalization, and validation to **cgs_format.py** and produces the same canonical **CgsDocument** as an equivalent **.cgs** file.

All initialization paths end in a **READY** tree or fail explicitly.

Before a **.cgs** source is confirmed ready, every repository with children (root, or any nested repository that itself has further nested children) is safely pulled parent-first and has its **.gitignore** updated with the relative path of each immediate child — nested repositories are plain independent clones rather than gitlinks, so without this a parent's **git status/git add** would otherwise see a child's working tree as ordinary untracked content. This is logged as the **GT-GITIGNORE** phase, after **GT-CLONE**. If the safe pull for one of these repositories fails, **initialise** raises immediately and nothing is written; pass **-force-gitignore-sync** to instead fall back to a pull-force recovery for that one repository (never a force-push). By default nothing is staged, committed, or pushed by this step — it only writes the file and prints what changed. Pass **-commit-gitignore** to explicitly approve staging (**.gitignore** alone), committing (with a message listing exactly which children were added), and pushing each changed repository. The

commit identity defaults to local git config; `-git-user-name/-git-user-email` override it and persist the override to `CGSHOME/.cgitsync/master.toml` via `MasterConfig`, so later invocations on the same workspace pick it up without repeating the flags.

The root's own `.gitignore` additionally always gains `.cgitsync/` (the generated runtime-state directory — snapshots, register, run logs, never part of the `.cgs/.gts` project spec) and its `<project-name>.lgr` register file, whether or not the tree has any nested repositories at all — that state is written under the root regardless of tree shape, so it is excluded the same idempotent way, via the same underlying write `sync_gitignore()` already uses for child mount points.

`-force-protocol {ssh,https}` is an expert option, typically used systematically in CI rather than for everyday development. It overrides `access_protocol` in memory for every repository this run clones — including ones discovered later from a nested `.cgs` living in a different, separately-cloned repository — so no `.cgs` file is ever read differently or written to. Forcing `https` is the usual CI case: it removes the dependency on an SSH key or agent being present on the runner, a dependency that otherwise differs between a `push` run and a `pull_request` run (GitHub Actions withholds repository secrets from a pull request opened from a fork). Omitted (the default), each repository follows whatever protocol its own `.cgs` entry declares, exactly as without the flag.

4.2 bootstrap

```
$ pixi run cgitsync bootstrap <spec.cgs> <project_name> [--cgs-path DIR]
  [--force-protocol {ssh,https}]
```

Clones the full repository tree from a `.cgs` source into an isolated `CGSHOME`, for running `cgitsync` from its own standalone clone rather than nested inside the project tree it manages — one `ComplexGitSync` clone reused across many projects. It delegates to the same `ComplexGitSyncClient.clone_cgs` pipeline as `clone` below, and so shares its branch-fallback and nested-discovery behaviour, but differs from both `clone` and `initialise` in two ways:

- `project_name` is a required positional argument, not inferred from the `.cgs` document. It always forms the final path segment of `CGSHOME`, regardless of the specification's own project name.
- `CGSPATH` does not default to `../..` relative to the current directory (that default assumes `ComplexGitSync` is cloned inside the tree it manages — the nested-mode case `initialise` is for). When `-cgs-path` is omitted, `CGSPATH` instead defaults to a fresh `$HOME/.cgs/CGS<timestamp>/` directory, created automatically if it does not exist, so a bootstrapped project can never land inside `ComplexGitSync`'s own clone.

`-force-protocol {ssh,https}` behaves exactly as described under `initialise` above, applying here to every repository the run clones — including the root, which `bootstrap` (unlike `initialise`) also clones from scratch rather than assuming already checked out.

4.3 discover

```
$ pixi run cgitsync discover [ROOT] [--write FILE] [--max-depth N]
```

Scans `ROOT` (default: the current directory) for git repositories and drafts a `.cgs` from what is checked out, through the `ComplexGitSyncClient.discover_repos()` facade. This is the entry point for adopting a project that exists on disk but has no `.cgs` describing it yet.

The command is a pure read of the filesystem and of each repository's git config: nothing is cloned, fetched, staged, or modified, and no network call is made. Without `-write` it only prints

what it found, matching the “report first, write only when asked” posture of `-commit-gitignore` and `import-submodules -apply`.

The walk descends up to `-max-depth` levels (default 5; `ROOT` itself is depth 0), treating every directory that contains a `.git` entry as a repository. It never descends *into* a `.git` directory: for a submodule the real git directory lives at `<parent>/<.git/modules/<name>` while the child’s own `.git` is a file, so walking into it would report the same repository twice.

For each repository, `origin`’s URL is read and converted to the canonical `provider:owner/repository` shorthand through the existing `parse_repo_id()` grammar — this command adds no second parser. `relative_path` is taken straight from the walk rather than from a repository name, so a child mounted at `external/Thing` is recorded there and not at `Thing`. `nested_config` is left unset on every entry: the default `auto` already resolves cleanly whether or not a repository carries its own `*.cgs`.

Repositories with no `origin`, or whose remote URL does not resolve to a registered provider, are reported as warnings and left out of the draft. They are never guessed at: a draft that silently invented an address would be worse than one that states what it could not determine. Always review the generated file, then `validate` it.

Only what is *checked out at scan time* can be found. A repository cloned without `-recurse-submodules` leaves its submodule paths as empty directories, and those are correctly not reported; recovering them from git metadata instead is `import-submodules`’ job.

4.4 configure

```
$ pixi run cgitssync configure [--output FILE]
```

Interactively prompts for a project name, default branch, and one or more repositories (provider, owner, name, and per-repository overrides), then writes the resulting `.cgs` file through the same offline `ComplexGitSyncClient.configure()` facade used by `initialise -project/-repo` and `create-cgs`. The provider prompt accepts `github`, `gitlab`, `codeberg`, or `custom`; `custom` additionally prompts for the provider URL. When `-output` is omitted, the CLI prompts for a destination path, defaulting to `<project-name>.cgs`.

4.5 create-cgs

```
$ pixi run cgitssync create-cgs --project CGSil1 \  
  --repo github:flipoyo/ComplexGitSync \  
  --repo codeberg:GX4G/GX4G \  
  --output CGSil1.cgs
```

Builds the canonical `CgsDocument` through the offline format pipeline and serializes concise `.cgs` TOML. It performs no Git or network work.

4.6 clean-init

```
$ pixi run cgitssync clean-init <spec.cgs> [--output-path DIR] [--commit-  
gitignore]  
  [--force-gitignore-sync] [--git-user-name NAME] [--git-user-email  
  EMAIL]  
  [--force-protocol {ssh,https}]
```

Recovery-oriented initialisation for a `.cgs` source. It follows the same high-level pipeline as `initialise(.cgs)` (including the `.gitignore` lifecycle sync and `-force-protocol` behaviour described there), but inserts a cleanup phase before cloning:

load->expand->validate->purge->clone->gitignore

Use it when an earlier initialisation attempt left partial child checkouts. `CGSHOME/.cgitsync/master.toml` (the persisted Git identity override, if any) is preserved by the purge phase — it is workspace-local configuration, not generated clone state.

4.7 purge

```
$ pixi run cgitsync purge <spec.cgs> [--output-path DIR]
```

Removes generated clone state from the resolved `CGSHOME` without cloning. It deletes child repository directories declared directly under the project root and project-local `*.lgr` files. Nested directories that are not immediate root children, and `.cgitsync/master.toml` (see `clean-init` above), are left untouched by this command.

4.8 pull

```
$ pixi run cgitsync pull [spec.cgs|snapshot.gts] [--commit-gitignore]
  [--force-gitignore-sync] [--git-user-name NAME] [--git-user-email
    EMAIL]
  [--force-protocol {ssh,https}]
```

Resynchronises the project tree. `.cgs` sources reload the source, discover nested configs, then resynchronise the loaded tree. `.gts` sources load the saved registry as the starting point and then run the same pull workflow. In both cases the operation starts at the project root: `root -> parent -> leaf`. Every repository — root, parent, and leaf alike — is a plain independent clone and receives its own `git pull -ff-only`. Use `launch-release` when you want to check out a frozen recorded release state instead of pulling current remotes. If local changes block this safe pull, the CLI prints `You can try cgitsync pull-force command`.

For a `.cgs` source, `pull` also runs the same `.gitignore` lifecycle sync described under `initialise` — including `-commit-gitignore`, `-force-gitignore-sync`, and the `-git-user-name/-git-user-email` identity override — once the tree-wide pull completes. A `.gts` source runs no discovery, so there is nothing new for the sync to find. `pull-force` does not run this sync at all; it is a destructive recovery command, not a lifecycle path the sync is wired into.

`-force-protocol {ssh,https}` rewrites every repo's remote to that protocol before pulling, persisting the change (`git remote set-url`, a no-op when the URL already matches) rather than a one-off override — the switch sticks for every command after this one too, the same way a repo's protocol at clone time sticks for everything downstream of it. Same meaning as `initialise/bootstrap`'s `-force-protocol`, applied to an already-cloned tree instead of at clone time — useful when a repo was adopted rather than cloned by `ComplexGitSync` (`initialise` never touches an adopted root's remote) and its remote's protocol does not match what the ambient environment can actually authenticate with. On a failure that looks like an SSH or HTTPS auth problem, the error gains an actionable hint naming `-force-protocol <the other one>` even without the flag.

4.9 pull-force

```
$ pixi run cgitsync pull-force [spec.cgs|snapshot.gts] [--force-protocol
  {ssh,https}]
```

Destructively resynchronises the same tree. Every repository — root, parent, and leaf alike — is forced to the selected remote branch, parent-first, with `git fetch`, `git checkout -B <branch> FETCH_HEAD`, and `git clean -fd`. This command can discard local uncommitted changes and untracked files; it never force-pushes. `-force-protocol` behaves exactly as described under `pull` above.

4.10 clone

```
$ pixi run cgitSync clone <spec.cgs> [--target-dir DIR] [--output-path DIR]
```

Clones the full repository tree declared by the `.cgs` file. This CLI command delegates to `ComplexGitSyncClient.clone`. When `-target-dir` is omitted, the project root is derived from the specification. `-output-path` provides the parent directory used to derive the project root.

For each repository, `cgitSync` tries the repo target branch first and falls back to the repo fallback branch when the preferred branch does not exist on the remote. Nested `.cgs` files are discovered after parent repositories are cloned, so explicit and automatic nested trees are materialised during the same command.

4.11 checkout

```
$ pixi run cgitSync checkout <branch> [--gts <snapshot.gts>] [--ref-kind branch|tag]
```

Checks out a branch or tag across the whole tree, parent-first. Loads the `READY` registry from `-gts`, then propagates the ref, creates missing local branches, and runs `git checkout` in every repo. On success the tree remains `READY` and a new `.gts` snapshot is written.

4.12 add

```
$ pixi run cgitSync add [PATH ...] [--gts <snapshot.gts>] [--dry-run]
```

With no `PATH` arguments (the default), stages all changes across the tree (`git add -all`), leaf-first. Requires `READY`; tree stays `READY`. With `-dry-run`, `cgitSync` prints the leaf-first execution plan and does not mutate repositories.

With one or more `PATH` arguments, each is resolved (relative to `CGSHOME`, or absolute) to the one repo in the tree that owns it and staged there individually (`git add - <path>`), leaving every other repo untouched. A path outside every repo in the tree raises an error immediately, before anything is staged.

4.13 rm

```
$ pixi run cgitSync rm PATH [PATH ...] [--gts <snapshot.gts>] [--dry-run]
```

Removes one or more tracked files, each resolved the same way as `add`'s targeted form: to the one repo in the tree that owns it, where it is deleted from disk and the removal staged (`git rm - <path>`). A plain tracked file only — a path that resolves to a directory, or that does not exist, raises an error rather than partially applying, and a path outside every repo in the tree raises before anything is removed. Requires `READY`; tree stays `READY`. With `-dry-run`, `cgitSync` prints the plan without mutating repositories.

Distinct from and unrelated to `import-submodules`' internal use of `git rm -cached` (index-only, dropping a gitlink while keeping the child's working tree) — `rm` deletes the file from disk.

4.14 commit

```
$ pixi run cgitSync commit <message> [--gts <snapshot.gts>] [--no-stage] [--dry-run]
```

Commits changes across the tree, leaf-first. Loads the READY registry from `-gts`. Repositories with no staged changes after the optional `git add -all` step (suppressed by `-no-stage`) are silently skipped. Requires a READY tree; the tree remains READY on success. Commit preflight now emits warnings for actionable workspace issues such as dirty worktrees, ahead branches, or stale recorded `commit_sha` values. With `-dry-run`, `cgitsync` prints the planned stage/commit sequence without performing git writes.

The commit message conventionally ends with `CGS#VERSION`.

4.15 push

```
$ pixi run cgitsync push [--gts <snapshot.gts>] [--dry-run] [--force-protocol {ssh,https}]
```

Pushes all repositories to their configured remotes, leaf-first. Loads the READY registry from `-gts`. Each repo is pushed to `entry.remote_name` (defaulting to "origin") on its currently resolved branch. Refreshes the stored hash in `GitTree`. Requires a READY tree; the tree remains READY on success. Push preflight blocks detached HEADs, missing remotes, unresolved merges, and behind/diverged branches; it warns when the local branch is ahead or when the loaded snapshot records an older `commit_sha`. With `-dry-run`, `cgitsync` prints the push plan without mutating any repository. `-force-protocol` behaves exactly as described under `pull` above.

4.16 freeze-release

```
$ pixi run cgitsync freeze-release <name> <message> [--gts <snapshot.gts>] [--dry-run]
  [--force-protocol {ssh,https}]
$ pixi run cgitsync freeze-release-force <name> <message> [--gts <snapshot.gts>] [--dry-run]
  [--force-protocol {ssh,https}]
```

Minimalist release workflow from a READY tree. It chains public operations in order: `add -> commit -> pull -> push -> freeze`. The force variant uses `pull-force` instead of `pull`. The release name becomes the shared tag and freeze snapshot label; the message is used for the release commit.

The `pull/pull-force` step is skipped (not attempted) when the current branch has no upstream configured yet — e.g. a branch just created and checked out this same session, never pushed before. There is nothing to pull in that case; `push` (already upstream-aware, adding `-u` automatically the same way plain `git push -u` would) publishes the branch on its own. On any branch that already has an upstream, the workflow is unchanged.

`-force-protocol` is forwarded to the `pull/pull-force` and `push` steps above, behaving exactly as described under `pull`; the remote rewrite it makes persists, so the final `freeze` step's own tag push picks it up too without needing the flag itself.

4.17 freeze

```
$ pixi run cgitsync freeze <name> [--gts <snapshot.gts>] [--dry-run]
```

Performs a release freeze across all repos, leaf-first: stage/commit, create+push the shared release tag, refresh SHA/state, and write a `.gts` snapshot. Loads the READY registry from `-gts`. Requires READY and leaves the tree READY. Freeze preflight checks remote availability, branch alignment, detached HEADs, unresolved merges, and tag absence. Dirty worktrees and stale recorded `commit_sha` values are reported as warnings because freeze will stage, commit, and snapshot them. Freeze snapshots also include a deterministic `freeze_manifest` section that records freeze invariants (immutable snapshot, validated workspace, synchronized tag,

`release-name`, ledger checkpoint) and declares `launch_state` as the canonical restore operation. Their immutable snapshot filename includes the release, for example `gts-000001-release-2026.05.gts`, while the ledger id remains `gts-000001`. With `-dry-run`, `cgitsync` prints the planned add/-commit/tag/push graph for the loaded workspace without mutating it.

4.18 import-submodules

```
$ pixi run cgitsync import-submodules REPO_ROOT [--apply] [--recursive]
```

Reads `REPO_ROOT/.gitmodules` and reports (or converts) every declared git submodule to a plain ComplexGitSync nested clone. This is the whole job: turning gitlinks into plain clones on disk. It does not author a `.cgs` — `.gitmodules` never records the root’s own identity, and a checkout worth importing already has a `.cgs` (hand-authored) or can get one from `discover` (§1 “discover”), before or after applying.

Without `-apply` (the default), the command performs a *dry run*: it prints each submodule’s name, path, URL, and branch, without touching the repository.

`-recursive` (same name and meaning as `git submodule update`’s own flag) also converts any submodule that itself has its own checked-out `.gitmodules`, at any depth — root first, not leaf first: converting a submodule stages changes in its own working tree, and converting a deeper level first would make the shallower level’s own preflight check (is the submodule’s working tree clean?) see that staged dirt and reject its own conversion; converting the shallower level first avoids this, since `git rm -cached <path>` only ever touches the parent’s own index, never the submodule’s working tree. A submodule path that was never checked out (`git submodule update -init` not run for it) has no `.git` to read a nested `.gitmodules` from and is invisible either way — the same ceiling `discover` already has for itself. Without `-recursive`, behavior is unchanged: exactly `REPO_ROOT/.gitmodules`, one level. The dry-run report is one flat list combining every level, each entry independent of how deep it was found — the same shape `discover`’s own report already uses.

With `-apply`:

- Verifies every submodule’s working tree is clean (`git status -porcelain` must be empty); rejects dirty trees immediately.
- Runs `git rm -cached <path>` per submodule, dropping the gitlink from the index while leaving the child’s working tree and `.git` directory intact (no re-clone, no local history lost).
- Removes the converted stanza from `.gitmodules` (deletes the file entirely when all stanzas are converted) and stages the change.
- Appends `<path>` to the parent’s `.gitignore` using the same helper that the `.gitignore` lifecycle sync uses.

After applying, review and commit the staged changes manually:

```
$ git -C REPO_ROOT status                # deleted .gitmodules, modified .
    gitignore
$ git -C REPO_ROOT commit -m "chore: retire git submodules"
```

Note: ComplexGitSync stores no credentials and has no private-repo authentication story. If a submodule’s upstream is private and the ambient environment lacks access, the subsequent `cgitsync initialise` or `pull` will fail at the clone step. The `import-submodules` step itself (which only touches the local index and working tree) will still succeed.

4.19 verify

```
$ pixi run cgitssync verify [--search-dir DIR] [--repair]
```

Verifies the hash-chained `.cgitssync/lgr` register for tamper-evidence: every entry's `prev` field must match the previous entry's `entry_hash` (`BROKEN_LINK` if not), every entry's own `entry_hash` must match its recomputed canonical hash (`BAD_ENTRY_HASH` if not), `seq` numbers must be gap-free and unique (`SEQ_GAP/SEQ_DUPLICATE`), and the cached `HEAD` pointer must agree with the recomputed true head (`HEAD_STALE`). A register with no entries yet — the common case, since nothing currently writes to this format — is reported clean; that is not itself a finding.

`CGSHOME` is located the same way as `status`: from `-search-dir`, else `$CGSHOME`, else the current working directory's ancestors. Exits 0 when clean, 1 when any finding is reported.

With `-repair`, a stale `HEAD` cache is corrected to match the recomputed true head. **Entries themselves are never rewritten or deleted** by `verify`, `repair` or not — a broken chain is reported, not silently healed, since a register that can be edited back to looking clean provides no evidence of anything.

Scope note: this checks chain linkage and the `HEAD` cache only. Cross-referencing entries against the actual `state(<hash>)_n/` directories on disk (`MISSING_STATE`, `ORPHAN_STATE`, `STATE_DIGEST_MISMATCH`) is not implemented yet.

4.20 launch-release

```
$ pixi run cgitssync launch-release <name> [--gts <snapshot.gts>]
```

Checks out the frozen release tag `<name>` across the loaded `READY` tree, parent-first, and writes a fresh `.gts` snapshot. This is the release oriented CLI path for returning a workspace to a frozen version; direct tag creation remains available from the Python client API as `tag()`.

The integration suite validates local no-network lifecycle coverage through the CLI path, including initialisation and the `READY` git command cycle `add -> commit -> push -> freeze -> launch-release`.

4.21 view-tree

```
$ pixi run cgitssync view-tree [spec.cgs|snapshot.gts] [--depth N] [--collapse REPO]
```

Renders a deterministic terminal tree that focuses on repository topology and operational state: `name` [`branch`] `local_state` `sync_state`. Use `-depth` to limit visible levels and repeat `-collapse` to hide selected subtrees.

Branch Topology Propagation Rules (T35):

1. **Reference branch:** The root repository's current branch is the canonical reference for all repos.
2. **Leaf-to-root inheritance:** Branch targeting flows root-first via `propagate_global_branch`, verified on-disk by `ComplexGitSyncClient.validate_topology()` (Python API only) without issuing any git writes.
3. **Allowed divergence:** Repositories in a frozen (`TAG`) state produce a `tag_divergence` diagnostic that does *not* make the topology incoherent.
4. **Incoherent states (blocking):** `misaligned_branch` (different branch from root) and `detached_head` (detached `HEAD` without a tag reference).

4.22 status

```
$ pixi run cgit sync status [--gts FILE]
```

Summarises tree readiness and per-repository sync state. The table reports the local branch, upstream branch, local worktree state, ahead/behind tracking counts, current HEAD, and the commit recorded in the loaded `.gts`.

5 Document Formats

`.cgs` means **ComplexGitSync** specification, `.gts` means **GitTreeState** snapshot, and `.lgr` means **Local Git Register**.

5.1 Local Authoring Spec (`.cgs`)

A TOML file that describes the repository tree to manage. It is the only hand-authored input; it is never modified at runtime. The normal form has two top-level keys:

```
project = "CGSil1"
repos = [
  "gitlab:CGS_test/CGSil1",
  "gitlab:CGS_test/CGSil2",
  "github:flipoyo/CGSih1",
]
```

Repository identifiers have the form `provider:owner/repository`. Nested GitLab namespaces are supported; the final path segment is the repository name. The document pipeline is:

PARSE -> NORMALIZE -> VALIDATE -> canonical CgsDocument

The canonical providers and hosts are:

Provider	Host	Remote generation
github	github.com	SSH and HTTPS
gitlab	gitlab.com	SSH and HTTPS
codeberg	codeberg.org	SSH and HTTPS
custom	explicit URL required	SSH and HTTPS

Repository-ID parsing is provider-independent and deterministic. For example:

```
codeberg:GX4G/GX4G
```

normalizes to `gitprovider = codeberg`, `project_owner_name = GX4G`, and `repo_name = GX4G`. A custom identifier must use an inline table so the host is explicit:

```
{ repository = "custom:team/tool", gitprovider_url = "https://git.
  example.com" }
```

No host is inferred for `custom`. The configured access protocol then selects `git@host:owner/repository.git` or `https://host/owner/repository.git`.

The textual grammar and its only parser, `parse_repo_id()`, live in `cgs_format.py`. The provider model in `git_repo.py` receives the already-separated provider, owner, and repository fields and composes remotes; it does not parse authoring shorthand.

The `.cgs` format pipeline is deterministic and offline. A syntactically valid repository may therefore reference a host, owner, branch, or tag that is not currently reachable. Remote existence and reference availability are checked only by explicit Git operations during runtime resolution and execution.

Normalization supplies `default_branch = main`, makes `fallback_branch` equal to that default, selects `access_protocol = ssh`, enables `nested_config = auto`, and uses the repository name as `relative_path`. If exactly one repository name matches `project`, its path is inferred as `..`

Advanced inline tables are used only where a value differs from those defaults:

```
project = "demo"
repos = [
  "github:owner/demo",
  { repository = "github:owner/docs", relative_path = "documentation",
    access_protocol = "https" },
]
```

The legacy advanced `[project]` and `[[repos]]` tables remain accepted for project-wide branch settings, custom provider URLs, tags, and other explicit overrides. Unknown providers, malformed identifiers, duplicates, and missing `project` or `repos` are rejected before a `GitTree` is built.

Two checked-in files document this boundary. Copy `examples/template.cgs` for normal authoring. Its equivalent `examples/normalized_template.cgs` expands every inferred field and is provided as a developer reference for the canonical `CgsDocument` shape. The two files are regression-tested for semantic equivalence.

The repository also keeps three checked-in, didactically ordered tutorials under `docs/tutorials/` — easiest first, see `docs/tutorials/README.md` for the guided order — exercising this authoring surface end to end: `docs/tutorials/01_first_multi_repo_workspace.md` walks a fully exercised local sandbox topology (CGS111) through the complete CLI lifecycle; `docs/tutorials/02_onboarding_a_hand-authors a .cgs` for the larger, real-world `cawaqs` tree and the point where `cgitsync` hands off to the project's existing make-based build workflow; and `docs/tutorials/03_adopting_a_real_project.md` covers the real-world `cawaqsviz` project (not synthetic), which has no `.cgs` of its own and still tracks two children as git submodules, as one verified ten-step procedure: clone, convert the submodules, discover, import-submodules, reach READY with `initialise`, then `branch/checkout/add/commit/push`.

`examples/cawaqsviz.cgs`, the hand-authored alternative mentioned in `docs/tutorials/03_adopting_a_real_project.md` above, describes `https://gitlab.com/cawaqs/gviz/cawaqsviz` and exercises several patterns above at once: a nested GitLab subgroup path (`cawaqs/gviz/cawaqsviz`, three segments rather than a plain `owner/repository` pair), an explicit `relative_path = "."` on the root entry rather than relying on the project-name auto-mount rule, two GitHub children mounted at non-default relative paths (`external/HydrologicalTwinAlphaSeries` and `docs/CWV_user_guide`). Neither child has a `.cgs` of its own, but no override is needed for that: the default `auto` nested discovery resolves a repository with zero `*.cgs` matches as a normal leaf. This file previously shipped with a nonexistent repository identifier and an invalid `default_branch`; it was corrected and given real end-to-end test coverage (`tests/integration/test_cgsi_topology.py`, and one verified run against the live repositories) as `AgentSpec/Onboarding_DevPlanTicket.md` Phase 1. See `docs/tutorials/03_adopting_a_real_project.md` for the full worked example, and `bootstrap` above for running `ComplexGitSync` against it without cloning `ComplexGitSync` inside the tree it manages.

Generated specifications use the same concise representation. The `GitTree.to_cgs()` convenience method delegates model projection to `cgs_format.py`; neither `GitTree` nor `GitRepo` formats TOML or implements the authoring grammar. Serialization omits every default that normalization can deterministically reconstruct and retains inline tables only for exceptional

settings such as a non-default branch, path, protocol, tag, custom host, or discovery rule.

The supported round trip is semantic:

```
.cgs -> CgsDocument -> GitTree -> CgsDocument -> .cgs
```

Parsing and normalizing the generated file must reproduce the initial canonical document. Whitespace, comments, and TOML table layout need not be byte-for-byte identical.

5.2 Repository Placement and Nested Discovery

For every non-root entry, `relative_path` is relative to the parent repository represented by the current `.cgs`; it is not relative to the process working directory. At the top level that parent is the project root. While expanding a nested config, it is the repository containing that config. The default is the repository name. A unique repository matching the project name uses `.` because it represents the current root.

The `nested_config` option controls whether traversal continues after the repository is available:

- `auto` (default) loads the sole root-level `*.cgs` file, if one exists; finding none resolves the repository as a normal leaf; multiple matches are rejected as ambiguous.
- `disabled` does not inspect the repository for nested config.
- A relative path ending in `.cgs` loads that exact file inside the repository, failing if it does not exist. It may not escape the repository root.

For the integration topology, `CGSi12.cgs` contains:

```
{ repository = "github:flipoyo/CGSi1", relative_path = "../CGSi1" }
```

Because the config describes the tree below `CGSi12`, the path resolves from that directory:

```
<CGSHOME>/CGSi12/../CGSi1 -> <CGSHOME>/CGSi1
```

It therefore references the existing sibling declared by `CGSi11.cgs`, instead of cloning another `CGSi1` under `CGSi12`. Discovery recognizes the already-registered absolute path and keeps the canonical entry — this guard runs before `auto` would ever get a chance to reopen `CGSi1.cgs` through the cross-reference, so no `nested_config` override is needed here.

5.3 Git Tree State Snapshot (`.gts`)

A TOML file generated automatically by bootstrapping and release operations. It must never be hand-edited. It captures the exact commit SHAs and lifecycle state of the tree at a point in time.

Top-level sections:

- `[document]` — `format_version`, `schema_version`, `generated_at`, `command_origin`, `hash_algorithm`, `snapshot_hash`.
- `[project]` — project name and `root_absolute_path`.
- `[tree_state]` — `lifecycle_state`, `is_ready`, `registry_complete`.
- `[[repo_state]]` — one entry per repo; includes `commit_sha`, `sync_state`, and ref information.

Why both version fields and hash metadata exist:

- `format_version` identifies the broad document family and keeps long-range compatibility intent explicit.
- `schema_version` identifies the exact field-level contract used by validation and canonical snapshot serialization.
- `snapshot_hash` (with `hash_algorithm = "sha256"`) provides deterministic workspace identity: identical tree state produces identical digest even if volatile metadata (`generated_at`, `command_origin`) differs.

How this is used at runtime:

- During snapshot generation, `ComplexGitSync` writes `schema_version`, `hash_algorithm`, and canonical `snapshot_hash`.
- During load/validation, `snapshot_hash` is recomputed from the canonical payload and must match.
- The project-local `.lgr` register uses this canonical hash to deduplicate equivalent snapshots.

5.4 Local Git Register and Sync Ledger (`.lgr`)

A TOML file maintained per project at `<project-root>/<Project_name>.lgr`. It is updated automatically whenever a `.gts` snapshot is written.

Sections:

- `[register]` — current snapshot pointer (`current_snapshot_id`, `current_snapshot_hash`, `current_snapshot_path`).
- `[[snapshots]]` — list of stable `gts-XXXXXX` identifiers, one per unique workspace state, deduplicated by SHA-256 hash.
- `[[ledger]]` — append-only list of synchronisation events forming a DAG via `parent_sync_ids`.

Ledger event schema:

```
[[ledger]]
sync_id      = "lgr-000001"
parent_sync_ids = []
operation    = "clone"
timestamp    = "2026-05-20T19:48:50.159Z"
actor        = "username"
workspace_hash = "5f7c8a2d..." % 64-character SHA-256 hex digest
gts_snapshot_id = "gts-000001"
affected_repos = ["demo", "dep-a"]
```

The `workspace_hash` field equals the canonical SHA-256 digest (`document.snapshot_hash`) of the associated `.gts` file, creating a direct link between each ledger event and the immutable workspace state it records. Events are parents-before-children in DAG order.

6 Worked Examples: From `CGSill` to `cawaqsviz`

`ComplexGitSync` ships four checked-in `examples/` topologies, and a same-numbered tutorial under `docs/tutorials/` for each level below (`docs/tutorials/README.md` lists all three in order). Run through them in order: each one adds exactly one new idea on top of the last, so

together they form a guided path from the simplest possible `.cgs` to a real project with no `.cgs` of its own at all.

Every command below is a Pixi task. `cgitsync` is not a globally installed executable — always run `pixi run cgitsync ...`, never a bare `cgitsync ...` (see the §1 “CLI Overview” note above).

Level	Topology	Entry point	New idea introduced
1	CGSil1	hand-authored <code>.cgs</code>	minimal spec, name-matching auto-mount
2	cawaqs	hand-authored <code>.cgs</code>	the same minimal-field style as Level 1, at 19-repo scale
3a	cawaqsviz	hand-authored <code>.cgs</code>	explicit overrides on a real, irregular tree
3b	cawaqsviz	discover	drafting a <code>.cgs</code> from a checkout, no authoring at all
3c	cawaqsviz	import-submodules	migrating an existing git-submodules project

Levels 3a–3c are not three different projects: they are three different *starting points* for the same real project, `cawaqsviz`, chosen so this section can demonstrate every route `ComplexGitSync` offers for arriving at a working `.cgs` — write it by hand, derive it from a checkout, or migrate it from an existing submodules setup — without inventing a fourth toy topology to do it. It is the most advanced level not because `cawaqsviz` is a larger tree than `cawaqs` (it is much smaller, three repos against nineteen) but because, unlike either earlier level, it has no `.cgs` anywhere upstream to copy from.

6.1 Level 1 — CGSil1: the minimal synthetic topology

`CGSil1` is the easiest way into `ComplexGitSync`: a 4-repository, mixed-provider tree with every field left at its default. Its full `.cgs` and the rationale for each line are in §1 “Local Authoring Spec” above; `docs/tutorials/01_first_multi_repo_workspace.md` carries the full transcript with expected output for every step. What follows is the command sequence itself.

```
# 1. Fetch the root repo and cgitsync itself (nested mode: cgitsync is
#    cloned inside the tree it will manage).
$ git clone https://gitlab.com/CGS_test/CGSil1
$ cd CGSil1 && git clone https://github.com/flipoyo/ComplexGitSync
$ cd ComplexGitSync

# 2. Check the spec offline, no network beyond parsing.
$ pixi run cgitsync validate ../CGSil1.cgs

# 3. Preview the topology before touching disk.
$ pixi run cgitsync view-tree ../CGSil1.cgs

# 4. Clone every declared repo and reach READY.
$ pixi run cgitsync initialise ../CGSil1.cgs

# 5. The ordinary git cycle, run tree-wide from here on --- no path
#    argument needed, the .gts snapshot is discovered automatically.
$ pixi run cgitsync pull
$ pixi run cgitsync add
$ pixi run cgitsync commit "my commit message"
$ pixi run cgitsync push

# 6. Minimalist release: stage, commit, pull, push, freeze in one call.
```

```
$ pixi run cgitssync freeze-release v1.1.0 "release v1.1.0"

# 7. Return to a frozen release at any later point.
$ pixi run cgitssync launch-release v1.1.0
```

The only `.cgs` idea this level relies on is the **name-matching auto-mount**: because CGSill1's repository identifier's last segment equals `project = "CGSill1"`, the root is inferred at `relative_path = "."` with no override written anywhere. That convenience is exactly what stops being safe once a project's identifier and display name diverge — which is where Level 3a picks up.

6.2 Level 2 — cawaqs: the same minimal style, at scale

`cawaqs` scales Level 1's minimal, no-override authoring style up to a real 19-repository build tree (root + 17 physics libraries across five GitLab groups + one required build-tooling repo), instead of a synthetic 4-repo one. Every entry's on-disk layout already matches the default `relative_path = <repo_name>`, so not a single `relative_path` override is written anywhere in `examples/cawaqs.cgs` — only the shared branch-fallback convention. Full narrative in `docs/tutorials/02_onboarding_a_real_build_tree.md`.

```
$ pixi run cgitssync validate examples/cawaqs.cgs
$ pixi run cgitssync bootstrap examples/cawaqs.cgs cawaqs-smoke-test
$ pixi run cgitssync view-tree --search-dir <path bootstrap printed>

# Move the whole 19-repo tree to a shared branch in one call, falling
# back to main per-repo wherever that branch does not exist.
$ pixi run cgitssync checkout my-feature-branch
```

Reaching READY here only replaces the *repository-fetching and branch-selection* half of `cawaqs`'s own `make_Cawaqs.sh/make_Cawaqs_from_branches.sh` scripts. `ComplexGitSync` does not compile anything: the remaining `make -f Makefile` build step is still the user's job, and only succeeds from this tree with `LIB_HYDROSYSTEM_PATH` left unset or pointed at the bootstrapped root — the alternative shared, decoupled install layout those scripts also support is out of scope for `ComplexGitSync`'s containment model.

`discover` (Level 3b below) is not a route into `cawaqs.cgs`: the 17 library repositories never coexist inside one directory tree until *after* a `.cgs` already lists them, so there is no single checkout for a filesystem walk to scan. Authoring this one from documented developer knowledge, the way Level 3a does for `cawaqsviz`, is the only available route.

6.3 Level 3 — cawaqsviz: three ways to the same .cgs

`cawaqsviz` (<https://gitlab.com/cawaqs/gviz/cawaqsviz>) is a real GitLab project, nested three path segments deep, with two GitHub children that were, until recently, plain git submodules. It has no `.cgs` of its own anywhere upstream. That makes it a good vehicle for showing all three ways `ComplexGitSync` can produce a working `.cgs` for a project it does not already control the source of, ordered here by how much the operator has to already know about the tree before running the command. Full narrative, as one combined ten-step procedure rather than three independent routes, in `docs/tutorials/03_adopting_a_real_project.md`.

6.3.1 3a — Write it by hand

The most explicit, and most error-prone, route: read the project's own `.gitmodules` and topology, then author `examples/cawaqsviz.cgs` directly. Its corrected content and the exact mistakes the first draft made (wrong nested-subgroup identifier, missing `relative_path` overrides)

are already spelled out in §1 “Local Authoring Spec”; this level is about running it, not re-deriving it:

```
$ pixi run cgitSync validate examples/cawaqsviz.cgs
$ pixi run cgitSync bootstrap examples/cawaqsviz.cgs cawaqsviz-demo
$ pixi run cgitSync view-tree --search-dir <path bootstrap printed>
```

`bootstrap` is used instead of `initialise` here because, unlike `CGSil1` above, this example is not meant to have `ComplexGitSync` cloned inside the tree it manages — see `bootstrap` in §1 for why the two commands pick different default locations.

6.3.2 3b — Derive it with `discover` (autodiscover mode)

The opposite route: start from nothing but a checkout, and let `ComplexGitSync` read the filesystem instead of writing the `.cgs` by hand. This is the route to prefer whenever a checkout is already available, since it cannot repeat the hand-authoring mistakes of 3a — `relative_path` falls out of the walk directly instead of being typed.

```
# A plain clone leaves submodule paths empty; initialise them first so
# discover has something to find at those paths. --init only (not
# --recursive): a nested submodule one level deeper would otherwise show
# up as a fourth repository discover has no use for here. (Want that
# nested submodule too? Use --init --recursive here and
# import-submodules --recursive --apply in 3c.)
$ git clone https://gitlab.com/cawaqs/gviz/cawaqsviz cawaqsviz
$ cd cawaqsviz && git submodule update --init

# Dry run: report what discover sees, write nothing.
$ pixi run cgitSync discover . --max-depth 3

# Satisfied with the report: draft the .cgs.
$ pixi run cgitSync discover . --write cawaqsviz-discovered.cgs
$ pixi run cgitSync validate cawaqsviz-discovered.cgs
```

The draft reconstructs 3a’s hand-corrected file field-for-field: the root at `relative_path = "."` and both children at their real submodule paths (`external/HydrologicalTwinAlphaSeries`, `docs/CWV_user_guide`) rather than their bare repo names. Neither child has a `.cgs` of its own, but `discover` writes no `nested_config` override for that: the default “auto” already resolves a repository with zero nested `*.cgs` matches as a normal leaf. See `discover` in §1 for exactly what is and is not reported (no network calls, unresolvable remotes are warned about and left out, never guessed at).

6.3.3 3c — Migrate it with `import-submodules`

The historical route: before either `.cgs` above existed, `cawaqsviz` tracked both children as real git submodules. This mode starts from that state and converts it, rather than describing a tree that is assumed to already be plain clones.

```
# Dry run against a real cawaqsviz checkout that still has submodules:
# reports name, path, URL, branch per submodule; changes nothing.
$ pixi run cgitSync import-submodules /path/to/cawaqsviz

# Convert: drop the gitlinks, retire .gitmodules, extend .gitignore.
$ pixi run cgitSync import-submodules /path/to/cawaqsviz --apply

# Review and commit the resulting working-tree changes as usual.
$ cd /path/to/cawaqsviz && git status
```

```
$ git commit -m "chore: retire git submodules in favour of
  ComplexGitSync"
```

This is the whole job: turning gitlinks into plain clones on disk. It does not also write a `.cgs` — `.gitmodules` never records the root’s own identity, and a checkout worth converting already has a `.cgs` (3a) or can get one from `discover` (3b), run before or after `-apply`. The full before/after picture (index, `.gitmodules`, `.gitignore`) and the automated test that proves it against fixture repositories are in `docs/tutorials/03_adopting_a_real_project.md` §4 — this level is the condensed command sequence, not a restatement of that walkthrough. `import-submodules` and `discover` answer different questions about the same tree: `discover` reports what is *checked out*, `import-submodules` reads what git *declares* in `.gitmodules` and acts on it — a submodule path that was never initialised is invisible to 3b but not to 3c.

6.3.4 A shared caveat across all three

`ComplexGitSync` stores no credentials and has no private-repository authentication story (§1 “`import-submodules`” and “`discover`”). All three routes above assume every repository in the tree is reachable anonymously or through credentials the ambient environment (`ssh-agent`, an HTTPS credential helper) already holds.

7 Configuration and Environment

`ComplexGitSync` uses project files for topology and does not require global topology configuration. Snapshot discovery can use `CGSHOME`; when it is not set, the `initialise(.cgs)` output-path default is `CGSPATH=../..` (nested mode: `ComplexGitSync` cloned inside the tree it manages); later commands can also walk upward from the current directory to find `.cgitsync/state/.bootstrap(.cgs)` uses a different default instead — `CGSPATH=$HOME/.cgs/CGS<timestamp>/`, created automatically — since it is meant for a `ComplexGitSync` clone that is not nested inside any project tree; see `bootstrap` above. The logging and runtime-state subsystems use the user state directory by default:

- logs: `/.local/state/ComplexGitSync/logs/`
- latest runtime-state mapping: `/.local/state/ComplexGitSync/runtime/`

If `XDG_STATE_HOME` is set, these directories are rooted there instead.

8 Error Reference

ConfigValidationError Raised when `project` or `repos` is missing, a repository identifier is malformed, or a canonical field is invalid (for example an unknown `gitprovider`).

GitSyncError Raised when clone-time Git operations fail, for example because the remote branch cannot be resolved or the target directory is already occupied.

Exit code 1 General CLI failure (parse error, validation error).

Exit code 2 Command exists but is not yet implemented.

9 Troubleshooting

“`gitprovider_url` is required for custom provider” Add a `gitprovider_url` field to the offending `[[repos]]` entry in your `.cgs` file.

validate exits non-zero despite a correct-looking file Check that `project` is present and every `repos` entry uses `provider:owner/repository`. For advanced `[[repos]]` blocks without a `repository` shorthand, include `project_owner_name` and `project_name`.

Clone destination already exists and is not empty Re-run `clone` with `-target-dir` to force a clean location, or let `cgitsync` choose a suffixed default directory.

No cloneable branch found for <repo> Confirm that the remote exposes either the repo's `default_branch` or its `fallback_branch`.

PyYAML import error when calling `from_yaml/to_yaml` Add PyYAML in the Pixi environment: `pixi add pyyaml`.